US006189146B1

(12) **United States Patent**
Misra et al.

(10) **Patent No.: US 6,189,146 B1**
(45) **Date of Patent: Feb. 13, 2001**

(54) **SYSTEM AND METHOD FOR SOFTWARE LICENSING**

(75) Inventors: **Pradyumna K. Misra**; **Bradley J. Graziadio**, both of Redmond; **Terence R. Spies**, Kirkland, all of WA (US)

(73) Assignee: **Microsoft Corporation**, Redmond, WA (US)

(*) Notice: Under 35 U.S.C. 154(b), the term of this patent shall be extended for 0 days.

(21) Appl. No.: **09/040,813**

(22) Filed: **Mar. 18, 1998**

(51) **Int. Cl.**[7] **G06F 17/40**
(52) **U.S. Cl.** **717/11**; 380/4; 380/25
(58) **Field of Search** 395/712; 701/1; 380/3, 4, 30, 44, 25; 717/11

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,924,378	*	5/1990	Hershey et al.	713/201
5,138,712	*	8/1992	Corbin	713/200
5,204,897	*	4/1993	Wyman	380/4
5,343,524	*	8/1994	Mu et al.	380/4
5,553,143	*	9/1996	Ross et al.	380/25
5,671,412	*	9/1997	Christiano	707/104
5,724,425	*	3/1998	Chang et al.	380/25
5,745,879	*	4/1998	Wyman	705/1
5,790,677	*	8/1998	Fox et al.	380/24

* cited by examiner

Primary Examiner—Reba I. Elmore
(74) *Attorney, Agent, or Firm*—Lee & Hayes, PLLC

(57) **ABSTRACT**

A software licensing system includes a license generator located at a licensing clearinghouse and at least one license server and multiple clients located at a company or entity. When a company wants a software license, it sends a purchase request (and appropriate fee) to the licensing clearinghouse. The license generator at the clearinghouse creates a license pack containing a set of one or more individual software licenses. To prevent the license pack from being copied and installed on multiple license servers, the license generator assigns a unique license pack ID to the license pack and associates the license pack ID with the particular license server in a master license database kept at the licensing clearinghouse. The license generator digitally signs the license pack and encrypts it with the license server's public key. The license server is responsible for distributing the software licenses from the license pack to individual clients. When a client needs a license, the license server determines the client's operating system platform and grants the appropriate license. To prevent an issued license from being copied from one client machine to another, the software license is assigned to a specific client by including a client ID within the license. The software license also has a license ID that is associated with the client ID in a database record kept at the license server. The license server digitally signs the software license and encrypts it using the client's public key. The license is stored locally at the client.

20 Claims, 8 Drawing Sheets



IPR2021-01406
ANCORA EX 2014


20
22
Clearinghouse
26
License Generator
24
Company
28
License Server
32(1)
Intermediate Server
32(2)
Intermediate Server
30(5)
Client
30(6)
Client
30(1)
Client
30(2)
Client
30(3)
Client
30(4)
Client

Fig. 1


Fig. 2
40
42
Processing Unit
44
System Memory
48
(ROM)
BIOS
52
50
(RAM)
Operating System
70
Application Programs
72
Other Program Modules
74
Program Data
76
46
System Bus
86
Video Adapter
84
Hard Disk Drive Interface
64
Magnetic Disk Drive Interface
66
Optical Drive Interface
68
Serial Port Interface
82
Network Interface
88
54
56
58
60
62
78
80
Keyboard
Modem
90
Network
92
Operating System
70
Application Programs
72
Other Modules
74
Program Data
76


20
Intermediate Server
32
Legacy License Store
130
Client Licensing Unit
128
System ID
License
Challenge
Response
License for Client ID
Client
30
License Requester
132
License Cache
136
Challenge Handler
134
System ID
142
License Server
28
Request Handler
122
Client Authenticating Module
124
Granting Module
126
License Server Cert.
140
Client Image Installer
118
Client Image Cache
120
Secure License Store
112
CA Table
116
LP Table
114
License Pack Installer
110
License Pack
108
Client Image, Client Sig
Licenser Generator
26
Master License Databases
100
License Producer
102
Request Handler
104
Purchase Request (LS Certificate, Platform, # Licenses)
106

Fig. 3


License Server 28
Generate and Send Purchase Request
150
Verify Signature of Clearinghouse
164
K_{CH_pub}
Decrypt License Using K_{LS_pri}
166
K_{LS_pri}
Evaluate License Pack ID
168
Install License Pack in Secure License Store
170
Purchase Request
Platform Type
Quantity of Licenses
Product ID
LS Certificate
Requested Features
106
License Pack
Non-Assigned Licenses
License Pack ID
108
License Generator 26
Create License Pack with Pack ID
152
Store Request Information in Master License DB
154
Associate Pack ID with License Server
156
Encrypt License Pack Using K_{LS_pub}
158
K_{LS_pub}
Sign License Pack Using K_{CH_pri}
160
K_{CH_pri}
Return License Pack
162

Fig. 4


Client 30
Submit Connect Request
172
Query License Cache
176
Send Client ID and any S/W License
178
System ID
Client ID
S/W License (if available)
Intermediate Server 32
Send List of Accepted Product IDs
174
License Submitted?
180
No
Yes
Request New License from License Server
188
Verify License Signature and Client ID
182
Not Valid
Rejected
Valid
License Expired?
184
Yes
No
Complete Connection
186
K_{LS_pub}

Fig. 5



Fig. 6

IPR2021-01406
ANCORA EX 2014


Client 30
Intermediate Server 32
License Server 28
220
Submit Client Software ID
230
Hash (Challenge, Client Image)
232
Return Hash Value
226
Inform User of Rejection
S/W ID
H
Challenge
Rejection
222
Client Image in Cache?
Yes
No
228
Send Challenge to Client
234
Retrieve Client Image from Cache
236
Hash (Challenge, Client Image)
H'
238
H' = H?
Yes
No
Trust Established
224
Return Rejection

Fig. 7


Client 30
Submit Connect Request
172
Query License Cache
176
Send Old S/W License
240
Replace Old License in Cache
252
System ID, Product ID
List
Old License
Upgraded License
Intermediate Server 32
Send List of Accepted License Servers and Product IDs
174
Expired or Old Version?
242
No
Request Upgrade to Old License
244
Forward Upgraded License and Complete Connection
250
Old License, System ID
Upgraded License
License Server 28
Upgrade Available?
246
Yes
Send Upgraded License
248

Fig. 8

SYSTEM AND METHOD FOR SOFTWARE LICENSING

TECHNICAL FIELD

This invention relates to systems and methods for licensing software. This invention further relates to systems and methods for enforcing software licenses.

BACKGROUND

Software licensing has historically been based on a "trust" model in which the user (i.e., licensee) is presumed to be honest and trustworthy and to abide by the legal requirements of the license. Under the trust model, a software license typically accompanies a software product to explain the terms of use. For instance, the software license might dictate that the program code is to be installed on only one computer, and may be used to make one backup copy.

Common types of licenses include "shrink wrap" licenses, "online" licenses, and "site" licenses. A "shrink wrap" license is a license that accompanies each software product that is sold individually in a shrink-wrapped package through retail stores. The user is typically assumed to accept the terms of the shrink wrap license upon breaking the seal of the package, or the container that holds the disk itself.

An "online" license is one that accompanies software products that are downloaded online, such as from the Internet. The license is typically presented to the user prior to downloading the code. The user is presented with a choice to accept or reject the license. If the user accepts the license (e.g., by clicking an "Accept" button on the screen), the user is presumed to have accepted the terms of the license and the code is downloaded to the user's computer.

A "site" license is a single license that allows installation of multiple copies of software on many different computers at a particular site or many sites. It is commonly used to sell software to corporations, firms, or other entities having many computers. The purchaser pays for a certain number of copies (e.g., hundreds or thousands), and the site license enables the purchaser to install that many copies on its computers. The site license is beneficial because the software vendor need not supply a large number of program disks, but merely supplies one or a few copies of the software and lets the purchaser install the copies without violating the agreement.

Each of the above license arrangements assumes that the purchaser is honest. The software purchaser must abide by the license terms in order to legally use the software. If the purchaser fails to abide by the provisions, the purchaser can be charged with civil and criminal violations.

However, enforcement of such licenses is impractical, if not impossible. Unscrupulous users might make multiple copies of the software code and install it on more computers than the license allows. Yet, software vendors cannot begin to monitor these abuses because they occur in the privacy of the home or company. Thus, it is believed that the software industry loses a large percentage of revenues each year simply due to illegitimate use of software by the licensees. This loss does not even account for the problems of overseas pirating.

Another problem with conventional software licensing practices concerns internal monitoring and bookkeeping on the part of large-site licensees. In most cases, the licensees want to comply with the terms of the software licenses, but are unable to adequately track the software as it is used throughout the site. For example, a large corporation might

purchase several thousand copies of the software and begin installing the copies. However, computers and personnel change over time and it is difficult to centrally monitor how many copies have been installed, whether the copies have expired, whether they need upgrading, and SO forth.

Accordingly, there is a need to develop a new approach to licensing software in a manner that assures that the terms are being meet and assists the licensee with monitoring whether it is in compliance with the software license.

SUMMARY

This invention concerns a system and method for licensing software. The system and method provides confidence to the vendor that the software license is being complied with, while also assisting the purchaser in monitoring its own compliance with the license.

According to one aspect of this invention, computer software licenses are electronically issued as digital certificates that can be distributed in one-to-one correlation with individual client computers and traced to an issuing authority.

According to another aspect, the system includes a license generator located at a licensing clearinghouse and at least one license server and multiple clients located at or affiliated with a company or other entity. Because the clients might not have network connectivity to the license server, one or more intermediate servers may act as an intermediary for the clients. These intermediate servers are otherwise common servers that provide resources to clients, but with the added ability to facilitate connectivity to the license server for purposes of distributing software licenses to the clients.

When a company wants a software license, it sends a purchase request (and an appropriate fee) to the licensing clearinghouse. The license generator at the licensing clearinghouse creates a license pack containing a set of one or more individual software licenses. To prevent the license pack from being copied and installed on multiple license servers, the license generator assigns a unique license pack ID to the license pack and associates the license pack ID with the license server in a master license database kept at the licensing clearinghouse. The license generator also digitally signs the license pack and encrypts it with the license server's public key. The license generator sends the license pack to the license server using standard communications, such as over a data communication network (e.g., Internet) or via a portable data medium (e.g., floppy diskette, CD-ROM, etc.).

The license server verifies the license generator's digital signature on the license pack and if valid, installs the license pack for subsequent distribution of licenses. The license server maintains an inventory of software licenses that have been purchased from the licensing clearinghouse. The license server is responsible for distributing the software licenses contained in the license pack to individual clients. It monitors the software licenses that have been granted to clients and continues to distribute licenses as long as non-assigned licenses remain available. Once the supply of non-assigned licenses is exhausted, however, the license server can no longer grant licenses to the clients and the customer must purchase a new pack from the license clearinghouse.

When a client connects to a server, the client presents a valid license (if it has one). If the client does not have an appropriate license, the server assists the client in obtaining a license from the license server. This provides an automated mechanism for clients to obtain and license server to distribute licenses to clients.

When a license is requested, the license server initially checks if the requesting client has already been issued a license. When this situation is detected, the license server issues the existing license to the client. This is actually reissuing of the same license that was previously issued. This allows the client to gracefully recover licenses when they are lost.

In one implementation, the license server determines an appropriate type of license based in part on the client's operating system platform. The license server derives the platform information by establishing a trust relationship with the client and then querying its platform type. If a software license is available for allocation, the license server grants a software license that is appropriate for the client's platform.

To prevent an issued license from being copied from one client machine to another, the software license is assigned to a specific client by including its client ID within the license. The software license also has a corresponding license ID that is associated with the client ID in a database record kept at the license server.

The license server digitally signs the software license. The license is passed to the client, where it is stored in a local cache at the client. Once a client has obtained a license, it is responsible for managing the storage of that license.

BRIEF DESCRIPTION OF THE DRAWINGS

The same reference numbers are used throughout the drawings to reference like components and features.

FIG. **1** shows a software licensing system.

FIG. **2** shows a block diagram of a computer used to implement the software licensing system.

FIG. **3** shows a functional block diagram showing software components and databases that implement the software licensing system.

FIG. **4** shows steps in a method for issuing a license pack of individual licenses.

FIG. **5** shows steps in a method for initiating a connection between a client and a server and determining whether the client has a valid license.

FIG. **6** shows steps in a method for distributing a software license to a client.

FIG. **7** shows steps in a method for challenging a client prior to granting a software license to that client.

FIG. **8** shows steps in a method for upgrading a software license.

DETAILED DESCRIPTION

The following discussion assumes that the reader is familiar with public key cryptography. For a basic introduction to cryptography, the reader is directed to a text written by Bruce Schneier and entitled, "Applied Cryptography: Protocols, Algorithms, and Source Code in C," published by John Wiley & Sons, copyright 1994 (second edition 1996), which is hereby incorporated by reference.

FIG. **1** shows a system **20** for licensing software. The system **20** has a licensing clearinghouse **22** that creates and issues valid software licenses to one or more companies, firms, agencies, or other entities, as represented by company **24**. The clearinghouse **22** is a separate entity from the company **24**. Examples of the clearinghouse include a software manufacturer, a software vendor, or a third party agent that is authorized to issue software licenses on behalf of the software manufacturer or vendor.

The company **24** contacts the clearinghouse **22** when it desires to purchase a software license to run software on the company computers. The clearinghouse **22** has a license generator **26** that creates a "license pack" containing a set of one or more individual software licenses. The clearinghouse **22** encrypts the license pack using the destination license server's public key and digitally signs the license pack with a digital signature unique to the clearinghouse.

The company **24** has at least one designated license server **28**. The license pack is sent to the company **24** using standard communications, such as over a data communication network (e.g., Internet) or via a portable data medium (e.g., floppy diskette, CD-ROM, etc.), and installed on the license server **28**.

The license server **28** is responsible for distributing the software licenses contained in the license pack to individual clients, as represented by clients **30(1)–30(6)**. The license server **28** verifies the license generator's digital signature on the license pack, decrypts the contents of the license pack, and stores the individual software licenses for subsequent distribution to individual clients.

The license server **28** maintains an inventory of software licenses that have been purchased from the licensing clearinghouse **22**. The license server **28** monitors the software licenses that have been granted to clients. The license server **28** can distribute licenses to new clients as long as it has available non-assigned licenses. Once the supply of non-assigned licenses is exhausted, however, the license server **28** can no longer grant licenses to the clients. The only way for the license server **28** to obtain new non-assigned licenses is to purchase a license pack from the clearinghouse **22**.

Because the clients might not have network connectivity to the license server **28**, one or more intermediate servers, as represented by servers **32(1)** and **32(2)**, can act as an intermediary for the clients. Each intermediate server **32** is a common server that provides conventional resources to the clients. In addition, each intermediate server **32** has network connectivity to the license server **28** to facilitate license distribution from the license server **28** to the clients **30**. The intermediate servers **32** accept software licenses issued by the license server **28**; therefore, the intermediate server associations determine the scope of the license pack to a particular license server.

The clients **30** may be directly coupled to the intermediate servers **32** via a LAN (local access network) or WAN (wide area network), as represented by clients **30(1)–30(4)**. Additionally, the clients **30** may be indirectly coupled to the intermediate servers **32**, such as using a dialup connection as represented by clients **30(5)** and **30(6)**.

When a client **30** connects to the intermediate server **32**, it must present a valid license. If the client does not have an appropriate license, the intermediate server **32** assists the client in obtaining a license from the license server **28**. This provides an automated mechanism for distributing licenses to clients. The license server **28** initially checks if the requesting client already has been issued a license. When this situation is detected, the license server **28** issues the existing license to the client. This allows the client to gracefully recover licenses when they are lost.

In one particular implementation, the license server **28** determines an appropriate type of license based in part on the client's platform operating system type. The license server **28** derives the platform information by establishing a trust relationship with the client **30** and then querying its platform type. Once a client **30** has obtained a license, it is responsible for managing the storage of that license. The platform challenge process is described below in more detail.

IPR2021-01406
ANCORA EX 2014

Exemplary Computer Used to Implement Servers and/or Client

The license generator **26**, license server **28**, and intermediate server **32** are preferably implemented as computer servers, such as Windows NT servers that run Windows NT server operating systems from Microsoft Corporation or UNIX-based servers. It is noted, however, that the license generator **26** and license server **28** may be implemented using other technologies, including mainframe technologies, as long as they share an inter-operable communication mechanism like remote procedure call (RPC) and these systems are secure.

The clients **30** can be implemented as many different kinds of computers, including a desktop personal computer, a workstation, a laptop computer, a notebook computer, a handheld PC, and so forth. The clients **30** may further represent a terminal device, which is a low cost machine with limited local processing and local memory. The terminal device includes a display, a keyboard, a mouse (optional), limited computer resources like memory, and enough intelligence to connect to an intermediate server. All applications run at the server. The terminal merely provides a connection point to the server-based processing.

The clients **30** might also represent a network-centric computer, such as a Network Computer (or NC) or a Net PC.

FIG. **2** shows an example implementation of a computer **40**, which can be used to implement the license generator **26**, license server **28**, and intermediate server **32**. The server **40** includes a processing unit **42**, a system memory **44**, and a system bus **46** that interconnects various system components, including the system memory **44** to the processing unit **42**. The system bus **46** may be implemented as any one of several bus structures and using any of a variety of bus architectures, including a memory bus or memory controller, a peripheral bus, and a local bus.

The system memory **44** includes read only memory (ROM) **48** and random access memory (RAM) **50**. A basic input/output system **52** (BIOS) is stored in ROM **48**.

The computer **40** has one or more of the following drives: a hard disk drive **54** for reading from and writing to a hard disk or hard disk array, a magnetic disk drive **56** for reading from or writing to a removable magnetic disk **58**, and an optical disk drive **60** for reading from or writing to a removable optical disk **62** such as a CD ROM or other optical media. The hard disk drive **54**, magnetic disk drive **56**, and optical disk drive **60** are connected to the system bus **46** by a hard disk drive interface **64**, a magnetic disk drive interface **66**, and an optical drive interface **68**, respectively. The drives and their associated computer-readable media provide nonvolatile storage of computer readable instructions, data structures, program modules and other data for the computer **40**.

Although a hard disk, a removable magnetic disk **58**, and a removable optical disk **62** are described, other types of computer readable media can be used to store data. Other such media include magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, random access memories (RAMs), read only memories (ROM), and the like. Additionally, the computer **40** may be configured to serve data stored on an independent storage systems, such as disk array storage systems.

A number of program modules may be stored on the hard disk, magnetic disk **58**, optical disk **62**, ROM **48**, or RAM **50**. These programs include a server operating system **70**, one or more application programs **72**, other program modules **74**, and program data **76**. The operating system **70** is preferably a Windows-brand operating system such as Windows NT, Windows 95, Windows CE or other form of Windows. The operating system **70** may alternatively be other types, including Macintosh and UNIX-based operating systems.

A user may enter commands and in formation into the computer **40** through input devices such as a keyboard **78** and a mouse **80**. Other input devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner, or the like. These and other in put devices are connected to the processing unit **42** through a serial port interface **82** that is coupled to the system bus **46**, but may alternatively be connected by other interfaces, such as a parallel port, game port, or a universal serial bus (USB).

A monitor **84** or other type of display device is also connected to the system bus **46** via an interface, such as a video adapter **86**. The computer **40** has a network interface or adapter **88**, a modem **90**, or other means for establishing communications over a network **92**.

5 System Architecture

FIG. **3** shows an exemplary software/hardware architecture of the system **20**. The architecture includes four components: a license generator **26**, a license server **28**, a client **30**, and an intermediate server **32**. The license generator **26** produces license packs for a fee and the license server **28** consumes the licenses by installing them. In turn, the license server **28** distributes a license to the client **30** with the help of the intermediate server **32**. The client **30** then uses the license to gain access to the resources provided by the inter mediate server **32**.

The entity or organization that owns, or is responsibe for, the license server **28** registers itself with an independent certifying authority that is trusted by both the organization and the clearinghouse. The organization submits information identifying itself and various license servers to the certifying authority. The certifying authority performs a verification analysis of the organization to verify that it is a real entity and that the identification information is true and accurate. The certifying authority issues a certificate to the organization. The certificate contains the public key of the organization (or particular license server), which is signed by the certifying authority. This certificate becomes the license server's certificate during the initial purchase request process when the license server requests a license pack from the clearinghouse.

Similarly, the clearinghouse also registers with the certifying authority to receive a public certificate. The clearinghouse certificate contains the clearinghouse's public key, signed by the certifying authority.

The license generator **26** has a master license database **100**, a licensing producer **102**, and a request handler **104**. The request handler **104** receives a purchase request **106** from the license server **28** asking to purchase one or more license packs. The purchase request includes information pertaining to the licenses and license server **28**. For example, the purchase request might contain such information as a license server ID, the license server's certificate (which contains the license server's public key), a client's platform type, the quantity of licenses desired, a product ID, and a list of features that the licenses should enable. Additional information about a customer (e.g., name, contract number, etc.) may also be requested for purposes of tracking and report generation. This information is stored in the master license database **100**.

In response to the request, the license producer **102** generates one or more license packs **108**, each of which contains a set of one or more non-assigned licenses that are

IPR2021-01406
ANCORA EX 2014

purchased from the license clearinghouse. The license generator **26** creates licensing packs in a way that prevents them from being copied and installed on multiple license servers **28** or being applied multiple times on the same server. In the preferred implementation, this is accomplished using IDs and cryptographic tools. The license producer **102** assigns a unique license pack ID to each license pack and associates the license pack ID with the license server **28** in the master license database **100**. The license pack ID is embedded in the license pack **108**. This prevents users from multiplying the number of licenses they purchase by installing the same license pack multiple times on the same license server.

The license generator **26** encrypts the license packs **108** with the license server's public key to ensure protected transport to the license server **28** and to ensure that only the license server **28** can open the packs **108**. The license generator **26** also digitally signs the license packs **108** with a private signing key of the license generator **26**. The license server **28** uses this signature to validate that the license pack came from an authorized license generator and has not been altered.

The license pack **108** is a data structure that contains various information to enable the license server to distribute software licenses. The data structure contains fields with the licensing information. Table 1 shows the data fields of a license pack data structure.

TABLE 1

Field	Description / Purpose
Message Version	An ID used to distinguish different versions of the data structure.
License Pack Serial Number	A serial number assigned by the license generator to prevent the license pack from being installed multiple times on the same license server.
Issue Date	The date the license pack is issued by the clearinghouse.
First Active Date	The date on which the licenses within the license pack can first be used.
Expiration Date	The date on which the licenses within the license pack will expire. A license could be set such that it does not expire.
Begin Serial Number	The beginning serial number for the licenses in the license pack. The number is used to assign a unique serial number to each license within the license pack.
Quantity of Licenses	The number of licenses contained within the license pack.
Number of Human Descriptions	The number of Human descriptions included for the license pack.
Array of Human Descriptions (Locale, Description)	Locale-Identifies the locale for the Human Description. Human Description-A description of the contents of the license pack in a localized form.
Manufacturer	Identity of the manufacturer of the product being licensed.
Manufacturer-Specific Product Data	Manufacturer-dependent information used to identify the product. As an example, this data might include: 1. Product Family Code 2. Product Version 3. License Type
Signature	Digital signature generated by the license generator using the clearinghouse private key.
Clearinghouse's Public Key Certificate	The certificate issued to the clearinghouse and containing the clearinghouse's public key. This public key is used to sign the encrypted license pack.

One parameter of the purchase request and subsequent license pack is the client platform type. As one possible implementation, the system **20** is configured to reliably recognize four different platform types: Windows, Non-Windows, Legacy, and Direct-Connect. A "Windows"-type platform means the client computer runs a 32-bit version of Microsoft Windows operating system (e.g., Windows 95, Windows 98, Windows NT, etc.). A "Non-Windows"-type platform means the client computer runs an operating system other than a Windows brand operating system. A "Legacy"-type platform indicates that the client runs an older version of an operating system that cannot be adequately determined by the license server as a "Windows"-type or a "Non-Windows"-type. A "Direct-Connect" platform means the client is a terminal that attaches directly to the server's bus and thus, all of the operating system functionality is provided directly by the server. Table 2 summarizes the platform types.

TABLE 2

Platform Types

Platform Type	Description
Windows	Authenticated client platforms that are Win32-based.
Non-Windows	Authenticated client platforms that are not Win32-based.
Legacy	Clients that are implemented with older operating systems that are incapable of fielding a client platform challenge from the license server. There is no way of determining whether or not the client's platform is Win32 capable.
Direct-Connect	Multi-console clients that are attached directly to the server's BUS. These clients derive the operating system capabilities from the server itself.

The license server **28** has a license pack installer **110** and a secure license store **112**. The license pack installer **110** installs the license pack(s) **108** received from the license generator on the secure license store **112**. The license pack installer **110** may also be used to order the license packs, when such purchase requests are made electronically. The license pack is stored in a secured database. A library of routines for adding, removing, querying, upgrading and extracting licenses are used to manage the licenses within the license store. As noted above, the license packs are encrypted using the license server's private key to prevent users from tampering with the licenses or moving them to another license server. License store APIs (application program interfaces) are used to encrypt the licenses as they are placed on the secure license store **112** and to decrypt the licenses as they are removed from the store.

To prevent the same licenses from being applied multiple times on the same license server, each license pack **108** contains a unique license pack ID assigned by the license generator **26** when the license pack is created. The licenses are stored in the license store **112** based on the license pack ID.

The license store **112** contains two tables: a license pack (LP) table **114** and a client assignment (CA) table **116**. The license pack table **114** records information pertaining to the license packs **108**. The license pack table **114** is indexed using the license pack ID, which enables quick access and a convenient way to check if a particular license pack is already installed in the secure store.

IPR2021-01406
ANCORA EX 2014

Table 3 shows the fields in the license pack table **114**.

TABLE 3

License Pack Table

Field	Description
License Pack ID	A unique identifier assigned by the license generator.
Quantity	The number of software licenses contained in the license pack.
Number Assigned	The number of software licenses that have been assigned to clients.
First Active Date	The date on which the licenses within the license pack can first be used.
Expiration Date	The date on which the software licenses in the license pack will expire.
Begin Serial Number	The beginning serial number for the licenses in the license pack. The number is used to assign a unique serial number to each license within the license pack.
Product-Specific Attributes	Product-dependent information to indicate specific features of a product. As an example, this date might include: 1. Product ID 2. Product Flags 3. Platform Type

The number assigned field need not be kept, but it helps eliminate the need to count the number of assigned licenses each time an administrator wants to determine how many free licenses are available.

The client assignment table **116** contains a list of all licenses that have been distributed to the clients. Each record in the client assignment table **116** is assigned a unique license ID. The license ID serves two purposes: (1) it allows the table **116** to be indexed and (2) it provides a license tracking mechanism for the client. The client assignment table **116** also contains the license pack ID from which each license is derived.

Table 4 shows the fields in the client assignment table **116**.

TABLE 4

Client Assignment Table

Field	Description
License ID	A unique identifier assigned by the license server to each software license, based on the begin serial number.
License Pack ID	The unique identifier assigned by the license generator.
Client ID	A unique identifier of the client to which the software license is granted.
Issue Date	The date on which the software license is issued to the client.

The license pack ID fields in the license pack table **114** and the client assignment table **116** can be used to join the tables in a one-to-many relationship; that is, one record identified in the license pack table **114** to many records in the client assignment table **116** as software licenses are issued to clients. This joinder yields a list of all software licenses assigned to clients from a given license pack. The client ID field enables the administrator to query all licenses for a particular client.

In this manner, the two tables **114** and **116** help the company's license administrator track the number of licenses available, the number installed, and which clients have which licenses. This tracking mechanism is useful because the administrator can quickly determine whether the company is in compliance with the terms of the license. Additionally, the tracking mechanism allows the administrator to plan for purchasing of additional licenses.

With continuing reference to FIG. **3**, the license server **28** also has a client image installer **118** and a client image cache **120**. The client image installer **118** installs executable images and client signatures of authorized clients in the client image cache **120**. The client images are used to challenge clients during software distribution. The reason that the entire client image is stored on the license server is to prevent a third party from replaying exchanges between client and server for platform challenge and response.

The client digital signatures are based on client information provided by the manufacturer (i.e., OEM). The OEM submits a client executable image to a third party, or to the software manufacturer of the server software, or to a signing authority (hereinafter, collectively referred to as the signing authority). The signing authority computes a value as a one-way function of a client executable image. Preferably, the signing authority hashes the image, or slices of the image, using a hashing algorithm to produce a hash value. The signing authority then signs the client image hash with a private key associated with the license server.

The client's digital signature is presented to a license server **28** when installing client images in the server's client image cache **120**. The client image installer **118** has access to the corresponding public key, which is maintained at the license server, and uses this public key to verify the client's signature before installing the client image on the cache **120**.

The license server **28** also has a request handler **122**, a client authenticating module **124**, and a granting module **126**. The request handler **122** receives requests for software licenses from clients. The client request typically includes the client ID. The request handler **122** passes the request to the client authenticating module **124**, which determines whether the client is authentic and able to receive a software license.

As part of the authentication process, the client authenticating module **124** initiates a platform challenge requesting a client executable image from the client **30**. One preferred approach to performing a platform challenge is described below in more detail under the sub-heading "Platform Challenge".

The client authenticating module **124** compares the client executable image received from the client to the client executable image stored in the client image cache **120**. The client is deemed authentic if the two images match. The client authenticating module **124** informs the granting module **126** when the client is authenticated.

The granting module **126** grants a software license from the secure license store **112** to the authenticated client. To prevent an issued license from being copied from machine to machine, the software license is assigned to a specific client by assigning a client ID to the license and including that ID within the license. The software license is also given a license ID. The license ID is associated with the client ID in the client assignment table **116** to track which client receives the issued license.

The license server **28**, based on information derived from the license pack, fills in fields of a license data structure at the time the license is issued. As one example, the license data structure is implemented using an X.509 certificate, which is well known in the art. The license server **28** then digitally signs the software license using a signing key that is not disclosed to the client. Table 5 shows the data fields of a software license data structure.

TABLE 5

Software License Contents

Field	Description / Purpose
Version	Identifies the "data structure" version of the software license so newer licenses can be used on older servers.
License ID	A unique ID assigned to the software license by the license server at the time of issuance to the client.
Client ID	The unique identifier of the client to which the software license is assigned.
Issue Date	The date on which the software license is assigned to the client.
Expiration Date	The date on which the software licenses in the license pack will expire.
Product-Specific Attributes	Product-dependent information to indicate specific features of a product. As an example, this date might include: 1. Product ID 2. Product Flags 3. Platform Type
Signature	Digital signature generated by the license generator using the clearinghouse private key.
License Server's Certificate	The license server's public key in certificate form, as issued by the certifying authority.

As part of the granting process, the client assignment table **116** is updated to reflect that a particular license having a specific license ID is issued to a particular client having a specific client ID. Additionally, the number assigned field in the license pack table **114** is updated to reflect that another license has been assigned to a client.

The license pack installer **110**, client image installer **118**, request handler **122**, client authenticating module **124**, and granting module **126** are preferably implemented as software programs executing on the license server **28**. These software programs are preferably implemented as part of the operating system at the license server.

The intermediate server **32** acts as a go between for the client **30** and license server **28**. The intermediate server is a full-service server that is used regularly by the client to perform normal tasks that are customary for the company or entity. But, the intermediate server is further equipped with a client licensing unit **128** to facilitate communication between the client **30** and license server **28**. The intermediate server **32** also has a legacy license store **130**, which stores licenses for clients whose platforms cannot generate a unique system ID.

The client **30** has a license requestor **132**, a challenge handler **134**, and a license cache **136**. The license requestor **132** initiates the license requests for obtaining a software license from the license server **28**. This involves connecting to the intermediate server **32** and presenting a software license and a client ID to the intermediate server **32**. The client ID submitted by the client is validated against the client ID within the license. To prevent a client from simply looking within a license to find its associated client ID, the license server encrypts the software license with a key that is never disclosed to clients and hence the client is incapable of decrypting the software license. Furthermore, license tampering is prevented by digitally signing the software licenses when the license server issues them.

The client ID is passed onto the license server **28**, which then initiates a platform challenge. The client's challenge handler **134** handles the platform challenge from the license server **28**. It computes a response to the challenge that contains the client's image, which can be used by the license server **28** to authenticate the client.

If the client is deemed authentic, the license server downloads a software license to the client. The license server **28** encrypts the license using the client's public key and digitally signs the license. Additionally, the license generator assigns a unique license ID to the issued license. Because the licenses are tied to a specific client through a client ID, digitally signed by the license server and encrypted, the software licenses cannot be activated on other clients.

The license requestor **132** verifies the signature on the license to confirm that it came from the license server **28** and stores the software license in the license cache **136**. It is the responsibility of the license requester **132** to manage the licenses stored in the cache **136**. The licenses are organized in the license cache **136** according to information about the license issuing authority and product ID.

The license cache **136** is kept in persistent (non-volatile) storage. Clients that do not have persistent storage can be issued licenses as long as they can generate a unique client ID and can respond to the client platform challenge protocol. The licensing system handles this case in the same way it recovers lost licenses. On connect, the intermediate server contacts the license server for a new license. The license server realizes, through the system ID, that the license has already been issued. In this case, the old license is simply returned to the client. Clients that cannot generate a system ID or respond to the platform challenge protocol use the legacy licenses stored in the legacy license store **130** at the intermediate server **32**.

The license requester **132** and the challenge handler **134** are preferably implemented in software executing on the client **30**. These software programs are preferably implemented as part of the client's operating system.

It is noted that FIG. **3** illustrates one possible implementation of the software licensing system **20**. Other implementations are possible. As one example, the components associated with a client platform challenge may be removed. These components include the client image installer **118**, the client image cache **120**, and the client authenticating module **124** in the license server **28**, and the challenge handler **134** in the client **30**.

System IDs

One aspect of system **20** is the ability to generate unique identifiers for the servers and clients. These unique IDs include the license server ID in license server certificate **140** and the client's system ID **142** (collectively referred to as "System IDs"). The system **20** employs a per-seat licensing technique, in which licenses are associated with a particular client or machine (i.e., "seat" or "node"). The license server certificate **140** contains a unique ID for the license server **28**, which is passed to the license generator during a request for a license pack. The client's system ID **142** is a unique identifier of the client computer. It is noted that the client ID assigned by the license server to a software license may be client's system ID, although it will typically be a separate identifier created by the license server solely for tracking purposes.

As one possible implementation, the system IDs can be based on information collected form a computer's hardware and installed software. For example, hard disk volume numbers, network cards, registered software, video cards, and some microprocessors contain unique identifiers. On PCs, this information can be combined to uniquely identify a particular PC. Other information that might be used includes total RAM and floppy disk drive configuration. Because these components can be removed or replaced, thus changing the system ID, procedures for accepting system IDs allow for some variations. For instance, the procedures might allow for a few parameters to vary.

However, relying on a machine's hardware characteristics may not always be sufficient when generating unique machine IDs. For example, the hardware characteristics of some computers may not vary, so they would all generate the same machine ID. In these cases, manufacturers "brand" the computers with a unique identifier that it can be used to generate a unique machine ID. Client platforms that cannot generate a unique machine ID are still permitted to connect to an intermediate server and are deemed legacy platforms. Legacy licenses maintained in the legacy license store **130** are used for these machines.

Issuance of License Pack

FIG. **4** shows steps in a method for requesting and issuing a license pack from a license generator. At step **150**, the license server **28** generates and sends a purchase request **106** to an authorized license generator **26**. The request **106** contains information used by the license generator **26** to issue one or more software license packs to the requesting license server **28**. The purchase request **106** contains the platform type (see Table 2), the quantity of licenses desired, the product ID, the license server's certificate (containing the license server's public key $K_{LS}^{-}{}_{pub}$ and the license server ID), and the list of features that the license should enable. The license server can submit this information electronically to the **11** license generator via the Internet, modem, e-mail, on a floppy diskette, or other electronic means. Additionally, the administrator at the company or entity might submit a purchase request to the licensing clearinghouse **22** in writing on paper, or place an order orally by telephone. The license server **28** typically submits a licensing fee with the purchase request, or sometime following the initial communication.

After collecting the fee for the software licenses, the license generator **26** creates a license pack containing a set of one or more individual software licenses and assigns a unique license pack ID to the license pack (step **152** in FIG. **4**). The license generator **26** stores the collected information in the master license database **100** (step **154**). The information from the license server **28** is correlated within the database **100** to the license pack ID. In this manner, the license pack ID is associated with a particular license server having a specific license server ID (step **156**).

The license generator **26** encrypts the license pack of software licenses using the license server's public key $K_{LS}^{-}{}_{pub}$, thus binding the license pack to the requesting license server **28**. The license generator **26** digitally signs the license pack using its (i.e., the clearinghouse's) private signing key $K_{CH}^{-}{}_{pri}$ (step **160** in FIG. **4**) and sends the license pack to the requesting license server **28**.

The license pack **108** contains a set of one or more non-assigned licenses and the license pack ID. Table 1 lists the contents of the license pack **108**.

At step **164** in FIG. **4**, the license server **28** uses the clearinghouse's public signing key $K_{CH}^{-}{}_{pub}$ to verify that the digital signature accompanying the license pack **108** belongs to the license generator **26** of clearinghouse **22** and that the **11** license pack **108** has not been altered. If the signature is authentic and from a known clearinghouse, the license server **28** decrypts the license pack contents using its private key $K_{LS}^{-}{}_{pri}$ (step **166**). The license server **28** extracts the license pack ID and queries the secure license store **112** to see if it already contains the same license pack (step **168**). If the license pack is new, the license server installs it on the secure license store **112** (step **170**).

Distribution of Licenses

Client Connection

FIG. **5** shows steps in a process that facilitates a client's initial connection to the intermediate server. The client connects to the intermediate server **32** to ask for services or data provided by the server. Prior to working with the client and providing access to files, the intermediate server **32** wants to verify first that the client has a valid software license issued by a recognized license server. The client **30** may or may not have a valid license, so the intermediate server makes an initial evaluation when the client attempts to connect. Generally, if the client **30** has a valid license, the client is permitted to connect and use the server's resources. If the client **30** offers an invalid license, the client is disconnected. If the client **30** does not offer a valid license or offers an expired license, the intermediate server **32** facilitates the process of obtaining a new software license.

At step **172**, the client **30** submits a connection request to the intermediate server **32**. The connection request includes the client's system ID that uniquely identifies the computer. In response, the intermediate server **32** passes a list of the product IDs required (step **174**). In this manner, the intermediate server **32** limits its acceptance of software licenses to those that are issued by legitimate and authorized license servers.

With this information, the client **30** queries its license cache **136** to search for a suitable license from a license server that appears on the list (step **176** in FIG. **5**). If a software license is found, the client **30** sends the software license to the intermediate server **32** along with the client ID; otherwise, the client **30** submits only a client ID (step **178**). The software license contains the digital signature of the license server.

At step **180** in FIG. **5**, the intermediate server **32** determines whether the client submitted a software license. If so, the intermediate server **32** verifies whether the digital signature belongs to an authorized license server and whether the license contains a valid client ID (step **182**). The client ID is checked by extracting the client ID from the license (which was provided originally by the licensing server, as described below) and comparing it to the client ID received from the client. If the two match, the client ID passes.

If the digital signature or the client ID is not valid (i.e., the "not valid" branch from step **182**), the software license is deemed invalid. The client's request for connection is then rejected and the client is disconnected. On the other hand, if the digital signature and the client ID are both valid (i.e., the "valid" branch from step **182**), the intermediate server **32** checks if the license has expired (step **184**), the connection is completed if the license is still valid i.e. has not expired and the client is allowed access to the services and files of the intermediate server (step **186**).

In the event that the client **30** does not submit a valid license or submits an expired license, the intermediate server requests a new software license from the license server (step **188** in FIG. **5**).

New License Grant

Software licenses are distributed to the client automatically by the license server. As discussed above, when a client **30** connects to an intermediate server **32**, the client must present a valid license. If it cannot, the intermediate server acts as a proxy for the client and requests a license from its associated license server.

FIG. **6** shows steps in a method for granting a new software license from the **9** license server **28** to the client **30**. The method begins with step **188**, which is the same new license request discussed above with respect to step **188** of FIG. **5**. The new license request includes the client's system ID and the product ID. In response to the request, the license server **28** initiates a client challenge to determine who the client is and what platform it is running (step **190**). In

IPR2021-01406
ANCORA EX 2014

general, this involves generating a challenge and sending it to the intermediate server **32** (step **192**). The intermediate server **32** forwards the challenge to the client **30** (step **194**).

At step **196** in FIG. **6**, the client responds to the challenge in a manner that provides trusted information about client, including the platform type and the client's public key. The response is passed to the intermediate server **32**, which forwards it to the license server **28** (step **198**).

At step **200** in FIG. **6**, the license server determines whether the response is proper, and hence, whether the client is authentic. If the client is authenticated (i.e., the "yes" branch from step **200**), the license server proceeds with granting a software license. The license server **28** first queries the secure license store **112** to ii determine if a license for that client has already been issued (step **202**). This procedure accommodates the case in which the client has lost its valid software license. If a non-expired license is found, the license server **28** forwards it to the client **30**.

Otherwise, the license server **28** attempts to allocate a software license for the client, assuming a non-assigned license still exists in the license pack. If a license can be allocated, the license server **28** retrieves a software license that is appropriate for the client's platform from the secure software store **112** and grants the software license to the client (step **204** in FIG. **6**). The license server **28** adds a record to the client assignment table **116** and the corresponding number assigned field is updated to reflect one additional allocation.

To prevent the software license from being copied from one client machine to another, the software license is assigned to the specific client by including its client ID within the license. The software license also has a corresponding license ID that is associated with the client ID in the client assignment table **116** in the secure license store **112** at the license server. The contents of the license are described above in Table 5.

The license server **32** digitally signs the software license (step **206**) and encrypts it using the client's public key K_{C^-pub} (step **208**), thereby binding the license to the client. The encrypted license is forwarded to the intermediate server **32**, which passes it on to the client **30** and completes the connection (step **210**). By encrypting the license, the client or the license server need not trust the intermediate server because the intermediate server cannot maliciously utilize or modify the encrypted license. It also removes the risk of a rogue server masquerading as intermediate server. At step **212**, the client **30** decrypts the license using the client's private key K_{C^-pri} and stores the license in the license cache **136**.

In the event that the client's response to the challenge is deemed improper (i.e., the "no" branch from step **200**), the license server returns a rejection notice (step **214** in FIG. **6**). This rejection notice is passed on by the intermediate server **32** (step **216**) and used to inform the user (step **218**).

Platform Challenge

FIG. **7** shows a more detailed method for providing a platform challenge to the client. In this illustration, the intermediate server **32** is shown as the go between, with the forwarding steps omitted for ease of description.

An aspect of platform validation is establishing the authenticity of the client. The system utilizes the client's executable image to generate a digital signature that uniquely identifies the client. As noted above, the client's executable image is available to the license server **28** because it is stored in the client image cache **120**.

When a client requests a software license from the license server, the client **30** submits a client software ID (step **220** in FIG. **7**). The software ID is assigned by the software manufacturer/vendor to be unique for each client release. The client software ID is a bit field that contains a platform identifier, a vendor identifier, and a client revision field. The arrangement of the bits depends on how many platforms and clients are supported.

At step **222**, the license server **28** uses the software ID to lookup the client's executable image in the client image cache **120**. If the image is not present in the cache (i.e., the "no" branch from step **222**), the client is denied a software license and a rejection is returned to the client and informs the user (steps **224** and **226**).

On the other hand, if an image is present (i.e., the "yes" branch from step **222**), the license server **28** sends a challenge to the client **30** to establish a trust relationship with the client (step **228**). The challenge is preferably a 128-bit random number.

The client **30** applies a one-way function to a combination of the challenge and the client's image (step **230**). Preferably, the client concatenates the challenge and the client image and computes a hash value, as follows:

$$\text{Challenge Response}=\text{Hash}(\text{challenge}|\text{client image}|\text{challenge})$$

The client **30** sends the challenge response (i.e., the hash value) back to the license server **28** (step **232**).

Meanwhile, the license server **28** uses the software ID to retrieve a reference copy of the client image from its cache **120** (step **234** in FIG. **7**). The license server then computes a test hash value using the same hash function, and a concatenated version of the same 128-bit challenge and the client image retrieved from the cache **120** (step **236**).

The license server **28** compares the test hash value (H') with the hash value (H) returned from the client (step **238**). If the two values are the same, the client's platform information is extracted from the client software ID and a trust relationship established (i.e., the "yes" branch from step **238**). Otherwise, the client is denied a software license and a rejection is returned to the client (i.e., the "no" branch from step **238**).

Upgrading Licenses

The process for upgrading an existing license is very similar to the license distribution process. The primary difference is that a platform challenge is not performed because a valid, digitally signed license is presented to the license server.

FIG. **8** shows the steps in a method for upgrading an existing license. Steps **172–176** are identical to those defined above with respect to FIG. **5**. At step **240**, the client **30** submits a valid software license to the intermediate server **32**.

At step **242** in FIG. **8**, the intermediate server **32** determines whether the license has expired and/or is for an older version. Assuming it meets one of these conditions, the intermediate server automatically contacts the license server **28** and requests that the license be upgraded (step **244**). The intermediate server passes the old license and the client's system ID to the license server **28**.

The license server **28** validates the old license and extracts the license's ID, which is used as an index into the client assignment table **116** in the secure license store **112**. The license server **28** examines the table **116** to determine whether an upgrade is available (step **246**). If so, the license server **28** upgrades a record in the table, consuming one upgrade license, and returns an upgraded licese to the intermediate server **32** (step **248**). The intermediate server **32** forwards the upgraded license to the client and completes the connection (step **250**). The client **30** replaces the old license with the upgraded one in the license cache **136** (step **252**).

IPR2021-01406
ANCORA EX 2014

As a matter of policy, licenses are assumed to be backward compatible. That is, a next generation 5.X license is always accepted by a current generation 4.X server. This allows a customer to have a seamless mix of different servers. Variances in the licenses internal data structures are taken into account by including a version number within the license.

Temporary Licenses

Suppose a client **30** requests a software license, but the license server **28** does not have an available license in the secure license store. In this case, the license server **28** issues a temporary license that is valid for a finite duration (e.g., 60 days).

With reference to FIG. **3**, the requesting client submits its system ID **142** to the intermediate server **32**, which forwards the client's system ID **142** to the license server **28**. The license server **28** generates a temporary license and associates it with the client's system ID **142**. The temporary license is passed back through the intermediate server **32** to the client **30**. Each time the client presents the temporary license, a new license request is generated. Once the license server has an available license (e.g., the license server purchased additional licenses from the license clearinghouse), it issues a permanent license to the client. Temporary licenses are replaced only by a valid permanent license.

When a temporary license expires, the license server **28** no longer accepts it and services are denied. Furthermore, the client is only granted one temporary license and will not be permitted to request a second temporary. If a client attempts to request a second temporary license, the license server will detect the system ID and recognize that this ID is already associated with a previously issued temporary license. The license server **28** simply returns the previously issued temporary license, which is inoperable because it has expired.

Although the invention has been described in language specific to structural features and/or methodological steps, it is to be understood that the invention defined in the appended claims is not necessarily limited to the specific features or steps described. Rather, the specific features and steps are disclosed as preferred forms of implementing the claimed invention.

What is claimed is:

1. A computer-implemented method comprising the following steps:

creating a license pack at a license generator, the license pack containing a set of one or more individual software licenses;

signing the license pack with a digital signature of the license generator;

issuing the license pack to a license server;

verifying, at the license server, the license generator's digital signature on the license pack;

distributing the software licenses contained in the license pack from the license server to corresponding clients;

determining whether an individual client has a non-expired license;

in the event that the client has a non-expired license, forwarding the non-expired license to the individual client; and

in the event that the client does not have a non-expired license, granting one of the software licenses from the license pack.

2. A computer-implemented method as recited in claim **1**, further comprising the step of encrypting said one software license using a public key of the individual client.

3. A computer-implemented method comprising the following steps:

creating a license pack at a license generator, the license pack containing a et of one or more individual software licenses;

signing the license pack with a digital signature of the license generator;

issuing the license pack to a license server;

verifying, at the license server, the license generator's digital signature on the license pack;

distributing the software licenses contained in the license pack from the license server to corresponding clients; and

evaluating whether an individual client already has a software license that has not yet expired.

4. A computer-implemented method comprising the following steps:

creating a license pack at a license generator, the license pack containing a set of one or more individual software licenses;

signing the license pack with a digital signature of the license generator;

issuing the license pack to a license server;

verifying, at the license server the license generator's digital signature on the license pack;

distributing the software licenses contained in the license pack from the license server to corresponding clients;

submitting an old software license from one of the clients to the license server, the old software license containing a license ID;

determining whether an upgrade software license is available for the license ID;

granting the upgrade software license if available to the one client; and

replacing, at the one client, the old software license with the upgrade software license.

5. A computer-implemented method comprising the following steps:

creating a license pack at a license generator, the license pack containing a set of one or more individual software licenses;

signing the license pack with a digital signature of the license generator;

issuing the license pack to a license server;

verifying, at the license server, the license generator's digital signature on the license pack;

distributing the software licenses contained in the license pack from the license server to corresponding clients; and

distributing a temporary license in an event that no more licenses are available from the license pack.

6. A computer-implemented method comprising the following steps:

receiving a request for a software license from a particular client;

determining an authenticity of the particular client;

selecting a software license from a pack of software licenses that is appropriate for the particular client, the software license having an associated license ID;

associating the license ID with the particular client;

granting the software license to the particular client; and

determining whether the particular client already has a non-expired license, and if so, forwarding the non-

IPR2021-01406
ANCORA EX 2014

expired license to the particular client rather than granting the software license.

7. A computer-implemented method comprising the following steps:

receiving: a request for a software license from a particular client;

determining an authenticity of the particular client;

selecting a software license from a pack of software licenses that is appropriate for the particular client, the software license having an associated license ID;

associating the license ID with the particular client;

granting the software license to the particular client; and

granting a temporary software license that expires in a substantially shorter duration in comparison to the software license.

8. A computer-implemented method comprising the following steps:

receiving a request for a software license from a client having a valid client image;

submitting a challenge to the client, the challenge comprising a random number;

computing, at the client, a function of the challenge and the client image to produce a response;

returning the response to the server;

deriving the client image from the response at the server; and

verifying the client image at the server prior to granting the software license.

9. A computer-implemented method as recited in claim **8**, wherein the computing step comprises the following steps:

concatenating the random number and the client image to produce a concatenated value; and

computing a hash function of the concatenated value.

10. A computer-implemented method as recited in claim **8**, further comprising the step of rejecting the request for the software license in the event that the client image cannot be verified.

11. A computer-implemented method as recited in claim **8**, further comprising the step of establishing a trust with the client and subsequently granting the software license in the event that the client image can be verified.

12. Computer-readable media distributed at the server and the client having computer readable instructions for performing the steps as recited in claim **8**.

13. A computer-implemented method comprising the following steps:

submitting an old software license from a client to a server, the old software license containing a license ID;

determining whether an upgrade software license is available for the license ID;

granting the upgrade software license, if available, to the client; and

replacing, at the client, the old software license with the upgrade software license.

14. A computer-implemented method as recited in claim **13**, further comprising the step of tracking at the server that the upgrade software license is granted to the client.

15. Computer-readable media distributed at the server and the client having computer readable instructions for performing the steps as recited in claim **15**.

16. A license generator for issuing packs of software licenses to authorized license servers, comprising:

a request handler to receive a request from a license server for a license pack;

a license producer responsive to the request received by the request handler to generate a license pack containing a set of one or more individual software licenses;

the license producer assigning a license pack ID to the license pack, associating the license pack ID with the license server, and digitally signing the license pack; and

a master license database, the license producer storing the license pack ID in correlation with an ID of the license server in the master license database.

17. A license server for issuing individual software licenses from a software pack received from a licensing clearinghouse, comprising:

a license store to store the software pack of individual software licenses, each software license having an associated license ID;

a client image cache to store a set of client images;

a request handler to receive a request for a software license from a client;

a client authenticating module to determine whether the client is authentic and can receive a software license, wherein the client authenticating module receives a client image from the client and compares the received client image to the set of client images to evaluate whether the client is authentic; and

a granting module to grant a software license from the license store to an authenticated client and to associate the license ID with the authenticated client.

18. A license server for issuing individual software licenses from a software pack received from a licensing clearinghouse, comprising:

a license store to store the software pack of individual software licenses, each software license having an associated license ID;

a request handler to receive a request for a software license from a client;

a client authenticating module to determine whether the client is authentic and can receive a software license;

a granting module to grant a software license from the license store to an authenticated client and to associate the license ID with the authenticated client; and

a client assignment table containing a list of the software licenses that are granted to clients.

19. A license server as recited in claim **18**, wherein the granting module upgrades the client assignment table after granting the software license to the authenticated client.

20. A client computer, comprising:

a license cache to store one or more software licenses;

a license requestor to request a software license from a license server;

a challenge handler to handle an authenticity challenge from the license server, the challenge handler computing a challenge response that contains a client image that can be used by the license server to evaluate whether the client is authentic and can be licensed, wherein the challenge contains a random number, and the challenge handler computes the challenge response by concatenating the random number with the client image to form a concatenated value and hashing the concatenated value; and

whereupon authentication by the license server and granting of a software license, the license requestor receiving the software license from the license server and storing the software license in the license cache.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,189,146 B1
DATED : February 13, 2001
INVENTOR(S) : Pradyumna K. Misra et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 12,
Lines 11 and 28, change "requester" to -- requestor --.

Column 14,
Line 61, delete "9" after the first occurence of "the".

Signed and Sealed this

Sixth Day of November, 2001

Attest:

Nicholas P. Godici

Attesting Officer

NICHOLAS P. GODICI
Acting Director of the United States Patent and Trademark Office

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,189,146 B1
DATED : February 13, 2001
INVENTOR(S) : Misra et al.

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 19,
Line 60, replace "15" after "claim" with -- 13 --.

Signed and Sealed this

Fifteenth Day of April, 2003

JAMES E. ROGAN
Director of the United States Patent and Trademark Office