US008599814B1

(12) **United States Patent**
Vleugels et al.

(10) **Patent No.: US 8,599,814 B1**
(45) **Date of Patent: *Dec. 3, 2013**

(54) **APPARATUS AND METHOD FOR INTEGRATING SHORT-RANGE WIRELESS PERSONAL AREA NETWORKS FOR A WIRELESS LOCAL AREA NETWORK INFRASTRUCTURE**

(75) Inventors: **Katelijn Vleugels**, San Carlos, CA (US); **Roel Peeters**, San Carlos, CA (US)

(73) Assignee: **Omega Sub Holdings, Inc.**, Scottsdale, AZ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 30 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/560,917**

(22) Filed: **Jul. 27, 2012**

Related U.S. Application Data

(60) Continuation of application No. 12/892,825, filed on Sep. 28, 2010, which is a division of application No. 11/422,945, filed on Jun. 8, 2006, now Pat. No. 7,826,408, which is a continuation of application No. 11/376,729, filed on Mar. 14, 2006, now abandoned.

(60) Provisional application No. 60/661,763, filed on Mar. 14, 2005.

(51) **Int. Cl.**
H04W 40/00 (2009.01)

(52) **U.S. Cl.**
USPC **370/338**

(58) **Field of Classification Search**
USPC 370/338, 509, 349, 401; 455/1, 41.2, 455/426, 562
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,141,763 A 10/2000 Smith et al.
6,272,140 B1 8/2001 LaRowe, Jr. et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1207654 A2 5/2002
WO WO 97/48198 A2 12/1997
(Continued)

OTHER PUBLICATIONS


International Search Report and Written Opinion corresponding to the PCT application No. PCT/US06/09786, dated Sep. 25, 2007, 9 pages total.
(Continued)

Primary Examiner — Faruk Hamza
Assistant Examiner — Jean F Voltaire
(74) *Attorney, Agent, or Firm* — Davis Wright Tremaine LLP; Philip H. Albert

(57) **ABSTRACT**

A network system comprises a first logic block providing a link to a first network via an access point of a WLAN and a second logic block communicating with a node of a second network (such as a WPAN) and configured to provide a link between the node and the first network via the access point. The network system is configured to maintain continuous connections to both the access point and the node while receiving power. The second logic block can communicate with the node using a modified communication protocol that is only partially compliant with an 802.11x communications protocol. A wireless hub can integrate a WPAN with a WLAN including, in part, a wireless circuit compliant with the WLAN standard (such as an 802.11x standard), a processor, and a memory. The wireless circuit can connect to the WPAN without losing connectivity (such as association and synchronization) to the WLAN.

29 Claims, 12 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

6,505,253	B1	1/2003	Chiu et al.	
6,751,455	B1	6/2004	Acampora	
6,768,896	B2	7/2004	Tjalldin et al.	
6,771,933	B1 *	8/2004	Eng et al.	455/41.2
6,842,460	B1	1/2005	Olkkonen et al.	
6,879,574	B2	4/2005	Naghian et al.	
7,003,102	B2	2/2006	Kiko	
7,039,358	B1	5/2006	Shellhammer et al.	
7,088,687	B2	8/2006	Ayyagari et al.	
7,095,748	B2	8/2006	Vij et al.	
7,190,972	B1	3/2007	Hollister et al.	
7,333,829	B2	2/2008	Malone et al.	
7,463,907	B2	12/2008	Smith et al.	
7,590,101	B2	9/2009	Forand et al.	
7,664,081	B2	2/2010	Luoma et al.	
7,733,885	B2	6/2010	Ayyagari et al.	
7,826,408	B1	11/2010	Vleugels et al.	
2002/0039357	A1 *	4/2002	Lipasti et al.	370/338
2003/0119527	A1	6/2003	Labun et al.	
2003/0152110	A1 *	8/2003	Rune	370/509
2004/0076136	A1	4/2004	Beach	
2004/0157551	A1	8/2004	Gainey et al.	
2004/0170120	A1	9/2004	Reunamaki et al.	
2004/0252674	A1	12/2004	Soininen et al.	
2004/0259544	A1	12/2004	Amos	
2004/0259552	A1	12/2004	Ihori et al.	
2005/0025104	A1	2/2005	Fischer et al.	
2005/0036484	A1	2/2005	Barker	
2005/0058112	A1	3/2005	Lahey et al.	
2005/0068965	A1	3/2005	Lin et al.	
2005/0086393	A1	4/2005	Meng et al.	
2005/0099275	A1	5/2005	Kamdar et al.	
2005/0101260	A1	5/2005	Hunt et al.	
2005/0119025	A1	6/2005	Mohindra et al.	
2005/0176473	A1	8/2005	Melpignano	
2005/0192044	A1	9/2005	Travis	
2005/0238046	A1	10/2005	Hassan et al.	
2005/0286474	A1	12/2005	van Zelst et al.	
2006/0015621	A1 *	1/2006	Quinn	709/227
2006/0063560	A1	3/2006	Herle	
2006/0146868	A1	7/2006	Ginzburg	
2006/0165035	A1	7/2006	Chandra et al.	
2006/0203841	A1	9/2006	Fischer	
2006/0215601	A1	9/2006	Vleugels et al.	
2007/0093198	A1 *	4/2007	Beckers	455/1
2008/0144493	A1	6/2008	Yeh	
2008/0291858	A1	11/2008	Kandala et al.	
2009/0086619	A1	4/2009	Santhoff et al.	

FOREIGN PATENT DOCUMENTS

WO	WO 03/065654	A1	8/2003
WO	WO 2006/099588	A2	9/2006

OTHER PUBLICATIONS

The State Intellectual Property Office of the People's Republic of China, First Office Action for Application No. 200680013461.6, dated May 12, 2010, 24 pages total.

Office Action for U.S. Appl. No. 11/422,945, dated Nov. 21, 2008.

Office Action for U.S. Appl. No. 11/422,945, dated Oct. 22, 2009.

Notice of Allowance for U.S. Appl. No. 11/422,945, dated Jun. 23, 2010.

Office Action mailed Oct. 10, 2012 in U.S. Appl. No. 12/892,825, 18 pages.

Non-Final Office Action for U.S. Appl. No. 12/892,825, date Jul. 30, 2013, 19 pages.

* cited by examiner



WWAN
<15km
WMAN
<5km
70Mbit/s
WLAN
<100m
~11- 54Mbit/s
WPAN
<10 m
~1Mbit/s
802.20
802.16a/e (WiMax)
802.11a/b/g (Wi-Fi)
802.15.1 (Bluetooth)
802.15.3 (UWB)
802.15.4 (Zigbee)
Proprietary

FIG. 1



internet
internet router
3
1
2
IEEE 802.11 AP
4
IEEE 802.11 STA
4
IEEE 802.11 STA
4
IEEE 802.11 STA
Association
Authentication
Encryption
Synchronization
(beacons)
Data transfer
...

FIG. 2



internet
internet router
9
6
8
IEEE 802.11 STA
5
IEEE 802.11 AP
7
12
wireless hub
10
11
PS-STA
11
PS-STA
11
PS-STA
8
IEEE 802.11 STA

FIG. 3



internet
internet router
9
IEEE 802.11 AP
7
wireless hub
15
PS-STA
PS-STA
13
14
wireless hub
15
PS-STA
PS-STA
PS-STA
13
IEEE 802.11 STA
8

FIG. 4



20
19
radio
21
wireless transceiver
baseband modem
22
memory
25
16
battery
+
-
23
control/ datapath logic
CPU
24
interface circuits
26
17
sensor/ stimulus
clock
18

FIG. 5



38
31
radio
27
35
32
baseband modem
IEEE802.11-compliant wireless transceiver
memory
29
30
supply
regulator
clock
34
33
control/ datapath logic
interface circuits
processing unit
28
36
software platform enabling WPAN/ WLAN connectivity
37
OS for running applications

FIG. 6



work
41
STA
46
47
49
AP
48
router
internet
router
44
AP
45
STA
STA
STA
43
monitoring device (PS-STA)
39
Wi-Fi enabled power outlet
42
home
40

FIG. 7



114
PER1
PER2
PER3
116
PER10
PER11
100
STA1 (COORD)
STA2
STA3
STA4 (COORD)
AP
110
Wired Network
112

FIG. 8



126
AB
(PER2)
124
(PER1)
122
Laptop
(COORD)
110
AP
Access Point
120
112
Wired
Network

FIG. 9



internet
AP
primary network: BSS1
regular wireless LAN network
STA2
STA3
laptop
STA1
COORD
PER2
PER1
PER3
secondary network

FIG. 10



COORD
PER1
PER2
contention for WM
Frame 1
1 SIFS
Frame 2P1
Ack (opt.)
Frame 2P2
T_0
T_1
T_2
Coordinator awake
PER1/2 awake
Coordinator awake
PER1 awake
PER2 sleep (opt.)
Coordinator awake
PER2 awake
PER1 sleep (opt.)

FIG. 11



COORD
PER1
PER2
contention for WM
Frame 1
1 SIFS
Frame 2P1
Ack (opt.)
Frame 1
Frame 2P2
Ack (opt.)
T0
T1
T2
Coordinator awake
PER1awake
PER2 sleep (opt.)
Coordinator awake
PER1 awake
PER2 sleep (opt.)
Coordinator awake
PER2 awake
PER1 sleep (opt.)

FIG. 12

APPARATUS AND METHOD FOR INTEGRATING SHORT-RANGE WIRELESS PERSONAL AREA NETWORKS FOR A WIRELESS LOCAL AREA NETWORK INFRASTRUCTURE

CROSS-REFERENCES TO RELATED APPLICATIONS

This is a continuation of U.S. patent application Ser. No. 12/892,825, filed Sep. 28, 2010, which is a divisional application of U.S. patent application Ser. No. 11/422,945, filed Jun. 8, 2006, which is a continuation of U.S. patent application Ser. No. 11/376,729, filed Mar. 14, 2006, and claims the benefit of U.S. Provisional Patent Application No. 60/661,763, filed on Mar. 14, 2005. Each of the referenced applications are incorporated by reference herein in their entirety for all purposes, and the present application also incorporates by reference herein U.S. patent application Ser. No. 11/376,753, filed Mar. 14, 2006, hereinafter referred to as "Vleugels I" and U.S. Provisional Patent Application No. 60/661,746.

FIELD OF THE INVENTION

The present invention generally relates to wireless communications. More particularly, the invention relates to seamlessly integrating short-range wireless personal area networks ("WPANs") into longer-range wireless local area networks ("WLANs").

BACKGROUND OF THE INVENTION

FIG. **1** depicts some parameters associated with a few existing and emerging standards for wireless connectivity. Based on targeted range and supported data rates, these standards can be grouped into four categories: wireless wide area networks ("WWANs"), wireless metropolitan area networks ("WMANs"), wireless local area networks ("WLANs") and wireless personal area networks ("WPANs").

An example of a wireless local area network ("WLAN") is an 802.11x (x=a, b, g, n, etc.) network. An 802.11x NIC (network interface card) or 802.11x built-in circuitry might be used for networking an electronic device to the outside world, or at least to devices at other nodes of a WLAN 802.11x network.

The 802.11x specifications uses unlicensed, free spectrum in either the 2.4 GHz or 5 GHz frequency bands, supporting data rates of up to 54 Megabits per second (Mbps) and ranges of 300 feet and more. The 802.11x standard, also known as Wi-Fi, was adopted several years ago, and is now being widely deployed for WLAN connectivity in homes, offices and public places like airports, coffee shops and university campuses.

The adoption and deployment of 802.11x-compliant equipment has experienced tremendous growth in recent years. The majority of laptops manufactured today include a built-in wireless circuit compliant with some variant of the 802.11x standard. While originally devised for enabling wireless network connectivity ("wireless Ethernet"), WLAN connectivity based on the 802.11x standard is rapidly finding its way in new applications like mobile phones—primarily driven by the adoption of Voice-over-IP ("VoIP")—and consumer electronics (home entertainment, video streaming, etc.). In addition, with the development of the new 802.11n specification, and the proliferation of citywide 802.11x deployment initiatives, the 802.11x standard is expanding into longer range applications.

FIG. **2** illustrates a typical 802.11x WLAN configuration in infrastructure mode **1**. Although the 802.11x standard supports two modes of operation, namely ad-hoc mode and infrastructure mode, the infrastructure mode is used more often. In the infrastructure mode, a dedicated 802.11x wireless circuit, also called an access point ("AP"), is necessary for and manages an infrastructure network. AP **2** is configured specifically to coordinate the activities of the infrastructure network and to enable connectivity to, for example, the Internet or other WLANs via an Internet router **3**, which may be disposed in AP **2**. Other 802.11x-compliant wireless circuits, hereafter alternatively referred to as stations ("STAs") **4** can become a member of the infrastructure network by going through an authentication and association procedure. Additional security procedures may be required as well. Once associated with the infrastructure network, a STA **4** can communicate with AP **2**. A STA **4** may communicate with other STAs **4** of infrastructure network **1** via AP **2**. Furthermore, a STA **4** may communicate with STAs of other infrastructure networks (not shown) via AP **2**. On a regular basis, the STAs listen to the beacons and pending traffic from the AP **2**.

In contrast to WLAN, no such unifying standard exists for WPAN. Instead, a number of proprietary and standardized communication protocols have been and are being developed for establishing short-range WPAN connectivity. Standardized protocols include the Bluetooth specification (based on the IEEE 802.15.1 standard), the recently approved Zigbee specification (based on the IEEE 802.15.4 standard), and the Ultra-Wideband ("UWB") specification which is still under development. In addition, there are several proprietary protocols in the unlicensed 27 MHz, 900 MHz, and 2.4 GHz frequency bands developed for the sole purpose of providing short-range wireless connectivity. Examples include Cypress Semiconductor's proprietary wireless USB solution, or Logitech's proprietary FastRF solution. The lack of a unified standard is hindering the widespread adoption of WPAN technologies. In addition, several WPAN communication protocols co-exist in the same 2.4-GHz frequency band as a commonly used version of the WLAN protocol. Because they use different methods of accessing the wireless medium, and are not synchronized with one another, severe interference may result when devices conforming to such standards are made to co-exist and are positioned in the same physical vicinity.

One alternative for avoiding the above mentioned problems when seeking to establish interoperability between WPAN and WLAN networks, is to use network interface circuitry based on the WLAN protocol in WPAN STAs. However, the power dissipation of the resulting STA would be several orders of magnitude higher than what is acceptable in typical WPAN applications. WPAN technologies are typically used to establish communication with a remote battery-operated device for which it is inconvenient, impractical, or may be impossible to replace batteries. Examples include security sensors in windows, wearable or implanted medical monitoring devices or environmental sensors to monitor temperature, humidity or other environmental parameters. To minimize the frequency at which batteries need replacement, maximizing the battery life is of paramount importance, thus placing stringent requirements on the power that can be dissipated in establishing and maintaining the wireless communication link.

The power dissipation of a standard WLAN STA is several orders of magnitude higher than what is acceptable in most battery-operated devices for a number of reasons. First, in order to be able to communicate with the AP, which may be, for example, 300 feet away, a standard WLAN STA transmits

at high transmit powers (up to 20 dBm) and is also required to receive relatively weak signals, attenuated heavily by the path loss it encounters in the over-the-air transmission. Second, the WLAN must adhere to stringent receiver sensitivity requirements. Both the transmit and receive requirements result in relatively large power dissipation in the network interface circuits. Furthermore, WLANs typically operate at relatively high data rates (up to 54 Mbps). It is thus undesirable to have a STA that is part of an infrastructure network to communicate at lower data rates, since such a STA will slow down the entire infrastructure network. This is the case because some of the communication between the AP and its associated STAs occurs at the lowest common data rate supported by all STAs. The noise and linearity requirements associated with transmitting at high data rates thus result in large power dissipation of the wireless 802.11x wireless circuit. Furthermore, there is significant protocol overhead associated with the services and procedures required to establish and maintain an association with an infrastructure network. This overhead translates directly in higher power dissipation. As a member of an infrastructure network coordinated by an AP, the STA has, on a regular basis, to listen to the beacons transmitted by the AP. Also, although the 802.11x standard specifies power save modes that allow the STA to skip some of the beacons, the STA is still required to wake up on a regular basis to maintain association and synchronization with the AP.

Accordingly, a need continues to exist for a method and apparatus that overcome the above-described problems and enable seamless integration of WPAN into WLAN infrastructure, and at power dissipation levels that meet the stringent requirements of battery-operated devices.

BRIEF SUMMARY OF THE INVENTION

A wireless hub for integrating a wireless personal area network ("WPAN") seamlessly into a wireless local area network ("WLAN") includes, in part, a wireless circuit compliant with the WLAN standard, a processor coupled to the wireless circuit and a memory module that is coupled to the wireless circuit and the processor.

In some embodiments, the WLAN standard is the 802.11x standard. In such an embodiment, the wireless circuit is an 802.11x-compliant wireless circuit, and the memory module may be integrated with the wireless circuit. The hub further includes software modules forming a software platform that allows the wireless circuit to connect to both the WPAN and WLAN. In accordance with one embodiment, the software platform allows the wireless circuit to connect to the WPAN, without losing connectivity (such as association and synchronization) to the WLAN. In another embodiment, the wireless circuit is configured to connect to the WLAN and WPAN alternately. In some embodiments, an operating system enables the operation of the wireless hub, thereby enabling users to write application-specific application software. The operating system may be Windows XP, Windows CE, Linux, Symbian, or the like, that may be used to develop additional applications.

In accordance with one embodiment, the wireless hub is seamlessly integrated into an electrical power outlet. This allows the hub to be unobtrusively and conveniently integrated in a home, business or industrial setting. Such embodiments are hereinafter alternatively referred to as "Wi-Fi-enabled power outlets". As is known, "Wi-Fi" is often used to refer to "wireless fidelity", and refers to 802.11x-based radio technologies.

Advantageously, the present invention extends the communication range of power-sensitive battery-operated devices and allows power-sensitive battery operated devices to become part of the larger WLAN infrastructure, thus enabling monitoring and control from any location that is within the range covered by the WLAN In addition, since battery-operated devices are IP addressable and since the AP of the WLAN can be connected to the Internet via an Internet router, the battery-operated devices may be monitored and controlled from any location when access to the Internet is available. The longer communication range and seamless integration into the larger WLAN infrastructure is obtained without incurring the power penalty that is typically unavoidable in longer range communication and is inherent to the protocol overhead of typical WLAN networks.

Other objects, features, and advantages of the present invention will become apparent upon consideration of the following detailed description and the accompanying drawings, in which like reference designations represent like features throughout the figures.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** depicts a number of parameters associated with a few existing and emerging standards for wireless connectivity, as known in the prior art.

FIG. **2** illustrates some of different components of an 802.11x WLAN in infrastructure mode, as known in the prior art.

FIG. **3** illustrates an apparatus configured to integrate a wireless personal area network ("WPAN") into a wireless local area network ("WLAN"), in accordance with an embodiment of the present invention.

FIG. **4** illustrates a number of WPANs integrated into a WLAN, in accordance with one embodiment of the present invention.

FIG. **5** is a simplified high-level block diagram of a power-sensitive station ("PS-STA"), in accordance with an embodiment of the present invention

FIG. **6** is a simplified high-level block diagram of a wireless hub configured for use as a bridge between a WPAN and a WLAN.

FIG. **7** illustrates a WPAN used for remote monitoring and controlling, in accordance with one embodiment of the present invention.

FIG. **8** is a block diagram illustrating various devices operating as part of a primary wireless network ("PWN"), a secondary wireless network ("SWN"), or both, wherein the SWN operates using an SWN protocol that co-exists with the PWN protocol.

FIG. **9** is a block diagram illustrating a subpart of the elements of FIG. **8**, in greater detail.

FIG. **10** is a block diagram illustrating a secondary network including multiple WPAN peripherals ("PERs").

FIG. **11** illustrates method to coordinate the communication between a WPAN coordinator ("COORD") and multiple WPAN peripherals.

FIG. **12** illustrates an alternative frame exchange sequence for the coordination of multiple WPAN peripherals.

DESCRIPTION OF THE INVENTION

FIG. **3** illustrates a wireless personal area network ("WPAN") **10** integrated with wireless local area network ("WLAN") **6** to form an integrated network **5**, in accordance with one embodiment of the present invention. In the embodiments described below, WLAN **6** is compliant with the

802.11x specification. It is understood, however, that the WLAN may be compliant with other protocols, such as WiMax. WLAN **6** may operate either in ad-hoc or in infrastructure mode. Moreover, the following description is provided with reference to the infrastructure mode of operation of WLAN **6**. It is understood that the present disclosure equally applies to the ad-hoc or any other mode. The infrastructure WLAN **6** is shown as including an AP **7** and one or more STAs **8**. STAs **8** are associated with and synchronized to AP **7** and periodically listen to beacons from AP **7**.

Each STA **8** is configured to include an 802.11x-compliant wireless circuit, such as a wireless enabled computer, a wireless Personal Digital Assistant, a Wi-Fi enabled cellular phone, or the like. The AP **2** can be connected to the Internet via an Internet router **9**. Internet connectivity can be established through any number of communication services, including Digital Subscriber Line ("DSL"), cable, satellite, or the like, as is well known.

WPAN **10** is shown as including one or more power-sensitive stations **11** ("PS-STA"). A PS-STA is defined herein as a device that is battery-operated and for which maximizing battery-life is beneficial to the application and/or user. Examples of PS-STAs include peripherals and accessories for personal computers, cellular phones, home entertainment accessories such as remote controls, monitoring devices for security, automation medical applications, or the like.

In accordance with one embodiment, a PS-STA is typically in a sleep mode the majority of the time, only waking up occasionally to communicate and exchange information with the outside world. In some systems described herein, each PS-STA **11** is equipped with a wireless circuit that can communicate directly with a standard 802.11x-compliant wireless circuit. PS-STAs **11** however are not required to be fully compliant with the 802.11x specification; some PS-STAs **11** may have reduced power dissipation thereby extending the battery life.

In embodiments in which PS-STAs **11** are not fully compliant with the 802.11x specification, the drivers or firmware of the 802.11x-compliant wireless circuit at the other end of the communication link (i.e., the device with which the PS-STA is interacting) may require modification. Thus, in some implementations, both the wireless circuit at the other end as well as the PS-STA are 802.11x-compliant, while in others the wireless circuit at the other end is 802.11x-compliant, but the PS-STA is not a fully compliant 802.11x wireless circuit, while in yet other implementations the driver or firmware of the 802.11x-compliant wireless circuit at the other end of the link requires modifications to accommodate the PS-STA. Integrated network **5** is also shown as including a wireless hub **12** adapted to facilitate seamless communication between the WLAN and the WPAN. The wireless hub **12** includes, in part, a wireless 802.11x-compliant wireless circuit that can communicate with the AP **7** disposed in infrastructure WLAN **6** as well as with PS-STAs **11** disposed in WPAN **10**. If more than one PS-STA is present in the WPAN, the wireless hub coordinates the timing and communication with each of the PS-STAs. In some embodiments, it may be desirable to shift as much as possible of the protocol overhead associated with the communication between wireless hub **12** and the PS-STAs **11** such as, for example, access to the medium, reservation of the medium, synchronization, etc., onto the wireless hub **12**, where power consumption is much less of a concern compared to the PS-STA. In such cases, the driver or firmware of the 802.11x-compliant components disposed in wireless hub **12** may require modification

To operate, wireless hub **12** is placed within the range of the AP **7** of the infrastructure WLAN **6**; this range is typically on the order of 300+ feet. The wireless hub **12** is also be placed within the range of each of the PS-STAs **11** in the WPAN **10** The PS-STAs **11** typically have a range of about 30 feet. This range can be longer or shorter depending on the application.

In one embodiment, the wireless hub **12** (alternatively referred to herein below as a "hub") is seamlessly integrated within an electrical power outlet. In a different embodiment, the hub can be a separate device that can be plugged into a power outlet. The wireless hub **12** can also be integrated inside other electronic devices, such as light bulbs, light switches, thermostats, energy meters, personal computers, Personal Digital Assistants ("PDAs"), cellular phones, home entertainment equipment and the like.

In some embodiments, a multitude of WPANs **13** may be so configured so as to be coupled to and in communication with a single WLAN **14**, as shown in FIG. **4**. Each WPAN **13** is coupled to the WLAN **14** by using a wireless hub **15**, as described above. If WPANs **13** are configured to operate independently, no additional coordination is required and each wireless hub **15** decides autonomously when to communicate with each of its respective PS-STAs under its control. However, in cases where additional coordination between the different WPANs is desirable, the necessary timing and control information can be exchanged between the wireless hubs **15** via the longer-range WLAN **14**.

FIG. **5** illustrates some of the components disposed in a PS-STA **11**, in accordance with one embodiment. PS-STA **11** typically includes, in part, a battery **16**, a sensor or stimulus unit **17**, a clock or crystal **18**, a wireless circuit **19** and an antenna **20**. Although not shown, other components like capacitors, resistors, inductors, an external power amplifier ("PA") and an external low-noise amplifier ("LNA") may also be included in PS-STA **11**. Wireless circuit **19** is configured so as to communicate over the physical layer ("PHY") of a standard 802.11x-compliant circuit chip disposed in the wireless hub (see FIGS. **3** and **4**). Wireless circuit **19** may be an embedded System-on-Chip ("SoC"), having disposed therein a radio **21** operating, for example, in the unlicensed 2.4-GHz and/or 5-GHz frequency bands, a baseband modem **22**, dedicated control and datapath logic **23**, a central processing unit ("CPU") **24**, a memory module **25** and interface circuitry **26**. CPU **24** and memory module **25** are used to implement the portion of the communication protocol that is not implemented in the dedicated control and datapath logic (also referred to as the 802.11x device drivers), together with any application-specific software. Wireless circuits are well known in the art and are not described herein.

FIG. **6** shows various blocks of a wireless hub, such as wireless hubs **12** and **15** shown respectively in FIGS. **3** and **4**, in accordance with one embodiment. The wireless hub acts as a pivot and provides communication between the corresponding WPAN and WLAN. The wireless hub includes an 802.11x-compliant wireless circuit **27**, a processing unit **28** coupled to or integrated with the 802.11x-compliant circuit, a memory module **29** that is coupled to or integrated with the 802.11x-compliant circuit, a crystal or clock **30**, and an antenna **38**. The 802.11x-compliant circuit **27** is shown as including a radio **31** operating, for example, in the unlicensed 2.4-GHz and/or 5-GHz frequency bands, a baseband modem **32**, and dedicated control and datapath logic **33**. Interface circuitry **34** provides an interface to the processing unit **28** and memory module **29**. Wireless hub may be connected to the power grid, in which case no batteries are needed to operate the device. Regulator **35** is adapted to regulate the supply. The wireless hub may further include various passive components like capacitors, resistors and/or inductors and an

external power amplifier ("PA") and/or external low-noise amplifier ("LNA") (not shown).

The wireless hub further includes a number of software modules forming a software platform **36** that enable circuit **29** to communicate with both the WPAN and WLAN. In one embodiment, the software platform **36** enables circuit **27** to connect to the WPAN, without losing connectivity (such as association and synchronization) to the WLAN, as described in Vleugels I. Circuit **27** can be connected to the WLAN and WPAN in alternating cycles, however added latency would be incurred.

In some embodiments, the wireless hub may further include an operating system **37** that may be used to write application-specific software. The operating system may be, for example, Windows XP, Windows CE, Linux, Symbian, or any operating system that may enable writing of applications.

The processing unit **28** and memory module **29** are used to implement that portion of the communication protocol that is not implemented in dedicated control and datapath logic; this portion of the communications protocol is referred to as the 802.11x device driver. If the communication protocol between the wireless hub and a PS-STA is modified to reduce power consumption of the PS-STA, the 802.11x device driver may also require slight modification to accommodate such changes. The CPU and memory module are also used for the implementation of the software platform that enables concurrent or alternating WLAN/WPAN connectivity, and can furthermore be used to run application-specific software.

The following example is provided to further aid in understanding the invention. FIG. **7** illustrates a WPAN used for remote monitoring and controlling, in accordance with one embodiment of the present invention. A user desires to check one or more security monitoring devices **39** inside or around his house **40** while at work **41**. Each security monitoring device is a PS-STA and is wirelessly connected to a Wi-Fi-enabled power outlet **42**. The Wi-Fi-enabled power outlet is furthermore within the range of a WLAN infrastructure network **43** which the user is assumed to have set up at his home.

The WLAN infrastructure network **43** is adapted to establish communication with the Internet via an Internet router **44** that is coupled to the AP **45**. At the office, the user has access to a laptop **46** that is equipped with an 802.11x-compliant wireless circuit. This circuit is associated with a WLAN infrastructure network **47** that has been set up in the user's office **41**. The WLAN network **47** is adapted to establish communication with the Internet via an Internet router **48** that is coupled to the infrastructure's network AP **49**. The connection at the office may be wireless or wired. In a wired office environment, the user's laptop is hooked up directly through the Internet router **48** with a cable, without making use of the WLAN **47**.

Application software on the user's laptop **46** allows the user to poll information from a specific PS-STA at home. To do so, the user sends a poll request, which contains the information required to unambiguously identify the PS-STA of interest, and possibly additionally information about the data to be retrieved. Destination address information includes the address of the router **44**, the address of the Wi-Fi-enabled power outlet **42** that controls the PS-STA of interest and the address of the PS-STA **39** itself. PS-STA address is typically required where multiple PS-STAs are connected to, for example, a single Wi-Fi-enabled power outlet. The poll request is transmitted over the WLAN **47** in the office, and via Internet router **48** transported over the Internet to the Internet router **44** at the home. At the user's home, the poll request is directed to the Wi-Fi-enabled power outlet that coordinates the PS-STA of interest. The Wi-Fi-enabled power outlet receives this request over the home's infrastructure WLAN. If the requested information has already been retrieved from the PS-STA during a previous data transfer event, the Wi-Fi-enabled power outlet responds to the poll request by sending the requested information over the home's infrastructure WLAN **43** to the Internet router that is connected to the home's WLAN AP. The requested information is transported over the Internet to the Internet router at the office, and from there directed to the user's laptop over the offices WLAN infrastructure network. Application software on the user's laptop receives the information and presents it to the user. In case the requested information has not yet been previously retrieved from the PS-STA, the Wi-Fi-enabled outlet does so during the next scheduled WPAN communication event. The timing of the occurrence of this event, depends, in part, on the power management techniques used for the WPAN communication.

To conserve power, the PS-STAs are typically mostly in sleep mode and only occasionally wake up as needed to transmit or receive data and/or control signals. When connected to the WPAN coordinated by the Wi-Fi-enabled power outlet **42**, a PS-STA **39** is synchronized to the Wi-Fi-enabled power outlet **42**, which as part of the infrastructure network, is in turn synchronized to the AP **45**. The synchronization between the PS-STAs and the Wi-Fi-enabled power outlet ensures that the Wi-Fi-enabled power outlet is in WPAN mode at the same time that a PS-STA wakes up to transmit or receive. The above example describes an instance where the information from a single PS-STA is remotely accessed, using a Wi-Fi-enabled power outlet. It is understood that the wireless hub does not have to be a Wi-Fi-enabled power outlet, and may be any wireless hub, as described above. Furthermore, it is understood that multiple PS-STAs may be connected to a single as well as to multiple wireless hubs. The present invention may also be used to activate or steer PS-STAs, in addition to monitoring or retrieving information.

In some embodiments, rather than having data transfer be triggered by a poll request, the PS-STAs may also transmit data to the wireless hub periodically. In such embodiments, the retrieved data can be stored and/or processed locally on the wireless hub, or, alternatively, be transferred to a different location.

The association of a PS-STA with a wireless hub may or may not be static. In some embodiments, the PS-STA may be attached to a moving object, in which case the nearest wireless hub is dynamic and may change over time. This scenario is common in the context of medical monitoring/treatment. In such embodiments, medical sensors and stimulus devices in, on and around a person's body communicate to a nearby wireless hub that acts as a seamless bridge between the low-power WPAN and the longer-range WLAN. As the person/patient moves around the house, the nearest wireless hub may change over time. In such applications, seamless transitioning between wireless hubs is carried out and includes dynamic association capabilities inside the PS-STA, as well as software on the wireless hub side to seamlessly handle the required hand-offs among wireless hubs. The present invention is also applicable, for example, to the following situations:

- Remote medical monitoring
- Medical monitoring/treatment in hospitals
- In-house monitoring and control from any location to any location
- Industrial monitoring/warehouse monitoring
- Home automation
- Energy metering

PC, cell phone and home entertainment peripherals and accessories

The following are among the advantages of embodiments of the present invention:

Cost savings associated with infrastructure/hardware re-use

Integration of low-power short-range networks in the ubiquitous WLAN infrastructure results in cost savings since already-present hardware can be re-used. Little or no dedicated set up is required to enable the short-range connectivity

IP-addressable PS-STAs, enabling remote monitoring

Low-power short-range networks typically act as isolated networks. As a consequence, such networks can only be accessed when in close vicinity. This enables access to the WPAN from any location that is within the coverage area of the WLAN, or even from a remote location. Unlike other low-power wireless technologies, the power-sensitive nodes described herein are IP-addressable and, consequently, can be monitored and/or controlled from any location that has Internet access.

Long-range connectivity is achieved, without putting the associated burden on the power-sensitive device

The burden of achieving long-range connectivity is shifted away from the power-sensitive device onto the wireless hub. Since typically, the wireless hub is a powered device, power dissipation is not much of an issue.

As a result, a power-sensitive battery-operated device can be connected to the ubiquitous WLAN infrastructure without having to bear the consequences in terms of power dissipation and protocol overhead that are typically associated with this.

Specific Examples

A WPAN is a short-range wireless network, with typical coverage ranges on the order of 30 feet, usable to connect peripherals to devices in close proximity, thereby eliminating cables usually present for such connections. For example, a WPAN might be used to connect a headset to a mobile phone or music/audio player, a mouse or keyboard to a laptop, a PDA or laptop to a mobile phone (for syncing, phone number lookup or the like), etc. Yet another example of a WPAN application is a wireless medical monitoring device that wirelessly connects monitoring hardware to a pager or similar read-out device. Yet another example is a remote control that connects to a wireless-enabled electronic device.

A WPAN is generally used for the interconnection of information technology devices within the range of an individual person, typically within a range of 10 meters. For example, a person traveling with a laptop will likely be the sole user of that laptop and will be the same person handling the personal digital assistant ("PDA") and portable printer that interconnect to the laptop without having to plug anything in, using some form of wireless technology. Typically, PAN nodes interact wirelessly, but nothing herein would preclude having some wired nodes. By contrast, a WLAN tends to be a local area network ("LAN") that is connected without wires and serves multiple users.

Communication with the WPAN device might use an SWN protocol that is only partially compliant with the protocol used over a conventional WLAN and might do so without interference from the conventional WLAN, yet usage of the WLAN is such that the WPAN device and computing device can communicate without interference. To reduce interference, the computing device coordinates the usage of the wireless medium with devices of a WLAN that may be active in the same space. Coordination is achieved by the use of a secondary network (WPAN) protocol that is an overlay protocol that is partially compatible with the WLAN protocol, but not entirely, in terms of power, frame contents and sequences, timing, etc. The secondary network (WPAN) protocols might be 802.11x frames with new frame arrangements adapted for WPAN needs, such as reduced latency, power etc. The computing device might determine to signal the primary network (WLAN) such that devices therein defer so that communications can occur with the secondary network.

In the general example, the computing device is a portable and/or mobile computing and/or communications device with some computing capability. Examples of computing devices include laptop computers, desktop computers, handheld computing devices, pagers, cellular telephones, devices with embedded communications abilities and the like. Examples of peripheral devices include typical computer, telephone etc. accessories where wireless connections are desired, but might also include less common devices, such as wearable devices that communicate with other devices on a person or even to communicate with other nearby devices, possibly using the electrical conductivity of the human body as a data network. For example, two people could exchange information between their wearable computers without wires, by transmission through the air, or using their bodies and/or clothing.

The computing devices may interface to 802.11 WLANs or other wireless networks to communicate with other network nodes, including nodes accessible through wired connections to the wireless network (typically via an access point). The computing devices also may interface to PAN devices over a WPAN, such as wireless headsets, mice, keyboards, accessories, recorders, telephones and the like. A wide variety of PAN devices are contemplated that are adapted for short-range wireless communications, typically bi-directional and typically low power so as to conserve a PAN device's limited power source. Some PAN devices might be unidirectional, either receive-only or transmit-only, devices.

In a typical approach, where a STA needs to connect to more than one wireless network, the STA associates with one wireless network and then when associating with another wireless network, it disassociates with the first wireless network. While this is useful for a WLAN where a STA might move out of one network's range and into the range of another network, this is not desirable when latency needs to be less than an association set-up time. The latency incurred with this switching procedure easily amounts to several hundreds of milliseconds.

In certain applications, it may be desirable for a STA to connect to multiple networks without incurring long switching-induced latencies. For example, consider a typical PER device, that of a cordless mouse. Since update rates for a cordless mouse during normal operation are on the order of 50 to 125 times per second, switching-induced latencies involved with 802.11x association set ups are not acceptable. Furthermore, the switching overhead significantly reduces the STA's usable communication time, defined as the time that the STA is available to transmit or receive data.

In a specific embodiment of the invention, a wireless peripheral like a mouse, is attached to an 802.11x-enabled computing device like a laptop computer, using the 802.11x wireless circuitry inside the laptop, or connected to the laptop via a NIC card. At the same time, the laptop may be connected to the Internet via a regular WLAN network, using the same 802.11x circuitry. Herein, a peripheral or WPAN node will be referred to as "PER". Multiple PERs can connect to a single WPAN. The wireless device coordinating the WPAN is called

the coordinator ("COORD"). Where the COORD is also able to connect to the 802.11x network, the COORD is referred to as a "dual-net" device, since it handles both networks. A typical dual-net device in this example is a device that is a STA on an 802.11x network while also having wireless peripherals used by applications running on that device.

While not always required, the PERs are power-sensitive devices. It should be understood that an object labeled "PER" need not be a peripheral in the sense of an object with a purpose to serve a particular purpose, but rather an object that performs the behaviors herein referred to as behaviors of a WPAN node. For example, a printer can be a PER when it is connected to a desktop computer via a WPAN, but some other device not normally thought of as a peripheral can be a PER if it behaves as one.

FIG. **8** illustrates various devices operating as part of a primary wireless network ("PWN") **100**, a secondary wireless network ("SWN") (such as **114** or **116**), or both. In the figure, an access point ("AP") **110** supports an infrastructure mode for PWN **100**, coupling various stations to the network allowing, for example, network traffic between a station and a wired network **112**. By communicating with the AP, a station can retrieve information from the Internet and exchange data with other stations that may or may not be part of the Basic Service Set ("BSS") managed by the AP.

As shown in the example, the stations present are STA**1**, STA**2**, STA**3** and STA**4**. Each station is associated with a node in PWN **100** and has the necessary hardware, logic, power, etc. to be a node device in PWN **100**. Station STA**1** also coordinates SWN **114** as the COORD for that network shown comprising PER**1**, PER**2** and PER**3**. Likewise, station STA**4** coordinates SWN **116** as the COORD for the network comprising STA**4**, PER**10** and PER**11**. In FIG. **8**, each node device is shown with an antenna to indicate that it can communicate wirelessly, but it should be understood that an external antenna is not required.

Other network components and additional instances might also be present. For example, more than one AP might be present, there might be overlaps of BSSes and other network topologies might be used instead of the exact one shown in FIG. **8** without departing from the scope of the invention. Examples used herein for PWN **100** include 802.11x (x=a, b, g, n, etc.), but it should be understood that the primary wireless network may well be another network selected among those in present use or available when the primary wireless network is implemented.

In this example, the secondary wireless networks are assumed to be used for WPAN functionality. The WPAN can be used for, but is not limited to, fixed data rate applications where exchange of data can be scheduled and the amount of data to be exchanged is known and a single dual-net device might interface with multiple PERs. Because the dual-net device may be a regular STA in the first WLAN, it can power-down as needed without problems, unlike an access point. However, since it is also the COORD, peripheral communication could be lost if the peripheral is powered up but the dual-net device/COORD is not. This can be dealt with using mutually agreeable inactivity periods.

FIG. **8** shows, at a high level, the interplay among various nodes of various networks. FIG. **9** illustrates a subpart of the elements of FIG. **8**, illustrating in greater detail. In this figure, AP **110** is coupled to wired network **112** via cable **120** and might communicate using any suitable wire-based networking protocol. On the other side, AP **110** transmits signals to a station device, in this case a laptop **122**, using the AP's antenna and those signals are received by laptop **112** using its antenna. Signals can also flow in the other direction. Such communications would be done according to a PWN protocol, such as an 802.11x protocol.

Laptop **122** (a dual-net device in this example) in turn can communicate with the peripherals shown, in this example a wireless mouse ("PER**1**") **124** and a wireless printer ("PER**2**") **126**. It may be that power for wireless printer **126** comes from an external power outlet, in which case power consumption might be less of a concern than with mouse **124** if it operates on battery power. Nonetheless, both peripherals might use the same power-saving protocol. Power conservation might also be performed on the dual-net device, for example, when it is a laptop.

To conserve power at the WPAN device and the computing device, they can agree on an inactivity time and disable at least a part of a coordination function of the computing device following a start of the inactivity time, wherein disabling is such that less power per unit time is consumed by the network circuit relative to power consumed when not disabled.

Coordination of Multiple PERs

When a secondary network includes multiple PERs as illustrated in FIG. **10**, it may be desirable to coordinate data exchanges in order to minimize the power dissipation, as well as to minimize the WM occupancy. A method to coordinate the communication between a COORD and multiple PERs is shown in FIG. **11**.

At time T_0, the COORD and PERs are programmed to start the frame exchange. If power-save modes are implemented in the COORD or the PERs, a wake-up request will be issued prior to T_0, to ensure that all necessary circuits are powered up at time T_0. At time T_0, the COORD contends for the WM and, optionally using the highest priority queue (AC-VO) transmits a first frame, frame **1**. The duration field of this frame has been increased to reserve the WM for the subsequent frame transmission by the PERs of the secondary network that are scheduled for a frame exchange during the current frame exchange sequence. The duration field might have been passed during the pairing state, so that the PER and COORD both know and agree on its value.

Furthermore, frame **1** contains a list of PERs it expects to respond, as well as an offset for each scheduled PER. At the specified offset, each PER is awake and responds with a frame containing its data (frame **2**P**1** and frame **2**P**2**). Optionally, the COORD acknowledges error free reception of the frame, or the COORD can respond with a frame that includes data to be transmitted from the COORD to the frame. Optionally, the PER acknowledges error free reception of the latter frame. Optionally, PERs can return to sleep during the time slots where the COORD is communicating with other PERs.

If one or more of the transmissions were not successful, the COORD may send an additional frame immediately following the above described frame sequence to reserve the medium for additional time to allow for retransmissions. This frame contains the PERs for which retransmission is desirable as well as the corresponding offsets for each PER. PERs that received acknowledgment of their transmission do not have to wake up to listen to this additional frame. In one embodiment, it may be left up to a PER to decide whether it will consider retransmission.

An alternative frame exchange sequence for the coordination of multiple PERs is illustrated in FIG. **12**. In this embodiment, the COORD polls each PER individually. At the start of a Service Period ("SP"), the COORD contends for the WM and after gaining access to the WM, the COORD polls the PERs in its secondary network one by one with 1 SIFS space intervals. The latter avoids the situation where the COORD has to contend for the WM for each PER in its secondary network.

To conserve power in the PERs, the expected time for communication with each PER can be pre-calculated based on the number of PERs that are scheduled to be polled prior to the respective PER and their scheduled traffic size.

In case a transmission fails, a retransmission mechanism can be initiated. Alternatively, the COORD may poll the next PER and come back to the failed transmission later, after it has polled all other PERs for which a traffic stream ("TS") has been set up.

Before entering the ACTIVE state, a COORD and PER first go through the PAIRING and CONNECTION states. The first step in establishing a new connection is device PAIRING. Device pairing comprises the first time configuration steps for linking a PER to a COORD.

Device Discovery

During a device discovery procedure, MAC address information is exchanged between the COORD and the PER. A dedicated configuration pushbutton or a simple user action will be used to initiate device discovery. Upon such user intervention, the COORD and PER both enter a "limited discoverable mode" for a certain period of time that is long enough to finish the device discovery procedure. Both COORD and PER can initiate the discovery procedure. The device that initiates the discovery procedure is called the "initiator"; the other device is hereafter referred to as the "follower".

Upon entering discoverable mode, the initiator sends a broadcast discovery request. The broadcast discovery request is a broadcast frame, and may contain information such as the initiator's MAC address, and the type of devices that should respond. A follower in discoverable mode responds to a broadcast discovery request with a discovery response. The discovery response frame is a unicast frame that is addressed to the initiator.

For security reasons, it is advisable that the amount of information exchanged while in discoverable mode is minimized. However, if appropriate, additional information can be exchanged during the device discovery procedure. For example, if generated by the COORD, the broadcast discovery frame may optionally contain information on the WLAN connectivity status (infrastructure/ad-hoc/unconnected, operating channel, power-save, etc.). If generated by the PER, the broadcast discovery frame may optionally contain information about the type of PER.

In one embodiment, the COORD acts as the initiator and sends an IEEE802.11 probe request frame. The SSID parameter of the broadcast probe request frame may be used to communicate specific information to the PER, in this case the follower. More specifically, the SSID field in the frame body can be used as a frame type identifier and to send additional information to a follower. For example, specific bits of the SSID can be used to identify the over-the-air protocol. Other bits of the SSID can be reserved to identify the frame as a broadcast discovery request frame. The remainder of the bits can be reserved or used to communicate additional information about the COORD or the WLAN it is associated with to the PER (follower).

In another embodiment, a data frame or standard or proprietary IBSS beacon frame or other management frame is used as a broadcast discovery request frame.

Upon receiving the broadcast device discovery request frame, the PER in discoverable mode (the follower) responds by sending a unicast discovery response frame. This can be a unicast IEEE802.11 probe response frame. The probe response frame is addressed to the initiator, and structured such that it is recognized as a discovery response frame by the initiator. Alternatively, the discovery response frame can be a data frame formatted to be recognized by the COORD as a discovery response frame.

A device discovery channel can be pre-defined in the protocol. In that case, an initiator put into discoverable mode will, by default, start sending broadcast discovery requests on the pre-defined channel, and a follower put in discoverable mode will, by default, listen for a broadcast discovery request on the pre-defined channel.

When device discovery is initiated, and no device discovery channel is pre-defined, the initiator and follower may need to search for each other. Either the initiator or the follower may perform this search. If the initiator performs the search, the follower listens on a fixed channel, while the initiator scans different channels, by subsequently transmitting broadcast discovery request frames on different channels. Alternatively, when the follower performs the search, the initiator transmits broadcast discovery request frames on a fixed channel at $T_{discovery}$ time intervals, while the follower performs a passive scan by listening for a broadcast discovery request on different channels. Note that the follower should stay on a single channel for at least $T_{discovery}$ to ensure it will capture a broadcast discovery frame.

At the conclusion of the device discovery procedure, at a minimum, the initiator and follower have knowledge of each other's MAC address and current operating channel of the COORD's primary network.

Variations

Other variations should be apparent upon review of this disclosure.

While the present invention has been described herein with reference to particular embodiments thereof, a latitude of modification, various changes, and substitutions are intended in the present invention. In some instances, features of the invention can be employed without a corresponding use of other features, without departing from the scope of the invention as set forth. Therefore, many modifications may be made to adapt a particular configuration or method disclosed, without departing from the essential scope and spirit of the present invention. It is intended that the invention not be limited to the particular embodiments disclosed, but that the invention will include all embodiments and equivalents falling within the scope of the claims.

What is claimed is:

1. A network-enabled hub, usable for facilitating data communications between two or more wireless devices that are configured to communicate indirectly with each other via the network-enabled hub, comprising:

an interface to a wireless radio circuit that can send and receive data wirelessly, providing the hub with bi-directional wireless data communication capability;

logic for processing data received via the wireless radio circuit;

logic for generating data to be transmitted by the wireless radio circuit;

logic for initiating and maintaining wireless network connections with nodes of a wireless network external to the network-enabled hub, maintaining at least a first wireless network connection using a first wireless network protocol and a second wireless network connection using a second wireless network protocol, that can be maintained, at times, simultaneously with each other in a common wireless space, wherein the second wireless network protocol is an overlay protocol with respect to the first wireless network protocol in that communications using the second wireless network protocol are partially consistent with the first wireless network pro-

tocol and at least some of the communications using the second wireless network protocol impinge on at least some antennae used for the first wireless network; and

data forwarding logic, implemented in the network-enabled hub using hardware and/or software, that forwards data between an originating node and a destination node, wherein the originating node is a node in one of the first and second wireless networks and the destination node is a node in the other of the first and second wireless networks.

2. The network-enabled hub of claim **1**, further comprising a routing module for receiving a poll request that contains information required to unambiguously identify a station that is a node in the second wireless network, wherein the routing module coordinates retrieval of information from the station.

3. The network-enabled hub of claim **1**, wherein the first wireless network connection provides a link via an access point of a wireless local area network ("LAN") and the second wireless network connection provides a link to a personal area network ("PAN") serving PAN devices, such that network nodes that have access to the wireless LAN can address packets to PAN devices that are nodes on the PAN.

4. The network-enabled hub of claim **1**, wherein the first wireless network protocol is an 802.11x wireless protocol and the second wireless network protocol is a modification of the 802.11x wireless protocol that is not entirely compliant with the 802.11x wireless protocol of the first wireless network but can be maintained in a common wireless space as the 802.11x wireless protocol.

5. The network-enabled hub of claim **1**, wherein the network-enabled hub includes logic to coordinate a mutually agreeable inactivity period between the network-enabled hub and wireless personal area network ("WPAN") devices such that the WPAN devices can enter a sleep mode and occasionally wake up to transmit or receive data and/or control signals, with the network-enabled hub and WPAN devices synchronized so that the network-enabled hub is able to communicate with WPAN devices when WPAN devices wake up.

6. The network-enabled hub of claim **1**, further comprising the wireless radio circuit interfaced to the logic for processing data, wherein the wireless radio circuit supports communications on both the first wireless network and the second wireless network.

7. The network-enabled hub of claim **1**, wherein the wireless radio circuit and the logic for processing data are configured to allow the network-enabled hub to transmit on more than one radio band.

8. The network-enabled hub of claim **1**, wherein the wireless radio circuit and the logic for processing data are configured to allow the network-enabled hub to alternate connectivity between the first wireless network connection and the second wireless network connection.

9. The network-enabled hub of claim **1**, wherein the network-enabled hub is embedded into a personal computer, a cellular phone, or home entertainment equipment.

10. The network-enabled hub of claim **1**, wherein the first wireless network connection is for a wireless network having a first operating range and the second wireless network is for a wireless network having a second operating range, where the first operating range is larger than the second operating range.

11. The network-enabled hub of claim **1**, wherein the data forwarding logic further comprises logic for uniquely identifying the destination node from data received from the originating node such that the network-enabled hub can use that data to transmit data into the second wireless network.

12. The network-enabled hub of claim **11**, wherein the data identifying the destination node is a network address of the destination node.

13. The network-enabled hub of claim **11**, wherein the data identifying the destination node is an Internet Protocol (IP) address of the destination node.

14. A computing device having therein a network-enabled hub, comprising hardware and software, usable for facilitating data communications between two or more wireless devices that are configured to communicate indirectly with each other via the network-enabled hub, comprising:

a wireless radio circuit that can send and receive data wirelessly, providing the hub with bi-directional wireless data communication capability, the radio circuit configured to handle 802.11x packet transmissions, and wherein the wireless radio circuit supports communications on both a wireless local area network ("WLAN") and wireless personal area network ("WPAN");

logic for processing data received via the wireless radio circuit;

logic for generating data to be transmitted by the wireless radio circuit;

logic for initiating and maintaining wireless network connections with nodes of the WLAN and WPAN external to the network-enabled hub, maintaining at least a first wireless network connection using a first wireless network protocol, of the WLAN, and a second wireless network connection using a second wireless network protocol, of the WPAN, that can be maintained, at times, simultaneously with each other in a common wireless space, wherein the second wireless network protocol is an overlay protocol with respect to the first wireless network protocol in that communications using the second wireless network protocol are partially consistent, but not entirely consistent, with the first wireless network protocol, and wherein the first wireless network protocol is an 802.11x wireless protocol and the second wireless network protocol is a modification of the 802.11x wireless protocol of the first wireless network but can be maintained with the 802.11x wireless protocol in the common wireless space wherein at least some of the communications using the second wireless network protocol impinge on at least some antennae used for the first wireless network; and

logic for data forwarding between an originating node that is a node in of one of the first and second wireless networks and a destination node that is a node in of the other of the first and second wireless networks;

at least one software module forming a software platform that allows the wireless radio circuit to connect to both the WLAN and the WPAN, and coordinate retrieval of information from the station; and

an operating system that enables operation of the network-enabled hub and execution of user-written application-specific application software for the network-enabled hub,

wherein the first wireless network connection provides a link via an access point of the WLAN and the second wireless network connection provides a link to the WPAN serving PAN devices, such that network nodes that have access to the WLAN can address packets to WPAN devices that are nodes on the WPAN and packets can be conveyed from a WPAN device, through the network-enabled hub, to the access point and from there to a destination over the Internet from the access point, and wherein the WPAN device's access to the Internet is via the network-enabled hub.

15. The computing device of claim 14, wherein the WPAN devices are IP addressable.

16. The computing device of claim 14, wherein the WPAN devices are a computer accessory, a telephone accessory, a wearable device, a wireless headset, a wireless mouse, a wireless keyboard, a wireless recorder, or a wireless telephone.

17. The computing device of claim 14, wherein the computing device is a component of a portable computing device, a mobile computing device, a communications device with computing capability, a laptop computer, a desktop computer, a handheld computing device, a pager, or a cellular telephone.

18. The computing device of claim 14, wherein the logic for data forwarding further comprises logic for uniquely identifying the destination node from data in a data packet received from the originating node and transmit data into the second wireless network using that unique identification of the destination node.

19. An electronic device having an ability to communicate wirelessly and configured to support functions requiring messages to be sent, or data to be received, to destination nodes not directly accessible by wireless communication circuits of the electronic device, the electronic device comprising:

a processor;

a memory;

control logic for generating a message based on inputs to the electronic device, wherein the message comprises data that depends on the inputs received and uniquely identifies a destination node on a network that is accessible using a first wireless network protocol but not accessible using a second wireless network protocol used by the electronic device, the first wireless network protocol and the second wireless network protocol being for use over wireless networks in a common wireless space, wherein the second wireless network protocol is an overlay protocol with respect to the first wireless network protocol in that communications using the second wireless network protocol in the common wireless space are partially consistent with the first wireless network protocol such that at least a first wireless network connection using the first wireless network protocol and a second wireless network connection using the second wireless network protocol can have their connections maintained, at times, simultaneously with each other in the common wireless space;

datapath logic for generating addressing information of an address of a network-enabled hub accessible directly by the electronic device using the second wireless network protocol, the address being of a network-enabled hub capable of sending messages to the destination node using the second wireless network protocol;

a wireless radio circuit that can send and receive data wirelessly between the electronic device and the network-enabled hub;

an interface between the processor and the wireless radio circuit for sending and receiving data wirelessly and processing that data.

20. The electronic device of claim 19, wherein the data identifying the destination node is a network address of the destination node.

21. The electronic device of claim 19, wherein the data identifying the destination node is an Internet Protocol (IP) address of the destination node.

22. The electronic device of claim 19, wherein the electronic device is a remote control for a home entertainment accessory.

23. The electronic device of claim 19, further comprising a battery for powering the electronic device and further wherein the electronic device is configured to wirelessly communicate with a network-enabled hub that is powered such that wireless communication power is not a constraint on the network-enabled hub.

24. The electronic device of claim 19, wherein the first wireless network protocol provides a link via an access point of a wireless local area network ("LAN") and the second wireless network protocol provides a link to a personal area network ("PAN") serving PAN devices including the electronic device.

25. The electronic device of claim 19, wherein the first wireless network protocol is an 802.11x wireless protocol and the second wireless network protocol is a modification of the 802.11x wireless protocol that is not entirely compliant with the 802.11x wireless protocol but can be maintained in the common wireless space with the 802.11x wireless protocol.

26. The electronic device of claim 19, further comprising logic for entering a sleep mode and synchronizing sleep periods with the network-enabled hub.

27. A network-enabled hub, usable for facilitating data communications between two or more wireless devices that are configured to communicate indirectly with each other via the network-enabled hub, comprising:

an interface to a wireless radio circuit that can send and receive data wirelessly, providing the hub with bi-directional wireless data communication capability;

logic for processing data received via the wireless radio circuit;

logic for generating data to be transmitted by the wireless radio circuit;

logic for initiating and maintaining wireless network connections with nodes of a wireless network external to the network-enabled hub, maintaining at least a first wireless network connection using a first wireless network protocol and a second wireless network connection using a second wireless network protocol, that can be maintained, at times, simultaneously with each other in a common wireless space, wherein the second wireless network protocol is an overlay protocol with respect to the first wireless network protocol in that communications using the second wireless network protocol are consistent with the first wireless network protocol, but the first wireless network and the second wireless network are distinct in that at least one node of the second wireless network is not a node in the first wireless network and at least some of the communications using the second wireless network protocol impinge on at least some antennae used for the first wireless network; and

data forwarding logic, implemented in the network-enabled hub using hardware and/or software, that forwards data between an originating node and a destination node, wherein the originating node is a node in of one of the first and second wireless networks and the destination node is a node in the other of the first and second wireless networks.

28. The network-enabled hub of claim 27, wherein the network-enabled hub is embedded into a personal computer, a cellular phone, or home entertainment equipment.

29. The network-enabled hub of claim 27, wherein the first wireless network connection is for a wireless network having a first operating range and the second wireless network is for a wireless network having a second operating range, where the first operating range is larger than the second operating range.

* * * * *