US009483448B2

(12) **United States Patent**
Pirnazar

(10) **Patent No.: US 9,483,448 B2**
(45) **Date of Patent: *Nov. 1, 2016**

(54) **METHOD AND APPARATUS FOR THE IMPLEMENTATION OF A REAL-TIME, SHARABLE BROWSING EXPERIENCE ON A HOST DEVICE**

(71) Applicant: **Samesurf, Inc.**, Beverly Hills, CA (US)

(72) Inventor: **Kambiz David Pirnazar**, Los Angeles, CA (US)

(73) Assignee: **SAMESURF, INC.**, Beverly Hills, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/830,710**

(22) Filed: **Aug. 19, 2015**

(65) **Prior Publication Data**

US 2015/0358386 A1 Dec. 10, 2015

Related U.S. Application Data

(63) Continuation of application No. 12/783,735, filed on May 20, 2010.

(51) **Int. Cl.**

G06F 15/173	(2006.01)
G06F 17/22	(2006.01)
H04L 29/08	(2006.01)
G06F 17/30	(2006.01)
H04L 12/58	(2006.01)
H04L 29/06	(2006.01)

(52) **U.S. Cl.**

CPC ***G06F 17/2235*** (2013.01); ***G06F 17/30873*** (2013.01); ***H04L 51/046*** (2013.01); ***H04L 65/403*** (2013.01); ***H04L 67/02*** (2013.01); ***H04L 67/104*** (2013.01); ***H04L 67/141*** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,572,483	B1	10/2013	DiLorenzo
2002/0073152	A1	6/2002	Andrew et al.
2004/0100507	A1	5/2004	Hayner
2005/0097107	A1	5/2005	Burt
2005/0108328	A1	5/2005	Berkeland

(Continued)

OTHER PUBLICATIONS

"Why WebEx? Discover the benefits of real-time web collaboration in your organization", Cisco WebEx LLC, 2009.*

(Continued)

Primary Examiner — Scott B Christensen

(74) *Attorney, Agent, or Firm* — Jafari Law Group, Inc.

(57) **ABSTRACT**

The present invention describes a method and apparatus for the implementation of a real-time, sharable web browsing experience on a host device, utilizing the transfer of URL and form data information. The present invention further describes a method for establishing a synchronized browsing session, comprising sending a request to establish the synchronized browsing session to a synchronization server, receiving a confirmation message from the synchronization server including a session identifier associated with the established synchronized browsing session, and sending an invitation to an invitee to join the synchronized browsing session, wherein the invitation includes the session identifier. The present invention further describes a method for implementing a synchronized browsing session, comprising recording a shared web browsing interaction, and transmitting information related to the shared web browsing interaction to a synchronization server.

16 Claims, 20 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

2005/0160141	A1	7/2005	Galley et al.	
2005/0198162	A1*	9/2005	Bauer	G06F 17/30873 709/206
2008/0016155	A1	1/2008	Khalatian	
2008/0028323	A1*	1/2008	Rosen	G06Q 10/10 715/752
2008/0289029	A1	11/2008	Kim et al.	
2009/0157507	A1	6/2009	Agius	

OTHER PUBLICATIONS

"Re: (Forward to attendees) Meeting invitation: Webex Demo". Published Jul. 29, 2009 on https://www.ietf.org/mailarchive/web/wgchairs/current/msg07340.html.

"Presenting Online". Publishhed Apr. 23, 2010.

"How do Affiliate Marketing Software Programs track sales, leads and clicks?" Published Jul. 1, 2009.

* cited by examiner

FIG. 1(a)


12
Website Server
Synchronization Server
13
Internet
11
10
14
15
Host Device
Guest Device
Guest Device

FIG. 1(b)


16
18
17
Web
Images
Videos
Maps
News
Books
Gmail
more
iGoogle
Settings
Sign out
Google Search
I'm Feeling Lucky
Advertising Programs
Business Solutions
About Google
Go to Google.com

FIG. 1(c)



FIG. 1(d)



FIG. 1(e)



FIG. 2(a)


13
Synchronization Server
40
43
44
10
14
Host Device
41
Guest Device
42

FIG. 2(b)


100
101
Click Hyperlink on Webpage to Host Synchronized Browsing
102
Software Detected?
No
Yes
103
Download Software From Sync. Server
104
Run Synchronized Browsing Software
105
Send Request for a Synchronization Session to Sync. Server
106
Receive Confirmation of Sync. Session Including Session Identifier
107
Send Invitation to One or More Guests Including Session Identifier
108
Receive Confirmation of One or More Guests Joining Sync. Session

FIG. 2(c)



FIG. 3


200
201
Receive Sync. Browsing Session Initialization Request From Host Device
202
Establish Sync. Session and Generate Session Identifier
203
Store Session Identifier and Host Device Info in Database
204
Send Confirmation of Session to Host Device With Session Identifier
205
Receive Guest Device Request to Join Session With Session Identifier
206
Store Guest Device Identification Info in Database
207
Generate Guest Info Notification Message For Synchronization
208
Send Notification to Host that Guest Device has Joined Sync. Session

FIG. 4(a)


300
301
Receive Session Invitation for Sync. Browsing Session Including Session Identifier
302
Activate Hyperlink From Session Invitation
303
Software Detected?
No
Yes
304
Download Software From Sync. Server
305
Run Synchronized Browsing Software
306
Send Request to Join Sync. Session to Sync. Server with Session Identifier

FIG. 4(b)


53
From: John@sharebrowsing.com
To: Bob@internet.com
Subject: Sync. Browsing Session
Bob,
John has invited you to a Synchronized Browsing Session.
To join, click on the following hyperlink:
http://www.synchronizedbrowsing.com/sessionid/374892375932875932759.htm
52

FIG. 4(c)


54
SOCIAL-NETWORKING WEBSITE
Picture
Message: Click here to join my Synchronized Browsing Session!
http://www.synchronizedbrowsing.com/sessionid/374932759.htm
52

FIG. 4(d)


55
MICRO-BLOGGING WEBSITE
John
Message: Click here to join my Synchronized Browsing Session!
http://www.synchronizedbrowsing.com/sessionid/374932759.htm
52
That is really cool, I'll join now!
Bob
That was really fun! I like synchronized browsing!!
Mary

FIG. 4(e)


56
NEWS FEED WEBSITE
52
Join John4859's Synchronized Browsing Session: http://www.synchbrowsing.com/32759.htm
Join Steve386's Synchronized Browsing Session: http://www.synchbrowsing.com/48357.htm
Join Betty132's Synchronized Browsing Session: http://www.synchbrowsing.com/18564.htm
Active Public Browsing Sessions:
Session ID: 3156231
Session ID: 6516194
Session ID: 1583513
Session ID: 9786203
Session ID: 3418560
Session ID: 7315089
Session ID: 2080030
To Find a Private Browsing Sesssion, CLICK HERE:

FIG. 5(a)


12
Website Server
13
Synchronization Server
63
65
60
66
64
62
67
10
61
14
Host Device
Guest Device

FIG. 5(b)


400
401
Transmit a Request To Website Server Including Form Data
402
Transmit URL of Webpage and Form Data to Sync. Server
403
Receive Affiliation ID Code?
No
Yes
404
Transmit Affiliation ID Code to Website Server
405
Receive Webpage Data From Website Server
406
Output Website Data in Shared Browsing Window

FIG. 5(c)


500
501
Receive Host Webpage Interaction Information
502
Query Internal Affiliation Database For a Match
503
Affiliation With Website Server Found?
No
504
Identify Guest Devices in Sync. Browsing Session
505
Transmit Host Webpage Interaction Information to Identified Guest Devices
Yes
506
Transmit Affiliate ID Code to Host Device
507
Identify Guest Devices in Sync. Browsing Session
508
Transmit Host Webpage Interaction Info. with ID Code to Identified Guest Devices

FIG. 5(d)


600
601
Receive Webpage Interaction Information From Sync. Server
602
Transmit Request to Webpage Server Utilizing Webpage Interaction Info
603
Receive Webpage Data From Webpage Server
604
Output Webpage Data in Shared Browsing Window

FIG. 6(a)


700
701
Detect Non-shared Activation of Hyperlink in Shared Browser Window
702
Generate an Unshared Browser Window
703
Contact Webpage Server
704
Receive Webpage Data
705
Output Webpage Data In Unshared Browser Window

FIG. 6(b)


750
751
Detect Activation of Hyperlink in Shared Browser Window
752
Generate an Unshared Browser Window
753
Contact Webpage Server
754
Receive Webpage Data
755
Output Webpage Data In Unshared Browser Window

FIG. 7(a)


16
17
18
70
71
72
73
74
75
76
samesurf
Fred (host)
John
Alice
Mary
John: Hey everyone
Alice: Hey John!
John: We're gonna start soon
Mary: ok

FIG. 7(b)


76
77
SAMESURF
START NEW ROOM
Shared Browser
Get Started
Apple Store
BROWSE
Search
Favorites
Happening Now
Shopping
Travel
Media
Apps
FEATURED ROOMS
FEATURED PEEPS
UPCOMING EVENTS
Shopping with Martha Stewart
Friends Online
Facebook
Buddies
The Dude
Water Sabbatch
Donny
Talk
Chat
Everyone

METHOD AND APPARATUS FOR THE IMPLEMENTATION OF A REAL-TIME, SHARABLE BROWSING EXPERIENCE ON A HOST DEVICE

PRIORITY NOTICE

The present application claims priority under 35 U.S.C. §120 to U.S. Nonprovisional patent application Ser. No. 12/783,735 filed on May 20, 2010, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD OF THE INVENTION

The present invention relates in general to a sharable browsing experience, and more specifically, to a method and apparatus for the implementation of a synchronized browsing session on a host device utilizing the transfer of URL, form data, script, and other information.

COPYRIGHT & TRADEMARK NOTICE

A portion of the disclosure of this patent application may contain material that is subject to copyright protection. The owner has no objection to the facsimile reproduction of any one of the patent documents or the patent disclosure as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyrights whatsoever. Certain marks referenced herein may be common law or registered trademarks of third parties affiliated or unaffiliated with the applicant or the assignee. Use of these marks is by way of example and shall not be construed as descriptive or to limit the scope of this invention to material associated only with such marks.

BACKGROUND OF THE INVENTION

The demand for social networking on the internet has resulted in an exponentially expanding number of social internet websites, applications, and other social network media. Internet websites such as FACEBOOK®, TWITTER®, and MYSPACE® have experienced rapid expansion as users attempt to post and share much of their lives and experiences online. In addition, online commerce shopping sites such as Amazon and EBay are now dominant entities in the field of online and mainstream commerce.

While the explosion of social media has allowed people to be connected on the internet more than ever before, browsing the internet has remained a largely solitary experience. Users of social media websites or applications communicate by taking turns, posting information rather than communicating with one another in real time. While real time internet communication methods such as internet telephone, video conferencing and chat rooms do exist, usage of these methodologies is limited by the applications or platforms that support them. For instance, chat software allows users to send messages back and forth, but users are typically limited to this simple exchange within the confines of that technology.

There exists a wealth of internet experiences that cannot be easily and effectively shared, viewed, or fully interacted with in real time by all of the parties who are or would like to share that content. Activities such as viewing pictures, watching video, or engaging in internet shopping cannot currently be experienced in a simple, real time, and fully interactive method that enables two or more users who are connected on separate devices to all interact with and

discuss that content simultaneously without having to take turns passing controls. In addition, there is no modality that enables all of the two or more users engaged in a synchronized or shared browsing session to (1) click on web links which open in new non-shared tabs, (2) log into and register at certain web sites separately, and/or (3) input form data or other information at the site or application in a simultaneous or nearly simultaneous manner. As such, the current art lacks technology that would simultaneously connect two or more users in a medium that would allow all of them to both interact with one another and with the content itself in real time and in a synchronized or shared fashion.

Despite the obvious demand for socialization on the internet and despite the desire of many users to utilize the web to view online content with others in real-time, there is no effective, fully interactive modality that enables a group of users to view and interact with internet content and media simultaneously with others on different computers or other connected devices with all of those users empowered to interact with that content in real-time on a simultaneous basis. Furthermore, there is no such modality that allows all users in a shared session to simultaneously log in or register into a certain web site, application, or experience with either or all of (1) their own credentials; (2) credentials passed to them by the host; (3) or with no log in credentials whatsoever. While some current methods such as "desktop or screen sharing" allow users to simply view the same internet content, these methods do not enable all users in a session to click, input, and log into those experiences in a simultaneous or nearly simultaneous manner. Furthermore, these methods are also less appealing because they work by broadcasting continuous screenshots of the host screen in large files or packets and require high levels of bandwidth and computer processing power. As a result of their high bandwidth and processing power requirements, current methods such as desktop sharing are inadequate for enabling larger groups to all view and fully interact with that interactive content in a simultaneous manner. Finally, current methods such as "desktop or screen sharing" afford little protection for the broadcasting host's private information since all participants in a particular session see the host screen as s/he enters sensitive information such as user names or passwords or when the host toggles back and forth in other areas on their desktop.

There is a need in the art for an internet enabled collaboration, online commerce, and social networking innovation that facilitates real time sharing of a more complete internet experience. Specifically, there is a need for a device that allows all users in a session to interact with, discuss, log in separately or together, and share internet browsing in real time for online activities such as shopping together, booking travel together, watching or listening to media together, and browsing the internet together in a simultaneous fashion from different devices and/or locations. It is to these ends that the present invention has been developed.

SUMMARY OF THE INVENTION

To minimize the limitations in the prior art and other limitations that will be apparent upon reading and understanding the present specification, the present invention describes a method for establishing a synchronized browsing session, comprising sending a request to establish the synchronized browsing session to a synchronization server, receiving a confirmation message from the synchronization server including a session identifier associated with the established synchronized browsing session, and sending an

invitation to an invitee to join the synchronized browsing session, wherein the invitation includes the session identifier.

The present invention further describes an apparatus for establishing a synchronized browsing session, comprising a network interface adapted to communicate with a synchronization server, and a processor adapted to send a request to establish the synchronized browsing session to the synchronization server via the network interface, receive a confirmation message from the synchronization server via the network interface, wherein the confirmation message includes a session identifier associated with the established synchronized browsing session, and send an invitation to an invitee to join the synchronized browsing session, wherein the invitation includes the session identifier.

The present invention further describes a method for implementing a synchronized browsing session, comprising recording a shared web browsing interaction, and transmitting information related to the shared web browsing interaction to a synchronization server.

The present invention further describes an apparatus for implementing a synchronized browsing session, comprising a network interface adapted to communicate with a synchronization server, and a processor adapted to record a shared web browsing interaction and transmit information related to the shared web browsing interaction to the synchronization server via the network interface.

It is an objective of the present invention to enhance social and personal internet communication and commercial and non-commercial activity by enabling users to invite and interact with one another while browsing the internet together in real time. As a result and as an illustrative list only, synchronized online activities such as shopping together, booking travel together, watching media together, and browsing the internet together in real time from different devices and/or locations will be supported for all participants in a simultaneous or nearly simultaneous fashion.

It is another objective of the present invention to enable users to communicate via (1) voice; (2) chat; (3) video conferencing; and (4) desktop sharing (via a small browser frame on each participant's screen that monitors the host path) as they browse the internet together in real time.

It is another objective of the present invention to enable users to detect when their friends or other designated users are connected to the internet or when they are logged into certain chat and specialty sites such as FACEBOOK®, GMAIL®, or YAHOO MESSENGER® in order to simplify and streamline the invitation process into a synchronized browsing session and to allow session participants or users of the invention to chat with friends who are not currently within the synchronized browsing session.

Finally, it is yet another objective of the present invention to provide a social networking, lead/visitor generation, promotional, and online commerce device that internet sites, virtual worlds, games and applications can use to increase their value, viewership, or purchasing or activity oriented conversion rates as a result of real-time referrals by current visitors to those sites or applications to invitees who may share common demographics, friendships, and/or affinities for that site's content or offerings.

These and other advantages and features of the present invention are described herein with specificity so as to make the present invention understandable to one of ordinary skill in the art.

BRIEF DESCRIPTION OF THE DRAWINGS

Elements in the figures have not necessarily been drawn to scale in order to enhance their clarity and improve understanding of these various elements and embodiments of the invention. Furthermore, elements that are known to be common and well understood to those in the industry are not depicted in order to provide a clear view of the various embodiments of the invention.

FIG. **1**(*a*) illustrates a block diagram of the components of an exemplary embodiment of the present invention for initializing and conducting a synchronized browsing session.

FIG. **1**(*b*) illustrates a screen shot of an exemplary embodiment of the synchronized browsing software during a synchronized browsing session.

FIG. **1**(*c*) illustrates a block diagram of the components of an exemplary leading device.

FIG. **1**(*d*) illustrates a block diagram of the components of an exemplary following device.

FIG. **1**(*e*) illustrates a block diagram of the components of an exemplary synchronization server.

FIG. **2**(*a*) illustrates a block diagram of exemplary data communication transferred between exemplary components of the present invention to initialize a synchronized browsing session.

FIG. **2**(*b*) illustrates a flow chart of a method utilized by a host device for the initialization of a synchronized browsing session.

FIG. **2**(*c*) illustrates an exemplary embodiment of the visual output on a host device of a third party website including a synchronization session activation hyperlink.

FIG. **3** illustrates a flow chart of a method utilized by a synchronization server for the initialization of a synchronized browsing session

FIG. **4**(*a*) illustrates a flow chart of a method utilized by an invited device for the acceptance and joining of a synchronized browsing session.

FIG. **4**(*b*) illustrates an exemplary embodiment of the visual output on an invited device for the acceptance of a synchronized browsing session invitation message through an email.

FIG. **4**(*c*) illustrates an exemplary embodiment of the visual output on an invited device for the acceptance of a synchronized browsing session invitation message through a social networking website.

FIG. **4**(*d*) illustrates an exemplary embodiment of the visual output on an invited device for the acceptance of a synchronized browsing session invitation message through a micro-blogging website.

FIG. **4**(*e*) illustrates an exemplary embodiment of the visual output on an invited device for the acceptance of a synchronized browsing session invitation message through a news feed website.

FIG. **5**(*a*) illustrates a block diagram of exemplary data communication transferred between exemplary components of the present invention during a synchronized browsing session.

FIG. **5**(*b*) illustrates a flow chart of a method utilized by a host device for the execution of a synchronized browsing session.

FIG. **5**(*c*) illustrates a flow chart of a method utilized by a synchronization server for the execution of a synchronized browsing session between a host device and one or more guest devices.

FIG. **5**(*d*) illustrates a flow chart of a method utilized by a guest device for the execution of a synchronized browsing session with a host device.

FIG. **6**(*a*) illustrates a flow chart of a method for the utilization of tabbed browsing within a synchronized browsing session by a host device.

FIG. **6**(*b*) illustrates a flow chart of a method for the utilization of tabbed browsing by a guest device within a synchronized browsing session.

FIG. **7**(*a*) illustrates a screen shot of an exemplary embodiment of synchronized browsing software being run on a host device.

FIG. **7**(*b*) illustrates an exemplary embodiment of synchronized browsing software on a host device highlighting an expanded browse menu.

DETAILED DESCRIPTION OF THE DRAWINGS

In the following discussion that addresses a number of embodiments and applications of the present invention, reference is made to the accompanying drawings that form a part hereof; these depictions are made by way of illustration and of specific embodiments in which the invention may be practiced. It is to be understood that other embodiments may be utilized and changes may be made without departing from the scope of the present invention.

The present invention allows two or more persons browsing the internet to share their internet browsing experience and have all users simultaneously browse and fully interact with web sites, games, virtual worlds, or other online applications in real time. To share their internet browsing experience, the present invention utilizes the passing of certain data such as URL information, form data, scripts (including java script), cookies, or other types of data information between browser clients. In a synchronized browsing session, two or more people may read the same article, watch the same video, or shop for the same item automatically, without the hassle of coordinating user input. Furthermore, utilization of the present invention does not materially impose more bandwidth or processing power requirements than simply browsing the internet using standard, conventional methods.

In the current art, should two or more people, on different devices, attempt to book an airline flight through an internet website, each person would be separately required to input identical information such as destination, date of departure, or date of arrival into their respective browser. Coordination of such data input is often difficult to accomplish and input errors can lead to conflicting search results. In a synchronized browsing session utilizing the present invention, however, such data input is automatically formatted, forwarded and inputted into the other devices, thereby allowing all persons to view, book, and alter the same flight results. Further activities may include, but are not limited to, enabling session attendees to shop, book travel, view or listen to media, chat, audio and video conference, screen share, screen draw, stay connected to contacts in order to send invites and chat with those not currently in the experience, detect online friends, and otherwise browse and fully interact in a shared browsing experience. As such, utilization of the present invention facilitates the initialization and implementation of a synchronized browsing session between two or more internet users, thereby allowing all of them to view and fully interact with the same internet content without the hassle of coordinated user input. For purposes of this discussion, the term, "fully interact with" may comprise, but is not limited to: (1) logging into or registering at certain sites or applications; (2) filling in form data; (3) performing multiple queries; (4) having following participants click on links that open in new non-shared tabs; (5) playing online games; (6) visiting virtual worlds; or (7) "drawing" on the screen and simultaneously transmitting those figures, annotations, or markups to other users in the session.

FIG. **1**(*a*) illustrates a block diagram of the components of an exemplary embodiment of the present invention for initializing and conducting a synchronized browsing session. FIG. **1**(*a*) illustrates host device **10**, internet **11**, website server **12**, synchronization server **13**, and exemplary guest devices **14** and **15**. In exemplary embodiments of the present invention, host device **10** may establish a synchronized browsing session with guest devices **14** and **15** via synchronization server **13**. In an exemplary synchronized browsing session, host device **10** may forward website interaction information with website server **12** to synchronization server **13**, which may relay the website interaction information to guest devices **14** and **15** for the recital of a synchronized browsing session.

Host device **10** is a component of the present invention that may initialize and conduct a synchronized browsing session with guest device **14** via synchronization server **13**. In an exemplary embodiment of the present invention, host device **10** may comprise a personal computer, mobile phone, Smartphone, IPAD®, or other type of electronic device with a visual user interface and a network connection such that a user may access and view a third party website such as one provided by website server **12** over internet **11**.

Guest devices **14** and **15** are components of the present invention that may join a synchronized browsing session to view internet browsing conducted by host device **10** via relay communication over synchronization server **13**. Like host device **10**, guest devices **14** and **15** may comprise a personal computer, mobile phone, Smartphone, IPAD®, or other type of electronic device with a visual user interface and a network connection such that a user may access and view an internet website such as one provided by website server **12** over internet **11**.

During a synchronized browsing session, data communications sent by host device **10** to website server **12** is forwarded to synchronization server **13** in order to provide for synchronized browsing with guest devices **14** and **15**. In exemplary embodiments of the present invention, prior to relaying the data communications to guest devices **14** and **15**, synchronization server **13** may analyze the data communications received from host device **10**, see FIG. **1**(*e*) and later discussion, to determine if there is an advertising partnership or other monetization deal ("advertising deal"), such as those related to revenue sharing, lead origination, affiliation, cost per action, cost per click, or cost per impression, with the website hosted on website server **12**. If an advertising deal exists with the website hosted on website server **12**, synchronization server **13** will then update the data communication for relay to guest devices **14** and **15**, and transmit an updated data communication back to host device **10**. This process will be discussed in more detail within FIG. **1**(*e*) and FIG. **5**(*d*).

Synchronization server **13** may then forward the data communication to guest devices **14** and **15**. In an exemplary embodiment of a synchronized browsing session, once data communication is forwarded to guest devices **14** and **15** from host device **10** via synchronization server **13**, guest devices **14** and **15** will transmit the same data communication to website server **12**, such that the communication sent is identical to communication sent to website server **12** by host device **10**. As such, guest devices **14** and **15** should receive the same or similar data response from website server **12** as that received by host device **10** from website server **12**.

In alternative embodiments of the present invention, a synchronized browsing session may be conducted by more than one device. In such embodiments, webpage interactions performed by any controlling party will be forwarded to the other attendees in the synchronized browsing session. As such, a leading device, such as host device **10**, may be defined as a device that possesses control within the synchronized browsing session, wherein webpage interactions performed by the leading device within shared browsing window **17** are forwarded to synchronization server **13**. In yet other embodiments of the present invention, control within the synchronized browsing session may be passed from one attending device to another.

A following device, such as guest device **14**, may be defined as any device that receives relayed webpage interactions from synchronization server **13**. In exemplary embodiments, relayed webpage interactions may include data such as URL, form data, scripts, advertising codes, or other information. A following device that does not possess leading device control within the synchronized browsing session may not forward or relay webpage interactions to synchronization server **13** unless the ability to do so is conferred upon the following device by a leading device or other authoritative party for either a full session or for a certain period of time.

In such various embodiments, a device in a synchronized browsing session may possess leading, following, or both leading and following characteristics. For example, in an embodiment wherein both host device **10** and guest device **14** are both leading and following devices, any webpage interaction performed by guest device **14** within the shared browsing window will be relayed to host device **10**, and any webpage interaction performed by host device **10** within the shared browsing window will be relayed to guest device **14**. In such an embodiment, any relayed webpage interactions will necessitate webpage requests to be sent to a webpage server, such as website server **12**.

FIG. **1**(*b*) illustrates a screen shot of an exemplary embodiment of the synchronized browsing software during a synchronized browsing session. FIG. **1**(*b*) illustrates the visual output of host device **10** running synchronized browsing software **16**, wherein synchronized browsing software **16** comprises shared browsing window **17** and shared browsing tab **18**. In an exemplary synchronized browsing session, the visual and audio output of shared browsing window **17** on a following device, such as guest device **14**, will be similar, if not identical, to the visual and audio output of shared browsing window **17** on a leading device, such as host device **10**.

In exemplary embodiments, synchronized browsing software **16** is designed to run on a computer or other electronic device, such as host device **10** or guest device **14**, in order for the user of the device to participate in a synchronized browsing session. Synchronized browsing software **16** may incorporate internet browsing software functionality on the existing device, such as INTERNET EXPLORER®, SAFARI®, CHROME®, FIREFOX®, or WEBKIT® to browse the internet. In such embodiments, synchronized browsing software **16** may integrate the native browser control components of commonly used web browsers such as INTERNET EXPLORER® into the software user interface for PC computers, or may integrate the native browser control components of the SAFARI® or WEBKIT® web browsers for the software user interface on APPLE® or MAC® computers. Some or all of these components may be pre-installed on the PC and APPLE® computers, respectively.

In other embodiments of the present invention, synchronized browsing software **16** may comprise an add-on or plug-in to commonly used internet browsing software such as INTERNET EXPLORER®, FIREFOX®, CHROME® or SAFARI®. In further embodiments, synchronized browsing software **16** may comprise independent functionality to browse the internet.

Shared browsing window **17** is an element of synchronized browsing software **16** wherein the webpage interactions of host device **10**, or other leading device, are relayed to following devices in the synchronized browsing session, such as guest device **14**. In exemplary embodiments, the audio and visual output of shared browsing window **17** may be similar or identical on both leading and following devices. Alternatively, if one or more users have already registered with a particular site or application and certain personalization settings are triggered, that particular user will receive a similar data response that also includes the output of the personalized settings that were set by that particular user.

In exemplary usage of the present invention, the user of guest device **14** views the same display of internet content as that displayed to the user of host device **10**. In alternative embodiments, the user of guest device **14** may view similar internet content as that displayed to user of host device **10**, with slight modifications due to personalization settings that may be triggered for the user of guest device **14** at that site or application due to prior, recent, or simultaneous website registration. In situations where screen size or screen resolution of guest device **14** is different than that of host device **10**, the user of guest device **14** should view a similar display of internet content as what is displayed to host device **10**, with modifications due to screen size and resolution.

Shared browsing tab **18** is a browsing tab identifier and extension of shared browsing window **17**. In exemplary usage, a user of synchronized browsing software **16** may click on shared browsing tab **18** in order to switch from another window into shared browsing window **17**. Clicking unshared browsing tab **70** may switch a user from shared browsing window **17** into an unshared browsing window.

In exemplary embodiments of the present invention, a variety of internet content and media may be shared between attendees of a synchronized browsing session. Textual articles, images, music, streaming video, e-commerce sites, games, documents for review or download, or any form of web-based content may be activated by a leading device, to be relayed by synchronization server **13**, and on to following devices within the synchronized browsing session.

In alternative embodiments, synchronized browsing software **16** may provide or integrate desktop sharing functionality, wherein following devices may view the screen of a leading device. For example, if host device **10**, the sole leading device, enabled desktop sharing, guest device **14**, a following device, would be able to see the screen of host device **10**, or a portion thereof. In other embodiments, desktop sharing may be enabled in small windows that may occupy or overlay upon a portion of shared browsing window **17**.

FIG. **1**(*c*) illustrates a block diagram of the components of an exemplary leading device. FIG. **1**(*c*) illustrates host device **10**, comprising processor **20**, network interface **21**, memory **22** and user interface **23**. Host device **10** is designed to initialize and conduct a synchronized browsing session with guest device **14** via synchronization server **13**

Processor **20** is a component of host device **10** adapted to perform and process web page interactions and communi-

cations with synchronization server **13** in order to initialize and host a synchronized browsing session.

Network interface **21** is a component of host device **10** designed to transmit and receive data communication with external electronic devices. In exemplary embodiments of the present invention, processor **20** may utilize network interface **21** to perform web page interactions, such as with website server **12**, and to communicate with synchronization server **13**.

Host device **10** may also utilize memory **22** and user interface **23**. Memory **22** may be adapted to store one or more software modules for controlling processor **20**. Alternatively, memory **22** may be adapted to store one or more software modules for output via user interface **23**. User interface **23** may be adapted to receive a user input for initiation of processor **20**, prompting data communication via network interface **21**. In other embodiments, webpage interactions may be outputted to the user of host device **10** via user interface **23**.

FIG. **1**(*d*) illustrates a block diagram of the components of an exemplary following device. FIG. **1**(*d*) illustrates guest device **14**, comprising processor **24**, network interface **25**, memory **26** and user interface **27**. Guest device **14** is designed to join and implement a synchronized browsing session.

Processor **24** is a component of guest device **14** that may utilize network interface **25**, memory **26** and user interface **27** to join and implement a synchronized browsing session with host device **10**. In exemplary embodiments, processor **24** may utilize network interface **25** to receive and transmit communication with synchronization server **13**. Processor **24** may also utilize network interface **25** to perform webpage interactions, such as transmit requests to website server **12**.

Guest device **14** may also utilize memory **26** and user interface **27**. Memory **26** may be adapted to store one or more software modules for controlling processor **24**, or for the output of webpage interactions via user interface **27**. User interface **27** may be adapted to output webpage interactions to the user of guest device **14** via user interface **27**. Alternatively, user interface **27** may be adapted to receive user input for initiation of processor **24**, prompting data communication via network interface **25**.

FIG. **1**(*e*) illustrates a block diagram of the components of an exemplary synchronization server. FIG. **1**(*e*) illustrates synchronization server **13**, comprising processor **28**, network interface **29**, session identification database **30**, and affiliate database **31**. Synchronization server **13** is designed to establish and facilitate a synchronized browsing session between host device **10** and guest device **14**.

Processor **28** is a component of synchronization server **13** that may utilize network interface **29**, session identification database **30** and affiliate database **31** in order to establish and facilitate a synchronized browsing session between host device **10** and guest device **14**. In exemplary embodiments, network interface **29** may both transmit and receive communication from host device **10** and guest devices, such as guest device **14**.

Session identification database **30** may be utilized by processor **28** for the storage of information related to the establishment and facilitation of a synchronized browsing session, which may include a synchronized browsing session identifier **19**, to be described later, routing information related to a lead device such as host device **10**, or routing information related to one or more of the following devices, such as guest device **14**. In exemplary embodiments of the present invention, should synchronization server **13** receive a request to establish a synchronized browsing session from host device **10**, processor **28** may assign the synchronized browsing session a unique session identifier, referred to as synchronized browsing session identifier **19**, and store identification information for host device **10**, along with session identifier **19**, within session identification database **30**.

In an exemplary embodiment, when synchronization server **13** receives website interaction information during synchronized browsing session from host device **10** via network interface **29**, processor **28** may utilize affiliate database **31** to determine if an affiliation, advertising or partnership agreement exists with the website hosted by website server **12**. For example, should website information sent from host device **10** include a URL comprising http://www.uspto.gov, processor **28** may determine if a partnership exists with said website by searching affiliate database **31**.

If processor **28** determines that a partnership exists, processor **28** may update the webpage interaction information and utilize network interface **29** to relay the updated website interaction information to host device **10** and guest device **14**. In alternative embodiments, network interface **29** may only transmit an adcode, cookies, scripts, XML, or other unique identifier signifying the website affiliation to host device **10**. If processor **28** determines that a partnership does not exist with the website hosted by website server **12**, then no update or update transmission is necessary.

FIG. **2**(*a*) illustrates a block diagram of exemplary data communication transferred between components of the present invention to initialize a synchronized browsing session. FIG. **2**(*a*) shows host device **10**, synchronization server **13** and guest device **14** transmitting data communication to initialize a synchronized browsing session between host device **10** and guest device **14**.

To initialize a synchronized browsing session, host device **10** transmits initialization request **40** to synchronization server **13**. In response to initialization request **40**, synchronization server **13** may transmit confirmation message **41** to host device **10**, including session identifier **19** (not shown). In exemplary embodiments, session identifier **19** may comprise an identification number, passkey, URL, MAC address, or other unique indicator such that the synchronized browsing session may be identified for joining the session.

Once the synchronized browsing session is established and session identifier **19** is transferred to host device **10**, host device **10** may transmit session invitation **42** to prospective guest devices, such as guest device **14**. In other embodiments of the present invention, other session attendees may transmit session invitation **42** to additional prospective guests. Session invitation **42**, to be described in detail below for discussion of FIG. **2**(*b*), may comprise an invitation hyperlink **52** (to be described and illustrated in FIGS. **4**(*a*)-**4**(*e*)) and session identifier **19**.

Should the user of guest device **14** decide to join the synchronized browsing session hosted by host device **10**, guest device **14** transmits request to join **43** to synchronization server **13**. Request to join **43** is a data communication sent to synchronization server **13** by a prospective guest device that comprises session identifier **19**.

After synchronization server **13** receives request to join **43** from guest device **14**, synchronization server **13** records identification and routing information of guest device **14**, such as IP address, MAC address, or other unique identifiers, in order to relay information in the synchronized browsing session to guest device **14**. In exemplary embodiments, synchronization server **13** may then transmit notification **44** to host device **10**, informing host device **10** that guest device **14** has joined the synchronized browsing session.

FIG. **2**(*b*) illustrates a flow chart of method **100** utilized by host device **10** for the initialization of a synchronized browsing session after the activation of a third party hyperlink from a website hosted by website server **12**. Method **100** is utilized by host device **10** to initialize a synchronized browsing session with guest device **14** through synchronization server **13**. Method **100** is explained in the order shown in FIG. **2**(*b*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention. Additionally, alternative embodiments of the present invention may not require the software download and acceptance process.

In step **101**, host device **10** activates activation hyperlink **51**, illustrated in FIG. **2**(*c*), from a website hosted by website server **12**. In step **102**, host device **10**, in response to the activation of activation hyperlink **51**, attempts to detect if synchronized browsing software **16** is installed or ready to launch or run on host device **10**. If the synchronized browsing software **16** is not detected on host device **10**, host device **10** proceeds to step **103**. If, however, synchronized browsing software **16** is detected, host device **10** proceeds to step **104**.

In step **103**, host device **10** sends a communication to synchronization server **13** requesting to download synchronized browsing software **16**. In exemplary embodiments, synchronization server **13** transmits synchronized browsing software **16** to host device **10**. In embodiments wherein synchronized browsing software **16** need to be installed in order for the software to run, host device **10**, upon complete reception of the software, installs synchronized browsing software **16**. Once the software is installed, host device **10** proceeds to step **104**. In embodiments wherein synchronized browsing software **16** does not need to be installed, once the download is completed, host device **10** proceeds to step **104**.

In step **104**, host device **10** launches synchronized browsing software **16**. In embodiments of the present invention wherein synchronized browsing software **16** comprises an add-on or plug-in to commonly used internet browsing software, then the add-on or plug-in is initialized.

In alternative embodiments of the present invention, a user of host device **10** may launch synchronized browsing software **16** directly, without the activation of activation hyperlink **51**. In such embodiments, once the software is activated or launched, host device **10** begins at step **105**. In such situations where host device **10** does not activate activation hyperlink **51**, but host device **10** does not have synchronized browsing software **16** installed or ready to launch, host device **10** may contact synchronization server **13** and begin the process at step **103**.

In step **105**, host device **10** sends initialization request **40** to synchronization server **13**. In step **106**, host device **13** receives confirmation message **41** from synchronization server **13**, indicating that a synchronized browsing session has been established. In exemplary embodiments, confirmation message **41** transmitted to host device **10** comprises session identifier **19**.

In step **107**, host device **10** sends session invitation **42** to one or more prospective guests, such as guest device **14**, to join the synchronized browsing session. In exemplary embodiments, session invitation **42** may comprise session identifier **19**, and invitation hyperlink **52** to join the synchronized browsing session. The prospective guests need to simply click invitation hyperlink **52** included in session invitation **42** to join the synchronized browsing session. In other embodiments, session invitation **42** may also comprise an image or message from the user of host device **10** to the user of the prospective guest device.

In exemplary embodiments of the present invention, session invitation **42** to join a synchronized browsing session may be sent to, or received by, a prospective guest device, such as guest device **14**, in numerous ways. In one embodiment, session invitation **42** may be set by host device **10** to prospective guests via an email message. In another embodiment of the present invention, session invitation **42** may be sent to prospective guests via an instant message communication. In yet other embodiments of the present invention, session invitation **42** may be sent to prospective guests via a social networking communication. Exemplary methods of sending session invitation **42** are illustrated and in FIGS. **4**(*b*)-**4**(*e*).

Alternatively, session invitation **42** may be displayed publicly or semi-privately on a website for viewers to click or activate. In such embodiments, session invitation **42** is not sent to one or more designated prospective guests, but rather is publicly displayed on a website so that anyone who views the invitation can activate it to enter into the synchronized browsing session. For example, should the user of host device **10** "tweet" an invitation to join a synchronized browsing session through the social communication website TWITTER®, any reader may accept the invitation by clicking on the shared hyperlink. In other embodiments, a user of host device **10** may post a public invitation through FACEBOOK®, GOOGLE® BUZZ, a website newsfeed, or as a hyperlink on a website, game, virtual world, or other application, in order to issue an open invitation to certain friends or the public to join their synchronized browsing session.

Finally, in step **108**, host device **10** receives notification message **44** from synchronization server **13** that one or more guest devices have joined the synchronized browsing session. In an exemplary embodiment, host device **10** receives notification message **44** for each guest device, such as guest device **14**, that has joined the synchronized browsing session. In such an embodiment, notification message **44** may comprise a visual, audio, or textual output through host device **10**. In yet other embodiments of the present invention, host device **10** may receive notification message **44** for only the first guest device that has joined the synchronized browsing session. Alternatively, host device **10** may receive notification message **44** for only designated guest devices that have joined the synchronized browsing session, such as those that have been made a priority, friends, or by some other means of designation.

FIG. **2**(*c*) illustrates an exemplary embodiment of the visual output on host device **10** of a third party website including activation hyperlink **51**. FIG. **2**(*c*) illustrates third party website **50**, comprising activation hyperlink **51**.

Third party website **50** is an exemplary internet website or application comprising activation hyperlink **51**. In the present embodiment, third party website **50** is an exemplary publication mechanism for delivering activation hyperlink **51** to a public audience. However, other methods of publication of activation hyperlink **51** are available, and discussion of these embodiments should in no way limit the interpretation or scope of the present invention.

Third party website **50** allows for a user of host device **10** to initiate a synchronized browsing session by clicking activation hyperlink **51**. For example, the publisher of third party website **50** may decide to publish activation hyperlink **51** to increase viewership of their website, because activation hyperlink **51** allows for the initiation of a synchronized browsing session, which may bring increased, higher converting, and more targeted web viewers to third party website **50**.

Activation hyperlink **51** is a website or application hyperlink designed to facilitate the initiation process for a synchronized browsing session hosted by host device **10**. When activation hyperlink **51** is clicked or activated by host device **10**, as described in step **101** and illustrated in FIG. **2**(*b*), host device **10** attempts to detect if synchronized browsing software **16** is installed or ready to launch on host device **10**. In alternative embodiments of the present invention, software download and installation may not be required. After hyperlink **51** is activated, host device **10** then performs the remainder of the steps in method **100**.

FIG. **3** illustrates a flow chart of method **200** utilized by synchronization server **13** for the initialization of a synchronized browsing session. Method **200** is utilized by synchronization server **13** to initialize a synchronized browsing session between host device **10** and guest device **14**. Method **200** is explained in the order shown in FIG. **3**; however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In step **201**, synchronization server **13** receives initialization request **40** from host device **10**, as previously discussed and illustrated in FIGS. **2**(*a*) and **2**(*b*). In step **202**, synchronization server **13** establishes a synchronized browsing session, hosted by host device **10**, and generates session identifier **19**. In step **203**, synchronization server **13** records session identifier **19** and the routing information of host device **10** within session identification database **30**.

In step **204**, synchronization server **13** transmits confirmation message **41** to host device **10**, confirming the establishment of the synchronized browsing session, wherein confirmation message **41** includes the transmittal of session identifier **19** to host device **10**.

In step **205**, synchronization server **13** may receive request to join **43** from a prospective guest device, such as guest device **14**. In exemplary embodiments, request to join **43** comprises a data communication requesting to join the synchronized browsing session, wherein the communication includes session identifier **19**. In step **206**, in response to receiving request to join **43**, synchronization server **13** records the routing and identification information of guest device **14** within session identification database **30** in association with session identifier **19**, such that synchronization server **13** may later relay synchronized browsing information sent from host device **10** to guest device **14**.

In steps **207** and **208**, synchronization server **13** generates and transmits notification **44** to host device **10**, wherein notification **44** comprises a confirmation message that guest device **19** has joined the synchronized browsing session. In exemplary embodiments, notification **44** comprises the identification information of guest device **19**.

FIG. **4**(*a*) illustrates a flow chart of method **300** utilized by invited, prospective, and guest devices for the acceptance and joining of a synchronized browsing session. Method **300** is utilized by a device, such as guest device **14**, to accept and join a synchronized browsing session by activating invitation hyperlink **52** (illustrated in FIGS. **4**(*b*)-**4**(*e*)). Method **300** is explained in the order shown in FIG. **4**(*a*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In step **301**, guest device **14** receives session invitation **42**, comprising invitation hyperlink **52** and session identifier **19**. Session invitation **42**, as illustrated in FIGS. **4**(*b*)-**4**(*e*), may comprise, but is not limited to, data communication, such as email, instant message or text, SMS, or a public or private internet posting, such as through social networking, applications, blogs, virtual world, game or news feeds.

In step **302**, guest device **14** activates invitation hyperlink **52**. In step **303**, guest device **14** detects if synchronized browsing software **16** is installed or ready to launch on guest device **14**. In an exemplary embodiment, activation of invitation hyperlink **52** prompts guest device **14** to detect if synchronized browsing software **16** is present and capable of being run. If synchronized browsing software **16** is not installed or ready to launch on guest device **14**, guest device **14** proceeds to step **304**. If, however, synchronized browsing software **16** is installed or ready to launch on guest device **14**, guest device **14** proceeds to step **305**. Further, in embodiments wherein synchronized browsing software **16** is not required to participate in a synchronized browsing session, guest device **14** proceeds to step **306**.

In step **304**, guest device **14** transmits a request to download synchronized browsing software **16** to synchronization server **13**. Once guest device **14** has downloaded synchronized browsing software **16** and the software is ready to launch, guest device **14** proceeds to step **305**. In step **305**, guest device **14** runs or launches synchronized browsing software **16**. Finally, in step **306**, guest device **14** transmits request to join **43** to synchronization server **13**, including session identifier **19**.

FIGS. **4**(*b*)-**4**(*e*) illustrate various embodiments of the visual output of an invited, prospective, and/or guest device, such as guest device **14**, which has received session invitation **42**. FIG. **4**(*b*) illustrates an exemplary embodiment of the visual output on guest device **14** of email message **53**, comprising invitation hyperlink **52**. FIG. **4**(*c*) illustrates an exemplary embodiment of the visual output on guest device **14** of social networking website **54**, comprising invitation hyperlink **52**. FIG. **4**(*d*) illustrates an exemplary embodiment of the visual output on guest device **14** of micro-blogging website **55**, comprising invitation hyperlink **52**. Finally, FIG. **4**(*e*) illustrates an exemplary embodiment of the visual output on guest device **14** of news feed website **56**, comprising invitation hyperlink **52**.

Invitation hyperlink **52** is a component of session invitation **42**, transmitted from host device **10** to guest device **14**, via a method such as those illustrated in, but not limited to, FIGS. **4**(*b*)-**4**(*e*). In exemplary embodiments, invitation hyperlink **52** comprises a URL address that contains an embedded session ID, such as session identifier **19**, for the designated synchronized browsing session. Activation of invitation hyperlink **52** prompts guest device **14** to join the synchronized browsing session, as previously described for FIG. **4**(*a*). In exemplary embodiments of the present invention, activation of invitation hyperlink **52** prompts guest device **14** to launch synchronized browsing software **16**. If synchronized browsing software **16** is not installed or ready to launch on guest device **14**, activation of invitation hyperlink **52** first prompts guest device **14** to download and launch the software, if such a download is necessary to participate in a synchronized browsing session.

Email message **53**, social networking website **54**, micro-blogging website **55**, and news feed website **56** are various embodiments of means to deliver invitation hyperlink **52** to guest device **14**. Email message **53**, or in alternative embodiments an instant message, text message, or other form of direct communication, may be sent directly from host device **10** to guest device **14**. Alternatively, social networking website **54**, micro-blogging website **55** and news feed website **56** allow for prospective guests to join a synchronized browsing session of their friends or people they read or follow, should that person post invitation hyperlink **52**.

Alternatively, news feed website **56** may comprise a list of invitation hyperlinks **52** for live synchronized browsing sessions that are open to the public, such that a prospective guest may browse the list and join a desired session.

Publicly shared synchronized browsing sessions, such as those that may be linked from news feed website **56**, may be open to large groups of people. For example, in an exemplary embodiment where a public figure or other famous person is leading a synchronized browsing session, thousands of their fans may join into the synchronized browsing session, wherein the public figure or a person designated by that figure or their staff may lead followers around to the figures' favorite websites with or without a pre-arranged itinerary or script. Alternatively, such publicly shared synchronized browsing sessions may be utilized for marketing purposes, such that the host of the browsing session may lead their followers to a variety of shopping products. In yet other embodiments, publicly shared synchronized browsing sessions may be utilized for fundraisers, nonprofit organizations, religious groups, educational means, or other like functions.

Complementary to publicly shared synchronized browsing sessions wherein webpage content may be shared, discussed, and interacted with among different groups of people, exemplary embodiments of the present invention may promote means for people of similar interests to connect and share media. These publicly shared synchronized browsing sessions may be driven by individual users who set up and host certain public rooms to discuss and fully interact with online content and other users who share certain interests, demographics, backgrounds, orientations, likes, or dislikes. Further, public rooms may be established to allow users to discuss and fully interact with online content and others about upcoming and current events, certain verticals of content, news, or other experiences. For example, an academy awards public room may comprise a place where people may congregate, discuss, and co-browse webpage content related to the awards presentation. Further, there may be a football public room where users discuss and co-browse online content related to college or professional football.

Alternatively, public rooms may be established where people who share an interest in a public figure, movie, political view, or other subject matter may congregate, discuss, and interact with both the online content and each other. In such embodiments, public rooms may be initialized by either an individual host or may be initialized, maintained or hosted by public sponsors, such as consumer products companies. For example, UNILEVER®, who owns the AXE® brand, may start an "AXE® Public Room" wherein people may congregate, discuss, and co-browse material related to AXE® products or consumer interests and subjects related to AXE® products.

In alternative embodiments, the link and browsing history for these publicly shared sessions, or single user browsing sessions, in general, may be recorded and made available both publicly or privately to users of the present invention. As such, users may view the link histories or favorites lists of other users so that they are enabled to visit one or more of the sites or applications visited in the link history or favorites at a later point in time. For example, if a certain public figure wanted to publish their browsing history or favorites via the invention and other users wanted access to that browsing history or favorites list, the invention would enable these users to view both the lists and to activate those sites directly. In either case, the sites would be similarly complemented with certain adcodes or other identifiers that would track or recognize that particular user back to the holder of that adcode or other identifier once a user visits that site, advertisement, game, virtual world, or application via that link.

FIG. **5**(*a*) illustrates a block diagram of exemplary data communication transferred between components of the present invention during a synchronized browsing session. FIG. **5**(*a*) shows host device **10**, website server **12**, synchronization server **13** and guest device **14** transmitting data communication for a synchronized browsing session.

As previously discussed, host device **10** may initialize and conduct a synchronized browsing session through communication with synchronization server **13**. During a synchronized browsing session, host device **10** may transmit website request **60** to website server **12**. In an exemplary embodiment, website request **60** is a data communication message sent to request webpage content at a designated location, such as website server **12**. For example, website request **60** sent to the United States Patent and Trademark Office ("USPTO") webpage, www.uspto.gov, would comprise a message sent to request website data content at the USPTO's webpage www.uspto.gov.

Typically, in response to website request **60** sent by host device **10**, website server **12** will send website content reply **66** to host device **10**. In exemplary communication, website content reply **66** comprises the website content requested in website request **60**. For example, should website request **60** be sent to www.uspto.gov, website content reply **66** may comprise the data necessary to view the website at www.uspto.gov.

During an exemplary synchronized browsing session, after host device **10** transmits website request **60** to website server **12**, host device **10** transmits communication message **61** to synchronization server **13**. Communication message **61** may comprise the URL address of website server **12**, cookie information, form data, java script, or other user inputted information, or attached files. In alternative embodiments, communication message **61** may further comprise information indicating whether the webpage interaction information is to be relayed to guest device **14**. In such embodiments, synchronization server **13** will not relay the webpage interaction information to guest device **14**.

In response to communication message **61**, synchronization server **13** may transmit reply message **62**. In an exemplary embodiment, reply message **62** may comprise an adcode identification code, adcode, XML, or other unique identifier related to the website of URL address contained in communication message **61**. In other embodiments of the present invention, reply message **62** may comprise a modified URL address, or webpage interaction information.

Affiliation message **63** is a communication sent by synchronization server **13** to website server **12** in order to update website server **12** with the relevant adcode, cookie, script, or other unique identifier related to the existing partnership or affiliation. In an exemplary embodiment of the present invention, synchronization server **13** may transmit affiliation message **63** to website server **12**, wherein affiliation message **63** comprises the routing information of host device **10** and the related adcode or unique identifier, thereby allowing website server **12** to update the browsing session of host device **10**.

Communication message **64** is designed to be forwarded by synchronization server **13** to guests in the synchronized browsing session, such as guest **14**, to perform the synchronized browsing session. In exemplary embodiments, communication message **64** may be a duplicate of website request **60**, or may comprise the URL address of website

server **12**. In other embodiments, communication message **64** may also include other transmitted data from website request **60**, such as cookie information, form data, java script, or other user inputted information, or attached files.

In yet further embodiments of the present invention, communication message **64** may comprise a modified URL address including an adcode or other unique identifier, such that later transmittal to website server **12** may indicate the existence of an affiliation or partnership between the designated web site and synchronization server **13**. In such embodiments, communication message **64** may include an adcode, adcode identification code, XML, or other unique identifier that is similar or identical to the identifier transmitted in reply message **62**.

After host device **10** transmits communication message **61** to synchronization server **13**, synchronization server **13** forwards communication message **64** to guest devices. In the present embodiment illustrated in FIG. **5**(*a*), synchronization server **13** forwards communication message **64** to guest device **14**. Communication message **64** may be used by guest device **14** to formulate website request **65** to be sent from guest device **14** to website server **12**. Website request **65** is a data communication message transmitted by guest device **14** to website server **12**. In exemplary embodiments, website request **65** should be similar or identical to website request **60**.

Form data may be defined as information inputted by a user in pre-defined fields on a webpage that may be transmitted to a website server. Website request **60** may include form data inputted by the user of host device **10**. For example, should the user of host device **10** search a website for hotel vacancies in New York City on a specified date, website request **60** would include form data for data fields such as location, data of travel, number of nights, number of guests, and other query fields. As such, in exemplary embodiments of the present invention, because communication message **61** may be a duplicate of website request **60**, communication message **61** may include the same form data as to that inputted by the user of host device **10** on the hotel reservation website. Form data may also include, but is not limited to, user name, email, password information, search queries, and/or other entry fields that may be inputted by host or guest.

Without the transfer of form data or other types of user input information, should website request **60** sent by host device **10** to website server **12** include any user input, website request **65** may be wholly different than website request **60**. In such embodiments, website content reply **66** may be wholly different than that of website content reply **67**. For example, in an embodiment wherein form data is not relayed by synchronization server **13** to guest device **14**, should host device **10** input hotel reservation information at a hotel or travel website, host device **10** will receive search results relevant to that hotel reservation. Guest device **14**, however, may not receive the same search results because guest device **14** was not forwarded the form data to transfer to the hotel website and, as a result, the received search results may not be based upon the same input information.

In exemplary embodiments, website request **65** is identical to website request **60** such that website content reply **67**, the data content sent by website server **12** in response to website request **65**, is similar or identical to website content reply **66**. As such, in a synchronized browsing session between host device **10** and guest device **14**, audio and visual output of shared browsing window **17** on guest device **14** is similar or identical to that on host device **10** unless personalization settings, such as private cookie information, are triggered for one of the devices on the site.

FIG. **5**(*b*) illustrates a flow chart of method **400** utilized by host device **10** for the execution of a synchronized browsing session. Method **400** is utilized by host device **10** after a synchronized browsing session has been established. Method **400** is explained in the order shown in FIG. **5**(*b*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In step **401**, host device **10** transmits website request **60**, as previously described, to website server **12**. In step **402**, host device **10** transmits communication message **61** to synchronization server **61**. In an exemplary embodiment of the present invention, communication message **61** may comprise the URL of the website requested, such as the URL for website server **12**, form data inputted by the user of host device **10**, java script, or other data. Additionally, communication message **61** may comprise any cookie data communication applicable to web site request **60**.

In step **403**, host device **10** awaits a response from synchronization server **13** regarding affiliation with the website hosted on website server **12**. If host device **10**, via network interface **21**, receives an affiliation identification code from synchronization server **13**, host device **10** proceeds to step **404**. If, however, host device **10** does not receive an affiliation identification code from synchronization server **13**, host device **10** proceeds to step **405**.

In step **404**, host device **10** after receiving an affiliation identification code from synchronization server **13**, host device **10** transmits the affiliation identification code to website server **12**. In exemplary embodiments, the affiliation identification code is used as a unique browsing session identifier for host device **10** while browsing upon website server **12**. In such embodiments, the affiliation identification code may be used to modify the URL address.

In step **405**, host device **10** receives website content reply **66** from website server **12**. Finally, in step **406**, host device **10** outputs webpage content reply **66** via user interface **23** to the user of host device **10** within shared browsing window **17** in synchronized browsing software **16**. In alternative embodiments wherein synchronized browsing software **16** is not required, host device **10** may output webpage content reply **66** via user interface **23** within a standard internet browser, or other compatible browsing software.

FIG. **5**(*c*) illustrates a flow chart of method **500** utilized by synchronization server **13** for the execution of a synchronized browsing session between a host device and one or more guest devices. Method **500** is utilized by synchronization server **13** to facilitate the execution of a synchronized browsing session between host device **10** and guest devices, such as guest device **14**. Method **500** is explained in the order shown in FIG. **5**(*c*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In Step **501**, synchronization server **13** receives communication message **61** from host device **10**. As previously described, communication message **61** includes webpage interaction information, such as a URL address, form data, java script, cookies, or other data communication. In Steps **502** and **503**, synchronization server **13** queries affiliate database **31** to check if the webpage hosted by website server **12** has an affiliation or partnership agreement with synchronized browsing. In exemplary embodiments of the present invention, synchronization server **13** analyzes communication message **61**, identifies the URL address of the webpage contacted by host device **10**, and checks for a

match within affiliate database **31**. In other embodiments, synchronization server **13** may query website server **12** for meta data or other website information for the purposes of determining if the website is an affiliate in the affiliate database **31**.

If an affiliation identification code with the webpage hosted by website server **12** is not found, synchronization server **13** proceeds to step **504**. If, however, an affiliation identification code with the webpage hosted by website server **12** is found within affiliate database **31**, synchronization server **13** proceeds to step **506**.

In step **504**, synchronization server **13** identifies guest devices that have joined the synchronized browsing session, such as guest device **14**. In an exemplary embodiment, synchronization server **13** queries session identification database **30** utilizing session identifier **19**, extracting routing information, or other unique information, for guest devices in the synchronized browsing session. In step **505**, synchronization server **13** transmits communication message **64** to guest device **14**.

In step **506**, synchronization server **13** transmits the affiliation identification code found affiliate database **31** to host device **10**. In step **507**, like in step **504**, synchronization server **13** identifies guest devices that have joined the synchronized browsing session, such as guest device **14**. Finally, in step **508**, synchronization server **13** transmits communication message **64** and the affiliation identification code from affiliate database **31** to guest device **14**. In alternative embodiments, synchronization server **13** may modify communication message **64** to include the affiliation identification code.

FIG. **5**(*d*) illustrates a flow chart of method **600** utilized by guest device **14**, for the execution of a synchronized browsing session with host device **10**. Method **600** is utilized by guest device **14** to facilitate a synchronized browsing session with host device **10**. Method **600** is explained in the order shown in FIG. **5**(*d*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In step **601**, guest device **14** receives communication message **64** from synchronization server **13**, as previously described. In step **602**, guest device **14** transmits website request **65** to website server **12**. As previously described, website request **65** is a data communication message sent to request web content at a designated URL location, such as website server **12**, and is similar or identical to website request **60** sent by host device **10**. Guest device **14** formulates website request **65** by processing communication message **64**. In exemplary embodiments, information in communication message **64**, including URL, form data, cookies or other data, is transmitted in website request **65**.

In step **603**, guest device **14** receives content reply **67** from website server **12**. Finally, in step **604**, guest device **14** outputs content reply **67** via user interface **27** to the user of guest device **14** within shared browsing window **17** in synchronized browsing software **16**. In alternative embodiments wherein synchronized browsing software **16** is not required, guest device **14** may output webpage content reply **67** via user interface **27** within a standard internet browser window or other compatible software. In exemplary embodiments, because website request **65** is similar or identical to website request **60**, audio and visual output of content reply **67** is similar or identical to audio and visual output of content reply **66** unless one or more of the users has already registered with that site and certain personalization settings are triggered for that user at that site in which case the rendered site would also include those settings within the context of the requested site.

FIG. **6**(*a*) illustrates a flow chart of method **700** for the utilization of tabbed browsing within a synchronized browsing session by a leading device, such as host device **10**. Method **700** facilitates unshared browsing in a separate tabbed browsing window during a synchronized browsing session by a leading device. Method **700** is explained in the order shown in FIG. **6**(*a*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In step **701**, the leading device detects a non-shared activation of a hyperlink in shared browser window **17** of synchronized browsing software **16**, or other software capable of performing a synchronized browsing session. In exemplary embodiments of the present invention, shared actions by the leading device within synchronized browsing software **16** prompt the transmission of both website request **60** and communication message **61**, as discussed previously. Non-shared action within the synchronized browsing software **16**, however, prompts the leading device to proceed to step **702**. In exemplary embodiments of the present invention, non-shared activation of hyperlinks in synchronized browsing software **16** may comprise a user click on a unopened or blank non-shared tab, right-click, control-click, "finger or screen" press, or some other form of activation such that the software recognizes the activation as to not be shared with guests in the synchronized browsing session.

In step **702**, the leading device generates an unshared browsing window within synchronized browsing software **16**. In exemplary embodiments, shared browsing window **17** within synchronized browsing software **16** on the leading device remains unaffected, and any activation within shared browsing window **17** prompts the transmission of both website request **60** and communication message **61** for the synchronized browsing session. Once an unshared browsing window is generated, the leading device proceeds to step **703**.

In step **703**, the leading device contacts the requested web site server, such as website server **12**, for the unshared website browsing window. In alternative embodiments of the present invention, the leading device may send communication message **61** to synchronization server **13** for a website affiliation query within affiliation database **31**. In such embodiments, communication message **61** may comprise data, an identifier, or some other information to indicate to synchronization server **13** that the webpage interaction information is not to be relayed to the following devices. As such, in response to communication message **61**, synchronization server **13** may transmit reply message **62** to the leading device, comprising an affiliation identification code or some other recognizable identifier for the affiliated website.

In step **704**, the leading device receives the unshared browsing data. Finally, in step **705**, the leading device outputs the unshared browsing data in the unshared browsing window.

FIG. **6**(*b*) illustrates a flow chart of method **750** for the utilization of tabbed browsing by a following device, such as guest device **14**, within a synchronized browsing session. Method **750** facilitates unshared browsing in a separate tabbed browsing window during a synchronized browsing session by a following device that does not possess leading device control of the synchronized browsing session.

Method **750** is explained in the order shown in FIG. **6**(*b*); however, the following steps may be taken in any other conceivable sequence without deviating from the scope of the present invention.

In step **751**, the following device activates a hyperlink within shared browsing window **17** of synchronized browsing software **16**. In exemplary embodiments, any interaction by the user of a following device that is not also a leading device prompts the following device to proceed to step **752**.

Step **752-755** of method **750** utilized by the following device are the same as steps **702-705** of method **700** utilized by the leading device. The following device generates an unshared browser window in response to the activation of the hyperlink in step **751**. The following device then contacts the website server and receives the requested webpage data. Finally, the following device outputs the unshared webpage data in the unshared browsing window.

In alternative embodiments of the present invention, either leading or following devices may send communication message **61** to synchronization server **13** for a website affiliation query within affiliation database **31** regarding unshared webpage interactions. In such embodiments, communication message **61** may comprise data, an identifier, or some other information to indicate to synchronization server **13** that the webpage interaction information is not to be relayed to other devices. As such, in response to communication message **61**, synchronization server **13** may transmit reply message **62** to the querying device, comprising an affiliation identification code for the affiliated website.

FIG. **7**(*a*) illustrates a screen shot of an exemplary embodiment of synchronized browsing software being run on a host device. FIG. **7**(*a*) illustrates the visual output of host device **10** running synchronized browsing software **16**, wherein synchronized browsing software **16** comprises shared browsing window **17**, shared browsing tab **18** and unshared browsing tab **70**. In various embodiments of the present invention, synchronized browsing software **16** may comprise new room button **71**, invitation button **72**, attendee list **73**, chat box **74**, buddy list **75**, and browse menu button **76**.

Unshared browsing tab **70** is a browsing tab identifier and extension of an unshared browsing window, as described in FIGS. **6**(*a*) and **6**(*b*). New room button **71** is a component of synchronized browsing software **16** that, when clicked or activated by a user, prompts the user to start a new synchronized browsing session. Like activation hyperlink **51**, previously discussed for FIG. **2**(*c*), activation of new room button **71** may prompt the user to start a new synchronized browsing session.

Activation of invitation button **72** allows a participant in a synchronized browsing session, whether leading or following, to invite a prospective guest to join the synchronized browsing session. In an exemplary embodiment, activation of invitation button **72** may prompt the user of synchronized browsing software **16** to input a desired recipient of the invitation request. In alternative embodiments, activation of invitation button **72** may allow the user of synchronized browsing software **16** to invite a prospective guest via methods discussed and illustrated in FIGS. **4**(*b*)-**4**(*e*).

Attendee list **73** is a component of synchronized browsing software **16** that lists the attendees present in the synchronized browsing session. In alternative embodiments of the present invention, attendee list **73** may only share attendee information with leading devices, such as host device **10**, and not following devices, such as guest device **14**. In alternative embodiments, however, attendee list **73** may only list known contacts or friends of the user of synchronized browsing software **16**. In exemplary embodiments, attendee list **73** may provide visual notification if an attendee has voice chat or video chat capability, or if the attendee has voice chat or video chat enabled.

Further, attendee list **73** may provide the user of synchronized browsing software **16** capability to audibly or visually communicate with individual attendees, groups of attendees, or all attendees of the synchronized browsing session. Additionally, attendee list **73** provides for mute, sound level and other audio and video control capabilities, including options to add, remove, or otherwise disable specific functionality for the user of synchronized browsing software **16**. In further embodiments, host device **10** may limit or restrict functionality available to guest devices in synchronized browsing software **16** during a synchronized browsing session. Finally, attendee list **73** also performs other functions such as, but not limited to, enabling users to pass and request controls, banning or ejecting certain users from sessions, audio or text muting certain users, viewing respective profiles for each of the attendees either within the application or on a separate web page, initiating private chat sessions, or other functions.

Chat box **74** is a component of synchronized browsing software **16** that allows attendees of the synchronized browsing session to communicate via text chat. In exemplary embodiments, synchronized browsing software **16** provides functionality to control to whom messages are sent via chat box **74**, or which attendees may send and receive messages via chat box **74**. Chat box **74** enables users to utilize both textual messages and emoticons that integrate links within them; when these emoticons are selected, clicked, or otherwise triggered, the user will visit the embedded link within a separate non-shared window. These links may also contain advertising, affiliate, or other similar codes that recognize the source of that traffic and give the publisher of that traffic credit for the user's visit to a certain site, game, virtual world, or other application.

Buddy list **75** is a component of synchronized browsing software **16** that provides a list of friends and contacts of the user. In exemplary embodiments, buddy list **75** may incorporate friend lists of the user of synchronized browsing software **16** from AOL®, GMAIL®, MSN®, YAHOO®, FACEBOOK®, or other communication, social networking, and social communication methods and platforms. Buddy list **75** may provide visual notification if a friend or contact listed in buddy list **75** is online, offline, busy, available, or some other status. In exemplary embodiments, activation of a contact in buddy list **75** may provide the user of synchronized browsing software **16** the option to chat, text, communicate, or invite the contact to a synchronized browsing session. Further, synchronized browsing software **16** may integrate social media services from media providers such as FACEBOOK®, TWITTER®, GOOGLE®, and others, to provide social media functionality to the user.

Browse menu button **76** is a component of synchronized browsing software **16** that provides a user access to the browse menu. Activation of browse menu button **76** opens the browse menu of synchronized browsing software **16**, which will be discussed for FIG. **7**(*b*).

FIG. **7**(*b*) illustrates an exemplary embodiment of synchronized browsing software on a host device highlighting an expanded browse menu. FIG. **7**(*b*) illustrates browse menu button **76** and browse menu **77**.

Browse menu button **76** and browse menu **77** are components of synchronized browsing software **16** that provide the user easy access to a vast amount of information and media. Activation of browse menu button **76** prompts the

opening of browse menu **77**. In exemplary embodiments, browse menu **77** may include tabbed windows of content. In the embodiment illustrated in FIG. **7**(*b*), the tabs include "favorites," "happening now," "shopping," "travel," "media," and apps." Alternatively, the tabbed windows may separate internet content by theme, alphabetically, or by some other sorting method. In yet other embodiments, the tabs may be editable, such that a user may sort content according to their preferences.

Browse menu **77** may provide access to featured and publicly shared synchronized browsing sessions. Further, browse menu **77** may inform the user of synchronized browsing software **16** of upcoming events, promotions, and other information. Additionally, a user may sign up, or rsvp, to a synchronized browsing session via browse menu **77**.

A method and apparatus for the implementation of a real-time, sharable browsing experience on a host device has been described. The foregoing description of the various exemplary embodiments of the invention has been presented for the purposes of illustration and disclosure. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention not be limited by this detailed description, but by the claims and the equivalents to the claims.

What is claimed is:

1. A method performed by a host device for establishing a synchronized browsing session between the host device and an invitee device, comprising:

sending a request to establish the synchronized browsing session to a synchronization server;

receiving a confirmation message from the synchronization server including a session identifier generated by the synchronization server, wherein the session identifier is associated with the host device and the established synchronized browsing session;

sending an invitation to an invitee device to join the synchronized browsing session, wherein the invitation includes the session identifier;

recording a shared web browsing interaction responsive to determining that a web browsing interaction of the host device within a web browsing window is a sharable web browsing interaction;

sending a request for webpage content to a website server independent of the synchronization server;

subsequent to sending the request for webpage content to the website server, transmitting information related to the shared web browsing interaction to the synchronization server,

wherein the information related to the shared web browsing interaction is to be processed by a browser of the invitee device and enables the invitee device to generate a request to retrieve a substantially the same webpage content as the request for the webpage content from the host device;

wherein the synchronization server transmits the information related to the shared web browsing interaction to the invitee device in response to receiving the information related to the shared web browsing interaction from the host device, and

wherein the invitee device retrieves data from the website server in response to receiving the information related to the shared web browsing interaction from the synchronization server, the data associated with the webpage content requested by the host device and the information related to the shared web browsing interaction; and

receiving, responsive to sending the request for webpage content to the website server and after transmitting the information related to the shared web browsing interaction to the synchronization server, the requested webpage content from the website server.

2. The method of claim **1**, further comprising receiving a notification message indicative of the invitee device joining the synchronized browsing session.

3. The method of claim **1**, further comprising activating a hyperlink on a website to initialize the sending of the request to establish the synchronized browsing session.

4. The method of claim **1**, wherein the invitation comprises a hyperlink for joining the synchronized browsing session.

5. The method of claim **1**, wherein the invitation is sent to the invitee device via:

a social network communication; a news feed; an email message; an instant message communication; a microblogging communication; a text message communication; or other communication medium that would be suitable for transmitting the invitation.

6. The method of claim **1**, wherein information related to the shared web browsing interactions comprises a URL, form data, cookie information, or script data.

7. The method of claim **1**, wherein the session identifier associated with the established synchronized browsing session comprises:

an identification number;

a passkey;

a URL;

MAC address; or

other unique indicator such that the synchronized browsing session may be identified for joining the session.

8. The method of claim **1**, wherein the web browsing window is capable of accepting both shared and non-shared web browsing interactions.

9. The method of claim **8**, wherein web browsing interactions of the host device determined to be non-shared web browsing interactions are depicted in a non-shared web browser window that is separate from the web browsing window.

10. The method of claim **1**, further comprising:

receiving, from the synchronization server, a reply message, wherein the reply message includes an adcode, an adcode identification code, XML, a modified URL address, cookie information, form data, script data, user input information, or attached files.

11. An apparatus for establishing a synchronized browsing session between a host device and an invitee device, comprising:

a network interface adapted to communicate with a synchronization server; and

a processor adapted to:

send a request from the host device to establish the synchronized browsing session to the synchronization server via the network interface;

receive a confirmation message from the synchronization server including a session identifier generated by the synchronization server, wherein the session identifier is associated with the host device and the established synchronized browsing session;

send an invitation from the host device to the invitee device to join the synchronized browsing session, wherein the invitation includes the session identifier;

record a shared web browsing interaction responsive to determining that a web browsing interaction of the host device within a web browsing window is a sharable web browsing interaction;

send a request for webpage content to a website server independent of the synchronization server;

transmit, subsequent to sending the request for webpage content to the website server, information related to the shared web browsing interaction to the synchronization server,

wherein the information related to the shared web browsing interactions is to be processed by an application of the invitee device, and enables the invitee device to generate a request to retrieve a substantially the same webpage content as the request for the webpage content from the host device;

wherein the synchronization server transmits the information related to the shared web browsing interaction to the invitee device in response to receiving the information related to the shared web browsing interaction from the host device, and

wherein the invitee device retrieves data from the website server in response to receiving the information related to the shared web browsing interaction from the synchronization server, the data associated with the webpage content requested by the host device and the information related to the shared web browsing interaction; and

receive, responsive to sending the request for webpage content to the website server and after transmitting the information related to the shared web browsing interaction to the synchronization server, the requested webpage content from the website server.

12. The apparatus of claim **11**, further comprising a user interface adapted to initiate the processor to send the request in response to a user input, wherein the user input comprises activation of a hyperlink on a website or third party application for initializing the sending of the request to establish the synchronized browsing session.

13. The apparatus of claim **11**, wherein the session identifier associated with the established synchronized browsing session comprises:

an identification number;

a passkey;

URL;

MAC address; or other unique indicator such that the synchronized browsing session may be identified for joining the session.

14. The apparatus of claim **11**, wherein the web browsing window is capable of accepting both shared and non-shared web browsing interactions.

15. The apparatus of claim **14**, wherein web browsing interactions of the host device determined to be non-shared web browsing interactions are depicted in a non-shared web browser window that is separate from the web browsing window.

16. The apparatus of claim **11**, wherein the processor is further adapted to:

receive, from the synchronization server, a reply message, wherein the reply message includes an adcode, an adcode identification code, XML, a modified URL address, cookie information, form data, script data, user input information, or attached files.

* * * * *