

McGRAW-HILL

DICTIONARY OF COMPUTING & COMMUNICATIONS



MORE THAN 11,000 ESSENTIAL TERMS

COVERS EVERY DISCIPLINE OF COMPUTING & COMMUNICATIONS

PROVIDES SYNONYMS, ACRONYMS, AND ABBREVIATIONS

M

CO

SE

HACKER

EMPLOYEE

Materials in this dictionary are derived from the McGRAW-HILL DICTIONARY OF SCIENTIFIC AND TECHNICAL TERMS, Sixth Edition, copyright © 2003 by The McGraw-Hill Companies, Inc. All rights reserved.

McGRAW-HILL DICTIONARY OF COMPUTING & COMMUNICATIONS, copyright © 2003 by The McGraw-Hill Companies, Inc. All rights reserved. Printed in the United States of America. Except as permitted under the United States Copyright Act of 1976, no part of this publication may be reproduced or distributed in any form or by any means, or stored in a database or retrieval system, without the prior written permission of the publisher.

1 2 3 4 5 6 7 8 9 0 DOC/DOC 0 9 8 7 6 5 4 3

ISBN 0-07-142178-5



This book is printed on recycled, acid-free paper containing a minimum of 50% recycled, de-inked fiber.

This book was set in Helvetica Bold and Novarese Book by TechBooks, Fairfax, Virginia. It was printed and bound by RR Donnelley, The Lakeside Press.

McGraw-Hill books are available at special quantity discounts to use as premiums and sales promotions, or for use in corporate training programs. For more information, please write to the Director of Special Sales, Professional Publishing, McGraw-Hill, Two Penn Plaza, New York, NY 10121-2298. Or contact your local bookstore.

Library of Congress Cataloging-in-Publication Data

McGraw-Hill dictionary of computing and communications/McGraw-Hill.

p. cm.

ISBN 0-07-142178-5

1. Computer science—Dictionaries.
2. Telecommunication—Dictionaries.
3. Engineering—Dictionaries.
- I. The McGraw-Hill Companies, Inc.

QA76.15D52634 2003

004'.03—dc21

2003051209

CUSTOMERS

BUSINESS
PARTNERS

DANIEL MINOLI •

Preface	ix
Staff	x
How to Use the Dictionary	xi
Fields and Their Abbreviations	xii
Pronunciation	xiii
A-Z Terms	xiv
Appendix	xv
Equivalents	xvi
Customary Units	xvii
Conversion Tables	xviii
Mathematical Symbols	xix
Schematic Symbols	xx
Partial List of Abbreviations	xxi
ASCII Codes	xxii
Electromagnetic Interference	xxiii
Radio Frequency	xxiv
Microprocessors	xxv

operator interrupt

rule. Abbreviated OI. ('äp-ä-rä-shän-äl 'äm-plä,fi-är)

[COMPUT SCI] Binary form of operation in which one of the states of the wave is the absence of energy. ('lön 'löl, kē-ig)
[COMPUT SCI] A computer system in which specifications are made so that third parties to develop software. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A computer system expansion bus that is designed to allow expansion boards. ('lön-pän 'är-ka, tek-ni-är)

plan position indicator [COMPUT SCI] A device that indicates the position of a set distance from the plan position indicator. ('lön-pän 'är-ka, tek-ni-är)
signaling [COMPUT SCI] A condition in which no current flows while the die condition. ('lön-pän 'är-ka, tek-ni-är)

[COMPUT SCI] Of technical nature or permit expansion of the system in capability; the condition of a system that is artificially constrained.

system [COMPUT SCI] A system in which the operation is derived from sources that are not within the character of the system. ('lön-pän 'är-ka, tek-ni-är)
system [COMPUT SCI] A file that contains the operating system. ('lön-pän 'är-ka, tek-ni-är)
system [COMPUT SCI] A file that contains the operating system. ('lön-pän 'är-ka, tek-ni-är)

[COMPUT SCI] 1. A routine that is directly into a larger program or calling sequence. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)

[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A data structure in which the data is processed in a sequence. ('lön-pän 'är-ka, tek-ni-är)

system architecture [COMPUT SCI] The structure of a computer network that allows different types of computers and peripheral devices from different manufacturers to be connected together. ('lön-pän 'sis-täm 'är-ka, tek-ni-är)

wire carrier system [COMPUT SCI] A system for carrier telephony using an open-wire line. ('lön-pän 'är-ka, tek-ni-är)

band [COMPUT SCI] Any one of the quantities entering into or arising from an operation. ('lön-pän 'är-ka, tek-ni-är)

time [COMPUT SCI] The phase of computer operation when an instruction is being carried out. ('lön-pän 'är-ka, tek-ni-är)

delay [COMPUT SCI] Computer time lost because of mistakes or inefficiency of operating personnel or users of the system, excluding time lost because of defects in programs or data. ('lön-pän 'är-ka, tek-ni-är)

instructions [COMPUT SCI] A detailed description of the actions that must be carried out by a computer operator in running a program or group of interrelated programs, usually included in the documentation of a program. ('lön-pän 'är-ka, tek-ni-är)
[COMPUT SCI] A file that contains the operating system. ('lön-pän 'är-ka, tek-ni-är)

position [COMPUT SCI] Terminal of a communications channel which is attended by an operator; usually the term refers to a single operator, such as a radio operator's position or a telephone operator's position; however, certain terminals may require more than one operating position. ('lön-pän 'är-ka, tek-ni-är)

power [ELECTROMAG] Power that is usually supplied to a radio transmitter antenna. ('lön-pän 'är-ka, tek-ni-är)

ratio [COMPUT SCI] The time during which computer hardware operates and gives results divided by the total time scheduled for computer operation. ('lön-pän 'är-ka, tek-ni-är)

system [COMPUT SCI] A set of programs and routines which guides a computer network in the performance of its tasks, includes the programs (and programmers) with certain supporting functions, and increases the efficiency of the computer or network hardware. ('lön-pän 'är-ka, tek-ni-är)

system supervisor [COMPUT SCI] A control program of a set of programs which runs a computer in the performance of its tasks and which assist the program with certain supporting functions. ('lön-pän 'är-ka, tek-ni-är)

[COMPUT SCI] 1. A process or procedure that obtains a unique result from any possible combination of operands. 2. The sequence of actions resulting from the execution of a digital computer instruction. ('lön-pän 'är-ka, tek-ni-är)

amplifier [ELECTR] An amplifier that provides high direct-current stability and high immunity to oscillation, generally achieved by a large amount of negative feedback; used

to perform analog-computer functions such as summing and integrating. ('äp-ä-rä-shän-äl 'äm-plä,fi-är)

operational label [COMPUT SCI] A combination of letters and digits at the beginning of the tape which uniquely identify the tape required by the system. ('äp-ä-rä-shän-äl 'lä-bäl)

operational standby program [COMPUT SCI] The program operating in the standby computer when in the duplex mode of operation. ('äp-ä-rä-shän-äl 'stand-bi, prö, gram)

operation code [COMPUT SCI] A field or portion of a digital computer instruction that indicates which action is to be performed by the computer. Also known as command code. ('äp-ä-rä-shän 'kōd)

operation cycle [COMPUT SCI] The portion of a memory cycle required to perform an operation; division and multiplication usually require more than one memory cycle to be completed. ('äp-ä-rä-shän, si-käl)

operation decoder [COMPUT SCI] A device that examines the operation contained in an instruction of a computer program and sends signals to the circuits required to carry out the operation. ('äp-ä-rä-shän 'dē-kōd-är)

operation number [COMPUT SCI] 1. Number designating the position of an operation, or its equivalent subroutine, in the sequence of operations composing a routine. 2. Number identifying each step in a program stated in symbolic code. ('äp-ä-rä-shän, nām-bar)

operation part [COMPUT SCI] That portion of a digital computer instruction which is reserved for the operation code. ('äp-ä-rä-shän, pärt)

operation register [COMPUT SCI] A register used to store and decode the operation code for the next instruction to be carried out by a computer. ('äp-ä-rä-shän, rej-ä-star)

operations research [MATH] The mathematical study of systems with input and output from the viewpoint of optimization subject to given constraints. ('äp-ä-rä-shän, ri-sörch)

operation time [COMPUT SCI] The time elapsed during the interpretation and execution of an arithmetic or logic operation by a computer. ('äp-ä-rä-shän, tīm)

operator's console [COMPUT SCI] Equipment which provides for manual intervention and monitoring computer operation. ('äp-ä-rä-ärz 'kän, söl)

operator [COMPUT SCI] Anything that designates an action to be performed, especially the operation code of a computer instruction. ('äp-ä-rä-är)

operator hierarchy [COMPUT SCI] A sequence of mathematical operators which designates the order in which these operators are to be applied to any mathematical expression in a given programming language. ('äp-ä-rä-är 'hi-är, ä-r-kē)

operator interrupt [COMPUT SCI] A step whereby control is passed to the monitor, and a message, usually requiring a typed answer, is printed on the console typewriter. ('äp-ä-rä-är 'in-tä-räpt)