

DICTIONARY
OF
**COMPUTER
SCIENCE
ENGINEERING
AND TECHNOLOGY**

EDITOR-IN-CHIEF
Phillip A. Laplante

 **CRC PRESS**

Siemens Exhibit 1028
Siemens et al. v. Metrom Rail

DICTIONARY
OF
**COMPUTER
SCIENCE,
ENGINEERING,
AND TECHNOLOGY**

EDITOR-IN-CHIEF
Phillip A. Laplante



CRC Press

Boca Raton London New York Washington, D.C.

Library of Congress Cataloging-in-Publication Data

Dictionary of computer science, engineering, and technology / edited by Phillip Laplante.

p. cm.

Includes bibliographical references and index.

ISBN 0-8493-2691-5 (alk. paper)

1. Computer science—Dictionaries. 2. Engineering—Dictionaries. 3.

Technology—Dictionaries. I. Laplante, Phillip A.

QA76.15.D5258 2000

004'.03—dc21

00-052882

This book contains information obtained from authentic and highly regarded sources. Reprinted material is quoted with permission, and sources are indicated. A wide variety of references are listed. Reasonable efforts have been made to publish reliable data and information, but the authors and the publisher cannot assume responsibility for the validity of all materials or for the consequences of their use.

Neither this book nor any part may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, microfilming, and recording, or by any information storage or retrieval system, without prior permission in writing from the publisher.

All rights reserved. Authorization to photocopy items for internal or personal use, or the personal or internal use of specific clients, may be granted by CRC Press LLC, provided that \$.50 per page photocopied is paid directly to Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923 USA. The fee code for users of the Transactional Reporting Service is ISBN 0-8493-2691-5/01/\$0.00+\$.50. The fee is subject to change without notice. For organizations that have been granted a photocopy license by the CCC, a separate system of payment has been arranged.

The consent of CRC Press LLC does not extend to copying for general distribution, for promotion, for creating new works, or for resale. Specific permission must be obtained in writing from CRC Press LLC for such copying.

Direct all inquiries to CRC Press LLC, 2000 N.W. Corporate Blvd., Boca Raton, Florida 33431.

Trademark Notice: Product or corporate names may be trademarks or registered trademarks, and are used only for identification and explanation, without intent to infringe.

Visit the CRC Press Web site at www.crcpress.com

© 2001 by CRC Press LLC

No claim to original U.S. Government works
International Standard Book Number 0-8493-2591-5
Library of Congress Card Number 00-052882
2 3 4 5 6 7 8 9 0

breakpoint instruction

breakpoint instruction a debugging instruction provided through hardware support in most microprocessors. When a program hits a breakpoint, specified actions occur that save the state of the program, and then switch to another program that allows the user to examine the stored state. The user can suspend the execution of a program, examine the registers, stack, and memory, and then resume the program's execution, which is very helpful in a program's debugging.

Brent-Kung adder a type of carry-lookahead adder; the organization is based on computing carries that are parallel prefixes.

Bresenham's algorithm a technique developed in the framework of raster graphics for generating lines and circles. These algorithms use only integer arithmetic, avoid rounding, and perform an iterative computation of the primitive points by approximating the distance to the nearest pixel center along either the x or y axis. These characteristics make for efficient algorithms.

bridge an edge of a connected graph whose removal would make the graph unconnected.

brightness the perceived intensity of a radiating object.

British museum algorithm a general approach to find a solution by checking all possibilities one by one, beginning with the smallest. The term refers to a conceptual, not a practical, technique where the number of possibilities is enormous. *See also* breadth-first search, brute force search, exhaustive search.

broadcast to send a message to all recipients.

Brownian motion a stochastic process with independent and stationary increments. The derivative of such a process is a white noise process. A Brownian motion process X_t is the solution to a stochastic differential equation of the form

$$\frac{dX}{dt} = b(t, X_t) + \sigma(t, X_t) \cdot W_t,$$

where W_t is a white noise process.

browse to read uncommitted.

brute force search *See* exhaustive search.

BSD acronym for Berkeley Software Distribution, a proprietary version of Unix.

b-spline (1) the shortest cubic spline consisting of different three-degree polynomials on four intervals; it can be obtained by convolving four box functions.

(2) a multi-segment spline curve representation based on local polynomials having continuity of curve orientation and curvature at the points (knots) where different segments join. Cubic b-splines are popular, but linear, quadratic, quartic, etc. splines are also used. The b in b-spline stands for basis because the b-spline segments are formed from the weighted sum of four local basis functions. The local shape of the spline segment is controlled by four control points; in the case of b-splines, these control points do not lie on the curve itself (i.e., b-splines are not interpolating). One important advantage of b-splines is that the movement of a control point affects only four segments of the curve. B-spline surfaces can be defined from b-spline curves lying in both directions on the surface. Here, 16 non-interpolated control points are needed per patch, but each patch then has tangent and curvature continuity where it joins a neighboring patch. The b-spline is defined over a uniform parameter domain, and is evaluated as a simple polynomial function. More complex forms, such as NURBS, relax these assumptions.

BTB *See* branch target buffer.

BTC *See* block truncation coding.

b-tree a balanced search tree in which every node has between $t - 1$ and $2t - 1$ children. Insertion and deletion algorithms are modified to ensure the tree remains balanced. For example, on insertion into a full block (i.e., a collision), the block is split and the middle value is propagated up a level to the parent node. All values less than the middle value are placed in the left child of the parent; other values are placed in the right child. This is a good structure if much of the tree is on disk, since the tree height, and