



US 20090144818A1

(19) **United States**

(12) **Patent Application Publication**
Kumar et al.

(10) **Pub. No.: US 2009/0144818 A1**

(43) **Pub. Date: Jun. 4, 2009**

(54) **SYSTEM AND METHOD FOR USING
VARIABLE SECURITY TAG LOCATION IN
NETWORK COMMUNICATIONS**

Related U.S. Application Data

(60) Provisional application No. 60/986,833, filed on Nov. 9, 2007.

(75) Inventors: **Srinivas Kumar**, Cupertino, CA
(US); **Vijayashree S. Bettadapura**,
Campbell, CA (US)

Publication Classification

(51) **Int. Cl.**
G06F 21/00 (2006.01)

(52) **U.S. Cl.** **726/13**

(57) **ABSTRACT**

Correspondence Address:

RATNERPRESTIA

P.O. BOX 980


VALLEY FORGE, PA 19482 (US)

A method of packet security management to ensure a secure connection from one network node to another. The method includes creating a security tag for each packet in a network session, selecting one of a number of possible tag locations within the packet, inserting the security tag at that location, transmitting the tagged packets from a sending node to the receiving node, authenticating the packets' security tags at the receiving node, and dropping non-authenticated packets. The method also includes determining best possible tag locations when sending a packet and locating a security tag when receiving a packet.

(73) Assignee: **Applied Identity**, San Francisco,
CA (US)

(21) Appl. No.: **12/267,850**

(22) Filed: **Nov. 10, 2008**







Fig. 1A

FIG. 1B






Fig. 2




Fig. 3A




Fig. 3B

310		Network Conditions Table	
320	330	Entry 1	
		IP Address Range	Tag Placement Directives
Entry 2			
Entry 3			
Entry 4			
Entry 5			
Entry 6			
Entry 7			
Entry 8			
▪			
▪			
▪			
Entry N			
340			

Fig. 4




Fig. 5A




Fig. 5B




Fig. 5C

SYSTEM AND METHOD FOR USING VARIABLE SECURITY TAG LOCATION IN NETWORK COMMUNICATIONS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 60/986,833, filed Nov. 9, 2007, entitled "System And Method For Using Variable Security Tag Location In Network Communications" the contents of which are hereby incorporated by reference.

FIELD OF THE INVENTION

[0002] This invention relates to computer system security and, more particularly, to a system and method for improved reliability in secure packet communication systems.

BACKGROUND OF THE INVENTION

[0003] Computer system resources such as web servers and database services may be directly accessible through networks such as LANs, WANs, and the Internet. Communication between computer systems over a network typically takes place through transmitted data structures called packets. A packet may include data being transported from one system to another system. Such data is generally referred to as payload. A packet may also include other data that defines the structure and nature of the packet, including information indicating the origin and destination of the packet and information indicating other packet characteristics. A stream of packets may constitute a communication from one system to another system.

SUMMARY OF THE INVENTION

[0004] The invention may be embodied as a method or system for inserting a security tag into a packet in one or more locations within the packet so that the packet may pass through a number of network impediments with the security tag or tags intact.

[0005] The sending node and receiving node may determine security tag placement using different methods. They may negotiate placement when they first establish secure communications. The sending node may determine placement based on known network impediments between it and the receiving node. The sending node may send a test packet to the receiving node to determine locations where security tags are removed and then determine placement based on the results (the received test packet). The sending node may arbitrarily or randomly determine one or more placement locations in each packet and the receiving node may check for the security tag in various placement locations when it receives the packet.

[0006] By providing a variety of security tag placement locations within a packet and then determining one or more locations to overcome network impediments between the sending node and the receiving node, secure communications may be enabled using security tags in network environments that may not typically allow such security tags within packets.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] The invention is best understood from the following detailed description when read in connection with the accompanying drawings. According to common practice, various features/elements of the drawings may not be drawn to scale. Common numerical references represent like features/elements. The following figures are included in the drawings:

[0008] FIG. 1A is a schematic diagram illustrating a network using secure communications in accordance with an exemplary embodiment of the invention;

[0009] FIG. 1B is a schematic diagram of sending and receiving nodes in accordance with an exemplary embodiment of the invention;

[0010] FIG. 2 is a data schema of an exemplary packet structure illustrating variable placement locations for a security tag in accordance with another exemplary embodiment of the invention;

[0011] FIGS. 3A and 3B are flow charts illustrating a method of creating an authenticated session between a sending node and a receiving node and of determining a location in which to insert a security tag in packets sent to the receiving node in accordance with yet another exemplary embodiment of the invention;

[0012] FIG. 4 is a block diagram illustrating a network conditions table in accordance with various embodiments of the invention, and

[0013] FIGS. 5A, 5B and 5C are flow charts illustrating a method of sending packets from a sending node to a receiving node over an authenticated session and of finding and reading the security tags in the packets when the receiving node receives the packets in accordance with yet another exemplary embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0014] Although the invention is illustrated and described herein with reference to specific embodiments, the invention is not intended to be limited to the details shown. Rather, various modifications may be made in the details within the scope and range of equivalents of the claims and without departing from the invention.

[0015] Direct user/client access through networks such as LANs, WANs, and the Internet may make them vulnerable to malicious trespasses. Computer security systems may prevent such trespasses by authenticating users that desire to use resources and then ensuring that the communications between authenticated users and resources are not taken over by outside entities intent on malicious trespass.

[0016] One method to maintain secure communications via packets is to insert a security tag into each packet. The security tag may include information that the sender and receiver may verify, and, thus ensures to the receiver that the packet is from a known (verified) sender and, for example, is not from an outside source that is attempting to break into a stream of packets. It may also ensure that the packet's payload has not been altered during transmission.

[0017] A security tag within a packet, however, may not make it through (across) a network. Different network elements that check (verify) packets as the packets pass through the network may, for example, remove the security tag from a passing packet. A proxy server may, for example, consider a security tag as extraneous data and remove it, or stateful firewalls and intrusion detection systems may misinterpret the security tag and generate false alarms. In such cases, these network element (impediments) may reduce or eliminate the effectiveness of the security of the communication.

[0018] FIG. 1A is a schematic diagram illustrating an exemplary network (environment) for secure communications using variable placement locations for placement of a security tag.

[0019] Referring to FIG. 1A, a user 10 may work with (operate) a sending node 20, which may be a personal computer or other computing device. Sending node 20 may have an operating system (OS) 30 that allows sending node 20 to communicate via a network 50 with other devices.

[0020] In certain exemplary embodiments, a security plug-in **40** that may run within OS **30**, may examine (analyze) and/or may modify packets sent by sending node **20**. In other exemplary embodiments, the security plug-in may be an application program, other program or hardware module executing on sending node **20**.

[0021] A receiving node **60** may be a gateway to a sub-network **90** of network **50** that connects to one or more network resources **95** such as web servers, database servers, and other services that user **10** may desire to access. A security gateway **70** (e.g., a program or hardware module) may run on receiving node **60**. A security server **80** may run as part of security gateway **70** to examine and/or modify incoming packets and may communicate with sending node **20** via sub-network **90** and/or network **50**.

[0022] Although the security plug-in and security gateway are illustrated in the network application and security server, respectively, the security plug-in and security gateway may be provided in any device on the network or sub-network that interacts with the stream of packets being secured.

[0023] Referring to FIG. 1B, sending node **20** may include: (1) a placement determination unit **22** for selecting at least one placement location among a plurality of locations for the security tag to be embedded in each of the plurality of packets; (2) an insertion unit **24** for inserting the security tag at the at least one placement location for each of the packets; and (3) a transmission/reception unit **26** for transmitting/receiving information such as transmission of the tagged packets from sending node **20** toward receiving node **60**.

[0024] In certain exemplary embodiments, receiving node **60** may include: (1) a receiving unit **62** for receiving the tagged packets from sending node **20**; (2) a packet processor **64** for authenticating each of the security tags of the tagged packets, and (3) a transmitting unit **66** for transmitting information such as the network conditions table **68**.

[0025] FIG. 2 is a data schema illustrating an exemplary packet structure (i.e., a Transmission Control Protocol/Internet Protocol (TCP/IP) packet **110** structure) that may be used to transport data between sending node **20** and receiving node **60**. FIG. 2 illustrates exemplary locations **130**, **150**, **170** and **180** within packet **110** where a security tag may be inserted to secure (verify) the packet (including its origin). Other placement locations are also possible.

[0026] A TCP/IP packet may include: (1) an IP header **120** that includes Internet Protocol (IP) information about packet **110**; (2) a TCP header **140** that includes transmission control protocol information about packet **110**; and (3) payload **160** may include data that one node requested to send to another node. IP header **120** may include an IP option field **130** that may include optional information. The TCP header **140** may include a TCP option field **150** that may include optional information. The payload **160** may include any kind of data or information a node desires to communicate to another node.

[0027] In certain exemplary embodiments, security plug-in **40** may insert a security tag in one or more placement locations within the packet **110** (e.g., in the IP option field **130**, in the TCP option field **150**, at the start of the payload field **170**, at the end of the payload field **180** and/or, anywhere within the payload).

[0028] If the security tag is inserted in either IP option field **130** or TCP option field **150**, the option field having the inserted security tag may start with an op-code, (for example, a one-byte value that may indicate the rest of the contents of the option field. The op-code value may be inserted in TCP or IP option field **130** or **150** to specify to receiving node **60** that the TCP or IP option field **130** or **150** includes a security tag.

[0029] FIGS. 3A and 3B are flow charts illustrating a method of using variable placement locations for inserting a security tag. The method includes, for example, sensing a user's **10** request to login to the sending node **20** and then to use a protected network resource **95**, and the action taken for initiating an authenticated session in which user **10** communicates with a network resource **95**.

[0030] Now referring to FIGS. 3A and 3B, the sending node **20**, may include an operating system plug-in **40** and the receiving node **60** may include the security server **80**.

[0031] At block **202** when user **10** logs into a network-connected computer and presents user credentials, such as user name and password, sending node **20** may send an authentication request including the user credentials along with information about the sending node's capabilities and a profile of sending node **20**. This information about sending node **20** may be pre-established. For example, such information may be entered into security plug-in **40** when it was installed on sending node **20**.

[0032] At block **204**, receiving node **60** authenticates user **10** using the information in the request and an authentication server, such as a Light Directory Access Protocol (LDAP) server, that may be accessed by receiving node **60**. Receiving node **60**, may also read packet data from the packets that include the log-in information. The packet data may indicate to receiving node **60**, sending node's **20** (i) IP address, (ii) system health status (e.g., security compliance information), (iii) host capabilities and/or (iv) profile.

[0033] At block **206**, receiving node **60** may then create a unique client ID and session key for user **10** for the authenticated session. Receiving node **60** may also assemble session data that may include security tag directives, a list of protected subnets that are available through receiving node **60**, and a network conditions table **310** (shown in FIG. 4) for sending node **20**. The list of protected subnets and the network conditions table **310** may be stored in a location accessible by receiving node (**60**).

[0034] Security tag directives may specify a tag location in a TCP/IP packet that sending node **20** may use when it inserts a security tag into outgoing packets traversing through receiving node **60**. If the security tag directives specify an IP option location or a TCP option location, then an op-code value may also be specified for IP/TCP option field **130** or **150** to indicate that it contains a security tag.

[0035] In various exemplary embodiments, security tag directives may also specify that sending node **20** may auto sense a tag location. That is, sending node **20** may automatically determine the best (optimum) security tag location by performing an automated test procedure.

[0036] At block **208**, receiving node **60** may send a client ID, a session key, and any other relevant connection data to sending node **20**. At block **210**, sending node **20** may use the client ID, the session key, and the other session data, as appropriate, to create a digital signature for the outgoing packet. The digital signature may be created in many ways including hashing the client ID with all or part of the packet's payload using the session key.

[0037] At block **212**, sending node **20** may check whether receiving node **60** specified an auto-sense, as a security tag directive. If receiving node **60** did not specify the auto-sense, at block **214**, sending node **20** checks for (e.g., notes) the tag location that receiving node **60** may have specified. Sending node **20** has then established an authenticated session to receiving node **60** for user **10**.

[0038] If receiving node **60** specified the auto-sense, as a security tag directive, at block **216**, sending node **20** may insert a security tag at each possible location (e.g., in the IP

header field, in the TCP header field, and/or the beginning or end of the payload field) in a test packet and may send the test packet to receiving node 60.

[0039] At block 218, receiving node 60 may check for security tags in each possible location and may detect from which locations the security tags have been removed by the network impediments. At block 220, receiving node 60 may send a placement message to sending node 20. The placement message may indicate one or more successful tag locations (e.g., locations which were not affected by the network impediments). At block 222, sending node 20 may choose one of those tag locations.

[0040] In certain exemplary embodiments, the tag locations are prioritized such that when the successful tag locations are determined, sending and receiving nodes 20 and 60 both determine the actual tag location based on the predetermined prioritization.

[0041] At block 224, sending node 20 establishes an authenticated session to receiving node 60 for user 10.

[0042] FIG. 4 is a block diagram illustrating a network conditions table in accordance with various embodiments of the invention.

[0043] Now referring to FIG. 4, network conditions table 310 may be sent by receiving node 60 to sending node 20 when sending node 20 establishes the authenticated session. Table 310 may include a set of entries 320. Each entry 320 may include an IP address range 330 that may specify a network address and subnet mask, and tag placement directives 340 that are provisioned based on information related to, for example, location and type of network impediments (e.g., predetermined network impediments) located between sending node 20 and receiving node 60 that may remove security tags from packets. Sending node 60 may read network conditions table 310 to determine if sending node 20 is located at an IP address defined within the IP address ranges in network conditions table 310 and, if so, to determine one or more tag locations most likely to carry a security tag intact over network 50 to receiving node 60.

[0044] FIGS. 5A, 5B and 5C are flow charts illustrating a method of sending packets from sending node 60 to receiving node 20 over an authenticated session and of finding and reading security tags in the packets when receiving node 60 receives the packets in accordance with yet another exemplary embodiment of the invention.

[0045] Referring to FIGS. 5A, 5B and 5C, at block 402, when sending node 20 detects that an outgoing packet is destined for (going to) protected network resource 95 or protected network 90 to which sending node 20 has an authenticated session, sending node 20 may use the digital signature, client ID, placement directives, and other control information sent by receiving node 60 to create a security tag.

[0046] At block 404, sending node 20 may check whether receiving node 60 sent network conditions table 310. If not, at block 408 sending node 20 may insert a security tag in the packet at the specified location. The specified location was previously determined when sending node 20 established the authenticated session with receiving node 60 for user 10.

[0047] At block 406, if receiving node 60 sent network conditions table 310, sending node 20 may check network conditions table 310 to determine if the sending node's current IP address is within the IP address ranges 320 defined by entries in network conditions table 310. At block 408, if the current IP address is not defined within an IP address range in the network conditions table 310, sending node 20 may insert the security tag in the packet at the specified location.

[0048] At block 410, if the current IP address is defined in an IP address range in the network conditions table 310,

sending node may read the table entry's tag placement directives 330 to determine network impediments which are located between sending and receiving nodes 20 and 60. Sending node 20 may determine the tag location or locations that are most likely to carry the security tag intact over network 50 and may insert the security tag at one or more of these locations.

[0049] At block 412, sending node 20 may send the packet with the security tag to receiving node 60. At block 414, when receiving node 60 receives the packet from sending node 20, receiving node 60 may determine whether or not it previously specified a fixed tag location to sending node 20. At block 416, if receiving node 60 specified a fixed location, receiving node 60 may check for the security tag in the specified location. At block 418, if receiving node 60 locates (finds) the security tag at the specified location, it may read the security tag and, at block 446, may check whether the security tag is authentic.

[0050] Many different methods for authentication are possible including receiving node 60 reading the client ID in the security tag, retrieving the session key it created for that user for the authenticated session, then hashing the client ID with the packet's payload using the session key and checking the resultant value against the digital signature contained in the security tag.

[0051] At block 420, if receiving node 60 had not previously specify a fixed tag location, or if receiving node 60 is unable to allocate the security tag in the fixed location, receiving node 60 may check a size of the packet's IP option field. At block 422, if the IP option field size is greater than or equal to the security tag size, receiving node 60 may check the op code value of IP option field 130 to determine if it matches the op code value receiving node 60 previously specified when it first negotiated the session information with sending node 20. At block 424, if so, receiving node 60 may read IP option field 130 to determine if it finds a valid security tag. At block 428, if the size of IP option field 130 is less than the size of the security tag, if receiving node 60 does not find the specified op code value in IP option field 130 or if receiving node 60 cannot find a valid security tag, receiving node 60 may check TCP option field 150. At block 424, if receiving node 60 finds a valid security tag, receiving node 60 may read the security tag in IP option field 130 and then at block 446 may check to determine if the security tag is authentic.

[0052] If receiving node 60 does not find a security tag in IP option field 130, it may check the size of the packet's TCP option field 150. At block 430, if the TCP option field size is greater than or equal to the security tag size, receiving node 60 may check the TCP option's op code value to determine if it matches the specified op code value the receiving node 60 previously specified when it first negotiated the session information with sending node 20. At block 432, if receiving node 60 does find the specified op code value, receiving node may read TCP option field 150 to determine if it finds a valid security tag. At block 438, if the option field size is less than the size of the security tag, if receiving node 60 does not find the specified op code value in TCP option field 130, or if receiving node 60 does not find a valid security tag, receiving node 60 may check the start of the payload field 170. At block 436, if the node finds a valid security tag, receiving node 60 may read the security tag in TCP option field 150 and then, at block 446, may check to determine if the security tag is authentic.

[0053] If receiving node 60 does not find a security tag in TCP option field 150, it may read the start of the packet's payload field 160 to determine if there is a valid security tag.

If so, at block 440, receiving node 60 may read the security tag and then, at block 446, may check to determine if the security tag is authentic.

[0054] At block 442, if no security tag is located in the start of the payload field 170, receiving node 60 may read the end of the packet's payload field 180 to determine if there is a valid security tag. If so, at block 440, receiving node 60 may read the security tag and then, at block 446, may check whether the security tag is authentic. If no security tag is located at the start or end of the payload field 170 or 180, receiving node 60 has not found a valid security tag and, at block 444, may drop the packet (e.g., to prevent or restrict access by the packet to the protected resource 95 and/or the protected network 90), thus blocking access to the protected resource 95 and/or the protected network 90. In certain exemplary embodiments receiving node 60 may quarantine the packet and/or send the packet elsewhere for analysis.

[0055] At block 448, if the security tag is authentic, receiving node 60 may remove the security tag from the packet and may send the packet to the desired network resource located behind (after) security gateway 70. In certain exemplary embodiments, security gateway 70 may include receiving node 60.

[0056] At block 450, when a subsequent packet for this authenticated session arrives at receiving node 60, receiving node 60 may check the same tag location where it found the security tag in the last session packet. At block 446, if receiving node 60 finds a security tag at the same location, it may determine the security tag's authenticity. If receiving node 60 does not find a security tag at the same location, it may continue processing at block 420 and search for the security tag in other locations.

[0057] The security system and the method for inserting a security tag at variable locations in a packet disclosed herein have diverse applicability in a range of markets including financial services, wireless LAN (e.g., wireless sales force automation and contractor services), and government regulated markets such as banking and health care, among others.

[0058] Although tag location are disclosed as being selected using either placement messages, network conditions tables or auto sense procedures, it is also possible that sending node may insert the security tags randomly or at a predetermined location or locations and then may send the packet with the security tag. In such cases, it is possible for the receiving node to check for security tags in packets and to drop packets, for example, when a valid security tag is not found within a predetermined number of packets or after a predetermined timeframe from the last valid security tag.

[0059] Although the sending node is shown as inserting a single security tags in each packet sent to the receiving node, it is contemplated that the sending node may select one or more of tag locations and may insert the security tag into the first packet, each packet or selected packets (periodically or pseudo-randomly) of the session according to network security levels indicated by receiving node 60.

[0060] Although verification of the security tag in placement locations is illustrated in a particular order (e.g., checking the IP option field, the TCP option field and then the payload), the verification may occur in any order. Moreover, the order of such checking may be based on any known network impediments.

[0061] Although various embodiments of the present invention have been described in terms of creating secure connections between nodes in a network, it is not limited thereto. The methods may be carried out between networks, for example, using any number of different protocols.

[0062] Although various embodiments of the present invention have been described in terms of messages being transmitted between client and server, it is not limited thereto. The identification techniques disclosed herein apply to communications transmitted with respect to a wide range of computer applications, and are not limited to server applications.

[0063] The terms message and communication as used herein are intended to refer to a broad class of transmissions carried out between computer systems or portions thereof; for example, inquiries, data updates, data edits, and data requests, among others.

[0064] As described herein, for example, the invention may be embodied in software, in a machine (e.g., a computer system, a microprocessor based appliance, etc.) that includes software in memory, or in a tangible computer storage carrier configured to carry out the protection scheme (e.g., in a self contained silicon device, a solid state memory, an optical disc, a magnetic disc, etc.). Further, when the invention is embodied in a remote system for a user to access a resource, the remote system is not limited to an application server, and the resource is not limited to an application on an application server. It is contemplated that the security system may be included in other layers of the network such as the network layer, or firewall layer of combinations of the other layers.

[0065] As described herein, the remote system may be any remotely accessible microprocessor based device (e.g., a PDA, a personal computer, a network server, etc.), and the resource may be any resource installed on (or accessible through a connection to) the remotely accessible device.

[0066] Although the invention is illustrated and described herein with reference to specific embodiments, the invention is not intended to be limited to the details shown. Rather, various modifications may be made in the details within the scope and range equivalents of the claims and without departing from the invention.

What is claimed:

1. A method for processing a security tag in each packet of a packetized communication, the packets being transmitted to a receiving node in a network, the security tag including information relating to at least a user, the method comprising the steps of:

selecting at least one placement location among a plurality of locations to embed the security tag in each packet of the packetized communication;

receiving, at the receiving node, each packet of the packetized communication, each packet having the security tag embedded at the selected placement location;

authenticating, at the receiving node, the embedded security tag in each packet; and

if a respective packet of the packetized communication is received by the receiving node without the security tag embedded in the selected placement location, preventing access by the respective packet which does not have the security tag embedded in the selected placement location to a secured resource.

2. The method according to claim 1, wherein the authenticating of the security tag in each packet of the packetized communication includes:

if a location placement message had been sent by the receiving node, checking a location in each packet of the packetized communication indicated by the location placement message for the security tag; and

determining if the security tag at the checked location is authentic.

3. The method according to claim 1, wherein the authenticating of the security tag in each packet of the packetized communication includes:

if the receiving node had not previously specify a fixed tag location, or if the receiving node is unable to locate the security tag in the fixed tag location, checking, by the receiving node, a size of one or both of: (1) an IP option field; or (2) a TCP option field of the respective packet of the packetized communication;

if the size of the IP option field or the TCP option field for the respective packet is greater than or equal to a size of the security tag embedded in the respective packet, determining for the option field or fields that are greater than or equal to the size of the security tag, if the security tag is embedded in the IP option field or TCP option field;

if the security tag is embedded in either the IP option field or the TCP option field, determining for each packet of the packetized communication if the security tag in the determined option field is authentic.

4. The method according to claim 3, wherein the authenticating of the security tag in each packet of the packetized communication further includes:

if the size of the IP option field and the TCP option field for the respective packet is less than the size of the security tag, checking a beginning and an ending of a payload field of the respective packet to determine whether the security tag is located therein; and

if the security tag is located in the beginning or the end of the payload field of the respective packet, determine for each packet of the packetized communication if the located security tag is authentic.

5. The method according to claim 1, wherein the authenticating of the security tag in each packet of the packetized communication includes:

quarantining each packet associated with an unauthenticated security tag; and

sending each packet associated with the unauthenticated security tag for analysis.

6. The method according to claim 1, further comprising:

passing, by the receiving node, each packet of the packet communication that is authenticated to the secured resource on the network.

7. The method according to claim 1, wherein the step of dropping the respective packet includes, if the security tag in the respective packet is not authenticated, preventing access by the respective packet having the security tag which is not authenticated to a secured resource.

8. The method according to claim 1, wherein the step of selecting the at least one placement location includes the steps of:

storing, in the receiving node, tag placement information based on network conditions that affect selection of the placement location of the security tag in accordance with address ranges of nodes in the network;

sending, by the receiving node to the sending node, the tag placement information indicating the network conditions that affect the selection of the placement location; and

establishing, by a sending node, the at least one placement location for each packet of the packetized communication based on the tag placement information associated with an address of the sending node.

9. The method according to claim 1, wherein the step of selecting the at least one placement location includes the steps of:

establishing, by the receiving node, the at least one placement location; and

transmitting, by the receiving node, a placement message indicating the at least one placement location of the security tag in each of the packetized communication packet.

10. The method according to claim 1, wherein the step of selecting the at least one placement location further includes:

receiving, by the receiving node from a sending node, a test packet having a plurality of security tags embedded in predetermined placement locations;

choosing, by the receiving node, one or more locations corresponding to one or more of the predetermined placement locations in the test packet where the security tags are to be embedded in each packet of the packetized communication; and

sending a placement message, from the receiving node to the sending node, that indicates the at least one placement location according to the chosen one or more predetermined placement locations.

11. A method for processing a security tag in each packet of a packetized communication, the packets being transmitted from a sending node in a network, the security tag including information relating to at least a user, the method comprising the steps of:

selecting at least one placement location among a plurality of placement locations to embed the security tag in each packet of the packetized communication;

inserting, by the sending node, the security tag at the selected at least one placement location for each packet of the packetized communication, as a tagged packet; and

transmitting, by the sending node, each tagged packet.

12. The method according to claim 11, wherein:

the step of selecting the at least one placement location includes the step of receiving, by the sending node, a placement message indicating one or more placement locations among the plurality of placement locations to insert the security tag; and

the step of inserting the security tag at the selected at least one placement location includes inserting the security tag in each tagged packet at the one or more placement locations indicated in the placement message.

13. The method according to claim 11, wherein the step of selecting the at least one placement location to embed the security tags includes:

establishing the at least one placement location as being in one or more of: (1) a transport payload portion of each packet; (2) a TCP option portion of each packet; or (3) an IP option portion of each packet.

14. A method for processing a security tag embedded in a plurality of packets of a packetized communication, the packets being transmitted from a sending node to a receiving node in a network, the security tag including security information regarding the packetized communication, the method comprising the steps of:

selecting a placement location among a plurality of placement locations to embed the security tag in each packet of the packetized communication;

authenticating, at the receiving node, each of the embedded security tags located at the selected placement location for the packets of the packetized communication; and passing packets that are authenticated to a secured resource on the network.

15. The method according to claim **14**, further comprising the step of:

preventing, by the receiving node, access by each respective packet of the packet communication to a secured resource: (1) if the respective packet does not have the security tag embedded at the selected placement location; or (2) if the respective packet has the security tag embedded at the selected placement location and the security tag is not authenticated.

16. The method according to claim **15**, further comprising: embedding the security tag at the selected placement location for each packet of the packetized communication sent by the receiving node in accordance with the placement location indicated in a placement message.

17. A sending node for transmitting packets toward a receiving node in a packetized communication network, comprising:

a placement determination unit for selecting at least one placement location among a plurality of placement locations for at least one security tag to be embedded in each of a plurality of packets of a packetized communication; an insertion unit for inserting the security tag at the at least one placement location for each of the packets, as tagged packets; and a transmission unit for transmitting the tagged packets from the sending node toward the receiving node.

18. The sending node according to claim **17**, wherein the sending node receives network conditions information associated with an address of the sending node to select the at least one placement location.

19. A receiving node for receiving packets sent by a sending node in a packetized communication network, comprising:

a receiving unit for receiving the packets from the sending node; and

a packet processor for authenticating, at the receiving node, a security tag embedded in each of the packets, wherein the packet processor prevents access by a respective packet of the packetized communication to a secured resource: (1) if the respective, received packet does not have the security tag embedded in a selected one of a plurality of placement locations or (2) if the security tag embedded at the selected one of the plurality of placement locations is not authenticated.

20. The receiving node according to claim **19**, further comprising:

a network conditions table for storing information indicating network conditions that affect selection of the placement locations for different ranges of addresses of nodes on the packetized communication network; and

a transmitting unit for sending, to the sending node, the network conditions table.

21. A computer readable storage medium for storing computer code to execute the method for processing a security tag in each packet of a packetized communication, the packets being transmitted to a receiving node in a network, the security tag including information relating to at least a user, the method comprising the steps of:

selecting at least one placement location among a plurality of locations to embed the security tag in each packet of the packetized communication;

receiving, at the receiving node, each packet of the packetized communication, each packet having the security tag embedded at the selected placement location;

authenticating, at the receiving node, the embedded security tag in each packet; and

if a respective packet of the packetized communication is received by the receiving node without the security tag embedded in the selected placement location, preventing access by the respective packet which does not have the security tag embedded in the selected placement location to a secured resource.

* * * * *