


Exhibit 1006



(12) **Patent Application Publication**
McCormack et al.

(43) **Pub. Date:** **Jul. 29, 2010**

(60) Provisional application No. 61/059,723, filed on Jun. 6, 2008, provisional application No. 61/109,776, filed on Oct. 30, 2008, provisional application No. 61/169,601, filed on Apr. 15, 2009.

Publication Classification

(51) **Int. Cl.**
A61B 17/00 (2006.01)
A61B 17/56 (2006.01)
A61F 2/44 (2006.01)

(52) **U.S. Cl.** **606/83**; 606/86 A; 606/90; 623/17.11

(57) **ABSTRACT**

A spinal joint distraction system for treating a facet joint including articular surfaces having a contour is disclosed and may include a delivery device including a generally tubular structure adapted to engage a facet joint, an implant adapted to be delivered through the delivery device and into the facet joint, the implant comprising two members arranged in opposed position, and an implant distractor comprising a generally elongate member adapted to advance between the two members of the implant causing separation of the members and distraction of the facet joint, wherein the implant is adapted to conform to the shape of the implant distractor and/or the articular surfaces of the facet upon being delivered to the facet joint. Several embodiments of a system, several embodiments of an implant, and several methods are disclosed including a method for interbody fusion.

Correspondence Address:


DORSEY & WHITNEY, LLP
INTELLECTUAL PROPERTY DEPARTMENT
370 SEVENTEENTH STREET, SUITE 4700
DENVER, CO 80202-5647 (US)


(21) Appl. No.: 12/653,283


(22) Filed: **Dec. 10, 2009**

Related U.S. Application Data

(63) Continuation-in-part of application No. 12/455,814, filed on Jun. 5, 2009, which is a continuation-in-part of application No. 12/317,682, filed on Dec. 23, 2008.





**FIG.1A**




FIG. 2




FIG. 3




FIG. 4




FIG.5




FIG.6









FIG. 6A














FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 16A




FIG. 16B








FIG. 17






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 23A




FIG. 24




FIG. 24A





FIG. 25






FIG.27




FIG.28




FIG.29




FIG.30




FIG.31




FIG.32




FIG.33




FIG.34






FIG.35




FIG.36




FIG. 37A




FIG. 37B




FIG. 37C







FIG. 37D






FIG. 39A




FIG. 39B

FIG. 39C





FIG. 39D




FIG. 40A




FIG. 40B








FIG. 40C






FIG. 42A




FIG. 42B




FIG. 42C





FIG. 42E




FIG. 42F




FIG. 43A




FIG. 43B





















FIG. 43C



















FIG. 50A




FIG. 50B




FIG. 51A



















FIG. 51B



















FIG. 58A




FIG. 58B




FIG. 59A




FIG. 59B




FIG. 60A




FIG. 60B




FIG. 61A




FIG. 61B




FIG. 61C




FIG. 62A




FIG. 62B







FIG. 62C






FIG. 64A




FIG. 64B







FIG. 64C






FIG. 66A




FIG. 66B




FIG. 66C




FIG. 67A




FIG. 67B




FIG. 67C




FIG. 68A




FIG. 68B







FIG. 68C






FIG. 70A




FIG. 70B








FIG. 70C






FIG. 72A




FIG. 72B




FIG. 72C




FIG. 73A




FIG. 73B




FIG. 73C




FIG. 74A




FIG. 74B




FIG. 74C




FIG. 75A




FIG. 75B




FIG. 76A




FIG. 76B




FIG. 76C




FIG. 77A




FIG. 77B







FIG. 77C






FIG. 79A




FIG. 79B








FIG. 79C






FIG. 81A




FIG. 81B




FIG. 81C




FIG. 82A




FIG. 82B







FIG. 82C






FIG. 83A




FIG. 83B




FIG. 84A




FIG. 84B




FIG.85




FIG. 86




FIG. 87




FIG. 88




FIG. 89




FIG. 90







FIG. 91








FIG. 95B




FIG. 96

FIG. 97




FIG. 98




FIG. 99




FIG. 99B




FIG. 99A




FIG. 99C









FIG. 99D










FIG.109








FIG. 110








FIG. 117




FIG. 118




FIG. 119









FIG. 120

















FIG.126




FIG. 126A





FIG. 126B







FIG. 127A






FIG. 129




FIG. 130




FIG. 131




FIG. 132







FIG. 132A






FIG. 134




FIG. 134A




FIG. 135A




FIG. 135B





FIG. 135






FIG.137







FIG. 138






FIG. 140




FIG. 141




FIG. 142






FIG. 143








FIG. 146








FIG. 149




FIG.150




FIG. 151





FIG. 152








FIG. 154








FIG. 157




FIG. 158




FIG.159




FIG. 160C




FIG. 160A




FIG. 160B




FIG. 161A




FIG. 161B




FIG.162

(all measurements in mm unless noted)

Implant

Plate thickness	0.38
A-P length	12.3
Width 1 (outside teeth)	5.5
Width 2 (inside teeth, at vertical)	4.8
Width 3 (inside teeth, at base)	4
Closed height 1 (incl. teeth)	2.3
Closed height 2 (at volcano)	2.3
Closed height 3 (plates only)	0.76
Fully Deployed max height 1 (incl. teeth)	5
Fully Deployed max height 2 (at volcano)	4.4
Fully Deployed max height 3 (plates only)	3.1
Fully Deployed plate angle (estimate)	10 deg
Screw slot width	0.85
Screw slot length	2.95
Tooth height (from plate surface)	0.75
Tooth thickness	0.38
Scissor joint height	1.34

FIG.163**Delivery Device**

Main shaft outside diameter	9
Overall length	267
exposed shaft length	222
Fork outside width	8
Fork width at tip	7
Fork inside gap	6
Fork arm width	1
Fork tip height	1.5
Distance, from Fork arm tip to 4mm height spot	12.5
Fork arm taper angle, from arm tip to 4mm height spot	10
Distance, from 4mm height spot on Fork arm to full 9mm dia.	2.5
Fork shoulder curvature angle (approx.)	37 deg.
Fork serration depth	0.25
Square opening height	5
Square opening width	6

FIG.164**Implant Distractor**

Shaft diameter (max)	2.2
Max diameter (incl. thread)	3.8
A-P length	13
Head diameter	12.25
Head height	2.5
Driver slot width	1
Driver slot depth	1.5
Thread pitch	2
Thread height (approx)	0.8
Tip taper angle (approx. at tip)	8 deg

FIG.165**Chisel**

Width	5.5
Height	4.25
Length	300
Tip thickness (at end)	0.4
Tip thickness (at start of main taper)	1.85
Tip chamfer angle	60 deg
Tip taper angle	10 deg
Tip Length (from distal end to main shaft)	12
Serration depth	0.4
Serration width	0.6
Lateral orientation marker dia.	2
Proximal hole dia.	3
Proximal shaft protrusion	12
Pry bar slot width	10
Pry bar slot height (combined with Guide Tube Handle slot)	2

FIG.166**Place Holding Chisel**

Width	5.5
Height	4.25
Length	300
Tip marker dia.	0.5

(Other features same as Chisel)

FIG.167

(all measurements in mm unless noted)

Driver Assembly

Main shaft outside diameter	5.5
Main shaft inside diameter	4
Overall length	320
Holder arm outside width	5.5
Holder arm width (avg)	0.77
Holder arm tip height	1
Holder arm height at Implant stop	1.9
Distance, from Holder arm tip to Implant stop	5.4
Holder arm taper angle, from arm tip to implant stop (incl)	10
Distance, from implant stop to full 5.5mm dia.	3.2
Holder tip shoulder curvature angle (approx.)	22 deg
Implant retention pin dia. (max)	1
Implant retention pin height	0.4
Screwdriver shaft diameter	3.8
Screwdriver blade thickness (avg)	1
Screwdriver knob diameter	28
Screwdriver knob height	18
Handle width	44
Handle thickness	14
Handle height (with "cage")	57

FIG.168

Decorticator


Blade outside diameter	10.5
Blade wall thickness	0.7
Blade inside diameter	9.2
Blade length	140
Blade tip angle	60 deg
Tooth height	2.4
Tooth angle (incl)	18 deg
Handle diameter (round side)	25
Handle length (straight side)	10
Handle height	8
Handle distal taper	45 deg
Handle thickness (straight side)	7.25

FIG.169

Malleting Tool

Length	160
Handle length	117
Handle cross section	10x10
Head length	43
Head outside width	30
Head U-slot width	9.5

FIG.170







FIG. 172






FIG. 174




FIG.175




FIG.176




FIG.177




FIG.178




FIG. 179




FIG. 180




FIG. 181




FIG. 182




FIG. 183




FIG. 184




FIG. 185

VERTEBRAL JOINT IMPLANTS AND DELIVERY TOOLS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to, and is a continuation-in-part ("CIP") application of, U.S. patent application Ser. No. 12/455,814, which was filed on Jun. 5, 2009, is entitled Facet Joint Implants and Delivery Tools and claims priority to: U.S. Provisional Application No. 61/059,723, which was filed on Jun. 6, 2008 and is entitled Spine Distraction Device; U.S. Provisional Application No. 61/109,776, which was filed on Oct. 30, 2008 and is entitled Facet Joint Implants; and U.S. Provisional Application No. 61/169,601, which was filed on Apr. 15, 2009 and is entitled Facet Joint Implants and Delivery Tools. The 12/455,814 application also claims priority to, and is a CIP application of, U.S. patent application Ser. No. 12/317,682, which was filed on Dec. 23, 2008, is entitled Facet Joint Implants and Delivery Tools, and claims priority to Provisional Applications 61/059,723 and 61/109,776. The contents of all of the above-mentioned patent applications are all hereby incorporated by reference herein in their entireties.

FIELD OF THE INVENTION

[0002] The following detailed description relates to a device for distracting the spine. More particularly the description relates to a tool for distracting a facet joint of the spine and an implant for maintaining the distracted position of the joint. More particularly the description relates to an implant that may be used together with a tool to distract a facet joint, the implant remaining in place separated from the tool. In some instances, the implant itself may extract the joint.

BACKGROUND

[0003] Chronic back problems cause pain and disability for a large segment of the population. Adverse spinal conditions may be characteristic of age. In particular, spinal stenosis (including, but not limited to, central, canal, and lateral stenosis) and facet arthropathy may increase with age. Spinal stenosis results in a reduction of foraminal area (i.e. the available space for the passage of nerves and blood vessels), which may compress cervical nerve roots and cause radicular pain. Both neck extension and ipsilateral rotation, in contrast to neck flexion, may further reduce the foraminal area and contribute to pain, nerve root compression, and neural injury.

[0004] Cervical disc herniations may be a factor in spinal stenosis and may predominantly present upper extremity radicular symptoms. In this case, treatment may take the form of closed traction. A number of closed traction devices are available that alleviate pain by pulling on the head to increase foraminal height. Cervical disc herniations may also be treated with anterior and posterior surgery. Many of these surgeries are performed through an anterior approach, which requires a spinal fusion. These surgeries may be expensive and beget additional surgeries due to changing the biomechanics of the neck. There is a three percent incidence of re-operation after cervical spine surgery. Moreover, these surgeries may be highly invasive leading to long recovery times.

[0005] There is a need in the art for a device and procedure to increase foraminal height to reduce radicular symptoms of patients suffering the effects of spinal stenosis. There is also

a need for the device to be adapted to allow for the procedure to be minimally invasive and to avoid modifying the biomechanics of the spine.

SUMMARY OF THE INVENTION

[0006] In one embodiment, a spinal joint distraction system may include a driver assembly including a tubular shaft having a longitudinal axis and a pair of implant holder arms positioned on a distal end of the tubular shaft, where the arms are configured to hold a spinal implant. In another embodiment, the driver assembly may also include an implant distractor positioned along the longitudinal axis near the distal end of the tubular shaft, an internal actuator positioned within the tubular shaft and adapted to advance the implant distractor, and a distractor knob adapted to control the internal actuator. In another embodiment, the system may also include a delivery device with a tubular shaft, a receiving assembly positioned on a proximal end of the tubular shaft, and a pair of forks extending from a distal end of the tubular shaft, where the may be adapted to penetrate a facet joint and the delivery device may be adapted to slidably receive the driver assembly. In some embodiments, the system may include an implant adapted for holding by the implant holding arms of the driver assembly. In some other embodiments, the system may include a chisel with a shaft portion, a tip at a distal end of the shaft, and a head at a proximal end of the shaft, where the delivery device is adapted to receive the chisel, and the head of the chisel is adapted to be tapped by a driving member to insert the tip of the chisel into a facet joint. In still other embodiments, the system may include an injector with a cannula with a closed distal end and two exit doors positioned on opposite sides of the distal end, a plunger with a seal positioned within the cannula, a stop disc at a proximal end of the cannula, and a handle positioned on a proximal end of the plunger, where the delivery device is further adapted to receive an injector.

[0007] In another embodiment, the internal actuator may be a stand alone device insertable into the driver assembly. In another embodiment, the internal actuator may include a handle and an internal rod, the internal rod being adapted to hold an implant distractor, and the handle being configured to release the implant distractor. In another embodiment, the system may include a collet positioned on a distal end of the internal rod, the collet adapted to securely hold the implant distractor.

[0008] In another embodiment, a spinal distraction implant may include an upper member and a lower member, the upper and lower member being generally rectangular and each having a distal edge, a proximal edge, and two parallel lateral edges, the upper and lower member positioned adjacent and substantially parallel to each other and having an inner surface and an outer surface, the distal edges of the upper and lower member connected to each other and the proximal edges adapted to receive an implant distractor, and teeth positioned along the lateral edges of at least one of the upper or lower member and extending outwardly. In another embodiment, the implant may include flanges extending substantially orthogonally from a proximal end of the upper and lower members. In some embodiments, the flanges may include openings for receiving anchors to anchor the implant to a lateral mass of a facet joint. In another embodiment, the implant may include a truncated threaded slot adapted to engage a cross-cut thread feature of an implant distractor. In

another embodiment, the upper and lower members may each include an interlocking scissor feature.

[0009] In another embodiment, a method of distracting a facet joint of the spine may include inserting a delivery device to access the facet joint of a patient, inserting a driver assembly holding an implant into the delivery device, and actuating the driver assembly thereby distracting the implant.

[0010] In another embodiment, a spinal distraction implant may include an upper member, a lower member, and a proximal member, the upper and lower members being generally rectangular and each having a distal edge and two parallel lateral edges, the upper and lower members extending generally continuously into each other to form the proximal member, the upper and lower member positioned adjacent and substantially parallel to each other and having an inner surface and an outer surface, the proximal member being generally perpendicular relative to the upper and lower members, at least one of the upper and lower members further including threaded slots adapted to receive threads of an implant distractor and outwardly extending teeth positioned along the lateral edges of at least one of the upper or lower members. In another embodiment, the proximal member may include a penetration for receiving an implant distractor.

[0011] In another embodiment, a spinal distraction implant may include a threaded bolt with a proximal end terminating in a head, a proximal non-threaded block positioned along the bolt and abutting the head of the bolt, a distal threaded block positioned a distance away from the proximal threaded block, and a plurality of expansion members positioned between the proximal and the distal threaded blocks. In one embodiment, the plurality of expansion members may be V-shaped members. In another embodiment, the plurality of V-shaped members may be adapted to deformably flatten out and expand laterally when compressed between the distal and proximal blocks. In another embodiment, the plurality of expansion members may be planar plates with slotted holes such that when freely positioned on the bolt, the plates are positioned in a skewed position relative to a longitudinal axis of the bolt. In another embodiment, the planar plates may be adapted to engage one another and thus position themselves perpendicular to the bolt when compressed between the distal and proximal blocks.

[0012] In another embodiment, a spinal distraction implant may include a pair of stacked structures separated by a sloping plane, the structures having an engagement surface along the plane including ratchet teeth. In one embodiment, a first structure of the pair of stacked structures increases in thickness in a proximal direction and a second structure of the pair of stacked structures increases in thickness in a distal direction.

[0013] In another embodiment, a spinal distraction implant may include a generally tapered shaft in the form of a screw, the shaft defining a longitudinal axis and having a length, the shaft having threads along an outer surface for engaging articular surfaces of a facet joint. In one embodiment, the threads may be notched along the length of the implant creating serrations for cutting into the articular surfaces of a facet joint. In another embodiment, the threads may include leaf springs for preventing backing out of the implant. In another embodiment, the threads may have a T-shaped cross-section. In another embodiment, the implant may include a relatively broad head with a decorticating feature on a distal surface thereof. In another embodiment, the decorticating feature may include tabs projecting distally from the head. In another

embodiment, the decorticating feature may include spurs. In another embodiment, the head may be in the form of a floating collar and be free to pivot about the longitudinal axis of the implant in a ball and socket type fashion. In another embodiment, the implant may include a torque limiting mechanism. In another embodiment, the shaft may include a hollow cavity and take the form of a cone, the cone being made from a relatively malleable material, the implant further including an inner core support member for use when inserting the implant and for removal once the implant is in place. In still another embodiment, the generally tapered shaft may be a first tapered shaft and the implant may also include a second generally tapered shaft in the form of a screw where the second generally tapered shaft may be positioned adjacent to the first generally tapered shaft and have communicative threaded serrations such that when one shaft is rotated, the other shaft rotates in the opposite direction. In another embodiment, the implant may include an arm type locking mechanism, the arm being biased in a distal direction such that when implanted the arm provides a biasing force to maintain friction on the threads. In another embodiment, the arm may have engaging teeth. In another embodiment, the implant may include flaps extending from the head of the shaft and including teeth for engaging a lateral mass of a facet joint.

[0014] In another embodiment, a spinal distraction implant may include a plate and a orthogonally positioned bumper, the superior aspect of the bumper having a rounded surface for opposing the lateral mass of a superior vertebra, the implant including an anchoring screw for securing the implant to a lateral mass of a facet joint.

[0015] In another embodiment, a spinal distraction implant may include a wedge insertable between facet surfaces, the wedge having teeth on at least one of an anterior and inferior surface thereof. In another embodiment, the implant may also include a diagonally placed anchor screw positioned through the implant for advancing into the surface of a facet joint.

[0016] In another embodiment, a spinal distraction implant may include an anterior hook, a posterior hook, and a bolt joining the anterior and posterior hook. In another embodiment, the anterior hook may be C-shaped with a lip and the posterior hook may be S-shaped with a lip, the anterior hook adapted to engage the anterior aspect of the inferior facet and the posterior hook adapted to engage the posterior aspect of the posterior facet.

[0017] In another embodiment, a spinal distraction implant may include an insert and tabs positioned to extend orthogonally from a proximal end of the insert. In one embodiment, the insert may be rectangular and the tabs may have holes for receiving an anchor.

[0018] In another embodiment, a spinal distraction implant may include a collapsible diamond shaped structure including two opposing threaded corners, and two opposing non-threaded corners including pads. The implant may also include a bolt threaded through the threaded corners of the diamond shaped structure, where actuating the bolt draws the threaded corners together and extends the non-threaded corners.

[0019] In another embodiment, a spinal distraction implant may include an upper member, a lower member, a hinge connecting the upper member to the lower member, and a brace member for maintaining the implant in an open position.

[0020] In another embodiment, a spinal distraction implant may include a generally cylindrically shaped member including at least two sections separated by a slot, the sections connected together at distal ends to form a tip, the member adapted to receive a screw to cause it to expand, and the outer surface of the sections including teeth for engaging articular surfaces of a facet joint.

[0021] In another embodiment, a method of securing a superior vertebra may include applying a force to the superior vertebra to increase the foraminal area between the superior vertebra and an inferior vertebra and placing an angled screw through a superior facet, through a facet capsule, and into an inferior facet.

[0022] In another embodiment, a spinal distraction implant may include a collapsible triangular shaped implant including a central shaft and at least two springing leaves connected to the distal end of the shaft, extending proximally along the shaft, and biased in a direction to form an arrow shape, where the implant may be collapsed within a tube and delivered to a site where the tube is removed and the implant is allowed to expand.

[0023] In another embodiment, a spinal distraction implant may include a facet spacer plate and screw, wherein the screw may be inserted diagonally through a facet surface to engage the facet spacer plate thereby forcing separation of a facet joint. In another embodiment, the spacer may have a C-shape and the screw may pass through the spacer plate prior to entering the spinal structure.

[0024] In another embodiment, a spinal distraction implant may include a first bracket, second bracket, and a bolt extending between the brackets, where the brackets are adapted to separate when the bolt is turned. In another embodiment, the first and second brackets may be adapted to be attached to a lateral mass of a facet joint. In yet another embodiment, the first and second brackets may include a leg adapted to be inserted into a facet joint.

[0025] In another embodiment, a spinal distraction implant may include a triangular shaped wedge, an anchor screw positioned diagonally through the wedge, and a malleable flap extending from the wedge including teeth for engaging a lateral mass of a facet joint.

[0026] In another embodiment, a spinal distraction implant may include an anchoring plug, an expandable plate, and two external plates, where securing the external plates to a lateral mass of a facet joint and inserting the anchoring plug causes the facet joint to separate.

[0027] In another embodiment, a spinal distraction implant may include a delivery system and at least two nitinol hooks, where the hooks may be flattened and inserted with the delivery system and once in place may be allowed to assume their pre-flattened shape.

[0028] In another embodiment, a spinal distraction implant may include a hollow screw sleeve having barbs adapted to be ejected from a retracted position and a wedge adapted to be inserted in the hollow screw sleeve to eject the barbs.

[0029] In another embodiment, a spinal distraction implant may include a collapsible nut positioned over a bolt, the bolt defining a longitudinal axis, where advancing the bolt may cause the nut to collapse along the longitudinal axis in an accordion shape, thereby expanding laterally.

[0030] In another embodiment, a spinal distraction implant may include a collapsible plate positioned over a bolt, the bolt defining a longitudinal axis, where advancing the bolt causes

the plate to collapse along the longitudinal axis in an accordion shape, thereby expanding laterally.

[0031] In another embodiment, a spinal distraction implant may include a wire surrounding a block in a helical fashion, the wire adapted to contract and expand laterally when pulled taught or released respectively.

[0032] In another embodiment, a spinal distraction implant may include an outer housing and an internal spring, where the housing may be biased to be in a laterally broad position when the spring is in a neutral position.

[0033] In another embodiment, a spinal distraction implant may include a pair of stacked structures separated by a sloping plane and a fastener positioned at an angle through the pair of structures thereby preventing relative movement along the plane.

[0034] In another embodiment, a spinal distraction implant may include a collapsible cylinder with side cutouts, the cylinder made from a resilient elastic material.

[0035] In another embodiment, a spinal distraction implant may include a distal tip of a delivery tool, where the tip is adapted to distract a facet joint and detach from the delivery tool.

[0036] In another embodiment, a spinal distraction implant may include a housing, a central gear rotatably positioned within the housing, and two plates slidably positioned in the housing and positioned opposite one another adjacent to the central gear and including teeth for engaging the gear, where rotating the gear slidably extends the plates beyond an outer surface of the housing in opposite directions.

[0037] In another embodiment, a spinal distraction implant may include a triangularly bent plate with a first and second bracket on each side, the first bracket adapted to receive an anchor screw and the second bracket including teeth for biting into a lateral mass of a facet joint.

[0038] In another embodiment, a spinal distraction implant may include a rotatable cone with a longitudinal axis including a shoulder with a ledge defining a cam surface and an anchor screw, where the shoulder is adapted to be inserted into a facet joint and the implant rotated to cause a superior facet to ride upward along the cam surface and distract the joint, wherein the screw may be advanced to secure the implant.

[0039] In another embodiment, a spinal distraction implant may include a housing with penetrations for ejection of spikes, internal spikes positioned with the housing and in alignment with the penetrations, and an internal wire routed through the spike positions, where pulling the wire taught forces the spikes from the housing to engage articular surfaces of a facet joint.

[0040] In another embodiment, a spinal distraction implant may include a housing, a cavity within the housing, penetrations on lateral surfaces of the housing extending from the cavity through the wall of the housing, spikes positioned to be ejected through the penetrations, the spikes having a beveled inner surface, and a piston having a torpedo shaped distal end positioned within the cavity, where advancing the piston engages the torpedo shaped distal end with the beveled inner surface of the spikes causing them to eject through the penetrations and engage articular surfaces of a facet joint.

[0041] In another embodiment, a spinal distraction implant may include two parallel equal length side bars and at least two struts pivotably positioned between the side bars at each end, the struts having textured surfaces on each end thereof, where the struts may be pivoted to lie in plane with and

parallel to the side bars and once in position in a facet joint, may be pivoted substantially perpendicular to the side bars to distract the facet joint.

[0042] In another embodiment, a spinal joint distraction system may include a delivery device with a tubular shaft, a receiving assembly positioned on a proximal end of the tubular shaft and including a seating cavity, and a pair of forks extending from a distal end of the tubular shaft, the forks adapted to penetrate a facet joint. The system may also include a chisel including a shaft with a chamfered tip, the chisel being adapted for slidable insertion through the delivery device. The system may further include a decorticator sleeveably positioned on the tubular shaft of the delivery device, the decorticator including a tubular shaft portion with a chamfered distal end, a plurality of serrated teeth at the distal tip of the chamfered end, a beveled edge extending along the periphery of the chamfered distal end, and a handle positioned on the proximal end of the tubular shaft portion, the handle having a bore adapted to receive a gripping tool and a threaded bore for receiving a set screw. The system may also include a driver assembly adapted for slidable insertion through the delivery device, the driver assembly including an implant shaft, a handle positioned on the proximal end of the implant shaft, and implant holding arms extending from the distal end of the implant shaft. The system may also include an internal actuator adapted for slidable insertion through the driver assembly and further adapted to advance an implant distractor, the internal actuator including a longitudinal shaft, a handle positioned on the proximal end of the longitudinal shaft and adapted to rotatably advance the implant distractor, and an internal rod including an engagement feature adapted to secure the implant distractor. The system may further include an injector adapted for slidable insertion through the delivery device, the injector including a longitudinal delivery shaft, a seating feature positioned around the shaft, and a plunger adapted to pass through the longitudinal delivery shaft causing ejection of material from the distal end of the longitudinal delivery shaft.

[0043] In another embodiment, a spinal joint distraction system may include a delivery device with a decorticator sleeveably positioned thereon, a chisel adapted for insertion through the delivery device, a driver assembly adapted for insertion through the delivery device and further adapted to hold an implant, an internal actuator adapted for insertion through the driver assembly and adapted to deliver and advance an implant distractor thereby distracting the implant, and an injector adapted for insertion through the delivery device and further adapted to deliver flowable material to or around the joint.

[0044] In another embodiment, a spinal distraction implant may include an upper member and a lower member each with a distal end, the distal end of the lower member coupled to the distal end of the upper member, and an implant distractor adapted to be advanced between the upper and lower member and separate the upper and lower members causing the upper and lower member to pivot relative to one another about their respective distal ends.

[0045] In another embodiment, a spinal distraction implant may include an upper member and a lower member each including a distal edge, a proximal edge, and two parallel lateral edges, the edges defining a generally rectangular shape, an inner surface, an outer surface, a threaded slot passing through the member from the inner surface to the outer surface, a truncated threaded slot passing through the

member from the inner surface to the outer surface, a plurality of teeth spaced along the two parallel lateral edges, a guide feature positioned on the proximal edge, and an interlocking scissor feature positioned on the distal edge. The implant may also include an implant distractor including a cylindrical body tapering to a point at a distal end, a coil shaped thread feature having an abrupt proximal end and being interrupted by at least one cross-cut, and an annular stop ring; wherein the upper and lower members may be pivotally coupled to one another via their respective interlocking scissor features, the respective guide features on the upper member and the lower member may oppose one another and may be adapted to receive and guide the distal end of the implant distractor between the upper and lower members, the respective threaded slots on the upper and lower member may be adapted to receive the coil shaped thread feature, and the respective truncated threaded slots may be adapted to engage the abrupt proximal end or the at least one cross-cut of the coil-shaped thread feature.

[0046] In another embodiment, a method of distracting a facet joint of the spine may include dilating a path to a facet joint using a dilator set, inserting a chisel into the facet joint, advancing a delivery device over the chisel and inserting forks of the delivery device into the facet joint, removing the chisel from the joint, inserting a driver assembly with an implant into the delivery device, seating the driver assembly in the delivery device thereby positioning the implant between the forks of the delivery device and in the facet joint, inserting an internal actuator into the driver assembly and advancing an implant distractor into the implant thereby distracting the implant, actuating a button on the internal actuator thereby releasing a grip on the implant distractor and removing the internal actuator and the driver assembly, and inserting an injector and injecting a flowable material into or around the facet joint.

[0047] In another embodiment, a method of distracting a facet joint of the spine may include inserting a chisel into a facet joint to provide initial distraction and decorticate the surface of the joint, inserting a delivery device over the chisel to maintain the initial distraction, inserting an implant through the delivery device and into the joint, the implant having teeth adapted to engage the surfaces of the joint, distracting the implant by advancing an implant distractor, the implant distractor having a coil-shaped thread feature for engaging threaded slots of the implant, the implant distractor further having cross-cut threads for engaging truncated threaded slots on the implant, wherein, advancing the implant distractor includes causing the cross-cut threads to engage the truncated threaded slots and prevent backing out of the implant, and releasing the implant distractor and removing the delivery device thereby leaving the implant and the implant distractor in place in the joint.

[0048] In another embodiment, a spinal joint distraction system may include a delivery device, a driver assembly adapted for insertion through the delivery device and further adapted to hold an implant, and an internal actuator adapted for insertion through the driver assembly and adapted to deliver and advance an implant distractor thereby distracting the implant.

[0049] In another embodiment, a spinal joint distraction system may include a driver assembly adapted to hold an implant and an internal actuator adapted for insertion through the driver assembly and adapted to deliver and advance an implant distractor thereby distracting the implant.

[0050] In another embodiment, a spinal joint distraction system may include an implant, an implant distractor adapted to engage the implant, and an internal actuator adapted to advance the implant distractor thereby distracting the implant.

[0051] In another embodiment, a method of distracting a facet joint of the spine may include inserting a delivery device into a facet joint, inserting an implant through the delivery device and into the joint, and distracting the implant by advancing an implant distractor.

[0052] In another embodiment, a method of distracting a facet joint of the spine may include partially engaging an implant distractor with an implant and engaging the implant distractor with an internal actuator to form an assembly, inserting the implant portion of the assembly into the facet joint, and distracting the facet joint.

[0053] In another embodiment, a spinal distraction implant may include an upper member and a lower member each with a distal end, the distal end of the lower member coupled to the distal end of the upper member, wherein the upper member and lower member each comprise a plurality of threaded slots adapted to engage an implant distractor.

[0054] In another embodiment, a spinal distraction implant may include an upper member and a lower member each with a distal end, the distal end of the lower member including an interlocking scissor feature coupled to a corresponding interlocking scissor feature included on the distal end of the upper member.

[0055] In another embodiment, a spinal distraction implant comprising an upper member and a lower member, each with a distal end, the distal end of the lower member coupled to the distal end of the upper member, wherein the implant is adapted to receive an implant distractor between the upper and lower member.

[0056] In another embodiment, a spinal distraction implant may include an upper member and a lower member, the upper member and lower member coupled at respective distal ends, the upper and lower members being biased toward a position parallel to one another.

[0057] In another embodiment, a spinal joint distraction system for treating a facet joint including articular surfaces having a contour can include a delivery device including a generally tubular structure adapted to engage a facet joint, an implant adapted to be delivered through the delivery device and into the facet joint, the implant comprising two members arranged in opposed position, and an implant distractor comprising a generally elongate member adapted to advance between the two members of the implant causing separation of the members and distraction of the facet joint, wherein the implant is adapted to conform to the shape of the implant distractor upon being delivered to the facet joint. The system can also include a driver assembly adapted to hold the implant and advance the implant distractor and the driver assembly can further be adapted for insertion through the delivery device. The system can also include a chisel adapted for insertion through the delivery device to facilitate initial engagement with the facet joint and a decorticator can be provided for lateral engagement with the delivery device. A malleting tool can be included with a first end adapted to engage the decorticator for a malleting process and a second end adapted to facilitate separation of parts of the system and an injector can be provided and adapted for insertion through the delivery device and further can be adapted to deliver a bone paste.

[0058] In another embodiment, a spinal joint distraction system can include a delivery device and chisel assembly adapted to engage a facet joint and a driver assembly adapted to hold and distract an implant, where the driver assembly can be adapted for insertion through the delivery device to deliver and distract the implant. The system can also include a place holding chisel adapted to replace the chisel and maintain the established position of the delivery device and chisel assembly. The delivery device can include a tubular shaft and a receiving assembly positioned on a proximal end of the tubular shaft and the chisel of the assembly can include a handle having a connection feature adapted to engage the receiving assembly. The connection feature can include a protrusion or recess adapted to form a detent relationship with an opposing protrusion or recess respectively. In another embodiment, the connection feature can include a latch type feature positioned on a deflectable portion of the handle, wherein advancing the chisel handle toward the receiving assembly causes the latch type feature to snap into place and depressing the deflectable portion of the handle releases the latch type feature. The receiving assembly can include a malleting anvil positioned on a proximal face of the receiving assembly and the chisel can include a slot cavity adapted to receive the malleting anvil and a malleting head adapted to engage the malleting anvil to resist relative motion between the delivery device and the chisel during malleting. The delivery device of the assembly can include forks adapted to penetrate the facet joint and it can also include a bull nose positioned on the surface of the forks near the intersection of the forks with the tubular structure, where the bull nose can be adapted to mark the position of the delivery device. The system can also include an indication hole positioned along the lateral side of the delivery device near the intersection of the forks and the tubular structure. The driver assembly can include an implant shaft having a diameter substantially equal to or less than a width of the implant and can also include a handle with a malleting bar adapted to transfer malleting blows to the driver assembly. The driver assembly can also include a slot cavity having a bearing surface where the slot cavity can be adapted to receive the malleting anvil of the receiving assembly and the bearing surface can be adapted to engage the malleting anvil to resist relative motion between the delivery device and the driver assembly during malleting. A decorticator can also be provided and can be adapted for positioning upon the delivery device from a lateral side of the delivery device. The decorticator can include a U-shaped longitudinally extending member with teeth on a distal end and it can include a malleting element at a proximal end adapted to distribute malleting blows to the longitudinally extending member. The driver assembly can include arms adapted to hold an implant and the arms can be positioned within a boundary defined by a width of the implant.

[0059] In another embodiment, a spinal distraction implant for the distraction of a facet joint having articular surfaces can include a first and a second member arranged in opposing position. Each of the first and second member can include a threaded slot passing through the member adapted to receive a thread feature and a plurality of teeth spaced along two parallel lateral edges, the teeth adapted to engage the articular surfaces of the facet joint, where the implant is constructed from a malleable material and is further adapted to conform to the shape of the articular surfaces upon being distracted within a facet joint. The plurality of teeth can have a linearly sloped distal face and a proximal face positioned orthogonally to the

respective first or second member and the teeth can be equally spaced. The first and second members can each have an interlocking engagement feature on respective distal edges, wherein the first and second members engage one another via their respective interlocking engagement features. The first and second members can also be coupled together via a weld.

[0060] In another embodiment, a method of distracting a facet joint and a contralateral facet joint of a spine can include inserting a delivery device and chisel assembly into the facet joint, removing the chisel from the assembly and replacing the chisel with a place holding chisel, removing the delivery device from the facet joint, inserting the delivery device and chisel assembly into the contralateral facet joint, removing the chisel from the assembly, placing and distracting a first implant in the contralateral facet joint, removing the delivery device from the contralateral facet joint, placing the delivery device back in the facet joint via the place holding chisel, placing and distracting a second implant in the facet joint. The place holding chisel can be a radiolucent chisel and the method can also include performing lateral fluoroscopy to determine proper placement of the first implant.

[0061] In another embodiment, a method of distracting a facet joint of the spine can include inserting a delivery device and chisel assembly into the facet joint to provide initial distraction and decorticate the surface of the joint, removing the chisel assembly from the delivery device, inserting a driver assembly through the delivery device, the driver assembly holding an implant and further comprising an implant distractor adapted to distract the implant, distracting the implant, and removing the driver assembly and the delivery device. The method can also include positioning the delivery device and chisel assembly by selectively malleting a proximal end thereof and/or selectively malleting a proximal end of the driver assembly. A decorticator can be positioned on the delivery device from the lateral side of the device and the method can include advancing the decorticator along the length of the driver assembly, positioning a malleting tool against the proximal end of the decorticator, and malleting the malleting tool to forcibly advance the decorticator and decorticate the lateral mass of the facet joint. The decorticator can be retracted, rotated, and re-advanced to a new position for malleted with the malleting tool to decorticate a different location. Intra-operative patient symptom feedback can also be obtained.

[0062] In another embodiment, a spinal distraction implant delivery tool can include an implant and an assembly, where the assembly includes a means for holding the implant, a means for positioning the implant within a facet joint, and a means for distracting the implant. The implant can include a first substantially planar member and a second substantially planar member arranged in parallel and opposing position to the first substantially planar member and a biasing connection connecting the first and second planar members to one another, the biasing connection adapted to create a biasing force directed toward biasing the members toward the parallel and opposing position. The means for holding can include a pair of implant holding arms, the arms adapted to pass between the planar members and force them apart against the biasing force. The holding arms can each include a means for engaging the implant. The means for distracting the implant can include an implant distractor and a means for rotatably advancing the implant distractor. The implant distractor can include a generally elongate member adapted to pass between

the substantially planar members and force the members apart against the biasing force.

[0063] In another embodiment, a method of performing an interbody fusion can include inserting a delivery device and chisel assembly into a joint between vertebral bodies of the spine, removing the chisel assembly from the delivery device, and inserting a driver assembly through the delivery device. The driver assembly can hold an implant and an implant distractor adapted to distract the implant. The method can also include distracting the implant and removing the driver assembly and the delivery device. In some embodiments, the method can further include repeating the steps to place a second implant in the joint.

[0064] Further aspects of the invention will be brought out in the following portions of the specification, wherein the detailed description is for the purpose of fully disclosing preferred embodiments of the invention without placing limitations thereon.

BRIEF DESCRIPTION OF THE DRAWINGS

[0065] FIG. 1 is a perspective view of a delivery device and chisel positioned relative to a facet joint of a spine, according to certain embodiments.

[0066] FIG. 1A is a perspective view of a chisel according to certain embodiments.

[0067] FIG. 2 is a perspective view of a distal end of a delivery device, according to certain embodiments.

[0068] FIG. 3 is a perspective view of a distal end of a delivery device with an advanced chisel, according to certain embodiments.

[0069] FIG. 4 is a perspective view of a distal end of a delivery device with an advanced internal decorticator, according to certain embodiments.

[0070] FIG. 5 is a perspective view of a delivery device and chisel positioned relative to a facet joint of a spine with a driving member positioned proximally to the chisel head, according to certain embodiments.

[0071] FIG. 6 is a perspective view of a delivery device with an exterior decorticator in an advanced position, according to certain embodiments.

[0072] FIG. 6A-6C are perspective views of a delivery device and an internal decorticator, according to certain embodiments.

[0073] FIG. 7 is a perspective view of a delivery device with an exterior decorticator being retracted, according to certain embodiments.

[0074] FIG. 8 is a perspective view of a delivery device with a driver assembly and implant poised for insertion into the delivery device, according to certain embodiments.

[0075] FIG. 9 is a close-up view of a distal end of a driver assembly and a delivery device, according to certain embodiments.

[0076] FIG. 10 is close-up view of a distal end of a driver assembly, according to certain embodiments.

[0077] FIG. 11 is a perspective view of an implant and a distal end of a driver assembly, according to certain embodiments.

[0078] FIG. 12 is a perspective view of distal end of a driver assembly holding an implant, according to certain embodiments.

[0079] FIG. 13 is a perspective view of a distal end of a driver assembly positioned within a delivery device, according to certain embodiments.

[0080] FIG. 14 is a perspective view of an implant distractor, according to certain embodiments.

[0081] FIG. 15 is a perspective view of a distal end of a driver assembly positioned within a delivery device, according to certain embodiments.

[0082] FIG. 16 is a perspective view of an implant according to certain embodiments.

[0083] FIG. 16A is a perspective view of an implant showing a guide feature, according to certain embodiments.

[0084] FIG. 16B is a perspective view of an implant showing a guide feature, according to certain embodiments.

[0085] FIG. 17 is a side view of an implant according to certain embodiments.

[0086] FIG. 18 is a top view of an implant according to certain embodiments.

[0087] FIG. 18A is a top view of an implant showing the guide feature of FIG. 16A, according to certain embodiments.

[0088] FIG. 18B is a top view of an implant showing the guide feature of FIG. 16B, according to certain embodiments.

[0089] FIG. 19 is a proximal end view of an implant according to certain embodiments.

[0090] FIG. 20 is a side view of an implant according to certain embodiments.

[0091] FIG. 21 is side view of a U-member according to certain embodiments.

[0092] FIG. 22 is a perspective view of a U-member according to certain embodiments.

[0093] FIG. 23 is a perspective view of an implant according to certain embodiments.

[0094] FIG. 23A is a perspective view of an implant according to certain embodiments.

[0095] FIG. 24 is a top view of an implant according to certain embodiments.

[0096] FIG. 24A is a side view of the implant shown in FIG. 23A, according to certain embodiments.

[0097] FIG. 25 is perspective view of a deliver device with a driver assembly inserted and advance, according to certain embodiments.

[0098] FIG. 26 is perspective view showing the removal of the driver assembly from the delivery device having left the implant behind, according to certain embodiments.

[0099] FIG. 27 is a perspective view of an injector, according to certain embodiments.

[0100] FIG. 28 is a perspective view of a delivery device with an advanced injector inserted and ejecting a material, according to certain embodiments.

[0101] FIG. 29 is a perspective view of an implant in a collapsed position according to certain embodiments.

[0102] FIG. 30 is a perspective view of an expanded implant according to certain embodiments.

[0103] FIG. 31 is a perspective view of an implant in a collapsed position according to certain embodiments.

[0104] FIG. 32 is a perspective view of an expanded implant according to certain embodiments.

[0105] FIG. 33 is a perspective view of an implant in a collapsed position according to certain embodiments.

[0106] FIG. 34 is a perspective view of an expanded implant according to certain embodiments.

[0107] FIG. 35 is a perspective view of an implant in a collapsed position according to certain embodiments.

[0108] FIG. 36 is a perspective view of an expanded implant according to certain embodiments.

[0109] FIGS. 37A-D include side and perspective views of an implant, according to certain embodiments.

[0110] FIGS. 38A-C include side and perspective views of an implant, according to certain embodiments.

[0111] FIGS. 39A-D include side and perspective views of an implant, according to certain embodiments.

[0112] FIGS. 40A-C include side views of an implant, according to certain embodiments.

[0113] FIGS. 41A-D include side and perspective views of an implant, according to certain embodiments.

[0114] FIGS. 42A-F include side and perspective views of an implant, according to certain embodiments.

[0115] FIGS. 43A-C include side and perspective views of an implant, according to certain embodiments.

[0116] FIGS. 44A-D include side and perspective views of an implant, according to certain embodiments.

[0117] FIGS. 45A-D include side and perspective views of an implant, according to certain embodiments.

[0118] FIGS. 46A-D include side and perspective views of an implant, according to certain embodiments.

[0119] FIGS. 47A-B include side views of an implant, according to certain embodiments.

[0120] FIGS. 48A-C include side and end views of an implant, according to certain embodiments.

[0121] FIGS. 49A-C include side and perspective views of an implant, according to certain embodiments.

[0122] FIGS. 50A-B include side views of an implant, according to certain embodiments.

[0123] FIGS. 51A-B include side views of an implant, according to certain embodiments.

[0124] FIGS. 52A-C include side and perspective views of an implant, according to certain embodiments.

[0125] FIGS. 53A-C include side and perspective views of an implant, according to certain embodiments.

[0126] FIGS. 54A-C include side and perspective views of an implant, according to certain embodiments.

[0127] FIGS. 55A-C include side and perspective views of an implant, according to certain embodiments.

[0128] FIGS. 56A-C include side and perspective views of an implant, according to certain embodiments.

[0129] FIGS. 57A-C include side and perspective views of an implant, according to certain embodiments.

[0130] FIGS. 58A-B include side views of an implant, according to certain embodiments.

[0131] FIGS. 59A-B include side views of an implant, according to certain embodiments.

[0132] FIGS. 60A-B include side views of an implant, according to certain embodiments.

[0133] FIGS. 61A-C include side and perspective views of an implant, according to certain embodiments.

[0134] FIGS. 62A-C include side and perspective views of an implant, according to certain embodiments.

[0135] FIGS. 63A-C include side and perspective views of an implant, according to certain embodiments.

[0136] FIGS. 64A-C include side and perspective views of an implant, according to certain embodiments.

[0137] FIGS. 65A-C include side and perspective views of an implant, according to certain embodiments.

[0138] FIGS. 66A-C include side views of an implant, according to certain embodiments.

[0139] FIGS. 67A-C include side and perspective views of an implant, according to certain embodiments.

[0140] FIGS. 68A-C include side and perspective views of an implant, according to certain embodiments.

[0141] FIGS. 69A-C include side and perspective views of an implant, according to certain embodiments.

[0142] FIGS. 70A-C include side views of an implant, according to certain embodiments.

[0143] FIGS. 71A-C include side and perspective views of an implant, according to certain embodiments.

[0144] FIGS. 72A-C include side and perspective views of an implant, according to certain embodiments.

[0145] FIGS. 73A-C include side and perspective views of an implant, according to certain embodiments.

[0146] FIGS. 74A-C include side and perspective views of an implant, according to certain embodiments.

[0147] FIGS. 75A-B include side views of an implant, according to certain embodiments.

[0148] FIGS. 76A-C include side and perspective views of an implant, according to certain embodiments.

[0149] FIGS. 77A-C include side and perspective views of an implant, according to certain embodiments.

[0150] FIGS. 78A-C include side and perspective views of an implant, according to certain embodiments.

[0151] FIGS. 79A-C include side and perspective views of an implant, according to certain embodiments.

[0152] FIGS. 80A-D include side and perspective views of an implant, according to certain embodiments.

[0153] FIGS. 81A-C include side views of an implant, according to certain embodiments.

[0154] FIGS. 82A-F include side and perspective views of an implant, according to certain embodiments.

[0155] FIGS. 83A-B include side and perspective views of an implant, according to certain embodiments.

[0156] FIGS. 84A-B include perspective views of an implant, according to certain embodiments.

[0157] FIG. 85 is an exploded perspective view of a kit, according to certain embodiments.

[0158] FIG. 86 is an assembled perspective view of a kit, according to certain embodiments.

[0159] FIGS. 87 and 88 are perspective views of a chisel portion of the kit shown in FIGS. 85 and 86.

[0160] FIGS. 89 and 90 are perspective views of a delivery device portion of the kit shown in FIGS. 85 and 86.

[0161] FIG. 91 is a perspective view of part of a driver assembly portion of the kit shown in FIGS. 85 and 86.

[0162] FIGS. 92 and 93 are perspective views of a part of a driver assembly portion of the kit shown in FIGS. 85 and 86.

[0163] FIGS. 94 and 94A are views of a chisel according to certain embodiments.

[0164] FIGS. 95, 95A and 95B are views of a delivery device according to certain embodiments.

[0165] FIG. 96 is a perspective view of a driver assembly according to certain embodiments.

[0166] FIG. 97 is a perspective view of an internal actuator according to certain embodiments.

[0167] FIG. 98 is a perspective view of an injector according to certain embodiments.

[0168] FIGS. 99-99D are several views of a driver assembly according to certain embodiments.

[0169] FIGS. 100-101 depict relative positions of a driver assembly and a delivery device according to certain embodiments.

[0170] FIGS. 102-103 depict relative positions of an internal actuator, a driver assembly, and a delivery device according to certain embodiments.

[0171] FIG. 104 is a side view of an internal actuator according to certain embodiments.

[0172] FIG. 105 is a side view of an internal actuator according to certain embodiments.

[0173] FIGS. 106-108 are several side and cross-section view of an internal actuator according to certain embodiments.

[0174] FIG. 109 is a side view of a collet according to certain embodiments.

[0175] FIG. 110 is a side view of a longitudinal shaft of an internal actuator according to certain embodiments.

[0176] FIGS. 111-113 include several views of an implant distractor according to certain embodiments.

[0177] FIG. 114 is a perspective view of an injector according to certain embodiments.

[0178] FIGS. 115-116 depict relative positions of an injector and a delivery device according to certain embodiments.

[0179] FIGS. 117-120 include several perspective views of an implant according to certain embodiments.

[0180] FIG. 121 includes several parts of a tool according to certain embodiments.

[0181] FIG. 122 is a perspective view of a chisel according to certain embodiments.

[0182] FIG. 123 is a perspective view of a delivery device according to certain embodiments.

[0183] FIG. 123A is a perspective view of the proximal end of a delivery device according to certain embodiments.

[0184] FIG. 124 is a perspective view of a decorticator according to certain embodiments.

[0185] FIG. 125 is a perspective view of a driver assembly according to certain embodiments.

[0186] FIG. 126 is a perspective view of an internal actuator according to certain embodiments.

[0187] FIGS. 126A and 126B are cross-sectional views of an internal actuator according to certain embodiments.

[0188] FIGS. 127 and 127A are perspective views of an internal rod with a collet according to certain embodiments.

[0189] FIG. 128 is a perspective view of an injector according to certain embodiments.

[0190] FIGS. 129-131 are several view of a dilator set according to certain embodiments.

[0191] FIGS. 132 and 132A are two views of a dilator rod according to certain embodiments.

[0192] FIGS. 133, 133A, and 133B are several views of a dilator sleeve according to certain embodiments.

[0193] FIGS. 134 and 134A are two views of a dilator sleeve according to certain embodiments.

[0194] FIGS. 135, 135A, and 135B are several views of a dilator sleeve according to certain embodiments.

[0195] FIG. 136 includes a perspective view of several parts of a tool according to certain embodiments.

[0196] FIG. 137 includes a perspective view of several parts of the tool of FIG. 136.

[0197] FIG. 138 is a perspective view of a chisel of the tool of FIG. 136.

[0198] FIGS. 139A-C include several views of a chisel of the tool of FIG. 136.

[0199] FIG. 140 is a perspective view of a malleting head of the chisel of FIG. 138.

[0200] FIG. 141 is a top view thereof.

[0201] FIG. 142 is a top view of a shaft portion of the chisel of FIG. 138.

[0202] FIG. 143 is a close up side view of a tip of the chisel of FIG. 138.

[0203] FIG. 144 is a top view of a chisel and delivery device of the tool of FIG. 136.

[0204] FIG. 145 is a close up side view of a tip of a chisel and delivery device of the tool of FIG. 136.

[0205] FIG. 146 is a perspective view of a decorticator of the tool of FIG. 136.

[0206] FIG. 147 is a perspective view of a driver assembly of the tool of FIG. 136.

[0207] FIG. 148 is a perspective view thereof.

[0208] FIG. 149 is a perspective view of several tips of several of the elements of the tool of FIG. 136.

[0209] FIG. 150 is a perspective view of the proximal ends of several of the elements of the tool of FIG. 136.

[0210] FIG. 151 is a perspective view of a plunger of the injector of the tool of FIG. 136.

[0211] FIG. 152 is a perspective view of an implant distractor, according to certain embodiments.

[0212] FIG. 153A-C are several side views thereof.

[0213] FIG. 154 is a perspective view of several handles and their engaging features for engaging with the receiving assembly of the delivery device of the tool of FIG. 136.

[0214] FIG. 155A-B include a cross-sectional view and close-up view thereof.

[0215] FIG. 156 is a perspective view of an implant according to certain embodiments.

[0216] FIG. 157-161B include several perspective views thereof including the relationship of the implant to a facet joint.

[0217] FIG. 162 is a side view of a mechanically tested implant, according to certain embodiments.

[0218] FIG. 163 is a table of exemplary dimensions of an implant.

[0219] FIG. 164 is a table of exemplary dimensions of a delivery device.

[0220] FIG. 165 is a table of exemplary dimensions of an implant distractor.

[0221] FIG. 166 is a table of exemplary dimensions of a chisel.

[0222] FIG. 167 is a table of exemplary dimensions of a place holding chisel.

[0223] FIG. 168 is a table of exemplary dimensions of a driver assembly.

[0224] FIG. 169 is a table of exemplary dimensions of a decorticator.

[0225] FIG. 170 is a table of exemplary dimensions of a malleting tool.

[0226] FIG. 171 is a perspective view of a chisel according to certain embodiments.

[0227] FIG. 172 is a top perspective view of a distal portion thereof.

[0228] FIG. 173 is a bottom perspective view of a distal portion thereof.

[0229] FIG. 174 is a perspective view of a proximal portion thereof.

[0230] FIG. 175 is a top view of implants positioned in a joint between two vertebral bodies.

[0231] FIG. 176 is another top view of implants positioned in a joint between two vertebral bodies.

[0232] FIG. 177 is yet another top view of implants positioned in a joint between two vertebral bodies.

[0233] FIGS. 178-185 depict several methods according to certain embodiments.

DETAILED DESCRIPTION OF THE INVENTION

[0234] The following description generally relates to devices and methods for treating spinal stenosis. Spinal stenosis reflects a narrowing of one or more areas of the spine often in the upper or lower back. This narrowing can put

pressure on the spinal cord or on the nerves that branch out from the compressed areas. Individual vertebrae of the spine are positioned relative to each other and their separation is maintained by discs separating main vertebral bodies and by capsules positioned within facet joints. The discs and capsules are separated from the bone of their respective joints by cartilage. Spinal stenosis is often indicative of degeneration of a disc, a capsule, or the cartilage in a joint, which leads to a compression of the joints and the narrowing mentioned.

[0235] As such, the following detailed description includes discussion of a device for distracting a facet joint of the spine to remedy this condition. The device may include a tool and an implant for distracting and maintaining the distracted position of the joint. Several embodiments of an implant are described in addition to several embodiments of a tool. In addition, several embodiments are described where the implant and the tool work together to distract the facet joint and thereafter leave the implant behind to maintain the distraction of the joint. In short, the device may be adapted to access a facet joint by inserting a delivery tool and an implant, forcibly separate the associated articular surfaces with the tool, the implant, or both, and leave the implant in place to maintain the separation of the articular surfaces. This approach may allow for maintaining the distraction of the joint, thereby relieving symptoms associated with spinal stenosis.

[0236] The present application hereby incorporates the following U.S. patent applications by reference herein in their entireties: U.S. patent application Ser. No. 11/618,619, which was filed on Dec. 29, 2006 and is entitled Cervical Distraction Device; U.S. Provisional Patent Application No. 61/020,082, which was filed on Jan. 9, 2008 and is entitled Methods and Apparatus for Accessing and Treating the Facet Joint; U.S. Provisional Application No. 61/059,723, which was filed on Jun. 6, 2008 and is entitled Spine Distraction Device; U.S. Provisional Application No. 61/097,103, which was filed on Sep. 15, 2008 and is entitled Cervical Distraction/Implant Delivery Device; U.S. Provisional Application No. 61/109,776, which was filed on Oct. 30, 2008 and is entitled Facet Joint Implants; U.S. Non-provisional application Ser. No. 12/317,682, which was filed on Dec. 23, 2008 and is entitled Facet Joint Implants and Delivery Tools; U.S. Non-provisional application Ser. No. 12/350,609, which was filed on Jan. 8, 2009 and is entitled Method and Apparatus for Accessing and Treating the Facet Joint; U.S. Provisional Application 61/169,601, which was filed on Apr. 15, 2009 and is entitled Facet Joint Implants and Delivery Tools; U.S. Non-provisional application Ser. No. 12/455,814, which was filed on Jun. 5, 2009 and is entitled Facet Joint Implants and Delivery Tools; and U.S. Non-provisional application Ser. No. 12/559,193, which was filed on Sep. 14, 2009 and is entitled Cervical Distraction/Implant Delivery Device.

[0237] Referring now to FIGS. 1-28, a first embodiment of a tool and an implant is shown. FIG. 1 shows the tool 100 in position posterior to the spine 102. The tool 100 includes a delivery device 104, a decorticator 106, and a chisel 108.

[0238] The delivery device 104 may include a receiving assembly 110 at a proximal end, anchoring forks 112 at a distal end, and a generally tubular shaft 114 defining a longitudinal axis and extending between the receiving assembly 110 and the anchoring forks 112. The tubular shaft 114 may have an annular shaped cross-section with an inner radius and an outer radius, where the difference between the two radii defines a thickness of the tubular shaft 114.

[0239] The receiving assembly 110 of the delivery device 104 may have a generally conical outer surface defining a generally hollow volume or solid mass. The conical outer surface may have a longitudinal axis that coincides with that of the tubular shaft 114. The conical outer surface may be defined by a first radius at a proximal end and a second radius at a distal end. Where the tubular shaft 114 and the receiving assembly 110 are manufactured as one piece, the second radius may match the outer radius of the tubular shaft. Alternatively, the distal end of the receiving assembly 110 may be adapted for a press fit over the proximal end of the tubular shaft 114. The receiving assembly 110 may also include a longitudinally extending bore 116 having an inner radius matching that of the tubular shaft 114 or may have a conically shaped inner surface leading to the tubular shaft 114. The receiving assembly 110 may also include a relatively thin annular ring 118 offset from its distal end by two relatively thin extension elements 120. The space between the proximal end of the conical portion of the receiving assembly 110 and the distal end of the annular ring 118 may define an access opening 122.

[0240] In another embodiment as shown in FIGS. 6A-6C, a receiving assembly 111 may not include the annular ring 118 and the extension elements 120, but may remain generally conical and may include the longitudinally extending bore 116. In addition, near the proximal end of the receiving assembly 111, seating recesses 119 may be included. These recesses 119 may be positioned on opposing sides of the bore 116 and may recess into the proximal end of the receiving assembly 111 and the inner surface of the bore 116. These recesses may function to receive positionally matched protrusions from any one or all of the devices being inserted into the delivery device. As such, the recesses 119, may allow for orienting the devices properly relative to the forks 112 positioned in the facet joint. It is noted that any number of recesses may be provided and that any orientation may be used, either symmetrical or non-symmetrical, such that one or several orientations may be controlled. That is, an asymmetrical arrangement may allow for only one proper insertion position as opposed to the symmetrical orientation shown, which may allow for two proper insertion positions.

[0241] As shown in more detail in FIG. 2, the delivery device 104 may include two anchoring forks 112 formed by coping two opposing portions of the distal end of the tubular shaft 114. The forks 112 may have a generally V-shaped tip 124 at their distal end and may have a generally rectangular cross-section extending from the V-shaped tip 124 to the proximal end of the forks 112. The rectangular cross-section may have an inside face and an outside face where the inside face faces the longitudinal axis of the delivery device 104. The rectangular cross-section may also have opposing surfaces connecting the inside face to the outside face and completing the rectangular cross-section. At the proximal end of the forks 112, as suggested by the coping mentioned above, the cross-section may gradually change from rectangular to a shape matching that of half of the annular shape of the tubular shaft portion. The forks 112 may also include serrations or teeth along the opposing surfaces to assist with anchoring the delivery device 104.

[0242] Referring again to FIG. 1, the chisel 108 may have a generally cylindrical cross-section forming a shaft 128. The shaft 128 may have a radius substantially equal to the inner radius of the tubular shaft 114 portion of the delivery device 104 allowing for slidable insertion of the chisel 108 within the

delivery device 104. The chisel 108 may include a basic single or doubly chamfered tip 130 at a distal end or may have a coped distal end. The chisel 108 may also include a head 132 at a proximal end. The head 132 may be a generally solid material and may have a generally flat distal face and a spherically shaped proximal face. The shaft 128 and tip 130 portion of the chisel 108, measured from the distal face of the head 132 to the distal end of the chamfered tip 130, may have a length substantially equal to the distance from a proximal face of the annular ring 118 of the delivery device 104 to the distal tip of the delivery device 104.

[0243] In another embodiment, the chisel 108 may include a longitudinal lumen 131 as shown in FIG. 1A. While not shown, this embodiment may also include the head 132 shown in FIG. 1 and the lumen 131 may extend there through. The lumen 131 in the chisel 108 may be used for advancing a scope along with the chisel 108 to properly place the chisel 108 and the delivery device 104. The lumen 131 may also be used to provide suction or fluid flushing to the surgical site to remove or flush debris created by inserting the serrated forks 112 of the delivery device 104 and the tip 130 of the chisel 108.

[0244] As shown in FIG. 3, the tip 130 of the chisel 108 may have a coped shaped similar to that of the forks 112 of delivery device 104. In this condition, the tip 130 may include a generally V-shaped distal end matching that of the forks 112. The tip 130 may have a width substantially equal to twice the inner radius of the tubular shaft 114 of the delivery device 104 such that the tip 130 extends between the two inside faces of the forks 112.

[0245] Referring again to FIG. 1, the decorticator 106 may have a tubular shaft 134 portion, an abrasive distal end 136, and a handle 138 at a proximal end. The tubular shaft 134 may have an inner radius substantially equal to the outer radius of the tubular shaft 114 of the delivery device 104 and may allow for sliding movement of the decorticator 106 along the length of the delivery device 104 and rotationally around the delivery device 104. The abrasive distal end 136 may include serrated teeth as shown, or may include a more flat annular surface with a gritty surface. The handle 138 may have a generally cylindrical portion with randomly or patterned raised portions or recesses adapted to assist gripping the handle. The proximal and distal ends of the handle 138 may be generally spherical. It is noted that the decorticator 106 may alternatively be separate from the delivery device 104 and may be slidably inserted within the delivery device 104 as shown in FIG. 4. In this embodiment, the decorticator 106 may be inserted, advanced to the implantation site, and rotated similar to the decorticator 106 described above to roughen the bone surface.

[0246] In still another embodiment, a decorticator 106 may take the form of a relatively sharp pick, as shown in FIG. 6A-6C. As shown in FIG. 6A, the decorticator 106 may include a control handle 139 for advancing and pivoting the device. The control handle 139 may be connected to a tubular shaft 135, which may be connected to a sharp flexible tip 137. As shown, the tip 137 may be relatively thin and may have a neutral position relative to the longitudinal axis of the delivery device 104 so as to position the tip 137 within the boundary defined by the inner surface of the delivery device 104. As such, when inserted in the delivery device 104, the tip 137 may slide readily through the delivery device 104. When the decorticator 106 is advanced to the distal end of the delivery device 104, the tip 137 may be rotated and maneuvered to

decorticate the surface of the lateral mass. It is noted that the shaft 135 may be relatively narrow when compared to the inner bore of the delivery device 104 to facilitate better maneuverability of the tip of the decorticator as it extends out the end of the deliver device. The decorticator may be used as shown in FIGS. 6B and 6C to rotationally scrape or longitudinally penetrate the lateral mass of a facet joint. A driving member may be used to assist the decorticating process.

[0247] Referring now to FIG. 5, the tool 100 is shown with the chisel 108 fully inserted into the delivery device 104 such that the distal face of the head 132 of the chisel 108 is in abutting relationship with the annular ring 118 of the receiving assembly 110 on the delivery device 104. The distal tip 130 of the chisel 108 thus extends to the distal end of the delivery device 104. A hammer 140 is shown for use in tapping the proximal end of the chisel 108 and thus advancing the forks 112 of the delivery device 104 and the tip 130 of the chisel 108 into the facet joint. As the chisel 108 and the delivery device 104 are advanced into the joint, the forks 112 of the delivery device may channel into the fact surface and displace or remove tissue. In some embodiments, this may be removed by a suction lumen in the chisel. Once the chisel 108 and delivery device 104 are tapped into place, the chisel 108 may be removed and the serrations on the opposing surfaces of the forks 112 may aid in anchoring the delivery device 104 in the joint and preventing dislodgement.

[0248] FIG. 6 shows the decorticator 106 in an advanced position along the length of the delivery device 104 such that the distal end is in contact with the bone surfaces surrounding the facet joint. The handle 138 is being used to rotate the decorticator 106 around the perimeter of the delivery device 104 to roughen the associated bone surfaces. Alternatively, either of the internal decorticators shown in FIG. 4 or 6A-6C may be used.

[0249] FIG. 7 shows the decorticator 106 retracted and also shows the resulting roughened bone surfaces.

[0250] Referring now to FIG. 8, the tool 100, including the delivery device 104 and retracted decorticator 106, is shown lodged in a facet joint. Also shown is a driver assembly 142 portion of the tool 100. The driver assembly 142 includes a distractor knob 144, an implant shaft 146, implant holding arms 148, an implant distractor 150, and an internal actuator 152 (not shown). The driver assembly 142 shown is holding an implant 154 and is poised for insertion into the delivery device 104.

[0251] Referring now to FIGS. 9-15 several views of the driver assembly 142 are shown. In FIG. 9, a portion of the delivery device 104 is shown for receiving the driver assembly 142. The distal end of the driver assembly 142 is also shown. FIG. 10 shows a close-up view of the distal end of the driver assembly 142 where the implant 154, the implant distractor 150 and the internal actuator 152 are not shown. As shown, the implant shaft 146 of the driver assembly 142 defines a longitudinal axis thereof and has a generally annular cross-section with an inner radius and an outer radius where the difference between the two radii defines the wall thickness of the shaft 146. The outer radius of the implant shaft 146 is substantially equal to the inner radius of the tubular shaft 114 of the delivery device 104. The implant shaft 146 also includes a keyway feature 156 for preventing relative rotation between the tubular shaft 114 of the delivery device 104 and the implant shaft 146 of the driver assembly 142 when inserted. As shown, the keyway feature 156 may include a pair of tabs on opposing sides of the implant shaft 146 for

engaging with a corresponding longitudinal slot in the inner surface of the tubular shaft 114 of the delivery device 104. In another embodiment, this keyway feature 156 may be in the form of a longitudinal slot in the outer surface of the implant shaft 146 of the driver assembly 142, as shown in FIG. 11, which may receive an internal ridge, tab, or other protrusion from the inner surface of the tubular shaft 114 of the delivery device 104.

[0252] With continued reference to FIG. 10, two arms 148 are shown extending from the distal end of the implant shaft 146. The arms 148 may be formed by coping opposing surfaces of the implant shaft 146. As shown, the arms 148 have a generally rectangular cross-section with an inside face facing the longitudinal axis of the implant shaft 146 and an opposite outside face. The inside and outside faces of the cross-section are connected by two opposing faces. The arms 148 may include an engagement feature 158 at a distal end for engaging an implant 154. As shown, the engagement feature 158 may include a generally rectangular element positioned orthogonal to the arms 148 and flush with the outside face of the arms. As shown in FIG. 9, the implant 154 may slide over the distal end of the arms 148 and may include a receiving feature 160 for receiving the engagement feature 158 of each of the arms 148.

[0253] Referring now to FIG. 11, another embodiment of the arms 148 is shown in relation to an implant 154. In this embodiment, the arms 148 may still be formed by coping opposing surfaces of the implant shaft 146. In this embodiment, the outside face of the arm 148 may be a continuation of the outside surface of the implant shaft 146. However, the inside face of the arm 148 is more detailed than that of the embodiment shown in FIG. 10. That is, as shown in FIG. 11, the inside surface may include a longitudinal ridge 162 extending the length of the arm 148. The arm 148 may also include a bull nose engagement feature 158 extending transverse to the longitudinal axis of the implant shaft 146 along the inside face of the arm 148. As shown in FIG. 12, where the arms 148 are engaged with and holding the implant 154, the longitudinal ridges 162 of each arm 148 are positioned between upper and lower planar members of the implant 154 and the bull nose engagement features 158 are positioned in the U-shaped receiving feature slots 160 on the lateral edges of the implant 154.

[0254] The implant distractor 150 is shown in FIG. 9 and a close-up view is shown in FIG. 14. The implant distractor 150 may be a generally narrow conical element tapered to a point at a distal end. At a proximal end, the implant distractor 150 is shown to include an extruded hexagon shape 164. In the present embodiment, the outer surface of the implant distractor 150 includes a continuous coil-shaped thread feature 166. The implant distractor 150 is shown positioned proximal to the implant 154 and engaged by the internal actuator 152. Those of skill in the art will understand and appreciate that the implant distractor 150 may take on a variety of shapes and sizes other than that shown in the present embodiment. For example, the implant distractor 150 may be a triangular shaped wedge, a generally conical shape without threads, or other shape adapted to cause separation and distraction of a facet joint.

[0255] Referring again to FIG. 9, the internal actuator 152 is visible extending from the distal end of the implant shaft 146. The internal actuator 152 generally includes a longitudinal shaft positioned within the driver assembly 142. The internal actuator 152 may have a radius substantially equal to

the inner radius of the driver assembly **142** and may be adapted for slidable longitudinal and rotational movement relative to the driver assembly **142**. The internal actuator **152** may be moved relative to the implant shaft **146** longitudinally, rotationally, or both via the distractor knob **144** and may cause a corresponding motion of the implant distractor **150**. As such, the internal actuator **152** may advance the implant distractor **150** into the implant **154** thus expanding the implant **154** in the joint causing distraction of the joint. The distal end of the internal actuator **152** may include a hex driver type tip as most clearly shown in FIG. **15** for engaging the extruded hexagonal shaped proximal end of the implant distractor **150**. Those skilled in the art will understand and appreciate that several driving engagements are known in the art including flat screwdriver types, phillips head types, square drive, etc. and that these are within the scope of the invention.

[0256] In one embodiment, when the driver assembly **142** is inserted, it may carry the internal actuator **152**, the implant distractor **150**, as well as the implant **154** with it. However, to properly position the driver assembly **142** and the implant **154**, some force may be required via a mallet or other member driving member. In this embodiment, the internal actuator **152** may be slightly isolated from the driver assembly **142**, so as to avoid advancing the internal actuator **152**, and thus the implant distractor **150**, when forcing the driver assembly **142** into the joint. This isolation may help to avoid inadvertently advancing the internal actuator **152** and the implant distractor **150**, thus avoiding inadvertent distraction prior to proper placement. The isolation of the internal actuator **152** from the driver assembly may take the form of a loosely fitting threaded engagement between the driver assembly **142** and the internal actuator **152**. Alternatively, this isolation may be in the form of a clip between the two features.

[0257] For a detailed discussion of an implant **154** according to certain embodiments, reference is now made to FIGS. **16-24**.

[0258] As can be understood from FIGS. **16** and **17**, the implant **154** may include upper **168** and lower **170** members. The members **168**, **170** may be generally planar and may also be generally rectangular. As most clearly shown in FIG. **18**, each of the upper **168** and lower **170** members may include a proximal edge **172**, a distal edge **174**, and a pair of parallel lateral edges **176** extending longitudinally between the distal edges **174** and the proximal edges **172**. The distal **174** and proximal edges **172** may be generally square edges, while the lateral edges **176** may be defined by a radiused curve. As shown in cross-section in FIG. **19**, the inner surface **178** of the upper **168** and lower **170** member may be generally flat as it approaches the lateral edge **176**. Gradually, the inner surface **178** departs from generally flat and follows a radiused curve until it intersects with the outer surface **180**. The members **168**, **170** may be joined at their respective distal edges **174** by a U-member **182** to form a leading end. Alternatively, as shown in FIGS. **23** and **24**, the leading end may be formed via a weld (not shown) that couples the distal edges **174** of the planar members **168**, **170** together. In yet another embodiment, the upper **168** and lower **170** members may be formed from a single plate bent to create the implant as shown in FIGS. **23A** and **24A**. In any or all of these embodiments, the planar members **168**, **170** may be biased by the leading end to be generally parallel to each other, the inner faces **178** of the planar members **168**, **170** facing each other in an opposed fashion and abutting or nearly abutting each other. A guide feature **184** may be included on each of the upper **168** and

lower **170** members as well as teeth **186** projecting outwardly from the outer faces **180** of the members **168**, **170**. The receiving features **160** mentioned above with respect to FIGS. **11** and **12** may also be included. Threaded slots **188** may also be included in each planar member **168**, **170** for receiving the coil-shaped thread feature **166** on the implant distractor **150**.

[0259] With continued reference to FIGS. **16** and **17**, the guide feature **184** may take the form of a half-conical feature and may be positioned at or near the proximal edge **172** of each of the upper **168** and lower **170** members. The half-conical feature may begin at the proximal edge **172** with the widest radius of the half-conical feature and may taper to a zero or approximately zero radius as the half-conical feature extends in the direction of the distal edge **174**. Where the upper **168** and lower **170** members are in parallel position, the half conical features may oppose one another and function to receive and guide an advancing implant distractor **150**. As such, like the upper **168** and lower **170** members described above, the half-conical features may also include threaded slots **188** for receiving the coil-shaped thread feature **166** on the implant distractor **150**. In other embodiments, the half-conical feature may not actually be a full half cone. Instead, the proximal end of the feature may be a segment of a circle and the feature may be relatively subtle in the form of a cone segment. In another embodiment the guide feature **184** may include a V-shaped notch or a rectangular notch in the proximal end of the upper **168** and lower **170** members as shown in FIGS. **16A** and **18A** and FIGS. **16B** and **18B** respectively. Those skilled in the art will understand and appreciate that other shaped notches or elements may be positioned on proximal end of the upper **168** and lower **170** members to guide the implant distractor **150**, and these elements are within the scope of the present disclosure.

[0260] As shown, the upper **168** and lower **170** members may also each include teeth **186** projecting outwardly (e.g. a direction opposite the position of the other upper or lower member) from the outer surfaces **180** of the upper **168** and lower **170** members. As shown in FIG. **17**, the teeth **186** may be equally spaced along each lateral edge **176** and may have a linearly sloped distal face **190** and a proximal face **192** oriented orthogonally to its respective upper **168** or lower **170** member. The distal face **190** and proximal face **192** may intersect to form a point **194**. The teeth **186** may also be bounded by opposing inside **196** and outside **198** lateral faces separated by a thickness approximately equal to the thickness of the upper **168** and lower **170** members. As shown in FIG. **19**, the outside face **198** of the teeth **186** follows an extension of the radiused curve formed by the inner surface **178** of the upper **168** or lower **170** member at the lateral edge **176**, this curve being referred to as a first radiused curve. Additionally, the inside face **196** of the teeth **186** follows a second radiused curve offset from the first radiused curve, such that the teeth **186** have a generally constant thickness from the location where they depart from the outer surface **180** of the upper **168** or lower **170** member to the point **194**. The radiused shape of the teeth **186** allows the implant **154** to slidably engage the inside of the delivery device **104** when it is advanced toward the implantation site. Those skilled in the art will understand and appreciate that one, as opposed to both, of the upper **168** and lower **170** members may include teeth **186** to facilitate freedom of motion of the facet joint once the implant **154** is in place.

[0261] As shown in FIGS. **16** and **17**, where a U-member **182** is used to connect the upper **168** and lower **170** members,

the U-member 182 may overlap the upper 168 and lower 170 members. Alternatively, as shown in FIG. 20, the U-member 182 may attach to the distal ends 174 of the upper 168 and lower 170 members via a butt joint. In either case, the U-member 182 may be fastened via welding, fusing, or other techniques known in the art. As shown in FIGS. 21 and 22, the U-member 182 may be a relatively thin, generally rectangular piece of material formed into the shape of the letter 'U'. The rectangular piece of material may have a length defined by the amount of overlap of the upper member 168 and the lower member 170 in addition to the length associated with hairpin or U portion of the member 182. The width of the rectangular plate may be substantially equal to the distance between the teeth 186 of the upper 168 and lower 170 members. The U-member 182 may be adapted to provide the parallel biased position mentioned and yet allow distraction of the upper 168 and lower 170 member when a separation force is applied, the proximal edge 172 of the upper 168 and lower 170 member distracting more than the distal edge 174.

[0262] As shown in FIGS. 23 and 24, where the distal edges 174 of the upper 168 and lower 170 member are joined via welding, the distal edges 174 may include a notch to facilitate more weld length and to cause flexure to occur in the upper 168 and lower 170 members rather than in the weld itself. Also shown in FIGS. 23 and 24 are the U-shaped receiving feature slots 160 for receiving the bull nosed engagement features 158 of the arms 148 of the driver assembly 142. As shown most clearly in FIG. 24, the U-shaped receiving feature slots 160 are positioned between the equally spaced teeth 186 and extend into the lateral edges 176 of the upper 168 and lower 170 member just beyond the inside edge of where the teeth 186 begin extending from the outer surfaces 180.

[0263] The receiving feature 160 may take several forms including a rectangular notch in the lateral edge 176 of the upper 168 and lower 170 member or a U-shaped notch. The receiving feature 160 may be adapted to receive an engagement feature 158 positioned on the arm 148 of the driver assembly 142. The receiving feature 160 may be any shaped recess and may be adapted to be engaged by the engagement feature 158 so as to prevent or limit relative longitudinal motion between the arms 148 and the implant 154, when the implant 154 is in the neutral position. However, when in an expanded or distracted position, the receiving features 160 may be such that they are lifted free of the engagement feature 158 of the arms 148, thus allowing relative longitudinal motion between the driver assembly 142 and the implant 154.

[0264] The driver assembly 142 and implant 154 described with respect to FIGS. 8-24, may be used to distract a facet joint. With the delivery device 104 positioned as shown and described with respect to FIG. 7, the implant 154 may be positioned to be held by the arms 148 of the driver assembly 142. The driver assembly 142 and implant 154 may then be inserted into the delivery device 104 and slidably advanced such that the implant 154 is positioned between the forks 112 of the delivery device 104 and within the facet joint. The advanced position of the driver assembly 142 and implant 154 within the delivery device 104 may be most clearly seen in FIG. 13. The proximal end of the driver assembly 142 may be tapped on to fully advance the driver assembly 142 and properly position the implant 154. The implant shaft 146 of the driver assembly 142 may be prevented from rotating by the keyway feature 156 securing it against relative rotation with respect to the delivery device 104. As such, once positioned, the distractor knob 144 of the driver assembly 142 may be

turned, as shown in FIG. 25, thereby advancing the internal actuator 152 and further advancing the implant distractor 150. In the embodiment described, the coil-shaped thread feature 166 on the implant distractor 150 may engage the threaded slots 188 of the half-conical features 184 of the upper 168 and lower 170 members of the implant 154. As such, the implant distractor 150 may be guided and remain in position to further engage the threaded slots 188 on the upper 168 and lower 170 members. As the implant distractor 150 continues to advance, those of skill in the art will understand and appreciate that its tapered shape advancing between the upper 168 and lower 170 members will force the upper 168 and lower 170 members of the implant 154 apart causing them to pivot about a point defined by the attachment to each other at their distal ends 174. As the implant 154 continues to be distracted, the upper 168 and lower 170 members of the implant 154 are laterally separated such that they clear the engagement features 158 on the arms 148 of the driver assembly 142. As shown in FIG. 26, when the implant distractor 150 has been fully advanced and the implant 154 is in place, the driver assembly 142 may be slidably removed from the delivery device 104 leaving behind the implant distractor 150 and the implant 154.

[0265] FIG. 27 shows yet another device, the device being adapted for placing bone paste over the implant 154 in the joint. An injector 202 is shown and includes a syringe type cannula 204 with a closed distal end 206 and two exit doors 208 positioned on opposite sides of the distal end 206 of the cannula 204. The cannula 204 includes a plunger 210 with a seal and further includes a stopping disc 212 at its proximal end, the plunger 210 penetrating the stopping disc 212 and having a handle 214. The cannula 204 may have an outer radius substantially equal to that of the inner radius of the delivery device 104 to allow for slidable engagement of the two devices. The disc 212 at the proximal end is generally flat and is adapted to engage the receiving assembly 110 of the delivery device 104 and provide a stop point for the injector 202 when inserted into the delivery device 104. As shown, the cannula 204 may contain a bone paste material in a liquid form.

[0266] As shown in FIG. 28, the injector 202 may be inserted into the delivery device 104 and slidably advanced such that the distal end 206 is near the implantation site and the disc 212 abuts the annular ring 118 of the receiving assembly 110 of the delivery device 104. The injector 202 may be rotatably positioned such that the doors 208 are positioned to open perpendicular to a line connecting the distal ends of the forks 112. The disc 212 may include tabs 216 for such positioning relative to the annular ring 118 on the receiving assembly 110. Once in position, the plunger 210 may be actuated to compress the bone paste material creating an internal pressure which forces the exit doors 208 open allowing the bone paste to escape and flow over the implantation site.

[0267] The above description has included some references to use to allow for a better understanding of the structure. Below is a more detailed discussion of that use including the devices and techniques for distracting and retaining a facet joint in a distracted and forwardly translated condition. The implantation procedure may be performed under conscious sedation in order to obtain intra-operative patient symptom feedback.

[0268] Initially an incision may be made in the patients back. Tools known in the art may be used to create this

incision and to open an access path through the tissues of the back to access the spine. Once an access path is created, the chisel 108 described above may be inserted into the delivery device 104 and the two of them may be inserted through the incision and the distal tip 130 may be positioned adjacent the target facet joint. It is noted that visualization may be provided by first inserting a scope down the delivery device 104 rather than the chisel 108. Additionally, an incision in the facet joint capsule may be made prior to beginning the procedure, and thus prior to insertion of the chisel 108. Once the distal tip of the delivery device 130 is properly positioned adjacent the facet joint and any other preparation steps are completed, the chisel 108 may be inserted. Once the chisel 108 and delivery device 104 are properly positioned, the head 132 of the chisel 108 may be tapped with a driving device 140 such as a hammer or other instrument to advance the distal tip 130 of the chisel 108 and the forks 112 of the delivery device 104 into the facet joint. Once the delivery device 104 is properly positioned, the chisel 108 may be removed. At this point, the implant 154 may be placed in the driver assembly 142 and the implant 154 and driver assembly 142 may be slidably advanced through the delivery device 104. The forks 112 of the delivery device 104 may be holding the facet joint slightly distracted. As such, the implant 154, in its flat and parallel position, may slide relatively easily into the facet joint. To the extent that it does not, the proximal end of the driver assembly 142 may be tapped to properly advance and position the implant 154. Once properly positioned, the distractor knob 144 on the driver assembly may be rotated or otherwise actuated to activate the internal actuator 152. The internal actuator 152 advances the implant distractor 150 into the implant 154 and thus distracts the implant 154. It is noted here that the distraction of the implant 154 may cause the upper 168 and lower 170 member of the implant 154 to clear the engagement features 158 of the holder arms 148 thus allowing the driver assembly 142 to be freely removed from the delivery device 104 leaving the implant 154 and the implant distractor 150 behind. The injector 202 may then be advanced through the delivery device 104 and positioned to allow the doors 208 to open in a direction approximately perpendicular to the forks 112 of the delivery device 104. The handle 214 may be depressed thus advancing the plunger 210 and ejecting the bone paste or other anchoring material. The injector 202 may then be removed. The delivery device 104 may also be removed and the incision closed.

[0269] Those skilled in the art will understand and appreciate that several modifications or variations from the above the identified embodiments may be made while still falling within the scope and spirit of the present disclosure. For example, several alternative actuation mechanisms at the proximal end of the tool for actuating the distracting elements of the tool may be available. Additionally, several alternative implants may be available. For example, as shown in FIGS. 29 and 30, an implant 218 similar to that previously described is shown and includes a body 220 and a screw 222. The body 220 includes an upper 224 and lower 226 face joined together at a leading end 228 and separated from each other at a trailing end 230.

[0270] As shown in FIG. 29, when the screw 222 is not received in the body 220, the upper 224 and lower 226 faces may reside against each other such that the body 220 is generally flat. As shown in FIG. 30, when the screw 222 is received in the body 220, the upper 224 and lower 226 faces may be separated from each other, the degree of separation

increasing as the screw 222 is increasingly received in the body 220. As the upper 224 and lower 226 faces are separated from each other, the body 220 takes on more of a wedge shape, with the leading end 228 being the narrow end of the wedge and the trailing end 230 being the wide end. The faces may include teeth 232 and the trailing end 230 of the upper face 224 may be formed to project towards the leading end, both of these features assisting in the implant 218 anchoring to the bone facet surfaces. Holes 234 may exist in the faces 224, 226 such that when the screw 222 is received in the body 220, the thread edges of the screw 222 may project through the holes 234 to bite into the facet surfaces. The wedge shape of the implant 218 may facilitate anchoring the implant 218 within the facet joint and may also facilitate distraction, translation, or subluxation of the facet surfaces relative to each other.

[0271] As can be understood from FIG. 29, the collapsed and flattened body 220 may be placed between the opposing surfaces of the facet joint. The posterior or trailing end 230 of the body 220 is configured to be capable of receiving a screw, bolt, or some other inserted component 222. As indicated in FIG. 30, upon insertion of the screw, bolt, etc. 222, the body 220 begins to expand. This expansion and separation is enabled by a hinge 236 at the anterior or leading end 228 of the body 220. As the body 220 expands, sharp directional teeth, cleats, or keels 232 on the opposing (superior & inferior) surfaces or faces 224, 226 of the body 220 may become anchored in the cortical bone of the opposing facet surfaces. These teeth, cleats, or keels 232 may engage the facet surfaces and provide acute fixation of the body 220 within the facet joint. The teeth, cleats, or keels 232 may be included on only one surface 224, 226 as opposed to both surfaces 224, 226 so as to allow for a movement of the joint after placement of the implant 218.

[0272] The distraction and separation of the facet joint via the expanded implant (see FIG. 30) may increase foraminal area and reduce the symptoms associated with nerve root compression.

[0273] Another implant embodiment is depicted in FIGS. 31 and 32, wherein a screw 238 also acts to spread apart the faces 240, 242 of the body 244 of the implant 236. In this embodiment, the implant 236 may have an upper 240 and a lower 242 member positioned adjacent to each other. The upper 240 and lower 242 member may be substantially rectangular with a distal edge a proximal edge and parallel lateral edges. The distal edge may be slightly radiused. The upper 240 and lower 242 members may be connected along their distal edge by a connection member 246 in the form of a triangularly bent plate or other connection. The connection member may include a penetration 248 adapted to receive an implant distractor 238. As with the previous embodiments, the implant 236 may include teeth 250 on the outer surface of the upper member 240 or the lower member 242 or both as shown. In one embodiment, the implant 236 may be formed from a single plate and folded to create the shape shown. In use, the implant 236 may be positioned in a facet joint and the implant distractor 238 may be advanced thereby separating the upper 240 and lower 242 member and distracting the joint. Similar to that discussed above with respect to FIGS. 29 and 30, such an embodiment as depicted in FIGS. 31 and 32 may have holes (not shown in FIGS. 31 and 32) in the body surfaces 240, 242 so as to allow the threads of the implant distractor 238 to extend through the surfaces of the body 244 to bite into the facet surfaces.

[0274] FIGS. 33 and 34 depict isometric views of another implant 248 with V-shaped members 250 residing on a threaded bolt 252 between an anterior threaded block 254 and a posterior non-threaded block 256. The V-shaped members 250 may slidably engage the bolt 252. As shown in FIG. 33, the V-shaped members 250 are in a non-expanded state and are spaced apart from each other along the length of the bolt 252. The implant 248 may be inserted into the facet joint in the non-expanded state depicted in FIG. 33. As can be understood from FIG. 34, the bolt 252 may be rotated to cause the anterior threaded block 254 to travel along the bolt 252 towards the posterior non-threaded block 256. It is noted that in use, the rotation of the blocks 254, 256 may be prevented by their position within a facet joint, thus causing the anterior threaded block 245 to travel rather than rotate when the bolt 252 is rotated. The posterior non-threaded block 256 may be in abutting position against the head 258 of the bolt 252 thereby preventing it from moving away from the anterior thread block 254. Thus, as the anterior threaded block 254 advances toward the posterior non-threaded block 256, the V-shaped members 250 are squeezed together. As the V-shaped members 250 are increasingly squeezed together between the blocks 254, 256, the V-shaped members 250 are increasingly expanded outward, thereby biting into the facet joint surfaces to anchor the implant 248 in the facet joint and distract, translate and/or subluxate the facet surfaces relative to each other.

[0275] FIGS. 35-36 and 37A-D, depict isometric views of another implant 260 with planar plates or leaves 262 residing on a threaded bolt 264 and parallel shafts 266 between an anterior threaded block 268 and a posterior non-threaded block 270. As shown in FIG. 35, the planar plates 262 are in a skewed non-expanded state and are spaced apart from each other along the length of the bolt 264 such that they lie generally flat or, more specifically, at approximately 45 degrees on the bolt 264 and shafts 266. The plates 262 may include a slotted hole for receiving the bolt 264, which allows for the position described. The implant 260 may be inserted into the facet joint in the non-expanded state depicted in FIG. 35. As can be understood, the bolt 264 may then be rotated to cause the anterior threaded block 268 to travel along the bolt 264 towards the posterior non-threaded block 270, thereby causing the planar plates 262 to squeeze together. As the planar plates 262 are increasingly squeezed together between the blocks 268, 270, the planar plates 262 are increasingly expanded outward or, more specifically, are caused to be generally perpendicular to the bolt 264 and shafts 266. As a result, the planar plates 262 bite into the facet joint surfaces to anchor the implant 260 in the facet joint and distract, translate and/or subluxate the facet surfaces relative to each other.

[0276] FIGS. 37A-D show an embodiment, which combines features of the embodiment shown in FIGS. 33 and 34 with features of the embodiment shown in FIGS. 35 and 36.

[0277] FIGS. 38A-C shows another embodiment of an implant 272. The implant 272 may include two stacked structures 274 that interface along a plane 276. Each structure 274 may include opposing ratchet teeth 278 along the plane. The position and orientation of the ratchet teeth 278 may be such that relative translation between the two structures 274 is allowed when a force is applied to each structure 274 in opposing directions. That is, once the implant 272 is properly positioned within the facet, a device may be used to apply a force to the superior structure 274 which causes forward translation of that structure 274 relative to the inferior struc-

ture 274. The ratchet teeth 278 on the superior structure 274 may slide up the slope of the teeth 278 on the inferior structure 274 until opposing apexes of teeth 278 pass by each other causing the two structures 274 to nest in a new relative position, the displacement being equal to the length of the teeth 278. Each structure 274, or only one of the structures 274, may increase in thickness along its length, such that continual relative ratcheted displacement creates a greater overall thickness. The increasing thickness of the implant structures 274 may cause distraction and forward translation in the facet joint. The opposing facet surfaces may be separated and the superior vertebra may be pushed anterior relative to the inferior vertebra. In addition, anchoring teeth 280 may be provided on the outer surface of both structures 274 of the implant 272 to provide acute fixation to the articular surfaces. The implant 272 may be configured in a number of different shapes including, but not limited to, a wedge, a double wedge, a rectangular box, and "v" shaped.

[0278] FIGS. 39A-D show another embodiment of an implant 282. In this embodiment, a screw like implant 282 may be inserted between the facet. The insertion of this screw may serve to distract the joint surfaces resulting in a decompression of the nerve root. Additionally, the threads 284 of the screw may include V-shaped notches 286 in the threads 284 spaced throughout the length of the screw creating serrated teeth. As the screw implant 282 is threaded progressively further anterior, the serrated teeth may cut/bore into the cortical bone of the opposing facet surfaces. The defect in the bone these serrations produce may prevent the implant 282 from backing out posteriorly or migrating medial/lateral because the threads 284 are configured with the serrated teeth to allow the implant 282 to catch or "bite" in the bone if any posterior withdraw or backing out occurs. Additionally or alternatively, as shown in FIGS. 40A-C, the screw threads 284 may include a leaf spring 288 to maintain friction of the threads 284 against the newly cut threads in the bone thereby preventing the screw from backing out.

[0279] FIGS. 41A-D show another embodiment similar to the one shown in FIGS. 39A-D. That is, in this embodiment, the implant 290 may take the form of a screw, but the threads 292 of the screw may have a T-shaped profile as shown in FIG. 41D. In addition, the flat surface of the T-shaped profile may define a diameter at any given point along the length of the screw. In one embodiment, the diameter may increase over the length of the screw and not be limited to just the tip like a traditional screw. As such, when the implant 290 is placed, the more it is advanced into the facet joint, the more separation it creates.

[0280] FIGS. 42A-F show another embodiment of an implant 294. In this embodiment, the implant 294 may again take the form of screw. The screw may have a washer or extra broad head 296 with sharp protrusions 298 on the distal surface of the head 296 that engage the superior and inferior lateral mass surfaces as the screw is inserted into the facet joint. The engagement of the sharp protrusions 298 may occur as a result of both the longitudinal translation of the screw together with the rotational motion causing the sharp protrusions 298 to cut into the lateral mass surface as the screw is advanced and rotated. As the washer 296 rotates, the sharp protrusions 298 roughen the lateral masses and create a fracture environment. This fracture environment causes osteoblastic activity that will lead to bone production and assist in fusion of the joint at the lateral mass. Moreover, the moat

created by the rotating and cutting protrusions **298** may begin to lock the facet surfaces together.

[0281] In the present embodiment, the protrusions **298** may be tab like and cut relatively deeply into the lateral mass. In addition as shown in FIGS. **42D-F**, the tabs may position themselves as shown where the superior tab is flared to engage the lateral mass and the inferior tab is wedged into the joint. In this configuration, the tabs may act to further distract the joint beyond that provided by the diameter of the screw portion of the implant. In other embodiments, as shown in FIGS. **43A-C**, the sharp protrusions **300** may be sharp prongs or spurs adapted to roughen the surface.

[0282] FIGS. **44A-D** show another embodiment of an implant **302**. In this embodiment, a facet distraction implant **302** has a floating collar **304** for use with a screw type implant. As shown, the collar **304** may be positioned to pivot about the head **306** of the screw due to the spherical shaped head **306** on the screw in a ball and socket fashion. The floating collar **304** allows the screw implant to accommodate irregular, non-planar surfaces of the lateral mass and may aid in the prevention of reverse threading of the implant **302** once the screw has been advanced to the proper position within the facet. As shown, the screw may be implanted to provide distraction and forward translation of the joint. The floating collar **304** may include teeth or spikes **308** that roughen/decorticate the cortical bone of the superior and inferior lateral masses resulting in the creation of a fracture environment. This may improve the chance of posterior lateral mass facet fusion.

[0283] FIGS. **45A-D** show yet another embodiment of a decortivating screw type implant **310**.

[0284] FIGS. **46A-D** show another embodiment of an implant **312**. In this embodiment, a structural implant **312** is inserted between the opposing surfaces of a facet joint. This implant **312** may be in the form of a screw as described above or may be a different implant requiring a torque or other force to be applied to anchor the implant **312** in the facet joint. As shown, when the implant **312** is inserted increasingly more anterior within the facet, a torque limiting mechanism **314** within the device may measure the force or torque applied to the system. Once a predetermined value of torque or force is achieved, the distal end of the system may detach causing the implant **312** to become a permanent distraction implant.

[0285] In the case of a screw implant, the torque limiting mechanism **314** may be a necked down portion of the device creating a calibrated weakened portion intended to fail when a specified torque is exceeded.

[0286] In this embodiment, the implant **312** may also include a number of anti migration features to prevent back-out. These features may include directional teeth, roughened surfaces, keels, spikes, or other features known in the art. As with other implants, the geometry of the implant may cause distraction of the joint and lead to a more pronounced forward translation of the joint as the opposing facet surfaces separate.

[0287] FIGS. **47A-B** show another embodiment of an implant **316**. In this embodiment, again a screw shaped implant **316** may be inserted into the facet to distract the facet surfaces and increase foraminal height resulting in a decompression of a symptomatic nerve root. In this embodiment, however, the implant may include two main components. First, the implant **316** may include a relatively stiff but maleable cone-shaped screw structure **318** with aggressive threads for biting into the opposing surfaces of the facet joint. These threads may have a number of variations for preventing movement of the implant after it is implanted. Second, the implant

may include an inner core support member **320**. The core support member **320** may be in place when the implant **316** is placed to assist in maintaining the shape of the screw structure **318**. After placement, the core support member **320** may be removed. The maleability of the screw structure **318** may allow it to collapse slightly once the implant **316** is properly positioned and inserted. The collapsing of the screw structure **318** would change the alignment of the threads and prevent reverse threading that could lead to posterior migration.

[0288] Yet another embodiment is shown in FIGS. **48A-C**. In this embodiment, a superior **324** and an inferior **326** screw may be used to create an implant **322**. The two screws **324**, **326** may have communicative threaded serrations that work in opposition to one another. As such, when the inferior screw **326** is rotated, the threads may interact with the superior screw **324** causing it to rotate in the opposite direction. Moreover, the threads on the inferior screw **326** and superior screw **324** are such that opposite direction rotation draws both screws **324**, **326** in to the facet joint. As the screws **324**, **326** enter the joint, the facet surfaces are distracted apart from one another and the threads of the screw bite into the facet surfaces. The opposing rotation of the two screws **324**, **326** may also assist in preventing back out of the implant or reverse threading/unscrewing. It is noted that several configurations may be used to create the opposite rotation of the screws. In one embodiment, a housing may be placed over each screw allowing the screws to freely rotate relative to the housing, but securing the screws adjacent to one another. In this embodiment, the opposite rotation may occur due to the threads engaging with one another as described above or the screw heads may have gear teeth for engaging one another and causing opposite rotation. In another embodiment, the screws may have gears on them positioned within the housing to engage one another and cause opposite direction rotation.

[0289] FIGS. **49A-C** show yet another embodiment of an implant **328**. In this embodiment, a translating system including a vertical plate **330** and a bumper **332** may be included. The superior aspect **334** of the bumper **332** may have a rounded concave surface for opposing the lateral mass of a superior vertebra. The translating system may be secured by anchoring a screw **336** to the lateral mass of an inferior vertebrae. The screw **336** may act as the foundation for a bumper system intended to push a superior vertebra forward (anterior) creating translation of the superior vertebra relative to the inferior vertebra. This forward translation may create an increase in foraminal area and results in a decompression of the nerve root. The implant **328** may be configured to maintain permanent forward translation in order to prevent foraminal narrowing and nerve root compression. In addition, the implant **328** may provide rigid resistance when the superior vertebra exerts posterior translation vectors because it is anchored by the inferior lateral mass screw. The prevention of this posterior translation may keep the segment in a state of forward translation and preserve the associated increase in foraminal area.

[0290] FIGS. **50A-B** show another embodiment of an implant **338**. In this embodiment, a wedge shaped or triangular implant **338** may be inserted between the face surfaces. The angled/pointed portion **340** with two acute line segments may allow the implant **338** to enter into the flat facet joint when sufficient force is applied. As the implant **338** is inserted progressively more anterior, the distraction of the opposing

facet surfaces may increase. This separation results in an increase of foraminal height and decompresses the symptomatic nerve root.

[0291] The surfaces of this implant **338** may include teeth, spikes, cleats, surface roughening, and/or keels **342** to help prevent migration or backout. In another configuration of this embodiment, as shown in FIGS. **51A-B**, the wedge shaped or triangular implant **338** may be anchored in position by one or two (one shown in FIG.) lateral mass screws/nails **344** that would connect the superior & inferior aspects of the implant **338** to the corresponding superior & inferior lateral masses of the affected segment.

[0292] FIGS. **52A-C** show another embodiment of an implant **346**. In this embodiment, a distraction/translation system may include an anterior hook **348** and a posterior hook **350** joined by a threaded bolt **352**. The anterior hook **348** may be placed over the anterior aspect of the inferior facet and the posterior hook **350** may be positioned posterior to the superior facet. The anterior hook **348** may have a C-shaped profile with a lip for engaging the anterior aspect of the inferior facet. The posterior hook **350** may have a S-shaped profile with a lip for engaging the posterior aspect of the superior facet. The threaded bolt **352** may be positioned through the facet joint and may threadably engage a posterior leg **354** of the anterior hook **348** and an anterior leg **356** of the posterior hook **350** as shown. As the bolt **352** is tightened and the hooks **348, 350** are drawn together, they create anterior translation of the superior vertebra relative to the inferior vertebra. This translation may result in increased foraminal area and nerve root decompression. The translation is maintained through the permanent placement of the hooks and bolt.

[0293] FIGS. **53A-C** show another embodiment of an implant **358**. In this embodiment, an insert **360** may be placed in the facet joint between two opposing facet surfaces. The geometry of the implant **358** could take a number of shapes including, but not limited to, rectangular, conical, triangular, or trapezoidal shape. Once the implant **358** is properly positioned, it may then be rotated some degree of rotation. This rotation may result in an increased height of the implant and cause facet surface separation and thus increased foraminal area and decompression of the symptomatic nerve root. In another configuration as shown in FIG. **53C**, the rotated implant **358** may have outer tabs **362** that are capable of receiving a bone screw, nail, or pin that can be anchored in the superior and inferior lateral masses. These tabs **362** and anchors may assist in the prevention of implant migration leading to a reduction in the foraminal area.

[0294] FIGS. **54A-C** show another embodiment of an implant **364**. In this embodiment, an implant **364** may take the form of a collapsible diamond shape **366** with an adjustment bolt **368** abutting a first corner **371** and threaded through an opposing corner **370** of the shape. The other corners **372** may include pads **374** for positioning against opposing articular faces of a facet joint. The implant **364** may be placed into the facet joint in a collapsed position and the adjustment bolt **368** may then be actuated to draw the opposing corners **371, 372** of the shape together thereby expanding the shape and pressing the pads **374** against the articular faces. As the shape expands, additional facet distraction is achieved resulting in an increased foraminal opening. This implant **364** may be provided in a number of geometries or materials to provide directional distraction where, for example, more distraction occurs near the posterior edge of the facet relative to the

anterior edge of the facet. Additionally, the surface of the pad **374** may include teeth or keels to enable bone purchase in the facet.

[0295] FIGS. **55A-C** show another embodiment of an implant **376**. In this embodiment, the implant **376** may take the form of an expandable hinged structure with an upper member **378** and a lower member **379** connected at their distal ends **380** by a hinge **382**. The implant **376** may be placed between the facet surfaces in a collapsed state. The posterior aspect of the implant **376** may include a receiving slot that is able to receive a screw, bolt, or other activation system. Engaging this slot with an activator would cause the implant **376** to expand on its hinge **382** creating distraction and translation of the joint. For example, the activator may be a wedge, a turnable flat tool, a tapered screw, or any other device that may be inserted into the receiving slot to forcibly expand the upper **378** and lower **379** members. As shown, the hinge **382** may also include a brace member **384** for maintaining the posterior halves of the hinge in a separated position. The brace member **384** may be spring loaded or otherwise engaged with the hinge halves **378, 379** such that when expanded the brace **384** moves into position to support the open position of the hinge **382**. In some embodiments, the upper **378** and lower **379** member of the implant **376** may have teeth, cleats, or keels **386** to engage the cortical bone of the opposing facet surfaces. These mechanisms would provide fixation of the implant **376** to the joint.

[0296] FIGS. **56A-C** include another embodiment of an implant **388**. In this embodiment, a collapsed and flattened structure **390** may be placed between the opposing surfaces of the facet joint. The posterior aspect **392** of the structure **390** may be configured to be capable of receiving a screw, bolt, or some other inserted component **394**. Upon insertion of the screw, bolt, etc. **394**, the structure may begin to expand. This expansion and separation may be enabled by a hinge **396** at the anterior aspects of the structure **390**. As the structure **390** expands, sharp directional teeth, cleats, or keels **398** on the opposing (superior & inferior) surfaces of the structure may become anchored in the cortical bone of the opposing facet surfaces. These teeth, cleats, or keels **398** may engage the face surfaces and provide acute fixation of the structure within the facet joint. Together with the these teeth, cleats, or keels **398**, or as an alternative to them, as shown, the proximal end of the implant **388** may also include flanges **400** that overlap the lateral mass of the facet joint. These flanges **400** may include holes **402** for anchoring the implant **388** to the superior and inferior facet masses, or to only one of the masses. In a related embodiment, the superior and inferior surfaces may have open ports **404** that enable the screw threads to exit the structure and gain purchase in the opposing facet surfaces. The distraction and separation of the joint may increase foraminal area and reduce the symptoms associated with nerve root compression.

[0297] FIGS. **57A-C** show yet another embodiment of an implant **406**. In this embodiment, the implant **406** may resemble a screw and wall anchor. The wall anchor portion **408** may be generally cylindrically shaped and include two half sections **410** separated by a slot or it may include a multitude of longitudinally extending sections **410**. These sections **410** may be connected together at the tip **412** as shown or they may be connected together at the proximal end **414** of the implant **406** and at the tip **412** and may include several connections along the length of the implant **406**. The implant **406** may have a sharp, triangular or conical tip **412**

that allows for access into the flattened facet joint. Once the implant **406** is inserted into the facet surface, a screw, bolt, or other insertion component **416** may be inserted into the implant **406**. As this component **416** is advanced the sections **410** may expand creating additional separation of the joint and allowing for measured distraction of the space. The sections **410** of the wall anchor portion **408** may include sharp directional teeth, cleats, or keels **418** that engage the cortical bone of the opposing facet surfaces.

[0298] FIGS. 58A-B show yet another embodiment of an implant **420**. In this embodiment, a tool **422** may be used to apply a force to the superior vertebra of a motion segment. This forward translation would result in an increase in foraminal area and reduced nerve root decompression. Following the forward translation of the motion segment, an angled screw **424** would be placed through the superior facet surface, facet capsule, and inferior facet surface. This screw **424** would provide temporary immobilization of the joint which leads to fusion.

[0299] FIGS. 59A-B show yet another embodiment of an implant **426**. In this embodiment, a collapsed, triangular shaped implant is inserted into the facet. The implant **426** may include a central shaft **428** and two or more springing leaves **430**. The leaves **430** may be connected to the distal end of the shaft **428** and may extend proximally along the shaft **428**. The leaves **430** may be connected at the distal end so as to be biased in a direction to form an arrow shape. The leaves **430** may be held in the compressed state by an insertion & delivery tool **432**. The delivery tool's compression of the implant **426** prevents the superior and inferior surfaces of the implant **426** from springing open to a distracted position. Once the compressed implant **426** is positioned correctly, the delivery tool **432** may be removed. Removing the tools causes the leaves **430** to open/expand causing distraction and separation of the facet joint thus resulting in increased foraminal area and reduced nerve root compression.

[0300] FIGS. 60A-B show yet another embodiment of an implant **434**. This concept has at least three embodiments. The first embodiment consists of a direction facet joint screw **436** that is advanced through an inferior facet until it makes contact with the opposing superior facet. Once the screw **436** makes contact with superior facet surface, the energy applied to advance the screw **436** results in distraction and separation of the joint due to bearing of the screw tip **438** on the underside of the superior articular surface. In one variation of this embodiment, the hole for the screw in the inferior facet may be pre-drilled. When the screw is installed and encounters the superior facet, the screw may bite into the superior facet as it forces the fact upward and distracts the joint. Alternatively, in this embodiment, the screw may have a blunt tip **438** to distract the joint without biting into the superior facet.

[0301] In the second embodiment, as shown, a directional facet screw **436** may be advanced through the inferior facet surface until it engages with a facet spacer/plate **440** that is inserted in between the facet surfaces within the facet capsule. As the screw **436** makes contact with the facet spacer/plate **440**, the flat surface of the spacer/plate **440** may push up against the opposing superior facet surface causes distraction and forward translation. This separation of the facet surfaces results in increased foraminal area and reduced nerve root compression.

[0302] In a third embodiment, the spacer/plate **440** may have a shape to allow the screw **436** to pass through a first end and the other end to be placed in the facet joint. In this

embodiment, the C-shaped spacer **440** may be positioned in the joint, thereby slightly distracting the joint. The screw may then penetrate a first end of the spacer **440** thereby anchoring the spacer **440** in the joint. The screw may then be advanced through the inferior facet surface until it engages with the spacer/plate **440**. As the screw **436** makes contact with the facet spacer/plate **440**, the flat surface of the spacer/plate **440** may push up against the opposing superior facet surface causes distraction and forward translation. In some embodiments, the screw may penetrate the spacer and aid in fixing the joint.

[0303] FIGS. 61A-C show yet another embodiment of an implant **442**. In this embodiment, bracket type structures **444** may be attached to the superior and inferior lateral masses. The bracket type structures **444** may enable the attachment of a single bolt **446**. The bolt **446** may be configured to create a distraction energy. That is, it may be connected to the inferior bracket **444** to allow rotation but not relative translation. In contrast, the bolt may threadably engage the superior bracket **444**. As such, when the bolt **446** is "unscrewed" it may function to push the inferior and superior brackets **444** apart. This distraction may result in increased foraminal area and reduction in nerve root compression.

[0304] FIGS. 62A-C show yet another embodiment of an implant **448**. In this embodiment, bracket type structures **450** may each have a leg **452** for positioning within a facet joint and another leg **454** for receiving a bolt **456**. As with the bracket above, the bolt **456** may be configured to create distraction energy. That is, it may be connected to one of the superior or inferior bracket **450** so as to allow rotation but not relative translation. The other bracket **450** may threadably engage the bolt **456**. As such, when the bolt **456** is "unscrewed" it may function to push the brackets apart resulting in and increased foraminal area.

[0305] FIGS. 63A-C show yet another embodiment of an implant **458**. In this embodiment, a triangular shaped implant **458** including a bent plate and a filler wedge may be inserted in the facet joint. As the triangular implant **458** is inserted progressively more anterior, the joint may be distracted to an optimal level. Once the desired distraction is achieved, an anchoring screw **460** may be inserted through the implant **458** and into the inferior lateral mass. The superior aspect of the implant **458** may include a metal flap **462** with teeth, spikes, or cleats **464**. This maleable flap **462** may be contoured to the superior lateral mass and anchored using its teeth, spikes, or cleats **464**. The metal flap **462** and inferior screw **460** may provide permanent fixation of the triangular implant **458** to enable permanent distraction of the facet and immobilization of the joint facilitating permanent fusion of the joint.

[0306] FIGS. 64A-C show yet another embodiment of an implant **466**. In this embodiment, a distraction system consists of a central anchoring plug **468**, an initiating plate **470**, and two external plates **472**. The two external (superior and inferior) plates **472** may be attached to the lateral masses of a motion segment and may be anchored using screws. The initiating plate **470** may then be inserted in the gap **471** between the external plates **472** to initiate opening of the plates **472** and the joint and allow for further insertion of the anchoring plug **468**. Following the insertion of this initiating plate **470** and turning or manipulating the plate **470** to open the external plates **472**, the central anchoring plug **468** may then be advanced into the gap **471** between the external plates **472** causing expansion of the plates and distraction and separation of the joint.

[0307] FIGS. 65A-C show yet another embodiment of an implant 474. In this embodiment, nitinol hooks 476 may be configured to have a memory. The hooks 476 may be flattened and inserted through a delivery system 478. The delivery system 478 may be placed in a facet joint. Once inserted within the facet, the nitinol hooks 476 may be activated via temperature, force, or other activation means causing them to assume their original (pre-flattened) shape and hook into the opposing facet surfaces. As the hooks 476 engage the cortical bone of the facet surfaces, they distract the joint. This separation results in increased foraminal area and reduced nerve root compression.

[0308] FIGS. 66A-C show yet another embodiment of an implant 480. In this embodiment, a hollow screw sleeve 482 may be placed within the facet joint. A wedge 484 may then be placed within the hollow screw sleeve 482 causing it to expand and distract the joint. Additionally, the screw sleeve 482 may include sharp barbs 486 having a retracted position and an ejected position. As the wedge 484 is inserted, the wedge 484 displaces the sharp barbs 486 causing them to be ejected through the screw sleeve 482 and engage the facet surfaces. These barbs 486 may provide acute fixation of the implant 480 to the joint and prevent migration of the implant 480. The distraction and separation of the joint result in increased foraminal area and reduced nerve root compression.

[0309] FIGS. 67A-C show yet another embodiment of an implant 488. In this embodiment, a panel anchor implant 488 may be placed within the facet joint. The implant 488 may include a bolt 490 and collapsible nut 492 that is rotationally free from the bolt 490 near the head of the bolt 490 and threadably engaged with the bolt 490 near the end opposite the head. As such, when the bolt 490 is advanced, the distal end of the nut 492 is squeezed toward the proximal end of the nut 492 and the nut 492 may collapse with an accordion effect. As shown, the compression of the nut 492 results in a taller structure that applies a distraction force to the opposing facet surfaces. This distraction leads to increased foraminal area and reduced nerve root compression.

[0310] In similar fashion, the embodiment shown in FIGS. 68A-C may collapse causing distraction of the joint. In lieu of the nut 492 shown in FIGS. 67A-C, this embodiment, shows a flat plate 494 that collapses into an accordion shape.

[0311] FIGS. 69A-C show yet another embodiment of an implant 496. In this embodiment, an implant 496 is placed within the facet joint. The implant could have a number of shapes and sizes but, in this embodiment, has a tension wire 498 that surrounds the implant 496 and is pulled taught during implantation. Once the implant 496 is properly positioned, the wire's tension is released. The release of this tension causes the wire 498 to return to a preset expanded shape and height that causes the implant 496 to expand. The expansion of the implant 496 as the wire returns to its preset, and larger profile, shape causes separation of the facet joint. This distraction results in increased foraminal area and reduced nerve root compression.

[0312] Similarly, as shown in FIGS. 70A-C, an implant 500 with an outer housing 502 and an internal spring 504 may be positioned in the facet joint with the wire spring 504 in a tensioned or elongated position. Once properly positioned, the tension on the spring 504 may be released thus collapsing the spring 504 and expanding the associated housing 502 of the implant 500.

[0313] FIGS. 71A-C show yet another embodiment of an implant 506. In this embodiment screw type implant 506 may be provided and may also include an arm type locking mechanism 508. The locking mechanism 508 may extend from all sides of the head of the screw as shown and may be biased in a distal direction. As the screw advances, the locking mechanism 508 may anchor in the lateral mass of a vertebra. The biased position of the arm 508 pressing against the lateral mass may provide a force biasing the implant 506 against the advancing direction. However, this may cause constant friction between any newly cut threads in the surfaces of the facet joint thereby preventing unscrewing or back out of the implant. In addition, teeth 509 may be included on the arms 508 and may bite into the lateral mass further preventing backing out of the implant.

[0314] FIGS. 72A-C show yet another embodiment of an implant 510. In this embodiment, two wedge shape opposing structures 512 are shown separated by a sloping plane 514. The structures 512 may have a predetermined relative position, or a series of predetermined relative positions, where a bolt or screw 516 may be advanced at an angle as shown through one of the structures 512 and into a predrilled hole of the other 512 to maintain their relative position. Alternatively, the relative positions may not be predetermined and a self-drilling screw 516 may be used. In either case, the implant 510 may be positioned in the facet joint in minimal profile position and then the two structures 512 may be slid relative to each other along the sloping plane 514 to expand the implant 510 and thus the facet joint. Once the desired position is achieved, the bolt, pin, screw, or other fastener 516 may be inserted to maintain the relative position of the structures 512.

[0315] FIGS. 73A-C show yet another embodiment of an implant 518. In this embodiment, an implant 518 is configured to be inserted in a collapsed state. In its non collapsed state, it has a vertical cylindrical profile with side cutouts 520. When the implant is compressed, the side cutouts 520 allow the wall panels 522 to bend out as the height of the cylindrical implant 518 is reduced. These wall panels 522 create an anchor shape that can engage bone structures. This implant 518 may be placed within the facet joint in its flattened, compressed profile. Once it is positioned correctly, a distraction energy may be applied to the implant 518 to cause it to expand or decompress. This decompression causes the implant 518 to attempt to return to its vertical cylindrical shape. The implant 518 may be made from a resilient elastic material such as nitinol, stainless steel, or other known materials. As the implant 518 becomes more cylindrical, it pushes against the opposing facet surfaces. This force causes distraction of the facet joint and results in increase foraminal area and reduced nerve root compression.

[0316] Similarly, as shown in FIGS. 74A-C, the implant 518 may be positioned on its side and the distraction energy may cause the implant 518 to collapse from its cylindrical shape and expand laterally to distract the facet joint.

[0317] FIGS. 75A-B show yet another embodiment of an implant 524. In this embodiment, a delivery tool 526 is inserted within the facet joint. The distal tip 528 of the delivery tool 526 is shaped to distract the joint. Once the tool 526 is inserted into the facet joint and the desired amount of distraction is achieved, the distal tip 528 (part that is in the facet joint) may be detached from the delivery tool 526. In one configuration of this embodiment, the detachable tip 528 would have teeth, cleats, spikes, or keels 530 to prevent it from migrating within the joint once it is detached. In another

configuration of this embodiment, the implant **524** may be anchored in the facet joint by inserting a screw **532** through the superior facet, the implant, and the inferior facet. In both configurations, the detachable tip **526** (implant) may provide permanent distraction of the joint resulting in increased foraminal area and reduced nerve root compression.

[0318] FIGS. 76A-C show yet another embodiment of an implant **534**. In this embodiment, the implant **534** may include a housing **536** with a central gear **538** turnable by an alien type head **540** or other known attachment for turning, such as any known screwdriver heads. Adjacent the central gear **538** on each side, the implant **534** may include two plates **542** slidable in the housing **536** in a direction tangential to the gear surface. The plates **542** may include teeth **544** engaging the central gear **538** such that when the gear **538** turns, the plates **542** slide tangentially to the gear **538** and extend beyond an outer surface of the housing **536**. As such, the implant **534** may be positioned in a facet joint as shown in FIG. 76A. Once positioned, the gear **538** may be turned thus extending the plates **542** in opposite directions and distracting the facet joint.

[0319] FIGS. 77A-C show another embodiment of an implant **546**. In this embodiment a triangular shaped implant **546** in the form of a bent plate **548** may be wedged into the facet causing distraction and separation of the joint. On one side of the triangular distraction structure **548** is a bracket **550** with a screw **552**. The screw **552** may be inserted into the lateral mass to provide anchoring of the facet distraction implant **546**. The other side of the triangular distraction structure **548** may include teeth or other features **554** for biting into the associated lateral mass. The implant **546** would provide permanent distraction of the joint resulting in increase foraminal area and reduced nerve root compression.

[0320] FIGS. 78A-C show another embodiment of an implant **556**. In this embodiment, the implant **556** may have a tapered shape that is taller at the posterior aspect relative to the anterior aspect. The implant could be tapped in, malleted in, screwed in with threads, or pushed in with hand pressure. Once the implant **556** is positioned correctly, the head **558** of the implant **556** (posterior aspect) may be configured to have sharp teeth, spikes, or cleats that can be pushed into the cortical bone of the superior and inferior lateral masses of a motion segment. These flaps **558** could be hinged on the posterior aspect of the implant **556** to allow the flaps **558** to be pushed anterior enough to match the irregular contours of the lateral mass. The implant **556** would provide permanent distraction of the joint resulting in increase foraminal area and reduced nerve root compression.

[0321] FIGS. 79A-C show another embodiment of an implant **560**. In this embodiment, the implant **560** includes a single rotatable cone **562** with a shoulder shaped ledge **564** defining a cam surface **566**, the distance between the ledge and the bottom of the implant defining a shoulder height. The shoulder height may vary gradually from low to high and back to low along the circumferential perimeter of the cone **562**. In use, the implant **560** may be initially positioned such that the shoulder portion with the low ledge height enters the facet joint. Once in position, the implant **560** may be rotated to cause the higher ledge height to enter the joint thereby distracting the posterior portion of the joint by causing the superior articular face to ride upward along the cam surface **566**. The implant **560** may then be secured with a screw **568** extending along the longitudinal axis of the implant.

[0322] FIGS. 80A-D show yet another embodiment of an implant **570**. In this embodiment, an implant **570** may include a housing **572** with penetrations **574** adapted for ejection of retracted spikes **576**. Within the housing **572**, a wire **578** may be routed between the spikes **576** as shown in FIG. 80D. The implant **570** may be inserted into the facet joint while the wire **578** is relaxed and the spikes **576** are contained within the folds/curves in the collapsed wire **578**. Once the implant **570** is positioned correctly, the wire **578** may be pulled taught causing the spikes **576** to displace outwardly, extending out of the housing **572** and engaging the opposing facet surfaces with a force. This force may create distraction and separation of the joint, while the pointed tips of the spikes **576** would penetrate the surface of the facet joint and provide acute fixation preventing migration of the implant **570**. The implant **570** would provide permanent distraction of the joint resulting in increase foraminal area and reduced nerve root compression.

[0323] FIGS. 81A-C show yet another embodiment of an implant **580**. In this embodiment, an implant **580** may include a housing **582** with a cavity **584** and penetrations **586** on lateral surfaces extending from the cavity **584** through the wall of the housing **582**, the penetrations **586** adapted for ejection of retracted spikes **588**. Within the housing **582**, a threaded piston **590** may be positioned at a distal end and may be adapted for displacement through the cavity **584** in the proximal direction. The piston **590** may have a torpedo shaped distal end **592** and may engage the a beveled inner surface **594** of the retracted spikes **588**. The implant **580** may be positioned within a facet joint and when properly positioned, the piston **590** may be advanced via a turning tool, the torpedo shaped distal end **592** of the piston **590** thus engaging the beveled end **594** of the spikes **588** and advancing them laterally relative to the implant **580** out of the housing **582** with a force and into the face of the facets. This force may create distraction and separation of the joint, while the pointed tips of the spikes **588** would penetrate the surface of the facet joint and provide acute fixation preventing migration of the implant **580**.

[0324] FIGS. 82A-F show yet another embodiment of an implant **596**. In this embodiment, the implant **596** may include two parallel equal length side bars **598** with pivoting struts **600** positioned on a pin **602** between the bars **598** at each end. The pivoting struts **600** may include textured surfaces **604** on each end and the struts **600** may be pinned to the side bars **598** through one end. As shown in FIG. 82F, the struts **600** may have length so as to allow them to be pivoted to lie parallel to one another in the plane of the side bars **598**. In this position, the implant **596** may be positioned in the facet joint as shown in FIG. 82A or anterior to the facet joint as shown in FIG. 82D. Once properly positioned, the struts **600** of the implant **596** may be rotated so as to be approximately perpendicular to parallel side bars **598** thus separating an inferior vertebra from a superior vertebra. It is noted that the generally stout shape of the struts **600** with relatively broad textured ends **604** may facilitate stability preventing the implant **596** from racking back to the parallel condition.

[0325] Another variation of this embodiment is shown in FIGS. 83A-B, where a series of varying height struts **600** are positioned along a shaft. The entire implant may be placed within a facet joint on its side and then a single ninety degree turn may position the implant and distract the joint.

[0326] FIGS. 84A-B show yet another embodiment of an implant **606**. In this embodiment, two rotatable cams **608** may

be positioned in a facet joint. It is noted that the cams may have a relatively low profile and the proportions in the FIGS. may be exaggerated for purposes of showing the concept. Once placed in the joint, a distraction/rotation energy may be applied to the cams causing them to rotate open to reveal two circular halves of the cam implant. As one half of the implant rotates superiorly, it may push the superior vertebra upward creating an increase in foraminal area and nerve root decompression.

[0327] In another embodiment, a kit is provided. As shown in FIGS. 85 and 86, the kit may include a delivery device 610, a chisel 612, several internal and external decorticators 614, 616, 618, and a driver assembly 620. As shown in FIGS. 87 and 88, the chisel head 622 and shaft 624 may be provided in two pieces that may be combined with a press fit. As shown in FIG. 89, the delivery device 610 may be provided in two pieces combinable with a press fit, the first piece being a tubular shaft and fork piece 626 and the second piece being a receiving assembly piece 628. As shown in FIGS. 90-93, the driver assembly 620 may be provided in several pieces including the internal actuator and the implant shaft/arms/handle portion. FIG. 90 shows the shaft/arms/handle portion comprising two pieces, the first piece being a shaft with arms 630 and the second piece being the handle 632. FIGS. 91 and 92 show the internal actuator including a tip 634, a shaft portion 636, an adapter 638, a pin 640, and a distractor knob 642. In addition to the elements shown, one or several implants may be provided as well as an injector as previously described. Several traditional instruments for use in accessing the surgical site and closing the surgical site may also be provided.

[0328] Referring now to FIGS. 94-116, another embodiment of a tool 800 is shown. FIGS. 94-98 show a chisel 808, a delivery device 804, a decorticator 806, a driver assembly 842, an internal actuator 852, and an injector 902.

[0329] As shown in FIG. 95, the delivery device 804 may include a receiving assembly 810 at a proximal end, anchoring forks 812 at a distal end, and a generally tubular shaft 814 defining a longitudinal axis and extending between the receiving assembly 810 and the anchoring forks 812. The tubular shaft 814 may have an annular shaped cross-section with an inner radius and an outer radius, where the difference between the two radii defines a thickness of the tubular shaft 814. Some of the features of the delivery device 804 will now be described and additional features of the delivery device 804 may include those features shown and described with respect to delivery device 104. For example, the delivery device 804 may include two anchoring forks 812.

[0330] The receiving assembly 810 of the delivery device 804 may have a generally rectangular outer surface defining a generally solid volume with a bore 811 there through. The bore 811 may be positioned proximal to and in alignment with the tubular shaft 814 and may have an inner radius matching that of the tubular shaft 814 allowing for a smooth transition of devices from the receiving assembly into the tubular shaft. The receiving assembly 810 may include a seating cavity 813 at its proximal end for receiving and seating of other devices such as the driver assembly 842 or the injector 902. The seating cavity 813 may be defined by an outer shell 815 that is substantially flush with the outer surface of the receiving assembly 810. The shell 815 may include protrusions or recesses 817 on its inner surface, the protrusions or recesses 817 corresponding to protrusions or recesses on other devices. As such, these protrusions or recesses 817 may pro-

vide for a detent relationship between the delivery device 804 and other devices. The rectangular outer surface of the receiving assembly 810 may have a long side and a short side. The long side may be oriented parallel to a line connecting the forks 812 in turn aligning the seating cavity 813 with the forks 812. As such, devices used with the delivery device 804 may be properly aligned relative to the forks 812 by positioning and seating them in the seating cavity 813. Additionally shown on the outer surface of the receiving assembly 810 is a decorticator release button 819. As shown, the button 819 may include slots on either side creating a cantilevered tab condition for the button 819. As such, the button 819 may deflect about its proximal end when depressed. The button 819 may also include recesses or bumps on its surface for gripping. The button 819 may extend beyond the distal end of the receiving assembly 810 and may include an upwardly extending ridge 821. The ridge 821 may be shaped and adapted to engage the decorticator 806 as described in greater detail below. There may be one button 819, or two buttons 819, one on each face of the receiving assembly 810. Any number of buttons 819 may be included, for example in the case of a varying shaped receiving assembly, 810.

[0331] Referring to FIG. 94, the chisel 808 may have a generally cylindrical cross-section forming a shaft 828. The shaft 828 may have a radius substantially equal to the inner radius of the tubular shaft 814 portion of the delivery device 804 allowing for slidable insertion of the chisel 808 within the delivery device 804. Alternatively, the radius of the shaft 828 may be smaller than the inner radius of the tubular shaft 814 providing for more play and adjustability of the chisel 808 and delivery device 804 relative to one another. The chisel 808 may include a single or doubly chamfered tip 830 at a distal end or may have a coped distal end. The chisel 808 may include a head or, in contrast to the chisel 108 described with respect to FIG. 1, the chisel 808 may not include a head as shown in FIG. 94. The chisel 808 may have an overall length slightly larger than the delivery device 804 so as to allow the chisel to be manipulated by its proximal end when sleeved within the delivery device 804. Additional features of the chisel 808 may include those features shown and described with respect to chisel 108. For example, similar to the chisel shown and described with respect to FIG. 1A, the chisel 808 may also include a longitudinally extending lumen 131. A more detailed view of the chisel 808 and its chamfered tip 830 may be seen in FIG. 94A. As shown, the chisel 808 may include a circumferential bevel at its proximal end opposite the chamfered tip 830.

[0332] In comparison to the use described with respect to FIG. 5 above, it is noted that the chisel 808 may allow the option of inserting the chisel 808 prior to the delivery device 804 and sleeving the delivery device 804 over the chisel 808. This is in contrast to the chisel 108, with the head 132, where the head 132 prevents the delivery device 104 from being sleeved over the chisel 108. As such, the facet joint may be distracted by the chisel 808 initially allowing for smoother insertion of the delivery device 804. Upon placement and proper positioning of the delivery device 804, the chisel 808 may then be removed. Those of skill in the art will understand and appreciate that a chisel with a removable head may also be provided and may allow for either order of insertion of the delivery device 804 and chisel 808 and the removable head, once replaced, may then be used to more readily manipulate and properly position the chisel 808.

[0333] In some embodiments, the forks **812** at the distal end of the delivery device **804** may have a bull nose tip as shown in FIG. **95A**. This is in contrast to the relatively sharp tip shown in FIGS. **2-4** with respect to forks **112**. The use of a chisel **808** without a handle, which may allow for insertion of the chisel **808** prior to the delivery device **804**, may, in turn, allow for this bull nose tip because the facet joint may be distracted prior to insertion of the delivery device **804**.

[0334] Referring again to FIG. **95**, the decorticator **806** may have a tubular shaft portion **834**, an abrasive distal end **836**, and a handle **838** at a proximal end. The tubular shaft **834** may have an inner radius substantially equal to the outer radius of the tubular shaft **814** of the delivery device **804** and may allow for sliding movement of the decorticator **806** along the length of the delivery device **804** and rotationally around the delivery device **804**. In some embodiments, the inner radius of the tubular shaft **834** may be slightly or substantially larger than the outer radius of the tubular shaft **814** of the delivery device allowing for more freedom of movement of the decorticator **806**. The abrasive distal end **836** may include serrated teeth as shown, or may include a more flat annular surface with a gritty surface. The handle **838** may include a generally cylindrical shaped knob with a gripping surface along its peripheral edge. The handle **838** may also include a cavity on its proximal face for receiving a distal end of the decorticator release button **819**. The cavity may thus create an inner cylindrical surface opposite the gripping surface of the handle **838**. The inner cylindrical surface may be beveled or may include a groove for receiving the tip of the ridge **821** extending upwardly from the release button **819**. As such, where the release button **819** is in its natural state, the ridge **821** may project into the groove or opposed to the beveled surface of the handle **838** preventing the decorticator from being advanced distally. Where the release button **819** is depressed, the ridge may be removed from the groove or beveled surface allowing the decorticator to advance freely. Additional features of the decorticator **806** may include those features shown and described with respect to decorticator **106**. For example, the decorticator **806** may alternatively be separate from the delivery device **804** and may be slidably inserted within the delivery device **804** similar to that shown and described with respect to FIG. **4** or FIGS. **6A-6C**.

[0335] Referring now to FIGS. **99-101**, the delivery device **804** and a driver assembly **842** are shown. As shown in FIG. **99**, the driver assembly **842** includes a handle **844**, an implant shaft **846**, and implant holding arms **848**. The driver assembly **842** shown is holding an implant **154**. The handle **844** of the driver assembly **842** may have an outer surface defining a generally rectangular volume with a bore **843** there through. The bore **843** may have an inner diameter substantially equal to the inner diameter of the implant shaft **846** allowing for a smooth transition of devices passing through the driver assembly **842**. The handle **844** may have a necked down portion **845** at its distal end. The necked down portion **845** may have protrusions or recesses **847** on its outer surface corresponding to respective protrusions or recesses **817** on the inner surface of the shell **815** of the receiving assembly **810** on the delivery device **804**. As such, and as shown in FIGS. **100** and **101**, the driver assembly **842** may be sleeveably positioned within the delivery device **804** to deliver an implant **154/854** to the facet joint. When fully advanced as shown in FIG. **101**, the handle **844** may be seated securely in the seating cavity **813** of the receiving assembly **810** and anchored with a detent relationship. Additional features of the

driver assembly **842** may include those features shown and described with respect to driver assembly **142**.

[0336] A more detailed view of the implant holding arms **848** is shown in FIG. **99A**. As shown, the implant holding arms **848** may include a chamfered tip. Additional features of the arms **848** may include features similar to those shown and described with respect to arms **148** in relation to FIG. **11**. For example, the inside surface of the arms **848** may include a longitudinal ridge **862** extending the length of the arms **848**. The arms **848** may also include a bull nose engagement feature **858** extending transverse to the longitudinal axis of the implant shaft **846** along the inside face of the arm **848**. Where the arms **848** are engaged with and holding the implant **154/854**, the longitudinal ridges **862** of each arm **848** may be positioned between upper and lower planar members of the implant **154/854** and the bull nose engagement features **858** may be positioned in the U-shaped receiving feature slots on the lateral edges of the implant **154/854**.

[0337] In contrast to the driver assembly **142** described above, in the present embodiment shown in FIGS. **102-105**, the internal actuator **852** may be a separate device from the driver assembly **842**. That is, while the internal actuator **852** may still function by passing longitudinally through the driver assembly **842**, the internal actuator **852** may be a separate device with its own handle **853**. The internal actuator **852** may include a longitudinal shaft **855** and an internal rod **857**. The longitudinal shaft **855** may be cylindrically shaped with an annular cross-section. The shaft **855** may have an outer diameter substantially the same as or smaller than the inner diameter of the implant shaft **846** of the driver assembly **842**. The shaft **855** may extend from the handle **853** proximally to a distal end. The internal rod **857** may be positioned within the shaft **855** and also may extend from the handle **853** to a distal end. The internal rod **857** may include an engagement feature **859** at its distal end for engaging and holding the implant distractor **850**. This engagement feature **859** may be any shape and provide for any engagement known in the art from a hex, allen, phillips, star, square, sleeve, or other connection capable of transmitting longitudinal and/or rotational forces from the internal rod **857** to the implant distractor **850**. As shown, in one embodiment, the engagement feature **859** includes a collet type device that is described in more detail with respect to FIG. **109** below. As shown, the internal rod **857** may sleeveably receive the implant distractor **850**. The internal rod **857** may be sleeveably positioned within the longitudinal shaft **855**, such that when the longitudinal shaft **855** is in an advanced position over the end of the internal rod **857**, the longitudinal shaft **855** causes a clamping force of the collet to restrain the implant distractor **850** against being dislodged from the collet. Each of the shaft **855** and the internal rod **857** may engage the handle **853** at their respective proximal ends. The handle **853** may be used to retract the longitudinal shaft **855** along the length of the internal rod **857** thereby exposing the collet and reducing the clamping force. As such, when the longitudinal shaft **855** is in a retracted position, an implant distractor may be inserted into and/or removed from the collet.

[0338] As shown in FIGS. **104** and **105**, the handle **853** may be a cylindrical/spherical handle or a T-type handle. Referring to FIG. **104**, the cylindrical/spherical handle may include an outer cylindrical portion **861** capped at a proximal end by a first spherical portion **863**, the first outer cylindrical portion **861** being open at a distal end. The handle **853** may also include an inner cylindrical portion **865** capped at a distal end

by a second spherical portion **867**, the inner cylindrical portion **865** being open at a proximal end. As shown, the proximal open end of the outer cylindrical portion **861** may be positioned opposing the distal open end of the inner cylindrical portion **865** and the inner cylindrical portion **865** may sleeveably slide within the outer cylindrical portion **861**. The handle **853** may further include a collar **869** integral with the second spherical portion **867**, positioned concentrically to each of the outer and inner cylindrical portions **861**, **865** and extending distally away from the second spherical portion **865**. Those of skill in the art will understand and appreciate that the collar **869** could also extend in a proximal direction. In either case, the shaft **855** of the internal actuator **852** may be connected to the distal end of the collar **869** and extend distally there from. The internal rod **857** of the internal actuator **852** passing proximally through the shaft may sleeveably penetrate the collar **869** and the second spherical portion **867**, extend through the handle **853** to the inner/distal surface of the first spherical portion **863**, and be coupled thereto. In addition, the first and second spherical portions **863**, **867** may have a biasing mechanism **871** positioned between them in the form of a spring, balloon, or other force inducing device. Those of skill in the art will understand and appreciate that the spherical portions **863**, **867** could be flat, concave, or otherwise shaped and are not limited to spherical shaped caps.

[0339] In use, as understood by a review of FIGS. **103** and **104**, a user may insert the internal actuator **852** through the driver assembly **842**, which is positioned and seated in the delivery device **804**. The internal actuator **852** may be used to advance and position the implant distractor **850** for advancement into the implant. Once properly positioned, the internal actuator **852** may be rotated via the handle **853** to advance the implant distractor **850**. In the cases of other implant distractors, the handle **853** may be otherwise manipulated to advance the implant distractor. Once the implant distractor is advanced and the implant is distracted, a user may compress the first and second spherical portions **863**, **867** toward one another against the force of the biasing mechanism **871** (e.g. by squeezing the handle with their hand). The inner cylindrical portion **865** of the handle **853** may retract relative to the outer cylindrical portion **861** causing the longitudinal shaft **855** also to retract relative to the outer cylindrical portion **861**. This retracting motion relative to the internal rod **857** may cause the distal end of the longitudinal shaft **855** to be retracted and expose the collet on the distal end of the internal rod **857**. As such, the clamping force of the collet on the implant distractor **850** may be reduced allowing for removal of the internal actuator **852**, while leaving the implant distractor **850** behind and in place in the implant. It is noted that the shaft portion **855** of the implant distractor **852** may include a keyway for engagement with the inner surface of the implant shaft **846** of the driver assembly **842**. As such, the shaft **855** of the internal actuator **852** may be prevented from rotating relative to the internal rod **857**.

[0340] Referring now to FIG. **105**, the T-type handle may have a cylindrical, rectangular, square, or other transverse cross-section, with a longitudinal axis extending generally perpendicular to the longitudinal axis of the internal rod **857** and shaft **855** and forming a T-shape. The longitudinal cross-section of the handle **853**, as depicted in FIG. **105**, may include a proximal portion **873** and a distal portion **875** connected at one end and separated by a gap **877**. The proximal portion **873** may be a relatively thick portion and the distal portion **875** may be relative thin. As such, the handle **853** may

be squeezable and may provide a biasing force which works to maintain the gap **877** between the distal and proximal portions **873**, **875**. The handle **853** may also include a generally cylindrical or conical collar **879** positioned near the middle of the handle **853** along its longitudinal length. The collar **879** may be positioned parallel to and concentrically with the internal rod **857**. The shaft portion **855** of the internal actuator **852** may extend distally from the distal end of the collar **879**. The internal rod **857** may sleeveably penetrate the collar **879** and the distal portion **875** of the handle **853** and may further be coupled to the proximal portion **873** of the handle **853** in a cylindrical bore **881**. A stop may be provided to prevent the internal rod **857** from passing proximally through the proximal portion **873** of the handle **853**. This may be in the form of a cap on the proximal portion **873** of the handle **853** covering the bore **881**, or the bore **881** may not pass all the way through the proximal portion **873** of the handle **853**. Alternatively, the internal rod **857** may be secured within the bore.

[0341] In this embodiment, as understood by a review of FIGS. **103** and **105**, the internal actuator **852** may be inserted through the driver assembly **842** and the implant distractor **850** may be advanced in the same or similar fashion as that described with respect to the internal actuator **852** of FIG. **104**. When the internal actuator is ready for removal, a user may compress the proximal **873** and distal **875** portions of the handle **853** toward one another against the biasing force by squeezing the handle **853**. The distal portion **875** of the handle **853** may retract relative to the proximal portion **873** causing the longitudinal shaft **855** also to retract relative to the proximal portion **873**. This retracting motion of the longitudinal shaft **855** relative to the internal rod **857** may cause the distal end of the longitudinal shaft **855** to be retracted and expose the collet on the distal end of the internal rod **857**. As such, the clamping force of the collet on the implant distractor **850** may be reduced allowing, for removal of the internal actuator **852**, while leaving the implant distractor **850** behind and in place in the implant.

[0342] Still another embodiment of a handle **853** is shown in FIGS. **106-108**. In this embodiment, a gripping mass **883** with a knob **885** is shown. A knob **885** is positioned on the proximal end of the internal rod **857** via a bore **887**. The knob **885** may be affixed against relative rotation with the internal rod **857**. The gripping mass **883** may include a generally rectangular mass spaced from the knob **885** along the internal rod **857** and including a bore **889** for the internal rod **857** to pass there through. The bore **889** may sleeveably receive the internal rod **857**. The gripping mass **883** and the internal rod **857** may form the shape of a T and the gripping mass **883** may be affixed to the proximal end of the longitudinal shaft **855**. The gripping mass **883** may be held apart from the knob **885** along the internal rod **857** by a biasing mechanism **891** in the form of a spring, balloon, or other known device.

[0343] The implant distractor **852** shown in FIGS. **106** and **107** may be inserted through the driver assembly similar to that shown and described with respect to FIG. **103** above. The implant distractor may be rotated or otherwise manipulated to advance the implant distractor **850**. Once the implant distractor is positioned, a user may grip the gripping mass **883** with their fingers and allow the knob **885** to settle into the palm of their hand. The user may then squeeze the knob **885** toward the gripping mass **883** depressing the biasing mechanism **891** between the two and retracting the longitudinal shaft **855** along the internal rod **857** and causing the distal end of the

longitudinal shaft **855** to be retracted and expose the collet on the distal end of the internal rod **857**. As such, the clamping force of the collet on the implant distractor **850** may be reduced allowing for removal of the internal actuator **852**, while leaving the implant distractor **850** behind and in place in the implant.

[0344] As shown in more detail in FIG. **108**, the engagement feature **859** at the distal end of the internal rod **857** may take the form of a collet **893** for holding the implant distractor **850**. The collet **893** may be affixed to the distal end of the internal rod **857** and may be adapted to hold the implant distractor **850**. Those of skill in the art will understand and appreciate that the collet **893** may be permanently affixed to the distal end of the internal rod **857** or may be interchangeably coupled thereto. Those of skill will further understand that several collet and chuck arrangements are known in the tool industry for receiving bits or other devices, which are within the scope of the invention. As shown, the collet **893** is extending slightly out of the distal end of the longitudinal shaft **855** and is thus in position to receive an implant distractor or is in position to allow removal of the internal actuator **852** after placement of the implant distractor **850**.

[0345] The collet **893**, positioned on the distal end of the internal rod **857** and shown in FIG. **108**, may be seen more clearly in FIG. **109**. In some embodiments as shown, the collet **893** may include a generally cylindrical body member **895** with four receiving fingers **897** equally spaced around a bore **899**. The body member **895** may be the internal rod **857** or may be a separate piece which is affixed to the end of the internal rod **857**. Each of the fingers **897** may extend distally from the body member **895** and be separated by slots **901**. The fingers **897** may extend laterally across approximately one quarter of a cylinder wall and may have constant thickness as they extend from the body **895**. Near the distal end of the fingers **897**, the outer surface of each finger **897** may be tapered up to define a thicker finger thickness and then tapered back down at the very distal end. As such, when the longitudinal shaft **855** is advanced over the collet **893**, the tapered outer surface causes the fingers **897** to deflect inward creating a clamping force on the implant distractor positioned within the collet. Those of skill in the art will understand and appreciate that the collet may include as few as two fingers **897** and may include any number of fingers. The bore **899** defined by the fingers **897** may extend into the cylindrical body **895** a specified distance. At the transition **903** between the body **895** and fingers **897**, which location is defined by the depth of the slots **901**, the transition **903** defines a neck where a wider body portion **895** necks down to the finger portion **897**.

[0346] Referring now to FIG. **110**, a cross-section of the longitudinal shaft **855** is shown. As shown, the longitudinal shaft **855** may include an internal bore **905** at its distal end for receiving the internal rod **857** and the collet **893**. The internal bore **905** may be the same or similar to the bore extending the length of the longitudinal shaft **855**. The distal end of the bore **905** may include an outwardly beveled edge for riding along the beveled outer surface of the collet **893** when the longitudinal shaft is advanced and creates a clamping force on the collet. **893**

[0347] Referring now to FIGS. **111-113** an implant distractor **850** is shown. The implant distractor **850** may be a generally narrow element having a cylindrical body **907** which tapers to a point at a distal end. At a proximal end **864**, the implant distractor **850** may have a square cross-section and

may include a circumferential groove **909** positioned just proximal to the distal end of the implant distractor **850**. This groove **909** may correspond to a protrusion or spring ball on the inner surface of the engagement feature **859** of the internal actuator **852** forming a detent connection between the engagement feature **859** and the implant distractor **850**. Alternatively or additionally, where a collet **893** is used the groove **909** may engage a feature inside the collet **893** so as to prevent the implant distractor **850** from inadvertently dislodging from the collet **893**. The square proximal end **864** may be isolated from the cylindrical body **907** by an annular stop ring **911**. The annular stop ring **911** may have an outer radius similar to the inner radius of the driver assembly **842**. This stop ring **911** may allow for sliding movement of the implant distractor **850** through the implant shaft **846** of the driver assembly **842**. The stop ring **911** may prevent over advancement of the implant distractor **850** by creating an abutting relationship between the distal face of the stop ring and the proximal edge of the implant.

[0348] As best shown in FIGS. **112** and **113**, the implant distractor **850** may include a generally continuous coil-shaped thread feature **866**. The thread feature **866** may have an abrupt proximal end **913** just distal to the annular stop ring **911** and may continue to the distal end of the implant distractor **850**. The thread feature **866** may gradually terminate at the distal end of the implant distractor **850** by gradually minimizing its cross-sectional profile. This may occur over several turns or in some embodiments, this transition may occur within a 180 degree turn. In other embodiments, this transition occurs between a 90 degree and a 180 degree turn. While the thread feature **866** is generally continuous, as shown in FIG. **112**, the thread feature **866** may be interrupted by at least one cross-cut **915** at one or more locations along the threaded feature **866**. In one embodiment, as shown in FIG. **112**, a single cross-cut **915** may be positioned just proximal to the distal end. This cross-cut **915** may be positioned approximately 180 degrees out of phase from the abrupt proximal end **913** of the thread feature **866**. Both the cross-cut **915** and the abrupt proximal end **913** may provide for interlocking engagement of the implant distractor **850** with the implant **154/854** and thus prevent backing out of the implant distractor **850**.

[0349] Turning now to FIGS. **114-116**, an injector **902** and delivery device **804** are shown. As shown in FIG. **114**, the injector **902** may include a longitudinal delivery shaft **917**, a seating feature **919**, a gripping feature **921**, and a plunger **923** with a handle **925**. The longitudinal delivery shaft **917** may have any cross-section and may have a cross-sectional size adapted to fit within the delivery device **804**. The longitudinal shaft **917** may have an opening **927** on its distal end for directing bone paste toward the lateral mass portion of a facet joint. In another embodiment, the shaft **917** may include two opposing openings **927** or a series of openings **927** on its distal end. The openings **927** may be positioned to penetrate the wall of shaft **917**. The seating feature **919** may include a rectangular or other shaped block positioned around the shaft **917** and sized and shaped to engage the seating recess **813** in the receiving assembly **810** of the delivery device **804**. As shown, the seating feature **919** may include a necked down portion on its distal end which may be received by the shell portion **815** of the receiving assembly **810**. As with the driver assembly **842**, the seating feature **919** of the injector **902** may include protrusions or recesses **929** corresponding to protrusions or recesses **817** on the inner surface of the shell **815**

allowing for a detent relationship for securing the injector **902** to the delivery device **804**. The seating feature **919** may have an orientation perpendicular to the orientation of the openings **927** at the distal end of the shaft **917** such that once in position, the openings **927** may direct bone paste or other material perpendicular to the facet joint surface along the spine and adjacent to the facet joint. The gripping feature **921** may be any shape and may be affixed to the proximal end of the shaft **917**. This feature **921** may include a gripping profile on its distal face for receiving 1, 2, or any number of fingers on one or either side of the shaft **917**. The gripping feature **921** may allow the user to grasp the injector **902** and squeeze the plunger handle **925** toward the gripping feature **921** thus advancing the internal piston and ejecting the bone paste or other material.

[0350] As shown in FIG. 116, the injector **902** may be sleeveably inserted into the delivery device **804** and advanced such that the distal end of the shaft **917** is positioned between the forks **812**. The seating feature **919** may be secured with the detents thus orienting the openings **927** in the shaft **917** perpendicular to the forks **812**. The plunger handle **925** may be squeezed relative to the gripping feature **921** and bone paste or other material may be injected toward the facet joint site. Additional features not mentioned may be included as shown and described with respect to the injector **202**. For example, the plunger **923** may include a seal.

[0351] Turning now to FIGS. 117-120, another embodiment of an implant **854** is shown. The implant **854** may include upper **868** and lower **870** members. The members **868, 870** may be generally planar and may also be generally rectangular. Each of the upper **868** and lower **870** members may include a proximal edge **872**, a distal edge **874**, and a pair of parallel lateral edges **876** extending longitudinally between the distal edges **874** and the proximal edges **872**. In the present embodiment, as shown in FIGS. 117-120, the distal edges **874** of the members **868, 870** may each include interlocking scissor features **931**. As shown, a portion of the member near the distal edge **874** of each member may be radiused and bend in the direction of the opposing member. As shown in FIGS. 118 and 119, an interlocking slot **933** may be provided extending laterally halfway across the member just proximal to the distal edge **874** and within the radiused bend portion of the member. In one embodiment, the width of the slot **933** may be generally similar in width to the distance from the distal edge **874** to the slot **933**. The slot **933** in the upper member **868** and lower member **870** may be positioned on the same side such that when one of the members is inverted, the slots may engage one another as best shown in FIG. 120. The upper and lower members **868, 870** may be welded together along an upper seam **935**, lower seam **937**, and/or a front seam **939**. Once interlocked, the planar members **868, 870** may be biased by the connection at their distal edges **874** to be generally parallel to each other, the inner faces **878** of the planar members **868, 870** facing each other in an opposed fashion and abutting or nearly abutting each other. It is noted that, while the interlocking slot **933** is shown extending anatomically laterally from the anatomical medial side of the upper member **868** and extending anatomically medially from the anatomical lateral side of the lower member **870**, the orientation of this slot may be reversed. This reversed orientation may provide resistance to shearing of the upper **868** and lower **870** members relative to one another upon receiving the implant distractor. That is, as the implant distractor is advanced into the implant **854**, it may be rotating

in a clockwise fashion. When engaging the implant **854**, this rotation may have a tendency to cause the upper member **868** to shift laterally and to cause the lower member to shift medially. The reversed orientation may resist this shifting.

[0352] Additional features of the implant **854** may include those features shown and described with respect to implant **154**. For example, a guide feature **884** may be included as shown. As an additional example, threaded slots **888** may also be included in each planar member **868, 870** for receiving the coil-shaped thread feature **866** on the implant distractor **850**. In the present embodiment, one of the threaded slots **888** on one of the members **868, 870** may be a truncated threaded slot **941** for engaging the cross-cut thread **915** or the abrupt proximal end **913** of the coil-shaped thread feature **866** and preventing unscrewing or backing out of the implant distractor **850** once advanced and positioned. As shown in FIGS. 118 and 119, each member **868, 870** may have one truncated threaded slot **941** for engaging either a cross-cut thread **915** or the abrupt proximal end **913** of the thread feature **866**. As such, the implant distractor **850** may be held in place and prevented from backing out by both the upper and lower member **868, 870**.

[0353] Those of skill in the art will understand and appreciate that the implant embodiments depicted herein may be made of several types of biocompatible materials including stainless steel, titanium, ceramics, nitinol, polymers, and other materials known in the art.

[0354] Referring now to FIGS. 121-128, another embodiment of a tool **1000** is shown. FIG. 121 shows a chisel **1008**, a delivery device **1004**, a decorticator **1006**, a driver assembly **1042**, an internal actuator **1052**, an internal rod **1057** for the internal actuator **1052**, an injector **1102**, and a gripping tool **1001**.

[0355] Referring to FIG. 122, the chisel **1008** may have a generally cylindrical cross-section forming a shaft **1028**. The shaft **1028** may have a radius substantially equal to the inner radius of the tubular shaft portion **1014** of the delivery device **1004** (shown in FIG. 123) allowing for slidable insertion of the chisel **1008** within the delivery device **1004**. Alternatively, the radius of the shaft **1028** may be smaller than the inner radius of the tubular shaft **1014** providing for more play and adjustability of the chisel **1008** and delivery device **1004** relative to one another. In some embodiments the shaft **1028** may have a radius ranging from approximately 1 mm to approximately 8 mm. In other embodiments, the shaft **1028** may have a radius of approximately 4 mm. The chisel **1008** may include a single or doubly chamfered tip **1030** at a distal end or may have a coped distal end or a combination of coping and chamfering. The tip **1030** may include a roughened surface on one or more sides to aid in anchoring or docking the chisel in the facet joint. Additionally, this roughened surface may allow for roughening or decorticating the inner surfaces of the facet joint. The tip **1030** may have a length **1037** adapted to extend substantially across the facet joint. As such, the length **1037** may be any length corresponding to the distance across a given facet joint. In one embodiment, the length **1037** may fall within a range from approximately 5 mm to approximately 35 mm long. In another embodiment, the length may fall within a range from approximately 10 mm to approximately 30 mm. In yet another embodiment, the length may fall within a range from approximately 14 mm to approximately 29 mm.

[0356] The chisel **1008** may include a head or, in contrast to the chisel **108** described with respect to FIG. 1, the chisel

1008 may not include a head as shown in FIG. 122. The chisel **1008** may have an overall length slightly larger than the delivery device **1004** so as to allow the chisel **1008** to be manipulated by its proximal end when sleeved within the delivery device **1004**. The chisel **1008** may have a coped proximal end **1033** as shown. The cope **1033** may occur on one or more sides of the chisel **1008** and may allow for easier grasping of the chisel **1008** with other tools. For example, a slap hammer may be used to grasp the chisel **1008** and hammer back on the chisel **1008** during removal. Additionally, a hemostat may be used to grasp, manipulate, or otherwise distance the surgeon's hand and/or body from the proximal end of the chisel **1008** to facilitate taking of x-rays. Further shown in FIG. 122 is a horizontal bore **1035** for receiving a shaft portion of the gripping tool **1001**. As such, the gripping tool **1001** may be inserted into the horizontal bore **1035** in the proximal end of the chisel **1008** forming a T-shaped grip that may be used to manipulate the chisel **1008** and/or remove the chisel **1008**.

[0357] Additional features of the chisel **1008** may include features of the other chisels shown and described herein. For example, similar to the chisel shown and described with respect to FIG. 1A, the chisel **1008** may also include a longitudinally extending lumen. In this embodiment, the chisel **1008** may allow for insertion of a scope or flushing fluids as discussed above. Also, the chisel **1008** may allow for diagnostic processes. That is, the chisel **1008** may be positioned in a facet joint and a diagnostic balloon catheter may be inserted through the lumen of the chisel **1008** to distract the joint. Feedback from a consciously sedated patient may allow a provider to obtain information relating to symptom relief. As such, one or more joints may be reviewed diagnostically and thus may allow for treatment of one or several problematic joints with confidence that the proper joints are being treated. An exemplary diagnostic balloon catheter and method suitable for this application is described in U.S. patent application Ser. No. 12/110,548, entitled Cervical Distraction Method, filed on Apr. 28, 2008, the contents of which are hereby incorporated by reference herein.

[0358] In comparison to the use described with respect to FIG. 5 above, it is noted that the chisel **1008** may allow the option of inserting the chisel **1008** prior to the delivery device **1004** and sleeving the delivery device **1004** over the chisel **1008**. This is in contrast to the chisel **108**, with the head **132**, where the head **132** may prevent the delivery device **104** from being sleeved over the chisel **108**. As such, the facet joint may be distracted by the chisel **1008** by inserting the chisel **1008** and tapping, hammering, or otherwise advancing the chisel **1008** into the facet joint. Once in place, the delivery device **1004** may be inserted. Upon placement and proper positioning of the delivery device **1004**, the chisel **1008** may then be removed. In another embodiment, a chisel with a removable head may also be provided and may allow for either order of insertion of the delivery device **1004** and chisel **1008**. In the case of inserting the chisel **1008** first, the removable head may initially be removed from the chisel **1008**. Once replaced, the removable head may then be used to more readily manipulate and properly position the chisel **1008**.

[0359] In some embodiments, the forks **1012** at the distal end of the delivery device **1004** may have a bull nose tip as shown in FIG. 123. This is in contrast to the relatively sharp tip shown in FIGS. 2-4. The use of a chisel **1008** without a handle, which may allow for insertion of the chisel **1008** prior to the delivery device **1004**, may, in turn, allow for this bull

nose tip because the facet joint may be distracted prior to insertion of the delivery device **1004**.

[0360] In still further embodiments, the chisel **1008** may be radiolucent. That is, the chisel may be made of plastic or other material not reflected by an x-ray. This may allow for lateral fluoroscopy to more readily show the position of a chisel, delivery device, or other device in a contra lateral facet joint without obstructing the view.

[0361] As shown in FIG. 123, the delivery device **1004** may include a receiving assembly **1010** at a proximal end, anchoring forks **1012** at a distal end, and a generally tubular shaft **1014** defining a longitudinal axis and extending between the receiving assembly **1010** and the anchoring forks **1012**. The tubular shaft **1014** may have an annularly shaped cross-section with an inner radius and an outer radius, where the difference between the two radii defines a thickness of the tubular shaft **1014**. The delivery device may and all of the associated elements may be any size and may be adapted for the particular anatomy being addressed. In some embodiments, the outer radius of the tubular shaft **1014** may range from approximately 2 mm to approximately 8 mm. In some embodiments, the tubular shaft **1014** may have an outer radius of approximately 5 mm.

[0362] Some of the features of the delivery device **1004** will now be described and additional features of the delivery device **1004** may include features of other delivery devices shown and described herein, such as, for example, the anchoring forks **1012**.

[0363] The receiving assembly **1010** of the delivery device **1004**, shown in FIGS. 123 and 123A, may have a generally smooth contoured outer surface that transitions from a generally rectangular cross-section at a proximal end to a narrower and generally circular cross-section at a distal end, the receiving assembly defining a volume with a bore **1011** extending there through. The bore **1011** may be positioned proximal to and in alignment with the tubular shaft **1014** and may have an inner radius matching that of the tubular shaft **1014** allowing for a smooth transition of devices from the receiving assembly **1010** into the tubular shaft **1014**. As best shown in FIG. 123A, the tubular shaft **1014** may engage the receiving assembly **1010** with a dove tail connection **1017** around the periphery of the proximal end of the tubular shaft **1014**. Also shown in FIG. 123A is a tapered entrance **1019** to the bore **1011** at its proximal end to facilitate ease of entry of other devices. The receiving assembly **1010** may include one or more seating cavities **1013** opening in a proximal direction for receiving and seating of other devices such as the driver assembly **1042** or the injector **1102**. These seating cavities **1013** may be defined by an outer shell **1015** that is substantially flush with the outer surface of the receiving assembly **1010**. The seating cavities **1013** may be positioned radially adjacent to the bore **1011**. In the present embodiment, two seating cavities are shown adjacent to the bore **1011** and on opposite sides of the bore **1011**. While not shown, the shell **1015** may include protrusions or recesses on its inner surface, the protrusions or recesses corresponding to protrusions or recesses on other devices. As such, these protrusions or recesses may provide for a detent relationship between the delivery device **1004** and other devices. Alternatively or in addition to the protrusions or recesses, the seating cavities **1013** may have an inner surface that tapers such that the cross-section of the cavity **1013** also tapers from a relatively broad cross-section at its proximal end to a relatively narrow cross-section at its distal end. As such, these seating cavities

1013 may provide for a friction fit between the receiving assembly **1010** and another device, where the other device may have a male portion with a shape corresponding to the shape of the seating cavity **1013**. The cross-sectional shape of the cavities **1013** may include a relatively trapezoidal shape with a concave base as shown, the base bordering along the perimeter of the bore **1011**. Any cross-sectional shape including square, rectangular, triangular, circular, or a more undefined random shape may be used.

[0364] The generally rectangular cross-section of the proximal portion of the receiving assembly **1010** may have a long side and a short side. The long side may be oriented parallel to a line connecting the forks **1012** in turn aligning the seating cavities **1013** with the forks **1012**. As such, devices used with the delivery device **1004** may be properly aligned relative to the forks **1012** by positioning and seating them in the seating cavities **1013**.

[0365] Just distal to the receiving assembly **1010**, a circumferential groove **1021** is shown on the tubular shaft **1014**. The groove **1021** may be adapted to aid in securing the decorticator (not shown), further described below. Alternatively, the groove **1021** may be adapted for gripping by a hemostat or other tool. For example, a hemostat may be used to hold the delivery device **1004** where the delivery device **1004** is being held in position for an x-ray and the practitioner or other user may be attempting to distance their hand from the x-ray field.

[0366] Also shown in FIG. **123** are the forks **1012**. These forks **1012** may be adapted to anchor the delivery device **1004** in the facet joint. As such, similar to the chisel **1008**, the forks **1012** may include a roughened or toothed surface. Additionally, the distal ends of the forks **1012** may be beveled to aid in advancing the tool through tissues and avoid snags. Moreover, the length **1023** of the forks **1012** may be adapted to extend substantially across the facet joint. As such, in one embodiment, the length **1023** of the forks **1012** may range from approximately 5 mm to approximately 35 mm. In another embodiment, the length **1023** may range from approximately 10 mm to approximately 30 mm. In still another embodiment, the length **1023** may range from approximately 14 mm to approximately 29 mm.

[0367] Referring now to FIG. **124**, the decorticator **1006** may have a tubular shaft portion **1034**, an abrasive distal end **1036**, and a handle **1038** at a proximal end. The tubular shaft **1034** may have an inner radius substantially equal to the outer radius of the tubular shaft **1014** of the delivery device **1004** and may allow for sliding movement of the decorticator **1006** along the length of the delivery device **1004** and rotationally around the delivery device **1004**. In some embodiments, the inner radius of the tubular shaft **1034** may be slightly or substantially larger than the outer radius of the tubular shaft **1014** of the delivery device **1004** allowing for more freedom of movement of the decorticator **1006**. In some embodiments, the outer radius of the decorticator may range from approximately 2 mm to approximately 10 mm. In another embodiment, the decorticator may have an outer radius of approximately 6 mm.

[0368] The abrasive distal end **1036** of the decorticator **1006** may include serrated teeth **1037** as shown, or may include a more flat annular surface with a gritty surface. In the embodiment shown in FIG. **124**, the distal end of the tubular shaft portion **1034** is chamfered and the serrated teeth **1037** are located on the distal most end of the chamfered end allowing for a more directed and controllable decorticating process. As such, the decorticator **1006** shown is well suited

for the intra facet process reflected by many of the embodiments described herein. That is, the human anatomy of the cervical spine may be such that the lateral mass of the facet joints are not perpendicular to the surface of the facet joint. Additionally, to properly place the forks **1012** of the delivery device **1004** within the joint, the delivery device **1004** may be positioned substantially parallel to articular surfaces of the facet joint. As such, the delivery device **1004** may not be positioned perpendicular to the lateral masses of the facet joints and may actually be directed with a downward slope as it extends in the distal direction. Where the decorticator **1006** has an non-chamfered annular end, depending on anatomy, the decorticator **1006** may be able to be placed in contact with the superior lateral mass, but may be unable to reach or contact the inferior lateral mass. In the present embodiment, the chamfered end of the tubular shaft portion **1034** will allow the distal tip of the chamfered end to reach and decorticate the inferior lateral mass. This chamfered distal end may define an angle to the longitudinal axis. In some embodiments this angle may range from approximately 10 degrees to approximately 80 degrees. In other embodiments, this angle may range from approximately 30 degrees to approximately 60 degrees. In other embodiments, this angle may be approximately 45 degrees. Additionally, the teeth **1037** may be relatively large as shown in FIG. **124**, or they may be relatively small. Moreover, the teeth **1037** may extend along the full perimeter surface of the chamfered end rather being positioned solely at the tip of the chamfered end.

[0369] Additionally shown in FIG. **124** is a beveled edge **1039** along the periphery of the chamfered end. That is, along the ovular shape created by the chamfered tubular shaft portion **1034**, the edge is beveled. As such, when the delivery device **1004** is inserted into the patient and/or when the decorticator **1006** is advanced along the delivery device **1004**, the beveled edge **1039** may assist in avoiding tissue snags and the decorticator **1006** may be placed in contact with the lateral mass of the facet joints in a much smoother process and may avoid damage to neighboring tissues.

[0370] The handle **1038** of the decorticator **1006** may include a generally cylindrically shaped knob with a gripping surface along its peripheral edge and may sleeveably receive the tubular shaft portion **1034**. The handle **1038** may also include radially extending bores **1041** adapted to receive the gripping tool **1001**. The bores **1041** may extend from the outer surface of the handle radially inward and end at the outer surface of the tubular shaft portion **1034**. As such, one or several gripping tools **1001** may be inserted into any one or several of the bores **1041** in the handle **1038** and may provide for better control and a higher amount of torsional leverage when decorticating the lateral masses of the facet joint. Additionally, the gripping tool **1001** extending laterally from the handle **1038** may allow for malleting in the longitudinal direction of the decorticator **1006**. That is, the gripping tool **1001** may be inserted into the bore **1041** and the decorticator **1006** may be advanced to contact the lateral mass of the facet joint. A mallet may be used to strike the side of the gripping tool **1001** to cause forceful decortication of the lateral mass. The decorticator may then be retracted, rotated to a new radial position, advanced, and struck again for additional decortication. In some embodiments, the handle **1038** may be shaped relatively oblong so as to provide a mass of material that extends laterally away from the longitudinal axis of the decorticator **1006**. In this embodiment, the bore **1041** may not be a radial bore **1041**, but may be offset from the passing through

the center point of the decorticator **1006** a distance equal to or greater than a radius of the tubular shaft portion **1034**. As such, the bore may pass all the way through the handle without encountering the tubular shaft **1034**. Accordingly, the gripping tool may be inserted into the bore **1041** and extended all the way through the handle **1038**, allowing for additional ability to grip and/or mallet the gripping tool **1001** and manipulate the decorticator **1006**.

[0371] In still another embodiment, the bores **1041** may be positioned on the distal face of the handle **1038**. In this embodiment, the bores may receive the gripping tool **1001**, the tool being oriented parallel to the longitudinal axis of the decorticator **1006** and allowing for malleting the proximal end of the gripping tool **1001** to decorticate the lateral mass. In still another embodiment a series of gripping tools **1001** may be inserted into a series of bores **1041** positioned on the distal face of the handle **1038**, each available to be used for malleting or manipulating the decorticator **1006**. In still another embodiment, a single malleting tool (not shown) may be included, which has a series of longitudinally extending rods each receivable by a series of bores **1041** on the distal face of the handle **1038**. At a position proximal to the receiving assembly **1010** of the delivery device **1004**, the series of rods may converge to a centrally positioned malleting surface. As such, this malleting surface may be used to mallet the decorticator **1006** allowing for the force of the mallet to be positioned along the longitudinal axis of the decorticator.

[0372] Additionally shown in FIG. 124 is a radially extending threaded bore **1047** adapted to receive a corresponding threaded set screw. This threaded bore **1047** may extend from the outer surface of the handle **1038** radially inward through the wall of the tubular shaft portion **1034** allowing access to the tubular shaft **1014** of the delivery device **1004**. The set screw may be advanced through the handle **1038** to engage the delivery device **1004** and prevent the decorticator **1006** from advancing or twisting inadvertently. As mentioned and shown in FIG. 123, the delivery device **1004** may include a groove **1021** on the outside surface of the tubular shaft **1014** for receiving the tip of the set screw or otherwise creating a catch point for the decorticator. As such, when the decorticator **1006** is in its fully retracted and most proximal position, the threaded bore **1047** and set screw may align with the groove **1021** in the tubular shaft **1014** and thus hold the decorticator **1006** in its most proximal position. The set screw may be a thumbscrew-type with a head that includes longitudinally extending ribs around its periphery for purposes of gripping the screw. Alternatively the head may be a wing nut type head for ease of setting and unsetting of the screw. In still another embodiment, the decorticator may have a relatively snug friction fit at the proximal end that engages the groove **1021** when retracted. In still another embodiment, the tubular shaft portion **1034** of the decorticator may include a protruding rib on its inside surface adapted to engage the groove **1021** on the tubular shaft **1014**. A key slot **1049** extending transversely across the threaded bore **1047** may also be provided. Additional features of the decorticator **1006** may include features of other decorticators shown and described herein. For example, the decorticator **1006** may alternatively be separate from the delivery device **1004** and may be slidably inserted within the delivery device **1004** similar to that shown and described with respect to FIG. 4 or FIGS. 6A-6C.

[0373] Referring now to FIG. 125, the driver assembly **1042** is shown. As shown, the driver assembly **1042** includes a handle **1044**, an implant shaft **1046**, and implant holding arms **1048**.

[0374] The implant shaft **1046** may have an outer radius substantially equal to the inner radius of the tubular shaft portion **1014** of the delivery device **1004** (shown in FIG. 123) allowing for slidable insertion of the driver assembly **1042** within the delivery device **1004**. Alternatively, the outer radius of the implant shaft **1046** may be smaller than the inner radius of the tubular shaft **1014** providing for more play and adjustability of the driver assembly **1042** and delivery device **1004** relative to one another. In some embodiments the implant shaft **1046** may have a radius ranging from approximately 1 mm to approximately 8 mm. In other embodiments, the implant shaft **1046** may have a radius of approximately 4 mm.

[0375] The handle **1044** of the driver assembly **1042** may have an outer surface defining a volume with a bore **1043** extending there through. The bore **1043** may have an inner diameter substantially equal to the inner diameter of the implant shaft **1046** allowing for a smooth transition of devices passing through the driver assembly **1042**. The handle **1044** may have a generally rectangular shape at its distal end corresponding to the proximal end of the receiving assembly **1010**. The handle **1044** may include gripping slots **1051** near its distal end to aid users with gloves in securely holding the driver assembly **1042**. Additionally, these slots **1051** may aid a user in hold the assembly **1042** with a hemostat or other gripping device. Additionally, the handle **1044** may have a necked down portion **1045** at its distal end in the form of one or more projections. In one embodiment, the necked down portion **1045** may have protrusions or recesses (not shown) on its outer surface corresponding to respective protrusions or recesses on the inner surface of the shell **1015** of the receiving assembly **1010** on the delivery device **1004**. As such, the driver assembly **1042** may be sleeveably positioned within the delivery device **1004** to deliver an implant to the facet joint. When fully advanced, similar to that shown in FIG. 101, the handle **1044** may be seated securely in the seating cavity **1013** of the receiving assembly **1010**. Where protrusions are included on the necked down portion **1045** and recesses are included on the inner surface of the shell **1015**, the handle may be anchored with a detent relationship. The projections of the necked down portion **1045** of the handle **1044** may correspond to the seating cavities **1013** of the receiving assembly. Additionally, these projections may taper as they extend distally to provide a friction type fit into the seating cavities **1013** of the receiving assembly **1010**.

[0376] The seating relationship provided by necked down portion **1045** of the driver assembly **1042** and the receiving assembly **1010** of the delivery device **1004** may allow the user to control the placement of the implant in both a longitudinal and a rotational direction. That is, once the anchoring forks **1012** of the delivery device **1004** are properly placed in the facet joint, proper placement of the driver assembly **1042** may then be ensured by aligning and seating the handle **1044** of the driver assembly **1042** in the receiving assembly **1010** of the delivery device **1004**. Thus, the seating relationship may prevent the driver assembly **1042** from being inserted too far and may also allow the driver assembly **1042** to be aligned with the delivery device **1004** rotationally to ensure proper rotational orientation of the implant. Additional features of the

driver assembly 1042 may include those features shown and described with respect to driver assembly 142.

[0377] The implant holding arms 1048 may include features similar to other arms shown and described herein. For example, the inside surface of the arms 1048 may include a longitudinal ridge 1062 extending the length of the arms 1048. The arms 1048 may also include a bull nose engagement feature 1058 extending transverse to the longitudinal axis of the implant shaft along the inside face of the arm 1048. Where the arms 1048 are engaged with and holding the implant, the longitudinal ridges 1062 of each arm 1048 may be positioned between upper and lower planar members of the implant and the bull nose engagement features 1058 may be positioned in the U-shaped receiving feature slots on the lateral edges of the implant.

[0378] In contrast to the driver assembly 142 and consistent with the driver assembly 842, each described above, in the present embodiment, the internal actuator 1052 may be a separate device from the driver assembly 1042. As shown in FIG. 126, the internal actuator 1052 may include a longitudinal shaft 1055 a handle 1053, and an internal rod 1057 (not shown in FIGS. 126-126B). The longitudinal shaft 1055 may be cylindrically shaped with an annular cross-section. The shaft 1055 may have an outer diameter substantially the same as or smaller than the inner diameter of the implant shaft 1046 of the driver assembly 1042. The shaft 1055 may extend from the handle 1053 proximally to a distal end. The internal actuator 1052 may be used in conjunction with the internal rod 1057 positioned within the shaft 1055.

[0379] The internal rod 1057, shown separately in FIG. 127, may be positioned within the shaft 1055 and may extend from the handle 1053 to the distal end of the longitudinal shaft 1055. The internal rod 1057 may include an engagement feature 1059 at its distal end for engaging and holding the implant distractor. This engagement feature 1059 may be any shape and provide for any engagement known in the art from a hex, alien, phillips, star, square, sleeve, or other connection capable of transmitting longitudinal and/or rotational forces from the internal rod 1057 to the implant distractor. In one embodiment, the engagement feature 1059 includes a collet type device that is described in more detail with respect to FIG. 127A below.

[0380] The internal rod 1057 may sleeveably receive the implant distractor. The internal rod 1057 may be sleeveably positioned within the longitudinal shaft 1055, such that when the longitudinal shaft 1055 is in an advanced position over the end of the internal rod 1057, the longitudinal shaft 1055 causes a clamping force of the collet to restrain the implant distractor against being dislodged from the collet. Each of the shaft 1055 and the internal rod 1057 may engage the handle 1053 at their respective proximal ends and be affixed there to. The shaft 1055 may be securely affixed to the handle 1053 such that rotational and longitudinal motion of the handle 1053 imparts the same motion on the shaft 1055. In contrast, the internal rod 1057 may be slidably affixed to the handle 1053 such that rotational motion of the handle 1053 imparts the same motion on the internal rod 1057, but longitudinal motion of the handle 1053 is isolated from the internal rod 1057 via a biasing mechanism. As such, the handle 1053 may be used to retract the longitudinal shaft 1055 along the length of the internal rod 1057 thereby exposing the collet and reducing the clamping force on the implant distractor, but when the handle 1053 is rotated, both the longitudinal shaft 1055 and internal rod 1057 rotate with the handle 1053. When the

longitudinal shaft 1055 is in a retracted position, an implant distractor may be inserted into and/or removed from the collet due to the reduced clamping force.

[0381] As shown in FIGS. 126A and 126B, the handle 1053 may be a generally cylindrical shape with a cone shaped distal end and a relatively flat proximal end. As shown, the proximal end of the handle 1053 may include a circumferential ridge 1051 projecting proximally and extending along the periphery of the cylindrical shape. The inner face of the ridge may be braced by a plurality of radially spaced ribs 1061. The center of the proximal end may include a button 1063 covered by a flexible membrane 1065, the proximal end of the button 1063 being recessed slightly from the circumferential ridge 1051, which protects the button 1063 against inadvertent triggering when the handle 1053 is being used to twist or turn the implant distractor. As such, the handle 1053 shown may reduce the chance that the implant distractor will become dislodged or released from the engagement feature 1059 of the internal actuator 1052 prior to being fully advanced and fully distracting the implant.

[0382] As shown in the cross-section of the handle 1053 in FIG. 126B, the button may be held in position by an internal spring 1067 or other biasing mechanism or device and may also include longitudinal keyways allowing for relative longitudinal motion of the button relative to the handle 1053, but preventing relative rotational motion. In use, the implant distractor may be placed in the engagement feature 1059 at the distal end of the internal rod 1057 and the internal rod 1057 may be in position inside the longitudinal shaft 1055. As mentioned above, in the embodiment, shown, when the internal rod 1057 has a collet type engagement feature 1059, the retraction of the internal rod 1057 within the longitudinal shaft 1055 may cause a circumferential clamping force from the longitudinal shaft 1055 onto the engagement feature 1059 of the internal rod 1057, thereby securing the implant distractor in the engagement feature 1059 of the internal rod 1057. Once assembled, the internal actuator 1052 may be inserted and advanced through the driver assembly 1042 positioning the implant distractor just proximal to the implant being held by the implant holder arms of the driver assembly. The handle 1053 may then be rotated to cause the implant distractor to advance into the implant thereby distracting the implant.

[0383] Once the implant distractor is fully advanced, the handle 1053 may be grasped and the button may be pressed, while pulling on the cone shaped portion of the handle 1053, which may counteract the biasing force of the spring 1067 or other biasing mechanism and cause relative longitudinal motion between the internal rod 1057 and the longitudinal shaft 1055. Accordingly, the distal end of the internal rod 1057 may extend beyond the distal end of the longitudinal shaft 1055 and the clamping force on the engagement feature 1059 may be removed allowing the internal actuator 1052 to be removed leaving the implant distractor behind.

[0384] As shown in more detail in FIGS. 127 and 127A, the engagement feature 1059 at the distal end of the internal rod 1057 may take the form of a collet 1093 for holding the implant distractor. The collet 1093 may be affixed to the distal end of the internal rod 1057 and may be adapted to hold the implant distractor. The collet 1093 may be permanently affixed to the distal end of the internal rod 1057 or may be interchangeably coupled thereto. Several collet and chuck arrangements are known in the tool industry for receiving bits or other devices and are within the scope of the invention.

[0385] The collet **1093** may include any or all of the features of other collets shown and described herein. For example, the collet **1093** may include a generally cylindrical body member **1095** with four receiving fingers **1097** equally spaced around a bore **1099**. The collet **1093** may include as few as two fingers **1097** and may include any number of fingers **1097**.

[0386] In still another embodiment, a second internal actuator may be provided. This second internal actuator may include a handle securely affixed to a shaft and an engagement feature securely affixed to a distal end of the shaft. The engagement feature may correspond to the shape of the proximal end of the implant distractor. In one embodiment, this shape is a female square shape corresponding to a square shaped proximal end of the implant distractor. This engagement feature may include any shape known in the art as mentioned with respect to the engagement feature **1059** discussed above. This second internal actuator may be used to advance the implant distractor. For example, the second internal actuator may be used if the internal actuator **1052** were to lose its grip on the implant distractor. That is, if the collet loses its grip for any reason including deformation of the fingers of the collet or due to malfunction of the internal actuator **1052** for any reason, the second internal actuator may be used. The second internal actuator may be passed down the tubular shaft **1046** of the driver assembly **1042** to engage the proximal end of the implant distractor. The engagement feature on the distal end of the second internal actuator may be brought into engagement with the proximal end of the implant distractor and the second implant distractor may be used to rotate or otherwise advance the implant distractor thereby distracting the implant.

[0387] Turning now to FIG. **128**, an injector **1102** is shown. The injector **1102** may include a longitudinal delivery shaft **1117**, a seating feature **1119**, and a plunger **1123** with a handle **1125**. The longitudinal delivery shaft **1117** may have any cross-section and may have a cross-sectional size adapted to fit within the delivery device **1004**. The longitudinal shaft **1117** may have an opening **1127** on its distal end for directing bone paste out the distal end of the shaft **1117** allowing the paste to flow into and/or over the facet joint and/or outward toward the lateral mass of a facet joint. The seating feature **1119** may include a rectangular or other shaped block positioned around the shaft **1117**, which may be sized and shaped to abut the receiving assembly **1010** of the delivery device **1004**. As with the driver assembly **1042**, the distal end of the seating feature **1119** may have a shape corresponding to the shape of the proximal end of the receiving assembly **1010**. As shown, this is a generally rectangular shape, but may be any shape. Additionally, the seating feature **1119** may include gripping slots **1027** near its distal end. Additionally, the seating feature **1119** may include a necked down portion **1025** on its distal end which may be received by the seating cavities **1013** of the receiving assembly **1010**. As with the driver assembly **1042**, the seating feature **1119** of the injector **1102** may include protrusions or recesses (not shown) corresponding to protrusions or recesses on the inner surface of the shell **1015** allowing for a detent relationship for securing the injector **1102** to the delivery device **1004**.

[0388] The injector **1102** may be sleeveably inserted into the delivery device **1004** and advanced such that the distal end of the shaft **1117** is positioned between the forks **1012**. The plunger handle **1125** may be pressed distally and bone paste or other material may be injected toward the facet joint site.

Additional features not mentioned may be included as shown and described with respect to the injector **202** and/or **902**. For example, the plunger **1123** may include a seal.

[0389] A gripping tool **1001** has been referenced for use with several of the above devices, including, but not limited to the chisel **1008** and the decorticator **1006**. As shown in FIG. **121**, the gripping tool **1001** may include a shaft **1003** and a handle **1005**. The shaft **1003** may be made of a relatively rigid material and may have a diameter adapted to fit into the bores provided in the chisel **1008** and the decorticator **1006**. The handle **1005** of the gripping tool **1001** may be any shape. In one embodiment, the handle **1005** is a T-type handle **1005**. In another embodiment, as shown, the handle **1005** is a spherically shaped handle **1005**. The handle **1005** may be adapted in size and shape to nest in the palm of a human hand and such that it can be used to push, pull, or rotate the devices it is connected to or be struck with a mallet.

[0390] Referring now to FIGS. **129-135B**, a dilator set **1200** is shown. FIGS. **129-131** show an assembled set of dilators including a dilator rod **1202** and a plurality of dilator sleeves **1204**, including a small **1204A**, medium **1204B**, and large **1204C** dilator. Any number of dilator sleeves **1204** may be included. Each of the dilator sleeves **1204** may have an inner diameter corresponding to the outer diameter of the next smallest sleeve, the smallest sleeve **1204A** having an inner diameter corresponding to the outer diameter of the dilator rod **1202**. Each of the dilator sleeves **1204** and dilator rod **1202** may have varying lengths, the largest of the sleeves **1204C** having the shortest length, the dilator rod **1202** having the longest length, and the other sleeves **1204A**, **1204B** having lengths there between, such that each rod **1202** or sleeve **1204** is longer than the next largest sleeve. Each of the dilator rods **1202** and sleeves **1204** may include a tapered tip.

[0391] As shown in FIGS. **132** and **132A**, the dilator rod **1202** is shown. The dilator rod **1202** may be a generally solid shaft or may include an interior lumen for receiving a guide wire. The rod **1202** may have any outer diameter. In one embodiment, the rod **1202** has an outer diameter of between approximately 1 mm and 5 mm. In another embodiment, the rod **1202** has an outer diameter of approximately 3 mm. The rod **1202** may have any length. In one embodiment, the rod **1202** has a length of between approximately 200 mm and 400 mm. In another embodiment, the rod **1202** has a length of approximately 290 mm. The tip of the rod **1202** may be tapered and may further include a radiused distal tip. As such, the tip may be adapted to penetrate and dilate tissue.

[0392] FIGS. **133**, **133A**, and **133B** show the small dilator sleeve **1204A**. The small sleeve **1204A** may have an inner diameter adapted to slide over the dilator rod **1202**. The inner diameter of the small sleeve **1204A** may be only slightly larger than the rod diameter or may be much larger. In one embodiment, the inner diameter of the small sleeve **1204A** is 0.6 mm larger than the dilator rod diameter. The small sleeve **1204A** may have any outer diameter and any length. In one embodiment, the small sleeve **1204A** has an outer diameter of between approximately 3 mm and 9 mm. In another embodiment, the small sleeve **1204A** has an outer diameter of approximately 6 mm. In one embodiment, the small sleeve **1204A** has a length of between approximately 200 mm and 300 mm. In another embodiment, the small sleeve **1204A** has a length of approximately 260 mm. The small sleeve **1204A** may include a tapered tip with a radiused distal edge and, as such, the small sleeve may be adapted to slide over the dilator rod and further dilate tissue.

[0393] FIGS. 134 and 134A and FIGS. 135, 135A, and 135B, show a medium dilator sleeve 1204B and a large dilator sleeve 1204C respectively. The medium sleeve 1204B may have an inner diameter adapted to slide over the small sleeve 1204A and the large sleeve 1204C may have an inner diameter adapted to slide over the medium sleeve 1204B. Each of the medium sleeve 1204B and large sleeve 1204C may have an inner diameter only slightly larger than the outer diameters of the small 1204A and medium 1204B sleeve respectively or they may have an inner diameter that is much larger. In one embodiment, the medium sleeve 1204B and the large sleeve 1204C may have an inner diameter that is approximately 0.6 mm larger than the outer diameter of the small sleeve 1204A and the medium sleeve 1204B respectively. The medium sleeve 1204B may have any outer diameter and any length. In one embodiment, the medium sleeve 1204B has an outer diameter of between approximately 4 mm and 12 mm. In another embodiment, the medium sleeve 1204B has an outer diameter of approximately 8 mm. In one embodiment, the medium sleeve 1204B has a length of between approximately 180 mm and 280 mm. In another embodiment, the medium sleeve 1204B has a length of approximately 230 mm. The large sleeve 1204C may also have any outer diameter and any outer length. In one embodiment, the large sleeve 1204C has an outer diameter of between approximately 6 mm and 18 mm. In another embodiment, the large sleeve 1204C has an outer diameter of approximately 11 mm. In one embodiment, the large sleeve 1204C may have a length of between approximately 150 mm and 250 mm. In another embodiment, the large sleeve 1204C may have a length of 200 mm. Each of the medium 1204B and large 1204C sleeves may include a tapered tip with a radiused distal edge. As such, each of the medium 1204B and large 1204C sleeves may be adapted to dilate tissue slightly more than the corresponding smaller sleeve.

[0394] In use, the dilator set of FIGS. 129-135B may be used to dilate tissues to access a facet joint. That is, once an incision is made, the dilator rod 1202 may be advanced alone or over a guidewire through the tissues of the back up to and/or into the facet joint. Once the rod 1202 is in position, the small sleeve 1204A may be advanced over the rod 1202 from the proximal end of the rod 1202 and may be advanced along the full length of the rod 1202. The longer length of the rod 1202 may allow the rod 1202 to extend out of the proximal end of the small sleeve 1204A such that control of both elements of the dilator set are maintained. The small sleeve 1204A may be advanced fully such that the tip of the small sleeve 1204A is flush with the tip of the rod 1202, thus dilating the tissues in an amount equal to the outer diameter of the small sleeve 1204A. This process may continue with larger and larger sleeves 1204 to appropriately dilate the tissues and allow access to the facet joint. Depending on the dilation necessary, the order and type of dilation may vary. That is, in some instances, the rod may not be necessary. In other instances, some of the sleeves may be omitted or skipped.

[0395] Referring now to FIGS. 136-170, another embodiment of a tool 2000 is shown. FIG. 136 shows a chisel 2008, a place holding chisel 2009, a delivery device 2004, a decorator 2006, a driver assembly 2042, an injector 2102, and a malleting tool 2001.

[0396] Referring more particularly to FIGS. 138-143, a chisel 2008 may be the same or similar to other chisel embodiments described herein. For example it may have a

tubular shaft portion 2028 and tip portion 2030 the same or similar to the chisel 1008 described above. Additionally, the chisel 2008 may include a handle 2032 the same or similar to the handle 1044 on the driver assembly 1042. However, in contrast to the driver assembly handle 1044, the chisel handle 2032 may include a recessed slot cavity on its distal face for receiving a malleting anvil 2041 of the receiving assembly 2010. The handle 2032 can also include a malleting head 2031 for advancing the chisel 2008 via malleting.

[0397] With reference to FIGS. 140-141, one embodiment of the malleting head 2031 is shown. The malleting head 2031 can include a cylindrical shaft portion 2051 and a flattened circular head portion 2053. The cylindrical shaft portion 2051 can be sized for sleeveable insertion into the proximal face of the handle 2032. Additionally, the cylindrical shaft portion 2051 can include a key slot 2055 extending longitudinally along its length. The key slot 2055 can be adapted to receive a longitudinal rib on an inner surface of a bore extending through the handle 2032. Accordingly, the malleting head 2031 can be prevented from twisting relative to the handle 2032 once assembled. Additionally, as shown in FIG. 141 the malleting head 2031 can include a flattened surface on the inner surface of the cylindrical shaft portion 2051. As shown in FIG. 142 the proximal end of the shaft portion 2028 of the chisel 2008 can include a corresponding flattened portion. Accordingly, once assembled, the shaft portion 2028 of the chisel 2008 can be prevented from twisting relative to the malleting head 2031. The malleting head 2031 can also include a counter bored hold extending into the circular head portion 2053 and the proximal end of the shaft portion 2028 of the chisel 2008 can include a corresponding pilot hole. Accordingly, once assembled, a screw can be inserted in the proximal end of malleting head 2031 and can extend into the proximal end of the shaft portion 2028 of the chisel 2008 thereby securing the two portions to one another.

[0398] As shown in FIGS. 139A-139C, the proximal end of the shaft portion 2028 of the chisel 2008 can extend through the distal face of the chisel handle 2032. The distal end of the malleting head 2031 can extend through the proximal face of the chisel handle 2032 until the bottom face of the circular head abuts the proximal surface of the handle 2032. The proximal end of the shaft portion 2028 can be sleeveably positioned within the cylindrical shaft portion 2051 of the malleting head 2031 and a screw can secure the malleting head 2031 to the shaft portion 2028 of the chisel 2008. In alternative embodiments, the shaft portion 2028 can be integral with the malleting head such that the two portions of the chisel are monolithic. It is noted, in the embodiment described, that once assembled, the malleting head 2031 can extend beyond the base of the slot cavity of the handle 2032. The malleting head 2031, being positioned on the proximal face of the handle 2032 and being directly attached to the shaft portion, can provide for forces from malleting the head 2031 of the chisel 2008 to transfer directly down the shaft portion 2028 of the chisel. Moreover, the distal end of the malleting head 2031, extending slightly beyond the base of the slot cavity, can allow the malleting head 2031 to directly abut the malleting anvil 2041 of the receiving assembly 2010 when the chisel 2008 is inserted into the deliver device 2004 as shown in FIG. 144. As such, when the malleting head 2031 of the chisel 2008 is struck, any advancing force of the chisel 2008 relative to the delivery device 2004 can be resisted by the interaction between the malleting head 2031 and the mal-

letting anvil **2041** thereby preventing relative advancing motion between the chisel **2008** and the delivery device **2004**.

[0399] Referring to FIGS. **145** and **149**, the distal end of the chisel **2008** is shown extending slightly beyond the distal tip of the delivery device **2004**. In some embodiments, the distal end of the chisel **2008** can be flush with the distal tip of the delivery device **2004** or it can extend up to approximately 6 mm beyond the end of the delivery device **2004**. In the embodiment shown, the distal end of the chisel **2008** extends approximately 2 mm beyond the end of the delivery device **2004**.

[0400] As also shown in FIG. **149**, the surfaces of the tip **2030** of the chisel can include a series of ridges **2033**. The ridges **2033** can be relatively sharp and can aid the user in roughening or decorticating the facet surfaces as the chisel **2008** is inserted and removed from a facet joint. The ridges **2033** can include a pattern adapted to maintain the chisel's position in a facet joint. In some embodiments, the ridges **2033** can include a sloping distal face and a relatively vertical (e.g., perpendicular to axis of chisel **2008**) proximal face. As the chisel **2008** is advanced, the surfaces in contact with the chisel **2008** may ride up along the sloping distal face until the chisel **2008** is positioned. The relatively sharp apex of the ridges **2033** formed by the sloping distal face and relatively vertical proximal face can function to hold the chisel in place. Moreover, the ridges **2033** can be arranged in a surface pattern suitable for holding the chisel **2008** in place. In one embodiment, the ridges **2033** can include a chevron pattern as shown. Patterns such as straight rows, diagonal rows, wavy rows, or other alternative patterns can be included.

[0401] Referring particularly to FIG. **143**, the distal end of the chisel can include a positioning opening **2059**. The positioning opening **2059** can extend transversely through the chisel **2008** and can be positioned near the proximal portion of the tip **2030** of the chisel **2008**. This opening **2059** can function to allow for longitudinal positioning of the chisel **2008** through lateral fluoroscopy. That is, the opening **2059** can be visible during lateral fluoroscopy due to the absence of material and the chisel **2008** can be advanced into a facet joint until the opening **2059** is at, near, or slightly beyond the posterior edge of the facet joint. It is noted that the position of the opening **2059** can be such that it aligns with a corresponding opening **2015** in the forks **2012** of the delivery device **2004**.

[0402] Referring to FIG. **138**, the handle **2032** can include connection features **2043** on the necked down portion of the handle **2032**. The connection features **2043** can create a detent relationship between the handle **2032** and the receiving assembly **2010** of the delivery device **2004** such that the two elements can resist separation without some force being applied. The detent relationship can be created by protrusions as shown, which engage a lip around the proximal end of the receiving assembly **2010** or a recess on the inner surface of the receiving assembly **2010**. Alternatively, the detent relationship can be created by recesses for receiving protrusions positioned on the inner surface of the receiving assembly **2010**.

[0403] Referring to FIGS. **139A-C**, **159**, and **155A-B**, the connection feature **2043** can also take the form of a latch type feature. For example, the feature **2043** can be wedge shaped and adapted to engage a corresponding ledge on the inside of the receiving assembly **2010**, as best shown in FIG. **155B**. The connection feature **2043** can be positioned on a deflectable lateral side of the handle **2032** and the deflectable lateral

side can include a push button for disengaging the connection feature **2043**. When the chisel **2008** is advanced into the delivery device **2004**, the deflectable lateral side of the handle **2032** can deflect to allow the connection feature **2043** to clear the opposing and corresponding ledge on the inside of the receiving assembly **2010** allowing the handle **2032** to snap into place in the receiving assembly **2010**. To remove the chisel **2008**, the push button can be depressed to clear the connection feature **2043** from the corresponding ledge and the chisel **2008** can then be removed. It is noted that a similar connection can be used on any of the handles or seating features described herein; particularly handles or seating features adapted to engage the receiving assembly **2010**.

[0404] In this embodiment, the chisel **2008** may be engaged with the delivery device **2004** via a connection between the handle **2032** and the receiving assembly **2010**. In this embodiment, both the chisel **2008** and the delivery device **2004** may be introduced into the facet joint at the same time allowing for a one-step process of initially entering the facet joint rather than initially entering the joint with the chisel **1008** and then passing the delivery device **1004** over the chisel **1008** as with the tool **1000**. Once the chisel **2008** and the delivery device **2004** are properly positioned, the chisel **2008** may be removed.

[0405] As shown in FIG. **136**, the tool **2000** can also include a place holding chisel **2009**. The place holding chisel **2009** can have a square cross-section adapted to be inserted into the delivery device **2004**. The diagonal dimension of the cross-section can be at least slightly smaller than the inner diameter of the delivery device **2004**. Alternatively, other cross-sections can be provided and can be adapted for insertion in the delivery device **2004**.

[0406] The place holding chisel **2009** can be a radiolucent chisel and as such can be made from a radiolucent material such as plastic, PEEK, or a polyetherimide material such as, for example, Ultem®. Other radiolucent materials can be used. The place holding chisel **2009** may include a positioning marker **2011** adapted to assist the user in properly positioning the place holding chisel **2009**. The positioning marker **2011** can include a guide line, a mark, or another surface indication on the surface of the chisel **2009** for alignment with a portion of the delivery device **2004**. In one embodiment, as shown, the positioning marker **2011** can be in the form of a double triangle separated by an alignment line. The double triangles can be positioned to form an alignment line on the place holding chisel **2009** such that when the alignment line is aligned with the proximal end of the delivery device **2004** (e.g., the proximal face of the receiving assembly **2010**), the distal end of the chisel **2009** is properly positioned to extend slightly out the end of the delivery device **2004**. Additionally, where the alignment line is not aligned with the distal end of the delivery device **2004**, the triangles can function as arrows indicating which direction to move the chisel **2009**. That is, the triangle closest to the distal face of the receiving assembly, may indicate which direction to move the chisel **2009**. As also shown, the proximal end of the chisel **2009** can include a hole extending transversely there through. The hole can be adapted to receive a transverse rod or shaft extending into the hole and/or through the hole. The rod or shaft and the chisel **2009** can form a T-grip or L-shaped grip for use in pulling on the chisel **2009** for removal.

[0407] Referring again to FIG. **149**, the distal tip of the place holding chisel **2009** can include a tip the same or similar to the chisel **2008**. For example, the chisel **2009** can include a

coped and/or chamferred tip **2035** similar to chamferred tip **2030**. Additionally, the chisel **2009** can include ridges **2037** arranged in a pattern similar to that shown and described with respect to chisel **2008**. Additionally, the chisel **2009** can include a radiopaque portion **2039** adapted to allow recognition of the chisel's location while avoiding occlusion of the lateral view. The radiopaque portion **2039** can include a straight, round, square, or other shaped piece of material positioned near the distal end of the chisel **2009** for locating the distal end. As shown, the radiopaque portion **2039** can be embedded in the surface of the distal tip of the chisel **2009** to cause the location of the distal tip to be ascertainable from lateral fluoroscopy.

[0408] In use, the place holding chisel **2009** can be used as a place holder without occluding the lateral view of a chisel and delivery assembly positioned in a contralateral facet joint. That is, upon placement of the chisel **2008** and the delivery device **2004** in a first facet joint, the chisel **2008** may be removed and replaced with the place holding chisel **2009** where the forks **2012** of the delivery device **2004** maintain the position of the tool **2000**. The delivery device **2004** may also be removed and reassembled with the chisel **2008** once the place holding chisel **2009** is properly positioned. The delivery device **2004** and chisel **2008** may then be inserted into the contralateral facet joint or second joint. By replacing the chisel **2008** in the first joint with the place holding chisel **2009**, the location of the chisel **2008** and delivery device **2004** in the second joint may be more readily ascertainable using lateral fluoroscopy. That is, if a radiopaque chisel or delivery device was left in place in the first joint, the fluoroscopic view of the contralateral facet joint would be relatively occluded. Upon placing the delivery device **2004** properly in the second facet joint, the procedure above may continue. Upon completing treatment of the second facet joint, the delivery device **2004** may be sleeved over the place holding chisel **2009** still positioned in and holding the place in the first facet joint and the first facet joint may then be treated with the above procedure. It is noted that initial placement of the deliver device **2004** can be conducted with the place holding chisel **2009** rather than the chisel **2008** to avoid having to replace the chisel **2008**. Additional features of the chisel **2008** may include features of the other chisels shown and described herein. For example, an internal lumen may be provided.

[0409] Referring now to FIGS. **137** and **144**, a delivery device **2004** is shown. The delivery device **2004** may include features the same as or similar to previously disclosed delivery devices. For example, the delivery device **2004** can include a receiving assembly **2010** at a proximal end and a pair of anchoring forks **2012** at a distal end with a generally tubular shaft **2014** extending there between. The delivery device **2004** can also include a malleting anvil **2041**. The malleting anvil **2041** can include a raised surface positioned on the proximal face of the receiving assembly **2010** adapted for contact with the distal end of the malleting head **2031** on the chisel **2008**, as described above, or on the driver assembly **2042**. As such, malleting on the proximal end of the chisel **2008** or the driver assembly **2042** can cause longitudinal forces along the length of the respective tool piece. These longitudinal forces can be transferred, at least partially, through the contact between the malleting head **2031** and the malleting anvil **2041**. Accordingly, relative motion between the respective tool piece and the delivery device **2004** can be prevented. As such, for example, the necked down portion **2045** of the driver assembly, can be prevented from wedging

inside the receiving assembly and getting lodged or stuck therein. Moreover, at the distal end of the delivery device **2004**, the relative position of the distal end of the chisel **2008** or the driver assembly **2042** relative to the distal end of the delivery device **2004** can be maintained.

[0410] Referring now to FIGS. **145** and **149**, a distal tip of the delivery device **2004** is shown. As shown, the distal tip of the delivery device **2004** can include anchoring forks **2012**. As shown, and previously described, the forks **2012** can include teeth or ridges along their surface for decorticating the interior surface of the facet and for temporarily anchoring the delivery device **2004** therein. In this embodiment, the teeth or ridges can extend along and across the coped portion of the tubular shaft **2014** of the delivery device **2004**. This coped portion can be tapered to avoid hanging up on the lateral mass of the facet joint. That is, as the forks **2012** are inserted into the joint the outward sloping portion of the distal end of the delivery device **2004** can approach the lateral mass of the joint. Where the coped portion slopes too abruptly, the contact between the sloped surface and the lateral mass can limit how far the forks **2012** can be advanced into the joint. In some embodiments, the coped portion of the distal end of the delivery device **2004** can include a taper angle **2013** ranging from approximately 5° to approximately 45°. Preferably, the taper angle **2013** is approximately 7° to approximately 15°. The taper angle can be adjusted to accommodate several different types and/or areas of the anatomy and can thus also include angles outside the mentioned ranges. For example, use of the device in the lumbar region of the spine may involve the use of different angles.

[0411] With continued reference to FIGS. **145** and **149**, along the lateral side of the tubular shaft portion **2014** near the proximal end of the forks **2012**, the tubular shaft portion **2014** can include an alignment hole **2015**. This alignment hole **2015** can align with the positioning opening **2059** in the chisel **2008** and can be used with lateral fluoroscopy for properly advancing the delivery device **2004** and/or the chisel **2008**. As discussed with respect to the chisel **2008**, the delivery device **2004** can be advanced until the alignment hole **2015** is just outside, at, or just inside the posterior edge of the facet joint.

[0412] In addition to the alignment hole **2015**, near the intersection of the forks **2012** and the tubular shaft portion **2014**, a bump or bull nose **2049** can be provided to further assist with properly placing the delivery device **2004**. The bump **2049** can be in alignment with the alignment hole **2015** and can serve a similar purpose as the alignment hole. Thus, the bump or bull nose **2049** can function to assist the user in properly advancing the delivery device **2004** where the alignment hole **2015** is blocked, or not provided, or in addition to the alignment hole **2015**. The bump **2049** can accentuate the location of the proximal end of the forks **2012** and the bumps position relative to the posterior edge of the facet joint can indicate to the user whether the forks **2012** are properly positioned. In some embodiments, the bump can also function to secure the forks **2012** in the facet joint. That is, as the delivery device **2004** is advanced into the joint, the bump or bull nose **2049** can be advanced just beyond the posterior edge of the articular surface of the facet joint. This articular surface can be relatively concave and the shape of the bump or bull nose **2049** can function to hook itself just inside the perimeter of the concave surface and resist withdrawal of the delivery device **2004**.

[0413] The generally rectangular cross-section of the proximal portion of the receiving assembly **2010** may have a

long side and a short side. The long side may be oriented perpendicular to a line connecting the forks **2012**. This may be in contrast to the previously described embodiments, where the long side was shown parallel to a line connecting the forks **2012**. In some embodiments, particularly where two contralateral facet joints are being treated, the shown orientation can assist in avoiding interference of adjacent handles. That is, the shown orientation can allow the forks of the delivery device **2004** to be inserted into the facet joint and the receiving assembly **2010** can maintain a vertical orientation relative to the patient allowing the nearby joint to be treated without interference with the receiving assembly **2010**. In the present tool assembly **2000**, the tool pieces adapted for insertion into the deliver device **2004** can also have a handle portion such as, for example, handle **2032** and/or **2044** that is oriented perpendicular to the chisel distal tip or the holding arms **2048** respectively. As such, devices used with the delivery device **2004** may be properly aligned relative to the forks **2012** by positioning and seating them in the seating cavities **2013** of the receiving assembly.

[0414] Referring now to FIG. **146**, a decorticator **2006** is shown. The decorticator **2006** shown can include a malleting element **2038** at its proximal end and a series of decorticating teeth **2037** on a distal end. The malleting element **2038** and the teeth **2037** can be connected by a generally U-shaped and relatively thin longitudinally extending member **2034**. The malleting element **2038** can include a relatively thick generally U-shaped member. As shown, the malleting element **2038** and the longitudinal member **2034** can be aligned and adapted to receive a tube from the lateral side. That is, for example, the decorticator **2006** can be applied to the delivery device **2004** from the side rather than being sleeved over the delivery device as shown in previous embodiments. The malleting element **2038** can be used for forcibly advancing the decorticator **2006**. Accordingly, the malleting element can be a relatively thick element adapted to absorb and distribute a malleting force to the longitudinal member **2034**. The teeth **2037** can be the same or similar to the decorticating teeth previously described, such as, for example, the serrated teeth **1037**. The teeth **2038** can be positioned along all or a portion of the half annular shape formed by the distal end of the U-shaped longitudinal member **2034**. As with the decorticator **1006**, the present decorticator **2006** can include a chamfered distal end allowing for acute decortication by the teeth **2037** without interfering with adjacent or surrounding structures. For example, decorticator **2006** can allow for access to the inferior lateral mass without interference from the superior lateral mass of a facet joint due to the chamfered distal end and also due to the u-shape. The decorticator can include features that are the same or similar to the decorticators previously described.

[0415] The malleting element **2038** can be used with a malleting tool **2001** as shown in FIGS. **136** and **150**. As shown best in FIG. **136**, the malleting tool **2001** can include a longitudinally shaped shaft with a U-shaped decorticator interface **2005** at one end and a chamfered tip **2003** at the other end. The decorticator interface **2005** can be adapted for positioning around the delivery device **2004** in a position just proximal to the malleting element **2038** of the decorticator. The u-shape of the decorticator interface **2005** may allow the malleting tool **2001** to be placed in position from the side of the delivery device and selectively used as required to forcibly advance the decorticator **2006**. The chamfered end of the tool **2001** can be held in position while the user mallets near

the decorticator interface end causing the interface **2005** to contact the malleting element **2038** on the decorticator. The decorticator **2006** may then be retracted, rotated to a new radial position, advanced, and struck again for additional decortication. The tool **2001** may rotate with the decorticator **2006** or it may remain in a position convenient for malleting. In addition to malleting, the malleting tool **2001** can be used to assist in separating several tools. That is, in some cases, the handles of a given tool piece, for example, the handle **2032** of the chisel **2006** can be difficult to separate from the receiving assembly **2010**. As mentioned, the malleting tool can include a chamfered tip **2003**. The chamfered tip can be used to wedge between a given handle and the receiving assembly **2010** to assist in separating the devices.

[0416] Referring now to FIGS. **147** and **148**, a driver assembly **2042** is shown. As shown, the driver assembly **2042** includes a handle **2044**, an implant shaft **2046**, implant holding arms **2048**, and an integrated internal actuator **2052**.

[0417] The handle **2044** of the driver assembly **2042** may include features the same or similar to previously described handles. In particular, the handle **2042** can include features the same or similar to the driver assembly handle **1042**. In the present embodiment, the handle can also include a slot cavity, similar to the chisel **2008**, for receiving and interfacing with the malleting anvil **2041** on the proximal end of the receiving assembly. Where the driver assembly **2042** is sleeveably positioned within the delivery device **2004**, the necked down portions **2045** of the handle **2044** can be received into the receiving assembly **2010** and the slot cavity can be positioned around the malleting anvil **2041** on the proximal face of the receiving assembly. Similar to the chisel **2008**, the slot cavity on the handle **2044** can include a bearing surface **2047** for interfacing with the malleting anvil **2041**. In addition, the handle **2044** can include a malleting bar **2043** extending distally from a first side of the body of the handle, laterally across the width of the body of the handle, and then proximally to a second side of the handle. The malleting bar **2043** may allow for malleting of the driver assembly **2042** and the interaction of the bearing surface with the malleting anvil can function to prevent relative longitudinal motion between the driver assembly **2042** and the delivery device **2004** when malleting the driver assembly. Additionally, as described with respect to the chisel **2008**, the handle **2044** can include connection features **2043** providing for a detent relationship with the receiving assembly **2010** or the latch type connections can be provided.

[0418] The integrated internal actuator **2052** can include features the same or similar to the internal actuator **1052**. In the present embodiment, the actuator can be integrated into the driver assembly **2042** and can be securably and pivotally positioned therein. For example, when compared to the internal actuator **852** and/or **1052**, the tubular shaft **855/1055** can be omitted and an internal rod **2057**, the same or similar to rods **857** and **1057**, can be positioned within the implant shaft **2046** of the driver assembly. As mentioned with respect to internal actuator **152**, the distal tip of the internal actuator can include flat screwdriver types, phillips head types, square drives, etc. As best shown in FIG. **148**, the distal tip of the internal actuator **2052** can be a flat screwdriver type tip.

[0419] The handle **2053** can be pivotally secured to the handle **2044** of the driver assembly **2042** allowing for pivotal motion of the handle **2053** relative to the implant shaft **2046** causing rotation of the internal rod **2057**. As shown, the handle **2053** can be positioned just proximal to the body of the

handle **2044** and the malleting bar **2043** can extend around its perimeter. A gap may be provided between the malleting bar **2043** and the handle **2053** to avoid interference with the rotation of the handle **2053** and to avoid transferring malleting force through the internal actuator. The handle **2053** can be adapted to advance as it is turned and can further be adapted to properly advance the implant distractor **2050**. That is, the clearance provided within the handle **2044** can be such that a particular advancing distance of the handle **2053** will cause the handle **2053** to interact with or abut the handle **2044** preventing over-advancing the internal rod **2057** and the implant distractor **2050**. This allows the advancement of the implant distractor **2050** and the associated distraction of the joint with the implant to be reproducible and consistent. In one embodiment, the implant distractor **2050** is advanced to a point where a cross-cut of a thread feature on the implant distractor **2050** engages a truncated slot on the implant. In one embodiment, the implant distractor **2050** can be started in the implant by $1\frac{1}{2}$ turns prior to insertion of the driver assembly **2042** in the delivery device **2004** where the leading portion of the thread feature on the implant distractor **2050** is engaged in the leading slot on the implant. The turning of the handle **2053** can then advance the implant distractor **2050** the remaining distance relative to the implant.

[0420] The implant holding arms **2048**, shown most clearly in FIG. **149** may include features similar to other arms shown and described herein. For example, an engagement feature **2058** similar to the bull nose engagement feature **1058** may be provided. In the present embodiment, the engagement feature **2058** can include a raised portion on the surface of the holding arms **2048** that can be adapted to be positioned in the U-shaped receiving feature slots on the lateral edges of the implant. The present embodiment can be contrasted with the arms **1048** shown in FIG. **125**. As shown, the arms **2048** are adapted to be positioned within the implant and do not extend along side the implant. This can allow for a narrower transverse dimension and an overall smaller system. The arms **2048** can include steps as the arms transition from the implant shaft **2046** of the driver assembly to the arms **2048**. The step can be adapted to accommodate the thickness of one of the upper and/or lower members of the implant such that, when placed thereon, an outer surface of the implant can be relatively flush with the upper level of the step.

[0421] The interaction of the driver assembly **2042** with the delivery device **2004** can function to properly position the implant. That is, both the alignment hole **2015** and the bump or bull nose **2049** can function to properly position the delivery device **2004** as described above. The driver assembly **2042** can include a length and handle engagement adapted to position the implant between the forks **2012** of the delivery device **2004** by fully inserting the driver assembly **2042** in the delivery device and engaging the connection features. Accordingly, the driver assembly **2042** can allow the implant to be positioned anterior to the alignment hole **2015** and/or the bumps **2049** of the delivery device **2004** and thus can be used to properly position the implant. This engagement of the handle of the driver assembly **2042** with the receiving assembly **2010** of the delivery device **2004** can simplify the delivery process. That is, once the delivery device **2004** is properly positioned, the mechanical engagement of the several pieces of the tool **2000** can control the proper position of the implant thereby simplifying and expediting the delivery and implantation process. The user can rely on the position of the deliv-

ery device **2004** for placement of the implant thereby minimizing time and/or adjustments to ensure that the implant is properly positioned.

[0422] Turning again to FIGS. **136** and **137**, several views of an injector **2102** are shown. The injector **2102** may include features the same or similar to the injectors previously described. In particular, the injector **2102** can include features the same or similar to the injector **1102**. In the present embodiment, the injector seating feature **2119** can include connection features **2043** the same or similar to those described on the necked down portion of the handles of the chisel **2006** and the driver assembly **2042**. In addition, the seating feature **2119** of the injector **2102** can include a slot cavity for positioning around and receiving the malleting anvil on the receiving assembly **2010** of the delivery device **2004**. The plunger **2123** of the injector **2102**, as shown in FIG. **151**, can include a handle **2125**, a shaft **2127**, and a seal **2129**. The plunger **2123** can be advanced through the injector **2102** to eject bone paste or other materials into and/or around the facet joint.

[0423] It is noted that when comparing tool **1000** to tool **2000** at least two differences include the handle **2032** on the chisel **2008** and the integration of the internal actuator **2052** with the driver assembly **2042**. With respect to the chisel difference, the tool **2000** can be adapted for a one-step facet joint access process. That is, rather than first advancing the chisel **1006** and then sleeving the delivery device **1004** over the chisel, both the chisel **2008** and the delivery device **2004** can be advanced into the facet joint at the same time. With respect to the driver assembly difference, the tool **2000** can be adapted for a smaller diameter than the tool **1000**. That is, in integrating the driver assembly **2042** with the internal actuator **1052**, one of the concentric tubes, namely the tubular shaft **1055**, has been omitted. Additionally, the implant holding arms **2048** can be adapted to hold the implant from behind rather than from the sides. That is, the arms **2048** can pass within the implant and remain within the width defined by the implant. This allows the driver assembly **2042** to have a smaller size than the driver assembly **1042** and also allows the delivery device **2004** to have a smaller size than the delivery device **1004**. Accordingly, the driver assembly **2042** can have a radius of approximately 1 mm to approximately 5 mm. In a preferred embodiment, the driver assembly can have a radius of approximately 3 mm. Additionally, the delivery device **2004** can have a radius of approximately 1.5 mm to approximately 6 mm. Preferably the delivery device **2004** can have a radius of approximately 4 mm. In one embodiment, the delivery device **2004** can have a radius of approximately 5 mm for a majority of its length and can have a radius of 4 mm near the forks **2012**. For example, as shown in FIG. **149**, the outer surface of the delivery device **2004** can neck down at or near the alignment hole. This necked down portion can be by way of squaring off the outside surface of the forks such that the outside surface of the forks is not radiused like the outer surface of the shaft portion of the delivery device **2004**.

[0424] Referring to FIGS. **152** and **153A-C**, an implant distractor **2050** is shown. The implant distractor **2050** can include features the same as or similar to the features of the implant distractor **850**. For example, the implant distractor **2050** can include a continuous coil-shaped thread feature **2066**. Additionally, the thread feature **2066** may be interrupted by at least one cross-cut **2115** at one or more locations along the threaded feature **2066**. In one embodiment, as shown, a single cross-cut **2115** may be positioned just prox-

mal to the distal end. This cross-cut **2115** may be positioned approximately 180 degrees out of phase from the abrupt proximal end **2113** of the thread feature **866**. Both the cross-cut **2115** and the abrupt proximal end **2113** may provide for interlocking engagement of the implant distractor **2050** with the implant **154/854** and thus prevent backing out of the implant distractor **2050**. As shown, the implant distractor **2050** can include a slotted proximal end **2064** adapted to receive a flat screwdriver type distal end of the internal actuator **2052** shown in FIG. **148**.

[0425] The implant distractor **2050** can include a generally elongate cylindrical body **2107** adapted to be advanced between the upper and lower members of the implant causing them to distract. The distal tip of the cylindrical body **2107** can be tapered to accommodate initial engagement with the implant and the remaining portion of the cylindrical body **2107** can be generally elongate with parallel extending edges. Accordingly, a relatively uniform outward force can be induced by the implant distractor **2050** as it advances through the implant **2054**. It is noted that other distractors other than those with thread features can be included and can include alternative advancing mechanisms or can be forcibly advanced.

[0426] Referring now to FIG. **156**, an implant **2054** is shown. The implant may include features that are the same as or similar to the implants **154** and/or **854** described with respect to FIGS. **16-24** and FIGS. **117-120** respectively. The implant **2054** can be made from a variety of materials including stainless steel, tungsten, titanium, PEEK, and nitinol. Other suitable materials can be used. The material can be a malleable material and the combination of the material properties and the thickness can be adapted to allow the implant to conform to the shaped of the implant distractor and/or the articular surfaces of the facet joint. For example, the thickness of the upper and lower members **2068**, **2070** can range from approximately 0.05 mm to approximately 2 mm. In a preferred embodiment, the thickness can be approximately 0.38 mm.

[0427] Referring to FIGS. **157-162**, several perspective views of an implant **2054** are shown. It is noted that the delivery tool has been omitted for clarity and the method/order of insertion of the implant and the distractor may be different from that depicted here. In FIG. **157**, the implant **2054** is shown prior to insertion into a facet joint. The implant can include upper and lower planar members similar to that described with respect to implants **154** and **854**. The planar members can be generally parallel to one another. As shown in FIG. **158**, the implant **2054** can be inserted into a facet joint. As further shown in FIG. **159**, an implant distractor can be advanced between the relatively planar members forcing the members apart and against the opposing surfaces of the facet joint.

[0428] Referring to FIGS. **160A-C**, the force of the distractor within the implant **2054** can cause the teeth of the implant to gain purchase in the facet joint surface and can further cause distraction of the joint. The relatively malleable nature of the implant **2054** can cause the implant **2054** to conform to the shape of either the implant distractor or the articular surfaces of the facet joint, or both, while still distracting the joint.

[0429] In the embodiment shown, the generally elongate implant distractor can be positioned generally centered across the width of the upper and lower members of the implant. Additionally as shown, the teeth of the implant can be posi-

tioned along the lateral edges of the implant. In this embodiment, as the implant distractor is advanced into the implant, the spreading force of the implant distractor can force the teeth of the implant into the opposing facet surfaces causing them to gain purchase therein as shown in FIG. **160A**. The teeth can engage the bone substantially. In some embodiments, the teeth can be completely seated in the facet surfaces such that the upper and/or lower members abut the surface of the facet joint. The thread feature of the implant distractor can also engage the facet surfaces as it protrudes through the slots in the implant.

[0430] The separation force of the implant distractor can act near the center of the upper and lower members between the teeth of the implant. This spreading force can be counteracted by the naturally resistive force of the articular surfaces of the facet. In this embodiment, this naturally resistive force can act on the engaged teeth of the implant. The concurrent spreading force and opposing resistive force can thus function to form or bend the implant around the axis of the elongate implant distractor forcing it to generally conform to the shape of the implant distractor, as best shown in FIG. **160B**. This forming can allow the center portion of the upper and lower member to more closely approach the articular surfaces of the facet joint rather than being held off from the articular surface by any remaining height of the teeth. Accordingly, the threaded slots in the upper and lower member can allow the thread feature of the implant distractor to project through and further engage the articular surfaces of the facet. It is also noted that to the extent the articular surface of the facet joint is concave across its lateral width, the forming of the implant can be emphasized. This is because the edges of the articular surface can continue to force the lateral edges of the implant around the implant distractor.

[0431] In some embodiments, the implant distractor can be generally straight with a tapered tip or it can include a tapered tip transitioning into a relatively barrel-shaped mid section followed by a tapered trailing end. In either case, and as shown best in FIG. **160A**, the outward forces of the implant distractor in conjunction with the compressive forces of the articular surfaces of the facet can cause the implant to conform to the shape of the implant in this direction also creating an generally elliptically shaped implant. Accordingly, and as shown by review of FIGS. **160A** and **160B**, the planar members of the implant **2054** can take on a doubly curved shaped corresponding to the shaped of implant and resembling the concave shape of the articular surfaces.

[0432] FIGS. **161A** and **161B** show additional views of the implant **2054** reflecting a similar conforming transition between opposed planar members of the implant **2054** in FIG. **161A**, and opposed doubly curved members of the implant **2054** in FIG. **161B**. In these views, the facet joint has been omitted for clarity. As can be seen from a review of FIG. **161B**, the upper member of the implant **2054** can be concave and can form about the longitudinal axis of the elongate distractor. Additionally, as can be seen by viewing the longitudinal seam between the upper and lower member, the upper member and lower member can also form a relatively elliptical shape about an axis perpendicular thereto.

[0433] It is noted that alternative implant distractors can be used depending on the shape of the implant desired. For example, a broader implant distractor can be provided for broader joints to broaden the longitudinal cross-section of the implant and better distribute the compressive forces. The anterior to posterior profile of the implant distractor can be

adjusted to reflect the shape of the articular surfaces of a particular joint thereby allowing the implant to do the same. Implant distractors that provide a relatively uniform expansive pressure to separate the upper and lower members can also be provided to cause the implant to more uniformly conform to the shape of the articular surfaces of a particular joint. These distractors can include fluid type distractors or other relatively uniform pressure devices.

[0434] Referring to FIG. 162, a mechanically tested implant is shown exhibiting the conforming properties described. That is, the implant has conformed under compressive pressure to reflect the shape of the implant distractor and/or the contour of the opposing surfaces of a facet joint. The implant exhibits a formed shape around the longitudinal axis and an axis transverse thereto.

[0435] Referring to FIGS. 163-170, the dimensions of a particular embodiment of the tool are shown. FIG. 163 includes exemplary dimensions of an implant. FIG. 164 includes exemplary dimensions of a delivery device. FIG. 165 includes exemplary dimensions of an implant distractor. FIG. 166 includes exemplary dimensions of a chisel. FIG. 167 includes exemplary dimensions of a place holding chisel. FIG. 168 includes exemplary dimensions of a driver assembly. FIG. 169 includes exemplary dimensions of a decorticator. FIG. 170 includes exemplary dimensions of a malleting tool. FIGS. 163-170 reflect dimensions of just one example of an embodiment of a tool. The tool can be constructed with alternative configurations, dimensions, and relationships and is not limited to these particular examples.

[0436] Referring now to FIGS. 171-174, an additional embodiment of a chisel 2209 is shown. The chisel 2209 can be adapted to facilitate easier initial access of the facet joint. The chisel 2209 can include features the same or similar to previously disclosed chisels, for example, chisel 2008 and/or chisel 2009. As shown in FIG. 171, the chisel 2209 can include a distal portion 2211 and a proximal portion 2213. The combined length of the distal portion 2211 and the proximal portion 2213 can form the overall length of the chisel 2209. The overall length of the chisel 2209 can be the same or similar to the length of the chisel 2009. As such, when the distal tip of the chisel is in place in a facet joint within, for example, a delivery device 2004, the distal end of the chisel 2209 can extend out of the distal end of the delivery device 2004 to allow for manipulation of the chisel 2209.

[0437] Referring now to FIG. 172, a close-up view of the distal portion 2211 of the chisel 2209 is shown. The distal portion 2211 can include a chamfered tip 2230 similar to the previously disclosed chamfered tips. However, the chamfered tip shown includes ridges 2037 on one face of the tip 2230 as shown in FIG. 172 and not on the opposing face as shown in FIG. 173. In some embodiments, ridges 2037 can be included on each face or may be omitted altogether. Where the ridges 2037 are omitted on one or both faces, resistance experienced by a user attempting to access a facet joint with the tip of the chisel 2209 may be minimized. However, the ability to deco-rotate the facet surfaces may also be reduced.

[0438] Referring still to FIG. 172, the distal portion 2211 of the chisel 2209 can be a generally elongate and cylindrically shaped member with a longitudinal bore 2215 extending there through. The cylindrical cross-section of the distal portion 2211 can have a radius ranging from approximately 1 mm to approximately 6 mm. In other embodiments, the radius can range from approximately 3 mm to approximately mm. In one embodiment, the radius can be approximately 4 mm. The

bore 2215 can be sized and adapted to receive and pass through a needle. In some embodiments, the needle can be approximately a 12 GA to approximately a 28 GA needle. In other embodiments, the needle can be a gauge somewhere in between 12 to 28 or a gauge beyond 12 to 28. In one embodiment, the needle may be a 22 GA needle.

[0439] The bore 2215 can be generally centered in the circular cross-section of the distal portion 2211 and can extend from the transition between the proximal portion 2213 and the distal portion 2211 to the distal tip of the chisel 2209. The bore can extend through the chamfered tip 2230 creating a notch 2217 in the chamfered tip 2230 at its distal edge. The bore 2215 can be exposed to the environment surrounding the chisel 2209 via a plurality of holes 2219 and/or a slot 2221.

[0440] The distal portion 2211 can have a length adapted to accommodate standard length needles. That is, the distal portion 2211 can have a length adapted to accommodate a 5", an 8", or a 10" standard length surgical needle for example. In these embodiments, the distal portion 2211 of the chisel 2209 can have a length such that when the needle is inserted into the bore 2215 from the proximal end and the needle hub provided on the needle abuts the transition between the distal portion 2211 and the proximal portion 2213, the distal tip of the needle can extend between approximately, 5 mm to approximately 35 mm beyond the distal tip of the chisel 2209. In some embodiments, the length of the distal portion 2211 is such that a standard length needle can extend between approximately 15 mm to approximately 25 mm beyond the distal tip of the chisel 2209.

[0441] Referring now to FIG. 174, the proximal portion 2213 is shown. The proximal portion 2213 of the chisel 2209 can extend from the distal portion 2211 and be adapted for manipulating the distal tip of the chisel 2209. The proximal portion 2213 can have a length adapted to extend from a delivery device 2004 when a delivery device is inserted over the chisel 2209. In the present embodiment, the proximal portion 2213 includes a semi-circular cross-section and is generally solid. The cross-sectional shape can define an arcuate surface and a generally flat surface of the proximal portion 2213. The arcuate portion can be a continuation of an arcuate $\frac{1}{2}$ of the distal portion 2211 and the flat portion can extend from the transition at approximately the mid-depth of the distal portion 2211 proximally to the proximal end of the chisel 2209. The proximal portion 2213 can be hollow and/or can include alternatively shaped cross-sections. As shown, the proximal portion 2213, near the transition to the distal portion 2211, can include an entry feature 2223 adapted to receive a needle and facilitate advancing the needle into and through the bore 2215 of the distal portion. The entry feature 2223 can be centered on the proximal portion 2213 in alignment with the bore 2215 and can be in the form of a groove or trough in the flat surface of the proximal portion 2213. The entry feature 2223 can extend from the transition proximally away from the transition and along the flat surface.

[0442] The above description has included some references to use to allow for a better understanding of the structure. Below is a more detailed discussion of that use including the devices and techniques for distracting and retaining a facet joint in a distracted and forwardly translated condition. The implantation procedure may be performed under conscious sedation in order to obtain intra-operative patient symptom feedback.

[0443] The joint, which can be difficult to access, may be accessed pursuant, for example, to a method and apparatus

disclosed in U.S. Non-provisional application Ser. No. 61/350,609, filed Jan. 8, 2009, which is commonly owned with the present application and hereby incorporated by reference. Pursuant to the disclosure in that application, the access system may include one or more cannulas made of steel, titanium, or plastic. The initial facet joint access cannula may have a sharp spatula tip on the distal end. The spatula tip may have a flat configuration to enable access into the flat facet joint. Once the spatula tip achieves access into the flatly oriented facet joint, subsequent stylets and working instruments may be passed down this access channel to complete a distraction procedure. Alternatively the dilation set **1200** may be used. Alternatively, one or a plurality of the chisel and delivery devices described above may be used to access the joint. The distraction procedure may then begin.

[0444] More particularly, initially, an incision may be made in the patients back. Tools known in the art may be used to create this incision and the dilator set **1200** may be used to open an access path through the tissues of the back as described above.

[0445] In the case of a tool **1000**, once an access path is created, the chisel **1008** described above may be advanced through the incision and the distal tip **1030** may be positioned adjacent the target facet joint. It is noted that chisel **1008** with an interior lumen may allow for visualization to be provided by including a scope within the chisel **1008**. Additionally, an incision in the facet joint capsule may be made prior to beginning the procedure, and thus prior to insertion of the chisel **1008**. Once the distal tip of the chisel **1008** is properly positioned adjacent the facet joint, the chisel **1008** may be inserted into the facet joint. The chisel **1008** may be used to decorticate the articular surfaces of the facet joint by manipulating the chisel **1008** within the joint. This may include tapping the chisel with a device such as a hammer, mallet, or other instrument to advance the distal tip **1030** of the chisel **1008** and may also include moving the proximal end of the chisel laterally from side to side, up and down, or rotationally, to decorticate the joint. The chisel **1008** may then be tapped into place anteriorly such that it extends substantially through the joint. Fluoroscopy from one or more directions may be used to verify the location of the chisel.

[0446] The delivery device **1004** may be slidably advanced over the chisel **1008** and the forks **1012** of the delivery device **1004** may be advanced into the facet joint. Additional fluoroscopy from one or more directions may be used to verify proper placement of the delivery device **1004** and forks **1012**. The chisel **1008** may be removed.

[0447] An implant may be placed in the driver assembly **1042** and the implant and driver assembly **1042** may be slidably advanced through the delivery device **1004**. The forks **1012** of the delivery device **1004** may be holding the facet joint slightly distracted. As such, the implant, in its relatively flat and parallel position, may slide relatively easily into the facet joint. To the extent that it does not, the proximal end of the driver assembly **1042** may be tapped to properly advance and position the implant.

[0448] The button on the handle **1053** of the internal actuator **1052** may be pressed to expose the engagement feature **1059** at the distal end of the internal rod **1057** of the internal actuator **1052** and the implant distractor may be placed therein. The button may be released causing at least the proximal end of the implant distractor and the engagement feature **1059** to be retracted within the longitudinal shaft **1055** of the

internal actuator **1052** thereby causing a clamping force on the engagement feature **1059** and securing the implant distractor.

[0449] The internal actuator **1052** may then be inserted into the proximal end of the driver assembly **1042** and advanced to a point just proximal to the implant. Once properly positioned, the handle **1053** may be rotated or otherwise actuated to advance the implant distractor into the implant thereby distracting implant and the facet joint.

[0450] The button on the handle **1053** may be pressed again to expose the engagement feature **1059** at the distal end of the internal rod **1057** from the longitudinal shaft **1055** thereby reducing the clamping force of the engagement feature on the implant distractor and allowing for removal of the internal actuator, while the implant distractor is threadably engaged with the implant. Additionally, the distraction of the implant may cause the upper and lower members of the implant to clear the engagement features **1058** of the holder arms **1048** thus allowing the driver assembly **1042** to be freely removed from the delivery device **1004** leaving the implant and the implant distractor behind.

[0451] The injector **1102** may be advanced through the delivery device **1004** and positioned adjacent to the facet joint. The handle **1025** of the plunger **1023** may be depressed thus advancing the plunger **1023** and ejecting the bone paste or other anchoring material. The injector **1102** may be removed. The delivery device **1004** may also be removed and the incision may be closed. The above procedure may be conducted to treat one or both contralateral facet joints.

[0452] An implant may additionally or alternatively be delivered with the tool **2000**. As discussed with respect the chisel **2008**, the delivery device **2004** and the chisel **2008** can be inserted in a one step process. That is, after the incision is made and the tissues of the back are properly dilated, the chisel **2008** and delivery device **2004** can be advanced into the facet joint. Once properly positioned, the chisel **2008** can be removed from the receiving assembly **2010** by prying it free with the malleting tool **2001** or using available push buttons. The removal of the chisel **2008** can prepare the tool **2000** for insertion of the driver assembly **2042**. Where contralateral facet joints are being treated, the placing holding chisel **2009** can be placed down the shaft of the delivery device **2004** and the delivery device **2004** can be removed. The delivery device **2004** and the chisel **2008** can then be inserted in the contralateral joint and once properly positioned, the chisel **2008** can be removed to prepare for insertion of the driver assembly **2042**.

[0453] In some embodiments, the chisel **2209** can be used to initially establish the location of the joint and the proper trajectory of the tool. In this embodiment, the chisel **2209** can be inserted toward a facet joint and be advanced to the lateral mass of the facet joint. This can be done prior to insertion of the tool as mentioned above. A needle can be inserted through the chisel **2209** and extended out the end of the chisel **2209**. The surrounding lateral mass can be probed with the needle to determine the location of the facet joint and the position and trajectory of the chisel **2209** can be adjusted until the needle enters the facet joint. Additionally, using lateral fluoroscopy, the needle can be used to determine if the trajectory of the entry is aligned with the slope of the facet joint. That is, if the needle enters the joint, but bends as it continues into and across the joint, the trajectory may not be aligned with the slope of the joint. The chisel trajectory can thus be adjusted, which may include adjusting the bodily entry point.

[0454] When the proper trajectory and location are established, the chisel **2209** can be advanced over the needle and into the joint. To transition back to the tool **2000**, a series of dilation tubes can be used. That is, as mentioned, in one embodiment, the chisel **2209** can have a cross-section radius of 4 mm. A 5 mm radius tube can be advanced over the chisel **2209** and a 6 mm radius tube can be advanced over the 5 mm radius tube and the 5 mm radius tube can then be removed, leaving the 6 mm radius tube sleeveably positioned over the 4 mm radius chisel **2209**. Dilations tubes similar to those described with respect to FIGS. **129-135** can be used.

[0455] The one-step tool **2000** can thus be used by removing the chisel **2008** from the delivery device **2004** and the delivery device **2004** can be sleeveably advanced over the chisel **2209** and within the 6 mm radius dilation tube and the forks **2012** can be advanced into the facet joint. The 6 mm radius dilation tube can be removed and the chisel **2209** can also be removed. To the extent decortication is desired, the chisel **2008** or **2009** can be inserted through the delivery device **2004** and the joint can be decorticated. Where contralateral joints are being addressed, the place holding chisel **2009** can be inserted in the joint to maintain the access to the joint without occluding fluoroscopic view of the contralateral joint.

[0456] An implant, for example implant **2054**, can be positioned on the distal end of the driver assembly **2042** and the U-shaped receiving feature slots on the lateral sides of the implant can be positioned over the engagement features **2058**. It is noted that, when in position, the width of the driver assembly **2042** can be the same or similar to the width of the implant. This is in contrast to that, which is depicted in FIG. **12**, for example, with driver assembly **142**. The upper and lower surfaces of the implant can be biased toward a parallel position and, as such, when placed over the distal end of the driver assembly **2042**, may provide a slight clamping force on the distal end of the driver assembly **2042**. In addition, an implant distractor such as, for example distractor **2050**, can be advanced slightly into the proximal end of the implant causing the continuous thread feature **2066** to engage the threaded slots of the implant and further secure the implant to the driver assembly. Moreover, this initial starting of the implant distractor **2050** in the implant **2054** can help avoid mis-threading of the distractor **2050**. In one embodiment, the implant distractor can be advance, for example, 2 turns into the implant.

[0457] Having placed the implant on the distal end of the driver assembly **2042**, the driver assembly **2042** and the implant can be advanced through the delivery device **2004** and the implant can be positioned in the facet joint. Rotation of the handle **2053** can cause rotation of the internal rod **2057** thereby causing rotation of the implant distractor **2050**. Accordingly, the thread feature **2066** can cause the implant distractor **2050** to advance relative to the implant **2054** thereby distracting the implant **2054** and, in turn, also distracting the facet joint. It is noted that distraction of the implant **2054** can cause the implant to be free from the engagement features **2058** on the distal end of the driver assembly **2042** and as such, once distracted, the driver assembly **2042** can be removed.

[0458] In another embodiment, a tool **3000** may include some or all of the elements described with respect to tool **1000**. However, rather than combining the driver assembly **1042** and the internal actuator **1052**, as with tool **2000**, in this embodiment, the driver assembly **1042** may be omitted. In this embodiment of a tool **3000**, delivery of the implant may

be conducted with the internal actuator **1052**. That is, the implant distractor may be initially partially engaged with or “started” in the implant sufficiently to hold the two together. This engagement may be due to the implant being biased to keep the upper and lower members in a parallel position thus creating a threaded and frictional resistance to separation of the implant and the implant distractor. Additionally or alternatively, this engagement may be due to engagement of a cross-cut thread on the implant distractor being engaged with a truncated threaded slot of the implant. Once the implant distractor is started in the implant, the implant distractor may be engaged with the engagement feature on the internal actuator **1052** thus stringing the internal actuator **1052**, the implant distractor, and the implant together. The internal actuator **1052** together with the implant distractor and the implant may then be advanced down the tubular shaft **1014** of the delivery device **1004** in lieu of the driver assembly **1042**.

[0459] In this embodiment, the omission of the driver assembly **1042** may allow for smaller sized shafts of several devices similar to tool **2000**. In one embodiment, the outer radius of the tubular shaft **1014** of the delivery device **1004** may be approximately 4 mm and the outer radius of the decorticator may be approximately 5 mm.

[0460] In still another embodiment, the several handles/seating features (e.g., **1044**, **2044**, **1119**) may include a slot opening on their distal end for use in separating the handles from the receiving assembly **1010**. That is, when the handles are engaged with the receiving assembly and the projections are seated in the seating cavities, the frictional/suctional fit of the handles in the receiving assembly may be difficult to separate. Accordingly, a slot opening on the distal end of the handles may be provided, which may provide for accessing the joint between the handles and the receiving assembly with a separation device which may assist in working the elements apart via prying, scissor action, or other known methods. Alternatively or additionally, the frictional engagement of the several handles in the receiving assembly may be reduced.

[0461] The delivery system disclosed herein is advantageous for at least the following reasons. First, the system facilitates delivery of an implant to a facet joint via a minimally invasive or percutaneous procedure, reducing the risk, surgical time and recovery time associated with the implantation of the implant in the facet joint. Accordingly, many of the dimensional characteristics associated with the delivery system, its components, and the implant are advantageous in that they facilitate or make possible the minimally invasive or percutaneous procedures described herein. Second, the system facilitates the implant being delivered while the patient is capable of providing verbal feedback as to the impact of the implant relative to symptoms being felt by the patient.

[0462] Referring now to FIGS. **175-177**, an implant is shown positioned between vertebral bodies of the lumbar spine and adapted for an interbody fusion. While the majority of this application has addressed the use of implants placed in one or more facet joints, the implants and delivery devices herein described can also be used in other joints of the spine. As shown, for example, the implant can be used where a disc has deteriorated and/or been removed from a spinal joint between vertebral bodies. In the case of a discectomy type procedure, the implants can be used after the disc has been removed to secure two adjacent vertebral bodies and maintain their separation. The currently described delivery tools and

implants are not limited to use in the cervical or lumbar spine and further are not limited to facet joints or joints between vertebral bodies.

[0463] Discectomy type procedures are often performed from one of three different access points. In one procedure, the spinal column is approached from the posterior. In another procedure, the spinal column is approached anteriorly and in another, from the lateral side of the patient. Referring particularly to FIG. 175, an implant procedure is shown where a posterior approach has been used. That is, where the discectomy is performed from the posterior, the implant can be delivered from the posterior as well. Referring particularly to FIG. 176, an implant procedure is shown where a lateral approach has been used and FIG. 177, shows the implant where an anterior approach has been used. It is noted that the implant can be delivered from any position and the delivery approach does not have to be consistent with the discectomy approach. That is, for example, if the discectomy is performed anteriorly, the implant delivery may be done anteriorly as well, but could also be performed posteriorly or laterally. However, it may be advantageous to use the same delivery approach as the discectomy for purposes of minimizing incisions.

[0464] In any of the above approaches, the procedure to place an implant between vertebral bodies can be the same or similar to the procedure to place the implants in a facet joint. For example, the chisel 2008 and delivery device 2004 of tool 2000, for example, can be advanced into the joint between vertebral bodies. As shown in FIGS. 175-177, this can be completed from one of several directions. The teeth of the chisel 2008 can be used to decorticate the joint as desired. Once properly positioned and decorticated, the chisel 2008 can be removed from the receiving assembly 2010 by prying it free with the malleting tool 2001 or using available push buttons. The removal of the chisel 2008 can prepare the tool 2000 for insertion of the driver assembly 2042. Fluoroscopy can be used to verify proper placement of the delivery device 2004 to ensure proper placement of an implant.

[0465] An implant, for example implant 2054, can be positioned on the distal end of the driver assembly 2042. The U-shaped receiving feature slots on the lateral sides of the implant 2054 can be positioned over the engagement features 2058 and an implant distractor 2050 can be advanced slightly into the proximal end of the implant 2054, for example, 2 turns into the implant. The driver assembly 2042 and the implant 2054 can be advanced through the delivery device 2004 and the implant 2054 can be positioned in the joint between the vertebral bodies. Rotation of the handle 2053 can cause rotation of the internal rod 2057 thereby causing rotation of the implant distractor 2050. Accordingly, the thread feature 2066 can cause the implant distractor 2050 to advance relative to the implant 2054 thereby distracting the implant 2054 and, in turn, also distracting the joint between the vertebral bodies. It is noted that distraction of the implant 2054 can cause the implant to be free from the engagement features 2058 on the distal end of the driver assembly 2042 and as such, once distracted, the driver assembly 2042 can be removed. A similar procedure can be performed to place a second implant 2054. While this procedure has been described with regard to tool 2000 and implant 2054, any of the described tools and implants described can be used.

[0466] Some additional methods of use are described below with reference to FIGS. 178-185. In each of the shown methods, any combination of the steps shown or portion of the

steps can be included. Additionally, the order of the steps can be rearranged and is not limited the orders of the boxes or label numbers shown.

[0467] Referring to FIG. 178, in one embodiment, a method of distracting a facet joint of the spine can include inserting a delivery device to access the facet joint of a patient (4000), inserting a driver assembly holding an implant into the delivery device (4002), and actuating the driver assembly thereby distracting the implant (4006). Inserting the delivery device can include inserting a chisel through the delivery device and tapping on the proximal end of the chisel to advance the chisel and the delivery device into the facet joint. Actuating the driver assembly can include turning a distractor knob on the driver assembly thereby rotating an internal actuator and advancing an implant distractor. The method can also include inserting an injector in the delivery device and delivering a bone paste to the implantation site (4008).

[0468] Referring to FIG. 179, in one embodiment, a method of distracting a facet joint of the spine can include dilating a path to a facet joint using a dilator set (4010), inserting a chisel into the facet joint (4012), advancing a delivery device over the chisel and inserting forks of the delivery device into the facet joint (4014), removing the chisel from the joint (4016), inserting a driver assembly with an implant into the delivery device, seating the driver assembly in the delivery device thereby positioning the implant between the forks of the delivery device and in the facet joint (4018), inserting an internal actuator into the driver assembly and advancing an implant distractor into the implant thereby distracting the implant (4020), actuating a button on the internal actuator thereby releasing a grip on the implant distractor and removing the internal actuator and the driver assembly (4022), and inserting an injector and injecting a flowable material into or around the facet joint (4024). In some embodiments, advancing the implant distractor can include turning a handle on the internal actuator thereby rotating an internal rod and threadably advancing an implant distractor.

[0469] Referring to FIG. 180, a method of distracting a facet joint of the spine can include inserting a chisel into a facet joint to provide initial distraction and decorticate the surface of the joint (4026), inserting a delivery device over the chisel to maintain the initial distraction (4028), inserting an implant through the delivery device and into the joint, the implant having teeth adapted to engage the surfaces of the joint (4030), distracting the implant by advancing an implant distractor, the implant distractor having a coil-shaped thread feature for engaging threaded slots of the implant, the implant distractor further having cross-cut threads for engaging truncated threaded slots on the implant, wherein, advancing the implant distractor includes causing the cross-cut threads to engage the truncated threaded slots and prevent backing out of the implant (4032), and releasing the implant distractor and removing the delivery device thereby leaving the implant and the implant distractor in place in the joint (4034).

[0470] Referring to FIG. 181 a method of distracting a facet joint of the spine can include inserting a delivery device into a facet joint (4036), inserting an implant through the delivery device and into the joint (4038), and distracting the implant by advancing an implant distractor (4040).

[0471] Referring to FIG. 182, a method of distracting a facet joint of the spine can include partially engaging an implant distractor with an implant and engaging the implant distractor with an internal actuator to form an assembly (4042), inserting the implant portion of the assembly into the

facet joint (4044), and distracting the facet joint (4046). In some embodiments, distracting the facet joint can include actuating the internal actuator which advances the implant distractor.

[0472] Referring to FIG. 183, a method of distracting a facet joint and a contralateral facet joint of a spine can include inserting a delivery device and chisel assembly into the facet joint (4048), removing the chisel from the assembly and replacing the chisel with a place holding chisel (4050), removing the delivery device from the facet joint (4052), inserting the delivery device and chisel assembly into the contralateral facet joint (4054), removing the chisel from the assembly (4056), placing and distracting a first implant in the contralateral facet joint (4058), removing the delivery device from the contralateral facet joint (4060), placing the delivery device back in the facet joint via the place holding chisel (4062); and placing and distracting a second implant in the facet joint (4064). In some embodiments, the place holding chisel can be a radiolucent chisel. The method can also include performing lateral fluoroscopy to determine proper placement of the first implant (4066).

[0473] Referring to FIG. 184, a method of distracting a facet joint of the spine can include inserting a delivery device and chisel assembly into the facet joint to provide initial distraction and decorticate the surface of the joint (4068), removing the chisel assembly from the delivery device (4070), inserting a driver assembly through the delivery device, the driver assembly holding an implant and further comprising an implant distractor adapted to distract the implant (4072), distracting the implant (4074), and removing the driver assembly and the delivery device (4076). The method can also include positioning the delivery device and chisel assembly by selectively malleting a proximal end thereof (4078). The method can also include selectively malleting a proximal end of the driver assembly (4080) and can further include positioning a decorticator on the delivery device from the lateral side of the device (4082). Still further, the method can include advancing the decorticator along the length of the driver assembly, positioning a malleting tool against the proximal end of the decorticator, and malleting the malleting tool to forcibly advance the decorticator and decorticate the lateral mass of the facet joint (4084). The method can also include retracting, rotating, and re-advancing the decorticator in a new position and malleting the malleting tool to decorticate a different location (4086). In addition, the method can include obtaining intra-operative patient symptom feedback (4088).

[0474] Referring to FIG. 185, a method of performing an interbody fusion can include inserting a delivery device and chisel assembly into a joint between vertebral bodies of the spine (4090), removing the chisel assembly from the delivery device (4092), inserting a driver assembly through the delivery device, the driver assembly holding an implant and further comprising an implant distractor adapted to distract the implant (4094), distracting the implant (4096), and removing the driver assembly and the delivery device (4098). The method can also include repeating the steps to place a second implant in the joint (4100).

[0475] Although the present invention has been described with a certain degree of particularity, it is understood the disclosure has been made by way of example, and changes in detail or structure may be made without departing from the spirit of the invention as defined in the appended claims.

What is claimed is:

1. A spinal joint distraction system for treating a facet joint including articular surfaces having a contour, the system comprising:

- a delivery device including a generally tubular structure adapted to engage a facet joint;
- an implant adapted to be delivered through the delivery device and into the facet joint, the implant comprising two members arranged in opposed position; and
- an implant distractor comprising a generally elongate member adapted to advance between the two members of the implant causing separation of the members and distraction of the facet joint,

wherein the implant is adapted to conform to the shape of the implant distractor upon being delivered to the facet joint.

2. The system of claim 1, further comprising a driver assembly adapted to hold the implant and advance the implant distractor, the driver assembly further adapted for insertion through the delivery device.

3. The system of claim 2, further comprising a chisel adapted for insertion through the delivery device to facilitate initial engagement with the facet joint.

4. The system of claim 3, further comprising a decorticator adapted for lateral engagement with the delivery device.

5. The system of claim 4, further comprising a malleting tool with a first end adapted to engage the decorticator for a malleting process and a second end adapted to facilitate separation of parts of the system.

6. The system of claim 5, further comprising an injector adapted for insertion through the delivery device and further adapted to deliver a bone paste.

7. A spinal joint distraction system comprising:

- a delivery device and chisel assembly adapted to engage a facet joint; and
- a driver assembly adapted to hold and distract an implant, the driver assembly further adapted for insertion through the delivery device to deliver and distract the implant.

8. The system of claim 7, further comprising a place holding chisel adapted to replace the chisel and maintain the established position of the delivery device and chisel assembly.

9. The system of claim 8, wherein:

the delivery device of the assembly comprises:

- a tubular shaft; and
- a receiving assembly positioned on a proximal end of the tubular shaft; and

the chisel of the assembly comprises a handle having a connection feature adapted to engage the receiving assembly.

10. The system of claim 9, wherein the connection feature includes a protrusion or recess adapted to form a detent relationship with an opposing protrusion or recess respectively.

11. The system of claim 9, wherein the connection feature includes a latch type feature positioned on a deflectable portion of the handle, wherein advancing the chisel handle toward the receiving assembly causes the latch type feature to snap into place and depressing the deflectable portion of the handle releases the latch type feature.

12. The system of claim 8, wherein the receiving assembly further comprises a malleting anvil positioned on a proximal face of the receiving assembly.

13. The system of claim 8, wherein the chisel includes a slot cavity adapted to receive the malleting anvil and a mal-

letting head adapted to engage the malleting anvil to resist relative motion between the delivery device and the chisel during malleting.

14. The system of claim **7**, wherein the delivery device of the assembly includes forks adapted to penetrate the facet joint.

15. The system of claim **14**, wherein the delivery device further comprises a bull nose positioned on the surface of the forks near the intersection of the forks with the tubular structure, the bull nose adapted to mark the position of the delivery device.

16. The system of claim **14**, further comprising an indication hole positioned along the lateral side of the delivery device near the intersection of the forks and the tubular structure.

17. The system of claim **7**, wherein the driver assembly includes an implant shaft having a diameter substantially equal to or less than a width of the implant.

18. The system of claim **7**, wherein the driver assembly further comprises a handle with a malleting bar adapted to transfer malleting blows to the driver assembly.

19. The system of claim **18**, wherein the driver assembly further comprises a slot cavity having a bearing surface, the slot cavity adapted to receive the malleting anvil of the receiving assembly and the bearing surface is adapted to engage the malleting anvil to resist relative motion between the delivery device and the driver assembly during malleting.

20. The system of claim **7**, further comprising a decorticator adapted for positioning upon the delivery device from a lateral side of the delivery device.

21. The system of claim **20**, wherein the decorticator comprises a U-shaped longitudinally extending member with teeth on a distal end.

22. The system of claim **21**, wherein the decorticator further comprises a malleting element at a proximal end adapted to distribute malleting blows to the longitudinally extending member.

23. The system of claim **7**, wherein the driver assembly includes arms adapted to hold an implant, wherein the arms are positioned within a boundary defined by a width of the implant.

24. A spinal distraction implant for the distraction of a facet joint having articular surfaces, the implant comprising a first and a second member arranged in opposing position, each of the first and second member comprising:

- a threaded slot passing through the member adapted to receive a thread feature; and
- a plurality of teeth spaced along two parallel lateral edges, the teeth adapted to engage the articular surfaces of the facet joint,

wherein, the implant is constructed from a malleable material and is further adapted to conform to the shape of the articular surfaces upon being distracted within a facet joint.

25. The implant of claim **24**, wherein the plurality of teeth have a linearly sloped distal face and a proximal face positioned orthogonally to the respective first or second member.

26. The implant of claim **25**, wherein the teeth are equally spaced.

27. The implant of claim **24**, wherein the first and second members each have an interlocking engagement feature on respective distal edges, wherein the first and second members engage one another via their respective interlocking engagement features.

28. The implant of claim **27**, wherein the first and second members are further coupled together via a weld.

29. A method of distracting a facet joint and a contralateral facet joint of a spine comprising:

- inserting a delivery device and chisel assembly into the facet joint;
- removing the chisel from the assembly and replacing the chisel with a place holding chisel;
- removing the delivery device from the facet joint;
- inserting the delivery device and chisel assembly into the contralateral facet joint;
- removing the chisel from the assembly;
- placing and distracting a first implant in the contralateral facet joint;
- removing the delivery device from the contralateral facet joint;
- placing the delivery device back in the facet joint via the place holding chisel; and
- placing and distracting a second implant in the facet joint.

30. The method of claim **29**, wherein the place holding chisel is a radiolucent chisel.

31. The method of claim **29**, further comprising performing lateral fluoroscopy to determine proper placement of the first implant.

32. A method of distracting a facet joint of the spine comprising:

- inserting a delivery device and chisel assembly into the facet joint to provide initial distraction and decorticate the surface of the joint;
- removing the chisel assembly from the delivery device;
- inserting a driver assembly through the delivery device, the driver assembly holding an implant and further comprising an implant distractor adapted to distract the implant;
- distracting the implant; and
- removing the driver assembly and the delivery device.

33. The method of claim **32**, further comprising positioning the delivery device and chisel assembly by selectively malleting a proximal end thereof.

34. The method of claim **32**, further comprising selectively malleting a proximal end of the driver assembly.

35. The method of claim **32**, further comprising positioning a decorticator on the delivery device from the lateral side of the device.

- 36.** The method of claim **35**, further comprising:
 - advancing the decorticator along the length of the driver assembly;
 - positioning a malleting tool against the proximal end of the decorticator; and
 - malleting the malleting tool to forcibly advance the decorticator and decorticate the lateral mass of the facet joint.

37. The method of claim **36**, further comprising retracting, rotating, and re-advancing the decorticator in a new position and malleting the malleting tool to decorticate a different location.

38. The method of claim **32**, further comprising obtaining intra-operative patient symptom feedback.

- 39.** A spinal distraction implant delivery tool, comprising:
 - an implant; and
 - an assembly, the assembly comprising:
 - a means for holding the implant;
 - a means for positioning the implant within a facet joint; and
 - a means for distracting the implant.

- 40.** The tool of claim **39**, wherein the implant comprises: a first substantially planar member and a second substantially planar member arranged in parallel and opposing position to the first substantially planar member; and a biasing connection connecting the first and second planar members to one another, the biasing connection adapted to create a biasing force directed toward biasing the members toward the parallel and opposing position.
- 41.** The tool of claim **40**, wherein the means for holding includes a pair of implant holding arms, the arms adapted to pass between the planar members and force them apart against the biasing force.
- 42.** The tool of claim **41**, wherein the holding arms each include a means for engaging the implant.
- 43.** The tool of claim **40**, wherein the means for distracting the implant includes an implant distractor and a means for rotatably advancing the implant distractor.
- 44.** The tool of claim **43**, wherein the implant distractor comprises a generally elongate member adapted to pass

between the substantially planar members and force the members apart against the biasing force.

45. The tool of claim **44**, further comprising a chisel configured to locate the facet joint and allow for adjustment of the trajectory of the tool.

46. A method of performing an interbody fusion, the method comprising:

inserting a delivery device and chisel assembly into a joint between vertebral bodies of the spine;

removing the chisel assembly from the delivery device;

inserting a driver assembly through the delivery device, the

driver assembly holding an implant and further comprising

an implant distractor adapted to distract the implant;

distracting the implant; and

removing the driver assembly and the delivery device.

47. The method of claim **46**, further comprising repeating the steps to place a second implant in the joint.

* * * * *