




US 20120000876A1

(19) **United States**(12) **Patent Application Publication**
Bergenstråle et al.(10) **Pub. No.: US 2012/0000876 A1**(43) **Pub. Date: Jan. 5, 2012**(54) **LIFT SYSTEMS WITH CONTINUOUS
IN-RAIL CHARGING**(52) **U.S. Cl. 212/336**(75) Inventors: **Robert Bergenstråle**, Lulea (SE);
Mattias Andersson, Sodra
Sunderbyn (SE)(73) Assignee: **LIKE RESEARCH &
DEVELOPMENT AB**, Lulea (SE)(21) Appl. No.: **13/168,409**(22) Filed: **Jun. 24, 2011****Related U.S. Application Data**(60) Provisional application No. 61/361,231, filed on Jul. 2,
2010.**Publication Classification**(51) **Int. Cl.**
A61G 7/10 (2006.01)
B66C 19/00 (2006.01)(57) **ABSTRACT**

Rail-mounted lift systems are disclosed. In one embodiment, the lift system includes a rail having at least one conductor positioned on an upper interior surface of the rail. A carriage may be slidably disposed in the rail for relative movement to the rail. The carriage generally includes a carriage body, at least one pair of support wheels rotatably coupled to the carriage body and slidably engaged with the rail, and a conductor truck comprising at least one conductive roller rotatably attached to the conductor truck. The conductor truck may be mounted to the carriage body with a biasing member upwardly biasing the conductive roller into rolling engagement with the at least one conductor. A lift unit may be coupled to the carriage body and includes a motor paying out and taking up a lifting strap. The lift unit is electrically coupled to the at least one conductive roller.






FIG. 1






FIG. 2








FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11

LIFT SYSTEMS WITH CONTINUOUS IN-RAIL CHARGING

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to U.S. Provisional Patent Application No. 61/361,231 entitled "Continuous In-Rail Charging For Lift Systems" filed Jul. 2, 2010, the entirety of which is herein incorporated by reference.

TECHNICAL FIELD

[0002] The present specification generally relates to rail-mounted lift systems and, more specifically, to rail-mounted lift systems with continuous in-rail charging of the lift unit.

BACKGROUND

[0003] Overhead lifting devices, such as patient lifts used in the health care industry, may generally comprise a lift unit with an actuator, such as an electric motor or similar actuator, coupled to a mechanical lifting arm or cable lift system, such as a lifting strap. The actuator facilitates actuation of the mechanical lifting arm or cable lift system thereby raising and/or lowering a load attached to the lifting arm or cable lift system. The lift unit may be coupled to a rail system with a carriage which facilitates positioning the lift unit with respect to the rail. Positioning the unit along the rail system may be accomplished manually or, in the alternative, with a motor mechanically coupled to the carriage and operable to traverse the carriage and lift unit over the span of the rail system. The actuator and motor may be powered by a battery system positioned in the lift unit. In order to charge the battery system of the lift unit, the lift unit must be periodically coupled to a charging station requiring the lift unit to be moved to specific locations along the rail. Accordingly, during charging, the lift unit may not be used for lifting and transport.

[0004] Accordingly, a need exists for alternative mechanisms for continuously powering and/or charging a lift unit as the lift unit is traversed across a rail.

SUMMARY

[0005] In one embodiment, a rail-mounted lifting system includes a rail comprising at least one conductor positioned in a carriage support channel formed in the rail. A carriage may be slidably disposed in the rail for relative movement to the rail. The carriage may include at least one conductive roller rotatably attached to the carriage and upwardly biased into rolling engagement with the at least one conductor. A lift unit may be coupled to the carriage body and electrically coupled to the at least one conductive roller. The lift unit may include a motor paying out and taking up a lifting strap.

[0006] In another embodiment, a rail-mounted lifting system includes a rail, a carriage and a lift unit. The rail may include at least one conductor positioned on an upper portion of the rail, a first support flange, and a second support flange. A carriage may be slidably disposed in the rail for relative movement to the rail. The carriage may include a carriage body and at least one pair of support wheels rotatably coupled to the carriage body. The at least one pair of support wheels may be slidably engaged with the first support flange and the second support flange. The carriage may also include a conductor truck comprising at least one conductive roller rotatably attached to the conductor truck. The conductor truck may be mounted to the carriage body with a biasing mechanism

which upwardly biases the at least one conductive roller into rolling engagement with the at least one conductor. The lift unit may be coupled to the carriage body and includes a motor paying out and taking up a lifting strap, wherein the lift unit is electrically coupled to the at least one conductive roller.

[0007] In yet another embodiment, a kit of parts for retrofitting an overhead rail for continuously charging a lift unit along a length of the rail may include a conductive tape and a carriage packaged together. The carriage generally includes a carriage body, and at least one pair of support wheels rotatably coupled to the carriage body. The carriage may also include at least one conductive roller rotatably attached to the carriage. The conductive roller is upwardly biased into rolling engagement with the conductive tape when the conductive tape and the carriage are installed in the rail.

[0008] These and additional features provided by the embodiments described herein will be more fully understood in view of the following detailed description, in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The embodiments set forth in the drawings are illustrative and exemplary in nature and not intended to limit the subject matter defined by the claims. The following detailed description of the illustrative embodiments can be understood when read in conjunction with the following drawings, where like structure is indicated with like reference numerals and in which:

[0010] FIG. 1 schematically depicts a rail-mounted lift system, according to one or more embodiments described herein;

[0011] FIG. 2 schematically depicts an exploded view of the rail-mounted lift system of FIG. 1;

[0012] FIG. 3A schematically depicts a carriage for use with the rail-mounted lift system of FIG. 1, according to one or more embodiments described herein;

[0013] FIG. 3B schematically depicts a partially exploded view of the carriage of FIG. 3A;

[0014] FIG. 4 schematically depicts a side view of a carriage for use with the rail-mounted lift system of FIG. 1;

[0015] FIG. 5 schematically depicts the electrical interconnectivity of the various components of the rail-mounted lift system of FIG. 1;

[0016] FIG. 6 schematically depicts a cross section of a rail of the rail-mounted lift system according to one or more embodiments described herein;

[0017] FIG. 7 schematically depicts a cross section of one embodiment of a conductive tape for use with the rail mounted lift system of FIG. 1, according to one or more embodiments described herein;

[0018] FIG. 8 schematically depicts a cross section of a rail-mounted lift system according to one or more embodiments shown and described herein;

[0019] FIG. 9 schematically depicts an applicator tool for applying a conductor to the rail of the rail-mounted lift system;

[0020] FIG. 10 schematically depicts the applicator tool of FIG. 9 being used to install a conductor in the rail of the rail-mounted lift system; and

[0021] FIG. 11 schematically depicts the applicator tool of FIG. 9 being used to install a conductor in the rail of the rail-mounted lift system.

DETAILED DESCRIPTION

[0022] FIG. 1 generally depicts one embodiment of a rail-mounted lift system. The lift system generally comprises a lift unit slidably coupled to a rail with a carriage. The rail includes a conductor which is electrically coupled to a power supply. The carriage includes at least one conductive roller which is upwardly biased from the carriage into rolling engagement with the conductor. The conductive wheel is also electrically coupled to the lift unit thereby electrically coupling the lift unit to the conductor and the power supply and enabling the lift unit to be powered and/or charged along the entire length of the rail as the lift unit is traversed over the rail. The lift system and the various components of the lift system will be described in more detail herein with specific reference to the appended figures.

[0023] Referring now to FIGS. 1, 2 and 5, the rail-mounted lift system 100 generally comprises a lift unit 104 which is slidably coupled to a rail 102 with a carriage 106. The lift unit 104 may be used to support and/or lift a patient with a lifting strap 108 which is coupled to a motor 133 contained within the lift unit 104. The motor 133 facilitates paying-out or taking-up the lifting strap 108 from the lift unit 104 thereby raising and lowering a patient attached to the lift strap. In the embodiments described herein, the lift unit 104 further includes a battery 132 which is housed in the lift unit 104 and electrically coupled to the motor 133 thereby providing power to the motor 133. However, it should be understood that, in other embodiments, the lift unit 104 may be constructed without the battery, such as when the motor is directly coupled to the conductors 114a, 114b located in the rail 102.

[0024] In the embodiment of the lift system 100 shown in FIG. 1, a patient may be attached to the lifting strap 108 with a sling bar 110 or a similar accessory attached to the lifting strap 108. More specifically, the sling bar 110 or a similar accessory may be attached to a harness or sling in which the patient is positioned thereby facilitating the lifting operation. The lift unit 104 may be actuated with hand control 112 which is communicatively coupled to the motor. In the embodiment shown in FIG. 1, the hand control 112 is directly wired to the lift unit 104. However, it should be understood that, in other embodiments, the hand control 112 may be wirelessly coupled to the lift unit 104 to facilitate remote actuation of the lift unit 104.

[0025] Referring now to the exploded view of the lift system 100 schematically depicted in FIG. 2, the lift unit 104 is mechanically coupled to a carriage 106 which facilitates slidably positioning the lift unit 104 along rail 102. In the embodiments of the lift unit 104 described herein, the lift unit 104 includes a connection rail 118 which is mounted to the top surface of the lift unit 104. The connection rail 118 facilitates connecting and securing the lift unit 104 to the carriage 106. In the embodiment of the lift unit 104 shown in FIG. 2, the connection rail 118 has a T-shaped configuration and the carriage 106 has a receiving slot 142 with a complimentary configuration for receiving the connection rail 118. The carriage 106 may be secured to the connection rail 118 with a fastener 119, such as a bolt and nut as depicted in FIG. 2, which extends transversely through openings in the carriage 106 and a corresponding opening in the connection rail 118.

[0026] Referring now to FIGS. 3A and 3B, the carriage 106 generally comprises a carriage body 140 to which a plurality of support wheels 144a, 144b, 144c, and 144d are rotatably attached for supporting the carriage 106 in the rail. The support wheels 144a, 144b, 144c, and 144d facilitate positioning the carriage 106 and lift unit along the length of the rail. In the embodiments described herein, the carriage 106 is depicted with four support wheels. However, it is contemplated that the carriage 106 may be constructed with fewer than 4 support wheels. For example, in some embodiments, the carriage may be constructed with one or two support wheels (i.e., a pair of support wheels). Accordingly, it should be understood that the carriage 106 includes at least one support wheel. The support wheels 144a-d are positioned on axles 120 which extend transversely through the carriage body 140. Each support wheel is secured to the axle 120 with a fastener, such as retaining clips 122, such that the support wheels are rotatable on the axle 120.

[0027] In the embodiment of the carriage 106 depicted in FIGS. 3A and 3B, the support wheels 144a, 144b, 144c, and 144d are passive (i.e., the support wheels are not actively driven with a motor or a similar drive mechanism) and the lift unit is manually traversed along the rail. However, in alternative embodiments (not shown), the support wheels may be actively driven such as when the support wheels are coupled to a motor or a similar mechanism. In such embodiments, the drive mechanism may be communicatively coupled to a hand control (such as hand control 112 shown in FIG. 1) which actuates the drive mechanism and facilitates traversing the lift unit along the rail with the drive mechanism.

[0028] In the embodiments described herein, the carriage 106 further comprises at least one conductive roller 156 (two shown in FIGS. 3A and 3B). The conductive rollers 156 electrically couple the battery and/or the motor of the lift unit to a conductor positioned in the rail to which the lift unit is attached, as will be described in more detail herein. The conductive rollers 156 are formed from an electrically conductive material such as copper or a copper alloy, aluminum or an aluminum alloy, steel, or a similar conductive metallic material and/or alloy. Alternatively, the conductive rollers 156 may be formed from an electrically conductive polymer material. In the embodiments described herein, the conductive rollers are formed from an oil-bronze, specifically SNF-12 oil bronze. However, it should be understood that the conductive rollers may be formed from other conductive materials.

[0029] In the embodiments described herein, the conductive rollers 156 are rotatably attached to a conductor truck 146 which, in turn, is mounted to the carriage body 140. Specifically referring to FIG. 3B, the conductor truck 146 is formed from a polymeric material and includes at least one axle 154 to which the conductive rollers are rotatably attached. In the embodiment of the conductor truck 146 shown in FIG. 3B, the axle 154 is integrally formed with the conductor truck 146. However, in other embodiments, the axles 154 may be independent of the conductor truck 146, such as when a separate axle is utilized in conjunction with the conductor truck 146.

[0030] The conductive rollers 156 are positioned on the axles 154 of the conductor truck 146 and a spacer 158 is positioned between the conductive roller 156 and the axle 154 to facilitate rotation of the conductive roller 156 on the axle 154. In the embodiments described herein, the spacer 158 is formed from an electrically conductive material, such as steel. However, it should be understood that the spacer 158

may be formed from other electrically conductive materials, including, without limitation, other electrically conductive metals and alloys and/or electrically conductive polymeric materials. The conductive rollers **156** are secured on their respective axles **154** with a fastener **174** and a washer **172**, both of which are electrically conductive. Specifically, the washer **172** is sized such that the washer is in direct contact with the conductive roller **156** and/or the spacer **158** when the conductive roller **156** is secured on the conductor truck **146** with screw **147**.

[0031] As noted hereinabove, the conductor truck **146** is attached to the carriage body **140**. Specifically, the carriage body **140** comprises a cutout feature **176** formed in an upper portion of the carriage body **140**. The conductor truck **146** is positioned in the cutout feature **176** with a biasing member **168**, such as a compression spring or another suitable biasing member, positioned between the conductor truck **146** and the carriage body **140**. The conductor truck **146** is secured to the carriage body **140** with a fastener **150** which extends through the conductor truck **146** and the biasing member **168** and into the carriage body **140**. The fastener prevents the lateral movement of the conductor truck **146** with respect to the carriage body. When the conductor truck **146** is installed in the cutout feature **176** and secured with fastener **150** the biasing member **168** bias the conductor truck **146** and the conductive rollers **156** upwards (i.e., in the z-direction in the coordinate axes depicted in FIG. 3B) and away from the carriage body **140**. Accordingly, it should be understood that, when the carriage **106** is installed in the rail **102** (FIG. 2), the biasing member **168** biases the conductive rollers **156** into rolling engagement with the conductors **114a**, **114b** (FIG. 2) positioned on an upper portion of the rail **102**.

[0032] Referring to FIGS. 2 and 3A-3B, the carriage **106** further comprises a power lead **148** electrically coupled to the conductive rollers **156**. Specifically, the power lead **148** comprises a plurality of electrical conductors (i.e., wires) which are coupled to an interface connector **149** on one end and the conductive rollers **156** on the opposite end. The electrical connection with the conductive rollers **156** is facilitated by eye connectors **178**, or similar electrical connectors, which are in electrical contact with the fastener **174** and/or washer **172**. Specifically, the fastener **174** is inserted through the eye connector **178** such that the eye connector **178** is positioned between the fastener **174** and the washer **172**. The power lead **148** conducts current from the conductive rollers **156** to the lift unit **104**, as will be described in more detail herein.

[0033] Referring now to FIGS. 1 and 4, in some embodiments, the carriage **106** may further comprise bumper assemblies **129** positioned on either end of the carriage body **140**. The bumper assemblies may be attached to the carriage body **140** and secured in place with the axles **120** which extend transversely through the carriage body **140**. The bumper assemblies **129** may include rubber end caps **131** which cushion the carriage **106** when the carriage **106** encounters an end stop **192** located at either end of the rail **102**. In the embodiments of the carriage **106** described herein, the bumper assemblies **129** are optional and, as such, it should be understood that the carriage **106** may be constructed without the bumper assemblies.

[0034] Referring to FIGS. 2 and 6, the lift system **100** further comprises a rail **102** in which the carriage **106** is slidably disposed for relative movement to the rail **102**. Accordingly, it should be understood that, when the lift unit **104** is mechanically coupled to the carriage **106**, the lift unit

may be traversed along the rail with the carriage **106**. In the embodiment of the rail **102** shown in FIG. 6, the rail **102** is generally formed from a metallic material, such as aluminum, an aluminum alloy, or a similar metallic material, and generally comprises an upper portion **130**, a first sidewall **132a** integrally formed with the upper portion **130**, and a second sidewall **132b** integrally formed with the upper portion **130**. The upper portion **130**, first sidewall **132a** and second sidewall **132b** are oriented such that the upper portion **130**, first sidewall **132a** and second sidewall **132b** form a carriage support channel **135** in which the carriage **106** is slidably disposed. To that end, the first sidewall **132a** further comprises a first support flange **134a** which extends from the first sidewall **132a** into the support channel **135** and the second sidewall **132b** further comprises a second support flange **134b** which extends from the second sidewall **132b** into the support channel **135**. In the embodiments described herein, the first support flange **134a** and the second support flange **134b** are generally opposed to one another and lie in a common horizontal plane (i.e., the x-y plane in the coordinate axes shown in FIG. 6). The first support flange **134a** and the second support flange **134b** may also be substantially parallel with the upper portion **130** of the rail **102**. However, it should be understood that other configurations of the support flanges and the upper portion of the rail are also contemplated. For example, in an alternative embodiment, the support flanges may be upwardly angled with respect to the horizontal plane. Moreover, it should be understood that the structure of the rail **102** depicted in FIGS. 2 and 6 is exemplary and that other rail configurations are contemplated.

[0035] Still referring to FIGS. 2 and 6, the lift system **100** further comprises a pair of conductors **114a**, **114b** positioned in the support channel **135** on the upper portion **130** of the rail **102**. When the carriage **106** is installed in the rail **102**, the conductive rollers **156** of the carriage are biased into rolling engagement with the conductors **114a**, **114b** such that current passing through the conductors **114a**, **114b** is communicated to the conductive rollers **156** and, in turn, to the power lead **148**. The conductors **114a**, **114b** may be formed from various conductive materials.

[0036] For example, referring now to FIGS. 6 and 7, one embodiment of a conductor **114** for use in the rail **102** of the lift system **100** is schematically depicted in cross section. In this embodiment, the conductor **114** is a flexible conductive tape which generally comprises an insulating layer **253**, a primary conductive layer **252**, and a protective layer **251**. The layers are ordered such that the primary conductive layer **252** is positioned between the insulating layer **253** and the protective layer **251**. When the conductor **114** is positioned in the upper portion **130** of the rail **102**, as described above, the insulating layer **253** is positioned closest to the upper portion of the rail **102** while the protective layer **251** is furthest from the upper portion of the rail.

[0037] In one embodiment, the insulating layer **253** is formed from an electrically insulating material, such as an insulating polymeric material, which also functions to adhesively bond the conductor **114** to the upper portion of the rail **102**. For example, the insulating polymeric material may be polyethylene terephthalate (PET) or a similar polymeric material. The insulating layer **253** may generally have a thickness of less than about 100 μm . For example, in one embodiment, the PET has a thickness of about 50 μm . The insulating layer **253** prevents current conducted through the primary conductive layer **252** from being conducted to the rail **102**

when the conductor is positioned on the upper portion of the rail 102. The insulating layer may be adhesively bonded to the rail with an adhesive material. For example, in one embodiment, the insulating layer 253 is bonded to the upper portion of the rail 102 with a double-sided adhesive tape, such as, for example, 9495 LE adhesive tape manufactured by 3M.

[0038] The primary conductive layer 252 is formed from an electrically conductive material such as copper or a copper alloy. For example, in one embodiment, the electrically conductive tape is formed from E-Cu58 copper alloy. However, it should be understood that the primary conductive layer 252 may be formed from other conductive materials including, without limitation, other elemental metallic materials and/or alloys thereof. The primary conductive layer 252 may generally have a thickness of less than about 100 μm . For example, in one embodiment, the primary conductive layer 252 has a thickness of about 50 μm . In one embodiment, the primary conductive layer 252 comprises multiple layers of conductive material, such as when the primary conductive layer 252 is constructed of two or more layers of conductive material such as copper or a copper alloy. The primary conductive layer 252 may be bonded to the insulating layer 253 with an adhesive material. For example, in one embodiment, the primary conductive layer 252 is adhesively bonded to an insulating layer 253 with a double-sided adhesive tape such as, for example 55256 double-sided adhesive tape manufactured by 3M.

[0039] The protective layer 251 is formed from a polymeric material. For example, the polymeric material may be a polyester, such as a polyester fabric. Alternatively, the polymeric material may be a polymeric film. In one embodiment, the protective layer is a polyester fabric coated with a conductive material such as, for example, CN-3190 conductive fabric tape manufactured by 3M which is coated on one side with an electrically conductive acrylic adhesive. The protective layer 251 may generally have a thickness of less than about 200 μm . For example, in one embodiment, the protective layer has a thickness of less than about 180 μm . When the conductor 114 is positioned on the upper portion of the rail 102, the conductor 114 is oriented such that the conductive rollers of the carriage are in rolling engagement with the protective layer 251, thereby enabling current flowing through the primary conductive layer 252 to pass through the protective layer 251 to the conductive rollers. While the protective layer 251 facilitates passing current from the primary conductive layer 252 to the conductive rollers, the protective layer also protects the primary conductive layer 252 from wear and/or corrosion. For example, the protective layer 251 provides a barrier between the primary conductive layer 252 and the outside environment. Moreover, the protective layer 251 mitigates wear and/or other mechanical damage as the conductive rollers of the carriage are rolled along the conductor 114.

[0040] Referring again to FIG. 2, the lift system 100 further comprises a connector card 160 which couples the conductors 114a, 114b to a power source, such as an electrical outlet. The connector card 160 generally comprises a plurality of spring contacts 162 which engage with the conductors 114a, 114b when the connector card 160 is installed in the rail 102. The connector card 160 further comprises a power port 164 which is electrically coupled to the spring contacts 162. The power port 164 is configured to receive an adapter plug 163, which, in turn, may be coupled to a power source (not shown) for providing current to the connector card 160 and the conductors 114a, 114b.

[0041] In the embodiments described herein, the connector card 160 may be mechanically coupled to an adapter 190 to facilitate positioning the connector card 160 in the support channel of the rail 102. In some embodiments, the adapter 190 may further comprise an end stop 192 which provides cushioning to the adapter 190 and connector card 160 when the adapter is contacted by the carriage 106.

[0042] The construction of the rail-mounted lift system 100 will now be described with specific reference to the exploded view of the lift system 100 shown in FIG. 2 and the cross section of the assembled lift system 100 shown in FIG. 8. The conductors 114a, 114b are adhesively attached to the upper portion 130 of the rail 102 such that the conductors 114a, 114b extend along the length of the rail 102. An insulating pad 180 may be positioned between the conductors 114a, 114b and the upper portion 130 of the rail proximate the end of the rail 102.

[0043] In one embodiment, the conductors 114a, 114b may be installed in the rail 102 utilizing an applicator tool 300, as depicted in FIG. 9. The applicator tool 300 generally comprises an applicator frame assembly 310 and a spindle 302 to which a spool of wound conductor may be attached. The applicator frame assembly 310 generally includes an extension body 313, a support arm assembly 312 and a dolly portion 315. The support arm assembly 312 is mechanically coupled to the extension body 313 and supports the spindle 302 such that the spindle 302 is free to rotate in the support arm assembly 312. The dolly portion 315 is coupled to the extension body 313 with sideplates 314 (one shown in FIG. 9).

[0044] Referring to FIGS. 9-11, the dolly portion 315 of the applicator tool 300 generally includes a contact roller mechanism 330 for impinging the conductor against the rail and a tensioning mechanism 320 for tensioning the conductor as it is paid-out from the spindle 302. The dolly portion 315 further comprises a dolly portion shoe 328 and a normalizing plate 326 which work in conjunction with one another to guide the conductor through the applicator tool 300 and into the tensioning mechanism 320. A lanyard 318 may be attached to the dolly portion 315 to assist in traversing the applicator tool 300 through the rail during application of the conductor to the rail.

[0045] The tensioning mechanism of the dolly portion 315 includes a pair of flange engagement wheels 322a, 322b positioned to engage the support flanges 134a, 134b of the rail 102 and thereby guide the applicator tool 300 in the rail 102. Similarly, the contact roller mechanism 330 contains a pair of contact wheels 332a, 332b positioned to engage the upper portion 130 of the rail 102 and thereby guide the applicator tool 300 in the rail 102 while simultaneously laminating the conductor to the rail 102, as will be described further herein.

[0046] Referring specifically to FIG. 11, the contact roller mechanism 330 includes a contact wheel 332 that is coupled to the applicator frame assembly 310 through a follower mechanism 336. The contact wheel 332 and the follower mechanism 336 are configured to translate inward and outward (i.e., in the +/-z-direction as shown in FIG. 11) relative to the applicator frame assembly 310. To facilitate this translation, the contact roller mechanism 330 includes a biasing member 334 that applies a force to the follower mechanism 336 and the contact wheel 332 in a direction that tends to position the contact wheel 332 and the follower mechanism

336 in a direction away from the applicator frame assembly **310**, which, in the embodiment shown in FIG. 11, is the positive z-direction.

[0047] Still referring to FIG. 11, the tensioning mechanism **320** further comprises a plurality of roller elements **340**, guide pins **341** and a pair of reversing wheels **324a**, **324b** (one shown in FIG. 11) through which the conductor laminate **113** may be wound in order to maintain tension on the conductor **114** as the conductor is applied to the rail **102**.

[0048] Referring again to FIGS. 9-11, to install the conductor in the rail **102**, a length of conductor laminate **113** (i.e., the conductor **114**, as described hereinabove, and a backing tape **115** applied to the adhesive layer) is arranged in a spool **304** and placed about the spindle **302** of the applicator tool **300**. The conductor laminate **113** is fed from the spool **304** and directed between the extension body **313** and an extension body follower **316** that is coupled to the extension body **313**. The conductor laminate **113** is passed between the applicator sideplates **314** and directed to the dolly portion **315**, as shown in greater detail in FIG. 11, where the conductor laminate **113** is introduced into the tensioning mechanism **320**. Specifically, the conductor laminate **113** first passes over a dolly portion shoe **328**, and is wound through the plurality of roller elements **340** and pins **341** that form the tensioning mechanism **320**, and directed over the reversing wheel **324**. At the reversing wheel **324**, the backing material **115** is removed from the conductor **114**, thereby exposing the adhesive layer of the conductor **114**. With the adhesive layer of the conductor **114** exposed, the conductor **114** may be directed over the reversing wheel **324**, over the normalizing plate **326**, and beneath a contact wheel **332** of the contact roller mechanism **330**. As is depicted in FIG. 11, as the conductor laminate **113** passes through the tensioning mechanism **320**, any twisting, for example, due to winding the conductor laminate **113** about the spindle **302**, is minimized, such that the conductor laminate **113** will generally lie flat when being applied to the rail **102**.

[0049] Referring now to FIGS. 10 and 11, once the conductor laminate **113** is loaded into the applicator tool **300**, the applicator tool **300** is positioned in the rail **102** such that the flange engagement wheels **322a**, **322b** engage the support flanges **134a**, **134b** of the rail **102** and the contact wheels **332a**, **332b** engage the upper portion **130** of the rail **102**. With the applicator tool **300** in this position, the contact wheel **332b** impinges the conductor **114** against the upper portion **130** of the rail **102** thereby laminating the conductor **114** to the rail. Thereafter, the applicator tool **300** is translated along a length of the rail **102** by a user. As the applicator tool **300** is translated along the rail **102**, additional conductor is paid out from the spindle **302**, passes through the applicator tool **300**, and below the contact roller mechanism **330** such that the conductor **114** is applied to the length of the rail. As the applicator tool passes through the rail, the biasing member **334** applies pressure through the contact wheel **332** to the conductor **114** as the applicator tool **300** is translated forward along the rail **102**. The pressure exerted by the contact wheel **332** secures the conductor **114** to the rail **102** by pressing the adhesive layer of the conductor **114** against the upper portion of the rail **102**. A user may grasp the lanyard **318** coupled to the applicator frame assembly **310** to translate the applicator tool **300** along the rail **102**. Two conductors **114** (i.e., the first conductor **114a** and the second conductor **114b**, as depicted in FIGS. 6 and 8) may be applied to the rail by first translating the applicator tool **300** along the rail **102** from a first end to a

second end, then rotating the applicator tool **300** within the rail **102** as to translate the applicator tool **300** from the second end to the first end of the rail **102**. Thus, the applicator tool **300** can place the first conductor **114a** and the second conductor **114b** such that they are approximately evenly spaced in a lateral direction across the rail **102**.

[0050] Referring again to FIGS. 2 and 8, after the conductors **114a**, **114b** are installed in the rail, the carriage **106** is installed on the lift unit **104** by inserting the connection rail **118** into the corresponding receiving slot **142** of the carriage **106** and securing the carriage **106** on the connection rail **118** with fastener **119**. The lift unit **104** with attached carriage **106** is then suspended from the rail **102** by positioning the carriage **106** in the rail **102** such that the support wheels **144a**, **144b** are slidably engaged with the first support flange **134a** and the second support flange **134b**, respectively. With the carriage **106** in this position, the biasing member **168** biases the conductor truck **146** and the conductive roller **156** upwards (i.e., in the z-direction of the coordinate axes shown in FIG. 8) and away from the carriage body **140** such that the conductive rollers are in rolling engagement with and electrically coupled to the conductors **114a**, **114b**, as depicted in FIG. 8. The power lead **148** is also electrically coupled to the battery and/or motor of the lift unit **104**.

[0051] Thereafter, the connector card **160** and adapter **190** are inserted into rail **102** such that the spring contacts **162** positioned on the connector card are engaged with the conductors **114a**, **114b**. The connector card **160** and adapter **190** are secured in the rail **102** with fastener **121**, such as a bolt and nut, and the adapter plug **163** is inserted in the power port **164** thereby providing power to the lift system **100**.

[0052] Referring now to FIGS. 1, 2 and 5, the lift unit **104** may be traversed over the rail **102** with the carriage **106**. As the lift unit **104** is traversed over the rail **102**, current provided to the conductors **114** through connector card **160** is communicated to the conductive rollers **156** which are in rolling engagement with the conductors **114**. The current passes from the conductors **114** through the power lead **148** to the lift unit **104** thereby providing power to charge the battery **132** and/or operate the motor **133**. For example, in embodiments where the lift unit **104** includes a battery **132**, as shown in FIG. 5, the current from the power lead charges the battery and may also power the motor. In these embodiments, the motor **133** may be actuated with either current from the battery **132** or current supplied directly from the power lead **148**. Alternatively, in embodiments (not shown) where the lift unit **104** does not include a battery **132**, the current supplied to the lift unit **104** with the power lead **148** directly powers the motor **133**.

[0053] Moreover, because the conductors **114a**, **114b** extend along the entire length of the rail **102** and the conductive rollers **156** are in rolling engagement with the conductors **114a**, **114b** as the lift unit **104** is traversed over the length of the rail **102**, it should be understood that power is continuously provided to the lift unit irrespective of the position of the lift unit **104** relative to the rail **102** (i.e., power is provided to the lift unit at every point along the length of the rail).

[0054] In the embodiments described herein and shown in the figures, the lift system **100** is constructed with the carriage **106**, conductors **114a**, **114b**, and connector card **160** to facilitate charging and/or providing power to the lift unit **104** at any point along the length of the rail **102**. However, it is also contemplated that certain components of the lift system **100** may be separately provided as a kit of parts which may be

used to retro fit lift systems which do not have continuous charging capabilities. For example, in one embodiment, a kit of parts for retrofitting a rail-mounted lift system for continuous charging of a lift unit along a length of a rail may include a conductor and a carriage which are packaged together. In one embodiment, the conductor is a flexible conductive tape as depicted in FIG. 7 and described hereinabove, although it should be understood that other conductors suitable for use in a rail-mounted lift system may be included in the kit of parts. In one embodiment, the carriage may include a carriage body, at least one support wheel rotatably coupled to the carriage body, and a conductor truck, as described hereinabove and depicted in FIGS. 3A and 3B. In this embodiment, the conductor truck includes at least one conductive roller rotatably attached to the conductor truck and the conductor truck is mounted to the carriage body with a biasing mechanism for upwardly biasing the at least one conductive roller away from the carriage body, as described above.

[0055] In another embodiment, the kit of parts may further comprise a connector card for electrically coupling the conductor and the carriage to a power source. In this embodiment, the kit of parts may optionally include an adapter for positioning the conductor card in the rail of a lift system and an end stop. The kit of parts may also optionally include a plug adapter and the corresponding power supply for electrically coupling the connector card to line voltage.

[0056] As noted above, the kit of parts may be used to retrofit and convert an existing rail-mounted lift system to a rail-mounted lift system with continuous charging capabilities. The various parts of the kit of parts may be installed in the rail of the existing lift system as described herein above thereby converting the existing lift system to a continuous charging system.

[0057] Based on the foregoing, it should now be understood that the embodiments shown and described herein relate to a rail-mounted lift system for lifting and supporting patients. The lift system includes a lift unit which is supplied with current along the entire length of the rail to which the lift unit is attached. The current supplied to the lift system may be used to either directly power a motor of the lift unit and/or charge a battery of the lift unit at any point along the length of the rail. In this manner, the lift unit can be powered by the line current or, when the line current is discontinued such as during a power failure, the lift unit can be powered by the battery.

[0058] In some embodiments, the rail-mounted lift system includes conductors formed from a flexible conductive tape having a primary conductive layer disposed between an insulating adhesive layer and a protective layer. The insulating adhesive layer facilitates installation of the conductor on a rail without modifying the rail. Moreover, the protective layer encapsulates the primary conductive layer thereby preventing degradation of the primary conductive layer due to exposure to environmental conditions and permitting the conductor to be used in lift systems installed in humid environments (i.e., over therapy pools and the like). Further, the protective layer also mitigates wear on the primary conductive layer as the conductive rollers of the carriage are brought into rolling engagement with the conductor.

[0059] Also described herein is a kit of parts for retrofitting and converting an existing rail-mounted lift system to a rail-mounted lift system in which the lift unit can be continuously charged and/or powered along the entire length of the rail, as described herein.

[0060] It is noted that the terms “substantially” and “about” may be utilized herein to represent the inherent degree of uncertainty that may be attributed to any quantitative comparison, value, measurement, or other representation. These terms are also utilized herein to represent the degree by which a quantitative representation may vary from a stated reference without resulting in a change in the basic function of the subject matter at issue.

[0061] While particular embodiments have been illustrated and described herein, it should be understood that various other changes and modifications may be made without departing from the spirit and scope of the claimed subject matter. Moreover, although various aspects of the claimed subject matter have been described herein, such aspects need not be utilized in combination. It is therefore intended that the appended claims cover all such changes and modifications that are within the scope of the claimed subject matter.

What is claimed is:

1. A rail-mounted lift system comprising:

- a rail comprising at least one conductor positioned in a carriage support channel formed in the rail;
- a carriage slidably disposed in the rail for relative movement to the rail, the carriage comprising at least one conductive roller rotatably attached to the carriage, wherein the at least one conductive roller is upwardly biased into rolling engagement with the at least one conductor; and
- a lift unit coupled to the carriage, the lift unit comprising a motor paying out and taking up a lifting strap, wherein the lift unit is electrically coupled to the at least one conductive roller.

2. The rail-mounted lift system of claim 1, wherein the at least one conductive roller is rotatably attached to a conductor truck and the conductor truck is mounted in the carriage with a biasing member upwardly biasing the conductor truck away from the carriage.

3. The rail-mounted lift system of claim 1, wherein the at least one conductor is a conductive tape comprising a primary conductive layer positioned between an insulating layer and a protective layer.

4. The rail-mounted lift system of claim 3, wherein the primary conductive layer comprises multiple layers of conductive material.

5. The rail-mounted lift system of claim 3, wherein the protective layer is a polymeric material.

6. The rail-mounted lift system of claim 3, wherein the protective layer is a polyester fabric.

7. The rail-mounted lift system of claim 3, wherein the primary conductive layer is a copper alloy.

8. The rail-mounted lift system of claim 3, wherein the insulating layer is PET.

9. The rail-mounted lift system of claim 1, wherein the at least one conductive roller is electrically coupled to at least one of a battery of the lift unit and the motor of the lift unit.

10. A rail-mounted lift system comprising:

- a rail comprising at least one conductor positioned on an upper portion of the rail, a first support flange, and a second support flange;
- a carriage slidably disposed in the rail for relative movement to the rail, the carriage comprising:
 - a carriage body;
 - at least one pair of support wheels rotatably coupled to the carriage body, the at least one pair of support

- wheels slidably engaged with the first support flange and the second support flange;
- a conductor truck comprising at least one conductive roller rotatably attached to the conductor truck, wherein the conductor truck is mounted to the carriage body with a biasing member upwardly biasing the at least one conductive roller into rolling engagement with the at least one conductor; and
- a lift unit coupled to the carriage body, the lift unit comprising a motor paying out and taking up a lifting strap, wherein the lift unit is electrically coupled to the at least one conductive roller.
11. The rail-mounted lift system of claim 10, wherein the lift unit further comprises a battery electrically coupled to the motor and the at least one conductive roller.
12. The rail-mounted lift system of claim 10, wherein: the carriage body comprises a receiving slot; and the lift unit comprises a connection rail, wherein the connection rail of the lift unit is slidably received in the receiving slot to couple the lift unit to the carriage body.
13. The rail-mounted lift system of claim 10, wherein the at least one conductor is a conductive tape comprising a primary conductive layer positioned between an insulating layer and a protective layer and the insulating layer is adhesively bonded to the upper portion of the rail.
14. The rail-mounted lift system of claim 13, wherein the primary conductive layer comprises multiple layers of conductive material.
15. The rail-mounted lift system of claim 13, wherein the protective layer is a polymeric material.
16. The rail-mounted lift system of claim 15, wherein the protective layer is a polyester fabric.
17. The rail-mounted lift system of claim 13, wherein the primary conductive layer is a copper alloy.
18. The rail-mounted lift system of claim 13, wherein the insulating layer is PET.
19. The rail-mounted lift system of claim 10, further comprising a connector card positioned in an end of the rail, the connector card electrically coupling the at least one conductor to a power supply.
20. The rail-mounted lift system of claim 10, wherein the rail comprises a first sidewall integrally formed with the upper portion, and a second sidewall integrally formed with the upper portion and opposed to the first sidewall, the first sidewall, the second sidewall and the upper portion defining a carriage support channel, wherein:
- the first support flange extends into the carriage support channel from the first sidewall;
 - the second support flange extends into the carriage support channel from the second sidewall; and

the at least one conductor is positioned in the carriage support channel and adhesively coupled to the upper portion of the rail.

21. The rail-mounted lift system of claim 10, wherein the carriage comprises a first end bumper attached to a first end of the carriage and a second end bumper attached to a second end of the carriage.

22. The rail-mounted lift system of claim 10, wherein: the carriage comprises a cutout feature formed in an upper portion of the carriage and the conductor truck is positioned in the cutout feature and secured to the carriage with a fastener, wherein the fastener prevents lateral movement of the conductor truck with respect to the carriage body; and

the biasing member is a compression spring positioned around the fastener between the conductor truck and the carriage such that the biasing member biases the conductor truck upwards, out of the cutout feature.

23. A kit of parts for retrofitting an overhead rail for continuously charging a lift unit along a length of a rail, the kit of parts comprising:

- a conductive tape; and

- a carriage comprising:

- a carriage body;

- at least one pair of support wheels rotatably coupled to the carriage body;

- at least one conductive roller rotatably attached to the carriage, wherein the conductive tape and the carriage are packaged together and the at least one conductive roller is upwardly biased into rolling engagement with the conductive tape when the conductive tape and the carriage are installed in the rail.

24. The kit of parts of claim 23, wherein the at least one conductive roller is rotatably attached to a conductor truck and the conductor truck is mounted in the carriage body with a biasing member upwardly biasing the conductor truck away from the carriage body.

25. The kit of parts of claim 23, further comprising a connector card for electrically coupling the conductive tape to a power source, wherein the conductive tape, the carriage and the connector card are packaged together.

26. The kit of parts of claim 25, further comprising a plug adapter and a power supply for electrically coupling the connector card to line voltage.

27. The kit of parts of claim 23, wherein the conductive tape comprises a primary conductive layer positioned between an insulating layer and a protective layer.

28. The kit of parts of claim 27, wherein the protective layer is a polyester fabric, the primary conductive layer is a copper alloy, and the insulating layer is PET.

* * * * *