

Electronic Acknowledgement Receipt

EFS ID:	15266916
Application Number:	13841141
International Application Number:	
Confirmation Number:	6565
Title of Invention:	ENHANCED OPTICAL AND PERCEPTUAL DIGITAL EYEWEAR
First Named Inventor/Applicant Name:	Scott W. LEWIS
Customer Number:	29141
Filer:	Joseph A. Sawyer/Sherry Long
Filer Authorized By:	Joseph A. Sawyer
Attorney Docket Number:	5266P
Receipt Date:	15-MAR-2013
Filing Date:	
Time Stamp:	18:42:52
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	Deposit Account
Payment was successfully received in RAM	\$3643
RAM confirmation Number	22415
Deposit Account	022120
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Charge any Additional Fees required under 37 C.F.R. Section 1.16 (National application filing, search, and examination fees)

File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1		5266P_Application.pdf	102747	yes	35
			c6423c88077e0478a5e92e8809f655f64522c76d		
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	29	
	Claims		30	34	
	Abstract		35	35	
Warnings:					
Information:					
2	Drawings-only black and white line drawings	5266P_Drawings.pdf	881822	no	28
			a8e45eb7a04a1c1d0268cf7c02fdc611953ba7f6		
Warnings:					
Information:					
3	TrackOne Request	5266P_TrackIRequest.pdf	183292	no	2
			b31c25d92e94311f68fc49dab929c7019bca b595		
Warnings:					
Information:					
4	Power of Attorney	5266P_POA.pdf	920634	no	2
			13a95e4d3171c6a52540f30c3ce185edb45f6a77		
Warnings:					
Information:					
5	Oath or Declaration filed	5266P_DeclarationandAssignm entEXECUTED.PDF	1025696	no	2
			6698b742ba662a4fc099126ca4d439cacd990bde		
Warnings:					
Information:					
6	Application Data Sheet	5266P_ADS.pdf	50486	no	6
			795f2e4ec66a516741f31b8d99a5af9b1cc8d8d4		
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					

7	Fee Worksheet (SB06)	fee-info.pdf	43272 d04505ce3f03006dbc4613decac6a2ffc7356530	no	2
Warnings:					
Information:					
Total Files Size (in bytes):				3207949	
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					

ENHANCED OPTICAL AND PERCEPTUAL DIGITAL EYEWEAR

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is a continuation-in-part and claims the benefit of priority to U.S. Patent Application No. 13/739,929, filed on January 11, 2013, entitled "DIGITAL EYEWEAR", which is a continuation application of U.S. Patent Application No. 13/078,589, filed on April 1, 2011, entitled "DIGITAL EYEWEAR", now U.S. Patent No. 8,353,594, issued on January 15, 2013, which is a continuation application of U.S. Patent Application No. 12/621,423, filed on November 18, 2009, entitled "DIGITAL EYEWEAR", now U.S. Patent No. 7,918,556, issued on April 5, 2011, which is a continuation application of U.S. Patent Application No. 12/029,068, filed February 11, 2008, entitled "DIGITAL EYEWEAR", now U.S. Patent No. 7,758,185, issued on July 20, 2010, which is a divisional application of U.S. Patent Application No. 11/245,756, filed October 7, 2005, entitled "DIGITAL EYEWEAR", all of which are incorporated herein by reference.

[0002] This application is related to U.S. Patent Application No. _____ (Docket No. 5087P), filed on March 15, 2013, entitled "ENHANCED OPTICAL AND PERCEPTUAL DIGITAL EYEWEAR", which is also incorporated herein by reference.

FIELD OF THE INVENTION

[0003] The present invention relates generally to wearable optics and more particularly to wearable optics that includes additional functionality.

BACKGROUND OF THE INVENTION

[0004] Wearable optics is utilized for a variety of purposes. Wearable optics is used for improving one's vision for reading glasses and to protect one's vision. Oftentimes protective goggles are used to protect eyes within dangerous areas. It is desirable to add additional functionality to glasses. This functionality can include a variety of forms, which are electronic, mechanical, aesthetic, etc. Accordingly, it is always desired to provide additional functionality to wearable optics. What is desired is a system and method which will increase the functionality of glasses beyond their normal use while still maintaining them for their primary uses. The present invention addresses such a need.

SUMMARY OF THE INVENTION

[0005] A wearable optics device and method of use is disclosed. In a first aspect a method comprises utilizing dynamic eye tracking with a wearable optics device; wherein parameters personalized to a user can be provided based upon the dynamic eye tracking.

[0006] In a second aspect, a wearable optics device comprises a lens and a dynamic eye tracking mechanism in communication with the lens. Parameters personalized to a user can be provided based upon the dynamic eye tracking.

[0007] In a third aspect, a method comprises utilizing dynamic eye tracking with a wearable optics device. A perceptual optimization is utilized based upon the dynamic eye tracking.

[0008] In a fourth aspect, a wearable optics device comprises a lens and a dynamic eye tracking mechanism in communication with the lens. A perceptual optimization is utilized based upon the dynamic eye tracking.

[0009] In a fifth aspect, a method comprises utilizing dynamic eye tracking with a wearable optics device. An augmented reality overlay is utilized based upon the dynamic eye tracking.

[0010] In a six aspect, a wearable optics device comprises a lens; and a dynamic eye tracking mechanism in communication with the lens. An augmented reality overlay is utilized based upon the dynamic eye tracking.

[0011] In a seventh aspect, a method comprises utilizing dynamic eye tracking with a wearable optics device. Augmented reality navigation is utilized based upon the dynamic eye tracking.

[0012] In an eighth aspect, a wearable optics device comprises a lens; and a dynamic eye tracking mechanism in communication with the lens. Augmented reality navigation is utilized based upon the dynamic eye tracking.

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] Figure 1 is a diagram that illustrates Media focals.

[0014] Figure 2 comprises an information bar on media focal wearable optics.

[0015] Figure 3 is a block diagram of wearable optics that is utilized in a music environment such as an MP3 player.

[0016] Figure 4 is a block diagram that illustrates wearable optics that is utilized as a cell phone.

[0017] Figure 5A is a block diagram that illustrates the cellular phone circuitry of Figure 4.

[0018] Figure 5B illustrates perceptual optimization utilizing optical and perceptual parameters.

[0019] Figure 5C illustrates the enhanced digital eyewear architecture.

[0020] Figure 6 illustrates the parts of an eye that may be utilized with the eye tracking mechanism of an embodiment.

[0021] Figure 7 illustrates a social networking application utilized with the wearable optics device.

[0022] Figure 8 illustrates a messaging application utilized with wearable optics device in accordance with an embodiment.

[0023] Figure 9 illustrates the wearable optics device utilized by an athletic sports spectator in accordance with an embodiment.

[0024] Figure 10 illustrates the wearable optics device utilized by an athletic sports player in accordance with an embodiment.

[0025] Figure 11 illustrates an augmented reality information, navigation, and advertising application utilized with the wearable optics device.

[0026] Figure 12 illustrates an augmented reality information patient data application utilized with the wearable optics device used in conjunction with a remote device.

[0027] Figure 13 illustrates a shading control application utilized with the wearable optics device.

[0028] Figure 14 illustrates an augmented reality application utilized with the wearable optics device.

[0029] Figure 15 illustrates a physical gaming application utilized with the wearable optics device.

[0030] Figure 16 illustrates a first embodiment of an online/mobile gaming application utilized with the wearable optics device.

[0031] Figure 17 illustrates a second embodiment of an online/mobile gaming application utilized with the wearable optics device.

[0032] Figure 18 illustrates shading control utilizing the wearable optics device.

[0033] Figure 19 illustrates an optical/perceptual operating system with the wearable optics device.

[0034] Figure 20 describes an embodiment of the digital architecture of the wearable optics device.

[0035] Figure 21 illustrates the embodiment of a system simulator for use by developers of applications and new lenses or expansion of the wearable optics device.

[0036] Figure 22A thru Figure 22F illustrate the embodiment of inverse shading using the wearable optics device.

[0037] Figure 23 illustrates an embodiment of eye tracking illumination and enhanced efficiency utilizing the wearable optics device.

[0038] Figure 24 illustrates an embodiment of real-time augmented reality overlay utilizing the wearable optics device.

DETAILED DESCRIPTION

[0039] The present invention relates generally to wearable optics and more particularly to wearable optics that includes additional functionality. The following

description is presented to enable one of ordinary skill in the art to make and use the invention and is provided in the context of a patent application and its requirements. Various modifications to the preferred embodiments and the generic principles and features described herein will be readily apparent to those skilled in the art. Thus, the present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features described herein.

[0040] A system and method in accordance with the present invention is directed to a variety of ways to enhance the use of wearable optics devices.

[0041] To describe the features of the present invention in more detail refer now to the following description in conjunction with the accompanying figures.

1. Media focals 100

[0042] Figure 1 is a diagram that illustrates Media focals 100. Media focals 100 comprises an information bar 102, receiver 104, digital circuitry 106, frames 108 and lens 110. Media focals 100 allow for enhancing the wearable optics for its primary purpose, for example, a digital camera could be placed within the wearable optics to allow for seeing certain of these images. For example, the circuitry 106 for the media focals 100 could be placed within the frame 108 of the wearable optics. The lens 110 could have a totally reflective surface, or a partially reflective surface using LCDs or the like. In effect the wearable optics could look like see-through glasses, but through the use of the circuitry 106 within the wearable optics it is actually a media focal. Additionally, the wearable optics could incorporate a camera to project the user onto a second lens to achieve a see-through effect.

[0043] In a preferred embodiment, an information bar 102 is provided across a portion of the wearable optics which is visible to the user. This information bar 102 is used to convey a variety of types of information.

[0044] Figure 2 comprises an information bar 102' on media focal wearable optics. The information bar 102' can be a stock ticker scrolling across the top portion of the wearable optics, as is shown in Figure 2. Although the information bar 102' is shown displaying a stock ticker, other kinds of information such as song titles, lyrics and the like could be displayed in the information bar. This information bar is referred to as E-focals. This information might be provided from a digital receiver through an FM station, through a cellular wireless device, or an MP3 player. Additional functionality of the E-focal will be described with more detail with respect to the cell phone enhancements as well as the music player enhancements.

[0045] One of the key features of the media focals 100 is the use of the media focals to enhance the primary function of the user, that is, being able to more accurately and clearly see the objects. In such an environment, for example, it is possible to have a zoom feature circuit to allow for the use of the wearable optics as binoculars. This would allow for the user to see objects more closely based on certain activities of the user. For example, there may be eye or pressure sensors on the wearable optics that will activate the binocular circuitry in the glasses which could receive visual data through a camera, CCD receiver of the like.

[0046] In the preferred embodiment, the circuitry 106 would be located somewhere in the frame of the glasses to provide this functionality and as circuits became smaller and devices became smaller it would be easier and easier to embed the circuitry that is

well known for use for such functions directly within the device. The circuitry 106 in the device could be, for example, eye sensors which could be pressure sensors, capacitive sensors or some other type of sensor for allowing the eyes to direct the activities. Eye movement sensors, for example, could be used to activate and control the binocular glasses. Similarly, a digital camera could be put on the glasses that would allow the same kinds of technology to take pictures by the person directly.

[0047] In a similar vein, the glasses could be used as a normal corrective lens glass utilizing the digital imagery, so that, for example, a user has a certain prescription that they use with their normal prescription glasses to view an object clearly. As the user's eyes change, it would be possible that an optometrist could download the new prescription to the wearable optics such that a digital transformation of the image information is provided which is compatible with the new prescription.

[0048] Also, in a preferred embodiment a method for sensing and controlling the digital media could be implemented in a variety of ways. For example, an activity of the eye itself would control the activity of the media focal. So, for example, if the idea was to zoom the image, the eye would blink twice. It would also be possible to detect facial and eye movements (squinting, for example), as well as changes in the pupil and iris.

[0049] In a further embodiment, it would be possible for the eyeglasses in accordance with the present invention to function within a client/server model or Bluetooth (Wi-Fi) model. Utilization of the client/server model and Bluetooth Wi-Fi would make possible, for example, the display of live news or special reports (such as financial reports) from the Internet or similar sources on the eyeglasses. This would

also allow for portions of circuitry to be located remotely such that less circuitry in the wearable optics is required.

[0050] The wearable optics could also include a logo, for example, law enforcement officers could have their glasses emblazoned with "Police", "Sheriff", "MP", etc.; young people could have their eyeglasses emblazoned with words and images that reflected their favorite performers, etc.; sports teams could offer the eyeglasses at discount with team monograms, etc. They could also be purchased by companies, emblazoned with the company logos, and given out as retirement gifts, etc.

2. Music Environment

[0051] Figure 3 is a block diagram of wearable optics 300 that is utilized in a music environment such as an MP3 player. Figure 3 comprises wearable optics 300, an information bar 302, MP3 player circuitry 304, storage 306, frames 308, and one or a plurality of lenses 310. Another environment as has been above described is the music environment. What would be desirable would be to provide music glasses in which an MP3 player on an iPod or the like is incorporated in the wearable optics, either in a wired or wireless environment. Through the use of this type of system, a plurality of users could be networked via an MP3 player type environment within a hotspot, or the like, which would allow one to have downloads of whatever music is required through the eyeglasses. The system could allow for downloadable music which could be selected via scrolling and the like through voice recognition systems.

[0052] By connecting to a client-server network or Bluetooth Wi-Fi installation, for example, the eyeglasses could link to a multimedia network, authorize downloading and

billing for selected music. By this means, access to a plurality of libraries for music selections could be provided.

[0053] It would also be possible to provide access to streaming audio media. Also, access can be provided to multimedia libraries, etc., via the client/server model.

[0054] Information could be received via a digital client/server model enabled to work with iPods or MP3 players. Similarly, bluetooth wireless technology could be utilized to provide access to music and live audio sources.

[0055] The wearable optics could also be utilized in conjunction with wireless technology to allow a user or a plurality of users to participate simultaneously in single or group karaoke singing. The wearable optics could be used specifically to display the lyrics of a song, melody, notes, name of the song or other associated references.

[0056] It would also be possible to receive and listen to AM or FM radio signals, via an AM/FM radio tuner connected to the wearable optics hardware.

[0057] In this type of environment, the headphones can be either digital or analog. The user doesn't need to have 10,000 songs, for example. They can come enrolled in an in-song virtual network library upon entering a hotspot. Therefore, the local storage 306 could be limited. In addition, this would provide location identity information for one who is using the network. The songs can be streamed as well as downloaded. The songs could be purchase using the wearable optics. The system could be scalable; depending upon what kind of device was being used.

3. Telecommunications Environment

[0058] Figure 4 is a block diagram that illustrates wearable optics that is utilized as a cell phone 400. Figure 4 comprises cellular phone circuitry 402, a microphone 104, frames 408 and one or a plurality of lenses 410. The cell phone wearable optics 400 could be implemented utilizing digital telephone technology. Circuitry 402 within the wearable optics could be utilized to allow a telephone number or other visual information such as that provided by multimedia messaging services to be displayed on the lens 410 of the wearable optics as shown in Figure 3. Figure 5 is a block diagram that illustrates the cellular phone circuitry of Figure 4. Figure 5 comprises noise cancelling circuitry 502, voice recognition circuitry 504, caller ID circuitry 506 and speaker recognition circuitry 508 and media processing circuits 509. The telephone number could be activated via the digital circuitry 402 as part of the media focal 100. In addition, the circuitry could be made truly digital via a digital signal processor which is coupled to a camera otherwise in the environment. The above system would allow for voice recording through use of a microphone 104 and would allow for voice recognition through use of the voice recognition circuitry 504, which would allow for signal conditioning on the cell phone in a variety of ways.

[0059] The cell phone environment 402 provides a plurality of areas for improvement utilizing existing technologies. Firstly, one of the major annoyances in cell phone use is that the users have to speak in a loud manner because of background noise and the like. There are a variety of reasons for this problem including the placement of the microphone of the cell phone relative to the speaker's mouth, due to the aforementioned background noise, and other issues. By placing the microphone 104 strategically on the wearable optics such as near the nose or mouth the user will not have to speak as

loudly. The microphone could also be located in flip down microphones. In addition noise canceling circuitry 502 could be utilized to remove the background noise. The microphone capability would include the advantage of utilizing noise rejection techniques. Buttons located on the wearable optics can be utilized to control features thereon. Finally, the microphone 104 could utilize whisper technology such that the speaker will not have to speak as loudly.

[0060] The wearable optics would in a preferred embodiment include voice recognition circuitry 504 and caller ID circuitry 506. The conventionality for hearing and talking in a preferred embodiment would be located in ear and nose pad portions of glasses. Referring back to Figure 3, the electronics for the cell phone in a preferred embodiment would be within the frame 308 of the wearable optics. In addition the wearable optics would include a fully integrated information bar 302. Finally, a speaker recognition algorithm 508 as shown in Figure 5 would allow only the voice of the user to be recognized and the background noise would be cancelled. Accordingly, the unique characteristics of the speaker are provided via an audible model.

[0061] This can performed utilizing a variety of methods. For example analyzing the voice of the user and combining the analysis with noise cancellation. In another example the user can talk softly and cancel noise and a directional microphone is used which takes advantage of device location.

[0062] Similar to the media focal and MP3 player environments, a digital client/server or Bluetooth/wifi model could be adapted to link the wearable optics to external communication equipment. Such equipment could include digital cell phones, PDAs or wifi enabled PCs or other devices. Such an embodiment could enable review of

voicemail, screen viewed emails, text to speech audio email conversions, multimedia messaging services, and other data sources.

[0063] Wireless or Bluetooth interconnection could also make possible VOIP glasses to be utilized instead of a cell phone. Other features enabled by a wireless link could link the eyewear to MP3 devices, an iPod, a printer, wireless/wired TV, coupons, and the like. Also “PDA glasses” could provide built in a time display, alarm calendar, interfacing with PCs or network sources, a speaker and the like.

[0064] As can be seen from the above description, digital eyewear is a rapidly evolving field with from the early innovation of digital eyewear with eye tracking capabilities thru Lewis ('185 filed Feb 2008), to eyewear with more complex lenses and communication/display capabilities (Lewis '556, filed Nov 2009), to more enhancements and capabilities (Lewis '594, filed April 2011). As technology progresses to make sensors, cameras, processors, and circuitry smaller, more and more capabilities become possible to implement using digital eyewear. This enhanced digital eyewear can be used to solve important areas ranging from superior vision enhancement and mobile advertising, to use in dental/medical procedures and physical and Internet navigation. The application and value of the enhanced eyewear is increased even further when combined with augmented reality, social networking, messaging, and communications.

[0065] With the introduction and use of new materials for lens and filter integration new enhancements and capabilities of the digital eyewear can be further realized. These materials include advances in OLED, LED, transparent LED, flexible LED, crystalline, prism, holographic, polarizing, and translucent material and the like to

electrorefractive, electrodiffractive, electroreflective, composite refractive materials and the like, with one or more lens material layers and passive or active display or projection based implementations.

[0066] With these new capabilities an important new set of optical and perceptual parameters can be measured and used as inputs, controls, or feedback elements that increase even further uses and value of the eyewear and lead to important improvements that can be used for teaching, sports, health, and improved perception.

[0067] Accordingly systems and methods in accordance with embodiments are disclosed that provide these enhanced features for wearable optics devices. To describe these features and embodiments in more detail refer now to the following description in conjunction with the following discussion. A key feature associated with these enhancements is providing a variety of perceptual parameters that can be utilized with the wearable optics devices. Examples of perceptual parameters include but are not limited to optical expression, voice, brain wave, environmental, audio, video, navigational, augmented reality, algorithmic, spatial, cognitive, interpretive.

[0068] Figure 5B illustrates a perceptual optimization system 550. The perceptual optimization system 550 receives a variety of inputs including optical parameter measurements, real world inputs, digital media inputs, expression parameter measurements, optical parameter measurement feedback, other parameter measurements to provide wearable optics visual display elements. Optical parameter measurements include for example, ciliary, pupil, corneal, lens, iris, eye lid, retina measurements. Real world inputs could be for example inputs from one or more

microphones or cameras. Digital media inputs could be for example from digital audio, digital video, graphics, images and augmented reality.

[0069] Other perceptual parameters could be for example, smell, touch, brainwave, temperature/humidity of the user, environmental conditions near the user. The optical feedback could be provided through information received about the retina/iris dynamics and/or the lens ciliary dynamics.

[0070] Figure 5C illustrates a wearable optics device architecture 560 in accordance with an embodiment. The architecture includes a frame 562 which includes a plurality of sensors on various areas thereon. Biometric sensors include a blood pressure sensor 617, temperature sensor 618, EEG sensor 616 and the like. Environmental sensors 615 are also provided. There are microphone sensors 606, 607, 611 on various areas of the frame. Included on the frame 562 are cameras rear, front and side 606, 607, 611 to detect objects. Within the lens is a lens display 601. A display projector 620 is provided thereon to project images on the lens display 601. The lens display 601 can be a single unit or multiple unit lens. There are infrared sensors 602 as well as a directional illumination unit 603 on the bridge of the architecture 560. There are facial and mouth movement sensors 604 and or cameras located on the lens holder of the architecture 560. There is a speaker and an extendable speaker 610 located on the frame when worn. The speaker 610 could be held in place with a head band. An outer ear speaker/vibration element 612 is provided thereon. A control communication unit 608 is utilized to control the architecture 560. A power unit can be utilized to enable the architecture. Typically the power unit 613 comprises a rechargeable battery. The battery can be charged via a connector, such as but not limited to an USB connector to

a charging device laptop, tablet or desktop PC for example. In addition the device could be solar powered either by solar cells being placed on the device or the solar cells could be placed on articles of clothing (i.e. hat, shirt or pants for example) to facilitate the charging thereof. The architecture 560 includes a directional illumination unit 603, smell sensors 605 and an extendable user microphone 619.

In an embodiment, the sensors may comprise any or any combination of gyroscopes, accelerometers, torque sensors, weight sensors, pressure sensors, magnetometers, temperature sensors, light sensor, cameras and microphones, GPS, wireless detection, altitude sensors, blood pressure, heart rate sensors, biometric sensors, radio frequency identification (RFID), near field communication (NFC), mobile communication, Wi-Fi, strain gauges, fingerprint sensors, smell sensors gas sensors, chemical sensors, color sensors, sound sensors, acoustic sensors, ultraviolet sensors, electric field sensors, magnetic field sensors, gravity sensors, wind speed sensors, wind direction sensors, compass sensors, geo-locator sensor, polarized light sensors, infrared emitter sensors.

[0071] This architecture can be utilized with a conventional mobile operating system such as Android or IOS or with a new operating system incorporating optical parameters and perceptual parameters for even further capabilities and enhanced perception - eye optical or perceptual operating system (eyePOS). By using this approach and capability set, a whole new class of custom applications ("apps") can be created using the standard mobile operating systems or eyePOS and an eyePOS simulator to address manifold valuable applications that can improve human learning, entertainment, and health on one side to new navigation systems (physically linked and search linked) and

enhanced perception. To describe these feature in more detail refer now to the following description.

[0072] A method and system in accordance with an embodiment comprises utilizing dynamic eye tracking with a wearable optics device; wherein parameters personalized to a user can be provided based upon the dynamic eye tracking. The method and system which includes providing an enhancement utilizing objective and subjective quality standards based upon perceptual parameters. The perceptual parameters include any and any combination of optical expression, voice, brain wave, environmental, audio, video, navigational, augmented reality, algorithmic, spatial, cognitive, interpretive. The wearable optics device controls any or any combination of mimics, amplifies, or expands a user perceptual physiology utilizing perceptual parameters.

[0073] The wearable optics device can include one or more inserts into eyeglasses. The eyeglasses comprise quad state eyeglasses. Shading control can be utilized on the wearable optics device. The shading control can be provided by one or more projectors within the wearable optics device. An occlusion effect can be projected on a lens of the wearable optics device. The shading can be provided on a lens of the wearable optics device wherein the surrounding area is occluded or reversed. The shading is provided by a polarized filter. The shading control can be provided by the lenses within the wearable optics device. The shading can be controlled using optical parameters. The optical parameters include any or any combination of ciliary, pupil, corneal, lens, iris, eye lid, and retina measurements. Materials that can electrically control any or any combination of chromatic, refractive, diffractive, transparent,

reflective properties of the wearable optics device are utilized with the dynamic eye tracking. The lens can be any or any combination of transparent LCD, LED, OLED, flexible LED, flexible OLED, transparent matrix, semi-transparent matrix, prism based, holographic, electroluminescence, electorelective, dynamic filtering materials.

[0074] The wearable optics device comprises an electrochromatic material. In a system and method in accordance with an embodiment one or more elements are utilized within the wearable optics device to provide image information into the eye. The one or more elements include any or any combination of a lens projector, retinal projection. The retinal projection or projector plus prism provide the occlusion.

[0075] The wearable optics device includes shading control for the eyewear. In the wearable optics device, portions of an image viewed by the wearable optics device can be shaded to control brightness. The lenses of the wearable optics device can be controlled polarizing, transparent OLED, or projection and prism lenses.

[0076] The parameters may include any or any combination of prescriptions for improving the vision of a user, a zoom feature, a microscope feature, magnifying feature, retinal projection feature. The wearable optics device can be utilized in a simulator. In an embodiment, a focal of the wearable optics device is utilized in conjunction with the dynamic eye tracking.

[0077] The parameters can include any or any combination of a zoom feature, a microscope feature, magnifying feature, illumination feature; a retinal projection feature. In an embodiment a 360 degree view can be provided. The 360 degree view can be any or any combination of a left or right panning, up and down panning, three dimensional rotations.

[0078] In another embodiment, an illumination feature is directed to a specific area based upon the dynamic eyetracking mechanism. A wearable optics device camera feature can filter certain light waves for controlled viewing or visual effects. The filtering feature can include controlling noise reduction, polarization, and creative effects. The wearable optics device feature can include controlling a stability control for facial or object focus. In an embodiment optical parameters can be utilized. The optical parameters include any of or any combination of ciliary, pupil, corneal, retina, lens, iris measurements. An embodiment may include detecting head movement. An acoustic wave mechanism may be utilized within the wearable optics device. A brain wave mechanism may be utilized within the wearable optics device. A magnetic wave mechanism may be utilized within the wearable optics device.

[0079] The wearable optics device can be utilized in a variety environments including but not limited to athletic, gaming, gambling, educational, military, firefighting, medical dental, and the like. To describe the features of the present invention in more detail refer now to the following description in conjunction with the accompanying figures

[0080] Figure 6 illustrates the parts of an eye that may be utilized with the eye tracking mechanism of an embodiment. In an embodiment, the iris, retina cornea, pupil, ciliary, and lens can all be utilized either singly or in combination to enable the dynamic eye tracking mechanism.

[0081] Social networks can be leveraged advantageously with the wearable optics device in accordance with an embodiment. Figure 7 illustrates a social networking application 700 utilized with the wearable optics device. The networks of Facebook,

Linked In, Twitter, Salesforce.com, and other networks, as well as the Internet are connected to the wearable optics device.

[0082] Individuals that are “Friends” for example, can be identified by a highlight by the wearable optics device. Information about individuals can be gathered by using eyes utilized by the wearable optics device architecture. In an embodiment, the individual can be selected. The individual can be identified in a variety of ways for example using facial recognition, target individual information, GPS, RFID, NFC, optical information, voice recognition, and mobile location.

[0083] Figure 8 illustrates a messaging application 800 utilized with wearable optics device in accordance with an embodiment. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter’s tweet. The wearable optics device can utilize R2R, NFC, Wi-Fi, Internet to communicate. It is possible to talk using a microphone, sensors near the face, jaw, and nose can be utilized to provide control of the messaging application. In addition lip motion, and lip reading can be utilized to transmit voice in a silent and confidential manner. An individual can be targeted by using selected eye movements.

[0084] Figure 9 illustrates the wearable optics device utilized by an athletic sports spectator in accordance with an embodiment 900. Networks such as Twitter, Facebook, Internet are connected to the spectator. For example the spectator can see who has the ball and its course during a play. Who has the ball as well as the ball's location is highlighted. Video information can be overlayed from scores of other games. Information about the location of the football during the game (line of scrimmage, first

down line). Video highlights of the game could be provided as well as augmented reality media.

[0085] Figure 10 illustrates the wearable optics device utilized by an athletic sports player in accordance with an embodiment 1000. Networks such as Twitter, Facebook, Coach/trainer communication, and other player communications are connected to the player. For example the spectator can see that a curve ball is hit at 102 mph. The trajectory of the ball is highlighted.

[0086] Figure 11 illustrates an augmented reality information, navigation, and advertising application 1100 utilized with the wearable optics device. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate. In one example the wearable optics device is utilized in a vehicle. In this example the wearable optics device includes speaker microphone and rear camera on the headset and also on the rear of a vehicle for example. Augmented reality real time information is provided. For example, the Augmented Reality Real time information provided is that the vehicle is traveling at 62 mph.

[0087] There also may be Augmented Reality Mirror Live Video from Rear Camera of the car. For a sign that reads, "Detour 1 Mile" is shown on as an emergency Augmented Reality sign from State/Federal Sources which could also provide additional information.

[0088] In another example, "McDonald's Free Coffee" next exit, seen as an Augmented Reality real-time advertisement. "Stage Road 1 Mile", will also be seen as an Augmented Reality Sign while the voice message "Next turn Stage Rd. 1 mile" is

transmitted to the driver together comprising an enhanced Augmented Reality GPS and navigation system.

[0089] Figure 12 illustrates an augmented reality information patient data application 1200 utilized with the wearable optics device used in conjunction with a remote device. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate.

[0090] Patient records and internet technical information are connected to the eyepiece and microphone of the person who is utilizing the wearable optics device. Utilizes an augmented reality zoom window to identify medical feature. Augmented reality patient data is made available to the person via the eyewear. There may also be a remote device camera utilized on the drill of a dentist for example. The dentist for example can utilize the dynamic eye tracking mechanism to focus on the correct tooth.

[0091] An overlay of the x-ray of the tooth can be seen utilizing the augmented reality. An augmented reality overlay of dental records and Internet research in tooth treatment is available. Dentist can use a remote drill with augmented reality. Illumination and zoom can also be utilized with an augmented reality window.

[0092] Figure 13 illustrates a shading control application 1300 utilized with the wearable optics device. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate. Shading settings can be chosen through push buttons on the eyewear frame, via eye movement, or

automatically. The shading can be uniform across the eyewear lens or concentrated in a specific area or areas of the lens.

[0093] In an embodiment a lamp/flashlight 1302 projects light to eye 1310. The camera 1306 and eye sensor 1308 pick up the light. The lens 1304 can be any or any combination of transparent LCD, LED, OLED, flexible LED, flexible OLED, transparent matrix, semi-transparent matrix, prism based, holographic, electroluminescence, electoreflective, dynamic filtering materials.

[0094] Light can be occluded in a specific area 1312 utilizing the wearable optics device. The camera 1306 determines position of light to be occluded (real time). The eye sensor 1308 determines the position of the eye/pupil/retina (real time). The camera 1306 /eye sensor 1308 determines line of sight between light to be occluded and eye 1310 and intersect area on lens 1304 (real time) or area to project occlusion from a projector embodiment.

[0095] Figure 14 illustrates an augmented reality application 1400 utilized with the wearable optics device 1410. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device 1410 can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate.

[0096] In an embodiment, an augmented reality keyboard 1404 appears selected by look at the phone/item and then blinking or the like. The augmented reality (AR) keyboard 1404 is utilized that is controlled by the dynamic eye tracking mechanism. An infrared camera 1402 is used to sense the position of any of the user's hand, hand movement, finger position, finger movement on the AR keyboard such as key highlight and key click sound. There is an augmented reality display 1406 which is an

enlargement of the small phone display, on the lens. There is also an augmented reality keyboard which is shown as being on the lens.

[0097] Figure 15 illustrates a physical gaming application 1500 utilized with the wearable optics device 1510. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device 1510 can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate.

[0098] In an embodiment, a person wearing the wearable optics device 1510 can analyze game strategy, count cards, determine the score, do analysis (of game statistics), and analyze other player's faces utilizing an augmented reality overlay 1502 and facial recognition.

[0099] Figure 16 illustrates a first embodiment of an online/mobile gaming application 1600 utilized with the wearable optics device 1610. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device 1610 can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate.

[00100] The player and opponent have augmented reality cards in hand. Augmented reality playing cards are utilized. Because of the augmented reality and communication link the players need not be present in the same location. The AR cards may be lifted by hand movement. There is a physics adjusted augmented reality card movement and dynamics. In an embodiment there can be a virtual game board, a background, and a playing field.

[00101] There is an infrared camera 1602 on the glasses to measure and judge hand and finger position and movement. There is an augmented reality scene or dynamics overlay 1612 which can be seen on the lenses.

[00102] Figure 17 illustrates a second embodiment of an online/mobile gaming application 1700 utilized with the wearable optics device 1710. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device 1710 can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate.

[00103] The scene that the player sees can be an actual real-world video game screen. It could also be utilized as an augmented reality video game screen (e.g. for mobile). Furthermore it could also be utilized as a full 3-D real time Augmented Reality game/battle field which the player sees. The player can use an augmented reality game controller. There is an infrared camera on the glasses to measure and judge hand and finger position and movement on the AR game controller. Augmented reality scenes, AR game controller, AR gun, or AR remote control overlay 1712 are seen on the lenses of the glasses.

[00104] Figure 18 illustrates shading control mechanism utilizing the wearable optics device. In this embodiment there are one or more cameras 1806 that measures changes in the eye (for example the pupil or the retina) and sends the information to a processing system. Thereafter, the processing system 1802 can control a display on the lens 1804 to provide shading.

[00105] Figure 19 illustrates an optical/perceptual operating system 1900 with the wearable optics device. As is seen a plurality of applications 1902-1910 interface with a

processing system. The processing system includes a CPU, Memory, computer control and a CPU updating system 1912.

[00106] The applications include but are not limited to an eye prescription 1902, shading 1904, a glare application, 1906, GPS for navigation of a vehicle 1908 and a medical application 1910. The system would include perceptual measurement/generators 1914. These would include but are not limited to calibration software, augmented reality software, entertainment software, video/audio conferencing software and external communication/databases. The system would also include one or more device drivers. They include but are not limited to display drivers 1916, optical/sensor drivers 1918, operating system drivers 1920, network drivers 1922, external remote object drivers 1924 and gaming/entertainment drivers 1926.

[00107] Figure 20 describes an embodiment of the digital architecture of a wearable optics device 2000. In this embodiment, the wearable optics device eyewear includes mobile/smart phone circuitry / external data communication / and circuitry for transmitting data via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet, along with networking to external networks platforms / data / media sites 2016 . The wearable optics contains a processing system 2002 with memory storage, sensors for optical and perceptual measurement 2006, circuitry to control the optical display and perceptual generation needs of the device 2004, and interface 2008 to remote devices such as tools, specialty camera, GPS, mobile phone, wearable devices and the like.

[00108] In this embodiment various types of application software ("apps") 2018 can be run on the wearable optics device 2000 including shading control applications, focus and user eye adjustment prescriptions, and augmented reality applications for games

such as football. An Internet browser 2010 that utilizes optical or perceptual parameters to drive navigation of the Internet can be used such that eye movements or facial expressions can accelerate the browsing process to the desired information. The wearable optics device 2000 contains a system browser 2012 with file storage that can be on the device or accessed via one of the networks to the device.

[00109] The device 2000 can be powered by a separate battery (not shown). The battery can be charged via a connector, such as but not limited to an USB connector to a charging device laptop, tablet or desktop PC for example. In addition the device 200 could be solar powered either by solar cells being placed on the device 2000 or the solar cells could be placed on articles of clothing (i.e. hat, shirt or pants for example) to facilitate the charging thereof.

[00110] Figure 21 illustrates the embodiment of a system simulator 2100 for use by developers of applications and new lenses or expansion of the wearable optics device. In this embodiment, there is a simulator for the operating system 2102, a lens simulator 2104, a display 2114, and an eyewear emulator 2116. Optical/perceptual measurements 2106, camera signals, and other sensors and measurements are inputs to the simulator. The developer apps or new lenses can then be tested for various types of wearable options with various types of operating systems including iOS, Andriod, and general purpose or optimized optical/perceptual operating systems.

[00111] Figure 22A through Figure 22F illustrate an embodiment of inverse shading using the wearable optics device. Figure 22A illustrates the problem of glare caused by ambient light which degrades the visibility of a object such as the screen of a mobile phone or laptop. Figure 22C describes the iris / pupil contraction due to brightness

which degrades retina/cornea and brain view of target object such as a phone screen or the like. In Figure 22E the phone screen appears dark since ambient light is far brighter than screen.

[00112] Figure 22B illustrates the selection of the target object as in a phone screen via eye or automatically by preferences, rules, camera image capture and object recognition. Figure 22D shows eye detection and capture of the object's position and image by a camera on the eyewear. Figure 22F shows the resulting elimination or reduction in glare and increase in visibility of the object wherein a shaded or translucent background follows surrounding area object in real time as seen from the user of the wearable optics device.

[00113] Figure 23 illustrates an embodiment of eye tracking illumination and enhanced efficiency utilizing the wearable optics device. Using the eye sensor and camera the line of sight and focal length can be determined and used to control a directional illumination source such that the illumination source illuminates the area corresponding to the area being focused on by the user of the wearable optics device

[00114] Figure 24 illustrates an embodiment of real-time augmented reality overlay 2400 utilizing the wearable optics device. In this embodiment, information is transmitted via mobile, text, R2R, Internet, Wi-Fi, Facebook message, Twitter's tweet. The wearable optics device can utilize mobile, R2R, NFC, Wi-Fi, Internet to communicate. In one example the wearable optics device is utilized in a vehicle. In this example the driver's eyewear uses augmented reality to overlay advertising signs which can be personalized to the user which appear as if they are normal roadside billboards. In this example a real-time updated augmented reality danger sign is posted before a road hazard with

the augmented reality sign being generated in real-time using information from the networks connected to the wearable eyewear device. This example also shows real-time translation from English to Spanish of navigational warning and advertising signs using augmented reality with the wearable optics device.

[00115] Accordingly systems and methods in accordance with embodiments are disclosed that provide these enhanced features for wearable optics devices. To describe these features and embodiments in more detail refer now to the following description in conjunction with the following discussion. A key feature associated with these enhancements is providing a variety of perceptual parameters that can be utilized with the wearable optics devices. Examples of perceptual parameters include but are not limited to optical expression, voice, brain wave, environmental, audio, video, navigational, augmented reality, algorithmic, spatial, cognitive, interpretive.

[00116] Although the present invention has been described in accordance with the embodiments shown, one of ordinary skill in the art will readily recognize that there could be variations to the embodiments and those variations would be within the spirit and scope of the present invention. Accordingly, many modifications may be made by one of ordinary skill in the art without departing from the spirit and scope of the appended claims.

CLAIMS

What is claimed is:

1. A wearable optics device comprising:
a lens; and
a dynamic eye tracking mechanism in communication with the lens; wherein an optical parameter based operating system is utilized based upon the dynamic eye tracking.
2. The wearable optics system of claim 1, wherein the dynamic eye tracking is utilized to control the operating system.
3. The wearable optics system of claim 1, wherein applications are utilized to control sensors and the communication of the wearable optics device.
4. The wearable optics system of claim 1, wherein lenses is controlled by the operating system.
5. The wearable optics device of claim 1, wherein the lens includes a plurality of layers.
6. The wearable optics system of claim 1, wherein lens layer drivers and an eye cursor are controlled by the operating system.

7. A wearable optics device comprising:
a lens; and
a dynamic eye tracking mechanism in communication with the lens; wherein shading or inverse shading is utilized based upon the dynamic eye tracking.
8. The wearable optics device of claim 7, wherein inverse shading is provide when viewing a display.
9. The wearable optics device of claim 7, wherein inverse shading is provided by a polarized filter.
10. The wearable optics device of claim 7, wherein algorithms for shading and inverse shading are provided within the wearable optics device.
11. The wearable optics device of claim 7, wherein algorithms are provided to transform non-visual spectrum to visible information.
12. The wearable optics device of claim 8, wherein the display is utilized with any of a smartphone, personal computer, laptop, desktop or portable device.

13. The wearable optics device of claim 7, wherein an object is unshaded but the area outside of the object is shaded.

14. The wearable optics device of claim 7, wherein object recognition is utilized.

15. The wearable optics device of claim 7, wherein if ambient light is above some predetermined value then you shade.

16. The wearable optics device of claim 7, wherein each lens has its own inverse shading.

17. The wearable optics device of claim 10, wherein translucency shading is provided for reading material.

18. A method comprising:
utilizing dynamic eye tracking with a wearable optics device; wherein a perceptual optimization is utilized based upon the dynamic eye tracking.

19. The method of claim 18 which includes providing an enhancement utilizing objective and subjective quality standards based upon perceptual parameters.

20. The method of claim 19, wherein the perceptual parameters include any and any combination of optical expression, voice, brain wave, environmental, audio, video, navigational, augmented reality, algorithmic, spatial, cognitive, interpretive.

21. The method of claim 18, wherein the wearable optics device controls any or any combination of mimics, amplifies, or expands a user perceptual physiology utilizing perceptual parameters.

22. The method of claim 20, wherein the optical expressions are images.

23. A wearable optics device comprising:

a lens; and


a dynamic eye tracking mechanism in communication with the lens; wherein an augmented reality overlay is utilized based upon the dynamic eye tracking.

24. The wearable optics device of claim 23, wherein an overlay translation is augmented reality overlay in real time

25. The wearable optics device of claim 23, wherein an overlay translation is provided in the wearable optics device using line of sight or focal length of the lens of the user to the object to provide an augmented reality overlay


ABSTRACT

Improved wearable optics is disclosed. The wearable optics comprises a frame member and a lens. The wearable optics also includes circuitry within the frame member for enhancing the use of the wearable optics. A system and method in accordance with the present invention is directed to a variety of ways to enhance the use of eyeglasses. They are: (1) media focals, that is, utilizing the wearable optics for its intended purpose and enhancing that use by using imaging techniques to improve the vision of the user; (2) telecommunications enhancements that allow the eyeglasses to be integrated with telecommunication devices such as cell phones or the like; and (3) entertainment enhancements that allow the wearable optics to be integrated with devices such as MP3 players, radios, or the like.




100

Figure 1




102'

Figure 2




300

Figure 3




400

Figure 4




402

Figure 5A




Perceptual Optimization through Optical and Perceptual Parameters

Figure 5B




Enhanced Digital Eyewear Architecture


Figure 5C



Optical Parameters
Figure 6




700
Social Networking
Figure 7



800


Messaging
Figure 8



900


Athletic Sports Spectator

Figure 9




Athletic Sports Player

Figure 10




1100

Figure 11



1200


Figure 12





1300

Shading Control


Figure 13




1400
 Augmented Reality
 Figure 14




1500
Gaming (physical)
Figure 15





1700
Gaming (online/mobile)

Figure 17



1800
Shading control via eye measurements
Figure 18






Figure 19



Digital System Architecture

Figure 20



2100
System Simulator
Figure 21





Figure 22B

Figure 22A

- Eye need not react to ambient brightness
- Eye can focus better, more comfortably on screen or object




Inverse Shading

Before
Figure 22C


After
Figure 22D

Shading or translucent background follows object in real time
 -shading optimized by tracking object and shading independently in each of two lenses (left and right eyes)

Object normal brightness




Phone screen appears dark since ambient light is brighter than screen



Inverse Shading


Viewing Plane
After
Figure 22F

Viewing Plane
Before
Figure 22E



Eye tracking illumination and enhanced efficiency

Figure 23



Real Time Augmented Reality Overlay

Figure 24