US006014491A

United States Patent [19]

Hair

[11] **Patent Number: 6,014,491**

[45] **Date of Patent: Jan. 11, 2000**

[54] **METHOD AND SYSTEM FOR MANIPULATION OF AUDIO OR VIDEO SIGNALS**

[75] Inventor: **Arthur R. Hair**, Upper St. Clair, Pa.

[73] Assignee: **Parsec Sight/Sound, Inc.**, Mt. Lebanon, Pa.

[21] Appl. No.: **08/811,266**

[22] Filed: **Mar. 4, 1997**

[51] **Int. Cl.**[7] **H04N 9/81**; H04N 9/79

[52] **U.S. Cl.** **386/31**; 386/34

[58] **Field of Search** 386/31, 34, 39, 386/1, 4, 27, 32, 33, 35, 40, 46, 92, 52, 95; 360/32; H04N 9/81, 9/79

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,677,645	6/1987	Kaniwa et al. .	
4,873,582	10/1989	Furuhata et al.	386/34
5,054,360	10/1991	Lisle et al. .	
5,155,589	10/1992	Gere	386/31
5,270,828	12/1993	Mogi .	
5,301,205	4/1994	Tsutsui et al. .	
5,388,209	2/1995	Akagiri .	
5,440,344	8/1995	Asamura et al. .	
5,461,378	10/1995	Shimoyoshi et al. .	
5,495,554	2/1996	Edwards et al. .	
5,530,750	6/1996	Akagiri .	
5,548,574	8/1996	Shimoyoshi et al. .	
5,659,654	8/1997	Nagasawa et al.	386/31

Primary Examiner—Robert Chevalier
Attorney, Agent, or Firm—Ansel M. Schwartz

[57] **ABSTRACT**

The present invention is a method and system to compress and/or convert audio and video signals into a static audio file format and/or a static video file format, respectively, in which a playing device can be instructed to commence playing specific sounds through an audio output device and/or commence displaying specific images composed of specific colors displayed, and/or replicated, within a plurality of discrete pixels on a video output device; continue to play, and/or replicate, such sounds or display, and/or replicate, such colors within such pixels without further input from the static audio and/or static video file; then cease playing the specific sounds and/or commence displaying, and/or replicated different colors within such pixels upon receipt of instruction from the static audio file and/or static video file.

10 Claims, 13 Drawing Sheets




800
10
ANALOG AUDIO SOURCE
20
ANALOG AUDIO RECORDER
30
ANALOG AUDIO FILE
40
ANALOG TO DIGITAL AUDIO CONVERTER
50
ANALOG TO DIGITAL AUDIO RECORDER
60
DYNAMIC AUDIO FILE
70
DYNAMIC AUDIO PLAYER
80
FREQUENCY / AMPLITUDE DATABASE COMPILER
90
F/A DATABASE
802
100
DYNAMIC TO STATIC AUDIO TRUNCATOR
110
STATIC AUDIO FILE
809
120
STATIC AUDIO PLAYER
190
AUDIO OUTPUT DEVICE
804
150
STATIC AUDIO FILE
130
STATIC AUDIO PLAYER
140
ELECTRONIC CONNECTION
170
STATIC AUDIO FILE
160
DYNAMIC AUDIO FILE
806
180
DYNAMIC AUDIO FILE

FIG.1


800
210
ANALOG VIDEO SOURCE
220
ANALOG VIDEO RECORDER
230
ANALOG VIDEO FILE
240
ANALOG TO DIGITAL VIDEO CONVERTER
250
ANALOG TO DIGITAL VIDEO RECORDER
260
DYNAMIC VIDEO FILE
270
DYNAMIC VIDEO PLAYER
290
R/G/B DATABASE
280
RED / GREEN / BLUE DATABASE COMPILER
390
802
300
DYNAMIC TO STATIC VIDEO TRUNCATOR
310
STATIC VIDEO FILE
809
320
STATIC VIDEO PLAYER
VIDEO OUTPUT DEVICE
804
350
STATIC VIDEO FILE
330
STATIC VIDEO PLAYER
340
ELECTRONIC CONNECTION
370
STATIC VIDEO FILE
360
DYNAMIC VIDEO FILE
380
DYNAMIC VIDEO FILE
806

FIG. 2


FREQUENCY F_1
TIME t_1
I_1 = 00001 0001 0000001 1
AMPLITUDE A_1
STATUS S_1 {ACTIVATE}

FIG. 3


FREQUENCY F_1
TIME t_8
I_8 = 00001 0001 0001000 0
AMPLITUDE A_1
STATUS S_0 {DEACTIVATE}

FIG. 4


FRAME HEIGHT h_1
FRAME LENGTH l_1
GREEN 000
TIME t_1
F_1 = 00001 00001 01110100 00000000 01011111 0000001
PIXEL $h_1 l_1$
RED 116
BLUE 095

FIG.5


FRAME HEIGHT h_1
FRAME LENGTH l_1
GREEN 140
TIME t_8
F_8 = 00001 00001 00000000 10001100 01110110 0001000
PIXEL $h_1 l_1$
RED 000
BLUE 118

FIG.6


FREQUENCY F5
AMPLITUDE
A5
A4
A3
A2
A1
1 1 1 1
1 1 1 1
1 1 1 1
I1 I2 I3 I4 I5 I6 I7 I8
TIME INTERVALS

FIG. 7


FREQUENCY F5
AMPLITUDE
A5
A4
A3
A2
A1
1 1 1 1
1 1 1 1
1 1 1 1
I1 I2 I3 I4 I5 I6 I7 I8
TIME INTERVALS

FIG. 8


FREQUENCY F5
AMPLITUDE
A5
A4
A3
A2
A1
1
1
1
0
0
0
I1
I2
I3
I4
I5
I6
I7
I8
TIME INTERVALS

FIG.9


FREQUENCY F5
AMPLITUDE
A5
A4
A3
A2
A1
1 1 1 1
1 1 1 1
1 1 1 1
I1
I2
I3
I4
I5
I6
I7
I8
TIME INTERVALS

FIG.10


VIDEO OUTPUT DEVICE 310
h... h... h... h22 h21 h20 h19 h18 h17 h16 h15 h14 h13 h12 h11 h10 h9 h8 h7 h6 h5 h4 h3 h2 h1
l1 l2 l3 l4 l5 l6 l7 l8 l9 l10 l11 l12 l13 l14 l15 l16 l17 l18 l19 l20 l21 l22 l... l... l...
PIXEL h1l1= R116G000B095
PIXEL h4l7= R142G195B232
PIXEL h11l20= R233G228B000
VIDEO FRAME F6 AT TIME t6

FIG. 11


DATA COLATION WITH A PRIMARY SORT BY SOUNDS F_XA_Y AND A SECONDARY SORT BY TIME INTERVAL I_W
DYNAMIC AUDIO FILE 60
SERIAL DATA FLOW BY TIME INTERVAL I_W
STACK
FREQUENCY/AMPLITUDE DATABASE COMPILER 80
F_1A_1 I_1 I_2 I_3 I_4 I_5 I_6 I_7
F_2A_1 I_1 I_2 I_3 I_4 I_5
F_2A_2 I_1 I_2 I_3 I_4 I_5
F_5A_1 I_4 I_5 I_6 I_7
F_5A_2 I_4 I_5 I_6 I_7
F_5A_3 I_4 I_5 I_6 I_7
SERIAL DATA FLOW BY SOUNDS F_XA_Y
FREQUENCY/AMPLITUDE DATABASE 90

FIG.12


FREQUENCY/AMPLITUDE DATABASE 90
DATA TRUNCATION OF REPETITIVE OCCURANCES OF SOUNDS F_XA_Y BY TIME INTERVAL I_W
SERIAL DATA FLOW BY SOUNDS F_XA_Y
STACK
DYNAMIC TO STATIC AUDIO TRUNCATOR 100
F_1A_1 I_1 = ON I_8 = OFF
F_2A_1 I_1 = ON I_6 = OFF
F_2A_2 I_1 = ON I_6 = OFF
F_5A_1 I_4 = ON I_8 = OFF
F_5A_2 I_4 = ON I_8 = OFF
F_5A_3 I_4 = ON I_8 = OFF
SERIAL DATA FLOW BY TIME INTERVAL I_W
STATIC AUDIO FILE 110

FIG.13


DYNAMIC VIDEO FILE 360
SERIAL DATA FLOW BY VIDEO FRAME F_W
RED/GREEN/BLUE DATABASE COMPILER 380
DATA COLATION WITH A PRIMARY SORT BY PIXELS $h_x l_y$ AND A SECONDARY SORT BY VIDEO FRAME F_W
PIXEL $h_{11} l_{20}$
$F_1 = R_{233}G_{228}B_{000}$ $F_2 = R_{233}G_{228}B_{000}$ $F_3 = R_{233}G_{228}B_{000}$ $F_4 = R_{233}G_{228}B_{000}$ $F_5 = R_{233}G_{228}B_{000}$ $F_6 = R_{233}G_{228}B_{000}$ $F_7 = R_{233}G_{228}B_{000}$ $F_8 = R_{233}G_{228}B_{000}$
PIXEL $h_4 l_7$
$F_1 = R_{074}G_{255}B_{000}$ $F_2 = R_{074}G_{255}B_{000}$ $F_3 = R_{074}G_{255}B_{000}$ $F_4 = R_{074}G_{255}B_{000}$ $F_5 = R_{074}G_{255}B_{000}$ $F_6 = R_{142}G_{195}B_{232}$ $F_7 = R_{142}G_{195}B_{232}$ $F_8 = R_{142}G_{195}B_{232}$
PIXEL $h_1 l_1$
$F_1 = R_{116}G_{000}B_{095}$ $F_2 = R_{116}G_{000}B_{095}$ $F_3 = R_{116}G_{000}B_{095}$ $F_4 = R_{116}G_{000}B_{095}$ $F_5 = R_{116}G_{000}B_{095}$ $F_6 = R_{116}G_{000}B_{095}$ $F_7 = R_{116}G_{000}B_{095}$ $F_8 = R_{000}G_{140}B_{118}$
SERIAL DATA FLOW BY PIXEL $h_x l_y$
RED/GREEN/BLUE DATABASE 290

FIG. 14


DATA TRUNCATION OF REPETITIVE COLOR OCCURANCES
IN PIXELS $h_x l_y$ BY VIDEO FRAME F_W
RED/GREEN/BLUE DATABASE 290
SERIAL DATA FLOW BY PIXEL $h_x l_y$
DYNAMIC TO STATIC VIDEO TRUNCATOR 300
PIXEL $h_{11} l_{20}$
PIXEL $h_4 l_7$
PIXEL $h_1 l_1$
$F_1 = R_{233} G_{228} B_{000}$
$F_1 = R_{024} G_{255} B_{000}$ $F_6 = R_{142} G_{195} B_{232}$
$F_1 = R_{116} G_{000} B_{095}$ $F_8 = R_{000} G_{140} B_{118}$
SERIAL DATA FLOW BY VIDEO FRAME F_W
STATIC VIDEO FILE 310

FIG. 15


PIXEL
h_{11} I_{20}
h_4 I_7
h_1 I_1
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{142}G_{195}B_{232}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{142}G_{195}B_{232}$
$R_{000}G_{140}B_{118}$
$R_{233}G_{228}B_{000}$
$R_{142}G_{195}B_{232}$
F_1 F_2 F_3 F_4 F_5 F_6 F_7 F_8
VIDEO FRAMES

FIG. 16


PIXEL
h_{11} I_{20}
h_4 I_7
h_1 I_1
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{074}G_{255}B_{000}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{142}G_{195}B_{232}$
$R_{116}G_{000}B_{095}$
$R_{233}G_{228}B_{000}$
$R_{142}G_{195}B_{232}$
$R_{000}G_{140}B_{118}$
$R_{233}G_{228}B_{000}$
$R_{142}G_{195}B_{232}$
F_1 F_2 F_3 F_4 F_5 F_6 F_7 F_8
VIDEO FRAMES

FIG. 17


PIXEL
h11 l20
h4 l7
h1 l1
R233 G228 B000
R074 G255 B000
R116 G000 B095
R142 G195 B232
R000 G140 B118
F1
F2
F3
F4
F5
F6
F7
F8
VIDEO FRAMES

FIG. 18


PIXEL
h11 l20
h4 l7
h1 l1
R233 G228 B000
R074 G255 B000
R116 G000 B095
R142 G195 B232
R000 G140 B118
F1
F2
F3
F4
F5
F6
F7
F8
VIDEO FRAMES

FIG. 19


GEOMETRIC SHAPE 4
VIDEO OUTPUT DEVICE 310
GEOMETRIC SHAPE 2
GEOMETRIC SHAPE 3
GEOMETRIC SHAPE 1
VIDEO FRAME F_{156} AT TIME t_{156}
h... h... h... h22 h21 h20 h19 h18 h17 h16 h15 h14 h13 h12 h11 h10 h9 h8 h7 h6 h5 h4 h3 h2 h1
l_1 l_2 l_3 l_4 l_5 l_6 l_7 l_8 l_9 l_{10} l_{11} l_{12} l_{13} l_{14} l_{15} l_{16} l_{17} l_{18} l_{19} l_{20} l_{21} l_{22} l... l... l...

FIG. 20

METHOD AND SYSTEM FOR MANIPULATION OF AUDIO OR VIDEO SIGNALS

FIELD OF THE INVENTION

The present invention is related to a method and system to compress, and/or convert, audio and video signals, or files, into a static file format, and more particularly to a method and system to playback, and/or replicate, static audio files using a static audio player; and/or to playback, and/or replicate, static video files using a static video player.

BACKGROUND OF THE INVENTION

Generally, computer file formats for digital audio (hereinafter referred to as a "Dynamic Audio File"), such as the AUI, WAV, etc. audio file formats, and digital video (hereinafter referred to as a "Dynamic Video File"), such as the MPEG video file format, are formatted in a dynamic manner permitting easy and routine editing, serving a very useful purpose in the music and movie industries. Unfortunately, the dynamic nature of these file formats results in the generation of very large computer file sizes (i.e. hundreds of millions of bytes in size for a 40 minute digital audio file of 44.1 kHz sound quality and multi Gigabytes of data for full length motion picture quality recordings in digital video form).

As example, each second of a CD quality Dynamic Audio File is divided into 44,100 discrete time intervals. Each of these time intervals can simultaneously contain multiple frequencies (i.e. pitch) of sound at multiple amplitudes (i.e. volume). The Dynamic Audio File instructs an audio playing device (hereinafter referred to as a "Dynamic Audio Player") to play discrete frequencies/amplitudes at a rate of 44,100 times per second for CD quality sound. In a Dynamic Audio File, even if a string of consecutive time intervals contains identical frequencies and their related amplitudes, such an occurrence is irrelevant since the Digital Audio File format was designed, in part, to enable specific editing and/or dynamic manipulation of each individual time interval. The Dynamic Audio File fails to take advantage of redundancies within a string of consecutive time intervals which happen to repeat one or more identical frequencies and their related amplitudes.

Additionally, motion picture quality Digital Video Files are generally composed of about 30 video frames (images) per second. Each of these video frames are composed of a two dimensional, usually rectangular or square, grid of pixels. Each such pixel is capable of being colorized by complex, and/or basic, colors. Usually, a complex color is generated by mixing distinct shades of the basic colors red, green, and blue. The greater the number of distinct shades of these three basic colors, the greater the color definition of the video recording. It is common practice to use 256 distinct shades of the basic colors red, green, and blue in combination to create a palette of 16,777,216 unique complex colors, which is more than enough complex colors to display a motion picture quality recording. As example, each pixel contains a numeric entry ranging from 000 to 255 to define a distinct shade of the basic color red, a numeric entry ranging from 000 to 255 to define a distinct shade of the basic color green, and a numeric entry ranging from 000 to 255 to define a distinct shade of the basic color blue, all three of these shades of the basic colors red, green, and blue combine to identify a specific complex color from the palette of 16,777,216 possible complex colors (i.e. 256×256×256=16,777,216). Furthermore, the complex color white is

defined, as is customary, as the mixture of the basic colors red_{255}, $green_{255}$, and $blue_{255}$, where the subscript defines the distinct shade; and the complex color black is defined, as is customary, as the mixture of the basic colors red_{000}, $green_{000}$, and $blue_{000}$. Using this manner to mathematically describe complex colors, red_{116}, $green_{000}$, and $blue_{095}$ mix to generate a discrete shade of purple. This manner to mathematically describe complex colors will be used throughout the teachings of the present invention.

The Dynamic Video File instructs a video playing device (hereinafter referred to as the "Dynamic Video Player") to display specific complex colors within each discrete pixel of each discrete video frame video frame of the video recording. In a Dynamic Video File, even if a string of consecutive video frames contains a pixel having the identical complex color, such a coincidence is irrelevant since the Digital Video File format was designed, in part, to enable very specific and independent editing or dynamic manipulation of each individual discrete pixel within each discrete video frame. The Dynamic Video File format fails to take advantage of similarities or redundancies within a string of consecutive video frames in which the color within discrete pixels remains constant over time.

Furthermore, use of the Dynamic Audio File and Dynamic Video File formats pose several problems when used to electronically distribute digital audio and digital video signals to the consumer markets (i.e. U.S. Pat. No. 5,191,573). The Dynamic Audio File and the Dynamic Video File formats, being very large as measured in bytes of data, require considerable time to transmit via telecommunications. Additionally, and as example, if the user desires to save Dynamic Audio Files in the home, a massive storage device would be required (i.e. 10 music albums of about 45 minutes in duration each, in AUI format, would require in excess of 7 Giga bytes of storage capacity).

SUMMARY OF THE INVENTION

The present invention offers a new and improved method and system to encode audio and video files in a static format for playback utilizing a static player. The static format takes advantage of consecutive redundancies within Dynamic Audio Files and Dynamic Video Files, with respect to time.

A static audio file (hereinafter referred to as the "Static Audio File") is encoded in a format which records a plurality of discrete frequency/amplitude (sound) information to be played, and/or replicated, on an audio output device, and the related starting points each such frequency/amplitude is to be played, and/or replicated, for one or more consecutive time interval, with respect to time. The Static Audio File provides instructions enabling a audio playing device (hereinafter referred to as the "Static Audio Player") to save, and/or replace, such frequency/amplitude information in a matrix of memory registers within the Static Audio Player. Upon instruction from the user, the Static Audio Player will commence the playback process whereby each such frequency/amplitude, generated from each such memory register, will commence to be played on an audio output device, commencing with a discrete time interval. The Static Audio Player continues to play, and/or replicate, each such frequency/amplitude, generated from each such memory register, on an audio output device in each subsequent time interval (generally about 44,100 time intervals per second for CD quality sound), without further instruction from the Static Audio File. If, and/or when, the Static Audio Player receives subsequent instructions from the Static Audio File to update the frequency/amplitude information in any such

memory register with new frequency/amplitude information corresponding with a specific time interval, then the Static Audio Player will then play, and/or replicate, such new frequency/amplitude, generated from any such updated memory register, on an audio output device starting with a subsequent time interval.

A static video file (hereinafter referred to as the "Static Video File") is encoded in a format which records color information to be displayed, and/or replicated, within discrete pixels on a video output device, and the related starting points each such color is to be displayed, and/or replicated, within each such pixel, for one or more consecutive video frames, with respect to time. The Static Video File provides instructions enabling a video playing device (hereinafter referred to as the "Static Video Player") to save, and/or replace, such color information in a matrix of memory registers within the Static Video Player. Upon instruction from the user, the Static Video Player will commence the playback process whereby each such color, generated from each such memory register, will commence to be displayed within the corresponding pixel on a video output device, commencing with a discrete video frame. The Static Video Player continues to display, and/or replicate, each such color, generated from each such memory register, within each such pixel on a video output device in each subsequent video frame (generally about 30 video frames per second for full motion video), without further instruction from the Static Video File. If, and/or when, the Static Video Player receives subsequent instructions from the Static Video File to update the color information in any such memory register with new color information corresponding with a specific video frame, then the Static Video Player will then display, and/or replicate, such new color, generated from any such updated memory register, within the corresponding pixel on a video output device starting with a subsequent video frame.

The present invention pertains to a method for manipulating video or audio signals. The method comprises the steps of analyzing a video or audio signal having information and a size. Then there is the step of producing a representative signal from and corresponding to the audio or video signal that identifies the audio or video signal but has less information than the audio or video signal such that the audio or video signal cannot be produced from the representative signal itself and is smaller in size than the size of the audio or video signal. Next there is the step of transmitting to a remote location the representative signal. Then there is the step of recreating the audio or video signal from the representative signal at the remote location.

The present invention pertains to an apparatus for manipulating video or audio signals. The apparatus comprises means or a mechanism for analyzing a video or audio signal having a size. The apparatus comprises means or a mechanism for producing a representative signal from and corresponding to the audio or video signal that identifies the audio or video signal but has less information than the audio or video signal and is smaller in size than the size of the audio or video signal. The producing means or mechanism is connected to the analyzing means or mechanism. The apparatus comprises means or a mechanism for transmitting to a remote location the representative signal. The transmitting means or mechanism is connected to the producing means or mechanism. The apparatus comprises means or a mechanism for recreating the audio or video signal from the representative signal at the remote location. The recreating means or mechanism is connected to the transmitting means or mechanism.

BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings, the preferred embodiment of the invention and preferred methods of practicing the invention are illustrated in which:

FIG. **1** is a pictorial flow chart which may be used in carrying out the teachings of this invention for the purpose of converting Dynamic Audio Files into Static Audio Files, and playback of such Static Audio Files by means of a Static Audio Player, and conversion of Static Audio Files to Dynamic Audio Files by means of a Static Audio Player; and

FIG. **2** is a pictorial flow chart which may be used in carrying out the teachings of this invention for the purpose of converting Dynamic Video Files into Static Video Files, and playback of such Static Video Files by means of a Static Video Player, and conversion of Static Video Files to Dynamic Video Files by means of a Static Video Player.

FIG. **3** is computer algorithm which details one possible configuration of the computer file format for the Static Audio File.

FIG. **4** is a computer algorithm which details one possible configuration of the computer file format for the Static Audio File.

FIG. **5** and FIG. **6** are computer algorithms which detail possible configurations of the computer file format for the Static Video File.

FIG. **7** is a graphical representation of a Dynamic Audio File **60** in which frequency F_5 is to be played at amplitudes A_1, A_2, and A_3 during time intervals I_4, I_5, I_6, and I_7 on an audio output device.

FIG. **8** is a graphical representation of the playback output of a Dynamic Audio File **60** by a Dynamic Audio Player **70** in which frequency F_5 is played at amplitudes A_1, A_2, and A_3 during time intervals I_4, I_5, I_6, and I_7 on an audio output device.

FIG. **9** is a graphical representation of a Static Audio File **110** in which frequency F_5 is to be played at amplitudes A_1, A_2, and A_3 during time intervals I_4, I_5, I_6, and I_7 on an Audio Output Device **190**.

FIG. **10** is a graphical representation of the playback output of a Static Audio File **110** by a Static Audio Player **120** in which frequency F_5 is played at amplitudes A_1, A_2, and A_3 during time intervals I_4, I_5, I_6, and I_7 on an Audio Output Device **190**.

FIG. **11** is a pictorial representation of the playback of a video frame F_6 of a Static Video File **310** in which a shade of purple ($R_{116}G_{000}B_{095}$) is to be displayed within pixel h_1l_1; a shade of powder blue ($R_{142}G_{195}B_{232}$) is to be displayed within pixel h_4l_7; and a shade of lemon yellow ($R_{233}G_{228}B_{000}$) is to be displayed within pixel $h_{11}l_{20}$ on a Video Output Device **390**.

FIG. **12** is a computer flow chart depicting the various functions of the Frequency/Amplitude Database Compiler **80**.

FIG. **13** is a computer flow chart depicting the various functions of the Dynamic to Static Audio Truncator **100**.

FIG. **14** is a computer flow chart depicting the various functions of the Red/Green/Blue Database Compiler **280**.

FIG. **15** is a computer flow chart depicting the various functions of the Dynamic to Static Video Truncator **300**.

FIG. **16** is a graphical representation of a Dynamic Video File **260** which recorded color information to be displayed in pixels h_1l_1, h_4l_7, and $h_{11}l_{20}$ on a video output device.

FIG. **17** is a graphical representation of the playback output of a Dynamic Video File **260** by a Dynamic Video

Player **270** which displays color information in pixels h_1l_1, h_4l_7, and $h_{11}l_{20}$ on a video output device.

FIG. **18** is a graphical representation of a Static Video File **310** which recorded color information to be displayed in pixels h_1l_1, h_4l_7, and $h_{11}l_{20}$ on a Video Output Device **390**.

FIG. **19** is a graphical representation of the playback output of a Static Video File **310** by a Static Video Player **320** which displays color information in pixels h_1l_l, h_4l_7, and $h_{11}l_{20}$ on a Video Output Device **390**.

FIG. **20** is a graphical representation of the playback output of a Static Video File **310** by a Static Video Player **320** which displays color information on a Video Output Device **390**, said playback displaying geometric shapes mathematically defined by, and with corners located at, pixels h_3l_5, h_3l_{18}, h_8l_{18}, and h_8l_5 (Geometric Shape **1**); and $h_{12}l_3$, $h_{12}l_4$, $h_{15}l_4$, $h_{15}l_7$, $h_{14}l_7$, $h_{14}l_8$, $h_{17}l_8$, $h_{17}l_6$, $h_{20}l_6$, $h_{20}l_5$, $h_{16}l_5$, and $h_{16/3}$ (Geometric Shape **2**) ; and $h_{12}l_{20}$, $h_{19}l_{20}$, $h_{19}l_{22}$, $h_{20}l_{22}$, $h_{20}l_{19}$, $h_{22}l_{19}$, $h_{22}l_{18}$, $h_{19}l_{18}$, $h_{19}l_{15}$, and $h_{17}l_{15}$ (Geometric Shape **3**); and t_{56} (Geometric Shape **4**).

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings wherein like reference numerals refer to similar or identical parts throughout the several views, and more specifically to FIGS. **1** and **3** thereof, there is shown an apparatus **800** for manipulating video or audio signals. The apparatus comprises means or a mechanism **802** for analyzing a video or audio signal having a size. The apparatus comprises means or a mechanism **804** for producing a representative signal from and corresponding to the audio or video signal that identifies the audio or video signal but has less information than the audio or video signal and is smaller in size than the size of the audio or video signal. The producing means or mechanism is connected to the analyzing means or mechanism. The apparatus comprises means or a mechanism **806** for transmitting to a remote location the representative signal. The transmitting means or mechanism is connected to the producing means or mechanism. The apparatus comprises means or a mechanism **809** for recreating the audio or video signal from the representative signal at the remote location. The recreating means or mechanism is connected to the transmitting means or mechanism **806**.

The present invention pertains to a method for manipulating video or audio signals. The method comprises the steps of analyzing a video or audio signal having information and a size. Then there is the step of producing a representative signal from and corresponding to the audio or video signal that identifies the audio or video signal but has less information than the audio or video signal such that the audio or video signal cannot be produced from the representative signal itself and is smaller in size than the size of the audio or video signal. Next there is the step of transmitting to a remote location the representative signal. Then there is the step of recreating the audio or video signal from the representative signal at the remote location.

The analyzing means or mechanism **802** can include a frequency/amplitude database compiler **80**, or a red/green/blue database compiler **280**. The producing means or mechanism **804** can include a dynamic to static audio truncator **100**, or a dynamic to static video truncator **300**. The transmitting means or mechanism **806** can include a transmitter or modem and a telecommunication connection. The recreating means or mechanism **809** can include a static audio file **110** and a sound card and a static audio player **120** and an audio output device **190**, or a static video file **310** and a static video player **320** and a video output device **390**.

Referring now to FIG. **1**, one preferred embodiment of the invention is comprised of the following:

10 Analog Audio Source
20 Analog Audio Recorder
30 Analog Audio File
40 Analog to Digital Audio Converter
50 Analog to Digital Audio Recorder
60 Dynamic Audio File
70 Dynamic Audio Player
80 Frequency/Amplitude Database Compiler
90 Frequency/Amplitude Database
100 Dynamic to Static Audio Truncator
110 Static Audio File
120 Static Audio Player
130 Static Audio Player
140 Electronic Connection
150 Static Audio File
160 Dynamic Audio File
170 Static Audio File
180 Dynamic Audio File
190 Audio Output Device

In FIG. **1**, the following components are already commercially available: the Analog Audio Source **10**; the Analog Audio Recorder **20**; the Analog Audio File **30**; the Analog to Digital Audio Converter **40**; the Analog to Digital Audio Recorder **50**; the Dynamic Audio File **60**, **160**, and **180**; the Dynamic Audio Player **70**; the Electronic Connection **140**; and the Audio Output Device **190**.

The Frequency/Amplitude Database Compiler **80**; the Frequency/Amplitude Database **90**; the Dynamic to Static Audio Truncator **100**; the Static Audio File **110**, **150**, and **170**; and the Static Audio Player **120** and **130**; are new teachings of this invention.

The Analog Audio Source **10** is the originating source of audio in the configuration as outlined in FIG. **1**.

The Analog Audio Recorder **20** (i.e. cassette tape recorder/player, etc.) is the means by which the Analog Audio Source **10** can be recorded in either analog form or digital form.

The Analog Audio File **30** is the resulting analog file produced by the Analog Audio Recorder **20**.

The Analog to Digital Audio Converter **40** is the means by which an Analog Audio File **30** is converted into a digital file format.

The Analog to Digital Audio Recorder **50** is the means by which the Analog Audio Source **10** can be recorded into a digital file format.

The Dynamic Audio File **60** (i.e. AUI, WAV, etc.) is encoded in a digital file format which contains a plurality of frequency/amplitude information by time interval and can be produced by either the Analog to Digital Audio Converter **40** or the Analog to Digital Audio Recorder **50**. The Dynamic Audio File **60** is formatted in the same digital audio file format as the Dynamic Audio File **160** and **180**.

The Dynamic Audio Player **70** is a means to playback a Dynamic Audio File **60**.

The Frequency/Amplitude Database Compiler **80** is the means by which data contained in the Dynamic Audio File **60** is accessed and inputted into the Frequency/Amplitude Database Compiler **80** and is compiled to create the Frequency/Amplitude Database **90**. The Frequency/Amplitude Database Compiler **80** is a software program, to be executed on a computer system, which can be written by one skilled in the art of audio database creation (see FIG. **12**).

The Frequency/Amplitude Database **90** is the resulting digital database which is composed of three dimensions: frequency, amplitude, and time, and is produced by the Frequency/Amplitude Database Compiler **80**. The Frequency/Amplitude Database **90** is a computer file which can be saved on the hard disk of a computer or saved to random access memory, or both.

The Dynamic to Static Audio Truncator **100** is the means by which repetitive data contained in the Frequency/Amplitude Database **90** is truncated to contain only the starting point of such repetition and its ending point, with respect to time, and removes any repetitive data between said starting point and said ending point and creates the Static Audio File **110**. The Dynamic to Static Audio Truncator **100** is a software program, to be executed on a conventional computer system, which can be written by one skilled in the art of audio database creation (see FIG. **13**).

The Static Audio File **110** is encoded in a digital file format which records a plurality of discrete frequency/amplitude information and their respective starting points and ending points, with respect to time and can be produced by the Dynamic to Static Audio Truncator **100**. The Static Audio File **110** is encoded in a format which is compatible for use by the Static Audio Player **120** and/or **130**, and can be saved on the hard disk of a conventional computer system. The Static Audio File **110** is formatted in the same digital audio file format as the Static Audio File **150** and **170**. The Static Audio File **110** is a computer file which can be saved on the hard disk of a computer or saved to random access memory, or both.

The Static Audio File **110**, **150**, and/or **170** and the Static Video File **310**, **350**, and/or **370** may be combined into one file for use by a device which is the combination of the Static Audio Player **120** and the Static Video Player **320**.

The Static Audio Player **120** is a computer software program executed by a conventional computer system. The Static Audio Player **120** is a means by which playback of the Static Audio File **110** through the sound card of the host computer system is possible in either digital audio form or analog audio form. The Static Audio Player **120** is designed to process the encoded information of the Static Audio File **110** for subsequent audio playback and/or replication. The Static Audio Player **120** invokes a sequential serial replication (i.e. a serial data replication is the process whereby the original copy of data is replicated, transmitted, and saved in series to a buffer memory) of sound information from the Static Audio File **110** and saves said sound information into a time interval buffer memory within the Static Audio Player **120**. Next, the Static Audio Player **120** invokes a sequential parallel data dump of said sound information by time interval from the time interval memory buffer into a matrix of frequency/amplitude memory registers Static Audio Player **120**. Next, the Static Audio Player **120** invokes a sequential parallel data replication of the sound information in the frequency/amplitude memory registers to the sound card buffer memory within the Static Audio Player **120**. Next, the Static Audio Player **120** invokes a sequential parallel data dump of the sound information in the sound card buffer memory to the sound card of the host computer system, whereupon the sound card relays/transmits the sound information to the Audio Output Device **190**. Each amplitude of each frequency is pre-assigned, or corresponds, to a specific frequency/amplitude memory register. The Static Audio Player **120** activates, or deactivates, the memory register corresponding to a discrete frequency/amplitude upon instruction from the Static Audio File **110** (i.e. a binary "**1**" activates, or is saved into, a frequency/amplitude memory register and a binary "**0**" deactivates, erases, or is saved into, said frequency/amplitude memory register). If the memory register of a discrete frequency/amplitude has been activated, or contains a binary "**1**", then the Static Audio Player **120** will playback, and/or replicate, that frequency/amplitude until its memory register has been deactivated, erased, or contains a binary "**0**". The Static Audio Player **120** may be configured to contain the functionality of the Dynamic Video Player **70**, the Frequency/Amplitude Database Compiler **80**, and the Dynamic to Static Audio Truncator **100**.

The Static Audio Player **120** is also a means to playback a Static Audio File **110**, **150**, and/or **170** in dynamic digital form on a digital Audio Output Device **190** with playback output being in digital form or (i.e. digital stereo speakers, etc.); or playback in analog form on an analog Audio Output Device **190** (i.e. analog stereo speakers, etc.) for listening by the user. The Static Audio Player **120** can playback the Static Audio File **110**, **150**, and/or **170** in static digital form to save computational instructions as a Static Audio File **170**. The Static Audio Player **120** can playback a Static Audio File **110**, **150**, and/or **170** in dynamic digital form to save computational instructions as a Dynamic Audio File **180**.

Additionally, the Static Audio Player **120** is a means to playback a Dynamic Audio File **160** and/or **180**, in dynamic digital form on an Audio Output Device **190** with playback output being in digital form or (i.e. digital stereo speakers, etc.); or playback in analog form on an Audio Output Device **190** (i.e. analog stereo speakers, etc.) for listening by the user. The Static Audio Player **120** can playback the Dynamic Audio File **160** and/or **180**, in static digital form to save computational instructions as a Static Audio File **170**. The Static Audio Player **120** can playback the Dynamic Audio File **160** and/or **180**, in dynamic digital form to save computational instructions as a Dynamic Audio File **180**.

Furthermore, the Static Audio Player **120** can receive computational instructions from a Static Audio File **150** or a Dynamic Audio File **160** (i.e. in broadcast fashion, download fashion (i.e. U.S. Pat. No. 5,191,573), etc.) by means of the Static Audio Player **130** via an Electronic Connection **140** (such as, but not limited to, transmission via: direct connect network, satellite, cable TV, coax cable, fiber optics, fiber/coax hybrid, Internet, cellular, microwave, radio, twisted pair telephone, ISDN telephone, T-1 telephone, DS-3 telephone, OC-3 telephone, etc.).

The Static Audio Player **120** and the Static Video Player **320** may be combined into one device enabling the simultaneous playback of recordings which are the combination of the Static Audio File **110**, **150**, and/or **170** and the Static Video File **310**, **350**, and/or **370**.

The Static Audio Player **130** is a means by which a Static Audio File **150** and/or a Dynamic Audio File **160** may be electronically transmitted (i.e. in broadcast fashion, download fashion (i.e. U.S. Pat. No. 5,191,573), etc.) to the Static Audio Player **120** via an Electronic Connection **140** for subsequent and/or real-time playback.

The Electronic Connection **140** (such as, but not limited to, transmission via: direct connect network, satellite, cable TV, coax cable, fiber optics, fiber/coax hybrid, Internet, cellular, microwave, radio, twisted pair telephone, ISDN telephone, T-1 telephone, DS-3 telephone, OC-3 telephone, etc.) is a means by which a Static Audio Player **130** of a first computer system and a Static Audio Player **120** of a second computer system can be electronically connected. The Static Audio Player **120** and the Static Audio Player **130** may be configured to have all, or some, of the same functionality and capabilities as the other.

The Static Audio File **150** is encoded in a digital file format which records a plurality of discrete frequency/amplitude information and the respective starting points and ending points, with respect to time. The Static Audio File **150** is encoded in a format which is compatible for use by the Static Audio Player **120** and/or **130**. The Static Audio File **150** is formatted in the same digital audio file format as the Static Audio File **110** and/or **170**.

The Dynamic Audio File **160** (i.e. AUI, WAV, etc.) is encoded in a digital file format which contains a plurality of frequency/amplitude information by time interval. The Dynamic Audio File **160** is formatted in the same digital audio file format as the Dynamic Audio File **60** and/or **180**.

The Static Audio File **170** is encoded in a digital file format which records a plurality of discrete frequency/amplitude information and the respective starting points and ending points, with respect to time and can be produced by the Static Audio Player **120**. The Static Audio File **170** is encoded in a format which is compatible for use by the Static Audio Player **120** and/or **130**. The Static Audio File **170** is formatted in the same digital audio file format as the Static Audio File **110** and/or **150**.

The Dynamic Audio File **180** (i.e. AUI, WAV, etc.) is encoded in a digital file format which contains a plurality of frequency/amplitude information by time interval and can be produced by the Static Audio Player **120**. The Dynamic Audio File **180** can be formatted in the same digital audio file format as the Dynamic Audio File **60** and/or **160**.

The Audio Output Device **190** (i.e. digital and/or analog stereo speakers, etc.) is the means by which sound can be produced, in either digital or analog form, when the Static Audio File **110**, **150**, and/or **170** or the Dynamic Audio file **160** and/or **180** is played by means of the Static Audio Player **120**. The Audio Output Device **190** is electronically connected to, and receives sound information from, a conventional computer sound card. The Audio Output Device **190** can be either a digital device or an analog device.

With respect to FIG. **1**, the invention records the Analog Audio Source **10**, being any form of audio source, by means of either an Analog Audio Recorder **20** or an Analog to Digital Audio Recorder **50**. The Analog Audio Recorder **20** is a device which records, and/or plays, analog audio signals (i.e. cassette tape recorder/player, etc.). If the Analog Audio Recorder **20** is used, an Analog Audio File **30** is produced which is then converted into a Dynamic Audio File **60** by means of Analog to Digital Audio Converter **40**. The Analog to Digital Audio Converter **40** is a device which converts analog audio signals into digital audio signals. If an Analog to Digital Audio Recorder **50** is used, a Dynamic Audio File **60** is directly produced. The Analog to Digital Audio Recorder **50** is a device which can convert analog audio signals directly into digital audio signals, can record digital audio signals, and can playback digital audio signals.

The Dynamic Audio File **60** is encoded in a format which contains a plurality of frequency/amplitude information by time interval (i.e. AUI, WAV, etc.) and can be easily edited and/or electronically manipulated. As example, and assuming that a Dynamic Audio File **60** is composed of a plurality of discrete sounds identified by their frequencies and their related amplitudes are mathematically expressed as time interval (I), frequency (F), and amplitude (A), where I_w identifies a discrete time interval within a range of intervals identified by subscript "w", and bounded by the first time interval and the last time interval of the audio recording; and F_x, identifies a discrete frequency within a range of frequencies identified by subscript "x"; and A_y identifies a specific amplitude, associated with said frequency F_x, within a range of amplitudes identified by subscript "y"; and assuming the following information after the equals sign is expressed in binary terms: F_0=00000; F_1=00001; F_2=00010; F_5=00101; A_0=0000; A_1=0001; A_2=0010; and A_3=0011; where F_1A_1, F_2A_1, F_2A_2, F_5A_1, F_5A_2, and F_5A_3 represent sounds and F_0A_0 represents the lack of sound, furthermore, the Dynamic Audio File **60** mathematically represents a consecutive pattern of sound as the algorithm "$I_w=F_xA_y$", and expressed in binary terms as: I_1=00001 0001 00010 0001 00010 0010; I_2=00001 0001 00010 0001 00010 0010; I_3=00001 0001 00010 0001 00010 0010; I_4=00001 0001 00010 0001 00010 0010 00101 0001 00101 0010 00101 0011; I_5=00001 0001 00010 0001 00010 0010 00101 0001 00101 0010 00101 0011; I_6=00001 0001 00101 0001 00101 0010 00101 0011; I_7=00001 0001 00101 0001 00101 0010 00101 0011; and I_8=00000 0000; which mathematically represents an audio recording whereby a sound F_1A_1 is to be played during time intervals I_1, I_2, I_3, I_4, I_5, I_6, and I_7; and sounds F_2A_1, and F_2A_2 are to be played during time intervals I_1, I_2, I_3, I_4, and I_5; and sounds F_5A_1, F_5A_2, and F_5A_3 are to be played during time intervals I_4, I_5, I_6, and I_7; and no sound is to be played in time interval I_8 (see FIG. **7**). The data string for each time interval I_w is composed of pairs of groups of binary information, the first group in any pair identifies the frequency F_x; and the second group in any pair identifies the amplitude A_y of said frequency F_x. Further clarifying of this example, the "00001" in the first group of the first pair of binary information in the data string associated with time interval I_1 identifies a discrete frequency F_1; the "0001" in the second group of the first pair of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_1 of said frequency F_1; and a specific sound F_1A_1 was consistently present in the audio recording during the time intervals from I_1 to I_7, and then the sound F_1A_1 is no longer present, or to be played, in time interval I_8. Additionally, the "00010" in the first group of the third pair of binary information in the data string associated with time intervals I_1 to I_5 identifies a discrete frequency F_2; the "0010" in the second group of the third pair of binary information in the data string associated with time intervals I_1 to I_5 identifies the specific amplitude A_2 of said frequency F_2; therefore a specific sound F_2A_2 was consistently present in the audio recording during the time intervals I_1 to I_5, and then the sound F_2A_2 is no longer present, or to be played, in time intervals I_6 to I_8. Furthermore, the "00101" in the first group of the sixth pair of binary information in the data string associated with time intervals I_4 and I_5 and the "00101" in the first group of the fourth pair of binary information in the data string associated with time intervals I_6 and I_7 identifies a discrete frequency F_5; the "0011" in the second group of the sixth pair of binary information in the data string associated with time intervals I_4 and I_5 and the "0011" in the second group of the fourth pair of binary information in the data string associated with time intervals I_6 and I_7 identifies the specific amplitude A_3 of said frequency F_5; therefore a specific sound F_5A_3 was consistently present in the audio recording during the time intervals I_4 to I_7, and then the sound F_5A_3 is no longer present, or to be played, in time interval I_8. The "00000" in the first group of the only pair of binary information in the data string associated with time interval I_8 represents the lack of a discrete frequency, or is represented as F_0; the "0000" in the second group of the only pair of binary information in the data string associated with time interval I_8 represents the lack of a specific amplitude, or is represented as A_0, of said frequency F_0; therefore F_0A_0 indicates that no sound was present in the audio recording during the time interval I_8. The Dynamic

Audio File **60** records discrete frequency/amplitude information for each, and every, time interval.

Playback of the Dynamic Audio File **60** is accomplished by means of a Dynamic Audio Player **70**.

The Frequency/Amplitude Database Compiler **80** is a computer software program executed by the host computer system, which inputs sound information from the Dynamic Audio File **60** into the Frequency/Amplitude Database Compiler **80** and converts the Dynamic Audio File **60** into a Frequency/Amplitude Database **90**. As example, the Frequency/Amplitude Database **90** can be composed of a three-dimensional matrix defined by three axes: time interval (I), frequency (F), and amplitude (A). For each time interval I_w and each possible amplitude A_y of each possible frequency F_x exists a unique matrix cell f_xa_y. As example, each matrix cell either has sound or lacks sound and can be mathematically expressed in binary terms by a "**1**" for the presence of sound or by a "**0**" (or no entry at all) for the lack of sound. The range of the frequency F_x and the range of the amplitude A_y and the range of time intervals I_w (or time intervals per second) can vary from application to application. As example, CD quality sound is generally, but not always, limited to frequencies and amplitudes which the human ear can perceive and each second of sound is divided into 44,100 discrete time intervals. The Frequency/Amplitude Database Compiler **80** accesses the sound information in the Dynamic Audio File **60** and invokes a serial data replication of said sound information to the Frequency/Amplitude Database Compiler **80** (see FIG. **12**). Next, the Frequency/Amplitude Database Compiler **80** performs a sort routine with a primary sort by frequency/amplitude F_xA_y and a secondary sort by time interval I_w (first time interval first, last time interval last). Next, the Frequency/Amplitude Database Compiler **80** saves said sorted/collated sound information as a Frequency/Amplitude Database **90**. The Frequency/Amplitude Database Compiler **80** can save the Frequency/Amplitude Database **90** on the computer hard disk of said host computer system. The Frequency/Amplitude Database Compiler **80** can electronically relay/transmit the Frequency/Amplitude Database **90** directly to the Dynamic to Static Audio Truncator **100**.

Furthermore, the invention utilizes the Dynamic to Static Audio Truncator **100** which is a computer software program to be executed by the host computer system, to mathematically analyze the matrix of the Frequency/Amplitude Database and identify patterns of consecutive sound entries over time for a specific amplitude of a discrete frequency. The Dynamic to Static Audio Truncator **100** creates a Static Audio File **110**. The Dynamic to Static Audio Truncator **100** accesses the sorted/collated sound information in the Frequency/Amplitude Database **90** and invokes a serial data dump/replication of said sound information to the Dynamic to Static Audio Truncator **100** (see FIG. **13**). Next, the Dynamic to Static Audio Truncator **100** identifies repetition strings of frequencies/amplitudes F_xA_y. Next, the Dynamic to Static Audio Truncator **100** converts the first occurrence of sound information in the repetition strings of frequencies/amplitudes F_xA_y to an "on" code (or a binary "**1**") in the corresponding matrix cell f_xa_y in the corresponding time interval I_w. Next, the Dynamic to Static Audio Truncator **100** saves an "off" code (or a binary "0") in the time interval I_w immediately following the last occurrence of sound information in the repetition strings of frequencies/amplitudes F_xA_y in the corresponding matrix cell f_xa_y. Next, the Dynamic to Static Audio Truncator **100** erases all occurrences of sound information related to said repetition strings of frequencies/amplitudes F_xA_y between the "on" code and the "off" code. At this point, the sound information has been truncated and the only remaining sound information with respect to said repetition strings of frequencies/amplitudes F_xA_y are "on" codes and "off" codes. Next, the Dynamic to Static Audio Truncator **100** performs a sort routine of said truncated sound information with a primary sort by time interval I_w (first time interval first, last time interval last) and a secondary sort by frequency/amplitude F_xA_y. Next, the Dynamic to Static Audio Truncator **100** saves said sorted and truncated sound information as a Static Audio File **110**. The Dynamic to Static Audio Truncator **100** can save the Static Audio File **110** on the computer hard disk of said host computer system. The Dynamic to Static Audio Truncator **100** can electronically relay/transmit the Static Audio File **110** directly to the Static Audio Player **120**.

The Static Audio File **110** contains information such as, but not limited to, discrete frequencies and their related amplitudes; the related starting points when each such frequency/amplitude shall commence to be played, and/or commence to be replicated, with respect to time; and the related ending points when each such frequency/amplitude shall cease being played, and/or cease to be replicated, with respect to time. As example, and assuming that discrete sounds identified by their frequency and related amplitude are mathematically expressed as time interval (I), frequency (F), amplitude (A), time (t), and status (s), where I_w identifies a discrete time interval within a range of time intervals identified by the subscript "w", which is bounded by the start time and finish time of the audio recording; and F_x identifies a discrete frequency within a range of frequencies identified by subscript "x"; and A_y identifies a specific amplitude, associated with said frequency F_x, within a range of amplitudes identified by subscript "y"; and time t_z identifies a discrete moment in time within a range of time identified by the subscript "z" which is bounded by the start time and finish time of the audio recording, and t_z identifies when the corresponding time interval I_w is to commence to be played, and/or to commence to be replicated; and s_m identifies the status of said frequency/amplitude F_xA_y identified by subscript "m" where a "1" identifies the status of said frequency/amplitude F_xA_y as activated, and a "0" identifies the status of said frequency/amplitude F_xA_y as deactivated; and further assuming the following information after the equals sign is expressed in binary terms: F_1=00001; F_2=00010; F_5=00101; A_0=0000; A_1=0001; A_2=0010; and A_3=0011; t_1=0000001; t_2=0000010; t_3=0000011; t_4=0000100; t_5=0000101; t_6=0000110; t_7=0000111; t_8=0001000; s_0=0; and s_1=1; the Static Audio File **110** mathematically represents the same consecutive pattern of sound, as used in the example above for the Dynamic Audio File **60**, as the algorithm "$I_w=F_xA_yt_zs_m$", and expressed in binary terms as: I_1=00001 0001 0000001 1 00010 0001 0000001 1 00010 0010 0000001 1; I_4=00101 0001 0000100 1 00101 0010 0000100 1 00101 0011 0000100 1; I_6=00010 0001 0000110 0 00010 0010 0000110 0; and I_8=00001 0001 0001000 0 00101 0001 0001000 0 00101 0010 0001000 0 00101 0011 0001000 0; which mathematically represents an audio recording whereby a sound F_1A_1, is to be played during time intervals I_1, I_2, I_3, I_4, I_5, I_6, and I_7; and sounds F_2A_1 and F_2A_2 are to be played during time intervals I_1, I_2, I_3, I_4, and I_5; and sounds F_5A_1, F_5A_2, and F_5A_3 are to be played during time intervals I_4, I_5, I_6, and I_7; and no sound is to be played in time interval I_8 (see FIG. **9**). The data string for each time interval I_w is composed of sets of four groups of binary information, the first group in any set identifies the frequency F_x; the second group in any set identifies the amplitude A_y of said frequency F_x; the third

group in any set identifies the time t_z corresponding to time interval I_w when said frequency/amplitude F_xA_y is to commence or cease to be played, and/or replicated; and the fourth group in any set identifies the status s_m of the frequency/amplitude F_xA_y and contains either a binary "1" to instruct the Static Audio Player **120** to commence to play, and/or commence to replicate, said frequency/amplitude F_xA_y, or a binary "0" to instruct the Static Audio Player **120** to cease to playing, and/or cease replicating, said frequency/amplitude F_xA_y. In the example above, and as further clarification, the "00001" in the first group of the first set of binary information in the data string associated with time interval I_1 identifies a discrete frequency $\#F_1$; the "0001" in the second group of the first set of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_1, of said frequency F_1; the "0000001" in the third group of the first set of binary information in the data string associated with time interval I_1 identifies the time t_1 corresponding to time interval I_1 when said frequency/amplitude F_1A_1 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the first set of binary information in the data string associated with time interval I_1 identifies the status s_1 of said frequency/amplitude F_1A_1 and provides the Static Audio Player **120** the instruction to commence to play, and/or commence to replicate, said frequency/amplitude F_1A_1, at time t_1 (see FIG. **3**); and the "00001" in the first group of the first set of binary information in the data string associated with time interval I_8 identifies a discrete frequency F_1; the "0001" in the second group of the first set of binary information in the data string associated with time interval I_8 identifies the specific amplitude A_1 of said frequency F_1; the "0001000" in the third group of the first set of binary information in the data string associated with time interval I_8 identifies the time t_8 when said frequency/amplitude F_1A_1 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the first set of binary information in the data string associated with time interval I_8 identifies the status s_0 of said frequency/amplitude F_1A_1 and provides the Static Audio Player **120** the instruction to cease to play, and/or cease to replicate, said frequency/amplitude F_1A_1 at time interval I_8 (see FIG. **4**). Additionally, the "00010" in the first group of the third set of binary information in the data string associated with time interval I_1 identifies a discrete frequency F_2; the "0010" in the second group of the third set of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_2 of said frequency F_2; the "0000001" in the third group of the third set of binary information in the data string associated with time interval I_1 identifies the time t_1 corresponding to time interval I_1 when said frequency/amplitude F_2A_2 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the third set of binary information in the data string associated with time interval I_1 identifies the status s_1 of said frequency/amplitude F_2A_2 and provides the Static Audio Player **120** the instruction to commence to play, and/or commence to replicate, said frequency/amplitude F_2A_2 at time t_1; and the "00010" in the first group of the second set of binary information in the data string associated with time interval I_6identifies a discrete frequency F_2; the "0010" in the second group of the second set of binary information in the data string associated with time interval I_6 identifies the specific amplitude A_2 of said frequency F_2; the "0000110" in the third group of the second set of binary information in the data string associated with time interval I_6 identifies the time t_6 when said frequency/amplitude F_2A_2 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the second set of binary information in the data string associated with time interval I_6 identifies the status s_0 of said frequency/amplitude F_2A_2 and provides the Static Audio Player **120** the instruction to cease to play, and/or cease to replicate, said frequency/amplitude F_2A_2 at time interval I_6, therefore a specific sound F_2A_2 was consistently present in the audio recording during the time intervals I_1 to I_5, and then the sound F_2A_2 is no longer present, or to be played, in time intervals I_6 to I_8. Furthermore, the "00101" in the first group of the sixth pair of binary information in the data string associated with time interval I_4 identifies a discrete frequency F_5; the "0011" in the second group of the sixth pair of binary information in the data string associated with time interval I_4 identifies the specific amplitude A_3 of said frequency F_5 ; the "0000100" in the third group of the third set of binary information in the data string associated with time interval I_4 identifies the time t_4 corresponding to time interval I_4 when said frequency/amplitude F_5A_3 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the third set of binary information in the data string associated with time interval I_4 identifies the status s_1 of said frequency/amplitude F_5A_3 and provides the Static Audio Player **120** the instruction to commence to play, and/or commence to replicate, said frequency/amplitude F_5A_3 at time t_4; and the "00101" in the first group of the fourth set of binary information in the data string associated with time interval I_8 identifies a discrete frequency F_5; the "0011" in the second group of the fourth set of binary information in the data string associated with time interval I_8 identifies the specific amplitude A_3 of said frequency F_5; the "0001000" in the third group of the fourth set of binary information in the data string associated with time interval I_8 identifies the time t_8 when said frequency/amplitude F_5A_3 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the fourth set of binary information in the data string associated with time interval I_8 identifies the status s_0 of said frequency/amplitude F_5A_3 and provides the Static Audio Player **120** the instruction to cease to play, and/or cease to replicate, said frequency/amplitude F_5A_3 at time interval I_8, therefore a specific sound F_5A_3 was consistently present in the audio recording during the time intervals I_4 to I_7, and then the sound F_5A_3 is no longer present, or to be played, in time interval I_8. The Static Audio File **110** is saved in the hard disk of the host computer system containing the Static Audio Player **120** and the Static Audio File **150** is saved in the hard disk of the computer system containing the Static Audio Player **130**.

The Static Audio Player **120** is a computer software program saved in the hard disk of the host computer system. When the Static Audio Player **120** is activated, the central processing unit of the host computer system transmits a copy of the program to random access memory within the host computer system for execution of the various functions of the Static Audio Player **120**, as is convention with most computer software programs. The Static Audio Player **120** accesses the Static Audio File **110** and replicates and saves sound information from the Static Audio File **110** into a time interval buffer memory within the Static Audio Player **120**. The Static Audio Player **120** then transmits said sound information from said time interval buffer memory to the frequency/amplitude memory registers within the Static Audio Player **120**, one time interval at a time. As example, the Static Audio Player **120** accesses the Static Audio File **110** and invokes a serial data replication of the sound information related to the first time interval into a frequency/

amplitude matrix within a time interval buffer memory within the Static Audio Player **120**. The Static Audio Player **120** then invokes a parallel data dump of said sound information related to the first time interval from said time interval buffer memory to the frequency/amplitude memory registers within the Static Audio Player **120**. The Static Audio Player **120** then invokes a parallel data dump (i.e. a data dump is the process whereby data in a buffer memory is electronically transmitted to another mechanism or memory then is electronically erased from said buffer memory) of said sound information related to the first time interval from said time interval buffer memory to said frequency/amplitude memory registers. As the Static Audio Player **120** invokes a parallel data dump of said sound information related to the first time interval from said time interval buffer memory to said frequency/amplitude memory registers, the Static Audio Player **120** accesses the Static Audio File **110** and invokes a serial data replication of the sound information related to the second time interval into said frequency/amplitude memory matrix within said time interval buffer memory within the Static Audio Player **120**. As the Static Audio Player **120** invokes a parallel data dump of the sound information related to the first time interval from said frequency/amplitude memory registers to a sound card buffer memory within the Static Audio Player **120** (as discussed herein below) the Static Audio Player **120** invokes a parallel data dump of said sound information related to the second time interval from said time interval buffer memory to said frequency/amplitude memory registers. The sound information in the third time interval, forth time interval, fifth time interval, etc. will continue in the above manner until the end of the Static Audio File **110**.

As mentioned above, the Static Audio Player **120** saves sound information from the Static Audio File **110** into a matrix of frequency/amplitude memory registers f_xa_y within the Static Audio Player **120**. Each frequency/amplitude F_xA_y is pre-assigned to a specific frequency/amplitude memory register f_xa_y. The Static Audio Player **120** activates, or deactivates, the memory register f_xa_y of a discrete frequency/amplitude F_xA_y upon instruction from the Static Audio File **110**. As example, a binary "1" activates, or is saved into, a frequency/amplitude memory register f_xa_y and a binary "0" deactivates, erases, or is saved into, said frequency/amplitude memory register f_xa_y. It is important to note that if any of the frequency/amplitude memory registers do not receive a data dump for any particular time interval I_w, those such frequency/amplitude memory registers f_xa_y will not be modified for any such time interval I_w. Furthermore, once a binary "1" has been saved in a frequency/amplitude memory register f_xa_y corresponding to a frequency/amplitude F_xA_y the Static Audio Player **120** does not need to receive any further sound information from the Static Audio File **110** to enable the Static Audio Player **120** to continue to play, and/or replicate, said frequency/amplitude F_xA_y on an Audio Output Device **190**. Conversely, once a binary "0" has been saved in said frequency/amplitude memory register f_xa_y corresponding to a frequency/amplitude F_xA_y, or said frequency/amplitude memory register f_xa_y has been erased and/or deactivated, the Static Audio Player **120** does not need to receive any further sound information from the Static Audio File **110** to enable the Static Audio Player **120** to continue to cease play of, and/or cease replication of, said frequency/amplitude F_xA_y on an Audio Output Device **190**. Using the previous example where the Static Audio File **110** mathematically represents an audio recording as the algorithm "$I_w=F_xA_yt_zs_m$", and expressed in binary terms as: I_1=00001 0001 0000001 1 00010 0001 0000001 1 00010 0010 0000001 1; I_4=00101 0001 0000100 1 00101 0010 0000100 1 00101 0011 0000100 1; I_6=00010 0001 0000110 0 00010 0010 0000110 0; and I_8=00001 0001 0001000 0 00101 0001 0001000 0 00101 0010 0001000 0 00101 0011 0001000 0; which mathematically represents an audio recording whereby a sound F_1A_1 is to be played during time intervals I_1, I_2, I_3, I_4, I_5, I_6, and I_7; and sounds F_2A_1 and F_2A_2 are to be played during time intervals I_1, I_2, I_3, I_4 and I_5; and sounds F_5A_1, F_5A_2, and F_5A_3 are to be played during time intervals I_4, I_5, I_6, and I_7; and no sound is to be played in time interval I_8 (see FIG. **9**). As further clarification, only said sounds F_1A_1, F_2A_2, and F_5A_3 are discussed below, detailing the process the Static Audio Player **120** utilizes to replicate sound information from the Static Audio File **110** to the frequency/amplitude memory registers within the Static Audio Player **120**. The "00001" in the first group of the first set of binary information in the data string associated with time interval I_1 identifies a discrete frequency F_1; the "0001" in the second group of the first set of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_1 of said frequency F_1; the "0000001" in the third group of the first set of binary information in the data string associated with time interval I_1 identifies the time t_1 when said frequency/amplitude F_1A_1 is to commence to be played and/or replicated; and the "1" in the fourth group of the first set of binary information in the data string associated with time interval I_1 identifies the status s_1 of said frequency/amplitude F_1A_1 and upon commencing the sequential serial transmission of sound information by time interval from the Static Audio File **110**, the Static Audio Player **120** replicates and saves sound information related to time interval I_1 from the Static Audio File **110** into the time interval buffer memory, including said "1" in said fourth group of said first set of binary information in said data string associated with time interval I_1 and then the Static Audio Player **120** invokes a parallel data dump of all sound information related to time interval I_1 from the time interval buffer memory to the frequency/amplitude memory registers, including said "1" in said fourth group of said first set of binary information in said data string associated with time interval I_1 which is saved in the f_1a_1 memory register within the Static Audio Player **120** at time t_1. The "00001" in the first group of the first set of binary information in the data string associated with time interval I_8 identifies a discrete frequency F_1; the "0001" in the second group of the first set of binary information in the data string associated with time interval I_8 identifies the specific amplitude A_1 of said frequency F_1; the "0001000" in the third group of the first set of binary information in the data string associated with time interval I_8 identifies the time t_8 when said frequency/amplitude F_1A_1 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the first set of binary information in the data string associated with time interval I_8 identifies the status s_0 of said frequency/amplitude F_1A_1 and when the sequential serial transmission of sound information by time interval reaches the point when sound information related to time interval I_8 is to be accessed from the Static Audio File **110**, the Static Audio Player **120** replicates and saves sound information related to time interval I_8 from the Static Audio File **110** into the time interval buffer memory, including said "0" in said fourth group of said first set of binary information in said data string associated with time interval I_8, and then the Static Audio Player **120** invokes a parallel data dump of all sound information related to time interval I_8 from the time interval buffer memory to the frequency/amplitude memory registers, including said "0" in said fourth group of said first

set of binary information in said data string associated with time interval I_8 which is saved in the f_1a_1 memory register within the Static Audio Player **120** at time t_8. Additionally, the "00010" in the first group of the third set of binary information in the data string associated with time interval I_1 identifies a discrete frequency F_2; the "0010" in the second group of the third set of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_2 of said frequency F_2; the "0000001" in the third group of the third set of binary information in the data string associated with time interval I_1 identifies the time t_1 corresponding to time interval I_1 when said frequency/amplitude F_2A_2 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the third set of binary information in the data string associated with time interval I_1 identifies the status s_1 of said frequency/amplitude F_2A_2 and upon commencing the sequential serial transmission of sound information by time interval from the Static Audio File **110**, the Static Audio Player **120** replicates and saves sound information related to time interval I_1 from the Static Audio File **110** into the time interval buffer memory, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_1, and then the Static Audio Player **120** invokes a parallel data dump of all sound information related to time interval I_1 from the time interval buffer memory to the frequency/amplitude memory registers, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_1 which is saved in the f_2a_2 memory register within the Static Audio Player **120** at time t_1. The "00010" in the first group of the second set of binary information in the data string associated with time interval I_6 identifies a discrete frequency F_2; the "0010" in the second group of the second set of binary information in the data string associated with time interval I_6 identifies the specific amplitude A_2 of said frequency F_2; the "0000110" in the third group of the second set of binary information in the data string associated with time interval I_6 identifies the time t_6 when said frequency/amplitude F_2A_2 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the second set of binary information in the data string associated with time interval I_6 identifies the status s_0 of said frequency/amplitude F_2A_2 and when the sequential serial transmission of sound information by time interval reaches the point when sound information related to time interval $I_6$is to be accessed from the Static Audio File **110**, the Static Audio Player **120** replicates and saves sound information related to time interval $I_6$from the Static Audio File **110** into the time interval buffer memory, including said "0" in said fourth group of said second set of binary information in said data string associated with time interval I_6, and then the Static Audio Player **120** invokes a parallel data dump of all sound information related to time interval $I_6$from the time interval buffer memory to the frequency/amplitude memory registers, including said "0" in said fourth group of said second set of binary information in said data string associated with time interval I_6 which is saved in the f_2a_2 memory register within the Static Audio Player **120** at time I_6. Furthermore, the "00101" in the first group of the sixth pair of binary information in the data string associated with time interval I_4 identifies a discrete frequency F_5; the "0011" in the second group of the sixth pair of binary information in the data string associated with time interval I_4 identifies the specific amplitude A_3 of said frequency F_5,; the "0000100" in the third group of the third set of binary information in the data string associated with time interval I_4 identifies the time t_4 corresponding to time interval I_4 when said frequency/amplitude F_5A_3 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the third set of binary information in the data string associated with time interval I_4 identifies the status s_1 of said frequency/amplitude F_5A_3 and when the sequential serial transmission of sound information by time interval reaches the point when sound information related to time interval I_4 is to be accessed from the Static Audio File **110**, the Static Audio Player **120** replicates and saves sound information related to time interval I_4 from the Static Audio File **110** into the time interval buffer memory, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_4, and then the Static Audio Player **120** invokes a parallel data dump of all sound information related to time interval I_4 from the time interval buffer memory to the frequency/amplitude memory registers, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_4 which is saved in the f_2a_2 memory register within the Static Audio Player **120** at time t_4. The "00101" in the first group of the fourth set of binary information in the data string associated with time interval I_8 identifies a discrete frequency F_5; the "0011" in the second group of the fourth set of binary information in the data string associated with time interval I_8 identifies the specific amplitude A_3 of said frequency F_5; the "0001000" in the third group of the fourth set of binary information in the data string associated with time interval I_8 identifies the time t_8 when said frequency/amplitude F_5A_3 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the fourth set of binary information in the data string associated with time interval I_8 identifies the status s_0 of said frequency/amplitude F_5A_3 and when the sequential serial transmission of sound information by time interval reaches the point when sound information related to time interval I_8 is to be accessed from the Static Audio File **110**, the Static Audio Player **120** replicates and saves sound information related to time interval I_8 from the Static Audio File **110** into the time interval buffer memory, including said "0" in said fourth group of said fourth set of binary information in said data string associated with time interval I_8, and then the Static Audio Player **120** invokes a parallel data dump of all sound information related to time interval I_8 from the time interval buffer memory to the frequency/amplitude memory registers, including said "0" in said fourth group of said fourth set of binary information in said data string associated with time interval I_8 which is saved in the f_5a_3 memory register within the Static Audio Player **120** at time I_8.

Furthermore, the invention utilizes the Static Audio Player **120** to playback, and/or replicate, sound information saved from the Static Audio File **110** into the frequency/amplitude memory registers in the Static Audio Player **120**. The Static Audio Player **120** sequentially replicates, one time interval at a time, the sound information contained in all of the frequency/amplitude memory registers into a sound card buffer memory within the Static Audio Player **120**. Next, the Static Audio Player **120** transmits said sound information to the sound card of the host computer. Upon receipt of the sound information, said sound card transmits said sound information to the Audio Output Device **190** for playback. As example, the Static Audio Player **120** invokes a parallel data replication of the sound information related to the first time interval from the frequency/amplitude memory registers to a sound card buffer memory within the Static Audio Player **120**. Next, the Static Audio Player **120** invokes a parallel data dump of the sound information related to the

first time interval from the sound card buffer memory, sequentially by time interval and at the intended playback rate (i.e. 44,100 time intervals per second for CD quality sound), to said sound card through an electronic connecting bus, and said sound card transmits/relays, in either digital form or analog form, said sound information related to said first time interval to the Audio Output Device **190** for playback. While the Static Audio Player **120** invokes a parallel data replication of the sound information related to said first time interval from the frequency/amplitude memory registers to said sound card buffer memory, the Static Audio Player **120** also invokes a parallel data dump of the sound information related to the second time interval from the time interval buffer memory (as mentioned hereinabove) to said frequency/amplitude memory registers. While the Static Audio Player **120** invokes a parallel data dump of the sound information related to said first time interval from said sound card buffer memory to said sound card, the Static Audio Player **120** also invokes a parallel data replication of the sound information related to the second time interval from said frequency/amplitude memory registers to said sound card buffer memory. While said sound card transmits/relays the sound information related to said first time interval to the Audio Output Device **190** for playback, the Static Audio Player **120** invokes a parallel data dump of the sound information related to the second time interval from the sound card buffer memory to said sound card through said electronic connecting bus, and said sound card transmits/relays, in either digital form or analog form, said sound information related to said second time interval to the Audio Output Device **190** for playback. The sound information in the third time interval, forth time interval, fifth time interval, etc. will continue in the above manner until the end of the Static Audio File **110**.

Additionally, the invention utilizes the Static Audio Player **120** to playback, and/or replicate, sound information saved from the Static Audio File **150** into the frequency/amplitude memory registers in the Static Audio Player **120** in a similar manner as mentioned above for the sound information received by the Static Audio Player **120** by the Static Audio File **110**. The Static Audio Player **120** may receive sound information from the Static Audio File **150** via the Electronic Connection **140** in a download fashion or in a broadcast fashion. As example, in a download transmission, a Static Audio Player **130** of a sending computer system creates an electronic copy of a Static Audio File **150** and transmits said Static Audio File **150** serially by means of a conventional modem electronically connecting said sending computer system to the Electronic Connection **140** and received by a receiving computer system by means of a conventional modem electronically connecting the receiving computer system to the Electronic Connection **140** and the sound information of the Static Audio File **150** is electronically stored in the hard disk of the receiving computer system as a Static Audio File **110** (i.e. U.S. Pat. No. 5,191,573). Also as example, in a broadcast transmission, a Static Audio Player **130** of a sending computer system creates an electronic copy of a Static Audio File **150** and transmits said Static Audio File **150** serially, and at the playback rate of the recording (i.e. 44,100 time intervals per second for CD quality sound), by means of a conventional modem electronically connecting the sending computer system to the Electronic Connection **140** and received by a Static Audio Player **120** of a receiving computer system by means of a conventional modem electronically connecting said receiving computer system to the Electronic Connection **140** and the sound information of said Static Audio File **150** is subsequently transmitted by the receiving Static Audio Player **120** to the sound card of the receiving computer system for playback on the Audio Output Device **190**.

The Static Audio Player **120** will playback, and/or replicate, discrete frequency/amplitude information corresponding to each memory register which is active, or contains a binary "1" . Conversely, the Static Audio Player **120** will cease playback, and/or replication, of any frequency/amplitude corresponding to any memory register which the Static Audio File **110** and/or **150** has instructed the Static Audio File **110** to deactivate, erase, or save a binary "0" within. Again, using the previous example where the Static Audio File **110** mathematically represents an audio recording as the algorithm "$I_w=F_xA_yt_2s_m$", and expressed in binary terms as: I_1=00001 0001 0000001 1 00010 0001 0000001 1 00010 0010 0000001 1; I_4=00101 0001 0000100 1 00101 0010 0000100 1 00101 0011 0000100 1; I_6=00010 0001 0000110 0 00010 0010 0000110 0; and I_8=00001 0001 0001000 0 00101 0001 0001000 0 00101 0010 0001000 0 00101 0011 0001000 0; which mathematically represents an audio recording whereby a sound F_1A_1 is to be played during time intervals I_1, I_2, I_3, I_4, I_5, I_6, and I_7; and sounds F_2A_1 and F_2A_2 are to be played during time intervals I_1, I_2, I_3, I_4, and I_5; and sounds F_5A_1, F_5A_2, and F_5A_3 are to be played during time intervals I_4, I_5, I_6, and I_7; and no sound is to be played in time interval I_8 (see FIG. **10**). As further clarification, only said sounds F_2A_1, F_2A_2, and F_5A_3 are discussed below, detailing the process the Static Audio Player **120** utilizes to play sound information from the frequency/amplitude memory registers within the Static Audio File **110** to the Audio Output Device **190**. The "00001" in the first group of the first set of binary information in the data string associated with time interval I_1 identifies a discrete frequency F_1; the "0001" in the second group of the first set of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_1 of said frequency F_1; the "0000001" in the third group of the first set of binary information in the data string associated with time interval I_1 identifies the time t_1 when said frequency/amplitude F_1A_1 is to be played and/or replicated; and the "1" in the fourth group of the first set of binary information in the data string associated with time interval I_1 identifies the status s_1 of said frequency/amplitude F_1A_1 and enables the Static Audio Player **120** to activate, or save a binary "1" in, the f_1a_1 memory register within the Static Audio Player **120**, and upon commencing the sequential parallel data replication of sound information by time interval from the frequency/amplitude memory registers the Static Audio Player **120** invokes a sequential parallel data replication of sound information related to time interval I_1 from the frequency/amplitude memory registers to the sound card buffer memory, including said "1" in said fourth group of said first set of binary information in said data string associated with time interval I_1, and then the Static Audio Player **120** invokes a sequential parallel data dump of sound information related to time interval I_1 from the sound card buffer memory to the sound card of the host computer system, including said "1" in said fourth group of said first set of binary information in said data string associated with time interval I_1, and the sound card then relays/transmits sound information related to time interval I_1 to the Audio Output Device **190**, including frequency/amplitude F_1A_1 thereby enabling playback, and/or replication, of frequency/amplitude F_1A_1 at time t_1. The "00001" in the first group of the first set of binary information in the data string associated with time interval I_8 identifies a discrete frequency F_1; the "0001" in the second

group of the first set of binary information in the data string associated with time interval I_8 identifies the specific amplitude A_1 of said frequency F_1; the "0001000" in the third group of the first set of binary information in the data string associated with time interval I_8 identifies the time t_8 when said frequency/amplitude F_1A_1 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the first set of binary information in the data string associated with time interval I_8 identifies the status s_0 of said frequency/amplitude F_1A_1 and enables the Static Audio Player **120** to deactivate, erase, or save a binary "0" in, the f_1a_1 memory register within the Static Audio Player **120**, and when the sequential parallel data replication of sound information by time interval from the frequency/amplitude memory registers reaches the point when sound information related to time interval I_8 is to be replicated from the frequency/amplitude memory registers, the Static Audio Player **120** invokes a sequential parallel data replication of sound information related to time interval I_8 from the frequency/amplitude memory registers to the sound card buffer memory, including said "0" in said fourth group of said first set of binary information in said data string associated with time interval I_8. Next, the Static Audio Player **120** invokes a sequential parallel data dump of sound information related to time interval I_8 from the sound card buffer memory to the sound card of the host computer system, including said "0" in said fourth group of said first set of binary information in said data string associated with time interval I_8, and the sound card then relays/transmits sound information related to time interval I_8 to the Audio Output Device **190**, however, since said "0" in said fourth group of said first set of binary information in said data string associated with time interval I_8 is a signal to terminate playback of frequency/amplitude F_1A_1, the sound card terminates the relay/transmit of frequency/amplitude F_1A_1, to the Audio Output Device **190** thereby terminating playback, and/or replication, of frequency/amplitude F_1A_1 at time t_8. Additionally, the "00010" in the first group of the third set of binary information in the data string associated with time interval I_1 identifies a discrete frequency F_2; the "0010" in the second group of the third set of binary information in the data string associated with time interval I_1 identifies the specific amplitude A_2 of said frequency F_2; the "0000001" in the third group of the third set of binary information in the data string associated with time interval I_1 identifies the time t_1 corresponding to time interval I_1 when said frequency/amplitude F_2A_2 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the third set of binary information in the data string associated with time interval I_1 identifies the status s_1 of said frequency/amplitude F_2A_2 and enables the Static Audio Player **120** the activate, or save a binary "1" in, the f_2a_2 memory register within the Static Audio Player **120**, and upon commencing the sequential parallel data replication of sound information by time interval from the frequency/amplitude memory registers the Static Audio Player **120** invokes a sequential parallel data replication of sound information related to time interval I_1 from the frequency/amplitude memory registers to the sound card buffer memory, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_1. Next, the Static Audio Player **120** invokes a sequential parallel data dump of all sound information related to time interval I_1 from the sound card buffer memory to the sound card of the host computer system, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_1, and the sound card then relays/transmits sound information related to time interval I_1 to the Audio Output Device **190**, including frequency/amplitude F_2A_2 thereby enabling playback, and/or replication, of frequency/amplitude F_2A_2 at time t_1. The "00010" in the first group of the second set of binary information in the data string associated with time interval I_6 identifies a discrete frequency F_2; the "0010" in the second group of the second set of binary information in the data string associated with time interval I_6 identifies the specific amplitude A_2 of said frequency F_2; the "0000110" in the third group of the second set of binary information in the data string associated with time interval I_6 identifies the time t_6 when said frequency/amplitude F_2A_2 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the second set of binary information in the data string associated with time interval I_6 identifies the status s_0 of said frequency/amplitude F_2A_2 and enables the Static Audio Player **120** to deactivate, erase, or save a binary "0" in, the f_2a_2 memory register within the Static Audio Player **120**, and when the sequential parallel data replication of sound information by time interval from the frequency/amplitude memory registers reaches the point when sound information related to time interval I_6 is to be replicated from the frequency/amplitude memory registers, the Static Audio Player **120** invokes a sequential parallel data replication of sound information related to time interval I_6 from the frequency/amplitude memory registers to the sound card buffer memory, including said "0" in said fourth group of said second set of binary information in said data string associated with time interval I_6. Next, the Static Audio Player **120** invokes a sequential parallel data dump of all sound information related to time interval I_6 from the sound card buffer memory to the sound card of the host computer system, including said "0" in said fourth group of said second set of binary information in said data string associated with time interval I_6, and the sound card then relays/transmits sound information related to time interval I_6 to the Audio Output Device **190**, however, since said "0" in said fourth group of said second set of binary information in said data string associated with time interval I_6 is a signal to terminate playback of frequency/amplitude F_2A_2, the sound card terminates the relay/transmit of frequency/amplitude F_2A_2 to the Audio Output Device **190** thereby terminating playback, and/or replication, of frequency/amplitude F_2A_2 at time t_8. Furthermore, the "00101" in the first group of the sixth pair of binary information in the data string associated with time interval I_4 identifies a discrete frequency F_5; the "0011" in the second group of the sixth pair of binary information in the data string associated with time interval I_4 identifies the specific amplitude A_3 of said frequency F_5; the "0000100" in the third group of the third set of binary information in the data string associated with time interval I_4 identifies the time t_4 corresponding to time interval I_4 when said frequency/amplitude F_5A_3 is to commence to be played, and/or to commence to be replicated; and the "1" in the fourth group of the third set of binary information in the data string associated with time interval I_4 identifies the status s_1 of said frequency/amplitude F_5A_3 and enables the Static Audio Player **120** the activate, or save a binary "1" in, the f_5a_3 memory register within the Static Audio Player **120**, and when the sequential parallel data replication of sound information by time interval from the frequency/amplitude memory registers reaches the point when sound information related to time interval I_4 is to be replicated from the frequency/amplitude memory registers, the Static Audio Player **120** invokes a sequential parallel data replication of

sound information related to time interval I_4 from the frequency/amplitude memory registers to the sound card buffer memory, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_4. Next, the Static Audio Player **120** invokes a sequential parallel data replication of all sound information related to time interval I_4 from the sound card buffer memory to the sound card of the host computer system, including said "1" in said fourth group of said third set of binary information in said data string associated with time interval I_4, and the sound card then relays/transmits sound information related to time interval I_1 to the Audio Output Device **190**, including frequency/amplitude F_5A_3 thereby enabling playback, and/or replication, of frequency/amplitude F_5A_3 at time t_4. The "00101" in the first group of the fourth set of binary information in the data string associated with time interval I_8 identifies a discrete frequency F_5; the "0011" in the second group of the fourth set of binary information in the data string associated with time interval I_8 identifies the specific amplitude A_3 of said frequency F_5; the "0001000" in the third group of the fourth set of binary information in the data string associated with time interval I_8 identifies the time t_8 when said frequency/amplitude F_5A_3 is to cease to be played, and/or to cease to be replicated; and the "0" in the fourth group of the fourth set of binary information in the data string associated with time interval I_8 identifies the status so of said frequency/amplitude F_5A_3 and enables the Static Audio Player **120** to deactivate, erase, or save a binary "0" in, the f_5a_3 memory register within the Static Audio Player **120**, and when the sequential parallel data replication of sound information by time interval from the frequency/amplitude memory registers reaches the point when sound information related to time interval I_8 is to be replicated from the frequency/amplitude memory registers, the Static Audio Player **120** invokes a sequential parallel data replication of sound information related to time interval I_8 from the frequency/amplitude memory registers to the sound card buffer memory, including said "0" in said fourth group of said fourth set of binary information in said data string associated with time interval I_8. Next, the Static Audio Player **120** invokes a sequential parallel data replication of all sound information related to time interval I_8 from the sound card buffer memory to the sound card of the host computer system, including said "0" in said fourth group of said fourth set of binary information in said data string associated with time interval I_8, and the sound card then relays/transmits sound information related to time interval I_8 to the Audio Output Device **190**, however, since said "0" in said fourth group of said fourth set of binary information in said data string associated with time interval I_8 is a signal to terminate playback of frequency/amplitude F_5A_3, the sound card terminates the relay/transmit of frequency/amplitude F_5A_3 to the Audio Output Device **190** thereby terminating playback, and/or replication, of frequency/amplitude F_5A_3 at time t_8.

As discussed above, the sound information saved in the f_xa_y memory registers within in the Static Audio Player **120** can be obtained from the Static Audio File **110** one time interval at a time during real-time playback of the audio recording or the Static Audio Player **120** can obtain and schedule sound information changes for all time intervals I_z in the audio recording, by each frequency/amplitude F_xA_y from the Static Audio File **110** at, or prior to, the commencement of playback of the audio recording by sequentially replicating and sequentially saving sound information related to all, or a plurality of, time intervals I_x from the Static Audio File **110** to the time interval buffer memory, then commencing the sequential parallel data dump from the time interval buffer memory to the frequency/amplitude memory registers. Additionally, the sound card buffer memory can be capable of sequentially storing sound information related to all, or a plurality of, time intervals I_x from the frequency/amplitude memory registers, prior to when the Static Audio Player **120** commences the sequential parallel data dump from the sound card buffer memory to the sound card of the host computer system for subsequent relay/transmission to the Audio Output Device **190**.

Furthermore, if in an audio recording, the amplitude A_x of a certain frequency F_x, is to be lowered (or deactivated) by multiple amplitude levels, from one time interval to the next, the Static Audio File **110** could be structured to contain information on only the lowest amplitude A_x to be deactivated. The Static Audio Player **120** could be structured to automatically deactivate (or erase) all amplitudes above said lowest amplitude A_x upon receipt of instructions from the Static Audio File **110** to deactivate the said lowest amplitude A_x. As example, if the memory registers f_1a_1, f_1a_2, f_1a_3, f_1a_4, f_5a_1, f_1a_6, and f_1a_7, are active in some time interval I_{13} and Static Audio Player **120** receives from the Static Audio File **110** the following algorithm "$I_{14}=F_1A_3t_{14}s_0$" expressed in binary terms as: I_{14}=00001 0011 0001110 0; then the memory registers f_1a_3, f_1a_4, f_1a_5, f_1a_6, and f_1a_7 will be deactivated, erased, or replaced with a binary "0", and the Static Audio Player **120** will cease playing, and/or replicating, F_1A_3, F_1A_4, F_1A_5, F_1A_6, and F_1A_7 at time t_{14}, however, the Static Audio Player **120** will continue to play, and/or replicate, frequency/amplitudes F_1A_1 and F_1A_2, since memory registers f_1a_1 and f_1a_2 have not been deactivated, erased, or replaced with a binary "0". Conversely, if in an audio recording, the amplitude A_x of a certain frequency F_x is to be increased (or activated) by multiple amplitude levels, the Static Audio File **110** could be structured to contain information on only the highest amplitude A_x to be activated. The Static Audio Player **120** could be structured to automatically activate all amplitudes below said highest amplitude A_x upon receipt of instructions from the Static Audio File **110** to activate the said highest amplitude A_x. As example, if the frequency/amplitude memory registers f_2a_1, f_2a_2, f_2a_3, and f_2a_4 are active in some time interval I_{26} and the Static Audio Player **120** receives from the Static Audio File **110** the following algorithm "$I_{26}=F_2A_9t_{26}m_1$" expressed in binary terms as: I_{26}=00010 1001 0011010 1; then in addition to the memory registers f_2a_1, f_2a_2, f_2a_3, and f_2a_4 being active in time interval I_{26}, the Static Audio Player **120** will activate, or save a binary "1" in, the frequency/amplitude memory registers f_2a_5, f_2a_6, f_2a_7, f_2a_8, and f_2a_9, and the Static Audio Player **120** will commence playing frequency/amplitudes F_2A_5, F_2A_6, F_2A_7, F_2A_8, and F_2A_9 at time t_{26}, and the Static Audio Player **120** will continue to play frequency/amplitudes F_2A_1, F_2A_2, F_2A_3, and F_2A_4 since memory registers f_2a_1, f_2a_2, f_2a_3, and f_2a_4 continue to be active.

Additionally, the Static Audio Player **120** can be configured to contain one or more memory registers corresponding to each discrete frequency/amplitude F_xA_y, in which information from the Static Audio File **110** can be saved. As example, the frequency/amplitude information may be configured to be saved in a frequency f_x memory register and an amplitude ay memory register corresponding with frequency/amplitude F_xA_y rather than to the individual f_xa_y frequency/amplitude memory register.

Additionally, instead of the Static Audio Player **120** containing a memory register for each possible amplitude of

a frequency, the Static Audio Player **120** can be configured to contain a memory register for a frequency and the corresponding binary code for the corresponding amplitude would be saved in the memory register instead of only a binary "0" or a binary "1". By means of example, and using the previously described algorithm "$I_w=F_xA_yt_zs_m$", the Static Audio Player **120** functions as previously described, however, the Static Audio Player **120** would contain only one frequency memory register f_x for each frequency F_x instead of plurality of frequency/amplitude memory registers f_xa_y for each such frequency F_x; and instead of storing a binary "0" or a binary "1" in said frequency memory register f_x, the binary code of the amplitude would be stored in said frequency memory register f_x, Using a portion of the previously discussed example, the Static Audio File **110** expressed in binary terms as: I_1=00001 0001 0000001 1 00010 0001 0000001 1 00010 0010 0000001 1; I_4=00101 0001 0000100 1 00101 0010 0000100 1 00101 0011 0000100 1; I_6=00010 0001 0000110 0 00010 0010 0000110 0; and I_8=00001 0001 0001000 0 00101 0001 0001000 0 00101 0010 0001000 0 00101 0011 0001000 0; which mathematically represents an audio recording whereby a sound F_1A_1 is to be played during time intervals I_1, I_2, I_3, I_4, I_5, I_6, and I_7; and sounds F_2A_1 and F_2A_2 are to be played during time intervals I_1, I_2, I_3, I_4, and I_5; and sounds F_5A_1, F_5A_2, and F_5A_3 are to be played during time intervals I_4, I_5, I_6, and I_7; and no sound is to be played in time interval I_8; the second group of the any set of binary information in the data strings identifies the amplitude code to be saved in, or erased from, the corresponding frequency memory register f_x depending on the second group of the any set of binary information in the data strings.

Referring now to the FIG. **2**, another preferred embodiment of the invention is comprised of the following:

210 Analog Video Source
220 Analog Video Recorder
230 Analog Video File
240 Analog to Digital Video Converter
250 Analog to Digital Video Recorder
260 Dynamic Video File
270 Dynamic Video Player
280 Frequency/Amplitude Database Compiler
290 Frequency/Amplitude Database
300 Dynamic to Static Video Truncator
310 Static Video File
320 Static Video Player
330 Static Video Player
340 Electronic Connection
350 Static Video File
360 Dynamic Video File
370 Static Video File
380 Dynamic Video File
390 Video Output Device

In FIG. **2**, the following components are already commercially available: the Analog Video Source **210**; the Analog Video Recorder **220**; the Analog Video File **230**; the Analog to Digital Video Converter **240**; the Analog to Digital Video Recorder **250**; the Dynamic Video File **260**, **360**, and **380**; the Dynamic Video Player **270**; the Electronic Connection **340**; and the Video Output Device **390**. However, the Red/Green/Blue Database Compiler **280**; the Red/Green/Blue Database **290**; the Dynamic to Static Video Truncator **300**; the Static Video File **310**, **350**, and **370**; and the Static Video Player **320** and **330**; would be designed specifically to meet the teachings of this invention.

The Analog Video Source **210** is the originating source of a video recording in the configuration as outlined in FIG. **2**.

The Analog Video Recorder **220** (i.e. VHS Video Cassette Recorder, BETA Video Cassette Recorder, etc.) is the means by which the Analog Video Source **210** can be recorded in either analog form or digital form.

The Analog Video File **230** is the resulting analog video file produced by the Analog Video Recorder **220**.

The Analog to Digital Video Converter **240** is the means by which an Analog Video File **230** is converted into a digital video file format.

The Analog to Digital Video Recorder **250** is the means by which the Analog Video Source **210** can be recorded directly into a digital video file format.

The Dynamic Video File **260** (i.e. MPEG, etc.) is encoded in a dynamic digital file format which contains basic, and/or complex, color information by pixel by video frame and can be produced by either the Analog to Digital Video Converter **240** or the Analog to Digital Video Recorder **250**. The Dynamic Video File **260** is formatted in the same dynamic digital video file format as the Dynamic Video File **360** and **380**.

The Dynamic Video Player **270** is a means to playback a Dynamic Video File **260**.

The Red/Green/Blue Database Compiler **280** is the means by which data contained in the Dynamic Video File **260** is accessed and inputted into the Red/Green/Blue Database Compiler **280** and is compiled to create the Red/Green/Blue Database **290**. The Red/Green/Blue Database Compiler **280** is a computer software program, to be executed on a computer system, which can be written by one skilled in the art of video database creation (see FIG. **14**).

The Red/Green/Blue Database **290** is composed of a plurality of video frames composed of a matrix of pixels, each pixel contains data representing a specific complex color which may be defined by various shades of the basic colors red, green, and blue.

The Dynamic to Static Video Truncator **300** is the means by which repetitive data contained in the Red/Green/Blue Database **290** is truncated to contain specific color information by pixel and the related the starting points each such color is to commence to be displayed, and/or commence to be replicated, within each such pixel, with respect to time, and removes any repetitive data between said starting point and said ending point and creates the Static Video File **310**. The Dynamic to Static Video Truncator **300** is a computer software program, to be executed on a conventional computer system, which can be written by one skilled in the art of video database creation (see FIG. **15**).

The Static Video File **310** is encoded in a digital file format which records basic color information of the red/green/blue components of specific complex colors to be displayed, and/or replicated, within discrete pixels on a Video Output Device **390** and the related starting points each such specific complex color is to commence to be displayed, and/or commence to be replicated, within each such pixel, for one or more consecutive video frames, with respect to time and can be produced by the Dynamic to Static Video Truncator **300**. The Static Video File **310** is encoded in a format which is compatible for use by the Static Video Player **320** and **330**, and can be saved on the hard disk of a conventional computer system. The Static Video File **310** is formatted in the same digital video file format as the Static Video File **350** and **370**.

The Static Video File **310** and the Static Audio File **110** may be combined into one file for use by a device which is the combination of the Static Video Player **320** and the Static Audio Player **120**.

The Static Video Player **320** is a computer software program executed by a conventional computer system. The Static Video Player **320** is a means by which display of the Static Video File **310** through the video card of the host computer system is possible in either digital audio form or analog audio form. The Static Video Player **320** is designed to process the encoded information of the Static Video File **310** for subsequent video display and/or replication. The Static Video Player **320** invokes a sequential serial replication (i.e. a serial data replication is the process whereby the original copy of data is replicated, transmitted, and saved in series to a buffer memory) of color information from the Static Video File **310** and saves said color information into a video frame buffer memory within the Static Video Player **320**. Next, the Static Video Player **320** invokes a sequential parallel data dump of said color information by video frame from the video frame memory buffer into a matrix of red/green/blue memory registers within the Static Video Player **320**. Next, the Static Video Player **320** invokes a sequential parallel data replication of the color information in the red/green/blue memory registers to the video card buffer memory within the Static Video Player **320**. Next, the Static Video Player **320** invokes a sequential parallel data dump of the color information in the video card buffer memory to the video card of the host computer system, whereupon the video card relays/transmits the color information to the Video Output Device **390**. Each red/green/blue memory register is pre-assigned, or corresponds, to a specific pixel on a Video Output Device **390**. The Static Video Player **320** saves red/green/blue color information from the Static Video File **310** into corresponding red/green/blue memory registers. The Static Video Player **320** generates complex colors from the red/green/blue color information. The Static Video Player **320** displays complex colors, generated from the red/green/blue color information saved in the red/green/blue memory registers, within the corresponding pixels on a Video Output Device **390**. As the color information saved in the red/green/blue memory registers changes from video frame to video frame, the complex color displayed within the corresponding pixels on a Video Output Device **390** changes accordingly. The Static Video Player **320** may be configured to contain the functionality of the Dynamic Video Player **270**, the Red/Green/Blue Database Compiler **280**, and the Dynamic to Static Video Truncator **300**.

The Static Video Player **320** is also a means to playback the Static Video File **310**, **350**, and/or **370** in dynamic digital form on a Video Output Device **390** (i.e. digital video monitor, digital television set, etc.); or playback in analog form on a Video Output Device **390** (i.e. analog video monitor, analog television set, etc.) for view by the user. The Static Video Player **320** can playback the Static Video File **310**, **350**, and/or **370** in static digital form to save computational instructions as a Static Video File **370**. The Static Video Player **320** can playback the Static Video File **310**, **350**, and/or **370** in dynamic digital form to save computational instructions as a Dynamic Video File **380**.

Additionally, the Static Video Player **320** is a means to playback the Dynamic Video File **360** and/or **380** in dynamic digital form on a Video Output Device **390** (i.e. digital video monitor, digital television set, etc.); or playback in analog form on a Video Output Device **390** (i.e. analog video monitor, analog television set, etc.) for view by the user. The Static Video Player **320** can playback the Dynamic Video File **360** and/or **380** in static digital form to save computational instructions as a Static Video File **370**. The Static Video Player **320** can playback the Dynamic Video File **360** and/or **380** in dynamic digital form to save computational instructions as a Dynamic Video File **380**.

Furthermore, the Static Video Player **320** can receive computational instructions from a Static Video File **350** or a Dynamic Video File **360** (i.e. in broadcast fashion, download fashion (i.e. U.S. Pat. No. 5,191,573), etc.) by means of the Static Video Player **330** via an Electronic Connection **340** (such as, but not limited to, transmission via: direct connect network, satellite, cable TV, coax cable, fiber optics, fiber/coax hybrid, Internet, cellular, microwave, radio, twisted pair telephone, ISDN telephone, T-1 telephone, DS-3 telephone, OC-3 telephone, etc.).

The Static Video Player **320** and the Static Audio Player **120** may be combined into one device enabling the simultaneous playback of recordings which are the combination of the Static Video File **310** and the Static Audio File **110**.

The Static Video Player **330** is a means by which a Static Video File **350** and/or a Dynamic Video File **360** may be electronically transmitting (i.e. in broadcast fashion, download fashion (i.e. U.S. Pat. No. 5,191,573), etc.) to a Static Video Player **320** via an Electronic Connection **340** for subsequent or real-time playback by the Static Video Player **320**.

The Electronic Connection **340** (such as, but not limited to, transmission via: direct connect network, satellite, cable TV, coax cable, fiber optics, fiber/coax hybrid, Internet, cellular, microwave, radio, twisted pair telephone, ISDN telephone, T-1 telephone, DS-3 telephone, OC-3 telephone, etc.) is a means by which a Static Video Player **330** of a first computer system and a Static Video Player **320** of a second computer system can be electronically connected. The Static Video Player **320** and the Static Video Player **330** may be configured to have all, or some, of the same functionality and capabilities as the other.

The Static Video File **350** is encoded in a digital file format which records basic color information of the red/green/blue components of specific complex colors to be displayed, and/or replicated, within discrete pixels on a Video Output Device **390** and the related starting points each such complex color is to commence to be displayed, and/or commence to be replicated, within each such pixel for one or more consecutive video frames, with respect to time. The Static Video File **350** is formatted in the same digital video file format as the Static Video File **310** and **370**.

The Dynamic Video File **360** (i.e. MPEG, etc.) is encoded in a file format which contains basic color, and/or complex color, information by pixel by video frame. The Dynamic Video File **360** is formatted in the same digital video file format as the Dynamic Video File **260** and **380**.

The Static Video File **370** is encoded in a digital file format which records basic color information of the red/green/blue components of specific complex colors to be displayed, and/or replicated, within discrete pixels on a Video Output Device **390** and the related starting points each such complex color is to commence to be displayed, and/or commence to be replicated, within each such pixel, for one or more consecutive video frames, with respect to time and can be produced by the Static Video Player **310**. The Static Video File **370** is formatted in the same digital video file format as the Static Video File **310** and **350**.

The Dynamic Video File **380** (i.e. MPEG, etc.) is encoded in a digital file format which contains basic color, and/or complex color, information by pixel by video frame and can be produced by the Static Video Player **320**. The Dynamic Video File **380** is formatted in the same digital video file format as the Dynamic Video File **260** and **360**.

The Video Output Device **390** (i.e. computer monitor, television set, video monitor, etc.) is the means by which an

image is produced, in either digital or analog form, for view when the Static Video File **310**, **350**, and/or **370** or the Dynamic File **360** and/or **380** is played by means of the Static Video Player **320**. The Video Output Device **390** is electronically connected to, and receives color information by pixel from, a computer video card. The Video Output Device **390** can be either a digital device or an analog device.

With respect to FIG. **2**, the invention records an Analog Video Source **210**, being any form of a video recording, through use of the Analog Video Recorder **220**, which is a device which records, and/or plays, analog video signals (i.e. VHS Video Cassette Recorder, BETA Video Cassette Recorder, etc.), or through use of the Analog to Digital Video Recorder **250**. The Analog to Digital Video Recorder **250** is a device which can convert analog video signals directly into digital video signals, can record digital video signals, and which can playback digital video signals. If the Analog Video Recorder **220** is utilized, an Analog Video File **230** is created. The Analog to Digital Video Converter **240**, a device which converts analog video signals into digital video signals, creates a Dynamic Video File **260** from the Analog Video File **230**.

The Dynamic Video File **260** is created in a dynamic digital video file format (i.e. MPEG). If the Analog to Digital Video Recorder **250** is used, the Dynamic Video File **260** is directly created. As example, and assuming that a Dynamic Video File **260** is composed a plurality of video frames (F), where F_w identifies a discrete video frame within a range of sequentially positioned video frames identified by subscript "w" which is bounded by the first video frame and last video frame of the video recording; and each such video frame F_w is composed of discrete pixels which are mathematically expressed as, and/or are located by, height (h) and length (l), where (h) is a vertical Euclidean axis at right angle to (l) , which is a horizontal Euclidean axis, and h_x identifies a discrete location along the (h) axis within a range of locations identified by subscript "x", and l_y identifies a discrete location along the (l) axis within a range of locations identified by subscript "y", and the intersection of h_x and l_y identifies a discrete video location, known as a pixel h_xl_y, within the area bounded by the (h) axis and the (l) axis; and complex colors are composed of a mixture of the basic colors red (R), green (G), and blue (B), where $R_vG_vB_v$ identifies discrete shades of red, green, and blue, respectively, within a range of shades from 0 to 255 identified by subscript "v"; and further assuming that the following information after the equals sign is expressed in binary terms: h_1=00001; h_4=00100; h=01011; l=00001; l=00111; l=10100; R_{000}=00000000; R_{074}=01001010; R_{116}=01110100; R_{142}=10001110; R_{233}=1101001; G_{000}=00000000; G_{140}=10001100; G_{195}=11000011; G_{228}=11100100; G_{255}=11111111; B_{000}=00000000; B_{095}=01011111; B_{118}=01110110; and B_{232}=11101000; the Dynamic Video File **260** mathematically represents a video recording as the algorithm "$F_x=h_xl_yR_vG_vB_v$", and expressed in binary terms as: F_1=00001 00001 01110100 00000000 01011111 00100 00111 01001010 11111111 00000000 01011 10100 11101001 11100100 00000000; F_2=00001 00001 01110100 00000000 01011111 00100 00111 01001010 11111111 00000000 01011 10100 11101001 11100100 00000000; F_3=00001 00001 01110100 00000000 01011111 00100 00111 01001010 11111111 00000000 01011 10100 11101001 11100100 00000000; F_4=00001 00001 01110100 00000000 01011111 00100 00111 01001010 11111111 00000000 01011 10100 11101001 11100100 00000000; F_5=00001 00001 01110100 00000000 01011111 00100 00111 01001010 11111111 00000000 01011 10100 11101001 11100100 00000000; F_6=00001 00001 01110100 00000000 01011111 00100 00111 10001110 11000011 11101000 01011 10100 11101001 11100100 00000000; F_7=00001 00001 01110100 00000000 01011111 00100 00111 10001110 11000011 11101000 01011 10100 11101001 11100100 00000000; and F_8=00001 00001 00000000 10001100 01110110 00100 00111 10001110 11000011 11101000 01011 10100 11101001 11100100 00000000; which mathematically represents a video recording whereby a shade of purple ($R_{116}G_{000}B_{095}$) is to be displayed within pixel h_1l_1 on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, and F_7, then in video frame F_8 a shade of teal ($R_{000}G_{140}B_{118}$) is to be displayed within pixel h_1l_1; a shade of lime green ($R_{074}G_{255}B_{000}$) is to be displayed within pixel h_4l_7 on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, and F_5, then in video frames F_6, F_7, and F_8 a shade of powder blue ($R_{142}G_{195}B_{232}$) is to be displayed within pixel h_4l_7; and a shade of lemon yellow ($R_{233}G_{228}B_{000}$) is to be displayed within pixel $h_{11}l_{20}$ on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, F_7, and F_8 (see FIG. **16**). The data string for each video frame F_w is composed of sets of five groups of binary information, each set contains binary information for a pixel h_xl_y, the first and second groups of binary information in a set identify a pixel h_xl_y, the third group of binary information in a set identifies red color information R_v, the fourth group of binary information in a set identifies green color information G_v, and the fifth group of binary information in a set identifies blue color information B_v. The "00001 00001" in the first and second groups of the first set of binary information in the data string associated with video frame F_1 identify the pixel h_1l_1; the "01110100 00000000 01011111" in the third, fourth, and fifth groups of the first set of binary information in the data strings associated with video frames F_1, F_2, F_3, F_4, F_5, F_6, and F_7 identify a shade of purple, being a complex color generated by the mixture of the basic colors $R_{116}G_{000}B_{095}$, to be displayed within pixel h_1l_1 on a Video Output Device **390**. The "00001 00001" in the first and second groups of the first set of binary information in the data string associated with video frame F_8 identify the pixel h_1l_1; the "00000000 10001100 01110110" in the third, fourth, and fifth groups of the first set of binary information in the data string associated with video frame F_8 identify a shade of teal, being a complex color generated by the mixture of the basic colors $R_{000}G_{140}B_{118}$, to be displayed within pixel h_1l_1 on a Video Output Device **390**. The "00100 00111" in the first and second groups of the second set of binary information in the data string associated with video frames F_1, F_2, F_3, F_4, and F_5 identify the pixel h_4l_7; the "01001010 11111111 00000000" in the third, fourth, and fifth groups of the second set of binary information in the data strings associated with video frames F_1, F_2, F_3, F_4, and F_5 identify a shade of lime green, being a complex color generated by the mixture of the basic colors $R_{074}G_{255}B_{000}$, to be displayed within pixel h_4l_7 on a Video Output Device **390**. The "00100 00111" in the first and second groups of the second set of binary information in the data string associated with video frames F_6, F_7, and F_8 identify the pixel h_4l_7; the "10001110 11000011 11101000" in the third, fourth, and fifth groups of the second set of binary information in the data string associated with video frames F_6, F_7, and F_8 identify a shade of powder blue, being a complex color generated by the mixture of the basic colors $R_{142}G_{195}B_{232}$, to be displayed within pixel h_1l_7 on a Video Output Device **390**. The "01011 10100" in the first and second groups of the third set of binary information in

the data string associated with video frames F_1, F_2, F_3, F_4, F_5, F_6, F_7, and F_8 identify the pixel $h_{11}l_{20}$; the "11101001 11100100 00000000" in the third, fourth, and fifth groups of the third set of binary information in the data strings associated with video frames F_1, F_2, F_3, F_4, F_5, F_6, F_7, and F_8 identify a shade of lemon yellow, being a complex color generated by the mixture of the basic colors $R_{233}G_{228}B_{000}$, to be displayed within pixel $h_{11}l_{20}$ on a Video Output Device **390**. The Dynamic Video File **260** records color information to be displayed in each pixel of a Video Output Device **390** for each, and every, video frame.

Playback of the Dynamic Video File **260** is accomplished by means of a Dynamic Video Player **270**, which is a device which can play the Dynamic Video File **260**. The Dynamic Video Player **270** receives color information from the Dynamic Video File **260** for playback one video frame at a time (see FIG. **17**).

The Red/Green/Blue Database Compiler **280** is a computer software program to be executed by the host computer system, which inputs color information from a Dynamic Video File **260** into the Red/Green/Blue Database Compiler **280** and creates a Red/Green/Blue Database **290**. As example, the Red/Green/Blue Database **290** can be composed of a three-dimensional matrix defined by three axes, video frame (F), video frame height (h), and video frame length (l). A video frame F_w, where subscript "w" represents the range of video frames bounded by the first video frame and the last video frame of the video recording, is composed of a plurality of discrete pixels. The location of each such pixel h_xl^y can be determined using a typical Euclidean coordinate system with video frame height (h) at right angle to video frame length (l), where subscript "x" represents the relative position along the (h) axis, and subscript "y" represents the relative position along the (l) axis. Each pixel contains a complex color composed of a mixture of the basic colors red (R), green (G), and blue (B), where $R_vG_vB_v$ identifies discrete shades of red, green, and blue respectively, within a range of shades identified by subscript "v". As example, white, being a complex color can be mathematically expressed as the mixture of the basic colors $R_{255}G_{255}B_{255}$, and black, being a complex color can be mathematically expressed as the mixture of the basic colors $R_{000}G_{000}B_{000}$, where the total possible shades identified by subscript "v" range from 000 to 255. These shades of basic colors, could be represented in binary terms as: 000=00000000; 001=00000001; 002=00000010; . . . 040=00101000; and so forth with 255=11111111. Therefore, a shade of purple, being a complex color can be mathematically expressed as the mixture of the basic colors $R_{116}G_{000}B_{095}$, is expressed in binary terms as "01110100 00000000 01011111" where R_{116}=01110100, G_{000}=00000000, and B_{095}=01011111. The number of shades of the basic colors red, green, and blue, and the number of video frames per second, and the number of pixels per video frame can vary from application to application. The Red/Green/Blue Database Compiler **280** accesses the color information in the Dynamic Video File **260** and invokes a serial data replication of said color information to the Red/Green/Blue Database Compiler **280** (see FIG. **14**). Next, the Red/Green/Blue Database Compiler **280** performs a sort routine with a primary sort by pixel h_xl_y and a secondary sort by video frame F_w (first video frame first, last video frame last). Next, the Red/Green/Blue Database Compiler **280** saves said sorted/collated color information as a Red/Green/Blue Database **290**. The Red/Green/Blue Database Compiler **280** can save the Red/Green/Blue Database **290** on the computer hard disk of said host computer system. The Red/Green/Blue Database Compiler **280** can electronically relay/transmit the Red/Green/Blue Database **290** directly to the Dynamic to Static Video Truncator **300**.

Furthermore, the invention utilizes the Dynamic to Static Video Truncator **300**, which is a computer software program to be executed by the host computer system, to mathematically analyze the matrix of the Red/Green/Blue Database **290** and identify patterns of specific complex colors, and/or basic colors, to be displayed, and/or replicated, within discrete pixels for one or more consecutive video frames, and records only the start point and finish point of any consecutive repetitions of color information corresponding to any pixel h_xl_y, with respect to time, and the Dynamic to Static Video Truncator **300** saves such truncated information in a Static Video File **310**. The Dynamic to Static Video Truncator **300** accesses the sorted/collated color information in the Red/Green/Blue Database **290** and invokes a serial data dump/replication of said color information to the Dynamic to Static Video Truncator **300** (see FIG. **15**). Next, the Dynamic to Static Video Truncator **300** identifies repetition strings of identical color information in pixels h_xl_y over video frames F_w. Next, the Dynamic to Static Video Truncator **300** erases the second occurrence and all subsequent occurrences of color information in the repetition strings related to the corresponding pixels h_xl_y over the corresponding video frames F_w. At this point, the color information has been truncated and the only remaining color information with respect to said repetition strings of identical color information in pixels h_xl_y over video frames F_w are the starting points of said repetition strings. Next, the Dynamic to Static Video Truncator **300** performs a sort routine of said truncated color information with a primary sort by video frame F_w (first video frame first, last video frame last) and a secondary sort by pixels h_xl_y. Next, the Dynamic to Static Video Truncator **300** saves said sorted and truncated color information as a Static Video File **310**. The Dynamic to Static Video Truncator **300** can save the Static Video File **310** on the computer hard disk of said host computer system. The Dynamic to Static Video Truncator **300** can electronically relay/transmit the Static Video File **310** directly to the Static Video Player **320**.

The Static Video File **310** contains information such as, but not limited to, specific complex and/or basic colors to be displayed, and/or replicated, within discrete pixels on a Video Output Device **390** and the related starting points each such complex color is, and/or basic colors are, to be displayed, and/or replicated, within each such pixel for one or more consecutive video frames, with respect to time. As example, and assuming that a Static Video File **310** is composed a plurality of video frames (F), where F_w identifies a discrete video frame within a range of sequential video frames identified by subscript "w", and bounded by the first video frame and last video frame of the video recording; and each such video frame F_w is composed of discrete pixels which are mathematically expressed as, and/or located by, height (h) and length (l), where (h) is a vertical Euclidean axis at right angle to (l), which is a horizontal Euclidean axis, and h_x identifies a discrete location along the (h) axis within a range of locations identified by subscript "x", and l_y identifies a discrete location along the (l) axis within a range of locations identified by subscript "y", and the intersection of h_x and l_y identifies a discrete location, or pixel h_xl_y, within the area bounded by the (h) axis and the (l) axis of the Video Output Device **390**; and complex colors are composed a mixture of the basic colors red (R), green (G), and blue (B), where $R_vG_vB_v$, where subscript "v" identify discrete shades of red, green, and blue, respectively, within

a range of shades from 0 to 255; and time t_z identifies a discrete moment in time within a range of time identified by the subscript "z" which is bounded by the start time and finish time of the video recording, and t_z identifies when the basic colors $R_vG_vB_v$ corresponding to video frame F_w are to commence to be displayed, and/or commence to be replicated, within pixel h_xl_y on a Video Output Device **390**; and further assuming the following information after the equals sign is expressed in binary terms: h_1=0001; h_4=00100; h_{11}=01011; l_1=00001; l_7=00111; l_{20}=10100; R_{000}=00000000; R_{074}=01001010; R_{116}=01110100; R_{142}=10001110; R_{233}=11101001; G_{000}=00000000; G_{140}=10001100; G_{195}=11000011; G_{228}=11100100; G_{255}=11111111; B_{000}=00000000; B_{095}=01011111; B_{118}=01110110; and B_{232}=11101000; t_1=0000001; t_2=0000010; t_3=0000011; t_4=0000100; t_5=0000101; t_6=0000110; t_7=0000111; and t_8=0001000; the Static Video File **310** mathematically represents the same video recording as used in the previous example for the Dynamic Video File **260**, as the algorithm "F_w=$h_xl_yR_vG_vB_vt_z$" and expressed in binary terms as: F_1=00001 00001 01110100 00000000 01011111 0000001 00100 00111 01001010 11111111 00000000 0000001 01011 10100 11101001 11100100 00000000 0000001; F_6=00100 00111 10001110 11000011 11101000 0000110; F_8=00001 00001 00000000 10001100 01110110 0001000; which mathematically represents a video recording whereby a shade of purple ($R_{116}G_{000}B_{095}$) is to be displayed within pixel h_1l_1 of a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, and F_7, then in video frame F_8 a shade of teal ($R_{000}G_{140}B_{118}$) is to be displayed within pixel h_1l_1; a shade of lime green ($R_{074}G_{255}B_{000}$) is to be displayed within pixel h_4l_7 on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, and F_5, then in video frames F_6, F_7, and F_8 a shade of powder blue ($R_{142}G_{195}B_{232}$) is to be displayed within pixel h_4**1**$_7$; and a shade of lemon yellow ($R_{233}G_{228}B_{000}$) is to be displayed within pixel $h_{11}l_{20}$ on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, F_7, and F_8 (see FIG. **18**). The data string for each video frame F_w is composed of sets of six groups of binary information, the first and second groups of binary information in a set identify a pixel h_xl_y, the third group of binary information in a set identifies red color information R_v, the fourth group of binary information in a set identifies green color information G_v, the fifth group of binary information in a set identifies blue color information B_v, and the sixth group of binary information in a set identifies a discrete time t_z. The "00001 00001" in the first and second groups of the first set of binary information in the data string associated with video frame F_1 identify pixel h_1l_1; the "01110100 00000000 01011111" in the third, fourth, and fifth groups of the first set of binary information in the data string associated with video frame F_1 identify a shade of purple, being a complex color generated by the mixture of the basic colors $R_{116}G_{000}B_{095}$; and the "0000001" in the sixth group of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** is to commence to display said shade of purple ($R_{116}G_{000}B_{095}$) within pixel h_1l_1 on a Video Output Device **390** and continue to replicate said shade of purple ($R_{116}G_{000}B_{095}$) within pixel h_1l_1 on a Video Output Device **390** during all subsequent video frames until instructed otherwise, and in this example those video frames are F_2, F_3, F_4, F_5, F_6, and F_7, (see FIG. **5**). The "00001 00001" in the first and second groups of the only set of binary information in the data string associated with video frame F_8 identify pixel h_1l_1; the "00000000 10001100 01110110" in the third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_8 identify a shade of teal, being a complex color generated by the mixture of the basic colors $R_{000}G_{140}B_{118}$; and the "0001000" the sixth group of the only set of binary information in the data string associated with video frame F_8 identifies the time t_8 when the Static Video Player **320** is to commence to display said shade of teal ($R_{000}G_{140}B_{118}$) within pixel h_1l_1 on a Video Output Device **390** (see FIG. **6**). The "00100 00111" in the first and second groups of the second set of binary information in the data string associated with video frame F_1 identify pixel h_4l_7; the "01001010 11111111 00000000" in the third, fourth, and fifth groups of the second set of binary information in the data string associated with video frame F_1 identify a shade of lime green, being a complex color generated by the mixture of the basic colors $R_{074}G_{255}B_{000}$; and the "0000001" in the sixth group of the second set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** is to commence to display said shade of lime green ($R_{074}G_{255}B_{000}$) within pixel h_4l_7 on a Video Output Device **390** and continue to replicate said shade of lime green ($R_{074}G_{255}B_{000}$) within pixel h_4l_7 on a Video Output Device **390** during all subsequent video frames until instructed otherwise, and in this example those video frames are F_2, F_3, F_4, and F_5. The "00100 00111" in the first and second groups of the only set of binary information in the data string associated with video frame F_6 identify pixel h_4l_7; the "10001110 11000011 11101000" in the third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_6 identify a shade of powder blue, being a complex color generated by the mixture of the basic colors $R_{142}G_{195}B_{232}$; and the "0000110" the sixth group of the only set of binary information in the data string associated with video frame F_6 identifies the time t_6 when the Static Video Player **320** is to commence to display said shade of powder blue ($R_{142}G_{195}B_{232}$) within pixel h_4l_7 on a Video Output Device **390** and continue to replicate said shade of powder blue ($R_{142}G_{195}B_{232}$) within pixel h_4l_7 on a Video Output Device **390** during all subsequent video frames until instructed otherwise, and in this example those video frames are F_7 and F_8. The "01011 10100" in the first and second groups of the third set of binary information in the data string associated with video frame F_1 identify pixel $h_{11}l_{20}$; the "11101001 11100100 00000000" in the third, fourth, and fifth groups of the third set of binary information in the data string associated with video frame F_1 identify a shade of lemon yellow, being a complex color generated by the mixture of the basic colors $R_{233}G_{228}B_{000}$; and the "0000001" in the sixth group of the third set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** is to commence to display said shade of lemon yellow ($R_{233}G_{228}B_{000}$) within pixel $h_{11}l_{20}$ on a Video Output Device **390** and continue to replicate said shade of lemon yellow ($R_{233}G_{228}B_{000}$) within pixel $h_{11}l_{20}$ on a Video Output Device **390** during all subsequent video frames until instructed otherwise, and in this example those video frames are F_2, F_3, F_4, F_5, F_6, F_7, and F_8. The Static Video File **310** is saved in the hard disk of the host computer system containing the Static Video Player **320** and the Static Video File **350** is saved in the hard disk of the computer system containing the Static Video Player **330**.

The Static Video Player **320** is a computer software program saved in the hard disk of the host computer system. When the Static Video Player **320** is activated, the central processing unit of the host computer system transmits a copy of the program to random access memory within the host

computer system for execution of the various functions of the Static Video Player **320**, as is convention with most computer software programs. The Static Video Player **320** accesses the Static Video File **310** and replicates and saves color information from the Static Video File **310** into a video frame buffer memory within the Static Video Player **320**. The Static Video Player **320** then transmits said color information from said video frame buffer memory to the red/green/blue memory registers within the Static Video Player **320**, one video frame at a time. As example, the Static Video Player **320** accesses the Static Video File **310** and invokes a serial data replication of the color information related to the first video frame into a red/green/blue matrix within a video frame buffer memory within the Static Video Player **320**. The Static Video Player **320** then invokes a parallel data dump (i.e. a data dump is the process whereby data in a buffer memory is electronically transmitted to another mechanism or memory then is electronically erased from said buffer memory) of said color information related to the first video frame from said video frame buffer memory to the red/green/blue memory registers within the Static Video Player **320**. The Static Video Player **320** then invokes a parallel data dump of said color information related to the first video frame from said video frame buffer memory to said red/green/blue memory registers. As the Static Video Player **320** invokes a parallel data dump of said color information related to the first video frame from said video frame buffer memory to said red/green/blue memory registers, the Static Video Player **320** accesses the Static Video File **310** and invokes a serial data replication of the color information related to the second video frame into said red/green/blue memory matrix within said video frame buffer memory within the Static Video Player **320**. As the Static Video Player **320** invokes a parallel data dump of the color information related to the first video frame from said red/green/blue memory registers to a video card buffer memory within the Static Video Player **320** (as discussed herein below) the Static Video Player **320** invokes a parallel data dump of said color information related to the second video frame from said video frame buffer memory to said red/green/blue memory registers. The color information in the third video frame, forth video frame, fifth video frame, etc. will continue in the above manner until the end of the Static Video File **310**.

As mentioned above, the Static Video Player **320** saves color information from the Static Video File **310** into a matrix video memory registers $r_{x/y}g_{x/y}b_{x/y}$ within the Static Video Player **320**, where $r_{x/y}$ represents memory registers for the basic color red, $g_{x/y}$ represents memory registers for the basic color green, and $b_{x/y}$ represents memory registers for the basic color blue. The video memory registers $r_{x/y}g_{x/y}b_{x/y}$ correspond to each such previously defined pixel h_xl_y, and subscript "x/y" of said memory registers corresponds to the subscripts "x" and "y" of each such pixel h_xl_y. It is important to note that if any of the video memory registers $r_{x/y}g_{x/b}b_{x/y}$ do not receive a data dump for any particular video frame F_w, those such video memory registers $r_{x/y}g_{x/y}b_{x/y}$ will not be modified for any such video frame F_w. Furthermore, once a specific color $R_vG_vV_vB_v$ has been saved in a memory register $r_{x/y}g_{x/y}b_{x/y}$, corresponding to a pixel h_xl_y of a Video Output Device **390**, the Static Video Player **320** does not need to receive any further color information from the Static Video File **310** to enable the Static Video Player **320** to continue to display, and/or replicate, said specific color $R_vG_vB_v$ within said pixel h_xl_y of a Video Output Device **390**. The Static Video Player **320** saves the $R_vG_vB_v$ color information from the Static Video File **310** into the corresponding video memory registers $r_{x/y}g_{x/y}b_{x/y}$ with respect to time, and corresponding to pixel h_xl_y of a Video Output Device **390**. Using the previous example where the Static Video File **310** mathematically represents a video recording as the algorithm "$F_w=h_xl_yR_vG_vB_vt_z$" and expressed in binary terms as: F_1=00001 00001 01110100 00000000 01011111 0000001 00100 00111 01001010 11111111 00000000 0000001 01011 10100 11101001 11100100 00000000 0000001; F_6=00100 00111 10001110 11000011 11101000 0000110; F_8=00001 00001 00000000 10001100 01110110 0001000; which mathematically represents a video recording whereby a shade of purple ($R_{116}G_{000}B_{095}$) is to be displayed within pixel h_1l_1 of a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, and F_7, then in video frame F_8 a shade of teal ($R_{000}G_{140}B_{118}$) is to be displayed within pixel h_1l_1; a shade of lime green ($R_{074}G_{255}B_{000}$) is to be displayed within pixel h_4l_7 on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, and F_5, then in video frames F_6, F_7, and F_8 a shade of powder blue ($R_{142}G_{195}B_{232}$) is to be displayed within pixel h_4l_7; and a shade of lemon yellow ($R_{233}G_{228}B_{000}$) is to be displayed within pixel $h_{11}l_{20}$ on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, F_7, and F_8 (see FIG. **18**). As further clarification, said pixels h_1l_1, h_4l_7, and $h_{11}l_{20}$ are discussed below, detailing the process the Static Video Player **320** utilizes to replicate color information from the Static Video File **310** to the red/green/blue memory registers within the Static Video Player **320**. The "00001 00001" in the first and second groups of the first set of binary information in the data string associated with video frame F_1 identify pixel h_1l_1; the "01110100 00000000 01011111" in the third, fourth, and fifth groups of the first set of binary information in the data string associated with video frame F_1 identify a shade of purple, being a complex color generated by the mixture of the basic colors $R_{116}G_{000}B_{095}$; and the "0000001" in the sixth group of the first set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** is to save the purple ($R_{116}G_{000}B_{095}$) color information into memory registers $r_{1/1}g_{1/1}b_{1/1}$, and upon commencing the sequential serial transmission of color information by video frame from the Static Video File **310**, the Static Video Player **320** replicates and saves color information related to video frame F_1 from the Static Video File **310** into the video frame buffer memory, including said "01110100 00000000 01011111" in said third, fourth, and fifth groups of said first set of binary information in said data string associated with video frame F_1, and then the Static Video Player **320** invokes a parallel data dump of all color information related to video frame F_1 from the video frame buffer memory to the red/green/blue memory registers, including said "01110100 00000000 01011111" in said third, fourth, and fifth groups of said first set of binary information in said data string associated with video frame F_1 which is saved in the $r_{1/1}g_{1/1}b_{1/1}$ memory register within the Static Video Player **320** at time t_1. The "00001 00001" in the first and second groups of the only set of binary information in the data string associated with video frame F_8 identify pixel h_1l_1; the "00000000 10001100 01110110" in the third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_8 identify a shade of teal, being a complex color generated by the mixture of the basic colors $R_{000}G_{140},B_{118}$; and the "0001000" the sixth group of the only set of binary information in the data string associated with video frame F_8 identifies the time t_8 when the Static Video Player **320** is to save the teal ($R_{000}G_{140}B_{118}$) color information into memory registers $r_{1/1}g_{1/1}b_{1/1}$ and when the sequential serial transmission of color information

by video frame reaches the point when color information related to video frame F_8 is to be accessed from the Static Video File **310**, the Static Video Player **320** replicates and saves color information related to video frame F_8 from the Static Video File **310** into the video frame buffer memory, including said "00000000 10001100 01110110" in said third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_8, and then the Static Video Player **320** invokes a parallel data dump of all color information related to video frame F_8 from the video frame buffer memory to the red/green/blue memory registers, including said "00000000 10001100 01110110" in said third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_8, which is saved in the $r_{1/1}g_{1/1}b_{1/1}$ memory register within the Static Video Player **320** at time t_8. The "00100 00111" in the first and second groups of the second set of binary information in the data string associated with video frame F_1 identify pixel h_4l_7; the "01001010 11111111 00000000" in the third, fourth, and fifth groups of the second set of binary information in the data string associated with video frame F_1 identify a shade of lime green, being a complex color generated by the mixture of the basic colors $R_{074}G_{255}B_{000}$; and the "0000001" in the sixth group of the second set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** is to save the lime green ($R_{074}G_{255}B_{000}$) color information into memory registers $r_{4/7}g_{4/7}b_{4/7}$, and upon commencing the sequential serial transmission of color information by video frame from the Static Video File **310**, the Static Video Player **320** replicates and saves color information related to video frame F_1 from the Static Video File **310** into the video frame buffer memory, including said "01001010 11111111 00000000" in said third, fourth, and fifth groups of said second set of binary information in said data string associated with video frame F_1, and then the Static Video Player **320** invokes a parallel data dump of all color information related to video frame F_1 from the video frame buffer memory to the red/green/blue memory registers, including said "01001010 11111111 00000000" in said third, fourth, and fifth groups of said second set of binary information in said data string associated with video frame F_1, which is saved in the $r_{4/7}g_{4/7}b_{4/7}$ memory register within the Static Video Player **320** at time t_1. The "00100 00111" in the first and second groups of the only set of binary information in the data string associated with video frame F_6 identify pixel h_4l_7; the "10001110 11000011 11101000" in the third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_6 identify a shade of powder blue, being a complex color generated by the mixture of the basic colors $R_{142}G_{195}B_{232}$; and the "0000110" the sixth group of the only set of binary information in the data string associated with video frame F_6 identifies the time t_6 when the Static Video Player **320** is to save the powder blue ($R_{142}G_{195}B_{232}$) color information into memory registers $r_{4/7}g_{4/7}b_{4/7}$, and when the sequential serial transmission of color information by video frame reaches the point when color information related to video frame F_6 is to be accessed from the Static Video File **310**, the Static Video Player **320** replicates and saves color information related to video frame F_6 from the Static Video File **310** into the video frame buffer memory, including said "10001110 11000011 11101000" in said third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_6, and then the Static Video Player **320** invokes a parallel data dump of all color information related to video frame F_6 from the video frame buffer memory to the red/green/blue memory registers, including said "10001110 11000011 11101000" in said third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_6, which is saved in the $r_{4/7}g_{4/7}b_{4/7}$ memory register within the Static Video Player **320** at time t_6. The "01011 10100" in the first and second groups of the third set of binary information in the data string associated with video frame F_1 identify pixel $h_{11}l_{20}$; the "11101001 11100100 00000000" in the third, fourth, and fifth groups of the third set of binary information in the data string associated with video frame F_1 identify a shade of lemon yellow, being a complex color generated by the mixture of the basic colors $R_{233}G_{228}B_{000}$; and the "0000001" in the sixth group of the third set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** is to save the lemon yellow ($R_{233}G_{228}B_{000}$) color information into memory registers $r_{11/20}g_{11/20}b_{11/20}$, and upon commencing the sequential serial transmission of color information by video frame from the Static Video File **310**, the Static Video Player **320** replicates and saves color information related to video frame F_1 from the Static Video File **310** into the video frame buffer memory, including said "11101001 11100100 00000000" in said third, fourth, and fifth groups of said third set of binary information in said data string associated with video frame F_1, and then the Static Video Player **320** invokes a parallel data dump of all color information related to video frame F_1 from the video frame buffer memory to the red/green/blue memory registers, including said "11101001 11100100 00000000" in said third, fourth, and fifth groups of said third set of binary information in said data string associated with video frame F_1 which is saved in the $r_{11/20}g_{11/20}b_{11/20}$ memory register within the Static Video Player **320** at time t_1.

Additionally, the invention utilizes the Static Video Player **320** to display, and/or replicate, color information saved from the Static Video File **350** into the red/green/blue memory registers in the Static Video Player **320** in a similar manner as mentioned above for the color information received by the Static Video Player **320** by the Static Video File **310**. The Static Video Player **320** may receive color information from the Static Video File **350** via the Electronic Connection **340** in a download fashion or in a broadcast fashion. As example, in a download transmission, a sending computer system may create an electronic copy of a Static Video File **350** and transmit said Static Video File **350** serially by means of a conventional modem electronically connected to the Electronic Connection **340** and received by a receiving computer system by means of a conventional modem electronically connected to the Electronic Connection **340** and electronically stored in the hard disk of the receiving computer system (i.e. U.S. Pat. No. 5,191,573). Also as example, in a broadcast transmission, a sending computer system may create an electronic copy of a Static Video File **350** and transmit said Static Video File **350** serially, and at the normal display rate of the video recording, by means of a conventional modem electronically connected to the Electronic Connection **340** and received by a receiving computer system by means of a conventional modem electronically connected to the Electronic Connection **340** and subsequently transmitted by the receiving computer system to the video card of the receiving computer system for display on the Video Output Device **390**.

When the Static Video Player **320** commences the display, and/or replication, process, whatever $R_vG_vB_v$ color information has been saved within the video memory registers $r_{x/y}g_{x/y}b_{x/y}$ will be displayed, and/or replicated, within the

corresponding h_xl_y pixel on the Video Output Device **390**. For each video frame F_z, the Static Video Player **320** first saves any new $R_vG_vB_v$ color information into the video memory registers $r_{x/y}g_{x/y}b_{x/y}$, then the Static Video Player **320** displays complex colors, as generated by the color information in the video memory registers $r_{x/y}g_{x/y}b_{x/y}$, within the corresponding pixels h_xl_y on the Video Output Device **390** at time t_z corresponding to video frame F_w. For any video frame F_w, if any memory register $r_{x/y}g_{x/y}b_{x/y}$ is not updated by the Static Video Player **320** with new $R_vG_vB_v$ color information from the Static Video File **310**, then the $R_vG_vB_v$ color information within any such memory register $r_{x/y}g_{x/y}b_{x/y}$ will not be altered until the Static Video Player **320** receives updated $R_vG_vB_v$ color information from the Static Video File **310** corresponding to said memory register $r_{x/y}g_{x/y}b_{x/y}$. The Static Video Player **320** sequentially replicates, one video frame at a time, the color information contained in all of the red/green/blue memory registers into a video card buffer memory within the Static Video Player **320**. The Static Video Player **320** then transmits said color information to the video card of the host computer. Upon receipt of the color information, said video card transmits said color information to the Video Output Device **390** for display. As example, the Static Video Player **320** invokes a parallel data dump of the color information related to the first video frame from the red/green/blue memory registers to a video card buffer memory within the Static Video Player **320**. Next, the Static Video Player **320** accesses the video card buffer memory, sequentially by video frame and at the intended playback rate (i.e. 30 video frames per second for motion picture quality recordings), and invokes a parallel data dump of all of the color information related to said first video frame to said video card through an electronic connecting bus. Upon receipt of the color information related to said first video frame, said video card will transmit/relay, in either digital form or analog form, the color information related to said first video frame to the Video Output Device **390** for display. While the Static Video Player **320** invokes a parallel data replication of the color information related to said first video frame from the red/green/blue memory registers to said video card buffer memory, the Static Video Player **320** invokes a parallel data dump of the color information related to the second video frame from the video frame buffer memory (as mentioned hereinabove) to said red/green/blue memory registers. Then, while the Static Video Player **320** invokes a parallel data dump of the color information related to said first video frame from said video card buffer memory to said video card, the Static Video Player **320** invokes a parallel data replication of the color information related to the second video frame from said red/green/blue memory registers to said video card buffer memory. Then, while said video card transmits/relays the color information related to said first video frame to the Video Output Device **390** for display, the Static Video Player **320** invokes a parallel data dump of the color information related to said second video frame from said video card buffer memory to said video card through said electronic connecting bus. Upon receipt of the color information related to said second video frame, said video card will transmit/relay, in either digital form or analog form, the color information related to said second video frame to the Video Output Device **390** for display. The color information in the third video frame, forth video frame, fifth video frame, etc. will continue in the above manner until the end of the Static Video File **310**.

Additionally, the Static Video Player **320** is capable of displaying, and/or replicating, color information in either digital video form or analog video form on the Video Output Device **390** within pixels h_xl_y corresponding to said video memory registers $r_{x/y}g_{x/y}b_{x/y}$. Again, using the previous example where the Static Video File **310** mathematically represents a video recording as the algorithm "F_w= $h_xl_yR_vG_vB_vt_z$" and expressed in binary terms as: F_1=00001 00001 01110100 00000000 01011111 0000001 00100 00111 01001010 11111111 00000000 0000001 01011 10100 11101001 11100100 00000000 0000001; F_6=00100 00111 10001110 11000011 11101000 0000110; F_8=00001 00001 00000000 10001100 01110110 0001000; which mathematically represents a video recording (see FIG. **19**) whereby a shade of purple ($R_{116}G_{000}B_{095}$) is to be displayed within pixel h_1l_1 of a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, and F_7, then in video frame F_8 a shade of teal ($R_{000}G_{140}B_{118}$) is to be displayed within pixel h_1l_1; a shade of lime green ($R_{074}G_{255}B_{000}$) is to be displayed within pixel h_4l_7 on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, and F_5, then in video frames F_6, F_7, and F_8 a shade of powder blue ($R_{142}G_{195}B_{232}$) is to be displayed within pixel h_4l_7; and a shade of lemon yellow ($R_{233}G_{228}B_{000}$) is to be displayed within pixel $h_{11}l_{20}$ on a Video Output Device **390** in video frames F_1, F_2, F_3, F_4, F_5, F_6, F_7, and F_8 (see FIG. **11**). The "00001 00001" in the first and second groups of the first set of binary information in the data string associated with video frame F_1 identify pixel h_1l_1; the "01110100 00000000 01011111" in the third, fourth, and fifth groups of the first set of binary information in the data string associated with video frame F_1 identify a shade of purple, being a complex color generated by the mixture of the basic colors $R_{116}G_{000}B_{195}$; and the "0000001" in the sixth group of the first set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** will commence to display within pixel h_1l_1 on the Video Output Device **390** commencing with video frame F_1 said shade of purple ($R_{116}G_{000}B_{095}$), as saved in time t_1 in the $r_{1/1}g_{1/1}b_{1/1}$ memory registers which correspond to said pixel h_1l_1, and the Static Video Player **320** will continue to display said shade of purple ($R_{116}G_{000}B_{095}$) within pixel h_1l_1 on the Video Output Device **390** during video frames F_2, F_3, F_4, F_5, F_6, and F_7 since the Static Video File **310** does not have instructions for the Static Video Player **320** to alter said $r_{1/1}g_{1/1}b_{1/1}$ memory registers during times t_2, t_3, t_4, t_5, t_6, and t_7. Upon commencing the sequential parallel data replication of color information by video frame from the red/green/blue memory registers to the video card buffer memory, the Static Video Player **320** invokes a sequential parallel data replication of color information related to video frame F_1 from the red/green/blue memory registers into the video card buffer memory, including said "01110100 00000000 01011111" in the $r_{1/1}g_{1/1}b_{1/1}$ memory register. Next, the Static Video Player **320** invokes a parallel data dump of color information related to video frame F_1 from the video card buffer memory to the video card within the host computer system, including said "01110100 00000000 01011111" related to said pixel h_1l_1 in video frame F_1. Next, the video card relays/transmits said color information related to video frame F_1 to the corresponding pixels h_xl_y of the Video Output Device **390**, including said shade of purple ($R_{116}G_{000}B_{095}$) to commence to be displayed within pixel h_1l_1 of the Video Output Device **390** time t_1. The "00001 00001" in the first and second groups of the first set of binary information in the data string associated with video frame F_8 identify pixel h_1l_1; the "00000000 10001100 01110110" in the third, fourth, and fifth groups of the first set of binary information in the data string associated with video frame F_8 identify a shade of

teal, being a complex color generated by the mixture of the basic colors $R_{000}G_{140}B_{118}$; and the "0001000" in the sixth group of the first set of binary information in the data string associated with video frame F_8 identifies the time t_8 when the Static Video Player **320** will commence to display within pixel h_1l_1 on the Video Output Device **390** commencing with video frame F_8 said shade of teal ($R_{000}G_{140}B_{118}$), as saved in time t_8 in the $r_{1/1}g_{1/1}b_{1/1}$ memory registers which correspond to said pixel h_1l_1. When the sequential parallel data replication of color information by video frame reaches the point when color information related to video frame F_8 is to be replicated to the video card buffer memory, the Static Video Player **320** invokes a sequential parallel data replication of color information related to video frame F_8 from the red/green/blue memory registers into the video card buffer memory, including said "00000000 10001100 01110110" in the $r_{1/1}g_{1/1}b_{1/1}$ memory register. Next, the Static Video Player **320** invokes a parallel data dump of color information related to video frame F_8 from the video card buffer memory to the video card within the host computer system, including said "00000000 10001100 01110110" related to said pixel h_1l_1 in video frame F_8. Next, the video card relays/transmits said color information related to video frame F_8 to the corresponding pixels h_xl_y of the Video Output Device **390**, including said shade of teal ($R_{000}G_{140}B_{118}$) to commence to be displayed within pixel h_1l_1 of the Video Output Device **390** in time t_8. The "00100 00111" in the first and second groups of the second set of binary information in the data string associated with video frame F_1 identify pixel h_4l_7; the "01001010 11111111 00000000" in the third, fourth, and fifth groups of the second set of binary information in the data string associated with video frame F_1 identify a shade of lime green, being a complex color generated by the mixture of the basic colors $R_{074}G_{255}B_{000}$; and the "0000001" in the sixth group of the second set of binary information in the data string associated with video frame F_1 identifies the time t_1 when the Static Video Player **320** will commence to display within pixel h_4l_7 on the Video Output Device **390** commencing with video frame F_1 said shade of lime green ($R_{074}G_{255}B_{000}$), as saved in time t_1 in the $r_{4/7}g_{4/7}b_{4/7}$ memory registers which correspond to said pixel h_4l_7, and the Static Video Player **320** will continue to display said shade of lime green ($R_{074}G_{255}B_{000}$) within pixel h_4l_7 on the Video Output Device **390** during video frames F_2, F_3, F_4, and F_5 since the Static Video File **310** does not have instructions for the Static Video Player **320** to alter said $r_{4/7}g_{4/7}b_{4/7}$ memory registers during times t_2, t_3, t_4, and t_5. Upon commencing the sequential parallel data replication of color information by video frame from the red/green/blue memory registers to the video card buffer memory, the Static Video Player **320** invokes a sequential parallel data replication of color information related to video frame F_1 from the red/green/blue memory registers into the video card buffer memory, including said "01001010 11111111 00000000" in the $r_{4/7}g_{4/7}b_{4/7}$ memory register. Next, the Static Video Player **320** invokes a parallel data dump of color information related to video frame F_1 from the video card buffer memory to the video card within the host computer system, including said "01001010 11111111 00000000" related to said pixel h_4l_7 in video frame F_1. Next, the video card relays/transmits said color information related to video frame F_1 to the corresponding pixels h_xl_y of the Video Output Device **390**, including said shade of lime green ($R_{074}G_{255}B_{000}$) to commence to be displayed within pixel h_4l_7 of the Video Output Device **390** time t_1. The "00100 00111" in the first and second groups of the only set of binary information in the data string associated with video frame F_6 identify pixel h_4l_7; the "10001110 11000011 11101000" in the third, fourth, and fifth groups of the only set of binary information in the data string associated with video frame F_6 identify a shade of powder blue, being a complex color generated by the mixture of the basic colors $R_{142}G_{195}B_{232}$; and the "0000110" in the sixth group of the only set of binary information in the data string associated with video frame F_6 identifies the time t_6 when the Static Video Player **320** will commence to display within pixel h_4l_7 on the Video Output Device **390** commencing with video frame F_6 said shade of powder blue ($R_{142}G_{195}B_{232}$), as saved in time t_6 in the $r_{4/7}g_{4/7}b_{4/7}$ memory registers which correspond to said pixel h_4l_7, and the Static Video Player **320** will continue to display said shade of powder blue ($R_{142}G_{195}B_{232}$) within pixel h_4l_7 on the Video Output Device **390** during video frames F_7 and F_8 since the Static Video File **310** does not have instructions for the Static Video Player **320** to alter said $r_{4/7}g_{4/7}b_{4/7}$ memory registers during times t_7 and t_8. When the sequential parallel data replication of color information by video frame reaches the point when color information related to video frame F_6 is to be replicated to the video card buffer memory, the Static Video Player **320** invokes a sequential parallel data replication of color information related to video frame F_8 from the red/green/blue memory registers into the video card buffer memory, including said "10001110 11000011 11101000" in the $r_{4/7}g_{4/7}b_{4/7}$ memory register. Next, the Static Video Player **320** invokes a parallel data dump of color information related to video frame F_6 from the video card buffer memory to the video card within the host computer system, including said "10001110 11000011 11101000" related to said pixel h_4l_7 in video frame F_6. Next, the video card relays/transmits said color information related to video frame F_6 to the corresponding pixels h_xl_y of the Video Output Device **390**, including said shade of powder blue ($R_{142}G_{195}B_{232}$) to commence to be displayed within pixel h_4l_7 of the Video Output Device **390** in time t_6. The "01011 10100" in the first and second groups of the third set of binary information in the data string associated with video frame F_1 identify pixel $h_{11}l_{20}$; the "11101001 11100100 00000000" in the third, fourth, and fifth groups of the third set of binary information in the data string associated with video frame F_1 identify a shade of lemon yellow, being a complex color generated by the mixture of the basic colors $R_{233}G_{228}B_{000}$; and the "0000001" in the sixth group of the third set of binary information in the data string associated with video frame F_1 identifies the time $t_1$when the Static Video Player **320** will commence to display within pixel $h_{11}l_{20}$ on the Video Output Device **390** commencing with video frame F_1 said shade of lemon yellow ($R_{233}G_{228}B_{000}$), as saved in time t_1 in the $r_{11/20}g_{11/20}b_{11/20}$ memory registers which correspond to said pixel $h_{11}l_{20}$, and the Static Video Player **320** will continue to display said shade of lemon yellow ($R_{233}G_{228}B_{000}$) within pixel $h_{11}l_{20}$ on the Video Output Device **390** during video frames F_2, F_3, F_4, F_5, F_6, F_7, and F_8 since the Static Video File **310** does not have instructions for the Static Video Player **320** to alter said $r_{11/20}g_{11/20}b_{11/20}$ memory registers during times t_2l t_3, t_{41} t_5, t_6, t_7, and t_8. Upon commencing the sequential parallel data replication of color information by video frame from the red/green/blue memory registers to the video card buffer memory, the Static Video Player **320** invokes a sequential parallel data replication of color information related to video frame F_1 from the red/green/blue memory registers into the video card buffer memory, including said "11101001 11100100 00000000" in the $r_{11/20}g_{11/20}b_{11/20}$ memory register. Next, the Static Video Player **320** invokes a parallel data dump of color information related to video frame F_1

from the video card buffer memory to the video card within the host computer system, including said "11101001 11100100 00000000" related to said pixel $h_{11}l_{20}$ in video frame F_1. Next, the video card relays/transmits said color information related to video frame F_1 to the corresponding pixels h_xl_y of the Video Output Device **390**, including said shade of lime green ($R_{074}G_{225}B_{000}$) to commence to be displayed within pixel $h_{11}l_{20}$ of the Video Output Device **390** time t_1.

As discussed above, the color information saved in the $r_{1/1}g_{1/1}b_{1/1}$ memory registers within in the Static Video Player **320** can be obtained from the Static Video File **310** one video frame at a time during real-time playback of the video recording or the Static Video Player **320** can obtain and schedule color information changes for all video frames F_w in the video recording, by pixel h_xl_y from the Static Video File **310** at, or before, the commencement of playback of the video recording, or a combination thereof.

Furthermore, and as example, if the Static Video Player **320** is displaying within a pixel h_xl_y on a Video Output Device **390** a complex color, and the difference between said complex color and the new complex color is due only to a change in the shade of the basic color green G_v, and the shades of the basic colors red R_v and blue B_v do not change, then the Static Video File **310** could only be required to contain new information as to the basic color green G_v, and the Static Video Player **320** could only be required to replace the green $g_{x/y}$ memory register within the Static Video Player **320** related to said pixel h_xl_y, with the green color information G_v from the Static Video File **310**, thereby enabling the Static Video Player **320** to subsequently display, and/or replicate, the new specific complex color within said pixel h_xl_y on the Video Output Device **390**.

Additionally, the Static Video Player **320** can be configured to contain one or more memory registers corresponding to each discrete pixel h_xl_y, in which information from the Static Video File **310** can be saved. As example, the red/green/blue information may be configured to be saved in only one memory register corresponding with a pixel h_xl_y rather than to the individual $r_{1/1}g_{1/1}b_{1/1}$ memory registers.

Additionally, if a video recording contains a situation in which a specific color is to be displayed within a plurality of contiguous pixels, forming a geometric shape, on a Video Output Device **390** commencing with a specific video frame F_w, instead of recording the entire volume of said geometric shape within the Static Video File **310**, only the corners (either interior or exterior corners) of said geometric shape could be recorded within the Static Video File **310** along with information instructing the Static Video Player **320** to colorized with said specific color the pixels h_xl_y within said geometric shape. By means of example (see Geometric Shape **1** in FIG. **20**), video frame F_{56} of a video recording contains a grouping of contiguous pixels which form a rectangle (Geometric Shape **1**) with corners located at pixels h_3l_5, h_3l_{18}, h_8l_{18}, and h_8l_5 in which the complex color red ($R_{255}G_{000}B_{000}$) is to commence to be displayed in time t_{56}. The color information within the Static Video File **310**, with respect to said red colored rectangle within said video frame F_{56} is encoded to contain only said 4 corner pixels h_3l_5, h_3l_{18}, h_8l_{18}, and h_8l_5, instead of the 84 individual pixels within the volume of said red ($R_{255}G_{000}B_{000}$) rectangle, and the Static Video Player **320** would save the complex color red ($R_{255}G_{000}B_{000}$) in the video memory registers $r_{x/y}g_{x/y}b_{x/y}$ corresponding to all pixels within the volume of the rectangle defined by the corners occupying pixels h_3l_5, h_3l_{18}, h_8l_{18}, and h_8l_5. To accomplish this, the algorithm "$F_x=h_xl_yR_vG_vB_vt_z$" as used in the previous example detailing how a Static Video File **310** could be encoded, would be modified to become the algorithm "$F_x=h_xl_y \ldots h_xl_yS_jR_vG_vB_vt_z$" where the "$h_xl_y \ldots h_xl_y$" identifies an unlimited plurality, or groupings, of pixels within a set of binary information in a data string associated with a video frame F_{56}, and the "S_0" identifies a code, expressed in binary terms as S_0=0000000000, which informs the Static Video Player **320** that the preceding groups of data identified the pixels which correspond to the corners of the red rectangle. Therefore, said algorithm "$F_x=h_xl_y \ldots h_xl_yS_0R_vG_vB_vt_z$" for the preceding Geometric Shape **1** would be mathematically expressed as "$F_{56}=h_3l_5h_5l_{18}h_8l_{18}h_8l_5S_0R_{255}G_{000}B_{000}t_{56}$" and would be expressed in binary terms as: F_{56}=00000011 00000101 00000011 00010010 00001000 00010010 00001000 00000101 0000000000 11111111 00000000 00000000 0111000. Again by means of example (see Geometric Shape **2** in FIG. **20**), video frame F_{56} of a video recording contains a grouping of contiguous pixels which form an irregularly shaped polygon with corners located at pixels $h_{12}l_3$, $h_{12}l_4$, $h_{15}l_4$, $h_{15}l_7$, $h_{14}l_7$, $h_{14}l_8$, $h_{17}l_8$, $h_{17}l_6$, $h_{20}l_6$, $h_{20}l_5$, $h_{16}l_5$, and $h_{16}l_3$ in which the complex color blue ($R_{000}G_{000}B_{255}$) is to commence to be displayed in time t_{56}. The color information within the Static Video File **310**, with respect to said blue colored irregularly shaped polygon within said video frame F_{56} is encoded to contain only said 12 corner pixels $h_{12}l_3$, $h_{12}l_4$, $h_{15}l_4$, $h_{15}l_7$, $h_{14}l_7$, $h_{14}l_8$, $h_{17}l_8$, $h_{17}l_6$, $h_{20}l_6$, $h_{20}l_5$, $h_{16}l_5$, and $h_{16}l_3$, instead of the 30 individual pixels within the volume of said blue ($R_{000}G_{000}B_{255}$) irregularly shaped polygon (Geometric Shape **2**), and the Static Video Player **320** would save the complex color blue ($R_{000}G_{000}B_{255}$) in the video memory registers $r_{x/y}g_{x/y}b_{x/y}$ corresponding to all pixels within the volume of the irregularly shaped polygon defined by the corners occupying pixels $h_{12}l_3$, $h_{12}l_4$, $h_{15}l_4$, $h_{15}l_7$, $h_{14}l_7$, $h_{14}l_8$, $h_{17}l_8$, $h_{17}l_6$, $h_{20}l_6$, $h_{20}l_5$, $h_{16}l_5$, and $h_{16}l_3$. To accomplish this, the algorithm "$F_x=h_xl_yR_vG_vB_vt_z$" as used in the previous example detailing how a Static Video File **310** could be encoded, would be modified to become the algorithm "$F_x=h_xl_y \ldots h_xl_yS_jR_vG_vB_vt_z$" where the "$h_xl_y \ldots h_xl_y$" identifies an unlimited plurality, or groupings, of pixels within a set of binary information in a data string associated with a video frame F_{56}, and the "S" identifies a code, expressed in binary terms as S_0=0000000000, which informs the Static Video Player **320** that the preceding groups of data identified the pixels which correspond to the corners of the blue irregularly shaped polygon. Therefore, said algorithm "$F_x=h_xl_y \ldots h_xl_yS_0R_vG_vB_vt_z$" for the preceding Geometric Shape **2** would be mathematically expressed as "$F_{56}=h_{12}l_3h_{12}l_4h_{15}l_4h_{15}l_7h_{14}l_7h_{14}l_8h_{17}l_8h_{17}l_6h_{20}l_6h_{20}l_5h_{16}l_5h_{16}l_3S_0R_{000}G_{000}B_{255}t_{56}$" and would be expressed in binary terms as: F_{56}=00001100 00000011 00001100 00000100 00001111 00000100 00001111 00000111 00001110 00000111 00001110 00001000 00010001 00001000 00010001 00000110 00010100 00000110 00010100 00000101 00010000 00000101 00010000 00000011 0000000000 00000000 00000000 11111111 0111000. Additionally, and to add efficiency to the encoding process, the Static Video File **310** can be structured to accommodate a "layering" or "overlapping" of geometric shapes within an individual video frame F_w. The encoding of a single video frame F_w of a Static Video File **310** can be separated into a plurality of video sub frames F_w^s, where the superscript "s" identifies a range of video sub frames for said video frame F_w. As example, commencing with a specific video frame F_w of a video recording in which a Video Output Device **390** is to display a second specific color within a plurality of contiguous pixels forming a second geometric shape, said second geometric shape being located within a first geomet-

ric shape formed by a plurality of contiguous pixels in which a Video Output Device **390** is to display a first specific color, and said second geometric shape occupies some common pixels as does said first geometric shape. To accomplish this, color information related to said first geometric shape is encoded in a video sub frame F_w^1 of the Static Video File **310**, where the superscript "1" identifies the first layer, or first video sub frame, of video frame F_w; next the color information related to said second geometric shape is encoded in a video sub frame F_w^2 of the Static Video File **310**, where the superscript "**2**" identifies the second layer, or second video sub frame, of video frame F_w. The Static Video Player **320** is capable of building a single video frame F_w from a plurality of video sub frames F_w^s, where the superscript "s" identifies a range of video sub frames for a single video frame F_w. The Static Video Player **320** invokes a sequential serial transmissions of color information related to said video sub frame F_w^1 from the Static Video File **310** into the video frame buffer memory; next the Static Video Player **320** invokes a parallel data dump of color information related to said video sub frame F_w^1 from the video frame buffer memory into the red/green/blue memory registers; as the Static Video Player **320** invokes a parallel data dump of color information related to said video sub frame F_w^1 from the video frame buffer memory into the red/green/blue memory registers, the Static Video Player **320** also invokes a sequential serial transmissions of color information related to said video sub frame F_w^2 from the Static Video File **310** into the video frame buffer memory; before the Static Video Player **320** invokes a parallel data dump of color information related to said video frame F_w from red/green/blue memory registers into the video card buffer memory, the Static Video Player **320** invokes a parallel data dump of color information related to said video sub frame F_w^2 from the video frame buffer memory into the red/green/blue memory registers, thus building said video frame F_w in layers. Further detailing this example (see Geometric Shapes **3** & **4** in FIG. **20**), video frame F_{56} of a video recording contains two geometric shapes, an irregularly shaped polygon (Geometric Shape **3**) and a single pixel (Geometric Shape **4**) within said irregularly shaped polygon. An irregularly shaped polygon with corners occupying pixels $h_{12}l_{20}$, $h_{19}l_{20}$, $h_{19}l_{22}$, $h_{20}l_{22}$, $h_{20}l_{19}$, $h_{22}l_{19}$, $h_{22}l_{18}$, $h_{19}l_{18}$, $h_{19}l_{15}$, and $h_{17}l_{15}$ of a Video Output Device **390** in which the complex color green ($R_{000}G_{255}B_{000}$) is to commence to be displayed in time t_{56}. Additionally, the complex color black ($R_{000}G_{000}B_{000}$) is to commence to be displayed in a single pixel $h_{18}l_{18}$ of a Video Output Device **390**, also in time t_{56}. To build video frame F_{56}, the algorithm "$F_x=h_xl_y \ldots h_xl_yS_jR_vG_vB_vt_z$" would be used twice with respect to Geometric Shapes **3** & **4**. Therefore, video frame F_{56} would be mathematically expressed as "$F_{56}^1=h_{12}l_{20}h_{19}l_{20}h_{19}l_{22}h_{20}l_{22}h_{20}l_{19}h_{22}l_{19}h_{22}l_{18}h_{19}l_{18}h_{19}l_{15}h_{17}l_{15}S_0R_{000}G_{255}B_{000}t_{56}+F_{56}^2=h_{18}l_{18}S_0R_{000}G_{000}B_{000}t_{56}$" and video frame F_{56} would be expressed in binary terms as: F_{56}^1=00001100 00010100 00010011 00010100 00010011 00010110 00010100 00010110 00010100 00010011 00010110 00010011 00010110 00010010 00010011 00010010 00010011 00001111 00010001 00001111 0000000000 00000000 11111111 00000000 0111000; F_{56}^2= 0010010 00010010 0000000000 00000000 00000000 00000000 0111000.

The analyzing mechanism for the system above can alternatively include the frequency/amplitude database compiler **80** and the dynamic to static audio truncator **100**, or the red/green/blue database compiler **280** and the dynamic to static video truncator **300**. The playing mechanism can include a static audio file and a static audio player **120** and an audio output device, or a static video file **310** and a static video player **320** and a video output device.

Although the invention has been described in detail in the foregoing embodiments for the purpose of illustration, it is to be understood that such detail is solely for that purpose and that variations can be made therein by those skilled in the art without departing from the spirit and scope of the invention except as it may be described by the following claims.

What is claimed is:

1. A system for manipulation of video signals comprising:

a memory mechanism having color information by pixel by video frame of a video signal;

an analyzing mechanism for analyzing color information by pixel by video frame of the video signal and identifying patterns of specific color entries for a discrete pixel of the video signal over multiple and consecutive video frames, said analyzing mechanism connected to said memory mechanism; and

a playing mechanism for playing said video signal, said playing mechanism connected to said memory mechanism and said analyzing mechanism, said playing mechanism continuing to play the corresponding color information for each pixel by video frame obtained from the memory mechanism for a first video frame until the color information changes in the video signal as indicated by the analyzing mechanism, at which time the changed color information is played from the memory mechanism.

2. A method for manipulating video signals comprising the steps of:

receiving a video signal;

converting the video signal into a digital signal;

playing the video signal based on the color of its pixel in its first video frame;

determining for its pixel of its second video frame of the video signal whether the color of the video signal has changed from the color of its pixel of its first video frame;

continuing to play the same color of the video signal for its pixel of its second video frame if it has not changed without obtaining the color of its pixel of its second video frame from memory; and

playing a new color of its pixel it the video signal has changed.

3. A method for manipulating video signals comprising the steps of:

filling a color database with specific color entries for corresponding pixels of color information by video frames of the digital video signals;

identifying patterns of consecutive specific color entries for a discrete pixel over the pixels by video frames for a specific color;

filling a static video file with a first starting point of a first specific color of a discrete pixel with respect to multiple and consecutive video frames;

filling a static video file with a second starting point of a second specific color of a discrete pixel with respect to multiple and consecutive frames;

providing a static video player with a starting point of a first specific color of a discrete pixel with respect to multiple and consecutive video frames from the static video file;

playing the first specific color of the discrete pixel by means of the static video player when the first starting point occurs;

continuing to play the first specific color of the discrete pixel by means of the static video player after the first starting point occurs;

providing the static video player with a next starting point of a next specific color of the discrete pixel with respect to multiple and consecutive video frames from the static video file;

playing the next specific color of the discrete pixel by means of the static video player when the next starting point occurs;

continuing to play the next specific color of the discrete pixel by means of the static video player after the next starting point occurs; and

stopping the playing of the static video player at the end of the static video file.

4. A method as described in claim **3** wherein before the filling step, there is the step of converting the analog video signal into a digital video signal.

5. A method as described in claim **4** including before the converting step, there is the step of recording an analog video signal.

6. A system for manipulation of video signals comprising:

a memory mechanism;

a storing mechanism for storing video signals as specific color entries for a discrete pixel in the memory mechanism, said storing mechanism connected to the memory mechanism;

an identifying mechanism for identifying one or more consecutive specific color entries for a discrete pixel over multiple and consecutive video frames and their respective starting points with respect to multiple and consecutive video frames, said identifying mechanism connected to the storing mechanism; and

a playing mechanism for playing the specific color entries stored in the memory mechanism for a discrete pixel commencing with their starting points, and continuing to play said specific color entries for said discrete pixel after their starting points until the memory mechanism contains different specific color entries for said discrete pixel, said playing mechanism connected to the identifying mechanism.

7. A system as described in claim **6** wherein the playing mechanism is remote from the identifying mechanism.

8. A system as described in claim **7** wherein the playing mechanism includes telecommunication lines that connect with the identifying mechanism.

9. A system as described in claim **8** wherein the playing mechanism includes a color entry mechanism for providing pixels with a specific color.

10. A system as described in claim **9** wherein the playing mechanism includes a controller for playing desired colors for corresponding pixels from the color entry mechanism based on their corresponding starting points, said controller connected to the color entry mechanism and the identifying mechanism.

* * * * *