

DICTIONARY
OF
**COMPUTER
SCIENCE,
ENGINEERING,
AND TECHNOLOGY**

EDITOR-IN-CHIEF
Phillip A. Laplante



CRC Press

Boca Raton London New York Washington, D.C.

Library of Congress Cataloging-in-Publication Data

Dictionary of computer science, engineering, and technology / edited by Phillip Laplante.

p. cm.

Includes bibliographical references and index.

ISBN 0-8493-2691-5 (alk. paper)

1. Computer science—Dictionaries. 2. Engineering—Dictionaries. 3.

Technology—Dictionaries. I. Laplante, Phillip A.

QA76.15.D5258 2000

004'.03—dc21

00-052882

This book contains information obtained from authentic and highly regarded sources. Reprinted material is quoted with permission, and sources are indicated. A wide variety of references are listed. Reasonable efforts have been made to publish reliable data and information, but the authors and the publisher cannot assume responsibility for the validity of all materials or for the consequences of their use.

Neither this book nor any part may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, microfilming, and recording, or by any information storage or retrieval system, without prior permission in writing from the publisher.

All rights reserved. Authorization to photocopy items for internal or personal use, or the personal or internal use of specific clients, may be granted by CRC Press LLC, provided that \$.50 per page photocopied is paid directly to Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923 USA. The fee code for users of the Transactional Reporting Service is ISBN 0-8493-2691-5/01/\$0.00+.50. The fee is subject to change without notice. For organizations that have been granted a photocopy license by the CCC, a separate system of payment has been arranged.

The consent of CRC Press LLC does not extend to copying for general distribution, for promotion, for creating new works, or for resale. Specific permission must be obtained in writing from CRC Press LLC for such copying.

Direct all inquiries to CRC Press LLC, 2000 N.W. Corporate Blvd., Boca Raton, Florida 33431.

Trademark Notice: Product or corporate names may be trademarks or registered trademarks, and are used only for identification and explanation, without intent to infringe.

Visit the CRC Press Web site at www.crcpress.com

© 2001 by CRC Press LLC

No claim to original U.S. Government works

International Standard Book Number 0-8493-2591-5

Library of Congress Card Number 00-052882

Printed in the United States of America 2 3 4 5 6 7 8 9 0

Printed on acid-free paper

bit-line capacitance the equivalent capacitance experienced in each "bit line" in a RAM or ROM device. *See also* bit line.

bitmap strictly a one-bit-per-pixel representation for a defined area of a display.

bitmapped image a digital image composed of pixels. Bitmapped images are resolution-dependent; i.e., if the image is stretched, the resolution changes. Also called a raster image. *See also* image, pixel, vector image.

bit normalization the process of shifting a binary pattern to the left until the most significant bit is a 1.

bit-oriented block transfer (bitBLT) a type of processing used mainly for video information characterized by minimal operations performed on large data blocks; a processor designed for such operations. BitBLT operations include transfers, masking, exclusive-OR, and similar logical functions.

bit parallel method to transmit or process information in which several bits are transmitted in parallel: e.g., a bit parallel adder with 4-bit data has 8 input ports for them (plus an initial carry bit); an 8-bit parallel port includes true 8-bit bi-directional datalines.

bit period the time between successive bits in data transmission or data recording. At the transmitter (or recorder) the timing is established by a clock. At the receiver (or reader) an equivalent clock must be recovered from the bit stream.

bit per second (bps) measure of transfer rate of a modem or a bus or any digital communication support. bps and baud are not equivalent because bps is a low-level measure and media; thus, it includes the number of bits sent for the low-level protocol, while baud is typically referred to as a higher level of transmission. *See also* baud and baud rate.

bit plane the binary $N \times N$ image formed by selecting the same bit position of the pixels when

the pixels of an $N \times N$ image are represented using k bits.

bit plane encoding lossless binary encoding of the bit planes is termed bit plane encoding. The image is decomposed into a set of k , $N \times N$ bit planes from the least significant bit to $k - 1$ most significant bits and then encoded for image compression.

bit rate a measure of signaling speed; the number of bits transmitted per second. Bit rate and baud are related but not identical. Bit rate is equal to baud times the number of bits used to represent a line state. For example, if there are 16 line states, each line state encodes four bits, and the bit rate is thus four times the baud. *See* baud.

bit serial processing of one bit per clock cycle. If word length is W , then one sample or word is processed in W clock cycles. In contrast, all W bits of a word are processed in the same clock cycle in a bit-parallel system.

For example: a bit serial adder with 4-bit data has one input signal for each bit of data, one bit for carry-in, and two 4-bit shift registers for data.

bit-slice processor a processor organization that performs separate computations (via multiple processing units) separately upon subsections of an incoming channel.

bits per pixel the number of bits used to describe the color or intensity of a pixel. For example, using 8 bits to store a value from the RGB color model would permit 3 bits to be used for both red and green values and 2 bits for the blue value. Blue gets a smaller range because the human eye contains less blue cones and thus is less sensitive to blue variations. True color images have 24 bits per pixel, or 8 bits for each of the red, green, and blue pixels. Typical grayscale images have 8 bits per pixel, giving 256 different gray levels. Compressed image sizes are often represented in bits per pixel, i.e., the total number of bits used to represent the compressed image divided by the total number of pixels.

bitwise an operation, typically a logical operation such as and, or, complement, or exclusive