

CENTRAL LOCK AND CANOPY

Field of Invention

The present invention relates to an outdoor product, in particular to a central lock and a canopy.

Description of Related Arts

With the continuous improvement of people's life, the use of canopys is increasingly frequent. Generally each canopy comprises a foldable canopy frame and a canopy fabric, the canopy frame consists of a roof frame and four or more supporting legs, the supporting legs are used for supporting the roof frame and are provided with a locking structure on each supporting leg respectively, the canopy fabric covers the roof frame and is used for sunshading, rain sheltering or wind sheltering. At present, the locking structure is generally a locking pin, and an unfolded state of the canopy is locked by way of respectively locking each supporting leg. However, this way has the following defects:

In a process that a canopy is unfolded or folded, a user needs to perform a locking operation or an unlocking operation on a locking mechanism of each supporting leg one by one when unfolding or folding the canopy, the operation is cumbersome, functional defects or misoperation of forcing unlocking would be caused if it is forgotten, and the unfolding or folding of the canopy needs cooperation of many people such that the canopy can be erected. In addition, in a process that the canopy is unfolded and is erected, stresses of stress points of a plurality of supporting legs are not uniform, thus it is very difficult to support the canopy at optimum points and consequently the supporting effect of the canopy is influenced. Besides, damages to the canopy are mostly appeared at the supporting legs of the canopy, since positions of sliding blocks need to be fixed after the canopy is unfolded, and holes are opened in the supporting legs at the fixing positions of the sliding blocks for inserting locking pins. Opening holes in the supporting legs weakens supporting strength of the supporting legs, and the supporting legs are usually damaged at the fixing positions of the sliding blocks and

1 consequently the service life of the canopy is shortened.

2

3 **Summary of the Present Invention**

4 In view of the above-mentioned disadvantages of the prior art, one technical problem
5 to be solved by the present invention is to provide a central lock enabling to support an entire
6 canopy and enabling the canopy to be uniformly stressed.

7 In order to realize the above-mentioned purpose, the present invention provides a
8 central lock comprising a center pole, a center top cap fixedly arranged at one end of the
9 center pole, and a center bottom cap detachably connected to the other end of the center pole,
10 a locking piece capable of moving back and forth along a radial direction of the center pole is
11 received in the center bottom cap, a first through hole through which the center pole can pass
12 is provided in the locking piece, and the end part of the center pole is provided with a
13 clamping groove and a clamp locking part located at the lower end of the clamping groove;
14 when the central lock is in a locked state, part of an inner wall of the first through hole of the
15 locking piece is clamped with the clamping groove of the center pole, and an upper end
16 surface of the clamp locking part abuts against a lower end surface of the locking piece; when
17 the central lock is in an unlocked state, the inner wall of the first through hole of the locking
18 piece is separated from the clamping groove, and the clamp locking part can pass through the
19 first through hole.

20 Another technical problem to be solved by the present invention is to provide a
21 canopy having a good supporting effect and uniform stress.

22 In order to realize the above-mentioned purpose, the present invention provides a
23 canopy comprising at least three supporting legs, outer retractable units connected between
24 every two adjacent supporting legs and inner retractable units connected to each supporting
25 leg, the outer retractable units and the inner retractable units form a roof frame of the canopy;
26 the canopy further comprises the above-mentioned central lock, and inner ends of the inner
27 retractable units are connected through the central lock.

28 As described above, the central lock and the canopy provided by the present
29 invention have the following beneficial effects:

1 In the central lock, clamping or separation between the center pole and the locking
2 piece can be achieved through a movement of the locking piece, thereby detachable
3 connection between the center pole and the center bottom cap is achieved, thus with the
4 central lock is applied to the canopy and the canopy is unfolded, the entire canopy can be
5 supported by connecting the center pole with the center bottom cap, the operation is very
6 convenient, uniform stress of each supporting leg of the canopy is guaranteed, and the overall
7 supporting effect of the canopy is improved. In addition, with the canopy with the central
8 lock is unfolded, the canopy can be fixed by connecting the center pole with the center
9 bottom cap, and holes for fixing sliding blocks are not necessary in the supporting legs of the
10 canopy, thereby the strength of the supporting legs of the canopy is enhanced, the structural
11 strength of the canopy is enhanced and the service life of the canopy is prolonged.

12

13 **Brief Description of the Drawings**

14 FIG. 1 illustrates an exploded view of a central lock of the present invention.

15 FIG. 2 illustrates a structural schematic view of a central lock in a locked state.

16 FIG. 3 illustrates an A-A sectional view of FIG. 2.

17 FIG. 4 illustrates a B-B sectional view of FIG. 2.

18 FIG. 5 illustrates a C-C sectional view of FIG. 2.

19 FIG. 6 illustrates a schematic view of a connection between a center pole and a
20 center bottom cap in FIG. 2.

21 FIG. 7 illustrates a structural schematic view of a central lock in an unlocked state.

22 FIG. 8 illustrates a D-D sectional view of FIG. 7.

23 FIG. 9 illustrates an E-E sectional view of FIG. 7.

24 FIG. 10 illustrates an F-F sectional view of FIG. 7.

25 FIG. 11 illustrates a schematic view of a connection between a center pole and a
26 center bottom cap in FIG. 7.

1 FIG. 12 illustrates a G-G sectional view of FIG. 8.
2 FIG. 13 illustrates a top view of a locking piece of the present invention.
3 FIG. 14 illustrates a left view of FIG. 13.
4 FIG. 15 illustrates an H-H sectional view of FIG. 13.
5 FIG. 16 illustrates a structural schematic view of a canopy in an unfolded state of the
6 present invention.
7 FIG. 17 illustrates a structural schematic view of the central lock in FIG. 16.
8 FIG. 18 illustrates a schematic view of a connection of the sliding block, the fixed
9 joint and the supporting leg in FIG. 16.
10 FIG. 19 illustrates a state view of a canopy in an unfolding or folding process.
11 FIG. 20 illustrates a structural schematic view of a canopy after being folded.
12 FIG. 21 illustrates another embodiment of a canopy.
13 FIG. 22 illustrates another embodiment of a central lock of the present invention.
14 FIG. 23 illustrates a schematic view of a connection between the center pole and the
15 center bottom cap when the central lock in FIG. 22 is in a locked state.
16 FIG. 24 illustrates an I-I sectional view of FIG. 23.
17 FIG. 25 illustrates a schematic view of a connection between the center pole and the
18 center bottom cap when the central lock in FIG. 22 is in an unlocked state.
19 FIG. 26 illustrates a J-J sectional view of FIG. 25.

20 Description of reference numerals

- 21 1 Center top cap
22 2 Center pole
23 3 Center bottom cap
24 4 Locking piece

1	5	Spring
2	6	Supporting leg
3	7	Outer retractable unit
4	8	Inner retractable unit
5	9	Sliding sleeve
6	10	Fixed joint
7	11	Screw
8	21	Clamping groove
9	22	Clamp locking part
10	31	Bottom cap seat
11	32	Bottom cap cover
12	41	First through hole
13	42	Groove
14	43	Guide supporting part
15	44	Locking piece pressing part
16	45	Elastic wire
17	46	Unlocking push piece
18	71	First eave pipe
19	72	Second eave pipe
20	81	First oblique top pipe
21	82	Second oblique top pipe
22	83	First connecting rod
23	84	Second connecting rod
24	85	Third oblique top pipe

1	86 Fourth oblique top pipe
2	221 Guide part
3	311 Receiving chamber
4	312 Opening
5	313 Detachment preventing part
6	314 Second through hole
7	315 First conical part
8	316 Cylindrical part
9	317 Second conical part
10	318 Connection piece
11	321 Receiving hole
12	322 Material reducing groove
13	411 Clamping hole part
14	412 Through hole part
15	413 Chamfered part
16	451 Elastic wire body part
17	452 Elastic deforming part
18	453 Narrow opening
19	454 Socket
20	461 Guide surface

21 **Detailed Description of the Preferred Embodiments**

22 The present invention provides a central lock and a canopy mounted with the central
23 lock. As illustrated in FIG 1 and FIG 2, the central lock comprises a center pole 2, a center

1 top cap 1 fixedly arranged at one end of the center pole 2, and a center bottom cap 3
2 detachably connected to the other end of the center pole 2. As illustrated in FIG 1, the center
3 top cap 1 is fixedly connected with one end of the center pole 2 through a screw 11; a
4 detachable connection structure between the center bottom cap 3 and the other end of the
5 center pole 2 is as illustrated in FIG 2 to FIG 12, a locking piece 4 capable of moving back
6 and forth along a radial direction of the center pole 2 is received in the center bottom cap 3, a
7 first through hole 41 through which the center pole 2 can pass is provided in the locking piece
8 4, and the end part of the center pole 2 is provided with a clamping groove 21 and a clamp
9 locking part located at the lower end of the clamping groove 21. When the central lock is in a
10 locked state, as illustrated in FIG 6, part of an inner wall of the first through hole 41 of the
11 locking piece 4 is clamped with the clamping groove 21 of the center pole 2, an upper end
12 surface of the clamp locking part 22 abuts against a lower end surface of the locking piece 4,
13 thus the clamp locking part 22 can not thread the first through hole 41 and the center pole 2
14 and the center bottom cap 3 are in a mutually connected state. When the central lock is in an
15 unlocked state, as illustrated in FIG 11, the locking piece 4 moves along the radial direction
16 of the center pole 2 such that the inner wall of the first through hole 41 of the locking piece 4
17 is separated from the clamping groove 21, the clamp locking part 22 can thread the first
18 through hole 41, thus the center pole 2 can be moved out of the center bottom cap 3 such that
19 the center pole 2 is separated from the center bottom cap 3.

20 Further, the central lock is mainly mounted in a canopy, so that the canopy can have
21 a better supporting effect. Of course, the central lock may also be mounted in other devices.
22 As illustrated in FIG 16, the canopy mounted with the central lock comprises at least three
23 supporting legs 6, outer retractable units 7 connected between every two adjacent supporting
24 legs 6 and inner retractable units 8 connected to each supporting leg 6, the outer retractable
25 units 7 and the inner retractable units 8 form a roof frame of the canopy, the roof frame and
26 the plurality of supporting legs 6 form a canopy frame of the canopy, a canopy fabric covers
27 the roof frame, and inner ends of the inner retractable units 8 of the canopy are connected
28 through the central lock. In this embodiment, there are four supporting legs 6. Accordingly,
29 there are four outer retractable units 7 and four inner retractable units 8 respectively. In

1 addition, for convenience of operation, the center top cap 1 is located at an upper end of the
2 center pole 2 and the center bottom cap 3 is located at a lower end of the center pole 2, so that
3 the center bottom cap 3 can be pulled upwards or downwards conveniently.

4 When the canopy is in a folded state, as illustrated in FIG 20, the center top cap 1
5 and the center bottom cap 3 of the central lock are in a mutually separated state. When the
6 canopy is unfolding, as illustrated in FIG 19, the four supporting legs 6 are centered about
7 the central lock and unfolded outwards, the outer retractable units 7 and the inner retractable
8 units 8 are gradually stretched outwards. After the canopy is unfolded, the center bottom cap
9 3 is pushed towards the center pole 2, i.e., the center bottom cap 3 moves upwards such that
10 the center pole 2 is inserted into the center bottom cap 3 and the clamping groove 21 of the
11 center pole 2 is clamped with part of the inner wall of the first through hole 41, thus part of
12 the upper end surface of the clamp locking part 22 abuts against part of the lower end surface
13 of the locking piece 4, so as to restrict the clamp locking part 22 from passing through the
14 first through hole 41 and further to restrict the center pole 2 from falling out of the center
15 bottom cap 3, accordingly, the mutual connection between the center bottom cap 3 and the
16 center pole 2 is achieved. After the center bottom cap 3 is connected with the center pole 2,
17 the unfolded state of the canopy is fixed and maintained, the entire canopy is locked, at this
18 point, the inner retractable units 8, as well as the outer retractable units 7 accordingly, can not
19 automatically extend and retract with no external force, and thus the stability of the unfolded
20 state of the canopy is very good. The plurality of inner retractable units 8 are uniformly
21 distributed at the periphery of the central lock, such that each inner retractable unit 8 is
22 uniformly stressed and each supporting leg 6 averagely undertakes the gravity of the roof
23 frame, so as to improve the overall supporting effect of the canopy. In addition, as the canopy
24 mounted with the central lock is unfolded, the canopy can be fixed by connecting the center
25 pole with the center bottom cap. As compared with the mechanical locking method in which
26 the sliding blocks are fixed by locking pins in the prior art, there is no need to fix the sliding
27 blocks in the supporting legs in the present application, thereby it is not necessary to provide
28 holes in the supporting legs of the canopy for fixing the sliding blocks, accordingly the
29 strength of the supporting legs of the canopy is enhanced, the structural strength of the

1 canopy is enhanced and the service life of the canopy is prolonged. When the canopy is
2 folded, the locking piece 4 is moved such that the inner wall of the first through hole 41 of
3 the locking piece 4 is separated from the clamping groove 21, at this point, the clamp locking
4 part 22 can pass through the first through hole 41, and the center pole 2 also can move out of
5 the center bottom cap 3 to separate the center pole 2 from the center bottom cap 3; and
6 thereafter, force is applied to pull the center bottom cap 3 away from the center pole 2, i.e.,
7 the center bottom cap 3 is pulled downwards to enable the inner retractable units 8 to be
8 folded towards the central lock, as illustrated in FIG. 19, finally the outer retractable units 7
9 are gradually folded and the plurality of supporting legs 6 are folded towards the central lock,
10 as illustrated in FIG. 20. To sum up, the canopy mounted with the central lock of the present
11 invention is very convenient to be unfolded or folded, and has good support effect and high
12 strength after the canopy is unfolded, and has long service life; the central lock is simple in
13 structure, easy to manufacture and low in cost.

14 Further, as illustrated in FIG. 16 to FIG. 18, each supporting leg 6 is sleeved with a
15 sliding sleeve 9 for moving along a length direction of the supporting leg 6, an upper end of
16 each supporting leg 6 is fixed with a fixed joint 10. The outer retractable unit 7 comprises
17 three hinged X-shaped rod members, each X-shaped rod member comprises a first eave pipe
18 71 and a second eave pipe 72 hinged to one another, with a hinging point between the first
19 eave pipe 71 and the second eave pipe 72 being located at or close to a midpoint of the first
20 eave pipe 71 or the second eave pipe 72. The inner retractable unit 8 comprises a first oblique
21 top pipe 81 and a second oblique top pipe 82 hinged to one another through a connection
22 piece with a U-shaped cross section, a first connecting rod 83 is hinged at or close to a
23 midpoint of the first oblique top pipe 81, a second connecting rod 84 is hinged at or close to a
24 midpoint of the second oblique top pipe 82; inner ends of four first oblique top pipes 81 are
25 all hinged with the center top cap 1 of the central lock, inner ends of four first connecting
26 rods 83 are all hinged with the center bottom cap 3 of the central lock. The fixed joint 10 at
27 the upper end of the supporting leg 6 is hinged with outer ends of the first eave pipes 71 of
28 two X-shaped rod members and an outer end of one second oblique top pipe 82, the sliding
29 sleeve 9 on the supporting leg 6 is hinged with outer ends of the second eave pipes 72 of two

1 X-shaped rod members and an outer end of one second connecting rod 84. In this
2 embodiment, the first oblique top pipe 81 and the first connecting rod 83, as well as the
3 second oblique top pipe 82 and the second connecting pipe 84, forms a Y-shaped member, i.e.,
4 the inner retractable unit 8 consists of a plurality of Y-shaped members. In another
5 embodiment, the inner retractable unit 8 may also consists of a plurality of X-shaped
6 members, as illustrated in FIG. 21, at this point, each X-shaped member of the inner
7 retractable unit 8 comprises a third oblique top pipe 85 and a fourth oblique top pipe 86
8 hinged to one another. As for the innermost X-shaped member of the inner retractable unit 8,
9 an inner end of the third oblique top pipe 85 is hinged with the center top cap 1 of the central
10 lock, and an inner end of the fourth oblique top pipe 86 is hinged with the center bottom cap
11 3 of the central lock. As for the outermost X-shaped member of the inner retractable unit 8,
12 an outer end of the third oblique top pipe 85 is hinged with the sliding sleeve 9, and an outer
13 end of the fourth oblique top pipe 86 is hinged with the fixed joint 10.

14 As for the roof frame of the canopy with the above-mentioned structure, in the
15 process that the center bottom cap 3 of the central lock is pushed upwards to unfold the
16 canopy, the upward movement of the center bottom cap 3 enables the inner retractable units 8
17 to extend outwards; and simultaneously the sliding sleeve 9 is enabled to move upwards
18 along the length direction of the supporting leg 6, such that the outer retractable units 7 and
19 the four supporting legs 6 gradually extend until the entire canopy is fully unfolded and the
20 center bottom cap 3 is connected with the lower end of the center pole 2. Contrarily, after the
21 center bottom cap 3 is separated from the lower end of the center pole 2, in the process that
22 the center bottom cap 3 is pulled downwards, the downward movement of the center bottom
23 cap 3 enables the inner retractable units 8 to fold inwards; and simultaneously the sliding
24 sleeve 9 is enabled to move downwards along the length direction of the supporting leg 6,
25 such that the outer retractable units 7 and the four supporting legs 6 gradually fold until the
26 entire canopy is fully folded.

27 Further, as illustrated in FIG. 1, FIG. 6 and FIG. 11, the center bottom cap 3
28 comprises a bottom cap seat 31 and a bottom cap cover 32 that are connected to one another
29 fixedly through a plurality of screws, a receiving chamber 311 is provided in the center

1 bottom cap 3 at a junction between the bottom cap seat 31 and the bottom cap cover 32, an
2 opening 312 communicated with the receiving chamber 311 is provided in an outer wall of
3 the center bottom cap 3, and the locking piece 4 is provided threading the receiving chamber
4 311 and the opening 312, located between the bottom cap seat 31 and the bottom cap cover
5 32, and supported by the bottom cap cover 32. The receiving chamber 311 may be fully
6 disposed in the bottom cap seat 31, or in the bottom cap cover 32, or in the bottom cap seat
7 31 and the bottom cap cover 32 together. The bottom cap seat 31 and the bottom cap cover 32
8 are detachably connected through the screws, thereby facilitating the mounting of the center
9 bottom cap 3 and the locking piece 4. In addition, there are eight connection pieces 318
10 provided in the bottom cap seat 31 of the center bottom cap 3 and the center top cap 1
11 respectively, the eight connection pieces 318 form four connection piece groups which are
12 provided at intervals of 90°, i.e., each connection piece group comprises two connection
13 pieces 318, with a receiving groove being formed between the two connection pieces 318.
14 The inner ends of the four first oblique top pipes 81 are disposed in the four receiving
15 grooves in the center top cap 1 and hinged with the connection pieces 318 through bolts
16 respectively, and threads at end portions of the bolts are connected with nuts. The inner ends
17 of the four first connecting rods 83 are disposed in the four receiving grooves of the bottom
18 cap seat 31 and hinged with the connection pieces 318 through bolts respectively, and threads
19 at end portions of the bolts are connected with nuts.

20 In the present application, there are two embodiments for the locking piece 4. The
21 first embodiment of the locking piece 4 is as illustrated in FIG. 1 to FIG. 15, and the second
22 embodiment of the locking piece 4 is as illustrated in FIG. 21 to FIG. 26. Specifically, in the
23 first embodiment, the locking piece 4 is an integral member, i.e., an integral structure. At this
24 point, as illustrated in FIG. 6 and FIG. 11, the receiving chamber 311 is provided with a
25 compressible elastic element along the radial direction of the center pole 2, the elastic
26 element abuts against the locking piece 4 and an inner wall of the receiving chamber 311 at
27 two ends respectively. The bottom cap seat 31 is provided with a protruding detachment
28 preventing part 313, the locking piece 4 is provided with a groove 42 for receiving the
29 detachment preventing part 313. When the central lock is in a locked state, the locking

1 piece 4 applies an acting force to center pole 2 in the radial direction by means of elastic
2 force of the elastic element, to enable part of the inner wall of the first through hole 41 to be
3 located in the clamping groove 21, i.e., to enable part of the inner wall of the first through
4 hole 41 to be clamped with the clamping groove 21 to restrict the center pole 2 from falling
5 out of the first through hole 41 along an axial direction. Part of the side surface of the
6 detachment preventing part 313 abuts against part of the inner wall of the groove 42 to
7 restrict the locking piece 4 from falling out of the receiving chamber 311. Preferably, as
8 illustrated in FIG 1, FIG 13 and FIG 14, the elastic element is a spring 5, the locking piece 4
9 is provided with a protruding guide supporting part 43 at the end away from the opening 312,
10 the guide supporting part 43 has a cross section of cross-shape and the spring 5 sleeves the
11 guide supporting part 43, to guarantee that the locking piece 4 has good stability when
12 moving inwards, and the overall structure also has good stability when the central lock is in
13 the locked state.

14 Preferably, as illustrated in FIG 13, the first through hole 41 comprises a clamping
15 hole part 411 and a through hole part 412 arranged side by side, the clamping hole part 411
16 has a diameter not smaller than that of the clamping groove 21, i.e., the diameter of the
17 clamping hole part 411 is equal to or slightly greater than the diameter of the clamping
18 groove 21; the through hole part 412 has a diameter greater than that of the clamp locking
19 part 22. Consequently, when the central lock is in the locked state, the clamping groove 21 at
20 the lower end of the center pole 2 is clamped with the clamping hole part 411 of the first
21 through hole 41, the center pole 2 and the through hole part 412 of the first through hole 41
22 are eccentrically arranged, as illustrated in FIG 4, i.e., an axis of the center pole 2 and an axis
23 of the through hole part 412 are in parallel but are not overlapped. When it needs to unlock
24 the central lock, the user exerts force to push a locking piece pressing part 44 to enable the
25 locking piece pressing part 44 to move inwards to compress the elastic element until the
26 center rod 2 and the through hole part 412 of the first through hole 41 in the locking piece 4
27 are concentrically arranged, as illustrated in FIG 9, i.e., the axis of the center pole 2 and the
28 axis of the through hole part 412 are overlapped, the inner wall of the clamping hole part 411
29 is removed from the clamping groove 21 and thereby the clamp locking part 22 at the lower

1 end of the center pole 2 can be removed from the through hole part 412.

2 In the second embodiment, the locking piece 4 is in a detachable form, as illustrated
3 in FIG 22 to FIG 26, and comprises an elastic wire 45 and an unlocking push piece 46, the
4 elastic wire 45 is U-shaped and comprises an elastic wire body part 451 and two elastic
5 deforming parts 452 respectively provided at two ends of the elastic wire body part 451, the
6 two elastic deforming parts 452 are X-shaped with a narrow opening 453 for forming the first
7 through hole 41 being provided in the middle of the two elastic deforming parts 452. The
8 narrow opening 453 is an opening section having a smallest spacing between the elastic
9 deforming parts 452, end portions of the elastic deforming parts 452 form a socket 454 and
10 an inner end of the unlocking push piece 46 is located in the socket 454. In a natural state, the
11 narrow opening 453 has a caliber smaller than or equal to the diameter of the clamping
12 groove 21, when the center pole 2 is inserted into the center bottom cap 3, the clamp locking
13 part 22 widens the narrow opening 453 until the clamping groove 21 in the center pole 2 is
14 aligned with the inner wall of the narrow opening 453 of the elastic wire 45, then the narrow
15 opening 453 is narrowed under the effect of the elastic restoring force of the elastic wire 45,
16 thereby the inner wall of the narrow opening 453 is enabled to be clamped in the clamping
17 groove 21 in the center pole 2, and thus the position locking of the center bottom cap 3 and
18 the center top cap 1 is achieved, as illustrated in FIG 23 and FIG 24. When it needs to unlock,
19 the unlocking push piece 46 is pressed and pushed inwards, the socket 454 of the elastic wire
20 45 is widened until the caliber of the narrow opening 453 is greater than the diameter of the
21 clamp locking part 22, such that the clamp locking part 22 is capable of passing through the
22 narrow opening 453, as illustrated in FIG 25 and FIG 26, consequently, the separation
23 between the center top cap 1 and the center bottom cap 3 is achieved and the folding action of
24 the canopy is achieved.

25 Preferably, as illustrated in FIG 23 and FIG 25, the bottom cap seat 31 is provided
26 with a protruding detachment preventing part 313, the unlocking push piece 46 is provided
27 with a groove 42 for receiving the detachment preventing part 313. With mutual cooperation
28 between the detachment preventing part 313 and the groove 42, it enables to prevent the
29 unlocking push piece 46 from falling out of the receiving chamber 311 as well as from being

1 excessively pressed during unlocking. The unlocking push piece 46 is provided with two
2 guide surfaces 416 in contact with the end portions of the elastic deforming parts 452
3 respectively, and the guide surfaces 461 are spread and inclining away from the elastic wire
4 45, i.e., an inner end of the unlocking push piece 46 is trapezoidal, so as to guarantee that the
5 socket 454 and the narrow opening 453 of the elastic wire can be accurately widened when
6 the unlocking push piece 46 is pushed inwards.

7 More preferably, in order to facilitate the movement of the locking piece 4, at least
8 part of the locking piece 4 is disposed outside the center bottom cap 3 to form the locking
9 piece pressing part 44.

10 Further, as illustrated in FIG 6, the bottom cap seat 31 is provided with a second
11 through hole 314 through which the center pole 2 can pass, the axis of the second through
12 hole 314 coincides with the axis of the center pole 2. The bottom cap cover 32 is provided
13 with a receiving hole 321 for receiving the clamp locking part 22 and being adaptive to an
14 outer wall of the clamp locking part 22. The second through hole 314, the first through hole
15 41 and the receiving hole 321 are in a communication manner. When the central lock is in the
16 locked state, the lower end of the center pole 2 is sequentially disposed in the second through
17 hole 314 of the bottom cap seat 31 and the first through hole 41 of the locking member 4, the
18 clamp locking part 22 is received in the receiving hole 321 of the bottom cap cover 32. Since
19 the shape of the inner wall of the receiving hole 321 is adapted to the shape of the outer wall
20 of the clamp locking part 22, the inner wall of the receiving hole 321 is fit with the outer wall
21 of the clamp locking part 22, thereby the clamp locking part 22 of the center pole 2 can be
22 prevented from shaking, jumping and the like under the effect of external force, and thus the
23 locking reliability of the central lock is improved.

24 To sum up, during the locking of the central lock comprising the bottom cap seat 31,
25 the bottom cap cover 32, the spring 5, the locking piece 4, the center pole 2, the center top
26 cap 1 and the like, the user pushes the center bottom cap 3 to move upwards, and the distance
27 between the center bottom cap 3 and the center top cap 1 gradually decreases. When no
28 external force is applied to the locking piece 4, the locking piece 4 is only subjected to the
29 elastic force of the spring 5, by which part of the inner wall of the groove 42 of the locking

1 piece 4 abuts against part of the outer wall of the detachment preventing part 313 of the
2 bottom cap seat 31, consequently, the locking ember 4 is still received in the receiving
3 chamber 311 under the effect of the elastic force of the spring 5 and is unable to fall out of the
4 receiving chamber 311, and the through hole part 412 of the first through hole 41 of the
5 locking piece 4 and the second through hole 314 of the bottom cap seat 31 are eccentrically
6 arranged. The user continues to push the center bottom cap 3 to move upwards until the lower
7 end of the center pole 2 enters the second through hole 314 in the bottom cap seat 31. The
8 user continues to apply force to move center bottom cap 3 upwards, and when the locking
9 part 22 at the lower end of the center pole 2 enters the upper end of the first through hole 41
10 of the locking piece 4, the user applies acting force to overcome the pressure applied by the
11 spring 5 to the locking piece 4 to move the locking piece inwards, so that the clamp locking
12 part 22 at the lower end of the center pole 2 passes through the first through hole 41 of the
13 locking piece 4 to be received in the receiving hole 321 of the bottom cap cover 32, further,
14 the locking piece 4 is restored under the effect of the elastic force of the spring 5, so that the
15 clamping hole part 411 of the first through hole 41 is enabled to be clamped with the
16 clamping groove 21 of the center pole 2, thereby the connection between the center pole 2
17 and the center bottom cap 3 is completed and the locking of the central lock is achieved.
18 During the unlocking, the user presses the locking piece pressing part 44 inwards to
19 overcome the elastic force of the spring 5 to move the locking piece 4 inwards; when the
20 inner wall of the clamping hole part 411 is separated from the clamping groove 21 and the
21 center pole 22 is aligned with the through hole part 412 of the first through hole 41, the center
22 bottom cap 3 is pulled to move downwards.

23 Further, in order to facilitate the center pole 2 to thread the bottom cap seat 31 and
24 the locking piece 4, as illustrated in FIG 6 and FIG 11, the second through hole 314
25 sequentially comprises a first conical part 315 with a gradually decreased diameter, a
26 cylindrical part 316 and a second conical part 317 with a gradually increased diameter along
27 the direction that the center pole 2 threads the center bottom cap 3, and a diameter of the
28 cylindrical part 316 is slightly greater than the diameter of the center pole 2. Consequently, as
29 the bottom cap seat 31 moves upwards to be connected with the lower end of the center pole

1 2, the opening of the first conical part 315 at the upper end of the second through hole 314 is
2 relatively larger to facilitate the clamp locking part 22 to be inserted into the bottom cap seat
3 31. As illustrated in FIG 15, the upper end of the first through hole 41 is chamfered to form a
4 chamfered part 413 with a gradually decreased diameter, thus the opening at the upper end of
5 the first through hole 41 is also relatively large and has a certain inclination to facilitate the
6 clamp locking part 22 to be inserted into the locking piece 4, so as to play a role of guiding.
7 When the center pole 2 is separated from the center bottom cap 3, the bottom cap seat 31
8 moves downwards, and the opening of the second conical part 317 at the lower end of the
9 second through hole 314 is relatively large to facilitate the clamp locking part 22 to fall out of
10 the second through hole 314. Preferably, the clamping groove 21 is an annular groove, an end
11 portion of the clamp locking part 22 is provided with a guide part 221 of a semispherical
12 shape or a conical shape with a gradually decreased diameter, by which the guide part 221
13 facilitates entering the first through hole 41 of the locking piece 4 and abrasion hardly occurs.

14 Further, as illustrated in FIG 1, in the case that the structural strength of the central
15 lock is guaranteed, the bottom cap seat 32 is provided with a plurality of material reducing
16 grooves 322 to reduce the amount of material and lower the cost. In addition, the center
17 bottom cap 3 has an arc-shaped side surface to facilitate grasping the center bottom cap 3.

18 To sum up, the present invention effectively overcomes various disadvantages in the
19 prior art and thus has a great industrial utilization value.

20