

Our product assortment is geared exclusively toward commercial customers.



Light Tubes

Quasar Science Crossfade X 4 ft

Linear 4' Bi-Color LED light tube with an operating voltage of 240 V AC, a power of 50 W, a brightness of up to 1,188 lux (at approx. 1 m) and integrated ballast



Order number: QUASAR_921-2208

RRP ~~€190.00~~ **-3%**

€185.00

brutto €220.15

Prices plus VAT [plus shipping costs](#)

Privacy settings

In order to offer you an optimal experience on our website and to improve the security and performance of the website, we use Cookies and other technologies. They help us to show you personalized content and suitable offers, remember settings you make on our site and collect anonymous data on user behavior.

You can change the cookie settings at any time. If it's okay with you, you consent to use of cookies and data for these purposes by clicking here: [accept cookies](#).

[More information about data privacy](#)

Cookie settings

Accept only functional cookies

Accept all cookies

[- Imprint](#) [- GTC](#)

CONTACT

Our experts are there for you:

Mo. - Fr.: 9am to 6pm

☎ +49 (0) 040/557624-50

✉ Contact form

✉ info@bpm-media.de

📍 Company



Description

Properties:

The Bi-Color LED light tubes of the Crossfade X series consist of the Candle Light Diode (2,000 K) and the Overcast Daylight Diode (6,000 K), which interact to produce a crossfade lamp with an adjustable color temperature of 2,000 to 6,000 Kelvin. The light tube produces flicker-free light with a high color purity (CRI 95+ and TLCI 97+). It has a integrated ballast and is operated with 240 V AC via the supplied power cable. The brightness of the light tube can be regulated via an external dimming system. It is compatible with most dimming systems such as ETC sensor, Lutron CL or ID: Rat Pac. The LED light tube enables easy illumination, especially in confined environments. Combinations of several light tubes of the Crossfade X series are possible.

- Perfect for illumination in confined environments
- Built-in crossfade wheel for color temperature adjustment
- Flicker-free light

Privacy settings

In order to offer you an optimal experience on our website and to improve the security and performance of the website, we use Cookies and other technologies. They help us to show you personalized content and suitable offers, remember settings you make on our site and collect anonymous data on user behavior.

You can change the cookie settings at any time. If it's okay with you, you consent to use of cookies and data for these purposes by clicking here: [accept cookies](#).

[More information about data privacy](#)

[- Imprint](#) [- GTC](#)

- Connection: Grounded G13 Single End

General Product Information:

- Length: 1.22 m (4')
- Diffusion Size (L x W): 113.3 x 3.5 cm (44 5/8" x 1 3/8")
- Weight: 770 g (1.7 lbs)
- Operating Voltage: 240 V AC (integrated ballast)
- Operating Current: 0.3 A
- Power Consumption: 50 W
- Apparent Power: 72 VA
- Power Factor: 0.694
- LED Lifetime: 25,000+ hours

Included in Delivery:

[Show less...](#)



OUR LATEST PRODUCTS

HPRC 2400 CUBBLK | Canon RF 24-105mm F2.8L IS USM Z | Sonnet Fusion SSD M.2 Silent 4x4 PCIe Card |

Canon EOS R6 Mark II + RF 24-105mm F4 L IS USM | Canon EOS R6 Mark II + RF 24-105mm F4-7.1 IS STM |

HPRC 2350 CUBBLK | Canon EOS R6 Mark II | HPRC S-MAVM-2300-04 |

Privacy settings

In order to offer you an optimal experience on our website and to improve the security and performance of the website, we use Cookies and other technologies. They help us to show you personalized content and suitable offers, remember settings you make on our site and collect anonymous data on user behavior.

You can change the cookie settings at any time. If it's okay with you, you consent to use of cookies and data for these purposes by clicking here: [accept cookies](#).

[More information about data privacy](#)

[- Imprint](#) [- GTC](#)