

EXHIBIT 1001



US011020129B2

(12) **United States Patent**
LaNeve et al.

(10) **Patent No.:** **US 11,020,129 B2**

(45) **Date of Patent:** **Jun. 1, 2021**

(54) **DRILL-LESS METHOD OF FUSING A SACROILIAC JOINT**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,569,338 A	2/1986	Edwards
5,334,205 A	8/1994	Cain
5,722,978 A	3/1998	Jenkins, Jr.
6,080,155 A	6/2000	Michelson
6,371,988 B1	4/2002	Pafford et al.
(Continued)		

FOREIGN PATENT DOCUMENTS

AU	726979	10/1998
AU	756550	5/2002

(Continued)

OTHER PUBLICATIONS

Steven P. Cohen, MD, Sacroiliac Joint Pain: A Comprehensive Review of anatomy, Diagnosis, and Treatment, Review Article, Apr. 27, 2005, 1440-1453, vol. 101, International Anesthesia Research Society, United States.

(Continued)

Primary Examiner — Christian A Sevilla

(74) *Attorney, Agent, or Firm* — Stephen E. Kelly;
Thomas J. Banks; Hill Ward Henderson, P.A.

(71) Applicant: **Pain TEQ, LLC**, Tampa, FL (US)

(72) Inventors: **Sean LaNeve**, Tampa, FL (US);
Charles Girsch, Tampa, FL (US);
Chris Girsch, Tampa, FL (US)

(73) Assignee: **Pain TEQ, LLC**, Tampa, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **17/063,613**

(22) Filed: **Oct. 5, 2020**

(65) **Prior Publication Data**

US 2021/0100662 A1 Apr. 8, 2021

Related U.S. Application Data

(63) Continuation-in-part of application No. 16/851,840, filed on Apr. 17, 2020.

(60) Provisional application No. 62/910,913, filed on Oct. 4, 2019.

(51) **Int. Cl.**

A61F 2/46 (2006.01)

A61B 17/16 (2006.01)

A61B 17/02 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/1671** (2013.01); **A61B 17/025**
(2013.01); **A61F 2/4611** (2013.01); **A61B**
17/1604 (2013.01); **A61B 2017/0256**
(2013.01); **A61F 2002/4681** (2013.01)

(58) **Field of Classification Search**

CPC **A61F 2/4611**; **A61F 2002/30995**; **A61B**
17/1671; **A61B 17/1604**


See application file for complete search history.

(57)

ABSTRACT

An method for installing a fusion implant into a sacroiliac joint ("SI Joint") without the use of a rotary cutting instrument. The method incorporates a multimodal abrading device having abrading surfaces on opposing sides and an open tip comprising a cutting edge. The method includes the step of using the abrading head to cut bone tissue from the SI Joint at an insertion point while simultaneously using the abrading surfaces to decorticate the cortical bone at the insertion point.

16 Claims, 25 Drawing Sheets



(56)	References Cited			10,820,917 B2	11/2020	Sharifi-Mehr et al.
	U.S. PATENT DOCUMENTS			D905,232 S	12/2020	Schifano et al.
				2001/0031967 A1	10/2001	Nicholson et al.
				2002/0143400 A1	10/2002	Biscup
6,436,098 B1	8/2002	Michelson		2005/0080422 A1	4/2005	Otte et al.
6,648,917 B2	11/2003	Gerbac et al.		2005/0240195 A1	10/2005	Axelsson, Jr. et al.
6,652,533 B2	11/2003	O'Neil		2006/0054171 A1	3/2006	Dall
6,770,074 B2	8/2004	Michelson		2006/0089633 A1 *	4/2006	L. Bleich A61B 90/04
6,846,327 B2	1/2005	Khandkar et al.				606/32
7,018,416 B2	3/2006	Hanson et al.		2006/0178673 A1 *	8/2006	Curran A61B 17/92
7,125,425 B2	10/2006	Foley et al.				606/100
7,229,477 B2	6/2007	Biscup		2007/0156241 A1	7/2007	Reiley et al.
7,648,509 B2	1/2010	Stark		2008/0009861 A1 *	1/2008	Stark A61F 2/4601
8,021,392 B2	9/2011	Petersen				606/914
8,025,684 B2	9/2011	Garcia-Bengochea et al.		2008/0154374 A1	6/2008	Labrom
8,128,700 B2	3/2012	Delurio et al.		2008/0249569 A1	10/2008	Waugh et al.
8,157,865 B2	4/2012	Hochschuler et al.		2009/0024174 A1	1/2009	Stark
8,162,981 B2	4/2012	Vestgaarden		2009/0076551 A1	3/2009	Petersen
8,197,513 B2	6/2012	Fisher et al.		2009/0099610 A1	4/2009	Johnson et al.
8,221,503 B2	7/2012	Garcia et al.		2009/0216238 A1 *	8/2009	Stark A61F 2/30988
8,348,950 B2	1/2013	Assell et al.				606/96
8,403,991 B2	3/2013	Ullrich, Jr. et al.		2009/0259261 A1	10/2009	Reiley
8,551,171 B2	10/2013	Johnson et al.		2009/0312763 A1 *	12/2009	McCormack A61B 17/8822
8,579,912 B2	11/2013	Isaza et al.				606/83
8,623,053 B2	1/2014	Vestgaarden		2011/0098817 A1	4/2011	Eckhardt
8,740,912 B2	6/2014	Stark		2011/0184518 A1 *	7/2011	Trieu A61B 17/562
8,882,818 B1	11/2014	Vestgaarden				623/17.11
8,945,224 B2	2/2015	Trieu		2011/0238181 A1	9/2011	Trieu
8,961,571 B2	2/2015	Lee et al.		2011/0264229 A1	10/2011	Donner
8,979,928 B2	2/2015	Donner		2012/0083883 A1	4/2012	Ginn
9,017,407 B2	4/2015	Donner		2012/0259365 A1	10/2012	Richelsoph
9,101,371 B2 *	8/2015	Assell A61B 17/320016		2012/0277801 A1 *	11/2012	Marik A61B 17/1671
9,119,732 B2	9/2015	Schifano et al.				606/279
9,186,155 B2	11/2015	Katzman et al.		2013/0006368 A1	1/2013	Walsh et al.
9,241,798 B2	1/2016	Petersen		2013/0173004 A1	7/2013	Greenhalgh et al.
9,247,943 B1	2/2016	Kleiner		2013/0218215 A1	8/2013	Ginn et al.
9,375,243 B1	6/2016	Vestgaarden		2014/0031935 A1 *	1/2014	Donner A61B 17/7055
9,421,109 B2	8/2016	Donner				623/17.11
9,451,986 B2	9/2016	Stoffman		2014/0081279 A1 *	3/2014	Kleiner A61F 2/4611
9,492,284 B2	11/2016	Ginn et al.				606/94
9,662,128 B2	5/2017	Reiley		2014/0088711 A1 *	3/2014	Chin A61F 2/447
9,668,781 B2	6/2017	Stark				623/17.16
9,700,356 B2	7/2017	Donner et al.		2014/0207191 A1	7/2014	Kornel
9,757,154 B2	9/2017	Donner et al.		2014/0277204 A1 *	9/2014	Sandhu A61F 2/447
9,795,396 B2	10/2017	Donner				606/86 A
9,801,732 B2	10/2017	Chin et al.		2015/0012097 A1 *	1/2015	Ibarra A61F 2/442
9,808,346 B2	11/2017	Stark				623/17.15
9,833,321 B2	12/2017	Rindal		2015/0025534 A1	1/2015	Gordon et al.
9,883,874 B1	2/2018	Vestgaarden		2015/0073552 A1 *	3/2015	To A61F 2/4684
9,895,176 B2	2/2018	Vestgaarden				623/17.15
9,949,843 B2	4/2018	Reiley et al.		2015/0112444 A1	4/2015	Aksu
10,004,547 B2	6/2018	Reiley		2015/0230937 A1 *	8/2015	Voellmicke A61F 2/4455
10,070,970 B2	9/2018	Lynn et al.				623/17.16
10,136,932 B2	11/2018	Freese		2015/0250611 A1	9/2015	Schifano et al.
10,149,764 B2	12/2018	Stark		2015/0250612 A1	9/2015	Schifano et al.
10,166,033 B2	1/2019	Reiley et al.		2015/0328012 A1 *	11/2015	Hansell A61F 2/4425
10,194,962 B2	2/2019	Schneider et al.				623/17.16
10,201,427 B2	2/2019	Mauldin		2016/0030191 A1 *	2/2016	McLuen A61F 2/447
10,206,739 B2	2/2019	Godara et al.				623/17.16
10,219,841 B1	3/2019	Compton		2016/0175113 A1	6/2016	Lins
10,219,912 B2	3/2019	Suh et al.		2016/0310197 A1	10/2016	Black et al.
10,245,044 B2	4/2019	Petersen		2017/0245999 A1	8/2017	Ginn et al.
10,245,158 B2	4/2019	Song		2018/0036017 A1	2/2018	Donner et al.
10,265,176 B2	4/2019	Donner et al.		2018/0092748 A1	4/2018	Donner et al.
10,292,720 B2	5/2019	Donner		2018/0303624 A1 *	10/2018	Shoshtaev A61F 2/4611
10,314,710 B2	6/2019	Donner et al.		2019/0021868 A1 *	1/2019	Ludwig A61F 2/447
10,321,945 B2	6/2019	Schifano et al.		2019/0083271 A1 *	3/2019	Donner A61B 17/1757
10,357,368 B2	7/2019	Aksu		2019/0090888 A1	3/2019	Sand et al.
10,363,140 B2	7/2019	Mauldin et al.		2019/0133613 A1	5/2019	Reiley et al.
10,426,539 B2	10/2019	Schifano et al.		2019/0262010 A1	8/2019	Cerundolo et al.
1,049,280 A1	12/2019	Donner et al.		2019/0336292 A1	11/2019	Aksu
10,555,818 B2	2/2020	McConnell et al.		2019/0343640 A1 *	11/2019	Donner A61F 2/447
1,064,625 A1	5/2020	Donner et al.		2020/0029979 A1	1/2020	Donner et al.
1,068,215 A1	6/2020	Stark		2020/0093612 A1 *	3/2020	Blain A61F 2/4601
10,736,752 B1	8/2020	Schifano et al.		2020/0138452 A1	5/2020	Gatrell et al.
10,744,003 B2	8/2020	Ryan et al.		2020/0138589 A1	5/2020	Abbasi
10,751,196 B1	8/2020	Schifano et al.		2020/0179135 A1 *	6/2020	Castro A61F 2/4455
10,765,532 B2	9/2020	Ashleigh et al.		2020/0253619 A1 *	8/2020	Gregory A61B 17/1757
10,779,958 B2	9/2020	Lins				

(56)

References Cited

U.S. PATENT DOCUMENTS

2020/0315811	A1*	10/2020	Cryder	A61F 2/4455
2020/0390566	A1*	12/2020	Murray	A61F 2/4657
2021/0015502	A1*	1/2021	Sharifi-Mehr	A61B 90/50

FOREIGN PATENT DOCUMENTS

CN	110123436	8/2019
FR	2727004	5/1996
WO	WO/2017066443	4/2017
WO	WO/2018195406	10/2018
WO	WO/2019137626	7/2019

OTHER PUBLICATIONS

K. A. Giannikas, A. M. Khan, M.T. Karski, H. A. Maxwell, Sacroiliac joint fusion for chronic pain: a simple technique avoiding the use of metalwork, Journal, Nov. 28, 2003, 253-256, vol. 13, Springer-Verlag, Greece.

Captiva Spine, TransFasten Posterior Sacroiliac (SI) Joint Fusion System, available at, <https://transfasten.captivaspine.com/si-joint-surgeon-providers/>, last visited on Jan. 5, 2021.
 United States Patent and Trademark Office, Office Action for U.S. Appl. No. 17/063,616, dated Jan. 4, 2021.
 International Search Report and Written Opinion for International. Appl. No. PCT/US20/54299, dated Jan. 8, 2021.
 International Search Report and Written Opinion for International. Appl. No. PCT/US20/54308, dated Jan. 8, 2021.
 International Search Report and Written Opinion for International. Appl. No. PCT/US20/54290, dated Jan. 21, 2021.
 U.S. Appl. No. 16/851,840, filed Apr. 17, 2020, Sean LaNeve Charles Girsch Chris Girsch.
 U.S. Appl. No. 17/063,609, filed Oct. 5, 2020, Sean LaNeve Charles Girsch Chris Girsch.
 U.S. Appl. No. 17/063,616, filed Oct. 5, 2020, Sean LaNeve Charles Girsch Chris Girsch, Jan. 4, 2021—Non-Final Office Action.
 United States Patent and Trademark Office, Office Action for U.S. Appl. No. 17/063,609, dated Feb. 2, 2021.
 International Search Report and Written Opinion for International. Appl. No. PCT/US20/54312, dated Feb. 8, 2021.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 6




FIG. 9




FIG. 8




FIG. 10




FIG. 11





FIG. 12






FIG. 15




FIG. 14




FIG. 16




FIG. 17





FIG. 18







FIG. 20






FIG. 22




FIG. 23






FIG. 24








FIG. 27




FIG. 28




FIG. 29




FIG. 30





FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36

1

DRILL-LESS METHOD OF FUSING A SACROILIAC JOINT

CROSS-REFERENCE TO RELATED APPLICATION

Pursuant to 35 U.S.C. §§ 119(e) and 120, this application:

- (i) is a continuation-in-part of U.S. patent application Ser. No. 16/851,840, filed on Apr. 17, 2020, which claims the benefit of U.S. Provisional Patent Application Ser. No. 62/910,913, filed on Oct. 4, 2019; and
- (ii) claims the benefit of U.S. Provisional Patent Application Ser. No. 62/910,913, filed on Oct. 4, 2019, the entire contents of each of which are incorporated herein by this reference.

BACKGROUND

(1) Field of Endeavor

The present invention relates generally to the field of sacroiliac joint fusion procedures, and more particularly, to a unique method for fusing a sacroiliac joint without the use of a rotary cutting instrument.

(2) Description of Related Art

The sacroiliac joint ("SI Joint") is located at the interface between the sacrum and ilium bones in a human's pelvic area. The SI Joint includes strong ligaments that permit only slight movement between the sacrum and the ilium. The sacrum is connected to the base of the spine, and each ilium is connected to the top of the leg and hip area. Thus, the SI Joint is the interface between a human's upper body and lower body.

Dysfunction in the SI Joint is a common problem of back pain. In fact, over 25% of back pain is caused by SI Joint dysfunction. Even a properly functioning SI Joint can become painful after certain types of spinal procedures. For example, over 75% of lumbar fusion surgeries lead to SI Joint pain. Often, SI Joint pain or dysfunction is addressed by fusing the SI Joint, and many past procedures exist for doing so. Past SI Joint fusion procedures involve installation of complex implant devices, such as bone anchors, fusion devices, and multi-component implants. These procedures involve complex devices, such as drills and drill bits, and multi-component dilators, braces, and anchor installation devices. As a result, fusion procedures using these devices are complex and time consuming, often leading to suboptimal results.

The present set of instruments seeks to overcome these problems by providing a streamlined system and procedure for installing an allograft implant in the SI Joint, without using a drill, drill bits, or other rotary cutting instruments.

Another complication of SI Joint fusion is that promoting bone fusion often involves decorticating the cortical bone inside the SI Joint. This decortication is accomplished with a broach, a rasp, or a similar abrading device. These abrading devices often become lodged inside the SI Joint during the decortication process. When the abrading device becomes lodged, counter pressure cannot be applied to the patient to counteract the pull-out force needed to dislodge the abrading device. Any such counter pressure applied to the patient could result in injury to the patient or damage to the tissue surrounding the surgical site. A past solution is to attach a separate slap hammer, or slide hammer, to the abrading device such that pull-out forces can be applied to

2

the abrading device without the need for applying any counter pressure to the patient or to any other object. However, past slide hammer assemblies are cumbersome to operate, difficult to attach to the abrading device, and difficult to operate. They also complicate the instrumentation needed to perform the SI Joint fusion procedure.

The present set of instruments seeks to overcome these problems by providing a slide hammer integrated into the abrading device in a single tool, which eliminates the need for using a rotary cutting instrument in the bone of the SI Joint to form a pilot hole for the implant.

SUMMARY OF THE PREFERRED EMBODIMENTS

In the preferred embodiment, the system and instrumentation described herein comprises a working channel, a joint locator, an abrading device, and an implant inserter. The working channel has an insertion end and a working end, and a channel extending therebetween. The working channel provides a working passage for insertion of the other instruments of the system, and for delivery of the implant to the SI Joint. The insertion end has a pair of arms for providing engagement of the SI Joint and distraction of tissue surrounding the insertion end. The insertion end further comprises a first iliac contour and a first sacral contour, both of which are defined by the contour between the insertion arms and the body of the working channel. The inside surface of the working channel has an alignment means comprising a groove, recess, channel, indent, or the like for receiving and engaging a ridge, rib, detent, or other protrusion on the mating instrument that is keyed to the alignment means. In one embodiment, the working channel further comprises a channel collar for receiving mating components of the joint locator, abrading device, or implant inserter in an abutting engagement.

The joint locator has an insertion end and a handle. The insertion end comprises a penetration tip for penetrating the soft tissue in proximity to the SI Joint. A leading edge of the penetration tip may comprise, in whole or in part, a blade or chisel component to promote this penetration. Alternately, the penetration tip may be rounded or dull so that it does not inadvertently penetrate the sacrum or ilium in the event that the joint locator is misaligned during insertion. The joint locator insertion end comprises a second iliac contour and a second sacral contour. The outside surface of the joint locator has a keying means for engagement with the alignment means of the working channel, the keying means comprising a ridge, rib, detent, or other protrusion on the outside surface of the joint locator capable of engaging the alignment means.

The abrading device comprises a hammer sleeve at a proximate end, an abrading head at a distal end, and a keying means that is similar to the joint locator keying means of the joint locator. In the preferred embodiment, the abrading device further comprises a slap hammer assembly, or slide hammer assembly. In one embodiment, the slide hammer assembly comprises a base connected to a shaft, and a releasing means that releasably connects a hammer sleeve to the base. The released hammer sleeve is configured for sliding engagement along the shaft. To operate the slide hammer assembly, the hammer sleeve is disengaged from the base, placing the slide hammer assembly in its released position. This released position enables the hammer sleeve to slide freely along the shaft. The hammer sleeve is pulled

3

until a diaphragm inside the hammer sleeve engages a stop end of the shaft, thereby causing an impact that delivers the slide hammer force.

The implant inserter comprises a handle and an implant insertion end. The implant insertion end has a pair of tines for holding the implant during the process of inserting the implant into the SI Joint. The implant inserter further comprises an inserter keying means, which is similar to the keying means of the joint locator.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 shows the posterior view of a typical human pelvis.

FIG. 2 is a perspective view of an embodiment of an allograft implant for insertion into the SI Joint.

FIG. 3 shows an alternate view of one embodiment of an allograft implant.

FIG. 4 shows an embodiment of the instruments in the joint fusion apparatus.

FIG. 5 shows an embodiment of the working channel and an embodiment of the joint locator.

FIG. 6 shows a close up of the insertion end of one embodiment of a working channel.

FIG. 7 shows an alternate view of the embodiment shown in FIG. 6.

FIG. 8 is an enlarged view of the insertion end of an embodiment of the joint locator fully inserted into the working channel of FIG. 4.

FIG. 9 is an enlarged view showing the device of FIG. 8 with the orientation reversed.

FIG. 10 shows a close up of the working end of one embodiment of a working channel.

FIG. 11 shows the joint locator of FIG. 4 partially inserted into the working channel.

FIG. 12 shows the joint locator of FIG. 4 fully inserted into the working channel.

FIG. 13 shows the working channel of FIG. 4 and an embodiment of the abrading device.

FIG. 14 is an enlarged view of an embodiment of the abrading head.

FIG. 15 shows an enlarged view of one embodiment of an abrading head.

FIG. 16 shows the abrading device of FIG. 13 with an embodiment of a slide hammer disassembled.

FIG. 17 is an enlarged view of an embodiment of the connection interface of a slide hammer.

FIG. 18 shows a close up of one embodiment of the diaphragm and threaded connector of a slide hammer assembly.

FIG. 19 shows the abrading device of FIG. 13 partially inserted into the working channel of FIG. 4.

FIG. 20 shows the abrading device of FIG. 13 fully inserted into the working channel of FIG. 4 with the slide hammer in its locked position.

FIG. 21 shows the abrading device of FIG. 13 fully inserted into the working channel of FIG. 4 with the slide hammer in its extended position.

FIG. 22 shows the working channel of FIG. 4 and an embodiment of the insertion device.

FIG. 23 is an enlarged view of the insertion end of the insertion device of FIG. 22.

FIG. 24 shows the insertion device of FIG. 22 with an embodiment of an allograft implant loaded into the tines of the insertion end.

FIG. 25 shows the insertion device of FIG. 22 and the allograft implant partially inserted into the working channel of FIG. 4.

4

FIG. 26 shows the insertion device of FIG. 22 and the allograft implant fully inserted into the working channel of FIG. 4.

FIG. 27 is a front view of one embodiment of the incision guide.

FIG. 28 is a top view of one embodiment of the incision guide.

FIG. 29 is a right side view of one embodiment of the incision guide.

FIG. 30 is a cross-sectional view A-A of the incision guide of FIG. 29.

FIG. 31 is an isometric view of one embodiment of the incision guide.

FIG. 32 is a side view of one embodiment of an allograft implant.

FIG. 33 is a cross-sectional view B-B of the allograft implant of FIG. 32.

FIG. 34 is a top view of one embodiment of an allograft implant.

FIG. 35 is a rear view of one embodiment of an allograft implant.

FIG. 36 is a front view of one embodiment of an allograft implant.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

With reference to the drawings, the method for fusing a sacroiliac joint ("SI Joint") now will be described with regard for the best mode and the preferred embodiment. The embodiments disclosed herein are meant for illustration and not limitation of the invention. An ordinary practitioner will appreciate that it is possible to create many variations of the following embodiments without undue experimentation.

The method and corresponding system and instrumentation described herein are used primarily for fusing an SI Joint 3 in the pelvis of a human. Referring to FIGS. 1-3, an allograft implant 5 is placed in the soft tissue of the SI Joint 3 between the sacrum 1 and the ilium 2 of the pelvis. For the purpose of reference, the SI Joint plane as used herein means the general plane of the SI Joint 3 as defined by the abutting surfaces of the sacrum 1 and ilium 2. The implant 5 provides a matrix for bone healing across the SI Joint, thereby fusing the sacrum 1 and ilium 2 together. In one embodiment, the implant 5 generally comprises a nose 6 and at least one pair of opposing lateral sides 7, each comprising a groove 8 that is disposed at least partially along the length of each such lateral side 7.

Referring to FIG. 4, in one embodiment, the system comprises a working channel 10, a joint locator 20, an abrading device 30, and an implant inserter 60. Each of these instruments has a longitudinal axis along the centerline of its length. Referring to FIG. 5, the working channel 10 is a tube-like member that provides a working passage for insertion of the other instruments of the system, and for delivery of the implant 5 to the SI Joint 3. The working channel 10 is a cannula, a lumen, a sleeve, or another device suitable for providing working access of the other instruments to the SI Joint 3, as described below. The working channel 10 has an insertion end 11 and a working end 12, and a channel 13 extending therebetween. The channel 13 is a tube or bore having a cross section that is rectilinear or curvilinear. The insertion end 11 has a pair of arms 14 for providing engagement of the SI Joint 3 and distraction of tissue surrounding the insertion end 11. The arms 14 are probes, prongs, or other members protruding from the insertion end 11 of the working channel 10. Insertion of the

5

arms **14** into the SI Joint **3**, as described below, resists or prevents the working channel **10** from rotating about its longitudinal axis in relation to the SI Joint **3**. The longitudinal axis generally extends along the length of the working channel **10** in proximity to the centerline of the channel **13**.

The insertion end **11** of the working channel **10** is configured for seating in and against the SI Joint **3**, and against the sacrum **1** and ilium **2** in particular. The insertion end **11** comprises a first iliac contour **15** and a first sacral contour **16**, both of which are defined by the contour between the insertion arms **14** and the body of the working channel **10**. For example, referring to FIGS. **6-9**, one side of the insertion end **11** comprises the arms **14** connected to the working channel **10** via the first iliac contour **15**, which is configured for abutment against the ilium **2** when the arms **14** are inserted into, and seated within, the SI Joint **3** as described below. The opposite side of the insertion end **11** comprises the arms **14** connected to the working channel **10** via the first sacral contour **16**, which is configured for abutment against the sacrum **1** when the arms **14** are inserted into, and seated within, the SI Joint **3**.

Referring to FIGS. **5** and **10**, the inside surface of the working channel **10** has a means for aligning instruments, the alignment means **17** comprising a groove, recess, channel, indent, or the like for receiving and engaging a ridge, rib, detent, or other protrusion on the mating instrument that is keyed to the alignment means **17**. In one embodiment, the working channel **10** further comprises a channel collar **18** for receiving mating components of the joint locator **20**, abrading device **30**, or implant inserter **60** in an abutting engagement, as described below. In an embodiment of the channel collar **18**, the collar further comprises an alignment means **17**.

Referring to FIG. **5**, the joint locator **20** has an insertion end **21** and a handle **22**, or working end. The insertion end **21** comprises a penetration tip **23** for penetrating the soft tissue in proximity to the SI Joint **3**. This soft tissue is the soft tissue between the surface of the patient's skin the SI Joint **3**, such as muscle tissue, and the soft tissue inside the SI Joint **3**, such as cartilage and ligaments. The penetration tip **23** is configured for penetrating these types of soft tissue. For example, one embodiment of the penetration tip **23** comprises a blade or chisel component for cutting the soft tissue. A leading edge of the penetration tip **23** may comprise, in whole or in part, such a blade or chisel component. In another embodiment of the penetration tip **23**, the penetration tip **23** is rounded or dull so that it does not inadvertently penetrate the sacrum **1**, the ilium **2**, or any other bone structure in the pelvic area in the event that the joint locator **20** is misaligned during insertion and penetration. In this embodiment, the penetration tip **23** tends to tear or rip through the soft tissue rather than slicing or cutting through it.

Referring again to FIGS. **8** and **9**, the joint locator **20** insertion end **21** comprises a second iliac contour **24** and a second sacral contour **25**. For example, one side of the joint locator **20** insertion end **21** comprises the second iliac contour **24**, which is configured for abutment against the ilium **2** when the penetration tip **23** is inserted into the SI Joint **3**, as described below. The other side of the joint locator **20** insertion end **21** comprises the second sacral contour **25**, which is configured for abutment against the sacrum **1** when the penetration tip **23** is inserted into the SI Joint **3**.

The outside surface of the joint locator **20** has a means for keying with the alignment means **17** of the working channel **10**, the keying means **27** comprising a ridge, rib, detent, or

6

other protrusion on the outside surface of the joint locator **20** capable of engaging the alignment means **17** to resist or prevent relative rotation between the joint locator **20** and the working channel **10**.

In one embodiment, referring to FIGS. **5**, **11**, and **12**, the joint locator **20** has a channel **26** for receiving the K-wire **4**. This channel **26** is a cannula, lumen, or other bore-like feature capable of receiving the K-wire **4** in a pass-through manner, preferably along a longitudinal axis, or centerline, of the joint locator **20**. In one embodiment of the joint locator **20**, the handle **22** further comprises a stop **28** for abutting against the channel collar **18** of the working channel **10**.

Referring to FIG. **13**, the abrading device **30** comprises a hammer sleeve **31** at a proximate end and an abrading head **32** at a distal end. The abrading head **32** is a rasp, broach, or other abrading tool that is used to grate, abrade, or otherwise decorticate the cortical bone inside the SI Joint **3**. In one embodiment, shown in FIGS. **14** and **15**, the abrading head **32** is a generally rectangular member comprising abrading surfaces **33** on a first pair of opposing sides of the head **32**, an open tip **34** for insertion into the SI Joint **3**, and a second pair of opposing sides **35** between the abrading surfaces **33**, the second pair of opposing lateral sides **35** having one or more lateral openings. Each abrading surface **33** comprises one or more teeth, barbs, blades, ridges, slots, broaches, or other members or features capable of abrading the cortical bone in the SI Joint **3**. The open tip **34** comprises a cutting edge **36** around all or part of the leading edge of the open tip **34**, the cutting edge **36** configured for cutting bone tissue inside the SI Joint **3**, such as the sacrum **1** or ilium **2**. The abrading surfaces **33** and lateral sides **35** form a box-like abrading head **32** having a void therein. The openings in the lateral sides **35** enable lateral ingress into and egress from the void. For example, as the cutting edge **36** cuts bone tissue inside the SI Joint **3**, the dislodged bone tissue falls into the void and may exit the abrading head **32** via the openings in the lateral sides **35**.

In one embodiment, each side of the first pair of opposing sides is a substantially planar member having a distal edge terminating at the open tip **34**, the interface between the open tip **34** and the distal edge comprising a substantially straight cutting edge **36**. Each side of the second pair of opposing sides may comprise a curved distal portion terminating at the open tip **34**, the interface between the open tip **34** and the curved distal portion comprising a curved cutting edge **36**. The curved distal portion of each side of the second pair of opposing sides **35** may further comprise a taper toward its opposite side of the second pair of opposing sides **35**.

Referring to FIG. **19**, the abrading device **30** further comprises a keying means **37**, which is similar to the joint locator **20** keying means **27** described above. The keying means **37** mates with the alignment means **17** in the working channel **10** to resist or to prevent relative rotation between the abrading device **30** and the working channel **10** about each member's respective longitudinal axis. The abrading device **30** further comprises an abrading stop **38** for abutting against the channel collar **18** of the working channel **10**. In one embodiment, the abrading device **30** further comprises a K-wire channel for receiving the K-wire **4**. This K-wire channel is a cannula, lumen, or other bore-like feature capable of receiving the K-wire **4** in a pass-through manner, preferably along a longitudinal axis of the abrading device **30**.

Referring to FIGS. **16**, **17**, and **18**, the abrading device **30** further comprises a slap hammer assembly, or slide hammer

assembly 40. In one embodiment, the slide hammer assembly 40 comprises a base 51 connected to a shaft 44, and a releasing means that releasably connects a hammer sleeve 31 to the base 51. The released hammer sleeve 31 is configured for sliding engagement along the shaft 44. The releasing means is any means for releasably connecting the hammer sleeve 31 to the base 51, thereby transitioning the slide hammer assembly between its released position and its locked position. The releasing means could be a mating threaded connection, a quick disconnect attachment, a depressible tab, a latch, a clasp, a clip, a clamp, or other equivalent connection structure.

In one embodiment, shown in FIGS. 16, 17, and 18, the releasing means is a mating threaded connection. This embodiment includes a collar 41 on the abrading device 30, a slide hammer shaft 44, and the hammer sleeve 31. The collar 41 comprises internal threads 42 and external threads 43. The shaft 44 comprises a threaded end 45 and a stop end 46. The hammer sleeve 31 has a threaded connector 48 and a hollow, cylindrical bore comprising an internal diaphragm 47 having a diaphragm opening 49 (see FIG. 18). The diaphragm opening 49 is sized to permit sliding passage of all parts of the shaft 44 except the stop end 46. The stop end 46 is sized too large to fit through the diaphragm opening 49.

To assemble the slide hammer assembly 40 of this embodiment, the threaded end 45 of the shaft 44 is inserted into the bore of the hammer sleeve 31, through the diaphragm 47 inside the hammer sleeve 31, and the threaded end 45 is threaded into, and mated with, the internal threads 42 of the collar 41. The threaded connector 48 in the hammer sleeve 31 is then mated to the external threads 43 on the collar 41 to promote a secure connection. The stop end 46 is disposed inside the bore of the hammer sleeve 31 on a side of the diaphragm 47 opposite that of the location of the threaded connector 48. In this configuration, shown in FIG. 20, the slide hammer assembly 40 is in its locked position.

To operate the slide hammer assembly 40, the threaded connector 48 is disengaged from the external threads 43 of the collar 41, placing the slide hammer assembly 40 in its released position, which is shown in FIG. 21. This released position enables the hammer sleeve 31 to slide freely along the shaft 44. The hammer sleeve 31 is pulled until the diaphragm 47 inside the hammer sleeve 31 engages the stop end 46 of the shaft 44, thereby causing an impact that delivers the slide hammer force. Thus, the slide hammer assembly has a released position that enables operation of the slide hammer assembly, and a locked position that prohibits operation of the slide hammer assembly.

Referring to FIGS. 22-26, the implant inserter 60 comprises a handle 61 and an implant insertion end 62. The implant insertion end 62 has a pair of tines 63 for holding the implant 5 during the process of inserting the implant 5 into the SI Joint 3. Each tine 63 is supported by a tine shaft 66, which terminates at a shoulder 67. The tine shafts 66 provide flexibility such that the implant 5 is removably retained between the tines 63 with the shoulder 67 abutting against the implant 5 (see FIG. 24). For example, in one embodiment the width of the implant 5 between the opposing grooves 8 is slightly larger than the space between the respective tines 63 such that when the implant 5 is seated in the implant insertion end 62, the respective tines 63 are pushed slightly apart by the grooves 8. This causes a slight amount of friction between the tines 63 and the grooves 8, thereby releasably retaining the implant 5 in the implant insertion end 62.

The implant inserter 60 further comprises an inserter keying means 65, which is similar to the keying means 27

of the joint locator 20. The inserter keying means 65 mates with the alignment means 17 in the working channel 10 to resist or to prevent relative rotation between the implant inserter 60 and the working channel 10 about each member's longitudinal axis. In one embodiment, the implant inserter 60 further comprises a channel 64 for receiving the K-wire 4 (see FIG. 23). This channel 64 is a cannula, lumen, or other bore-like feature capable of receiving the K-wire 4 in a pass-through manner. In one embodiment of the implant inserter 60, the handle 61 further comprises an inserter stop 68 for abutting against the channel collar 18 of the working channel 10.

In one embodiment of a method of installing the implant 5, the procedure for installing the implant 5 in the SI Joint 3 is started by locating an insertion point in the SI Joint 3, which is the location where the implant 5 is to be installed. For example, the free end of the K-wire 4 is inserted into the SI Joint 3 at the insertion point where the implant 5 is to be installed, thereby defining an intended location for the implant void. The implant void is a seat or groove between the sacrum 1 and ilium 2 for seating the implant 5, as described below. The K-wire 4 is preferably inserted from a posterior approach. It is preferable, but not required, that the implant 5 is installed under the portion of the posterior superior iliac spine that overhangs the SI Joint 3. One or more alternate location are also suitable for fusion of the SI Joint 3. A K-wire 4 is inserted into the SI Joint 3 at each location where an implant 5 is to be inserted.

In one embodiment, referring to FIGS. 27-31, the initial incision is made using an incision guide 70 that comprises a channel 71 for removably receiving a K-wire 4. The incision guide 70 further comprises a guide slot 72 for receiving a blade, scalpel, or similar cutting instrument (not shown). The guide slot 72 is disposed at an angle in relation to the channel 71 such that when the scalpel is extended through the guide slot 72, the tip of the scalpel is disposed above the patient's skin at the proper location for making the initial incision into the patient. This location is above the SI Joint 3 where the allograft implant 5 will be introduced into the soft tissue above the SI Joint 3, and eventually into the SI Joint 3 itself. In one embodiment, the guide slot 72 is oriented at an angle A of about 70° to about 75° in relation to horizontal H (see FIG. 30). In this orientation, the channel 71 is perpendicular to horizontal.

In this embodiment, the K-wire 4 is inserted into the SI Joint 3 as described above. The incision guide 70 is placed over the K-wire 4 such that the K-wire 4 is slidably received into the channel 71. In one embodiment, the scalpel is inserted into the guide slot 72 and retained in fixed relation to the channel 71 such that the cutting tip of the scalpel is located in close proximity to the K-wire 4. The incision guide 70 is then advanced toward the SI Joint 3, and the cutting tip of the scalpel makes the incision as the incision guide 70 advances. Once the initial incision is adequately formed, the incision guide 70 is lifted to remove it from the K-wire 4, and the surgery proceeds with other instruments for inserting the implant 5 into the SI Joint 3.

The joint locator 20 is then fully inserted into the working channel 10 (see FIG. 12). In mating the joint locator 20 inside the working channel 10, the keying means 27 of the joint locator 20 is oriented to engage the alignment means 17 of the working channel 10. This engagement enables the first iliac contour 15 of the working channel to be disposed in mating alignment with the second iliac contour 24 of the joint locator 20, and the first sacral contour 16 of the working channel 10 to be disposed in mating alignment with the second sacral contour 25 of the joint locator 20 (see

FIGS. 8 and 9). The respective first and second iliac contours 15, 24 are configured to be seated in mating placement against the ilium 2 when the insertion end 11 is disposed inside the SI Joint 3, and the respective first and second sacral contours 16, 25 are configured to be seated in corresponding mating placement against the sacrum 1 when the insertion end 11 is disposed inside the SI Joint 3. The stop 28 abuts against the channel collar 18 of the working channel 10 to prevent over penetration of the penetration tip 23 into the SI Joint 3, thereby avoiding damage to the soft tissue and nerves on the anterior side of the SI Joint 3.

The free end of the K-wire is inserted into the K-wire channel 26 of the combined joint locator 20/working channel 10, and this combined device is advanced toward the SI Joint 3, guided by the K-wire 4. As the joint locator 20/working channel 10 combination is advanced, the penetration tip 23 cuts or tears through the soft tissue above and inside the SI Joint 3. If necessary, the combined joint locator 20/working channel 10 is advanced via blows from a mallet against the proximal end of the handle 22 to deliver an appropriate axial force. The impact from the mallet causes an axial force that is transmitted through the handle 22 to the stop 28, where the axial force is imparted to the channel collar 18 and into the working channel 10. As such, the impact force from a mallet is shared between the working channel insertion end 11 and the joint locator insertion end 21.

The combined joint locator 20/working channel 10 is advanced until the respective first and second iliac contours 15, 24 abut the ilium 2 and the respective first and second sacral contours 16, 25 abut the sacrum 1. In this position, the arms 14 of the working channel 10 are disposed inside the SI Joint 3 to retain the proper alignment of the working channel 10, and therefore the alignment means 17, thereby ensuring a proper alignment of the abrading device 30 and the implant inserter 60 later in the procedure. In some embodiments, insertion of the arms 14 into the SI joint 3 will distract the joint, thus separating the sacrum 1 and the ilium 2. This distraction establishes a uniform width of the spacing in the SI joint 3 prior to use of the other instrumentation. Thus, the instrumentation described herein will work with a patient of any size because the arms 14 set the width of the SI joint 3 to a uniform distance regardless of the size or scale of the sacrum 1 or ilium 2.

In an alternate embodiment of the installation method, a K-wire 4 is omitted from the procedure. Instead, the combined joint locator 20/working channel 10 is advanced through an incision in the patient, and this advancement continues as described above until the insertion ends 11, 21 are inserted into the SI Joint 3 as described above.

Once the combined joint locator 20/working channel 10 device is properly seated in the SI Joint 3, the joint locator 20 is removed from the working channel 10. The surrounding soft tissue remains distracted or dilated by the working channel 10 and the respective arms 14, thereby enabling direct access to the SI Joint 3 area. The abrading device 30 is then inserted into the working channel 10, with the keying means 37 engaging the alignment means 17 to promote proper alignment of the abrading head 32 with respect to the SI Joint 3. The abrading head 32 is advanced through the working channel 10 until the abrading head 32 makes contact with the SI Joint 3. The abrading head 32 is forced into the SI Joint 3 (using a mallet if necessary), and the cutting edge 36 cuts the bone tissue and any soft tissue, such as ligaments or cartilage. The abrading stop 38 abuts against the channel collar 18 of the working channel 10 to prevent over penetration of the abrading head 32 into the SI Joint 3,

thereby avoiding damage to the soft tissue and nerves on the anterior side of the SI Joint 3. During this process, the cutting edge 36 cuts through the relevant bone portions of the sacrum 1 and ilium 2, and the abrading surfaces 33 work simultaneously in connection with the cutting edge 36 to decorticate the cortical bone inside the SI Joint 3, thereby forming a decorticated implant void at the insertion point of the SI Joint 3. The decorticated implant void has a generally rectangular cross sectional shape such that the decorticated implant void is adapted for receiving the fusion implant 5, which has a generally rectangular cross sectional shape for mating with the decorticated implant void. Thus, use of the abrading head 32 enables installation of the implant 5 without the need for using a drill or other rotary cutting instrument to form a pilot hole for the implant 5. As used herein, a rotary cutting instrument is any device capable of cutting material by turning, rotating, or other angular motion about an axis of the device, whether power-driven or hand-driven. This is a significant improvement of the present set of instruments over prior art methods and instrument sets for SI Joint 3 fusion.

The abrading device 30 is then worked in and out of the working channel 10 such that the abrading surfaces 33 abrade, or decorticate, the respective surfaces of the sacrum 1 and the ilium 2 inside the SI Joint 3. Again, the abrading stop 38 abuts against the channel collar 18 to prevent over penetration of the abrading head 32. During this process, the abrading head 32 may become lodged in the SI Joint 3, becoming difficult to remove. In these instances, the slide hammer assembly 40 is enabled so that the abrading head 32 may be removed by the impact force of the slide hammer assembly 40, as described above. Operation of the slide hammer assembly 40 provides a significant advantage over prior systems because when the abrading head 32 becomes lodged in the SI joint 3, counter pressure cannot be applied to the patient to counter the pull-out force needed to dislodge the abrading head 32 from the SI joint 3. The slide hammer assembly 40 enables removal of a lodged abrading head 32 in a safe manner without applying any counter pressure to the patient.

As the abrading head 32 is worked in and out of the SI Joint 3, the abrading surfaces 33 abrade the cortical bone of the sacrum 1 and the ilium 2 inside the SI Joint 3. The cortical bone is abraded until bleeding begins, thereby promoting the patient's healing process of the cortical bone. This degree of abrasion and corresponding healing promotes fusion of the SI Joint 3.

Once the SI Joint 3 is adequately abraded, the abrading device 30 is removed from the working channel 10. Thus, this method of fusing the SI Joint 3 comprises steps for forming a void for a fusion implant 5 in the SI Joint 3 without using a rotary cutting instrument. At this point in the procedure, the K-wire 4 may be removed from the working channel 10 to enable proper advancement of the implant 5 through the working channel 10 and proper installation of the implant 5 into the SI Joint 3. Alternately, the K-wire 4 can be removed from the working channel 10 at any time after the working channel 10 is properly seated in the SI Joint 3, as described above.

The allograft implant 5 is placed into the tines 63 of the implant inserter 60 such that each tine 63 is seated into a mating groove 8 on the lateral side 7 of the implant 5, and the shoulder 67 abuts the implant 5 (see FIG. 24). The implant inserter 60 is then inserted into the working channel 10 such that the keying means 65 engages the alignment means 17 to ensure proper orientation of the implant inserter 60, and thus, the implant 5. The implant inserter 60 is used

11

to deliver the implant **5** to the abraded area of the SI Joint **3** through the working channel **10**. If necessary, the implant inserter **60** is struck by a mallet to force the implant **5** into the abraded area of the SI Joint **3**, the shoulder **67** transferring the impact force to the implant **5**. In these instances, the inserter stop **68** abuts against the channel collar **18** of the working channel **10** to prevent over penetration of the implant **5** into the SI Joint **3**, thereby ensuring that the implant **5** is properly placed inside the SI Joint **3**.

Once the implant **5** is fully inserted into the SI Joint **3**, the implant inserter **60** is removed from the working channel **10**, leaving the implant **5** installed in the abraded area of the SI Joint **3**. In most instances, the friction force between the implant **5** and the inside of the SI Joint **3** is greater than the friction force between the respective tines **63** and grooves **8**. In these instances, removal of the implant inserter **60** is accomplished by applying a removal force to the implant inserter **60** greater than the friction force between the tines **63** and the grooves **8**. The tines **63** slice out of the grooves **8** as the implant inserter **60** is retracted from the working channel **10**. In other instances, the friction force between the implant **5** and the inside of the SI Joint **3** is less than the friction force between the respective tines **63** and grooves **8**. In these instances, removal of the implant inserter **60** is accomplished by inserting a K-wire **4** or similar device into the K-wire channel **64** and advancing the K-wire **4** until the distal end of the K-wire abuts against the implant **5** between the tines **63**. The K-wire **4** is used to hold the implant **5** in place inside the SI Joint **3** as the removal force is applied to the implant inserter **60**. The tines **63** are thereby removed from the grooves **8** as the K-wire **4** holds the implant **5** in its installed location. Once the tines **63** are pulled free from the grooves **8**, the implant inserter **60** is disengaged from the implant **5**, and the implant inserter **60** and the K-wire **4** are removed from the working channel **10**. The working channel **10** is then removed from the surgical site, causing the SI Joint **3** to contract, thereby exerting a compressive force on the implant **5**. This compressive force is caused by the ligaments of the SI Joint **3** that compress the joint, thereby holding it together. The surgical site is then sterilized and closed for healing.

As the abraded cortical bone heals, the bone fuses with the allograft implant **5**, eventually causing the sacrum **1** and the ilium **2** to grow together at the location of the implant **5**, thereby fusing the SI Joint **3**.

In any of the foregoing embodiments, one or more instruments may comprise disposable material, such as medical grade plastics, certain metals, or other disposable material.

Referring to FIGS. **32-36**, the implant **5** generally has two opposing faces **81**. When the implant **5** is inserted into the SI Joint **3**, one opposing face **81** is disposed against the sacrum **2**, and the other opposing face **81** is disposed against the ilium **3**. Each of the opposing faces **81** comprises one or more anti-migration features **82**, such as teeth or ridges, that resist movement of the implant inside the SI Joint **3**.

In one embodiment, the implant **5** comprises a body **83** having a proximal end **86**, a distal end **87**, and a length disposed therebetween, the distal end having a rounded nose **6**. The body **83** further comprises two sides **7**, each side **7** comprising a groove **8** beginning at the proximal end **86** of the body **83** and continuing along each of the two sides **7** for at least part of the length, the distance between the two sides **7** defining a width **W** of the body.

The implant **5** further comprises a central graft window **85** that enables fusion of the SI Joint **3** to occur through the implant **5**. The graft window **85** is disposed between each of the opposing faces **81**, the graft window **85** providing

12

passage through the body **83** between the two opposing faces **81**. The portion of the body **83** located between the graft window **85** and each of the sides **7** defines a wall **84**.

When viewed in cross section (see FIG. **33**), the area of the graft window **85** is about 35% to about 40% of a first cross-sectional area of the body, which is the area of the total implant **5** as shown by the hatched area in FIG. **33**. The area of the window **85** is about 60% of the total area of each opposing face **81** that makes contact with the bone, whether the sacrum **1** or the ilium **2**. These ratios provide a strength-to-contact area relationship that optimizes performance of the implant **5** as a promoter of SI Joint **3** fusion. In these ratios, the implant **5** provides enough strength so that it is not crushed inside the SI Joint **3**, and it provides a large enough graft window **85** to expedite fusion of the SI Joint **3** across and through the implant **5**.

In one embodiment, the graft window **85** has a proximal portion **88** located in proximity to the grooves **8**, and a distal portion **89**, the proximal portion **88** having a width **W1** that is less than a width **W2** of the distal portion **89** such that the wall **84** maintains a minimum thickness in a range of about 17% to about 20% of the width **W** of the body **83**.

In the foregoing embodiments, it is preferable, but not required, that the graft window **85** is unobstructed by internal or intermediate supports. Such internal or intermediate supports are sometimes used in allograft implants to provide structural support to the implant. However, these internal or intermediate supports obstruct bone fusion from occurring through the window. As such, the graft window **85** may provide an open passage through the body **83** between the opposing faces **81**. The open passage may be rectilinear or curvilinear. The proximal end **86** of the body **83** may further comprise a taper **90** that reduces a second cross-sectional area of the body **83**.

The foregoing embodiments are merely representative of the SI Joint fusion method and not meant for limitation of the invention. For example, persons skilled in the art would readily appreciate that there are several embodiments and configurations of abrading devices, slide hammer devices, and other devices and instruments described herein that will not substantially alter the nature of the SI Joint fusion method. Some steps of the method can be performed in a sequence other than that described above. Consequently, it is understood that equivalents and substitutions for certain elements and components set forth above are part of the invention described herein, and the true scope of the invention is set forth in the claims below.

What is claimed is:

1. A method of forming an implant void in a sacroiliac joint without the use of a rotary cutting instrument, the method comprising the steps of:

locating an insertion point in the sacroiliac joint, the insertion point defining an intended location for the implant void;

introducing a working channel into the insertion point, the working channel having an insertion end and a working end, the insertion end of the working channel further comprising a first iliac contour, a first sacral contour, and insertion arms;

inserting the insertion arms into the sacroiliac joint at the insertion point such that the first sacral contour is seated against a sacrum bone and the first iliac contour is seated against an ilium;

introducing an abrading device into the working channel, the abrading device comprising:

an abrading head at a distal end of the abrading device, the abrading head having:

13

abrading surfaces on each of a first pair of opposing sides, the abrading surfaces comprising one or more teeth, barbs, blades, ridges, slots, broaches, or other members capable of abrading a cortical bone of the sacroiliac joint; and

an open tip comprising a cutting edge disposed at a leading edge of the open tip, the cutting edge configured to cut bone tissue in the sacroiliac joint; and

a slide hammer assembly at a proximal end of the abrading device, the slide hammer assembly having a released position that enables operation of the slide hammer assembly, a locked position that prohibits operation of the slide hammer assembly, and a releasing means for transitioning the slide hammer assembly between the locked position and the released position; and

advancing the abrading device into the sacroiliac joint such that the open tip cuts bone tissue away from the sacrum or the ilium and the abrading surfaces decorticate the cortical bone inside the sacroiliac joint, thereby forming a decorticated implant void at the insertion point without using a rotary cutting instrument.

2. The method of claim 1, wherein, upon the abrading head becoming lodged inside the sacroiliac joint, unlocking the slide hammer assembly via the releasing means, and using the slide hammer assembly to dislodge the abrading head from the sacroiliac joint.

3. The method of claim 1, wherein introducing the working channel into the insertion point further comprises:

introducing a joint locator into the working channel, the joint locator having a penetration tip at an insertion end, the penetration tip comprising a second iliac contour and a second sacral contour; and

placing the first and second iliac contours and the first and second sacral contours in mating alignment by fully inserting the joint locator into the working channel, thereby defining a combined joint locator and working channel device.

4. The method of claim 3, wherein inserting the insertion arms into the sacroiliac joint further comprises inserting the combined joint locator and working channel device into the sacroiliac joint at the insertion point such that the first and second sacral contours are seated against the sacrum bone and the first and second iliac contours are seated against the ilium.

5. The method of claim 4, further comprising tearing through soft tissue above and inside the sacroiliac joint via the penetration tip until the first and second iliac contours abut the ilium and the first and second sacral contours abut the sacrum.

6. The method of claim 2, wherein introducing the working channel into the insertion point further comprises:

introducing a joint locator into the working channel, the joint locator having a penetration tip at an insertion end, the penetration tip comprising a second iliac contour and a second sacral contour; and

placing the first and second iliac contours and the first and second sacral contours in mating alignment by fully inserting the joint locator into the working channel, thereby defining a combined joint locator and working channel device.

7. The method of claim 6, wherein inserting the insertion arms into the sacroiliac joint further comprises inserting the combined joint locator and working channel device into the sacroiliac joint at the insertion point such that the first and

14

second sacral contours are seated against the sacrum bone and the first and second iliac contours are seated against the ilium.

8. The method of claim 7, further comprising tearing through soft tissue above and inside the sacroiliac joint via the penetration tip until the first and second iliac contours abut the ilium and the first and second sacral contours abut the sacrum.

9. The method of claim 1, wherein forming the decorticated implant void at the insertion point further comprises forming a generally rectangular cross sectional shape for the decorticated implant void such that the decorticated implant void is adapted for receiving a fusion implant having a generally rectangular cross sectional shape.

10. The method of claim 9, wherein, upon the abrading head becoming lodged inside the sacroiliac joint, unlocking the slide hammer assembly via the releasing means, and using the slide hammer assembly to dislodge the abrading head from the sacroiliac joint.

11. The method of claim 9, wherein introducing the working channel into the insertion point further comprises:

introducing a joint locator into the working channel, the joint locator having a penetration tip at an insertion end, the penetration tip comprising a second iliac contour and a second sacral contour; and

placing the first and second iliac contours and the first and second sacral contours in mating alignment by fully inserting the joint locator into the working channel, thereby defining a combined joint locator and working channel device.

12. The method of claim 11, wherein inserting the insertion arms into the sacroiliac joint further comprises inserting the combined joint locator and working channel device into the sacroiliac joint at the insertion point such that the first and second sacral contours are seated against the sacrum bone and the first and second iliac contours are seated against the ilium.

13. The method of claim 12, further comprising tearing through soft tissue above and inside the sacroiliac joint via the penetration tip until the first and second iliac contours abut the ilium and the first and second sacral contours abut the sacrum.

14. The method of claim 10, wherein introducing the working channel into the insertion point further comprises:

introducing a joint locator into the working channel, the joint locator having a penetration tip at an insertion end, the penetration tip comprising a second iliac contour and a second sacral contour; and

placing the first and second iliac contours and the first and second sacral contours in mating alignment by fully inserting the joint locator into the working channel, thereby defining a combined joint locator and working channel device.

15. The method of claim 14, wherein inserting the insertion arms into the sacroiliac joint further comprises inserting the combined joint locator and working channel device into the sacroiliac joint at the insertion point such that the first and second sacral contours are seated against the sacrum bone and the first and second iliac contours are seated against the ilium.

16. The method of claim 15, further comprising tearing through soft tissue above and inside the sacroiliac joint via the penetration tip until the first and second iliac contours abut the ilium and the first and second sacral contours abut the sacrum.

* * * * *