

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	802.16a OFDMA PHY suitability for mobile applications	
Date Submitted	19.9.2002	
Source(s)	Yigal Leiba Dr. Zion Hadad Itzik Kitroser Yossi Segal Moshe Levinson Runcom Technologies LTD. 2 Ahcoma St. 75655, Rishon Lezion Israel	Voice: 972-3-9528440 Fax: 972-3-9528805 yigall@runcom.co.il yossis@runcom.co.il itzikk@runcom.co.il zionh@runcom.co.il moshel@runcom.co.il
Re:	Call for contributions, document IEEE 802.16sgm-02/08	
Abstract	This document discusses channel models for mobile wireless channels, and discusses the suitability of the OFDMA PHY mode for operation over these channels	
Purpose	For discussion	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>	

Mobile Channel Models

Path loss

Path loss in mobile wireless channel is typically much higher than the path loss for an equivalent fixed wireless channel. This happens because the mobile reception unit typically uses a low height omni-directional antenna, and. The higher path loss requires higher system gain, and the high variance of the path loss causes inter-cell interference. Several path loss models are widely used to characterize the path loss in mobile environments mostly based on the Okumura-Hata measurement [1], and modifications to adapt it to higher frequency bands.

Multipath

Operation over broadband mobile wireless channels implies ability to operate even in fading channels in which significant multipath is present. In [1], [3], [4] and [5] it is shown that RMS delay spread for wireless mobile channels (mostly in 900MHz and 1900MHz) range anywhere between several hundreds of nanoseconds to several tens of microseconds. The large delay spreads are present in both vehicular and pedestrian mobility situations due to the small height of the antennas, and the fact that the mobile unit is typically using omni-directional antennas.

Doppler and fast fading

Doppler frequency shift can be estimated by $f_{carrier} \cdot V_{vehicle} / C$ (ignoring the angle of the movement). In order to estimate the Doppler effect at our target frequency bands, let's calculate for the MMDS (2.5GHz) and UNII (5.8GHz) bands. Assuming a vehicle speed of 100Km/H we get a maximal Doppler shift of about 230Hz for MMDS, and about 540Hz for UNII. The Doppler power spectrum used to characterize the fast fading can either be estimated as a flat spectrum as shown in [6], or follows the Jakes model [7].

Impact of mobile channel on OFDMA PHY

Timing synchronization

Timing synchronization in an OFDMA receiver is based primarily on the strong auto-correlation properties of the OFDMA waveform. This autocorrelation is a consequence of the cyclic prefix part of the waveform. The passage of the OFDMA waveform through the wireless channel smears the autocorrelation because the CP collects somewhat different multipath than original instance of the symbol. The longer the CP relative to the channel delay spread, the less the autocorrelation is smeared. For OFDMA, CP even for a fairly broad 14MHz channel can be up to 32usec, in conformance with delay spreads expected in a mobile environment.

Frequency synchronization

Carrier frequency synchronization is an essential component in every coherent receiver. In OFDMA this synchronization is even more crucial as transmission bursts from several transmitters are synchronously combined in the uplink.

Frequency synchronization in OFDM receivers is generally based on a pre-FFT stage that handles the fractional frequency offset (i.e. the part that is not an integer multiple of sub-carrier spacing) and a post-FFT stage that handles the integer frequency offset.

The pre-FFT stage will usually utilize the OFDMA waveform autocorrelation. As discussed with regard to the timing synchronization, the OFDMA waveform displays strong autocorrelation even in severe multipath conditions due to the fact the duration of the CP greatly exceeds the channel delay spread.

The post-FFT stage will usually utilize the pilot tones to correct the integer frequency offset. In OFDMA 166 out of the 1702 used carriers are pilots. This provides a processing gain in excess of 20dB for the pilots PN series autocorrelation peak.

Frequency synchronization in a mobile environment is more challenging due to the Doppler frequency shift and the fast fading effects. These effects tend to smear the sub-carriers and introduce inter-carrier-interference. OFDMA symbols are short enough (a typical value would be 300usec in a 6MHz MMDS channel) even relative to the highest Doppler spectral component, so the channel response can be assumed fairly stable across one symbol. With the help of the carrier frequency synchronization techniques mentioned above, even one OFDMA symbol is enough to extract accurate carrier frequency estimations, and ensure both downlink and uplink synchronization.

Channel estimation and demodulation

Channel estimation in OFDMA receivers is based on pilot sub-carriers. In OFDMA there are both constant location pilots and variable location pilots. The variable location pilots are arranged such that one of every 12 sub-carriers is a pilot. This means that by using the pilots from one symbol, a channel estimate with length of up to 1/12 of the symbol can be done. This capability, combined with the length of the OFDMA symbols enables fast, per symbol, estimation of the channel. Thus OFDMA does not require a downlink preamble, and does not require that a transmission burst be shorter than the channel coherence time.

Channel coding

The OFDMA PHY supports a mandatory RS-Convolutional block code and optionally turbo codes. Both these codes are robust, and have been used in fixed as well as mobile environments.

Ranging and power control

The process of ranging has an important role in maintaining the uplink channel integrity by keeping the received power at the BST within the allowed bounds. In a mobile environment ranging has to be more frequent because of the existence of fast fading effects in the channel. The OFDMA PHY can support the fast power control loop necessary in a mobile environment. The features that enable this are,

- Short frame duration – 2mS is the current minimum supported.
- The CPE can do ranging frequently, with small chances of collision – CDMA code ranging enables multiple CPE to perform ranging in parallel without collisions and with excellent processing gain at the BST
- Fast power control – The downlink map contains a power control IE that provides a BW efficient means for controlling the CPE transmitted power

Inter-system interference

Due to the large variance in a mobile system path loss, inter-cell interference is a common occurrence in mobile wireless systems. The OFDMA PHY is designed such that sub-channels can be composed from several distinct permutations of sub-carriers. This feature enables significant reduction in inter-cell interference because even on occasions where the same sub-channel is used at the same time in two different cells, there is only a partial collision on the actual sub-carriers.

Performance estimates/simulations

In May 1998, a consortium of 17 broadcasters, network operators, manufacturers of professional and domestic equipment and research centers, led by T-NOVA (formerly Deutsche Telekom Berkom), launched the MOTIVATE project funded by the European Commission in the ACTS Program (Advanced Communications Technologies and Services), to investigate the practical and theoretical performance limits of DVB-T for mobile

reception. MOTIVATE partners performed a considerable amount of work both in the Laboratory (simulations, tests campaigns) and in the field (field trials, demonstrations) to achieve the project goals [8]. DVB-T is a close kin of 802.16a OFDMA PHY that operates in VHF/UHF frequencies and supports 8K and 2K FFT modes. The report demonstrates operation in a mobile environment at velocities exceeding 200Km/H.

References

- [1] "Field Strength and Its Variability in VHF and UHF Land Mobile Service", Y. Okumura, E. Ohmori, T. Kawano, K. Fukuda, REV. ELEC. COMM. LAB., VOL 16, SEPTEMBER-OCTOBER 1968
- [2] "A New Path-Gain/Delay-Spread Propagation Model for Digital Cellular Channels", Larry J. Greenstein, Vinko Erceg, Yu Shuan Yeh, Martin V. Clark, IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, VOL. 46, NO. 2, MAY 1997
- [3] "Path Loss, Scattering, and Multipath Delay Statistics in Four European Cities for Digital Cellular and Microcellular Radiotelephone", Scott Y. Seidel, Theodore S. Rappaport, Sanjiv Jain, Michael L. Lord, Rajendra Singh, IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, VOL. 40, NO. 4, NOVEMBER 1991
- [4] "900MHz Multipath Propagation Measurements for U.S. Digital Cellular Radiotelephone", Theodore S. Rappaport, Scott Y. Seidel, Rajendra Singh, IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, VOL. 39, NO. 2, MAY 1990
- [5] "Propagation Measurements and Models for Wireless Communication Channels", Jorgen B. Andersen, Theodore S. Rappaport, Susumu Yoshida, IEEE COMMUNICATIONS MAGAZINE, JANUARY 1995
- [6] "3-D Mobile Radio Channel Statistics", Richard H. Clarke, Wee Lin Khoo, IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, VOL. 46, NO. 3, AUGUST 1997
- [7] "Microwave Mobile Communications", W. C. Jakes, New York: Wiley, 1974
- [8] MOTIVATE report to the 36th DVB-TM meeting, 26,27 January 2000