



US009436645B2

(12) **United States Patent**
Al-Ali et al.

(10) **Patent No.:** **US 9,436,645 B2**
(45) **Date of Patent:** **Sep. 6, 2016**

(54) **MEDICAL MONITORING HUB**

USPC 710/303
See application file for complete search history.

(71) Applicant: **Masimo Corporation**, Irvine, CA (US)

(72) Inventors: **Ammar Al-Ali**, San Juan Capistrano, CA (US); **Eric Karl Kinast**, Santa Ana, CA (US); **Bilal Muhsin**, San Clemente, CA (US); **Benjamin Triman**, Rancho Santa Margarita, CA (US)

(73) Assignee: **MASIMO CORPORATION**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 652 days.

(21) Appl. No.: **13/651,167**

(22) Filed: **Oct. 12, 2012**

(65) **Prior Publication Data**

US 2013/0262730 A1 Oct. 3, 2013

Related U.S. Application Data

(60) Provisional application No. 61/547,017, filed on Oct. 13, 2011, provisional application No. 61/547,577, filed on Oct. 14, 2011, provisional application No. 61/597,120, filed on Feb. 9, 2012, provisional application No. 61/703,773, filed on Sep. 20, 2012.

(51) **Int. Cl.**
G06F 13/40 (2006.01)
G06F 19/00 (2011.01)

(Continued)

(52) **U.S. Cl.**
CPC **G06F 13/4081** (2013.01); **A61B 5/0002** (2013.01); **A61B 5/002** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 5/14551; A61B 5/1455; A61B 5/0205; A61B 5/14552; G06F 19/3418

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,646,606 A 2/1972 Buxton et al.
3,690,313 A 9/1972 Weppner et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 735499 10/1996
EP 2 335 569 A2 6/2011

(Continued)

OTHER PUBLICATIONS

Wachter, S. Blake; Journal of the American Medical Informatics Association; *The Employment of an Iterative Design Process to Develop a Pulmonary Graphical Display*; vol. 10, No. 4, Jul./Aug. 2003; pp. 363-372.

(Continued)


Primary Examiner — Brian Misiura

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear LLP

(57) **ABSTRACT**

The present disclosure includes a medical monitoring hub as the center of monitoring for a monitored patient. The hub includes configurable medical ports and serial ports for communicating with other medical devices in the patient's proximity. Moreover, the hub communicates with a portable patient monitor. The monitor, when docked with the hub provides display graphics different from when undocked, the display graphics including anatomical information. The hub assembles the often vast amount of electronic medical data, associates it with the monitored patient, and in some embodiments, communicates the data to the patient's medical records.

16 Claims, 46 Drawing Sheets



- (51) **Int. Cl.**
- A61B 5/00* (2006.01)
- A61M 16/00* (2006.01)
- A61B 5/0205* (2006.01)
- A61B 5/021* (2006.01)
- A61B 5/08* (2006.01)
- A61B 5/1455* (2006.01)
- A61M 5/172* (2006.01)
- (52) **U.S. Cl.**
- CPC *A61M16/0051* (2013.01); *G06F 19/3406* (2013.01); *A61B 5/021* (2013.01); *A61B 5/02055* (2013.01); *A61B 5/0816* (2013.01); *A61B 5/14551* (2013.01); *A61B 5/4821* (2013.01); *A61B 5/4836* (2013.01); *A61B 2560/0214* (2013.01); *A61B 2562/08* (2013.01); *A61B 2562/227* (2013.01); *A61M 5/172* (2013.01); *A61M 2205/18* (2013.01); *A61M 2205/3368* (2013.01); *A61M 2205/3375* (2013.01); *A61M 2205/3561* (2013.01); *A61M 2205/3569* (2013.01); *A61M 2205/3584* (2013.01); *A61M 2205/3592* (2013.01); *A61M 2205/505* (2013.01); *A61M 2209/086* (2013.01); *A61M 2230/04* (2013.01); *A61M 2230/10* (2013.01); *A61M 2230/201* (2013.01); *A61M 2230/205* (2013.01); *A61M 2230/208* (2013.01); *A61M 2230/30* (2013.01); *A61M 2230/42* (2013.01); *A61M 2230/50* (2013.01)
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- 3,978,849 A 9/1976 Geneen
- 4,108,166 A 8/1978 Schmid
- 4,231,354 A 11/1980 Kurtz et al.
- 4,589,415 A 5/1986 Haaga
- 4,662,378 A 5/1987 Thomis
- 4,838,275 A 6/1989 Lee
- 4,852,570 A 8/1989 Levine
- 4,960,128 A 10/1990 Gordon et al.
- 4,964,408 A 10/1990 Hink et al.
- 5,041,187 A 8/1991 Hink et al.
- 5,069,213 A 12/1991 Polczynski
- 5,092,340 A 3/1992 Yamaguchi et al.
- 5,140,519 A 8/1992 Friesdorf et al.
- 5,159,932 A 11/1992 Zanetti et al.
- 5,161,539 A 11/1992 Evans et al.
- 5,163,438 A 11/1992 Gordon et al.
- 5,262,944 A 11/1993 Weisner et al.
- 5,277,189 A 1/1994 Jacobs
- 5,278,627 A 1/1994 Aoyagi et al.
- 5,282,474 A 2/1994 Valdes Sosa et al.
- 5,296,688 A 3/1994 Hamilton et al.
- 5,318,037 A 6/1994 Evans et al.
- 5,319,355 A 6/1994 Russek
- 5,331,549 A 7/1994 Crawford, Jr.
- 5,333,106 A 7/1994 Lanpher et al.
- 5,337,744 A 8/1994 Branigan
- 5,341,805 A 8/1994 Stavridi et al.
- 5,348,008 A 9/1994 Bornn et al.
- 5,358,519 A 10/1994 Grandjean
- D353,195 S 12/1994 Savage et al.
- D353,196 S 12/1994 Savage et al.
- 5,375,599 A 12/1994 Shimizu
- 5,375,604 A * 12/1994 Kelly A61B 5/0404 600/483
- 5,377,676 A 1/1995 Vari et al.
- 5,400,794 A 3/1995 Gorman
- 5,416,695 A 5/1995 Stutman et al.
- D359,546 S 6/1995 Savage et al.
- 5,431,170 A 7/1995 Mathews
- 5,434,611 A 7/1995 Tamura
- D361,840 S 8/1995 Savage et al.
- D362,063 S 9/1995 Savage et al.
- 5,452,717 A 9/1995 Branigan et al.
- D363,120 S 10/1995 Savage et al.
- 5,456,252 A 10/1995 Vari et al.
- 5,479,934 A 1/1996 Imran
- 5,482,036 A 1/1996 Diab et al.
- 5,483,968 A 1/1996 Adam et al.
- 5,490,505 A 2/1996 Diab et al.
- 5,494,041 A 2/1996 Wilk
- 5,494,043 A 2/1996 O'Sullivan et al.
- 5,503,149 A 4/1996 Beavin
- 5,505,202 A 4/1996 Mogi et al.
- 5,533,511 A 7/1996 Kaspari et al.
- 5,534,851 A 7/1996 Russek
- 5,544,649 A 8/1996 David et al.
- 5,553,609 A 9/1996 Chen et al.
- 5,558,638 A 9/1996 Evers et al.
- 5,561,275 A 10/1996 Savage et al.
- 5,562,002 A 10/1996 Lalin
- 5,566,676 A 10/1996 Rosenfeldt et al.
- 5,576,952 A 11/1996 Stutman et al.
- 5,579,001 A 11/1996 Dempsey et al.
- 5,590,649 A 1/1997 Caro et al.
- 5,602,924 A 2/1997 Durand et al.
- 5,619,991 A 4/1997 Sloane
- 5,632,272 A 5/1997 Diab et al.
- 5,638,816 A 6/1997 Kiani-Azarbayjany et al.
- 5,638,818 A 6/1997 Diab et al.
- 5,640,967 A 6/1997 Fine et al.
- 5,645,440 A 7/1997 Tobler et al.
- 5,685,299 A 11/1997 Diab et al.
- 5,685,314 A 11/1997 Geheb et al.
- 5,687,717 A 11/1997 Halpern et al.
- 5,694,020 A 12/1997 Lang
- 5,724,580 A 3/1998 Levin et al.
- 5,724,983 A 3/1998 Selker et al.
- 5,725,308 A 3/1998 Smith et al.
- 5,734,739 A 3/1998 Sheehan et al.
- D393,830 S 4/1998 Tobler et al.
- 5,743,262 A 4/1998 Lepper, Jr. et al.
- 5,758,079 A 5/1998 Ludwig et al.
- 5,758,644 A 6/1998 Diab et al.
- 5,760,910 A 6/1998 Lepper, Jr. et al.
- 5,769,785 A 6/1998 Diab et al.
- 5,772,585 A 6/1998 Lavin et al.
- 5,782,757 A 7/1998 Diab et al.
- 5,785,659 A 7/1998 Caro et al.
- 5,791,347 A 8/1998 Flaherty et al.
- 5,801,637 A 9/1998 Lomholt
- 5,810,734 A 9/1998 Caro et al.
- 5,822,544 A 10/1998 Chaco et al.
- 5,822,546 A 10/1998 George
- 5,823,950 A 10/1998 Diab et al.
- 5,830,131 A 11/1998 Caro et al.
- 5,833,618 A 11/1998 Caro et al.
- 5,855,550 A 1/1999 Lai et al.
- 5,860,919 A 1/1999 Kiani-Azarbayjany et al.
- 5,890,929 A 4/1999 Mills et al.
- 5,904,654 A 5/1999 Wohltmann et al.
- 5,910,139 A 6/1999 Cochran et al.
- 5,919,134 A 7/1999 Diab
- 5,921,920 A 7/1999 Marshall et al.
- 5,924,074 A 7/1999 Evans
- 5,931,160 A 8/1999 Gilmore et al.
- 5,934,925 A 8/1999 Tobler et al.
- 5,940,182 A 8/1999 Lepper, Jr. et al.
- 5,942,986 A 8/1999 Shabot et al.
- 5,987,519 A 11/1999 Peifer et al.
- 5,995,855 A 11/1999 Kiani et al.
- 5,997,343 A 12/1999 Mills et al.
- 6,002,952 A 12/1999 Diab et al.
- 6,011,986 A 1/2000 Diab et al.
- 6,018,673 A 1/2000 Chin et al.
- 6,024,699 A 2/2000 Surwit et al.
- 6,027,452 A 2/2000 Flaherty et al.
- 6,032,678 A 3/2000 Rottem
- 6,035,230 A 3/2000 Kang
- 6,036,642 A 3/2000 Diab et al.
- 6,045,509 A 4/2000 Caro et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,067,462 A	5/2000	Diab et al.	6,544,174 B2	4/2003	West et al.
6,081,735 A	6/2000	Diab et al.	6,551,243 B2	4/2003	Bocionek et al.
6,088,607 A	7/2000	Diab et al.	6,580,086 B1	6/2003	Schulz et al.
6,093,146 A	7/2000	Filangeri	6,584,336 B1	6/2003	Ali et al.
6,101,478 A	8/2000	Brown	6,595,316 B2	7/2003	Cybulski et al.
6,106,463 A	8/2000	Wilk	6,597,932 B2	7/2003	Tian et al.
6,110,522 A	8/2000	Lepper, Jr. et al.	6,597,933 B2	7/2003	Kiani et al.
6,124,597 A	9/2000	Shehada	6,606,511 B1	8/2003	Ali et al.
6,128,521 A	10/2000	Marro et al.	6,616,606 B1	9/2003	Peterson et al.
6,129,675 A	10/2000	Jay	6,632,181 B2	10/2003	Flaherty et al.
6,132,218 A	10/2000	Benja-Athon	6,639,668 B1	10/2003	Trepagnier
6,139,494 A	10/2000	Cairnes	6,640,116 B2	10/2003	Diab
6,144,868 A	11/2000	Parker	6,641,533 B2	11/2003	Causey et al.
6,151,516 A	11/2000	Kiani-Azarbayjany et al.	6,643,530 B2	11/2003	Diab et al.
6,152,754 A	11/2000	Gerhardt et al.	6,650,917 B2	11/2003	Diab et al.
6,157,850 A	12/2000	Diab et al.	6,650,939 B2	11/2003	Takpke, II et al.
6,165,005 A	12/2000	Mills et al.	6,654,624 B2	11/2003	Diab et al.
6,167,258 A	12/2000	Schmidt et al.	6,658,276 B2	12/2003	Kiani et al.
6,168,563 B1	1/2001	Brown	6,661,161 B1	12/2003	Lanzo et al.
6,171,237 B1	1/2001	Avitall et al.	6,671,531 B2	12/2003	Al-Ali et al.
6,183,417 B1	2/2001	Geheb et al.	6,678,543 B2	1/2004	Diab et al.
6,184,521 B1	2/2001	Coffin, IV et al.	6,684,090 B2	1/2004	Ali et al.
6,185,448 B1	2/2001	Borovsky	6,684,091 B2	1/2004	Parker
6,195,576 B1	2/2001	John	6,694,180 B1	2/2004	Boesen
6,206,830 B1	3/2001	Diab et al.	6,697,656 B1	2/2004	Al-Ali
6,221,012 B1	4/2001	Maschke et al.	6,697,657 B1	2/2004	Shehada et al.
6,224,553 B1	5/2001	Nevo	6,697,658 B2	2/2004	Al-Ali
6,229,856 B1	5/2001	Diab et al.	RE38,476 E	3/2004	Diab et al.
6,230,142 B1	5/2001	Benigno et al.	6,699,194 B1	3/2004	Diab et al.
6,232,609 B1	5/2001	Snyder et al.	6,714,804 B2	3/2004	Al-Ali et al.
6,236,872 B1	5/2001	Diab et al.	RE38,492 E	4/2004	Diab et al.
6,241,683 B1	6/2001	Macklem et al.	6,719,694 B2	4/2004	Weng et al.
6,253,097 B1	6/2001	Aronow et al.	6,721,582 B2	4/2004	Trepagnier et al.
6,256,523 B1	7/2001	Diab et al.	6,721,585 B1	4/2004	Parker
6,263,222 B1	7/2001	Diab et al.	6,725,075 B2	4/2004	Al-Ali
6,267,723 B1	7/2001	Matsumura et al.	6,728,560 B2	4/2004	Kollias et al.
6,269,262 B1	7/2001	Kandori et al.	6,735,459 B2	5/2004	Parker
6,278,522 B1	8/2001	Lepper, Jr. et al.	6,745,060 B2	6/2004	Diab et al.
6,280,213 B1	8/2001	Tobler et al.	6,751,492 B2	6/2004	Ben-haim
6,285,896 B1	9/2001	Tobler et al.	6,760,607 B2	7/2004	Al-Ali
6,301,493 B1	10/2001	Marro et al.	6,770,028 B1	8/2004	Ali et al.
6,312,378 B1	11/2001	Bardy	6,771,994 B2	8/2004	Kiani et al.
6,317,627 B1	11/2001	Ennen et al.	6,790,178 B1	9/2004	Mault et al.
6,321,100 B1	11/2001	Parker	6,792,300 B1	9/2004	Diab et al.
6,322,502 B1	11/2001	Schoenberg et al.	6,795,724 B2	9/2004	Hogan
6,325,761 B1	12/2001	Jay	6,804,656 B1	10/2004	Rosenfeld
6,329,139 B1	12/2001	Nova et al.	6,807,050 B1	10/2004	Whitehorn et al.
6,334,065 B1	12/2001	Al-Ali et al.	6,813,511 B2	11/2004	Diab et al.
6,338,039 B1	1/2002	Lonski et al.	6,816,741 B2	11/2004	Diab
6,343,224 B1	1/2002	Parker	6,817,979 B2	11/2004	Nihtila et al.
6,349,228 B1	2/2002	Kiani et al.	6,822,564 B2	11/2004	Al-Ali
6,354,235 B1	3/2002	Davies	6,826,419 B2	11/2004	Diab et al.
6,360,114 B1	3/2002	Diab et al.	6,830,711 B2	12/2004	Mills et al.
6,364,834 B1	4/2002	Reuss et al.	6,837,848 B2	1/2005	Bonner et al.
6,368,283 B1	4/2002	Xu et al.	6,841,535 B2	1/2005	Divita et al.
6,371,921 B1	4/2002	Caro et al.	6,850,787 B2	2/2005	Weber et al.
6,377,829 B1	4/2002	Al-Ali	6,850,788 B2	2/2005	Al-Ali
6,385,476 B1	5/2002	Osadchy et al.	6,852,083 B2	2/2005	Caro et al.
6,385,589 B1	5/2002	Trusheim et al.	6,855,112 B2	2/2005	Kao et al.
6,388,240 B2	5/2002	Schulz et al.	6,860,266 B2	3/2005	Blike
6,397,091 B2	5/2002	Diab et al.	6,861,639 B2	3/2005	Al-Ali
6,430,437 B1	8/2002	Marro	6,897,788 B2	5/2005	Khair et al.
6,430,525 B1	8/2002	Weber et al.	6,898,452 B2	5/2005	Al-Ali et al.
6,463,311 B1	10/2002	Diab	6,907,237 B1	6/2005	Dorenbosch et al.
6,470,199 B1	10/2002	Kopotic et al.	6,915,149 B2	7/2005	Ben-haim
6,470,893 B1	10/2002	Boesen	6,920,345 B2	7/2005	Al-Ali et al.
6,501,975 B2	12/2002	Diab et al.	6,931,268 B1	8/2005	Kiani-Azarbayjany et al.
6,505,059 B1	1/2003	Kollias et al.	6,934,570 B2	8/2005	Kiani et al.
6,515,273 B2	2/2003	Al-Ali	6,939,305 B2	9/2005	Flaherty et al.
6,519,487 B1	2/2003	Parker	6,943,348 B1	9/2005	Coffin, IV
6,524,240 B1	2/2003	Thede	6,950,687 B2	9/2005	Al-Ali
6,525,386 B1	2/2003	Mills et al.	6,952,340 B2	10/2005	Son et al.
6,526,300 B1	2/2003	Kiani et al.	6,961,598 B2	11/2005	Diab
6,541,756 B2	4/2003	Schulz et al.	6,970,792 B1	11/2005	Diab
6,542,764 B1	4/2003	Al-Ali et al.	6,979,812 B2	12/2005	Al-Ali
			6,980,419 B2	12/2005	Smith et al.
			6,983,179 B2	1/2006	Ben-haim
			6,985,764 B2	1/2006	Mason et al.
			6,988,989 B2	1/2006	Weiner et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,990,087 B2	1/2006	Rao et al.	7,377,899 B2	5/2008	Weber et al.
6,993,371 B2	1/2006	Kiani et al.	7,382,247 B2	6/2008	Welch et al.
6,996,427 B2	2/2006	Ali et al.	7,383,070 B2	6/2008	Diab et al.
6,997,884 B2	2/2006	Ulmsten	7,395,216 B2	7/2008	Rosenfeld
6,999,904 B2	2/2006	Weber et al.	7,411,509 B2	8/2008	Rosenfeld
7,003,338 B2	2/2006	Weber et al.	7,413,546 B2	8/2008	Agutter et al.
7,003,339 B2	2/2006	Diab et al.	7,415,297 B2	8/2008	Al-Ali et al.
7,015,451 B2	3/2006	Dalke et al.	7,419,483 B2	9/2008	Shehada
7,024,233 B2	4/2006	Ali et al.	7,428,432 B2	9/2008	Ali et al.
7,025,729 B2	4/2006	De Chazal et al.	7,433,827 B2	10/2008	Rosenfeld
7,027,849 B2	4/2006	Al-Ali	7,438,683 B2	10/2008	Al-Ali et al.
7,030,749 B2	4/2006	Al-Ali	7,439,856 B2	10/2008	Weiner et al.
7,033,761 B2	4/2006	Shafer	7,440,787 B2	10/2008	Diab
7,035,686 B2	4/2006	Hogan	7,454,240 B2	11/2008	Diab et al.
7,039,449 B2	5/2006	Al-Ali	7,454,359 B2	11/2008	Rosenfeld
7,041,060 B2	5/2006	Flaherty et al.	7,454,360 B2	11/2008	Rosenfeld
7,044,918 B2	5/2006	Diab	7,462,151 B2	12/2008	Childre et al.
7,063,666 B2	6/2006	Weng et al.	7,467,002 B2	12/2008	Weber et al.
7,067,893 B2	6/2006	Mills et al.	7,467,094 B2	12/2008	Rosenfeld
7,079,035 B2	7/2006	Bock et al.	7,469,157 B2	12/2008	Diab et al.
7,096,052 B2	8/2006	Mason et al.	7,471,969 B2	12/2008	Diab et al.
7,096,054 B2	8/2006	Abdul-Hafiz et al.	7,471,971 B2	12/2008	Diab et al.
7,132,641 B2	11/2006	Schulz et al.	7,475,019 B2	1/2009	Rosenfeld
7,142,901 B2	11/2006	Kiani et al.	7,483,729 B2	1/2009	Al-Ali et al.
7,149,561 B2	12/2006	Diab	7,483,730 B2	1/2009	Diab et al.
7,186,966 B2	3/2007	Al-Ali	7,489,250 B2	2/2009	Bock et al.
7,188,621 B2	3/2007	DeVries et al.	7,489,958 B2	2/2009	Diab et al.
7,190,261 B2	3/2007	Al-Ali	7,496,391 B2	2/2009	Diab et al.
7,215,984 B2	5/2007	Diab	7,496,393 B2	2/2009	Diab et al.
7,215,986 B2	5/2007	Diab	D587,657 S	3/2009	Al-Ali et al.
7,221,971 B2	5/2007	Diab	7,497,828 B1	3/2009	Wilk et al.
7,225,006 B2	5/2007	Al-Ali et al.	7,499,741 B2	3/2009	Diab et al.
7,225,007 B2	5/2007	Al-Ali	7,499,835 B2	3/2009	Weber et al.
RE39,672 E	6/2007	Shehada et al.	7,500,950 B2	3/2009	Al-Ali et al.
7,229,415 B2	6/2007	Schwartz	7,509,154 B2	3/2009	Diab et al.
7,239,905 B2	7/2007	Kiani-Azarbayjany et al.	7,509,494 B2	3/2009	Al-Ali
7,241,287 B2	7/2007	Shehada et al.	7,510,849 B2	3/2009	Schurman et al.
7,244,251 B2	7/2007	Shehada et al.	7,526,328 B2	4/2009	Diab et al.
7,245,953 B1	7/2007	Parker	7,530,942 B1	5/2009	Diab
7,252,659 B2	8/2007	Shehada et al.	7,530,949 B2	5/2009	Al Ali et al.
7,254,429 B2	8/2007	Schurman et al.	7,530,955 B2	5/2009	Diab et al.
7,254,431 B2	8/2007	Al-Ali	7,549,961 B1	6/2009	Hwang
7,254,433 B2	8/2007	Diab et al.	7,551,717 B2	6/2009	Tomé et al.
7,254,434 B2	8/2007	Schulz et al.	7,559,520 B2	7/2009	Quijano et al.
7,256,708 B2	8/2007	Rosenfeld	7,563,110 B2	7/2009	Al-Ali et al.
7,264,616 B2	9/2007	Shehada et al.	7,577,475 B2	8/2009	Cosentino et al.
7,267,671 B2	9/2007	Shehada et al.	7,590,950 B2	9/2009	Collins et al.
7,272,425 B2	9/2007	Al-Ali	7,596,398 B2	9/2009	Al-Ali et al.
7,274,955 B2	9/2007	Kiani et al.	7,597,665 B2	10/2009	Wilk et al.
D554,263 S	10/2007	Al-Ali	7,612,999 B2	11/2009	Clark et al.
7,280,858 B2	10/2007	Al-Ali et al.	7,618,375 B2	11/2009	Flaherty
7,285,090 B2	10/2007	Stivorice	D606,659 S	12/2009	Kiani et al.
7,289,835 B2	10/2007	Mansfield et al.	7,639,145 B2	12/2009	Lawson et al.
7,292,883 B2	11/2007	De Felice et al.	7,647,083 B2	1/2010	Al-Ali et al.
7,295,866 B2	11/2007	Al-Ali	7,650,291 B2	1/2010	Rosenfeld
7,307,543 B2	12/2007	Rosenfeld	D609,193 S	2/2010	Al-Ali et al.
7,313,423 B2	12/2007	Griffin et al.	7,654,966 B2	2/2010	Westinskow et al.
7,314,446 B2	1/2008	Byrd et al.	7,684,845 B2	3/2010	Juan
7,315,825 B2	1/2008	Rosenfeld	7,689,437 B1	3/2010	Teller et al.
7,321,862 B2	1/2008	Rosenfeld	RE41,236 E	4/2010	Seely
7,322,971 B2	1/2008	Shehada et al.	D614,305 S	4/2010	Al-Ali et al.
7,328,053 B1	2/2008	Diab et al.	7,693,697 B2	4/2010	Westinskow et al.
7,332,784 B2	2/2008	Mills et al.	RE41,317 E	5/2010	Parker
7,340,287 B2	3/2008	Mason et al.	7,729,733 B2	6/2010	Al-Ali et al.
7,341,559 B2	3/2008	Schulz et al.	7,734,320 B2	6/2010	Al-Ali
7,343,186 B2	3/2008	Lamego et al.	7,736,318 B2	6/2010	Cosentino et al.
D566,282 S	4/2008	Al Ali et al.	7,761,127 B2	7/2010	Al-Ali et al.
7,355,512 B1	4/2008	Al-Ali	7,761,128 B2	7/2010	Al-Ali et al.
7,356,178 B2	4/2008	Ziel et al.	7,763,420 B2	7/2010	Stritzker et al.
7,356,365 B2	4/2008	Schurman	7,764,982 B2	7/2010	Dalke et al.
7,371,981 B2	5/2008	Abdul-Hafiz	D621,516 S	8/2010	Kiani et al.
7,373,193 B2	5/2008	Al-Ali et al.	7,766,818 B2	8/2010	Iketani et al.
7,373,194 B2	5/2008	Weber et al.	7,774,060 B2	8/2010	Westenskow et al.
7,376,453 B1	5/2008	Diab et al.	7,778,851 B2	8/2010	Schoenberg et al.
7,377,794 B2	5/2008	Al Ali et al.	7,791,155 B2	9/2010	Diab
			7,794,407 B2	9/2010	Rothenberg
			7,801,581 B2	9/2010	Diab
			7,820,184 B2	10/2010	Stritzker et al.
			7,822,452 B2	10/2010	Schurman et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

RE41,912 E	11/2010	Parker	8,203,438 B2	6/2012	Kiani et al.
7,831,450 B2	11/2010	Schoenberg	8,203,704 B2	6/2012	Merritt et al.
7,841,986 B2	11/2010	He et al.	8,204,566 B2	6/2012	Schurman et al.
7,844,313 B2	11/2010	Kiani et al.	8,206,312 B2	6/2012	Farquhar
7,844,314 B2	11/2010	Al-Ali	8,219,172 B2	7/2012	Schurman et al.
7,844,315 B2	11/2010	Al-Ali	8,224,411 B2	7/2012	Al-Ali et al.
7,848,935 B2	12/2010	Gotlib	8,228,181 B2	7/2012	Al-Ali
7,858,322 B2	12/2010	Tymianski et al.	8,229,533 B2	7/2012	Diab et al.
7,865,222 B2	1/2011	Weber et al.	8,233,955 B2	7/2012	Al-Ali et al.
7,865,232 B1	1/2011	Krishnaswamy et al.	8,235,907 B2	8/2012	Wilk et al.
7,873,497 B2	1/2011	Weber et al.	8,239,780 B2	8/2012	Manetta et al.
7,880,606 B2	2/2011	Al-Ali	8,241,213 B2	8/2012	Lynn et al.
7,880,626 B2	2/2011	Al-Ali et al.	8,244,325 B2	8/2012	Al-Ali et al.
7,890,156 B2	2/2011	Ooi et al.	8,249,815 B2	8/2012	Taylor
7,891,355 B2	2/2011	Al-Ali et al.	8,255,026 B1	8/2012	Al-Ali
7,894,868 B2	2/2011	Al-Ali et al.	8,255,027 B2	8/2012	Al-Ali et al.
7,899,507 B2	3/2011	Al-Ali et al.	8,255,028 B2	8/2012	Al-Ali et al.
7,899,518 B2	3/2011	Trepagnier et al.	8,260,577 B2	9/2012	Weber et al.
7,904,132 B2	3/2011	Weber et al.	8,265,723 B1	9/2012	McHale et al.
7,909,772 B2	3/2011	Popov et al.	8,274,360 B2	9/2012	Sampath et al.
7,910,875 B2	3/2011	Al-Ali	8,294,716 B2	10/2012	Lord et al.
7,914,514 B2	3/2011	Calderon	8,301,217 B2	10/2012	Al-Ali et al.
7,919,713 B2	4/2011	Al-Ali et al.	8,306,596 B2	11/2012	Schurman et al.
7,937,128 B2	5/2011	Al-Ali	8,310,336 B2	11/2012	Muhsin et al.
7,937,129 B2	5/2011	Mason et al.	8,311,747 B2	11/2012	Taylor
7,937,130 B2	5/2011	Diab et al.	8,311,748 B2	11/2012	Taylor et al.
7,941,199 B2	5/2011	Kiani	8,315,683 B2	11/2012	Al-Ali et al.
7,951,086 B2	5/2011	Flaherty et al.	8,315,812 B2	11/2012	Taylor
7,957,780 B2	6/2011	Lamego et al.	8,315,813 B2	11/2012	Taylor et al.
7,962,188 B2 *	6/2011	Kiani et al. 600/300	8,315,814 B2	11/2012	Taylor et al.
7,962,190 B1	6/2011	Diab et al.	8,321,150 B2	11/2012	Taylor
7,963,927 B2	6/2011	Kelleher et al.	RE43,860 E	12/2012	Parker
7,967,749 B2	6/2011	Hutchinson et al.	8,326,649 B2	12/2012	Rosenfeld
7,976,472 B2	7/2011	Kiani	8,328,793 B2 *	12/2012	Birkenbach A61B 1/00039 600/101
7,988,637 B2	8/2011	Diab	8,337,403 B2	12/2012	Al-Ali et al.
7,988,639 B2	8/2011	Starks	8,346,330 B2	1/2013	Lamego
7,990,382 B2	8/2011	Kiani	8,353,842 B2	1/2013	Al-Ali et al.
7,991,446 B2	8/2011	Al-Ali et al.	8,355,766 B2	1/2013	MacNeish, III et al.
7,991,463 B2	8/2011	Kelleher et al.	8,359,080 B2	1/2013	Diab et al.
7,991,625 B2	8/2011	Rosenfeld	8,360,936 B2	1/2013	Dibenedetto et al.
8,000,761 B2	8/2011	Al-Ali	8,364,223 B2	1/2013	Al-Ali et al.
8,008,088 B2	8/2011	Bellott et al.	8,364,226 B2	1/2013	Diab et al.
RE42,753 E	9/2011	Kiani-Azarbayjany et al.	8,374,665 B2	2/2013	Lamego
8,019,400 B2	9/2011	Diab et al.	8,385,995 B2	2/2013	Al-Ali et al.
8,027,846 B2	9/2011	Schoenberg	8,385,996 B2	2/2013	Smith et al.
8,028,701 B2	10/2011	Al-Ali et al.	8,388,353 B2	3/2013	Kiani et al.
8,029,765 B2	10/2011	Bellott et al.	8,399,822 B2	3/2013	Al-Ali
8,033,996 B2	10/2011	Behar	8,401,602 B2	3/2013	Kiani
8,036,727 B2	10/2011	Schurman et al.	8,401,874 B2	3/2013	Rosenfeld
8,036,728 B2	10/2011	Diab et al.	8,405,608 B2	3/2013	Al-Ali et al.
8,036,736 B2	10/2011	Snyder et al.	8,414,499 B2	4/2013	Al-Ali et al.
8,038,625 B2	10/2011	Afonso et al.	8,418,524 B2	4/2013	Al-Ali
8,046,040 B2	10/2011	Ali et al.	8,423,106 B2	4/2013	Lamego et al.
8,046,041 B2	10/2011	Diab et al.	8,428,967 B2	4/2013	Olsen et al.
8,046,042 B2	10/2011	Diab et al.	8,430,817 B1	4/2013	Al-Ali et al.
8,048,040 B2	11/2011	Kiani	8,437,825 B2	5/2013	Dalvi et al.
8,050,728 B2	11/2011	Al-Ali et al.	8,455,290 B2	6/2013	Siskavich
8,068,104 B2	11/2011	Rampersad	8,457,703 B2	6/2013	Al-Ali
8,073,707 B2	12/2011	Teller et al.	8,457,707 B2	6/2013	Kiani
RE43,169 E	2/2012	Parker	8,463,349 B2	6/2013	Diab et al.
8,118,620 B2	2/2012	Al-Ali et al.	8,466,286 B2	6/2013	Bellot et al.
8,126,528 B2	2/2012	Diab et al.	8,471,713 B2	6/2013	Poeze et al.
8,128,572 B2	3/2012	Diab et al.	8,473,020 B2	6/2013	Kiani et al.
8,130,105 B2	3/2012	Al-Ali et al.	8,483,787 B2	7/2013	Al-Ali et al.
8,145,287 B2	3/2012	Diab et al.	8,489,167 B2 *	7/2013	Buxton G06F 19/3412 600/324
8,150,487 B2	4/2012	Diab et al.	8,489,364 B2	7/2013	Weber et al.
8,170,887 B2	5/2012	Rosenfeld	8,498,684 B2	7/2013	Weber et al.
8,175,672 B2	5/2012	Parker	8,504,128 B2	8/2013	Blank et al.
8,175,895 B2	5/2012	Rosenfeld	8,509,867 B2	8/2013	Workman et al.
8,180,420 B2	5/2012	Diab et al.	8,515,509 B2	8/2013	Bruinsma et al.
8,182,443 B1	5/2012	Kiani	8,523,781 B2	9/2013	Al-Ali
8,185,180 B2	5/2012	Diab et al.	8,529,301 B2	9/2013	Al-Ali et al.
8,190,223 B2 *	5/2012	Al-Ali A61B 5/14552 600/323	8,532,727 B2	9/2013	Ali et al.
8,190,227 B2	5/2012	Diab et al.	8,532,728 B2	9/2013	Diab et al.
			D692,145 S	10/2013	Al-Ali et al.
			8,547,209 B2	10/2013	Kiani et al.
			8,548,548 B2	10/2013	Al-Ali

(56)

References Cited

U.S. PATENT DOCUMENTS

8,548,549 B2	10/2013	Schurman et al.	8,878,888 B2	11/2014	Rosenfeld	
8,548,550 B2	10/2013	Al-Ali et al.	8,886,271 B2	11/2014	Kiani et al.	
8,560,032 B2	10/2013	Al-Ali et al.	8,888,539 B2	11/2014	Al-Ali et al.	
8,560,034 B1	10/2013	Diab et al.	8,888,708 B2	11/2014	Diab et al.	
8,570,167 B2	10/2013	Al-Ali	8,892,180 B2	11/2014	Weber et al.	
8,570,503 B2	10/2013	Vo et al.	8,897,847 B2	11/2014	Al-Ali	
8,571,617 B2	10/2013	Reichgott et al.	8,909,310 B2	12/2014	Lamego et al.	
8,571,618 B1	10/2013	Lamego et al.	8,956,292 B2 *	2/2015	Wekell	G06T 11/206 600/301
8,571,619 B2	10/2013	Al-Ali et al.	9,113,831 B2	8/2015	Al-Ali	
8,577,431 B2	11/2013	Lamego et al.	9,113,832 B2	8/2015	Al-Ali	
8,579,813 B2	11/2013	Causey	9,153,112 B1	10/2015	Kiani et al.	
8,581,732 B2	11/2013	Al-Ali et al.	9,161,696 B2	10/2015	Al-Ali et al.	
8,584,345 B2	11/2013	Al-Ali et al.	2001/0011355 A1	8/2001	Kawai	
8,588,880 B2	11/2013	Abdul-Hafiz et al.	2001/0031922 A1	10/2001	Weng et al.	
8,588,924 B2	11/2013	Dion	2001/0046366 A1	11/2001	Susskind	
8,600,467 B2	12/2013	Al-Ali et al.	2002/0045836 A1	4/2002	Alkawwas	
8,600,777 B2	12/2013	Schoenberg	2002/0052311 A1	5/2002	Solomon et al.	
8,606,342 B2	12/2013	Diab	2002/0063690 A1	5/2002	Chung et al.	
8,620,678 B2	12/2013	Gotlib	2002/0140675 A1	10/2002	Ali et al.	
8,626,255 B2	1/2014	Al-Ali et al.	2002/0177758 A1	11/2002	Schoenberg	
8,630,691 B2	1/2014	Lamego et al.	2002/0198445 A1	12/2002	Dominguez et al.	
8,634,889 B2	1/2014	Al-Ali et al.	2003/0052787 A1	3/2003	Zerhusen et al.	
8,641,631 B2	2/2014	Sierra et al.	2003/0058838 A1	3/2003	Wengrovitz	
8,652,060 B2	2/2014	Al-Ali	2003/0158466 A1 *	8/2003	Lynn et al.	600/300
8,663,107 B2	3/2014	Kiani	2004/0013647 A1	1/2004	Solomon et al.	
8,666,468 B1	3/2014	Al-Ali	2004/0122787 A1	6/2004	Avinash et al.	
8,667,967 B2	3/2014	Al-Ali et al.	2004/0126007 A1	7/2004	Ziel et al.	
8,670,811 B2	3/2014	O'Reilly	2004/0147818 A1	7/2004	Levy et al.	
8,670,814 B2	3/2014	Diab et al.	2004/0179332 A1	9/2004	Smith et al.	
8,676,286 B2	3/2014	Weber et al.	2004/0186357 A1	9/2004	Soderberg et al.	
8,682,407 B2	3/2014	Al-Ali	2004/0230118 A1	11/2004	Shehada et al.	
RE44,823 E	4/2014	Parker	2004/0230132 A1	11/2004	Shehada et al.	
RE44,875 E	4/2014	Kiani et al.	2004/0230179 A1	11/2004	Shehada et al.	
8,690,799 B2	4/2014	Telfort et al.	2004/0243017 A1	12/2004	Causevic	
8,700,112 B2	4/2014	Kiani	2004/0254431 A1	12/2004	Shehada et al.	
8,702,627 B2	4/2014	Telfort et al.	2004/0254432 A1	12/2004	Shehada et al.	
8,706,179 B2	4/2014	Parker	2005/0020918 A1	1/2005	Wilk et al.	
8,712,494 B1	4/2014	MacNeish, III et al.	2005/0038332 A1	2/2005	Saidara et al.	
8,715,206 B2	5/2014	Telfort et al.	2005/0038680 A1	2/2005	McMahon	
8,718,735 B2	5/2014	Lamego et al.	2005/0065417 A1	3/2005	Ali et al.	
8,718,737 B2	5/2014	Diab et al.	2005/0080336 A1	4/2005	Byrd et al.	
8,718,738 B2	5/2014	Blank et al.	2005/0096542 A1	5/2005	Weng et al.	
8,720,249 B2	5/2014	Al-Ali	2005/0113653 A1	5/2005	Fox et al.	
8,721,541 B2	5/2014	Al-Ali et al.	2005/0125256 A1	6/2005	Schoenberg	
8,721,542 B2	5/2014	Al-Ali et al.	2005/0164933 A1	7/2005	Tymianski et al.	
8,723,677 B1	5/2014	Kiani	2005/0191294 A1	9/2005	Arap et al.	
8,740,792 B1	6/2014	Kiani et al.	2005/0277872 A1	12/2005	Colby et al.	
8,754,776 B2	6/2014	Poeze et al.	2006/0058647 A1	3/2006	Strommer et al.	
8,755,535 B2	6/2014	Telfort et al.	2006/0089543 A1	4/2006	Kim et al.	
8,755,856 B2	6/2014	Diab et al.	2006/0094936 A1 *	5/2006	Russ	600/300
8,755,872 B1	6/2014	Marinow	2006/0149393 A1	7/2006	Calderon	
8,761,850 B2	6/2014	Lamego	2006/0155175 A1	7/2006	Ogino et al.	
8,764,671 B2	7/2014	Kiani	2006/0200009 A1 *	9/2006	Wekell	A61B 5/7275 600/300
8,768,423 B2	7/2014	Shakespeare et al.	2006/0217684 A1	9/2006	Shehada et al.	
8,771,204 B2	7/2014	Telfort et al.	2006/0217685 A1	9/2006	Shehada et al.	
8,777,634 B2	7/2014	Kiani et al.	2006/0224413 A1	10/2006	Kim et al.	
8,781,543 B2	7/2014	Diab et al.	2006/0235300 A1	10/2006	Weng et al.	
8,781,544 B2	7/2014	Al-Ali et al.	2006/0253042 A1	11/2006	Stahmann et al.	
8,781,549 B2	7/2014	Al-Ali et al.	2007/0000490 A1	1/2007	DeVries et al.	
8,788,003 B2	7/2014	Schurman et al.	2007/0021675 A1	1/2007	Childre et al.	
8,790,268 B2	7/2014	Al-Ali	2007/0027368 A1	2/2007	Collins et al.	
8,801,613 B2	8/2014	Al-Ali et al.	2007/0032733 A1	2/2007	Burton et al.	
8,821,397 B2	9/2014	Al-Ali et al.	2007/0055116 A1	3/2007	Clark et al.	
8,821,415 B2	9/2014	Al-Ali et al.	2007/0055544 A1	3/2007	Jung et al.	
8,830,449 B1	9/2014	Lamego et al.	2007/0060798 A1	3/2007	Krupnik et al.	
8,831,700 B2	9/2014	Schurman et al.	2007/0088406 A1	4/2007	Bennett et al.	
8,840,549 B2	9/2014	Al-Ali	2007/0096897 A1	5/2007	Weiner	
8,847,740 B2	9/2014	Kiani et al.	2007/0118399 A1	5/2007	Avinash et al.	
8,849,365 B2	9/2014	Smith et al.	2007/0140475 A1	6/2007	Kurtock et al.	
8,852,094 B2 *	10/2014	Al-Ali	2007/0156033 A1	7/2007	Causey et al.	
			2007/0163589 A1	7/2007	DeVries et al.	
			2007/0185390 A1	8/2007	Perkins et al.	
			2007/0232941 A1	10/2007	Rabinovich	
8,852,994 B2	10/2014	Wojtczuk et al.	2007/0244724 A1	10/2007	Pendergast et al.	
8,868,147 B2	10/2014	Stippick et al.	2007/0254593 A1	11/2007	Jollota et al.	
8,868,150 B2	10/2014	Al-Ali et al.	2007/0255114 A1	11/2007	Ackermann et al.	
8,870,792 B2	10/2014	Al-Ali et al.	2007/0255116 A1	11/2007	Mehta et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0255250	A1	11/2007	Moberg	2011/0028809	A1	2/2011	Goodman
2008/0000479	A1	1/2008	Elaz et al.	2011/0046495	A1	2/2011	Osyпка
2008/0003200	A1	1/2008	Arap et al.	2011/0077473	A1*	3/2011	Lisogurski 600/301
2008/0021854	A1	1/2008	Jung et al.	2011/0077488	A1*	3/2011	Buxton et al. 600/324
2008/0033661	A1	2/2008	Syroid et al.	2011/0078596	A1*	3/2011	Rawlins et al. 715/764
2008/0053438	A1	3/2008	DeVries et al.	2011/0080294	A1	4/2011	Tanishima et al.
2008/0058657	A1	3/2008	Schwartz et al.	2011/0082711	A1	4/2011	Poeze et al.
2008/0090626	A1	4/2008	Griffin et al.	2011/0087084	A1	4/2011	Jeong et al.
2008/0091089	A1	4/2008	Guillory et al.	2011/0087117	A1	4/2011	Tremper et al.
2008/0091090	A1	4/2008	Guillory et al.	2011/0087756	A1	4/2011	Biondi
2008/0091471	A1	4/2008	Michon et al.	2011/0098583	A1	4/2011	Pandia et al.
2008/0097167	A1	4/2008	Yudkovitch et al.	2011/0105854	A1	5/2011	Kiani et al.
2008/0099366	A1	5/2008	Niemiec et al.	2011/0118573	A1	5/2011	Mckenna
2008/0108884	A1*	5/2008	Kiani 600/301	2011/0152629	A1*	6/2011	Eaton et al. 600/300
2008/0119412	A1	5/2008	Tymianski et al.	2011/0172967	A1	7/2011	Al-Ali et al.
2008/0138278	A1	6/2008	Scherz et al.	2011/0184252	A1	7/2011	Archer et al.
2008/0171919	A1	7/2008	Stivoric et al.	2011/0184253	A1	7/2011	Archer et al.
2008/0188795	A1*	8/2008	Katz et al. 604/66	2011/0208015	A1	8/2011	Welch et al.
2008/0194918	A1	8/2008	Kulik et al.	2011/0208018	A1	8/2011	Kiani
2008/0208912	A1	8/2008	Garibaldi	2011/0208073	A1	8/2011	Matsukawa et al.
2008/0221396	A1	9/2008	Garces et al.	2011/0209915	A1	9/2011	Telfort et al.
2008/0228077	A1	9/2008	Wilks et al.	2011/0212090	A1	9/2011	Pedersen et al.
2008/0275309	A1	11/2008	Stivoric et al.	2011/0213212	A1	9/2011	Al-Ali
2008/0281167	A1	11/2008	Soderberg et al.	2011/0227739	A1*	9/2011	Gilham et al. 340/573.1
2008/0281168	A1	11/2008	Gibson et al.	2011/0230733	A1	9/2011	Al-Ali
2008/0281181	A1	11/2008	Manziona et al.	2011/0237911	A1	9/2011	Lamego et al.
2008/0287751	A1	11/2008	Stivoric et al.	2011/0257544	A1	10/2011	Kaasinen et al.
2008/0292172	A1	11/2008	Assmann et al.	2011/0295094	A1	12/2011	Doyle
2008/0300020	A1	12/2008	Nishizawa et al.	2012/0004579	A1	1/2012	Luo et al.
2008/0319275	A1	12/2008	Chiu et al.	2012/0029304	A1*	2/2012	Medina et al. 600/300
2008/0319354	A1	12/2008	Bell et al.	2012/0059230	A1	3/2012	Teller et al.
2009/0005651	A1	1/2009	Ward et al.	2012/0059267	A1	3/2012	Lamego et al.
2009/0018808	A1	1/2009	Bronstein et al.	2012/0071771	A1	3/2012	Behar
2009/0024008	A1	1/2009	Brunner et al.	2012/0095778	A1*	4/2012	Gross G06Q 50/22 705/2
2009/0052623	A1	2/2009	Tome et al.	2012/0101353	A1	4/2012	Reggiardo et al.
2009/0054735	A1	2/2009	Higgins et al.	2012/0116175	A1	5/2012	Al-Ali et al.
2009/0054743	A1	2/2009	Stewart	2012/0123799	A1	5/2012	Nolen et al.
2009/0062682	A1	3/2009	Bland et al.	2012/0136221	A1	5/2012	Killen et al.
2009/0069642	A1	3/2009	Gao et al.	2012/0157806	A1*	6/2012	Steiger G06F 19/3406 600/365
2009/0119330	A1	5/2009	Sampath et al.	2012/0179006	A1	7/2012	Jansen et al.
2009/0124867	A1	5/2009	Hirsch et al.	2012/0184120	A1*	7/2012	Basta et al. 439/213
2009/0131759	A1	5/2009	Sims et al.	2012/0197619	A1	8/2012	Namer Yelin et al.
2009/0143832	A1	6/2009	Saba	2012/0209082	A1	8/2012	Al-Ali
2009/0157058	A1	6/2009	Ferren et al.	2012/0209084	A1	8/2012	Olsen et al.
2009/0171225	A1	7/2009	Gadodia et al.	2012/0226160	A1	9/2012	Kudoh
2009/0177091	A1	7/2009	Grunwald et al.	2012/0227739	A1	9/2012	Kiani
2009/0182287	A1	7/2009	Kassab	2012/0239434	A1	9/2012	Breslow et al.
2009/0226372	A1	9/2009	Ruolahti et al.	2012/0265039	A1	10/2012	Kiani
2009/0247924	A1	10/2009	Harima et al.	2012/0282583	A1	11/2012	Thaler et al.
2009/0247984	A1	10/2009	Lamego	2012/0283524	A1	11/2012	Kiani et al.
2009/0264778	A1	10/2009	Markowitz et al.	2012/0284053	A1	11/2012	Rosenfeld
2009/0275844	A1	11/2009	Al-Ali	2012/0286955	A1	11/2012	Welch et al.
2009/0281462	A1	11/2009	Heliot et al.	2012/0294801	A1	11/2012	Scherz et al.
2009/0299157	A1	12/2009	Telfort et al.	2012/0296178	A1	11/2012	Lamego et al.
2009/0309755	A1	12/2009	Williamson et al.	2012/0302894	A1	11/2012	Diab et al.
2010/0004518	A1	1/2010	Vo et al.	2012/0319816	A1	12/2012	Al-Ali
2010/0030040	A1	2/2010	Poeze et al.	2012/0330112	A1	12/2012	Lamego et al.
2010/0030094	A1	2/2010	Lundback	2013/0006131	A1	1/2013	Narayan et al.
2010/0036209	A1	2/2010	Ferren et al.	2013/0006151	A1	1/2013	Main et al.
2010/0069725	A1	3/2010	Al-Ali	2013/0023775	A1	1/2013	Lamego et al.
2010/0125217	A1	5/2010	Kuo et al.	2013/0035603	A1	2/2013	Jarausch et al.
2010/0144627	A1	6/2010	Vitek et al.	2013/0041591	A1	2/2013	Lamego
2010/0185101	A1	7/2010	Sakai et al.	2013/0045685	A1*	2/2013	Kiani 455/41.2
2010/0198622	A1	8/2010	Gajic et al.	2013/0046197	A1*	2/2013	Dlugos et al. 600/529
2010/0210958	A1	8/2010	Manwaring et al.	2013/0046204	A1	2/2013	Lamego et al.
2010/0261979	A1*	10/2010	Kiani 600/301	2013/0060108	A1	3/2013	Schurman et al.
2010/0298659	A1	11/2010	Mccombie et al.	2013/0060147	A1	3/2013	Welch et al.
2010/0298661	A1	11/2010	Mccombie et al.	2013/0079610	A1	3/2013	Al-Ali
2010/0305412	A1	12/2010	Darrah et al.	2013/0096405	A1	4/2013	Garfio
2010/0312103	A1	12/2010	Gorek et al.	2013/0096936	A1	4/2013	Sampath et al.
2010/0317936	A1	12/2010	Al-Ali et al.	2013/0109929	A1*	5/2013	Menzel 600/301
2010/0317951	A1	12/2010	Rutkowski et al.	2013/0109935	A1	5/2013	Al-Ali et al.
2011/0001605	A1	1/2011	Kiani et al.	2013/0162433	A1	6/2013	Muhsin et al.
2011/0021930	A1	1/2011	Mazzeo et al.	2013/0178749	A1	7/2013	Lamego
2011/0023130	A1	1/2011	Gudgel et al.	2013/0190581	A1	7/2013	Al-Ali et al.
				2013/0197328	A1	8/2013	Diab et al.
				2013/0211214	A1	8/2013	Olsen

(56)

References Cited

U.S. PATENT DOCUMENTS

2013/0243021 A1 9/2013 Siskavich
 2013/0253334 A1 9/2013 Al-Ali et al.
 2013/0262730 A1 10/2013 Al-Ali et al.
 2013/0274571 A1 10/2013 Diab et al.
 2013/0296672 A1 11/2013 O'Neil et al.
 2013/0317327 A1 11/2013 Al-Ali et al.
 2013/0317370 A1 11/2013 Dalvi et al.
 2013/0324808 A1 12/2013 Al-Ali et al.
 2013/0324817 A1 12/2013 Diab
 2013/0331670 A1 12/2013 Kiani
 2013/0338461 A1 12/2013 Lamego et al.
 2014/0012100 A1 1/2014 Al-Ali et al.
 2014/0025306 A1 1/2014 Weber et al.
 2014/0031650 A1 1/2014 Weber et al.
 2014/0034353 A1 2/2014 Al-Ali et al.
 2014/0046674 A1 2/2014 Rosenfeld
 2014/0051952 A1 2/2014 Reichgott et al.
 2014/0051953 A1 2/2014 Lamego et al.
 2014/0051954 A1 2/2014 Al-Ali et al.
 2014/0058230 A1 2/2014 Abdul-Hafiz et al.
 2014/0066783 A1 3/2014 Kiani et al.
 2014/0073167 A1 3/2014 Al-Ali et al.
 2014/0077956 A1 3/2014 Sampath et al.
 2014/0081097 A1 3/2014 Al-Ali et al.
 2014/0081100 A1 3/2014 Muhsin et al.
 2014/0081175 A1 3/2014 Telfort
 2014/0094667 A1 4/2014 Schurman et al.
 2014/0100434 A1 4/2014 Diab et al.
 2014/0114199 A1 4/2014 Lamego et al.
 2014/0120564 A1 5/2014 Workman et al.
 2014/0121482 A1 5/2014 Merritt et al.
 2014/0121483 A1 5/2014 Kiani
 2014/0125495 A1 5/2014 Al-Ali
 2014/0127137 A1 5/2014 Bellott et al.
 2014/0128696 A1 5/2014 Al-Ali
 2014/0128699 A1 5/2014 Al-Ali et al.
 2014/0129702 A1 5/2014 Lamego et al.
 2014/0135588 A1 5/2014 Al-Ali et al.
 2014/0142399 A1 5/2014 Al-Ali et al.
 2014/0142401 A1 5/2014 Al-Ali et al.
 2014/0142402 A1 5/2014 Al-Ali et al.
 2014/0152673 A1* 6/2014 Lynn et al. 345/473
 2014/0155712 A1 6/2014 Lamego et al.
 2014/0163344 A1 6/2014 Al-Ali
 2014/0163402 A1 6/2014 Lamego et al.
 2014/0166076 A1 6/2014 Kiani et al.
 2014/0171763 A1 6/2014 Diab
 2014/0180038 A1 6/2014 Kiani
 2014/0180154 A1 6/2014 Sierra et al.
 2014/0194709 A1 7/2014 Al-Ali et al.
 2014/0194711 A1 7/2014 Al-Ali
 2014/0194766 A1 7/2014 Al-Ali et al.
 2014/0200420 A1 7/2014 Al-Ali
 2014/0200422 A1 7/2014 Weber et al.
 2014/0206963 A1 7/2014 Al-Ali
 2014/0213864 A1 7/2014 Abdul-Hafiz et al.
 2014/0243627 A1 8/2014 Diab et al.
 2014/0266790 A1 9/2014 Al-Ali et al.
 2014/0275808 A1 9/2014 Poeze et al.
 2014/0275835 A1 9/2014 Lamego et al.
 2014/0275871 A1 9/2014 Lamego et al.
 2014/0275872 A1 9/2014 Merritt et al.
 2014/0275881 A1 9/2014 Lamego et al.
 2014/0288400 A1 9/2014 Diab et al.
 2014/0296664 A1 10/2014 Bruinsma et al.
 2014/0303520 A1 10/2014 Telfort et al.
 2014/0309506 A1 10/2014 Lamego et al.
 2014/0309559 A1 10/2014 Telfort et al.
 2014/0316228 A1 10/2014 Blank et al.
 2014/0323825 A1 10/2014 Al-Ali et al.
 2014/0330092 A1 11/2014 Al-Ali et al.
 2014/0330098 A1 11/2014 Merritt et al.
 2014/0330099 A1 11/2014 Al-Ali et al.
 2014/0333440 A1 11/2014 Kiani
 2014/0336481 A1 11/2014 Shakespeare et al.

2014/0343436 A1 11/2014 Kiani
 2014/0357966 A1 12/2014 Al-Ali et al.
 2015/0097701 A1 4/2015 Al-Ali et al.
 2015/0106121 A1 4/2015 Muhsin et al.
 2015/0112151 A1 4/2015 Muhsin et al.

FOREIGN PATENT DOCUMENTS

EP 2766834 8/2014
 EP 2811894 12/2014
 JP 2002/513602 5/2002
 JP 2002/542493 12/2002
 JP 2005/218036 8/2005
 JP 2005/295375 10/2005
 JP 2007/095365 4/2007
 JP 2007/174051 7/2007
 JP 2008/519635 6/2008
 JP 2014/533997 12/2014
 WO WO 98/29790 7/1998
 WO WO 99/13766 3/1999
 WO WO 99/56613 11/1999
 WO WO 00/63713 10/2000
 WO WO/2004/056266 7/2004
 WO WO/2004/059551 7/2004
 WO WO 2006/051461 5/2006
 WO WO 2011002904 A2 * 1/2011
 WO WO 2013/056160 4/2013
 WO WO 2013/119982 8/2013
 WO WO 2015/054665 4/2015

OTHER PUBLICATIONS

Extended European Search Report for European Application No. 10195398.2 dated Jul. 5, 2012.
 US 8,845,543, 9/2014, Diab et al. (withdrawn).
 Capuano et al. "Remote Telemetry—New Twists for Old Technology." Nursing Management. vol. 26, No. 7. Jul. 1995.
 Elmer-Dewitt, Philip, Apple's iWatch: The killer apps may be in hospitals, not health clubs, Fortune.com, Feb. 3, 2014, <http://fortune.com/2014/02/03/apples-iwatch-the-killer-apps-may-be-in-hospitals-not-health-clubs/>, in 4 pages.
 Grundy et al. "Telemedicine in Critical Care: An Experiment in Health Care Delivery." Oct. 1977.
 Grundy et al. "Telemedicine in Critical Care: Problems in design, implementation and assessment." vol. 10, No. 7. Jul. 1982.
 PCT International Preliminary Report on Patentability for Application No. PCT/US2012/060109, dated Apr. 24, 2014.
 PCT International Search Report & Written Opinion, App. No. PCT/US2014/060177, dated Dec. 19, 2014.
 PCT International Search Report and Written Opinion, App. No. PCT/US2013/025384, dated Aug. 6, 2013.
 Rysavy, "Making the Call with Two-Way Paging", Network Computing, Published Jan. 15, 1997, www.rysavvy.com/Articles/twoway.htm.
 PCT International Search Report, App. No. PCT/US2012/060109, App. Date: Dec. 10, 2012, in 6 pages.
 U.S. Appl. No. 14/815,232, filed Jul. 31, 2015 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.
 U.S. Appl. No. 14/464,560, filed Aug. 20, 2014 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.
 U.S. Appl. No. 14/733,781, filed Jun. 8, 2015 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.
 U.S. Appl. No. 13/762,270, filed Feb. 7, 2013 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.

(56)

References Cited

OTHER PUBLICATIONS

U.S. Appl. No. 14/834,169, filed Aug. 24, 2015 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.

U.S. Appl. No. 29/537,221, filed Aug. 24, 2015 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.

U.S. Appl. No. 14/511,974, filed Oct. 10, 2014 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.

U.S. Appl. No. 14/512,237, filed Oct. 10, 2014 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.

U.S. Appl. No. 14/511,972, filed Oct. 10, 2014 including its ongoing prosecution history, including without limitation Office Actions, Amendments, Remarks, and any other potentially relevant documents.

EP Office Action dated Jun. 15, 2015 for EP App. No. 10195398.2.

JP Office Action dated Aug. 17, 2015 for JP Application No. 2014-556738.

* cited by examiner




FIG. 1A




FIG. 1B





FIG. 1C






FIG. 3




FIG. 4







FIG. 5



700






FIG. 8




FIG. 9A




FIG. 9B






FIG. 10






FIG. 11C




FIG. 11D




FIG. 11E





FIG. 11F






FIG. 11G2

SECTION A-A





FIG. 11H



EPROM




FIG. 11J




FIG. 11I




FIG. 11K




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16






FIG. 17B




FIG. 18




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 19D




FIG. 19E




FIG. 19F




FIG. 19G




FIG. 19H




FIG. 19I




FIG. 19J




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 21A




FIG. 21B




FIG. 22A




FIG. 22B




FIG. 23A




FIG. 23B




FIG. 23C




FIG. 23D




FIG. 23E




FIG. 23F

1

MEDICAL MONITORING HUB**PRIORITY CLAIM AND RELATED APPLICATIONS**

This application claims a priority benefit under 35 U.S.C. §119 to the following U.S. Provisional Patent Applications:

Serial No.	Date	Title
61/547,017,	Oct. 13, 2011,	Visual Correlation of Physiological Information,
61/547,577,	Oct. 14, 2011,	Visual Correlation of Physiological Information,
61/597,120,	Feb. 9, 2012,	Visual Correlation of Physiological Information, and,
61/703,773	Sep. 20, 2012	Medical Monitoring Hub

Each of the foregoing disclosures is incorporated by reference herein in its entirety.

FIELD OF THE DISCLOSURE

The present disclosure relates generally to patient monitoring devices and specifically to a patient monitor and medical data communication hub.

BACKGROUND OF THE DISCLOSURE

Today's patient monitoring environments are crowded with sophisticated and often electronic medical devices servicing a wide variety of monitoring and treatment endeavors for a given patient. Generally, many if not all of the devices are from differing manufactures, and many may be portable devices. The devices may not communicate with one another and each may include its own control, display, alarms, configurations and the like. Complicating matters, caregivers often desire to associate all types of measurement and use data from these devices to a specific patient. Thus, patient information entry often occurs at each device. Sometimes, the disparity in devices leads to a need to simply print and store paper from each device in a patient's file for caregiver review.

The result of such device disparity is often a caregiver environment scattered with multiple displays and alarms leading to a potentially chaotic experience. Such chaos can be detrimental to the patient in many situations including surgical environments where caregiver distraction is unwanted, and including recovery or monitoring environments where patient distraction or disturbance may be unwanted.

Various manufacturers produce multi-monitor devices or devices that modularly expand to increase the variety of monitoring or treatment endeavors a particular system can accomplish. However, as medical device technology expands, such multi-monitor devices begin to be obsolete the moment they are installed.

SUMMARY OF THE INVENTION

Based on at least the foregoing, a solution is needed that coordinates the various medical devices treating or monitoring a patient. Embodiments of such a solution should provide patient identification seamlessly across the device space and embodiments of such a solution should expand for future technologies without necessarily requiring repeated

2

software upgrades. In addition, embodiments of such a solution may include patient electrical isolation where desired.

Therefore, the present disclosure relates to a patient monitoring hub that is the center of patient monitoring and treatment activities for a given patient. Embodiments of the patient monitoring hub interface with legacy devices without necessitating legacy reprogramming, provide flexibility for interfacing with future devices without necessitating software upgrades, and offer optional patient electrical isolation. In an embodiment, the hub includes a large display dynamically providing information to a caregiver about a wide variety of measurement or otherwise determined parameters. Additionally, in an embodiment, the hub includes a docking station for a portable patient monitor. The portable patient monitor may communicate with the hub through the docking station or through various wireless paradigms known to an artisan from the disclosure herein, including WiFi, Bluetooth, Zigbee, or the like.

In still other embodiments, the portable patient monitor modifies its screen when docked. The undocked display indicia is in part or in whole transferred to a large dynamic display of the hub and the docked display presents one or more anatomical graphics of monitored body parts. For example, the display may present a heart, lungs, a brain, kidneys, intestines, a stomach, other organs, digits, gastrointestinal systems or other body parts when it is docked. In an embodiment, the anatomical graphics may advantageously be animated. In an embodiment, the animation may generally follow the behavior of measured parameters, such as, for example, the lungs may inflate in approximate correlation to the measured respiration rate and/or the determined inspiration portion of a respiration cycle, and likewise deflate according to the expiration portion of the same. The heart may beat according to the pulse rate, may beat generally along understood actual heart contraction patterns, and the like. Moreover, in an embodiment, when the measured parameters indicate a need to alert a caregiver, a changing severity in color may be associated with one or more displayed graphics, such as the heart, lungs, brain, or the like. In still other embodiments, the body portions may include animations on where, when or how to attach measurement devices to measurement sites on the patient. For example, the monitor may provide animated directions for CCHD screening procedures or glucose strip reading protocols, the application of a forehead sensor, a finger or toe sensor, one or more electrodes, an acoustic sensor, and ear sensor, a cannula sensor or the like.

For purposes of summarizing the disclosure, certain aspects, advantages and novel features are discussed herein. It is to be understood that not necessarily all such aspects, advantages or features will be embodied in any particular embodiment of the invention and an artisan would recognize from the disclosure herein a myriad of combinations of such aspects, advantages or features.

BRIEF DESCRIPTION OF THE DRAWINGS

The following drawings and the associated descriptions are provided to illustrate embodiments of the present disclosure and do not limit the scope of the claims.

FIGS. 1A-1C illustrate perspective views of an exemplary medical monitoring hub according to an embodiment of the disclosure. For example, FIG. 1A illustrates the hub with an exemplary docked portable patient monitor, FIG. 1B illustrates the hub with a set of medical ports and a noninvasive blood pressure input, and FIG. 1C illustrates the hub with

3

various exemplary temperature sensors attached thereto, all according to various embodiments of the disclosure.

FIG. 2 illustrates a simplified block diagram of an exemplary monitoring environment including the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 3 illustrates a simplified exemplary hardware block diagram of the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 4 illustrates a perspective view of an exemplary removable docking station of the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 5 illustrates a perspective view of exemplary portable patient monitors undocked from the hub of FIG. 1, according to an embodiment of the disclosure. Moreover, FIG. 5 illustrates an exemplary alternative docking station.

FIG. 6 illustrates a simplified block diagram of traditional patient device electrical isolation principles.

FIG. 7A illustrates a simplified block diagram of an exemplary optional patient device isolation system according to an embodiment of the disclosure, while FIG. 7B adds exemplary optional non-isolation power levels for the system of FIG. 7A, also according to an embodiment of the disclosure.

FIG. 8 illustrates a simplified exemplary universal medical connector configuration process, according to an embodiment of the disclosure.

FIGS. 9A-11K illustrate simplified block diagrams of exemplary universal medical connectors having a size and shape smaller in cross section than tradition isolation requirements.

FIG. 10 illustrates a perspective view of a side of the hub of FIG. 1, showing exemplary instrument-side channel inputs for exemplary universal medical connectors, according to an embodiment of the disclosure.

FIGS. 11A-11K illustrate various views of exemplary male and mating female universal medical connectors, according to embodiments of the disclosure.

FIG. 12 illustrates a simplified block diagram of a channel system for the hub of FIG. 1, according to an embodiment of the disclosure.

FIG. 13 illustrates an exemplary logical channel configuration, according to an embodiment of the disclosure.

FIG. 14 illustrates a simplified exemplary process for constructing a cable and configuring a channel according to an embodiment of the disclosure.

FIG. 15 illustrates a perspective view of the hub of FIG. 1, including an exemplary attached board-in-cable to form an input channel, according to an embodiment of the disclosure.

FIG. 16 illustrates a perspective view of a back side of the hub of FIG. 1, showing an exemplary instrument-side serial data inputs, according to an embodiment of the disclosure.

FIG. 17A illustrates an exemplary monitoring environment with communication through the serial data connections of FIG. 16, and FIG. 17B illustrates an exemplary connectivity display of the hub of FIG. 1, according to embodiments of the disclosure.

FIG. 18 illustrates a simplified exemplary patient data flow process, according to an embodiment of the disclosure.

FIGS. 19A-19J illustrate exemplary displays of anatomical graphics for the portable patient monitor of FIG. 1 docked with the hub of FIG. 1, according to embodiments of the disclosure.

FIGS. 20A-20C illustrate exemplary displays of measurement data showing data separation and data overlap on a display of the hub of FIG. 1, respectively, according to embodiments of the disclosure.

4

FIGS. 21A and 21B illustrate exemplary displays of measurement data showing data separation and data overlap on a display of the portable patient monitor of FIG. 1, respectively, according to embodiments of the disclosure.

FIGS. 22A and 22B illustrate exemplary analog display indicia according to an embodiment of the disclosure.

FIGS. 23A-23F illustrate exemplary displays of measurement data showing, for example, data presentation in FIGS. 23A-23D when a depth of consciousness monitor is connected to a channel port of the hub of FIG. 1, data presentation in FIG. 23E when temperature and blood pressure sensors communicate with the hub of FIG. 1 and data presentation in FIG. 23F when an acoustic sensor is also communicating with the hub of FIG. 1, according to embodiments of the disclosure.

While the foregoing "Brief Description of the Drawings" references generally various embodiments of the disclosure, an artisan will recognize from the disclosure herein that such embodiments are not mutually exclusive. Rather, the artisan would recognize a myriad of combinations of some or all of such embodiments.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present disclosure relates to a medical monitoring hub configured to be the center of monitoring activity for a given patient. In an embodiment, the hub comprises a large easily readable display, such as an about ten (10) inch display dominating the majority of real estate on a front face of the hub. The display could be much larger or much smaller depending upon design constraints. However, for portability and current design goals, the preferred display is roughly sized proportional to the vertical footprint of one of the dockable portable patient monitors. Other considerations are recognizable from the disclosure herein by those in the art.

The display provides measurement data for a wide variety of monitored parameters for the patient under observation in numerical or graphic form, and in various embodiments, is automatically configured based on the type of data and information being received at the hub. In an embodiment, the hub is moveable, portable, and mountable so that it can be positioned to convenient areas within a caregiver environment. For example, the hub is collected within a singular housing.

In an embodiment, the hub may advantageously receive data from a portable patient monitor while docked or undocked from the hub. Typical portable patient monitors, such as oximeters or co-oximeters can provide measurement data for a large number of physiological parameters derived from signals output from optical and/or acoustic sensors, electrodes, or the like. The physiological parameters include, but not limited to oxygen saturation, carboxy hemoglobin, methemoglobin, total hemoglobin, glucose, pH, bilirubin, fractional saturation, pulse rate, respiration rate, components of a respiration cycle, indications of perfusion including perfusion index, signal quality and/or confidences, plethysmograph data, indications of wellness or wellness indexes or other combinations of measurement data, audio information responsive to respiration, ailment identification or diagnosis, blood pressure, patient and/or measurement site temperature, depth of sedation, organ or brain oxygenation, hydration, measurements responsive to metabolism, combinations of the same or the like, to name a few. In other

5

embodiments, the hub may output data sufficient to accomplish closed-loop drug administration in combination with infusion pumps or the like.

In an embodiment, the hub communicates with other devices in a monitoring environment that are interacting with the patient in a number of ways. For example, the hub advantageously receives serial data from other devices without necessitating their reprogramming or that of the hub. Such other devices include pumps, ventilators, all manner of monitors monitoring any combination of the foregoing parameters, ECG/EEG/EKG devices, electronic patient beds, and the like. Moreover, the hub advantageously receives channel data from other medical devices without necessitating their reprogramming or that of the hub. When a device communicates through channel data, the hub may advantageously alter the large display to include measurement information from that device. Additionally, the hub accesses nurse call systems to ensure that nurse call situations from the device are passed to the appropriate nurse call system.

The hub also communicates with hospital systems to advantageously associate incoming patient measurement and treatment data with the patient being monitored. For example, the hub may communicate wirelessly or otherwise to a multi-patient monitoring system, such as a server or collection of servers, which in turn many communicate with a caregiver's data management systems, such as, for example, an Admit, Discharge, Transfer ("ADT") system and/or an Electronic Medical Records ("EMR") system. The hub advantageously associates the data flowing through it with the patient being monitored thereby providing the electronic measurement and treatment information to be passed to the caregiver's data management systems without the caregiver associating each device in the environment with the patient.

In an embodiment, the hub advantageously includes a reconfigurable and removable docking station. The docking station may dock additional layered docking stations to adapt to different patient monitoring devices. Additionally, the docking station itself is modularized so that it may be removed if the primary dockable portable patient monitor changes its form factor. Thus, the hub is flexible in how its docking station is configured.

In an embodiment, the hub includes a large memory for storing some or all of the data it receives, processes, and/or associates with the patient, and/or communications it has with other devices and systems. Some or all of the memory may advantageously comprise removable SD memory.

The hub communicates with other devices through at least (1) the docking station to acquire data from a portable monitor, (2) innovative universal medical connectors to acquire channel data, (3) serial data connectors, such as RJ ports to acquire output data, (4) Ethernet, USB, and nurse call ports, (5) Wireless devices to acquire data from a portable monitor, (6) other wired or wireless communication mechanisms known to an artisan. The universal medical connectors advantageously provide optional electrically isolated power and communications, are designed to be smaller in cross section than isolation requirements. The connectors and the hub communicate to advantageously translate or configure data from other devices to be usable and displayable for the hub. In an embodiment, a software developers kit ("SDK") is provided to a device manufacturer to establish or define the behavior and meaning of the data output from their device. When the output is defined, the definition is programmed into a memory residing in the cable side of the universal medical connector and supplied as an original

6

equipment manufacture ("OEM") to the device provider. When the cable is connected between the device and the hub, the hub understands the data and can use it for display and processing purposes without necessitating software upgrades to the device or the hub. In an embodiment, the hub can negotiate the schema and even add additional compression and/or encryption. Through the use of the universal medical connectors, the hub organizes the measurement and treatment data into a single display and alarm system effectively and efficiently bringing order to the monitoring environment.

As the hub receives and tracks data from other devices according to a channel paradigm, the hub may advantageously provide processing to create virtual channels of patient measurement or treatment data. In an embodiment, a virtual channel may comprise a non-measured parameter that is, for example, the result of processing data from various measured or other parameters. An example of such a parameter includes a wellness indicator derived from various measured parameters that give an overall indication of the wellbeing of the monitored patient. An example of a wellness parameter is disclosed in U.S. patent application Ser. Nos. 13/269,296, 13/371,767 and 12/904,925, by the assignee of the present disclosure and incorporated by reference herein. By organizing data into channels and virtual channels, the hub may advantageously time-wise synchronize incoming data and virtual channel data.

The hub also receives serial data through serial communication ports, such as RJ connectors. The serial data is associated with the monitored patient and passed on to the multi-patient server systems and/or caregiver backend systems discussed above. Through receiving the serial data, the caregiver advantageously associates devices in the caregiver environment, often from varied manufactures, with a particular patient, avoiding a need to have each individual device associated with the patient and possible communicating with hospital systems. Such association is vital as it reduces caregiver time spent entering biographic and demographic information into each device about the patient. Moreover, in an embodiment, through the SDK the device manufacturer may advantageously provide information associated with any measurement delay of their device, thereby further allowing the hub to advantageously time-wise synchronize serial incoming data and other data associated with the patient.

In an embodiment, when a portable patient monitor is docked, and it includes its own display, the hub effectively increases its display real estate. For example, in an embodiment, the portable patient monitor may simply continue to display its measurement and/or treatment data, which may be now duplicated on the hub display, or the docked display may alter its display to provide additional information. In an embodiment, the docked display, when docked, presents anatomical graphical data of, for example, the heart, lungs, organs, the brain, or other body parts being measured and/or treated. The graphical data may advantageously animate similar to and in concert with the measurement data. For example, lungs may inflate in approximate correlation to the measured respiration rate and/or the determined inspiration/expiration portions of a respiration cycle, the heart may beat according to the pulse rate, may beat generally along understood actual heart contraction patterns, the brain may change color or activity based on varying depths of sedation, or the like. In an embodiment, when the measured parameters indicate a need to alert a caregiver, a changing severity in color may be associated with one or more displayed graphics, such as the heart, lungs, brain, organs, circulatory

system or portions thereof, respiratory system or portions thereof, other body parts or the like. In still other embodiments, the body portions may include animations on where, when or how to attach measurement devices.

The hub may also advantageously overlap parameter displays to provide additional visual information to the caregiver. Such overlapping may be user definable and configurable. The display may also incorporate analog-appearing icons or graphical indicia.

In the interest of clarity, not all features of an actual implementation are described in this specification. An artisan will of course be appreciate that in the development of any such actual implementation (as in any development project), numerous implementation-specific decisions must be made to achieve a developers' specific goals and sub-goals, such as compliance with system- and business-related constraints, which will vary from one implementation to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming, but would nevertheless be a routine undertaking of device engineering for those of ordinary skill having the benefit of this disclosure.

To facilitate a complete understanding of the disclosure, the remainder of the detailed description describes the disclosure with reference to the drawings, wherein like reference numbers are referenced with like numerals throughout.

FIG. 1A illustrates a perspective view of an exemplary medical monitoring hub **100** with an exemplary docked portable patient monitor **102** according to an embodiment of the disclosure. The hub **100** includes a display **104**, and a docking station **106**, which in an embodiment is configured to mechanically and electrically mate with the portable patient monitor **102**, each housed in a movable, mountable and portable housing **108**. The housing **108** includes a generally upright inclined shape configured to rest on a horizontal flat surface, although the housing **108** can be affixed in a wide variety of positions and mountings and comprise a wide variety of shapes and sizes.

In an embodiment, the display **104** may present a wide variety of measurement and/or treatment data in numerical, graphical, waveform, or other display indicia **110**. In an embodiment, the display **104** occupies much of a front face of the housing **108**, although an artisan will appreciate the display **104** may comprise a tablet or tabletop horizontal configuration, a laptop-like configuration or the like. Other embodiments may include communicating display information and data to a table computer, smartphone, television, or any display system recognizable to an artisan. The upright inclined configuration of FIG. 1A presents display information to a caregiver in an easily viewable manner.

FIG. 1B shows a perspective side view of an embodiment of the hub **100** including the housing **108**, the display **104**, and the docking station **106** without a portable monitor docked. Also shown is a connector for noninvasive blood pressure.

In an embodiment, the housing **108** may also include pockets or indentations to hold additional medical devices, such as, for example, a blood pressure monitor or temperature sensor **112**, such as that shown in FIG. 1C.

The portable patient monitor **102** of FIG. 1A may advantageously comprise an oximeter, co-oximeter, respiratory monitor, depth of sedation monitor, noninvasive blood pressure monitor, vital signs monitor or the like, such as those commercially available from Masimo Corporation of Irvine, Calif., and/or disclosed in U.S. Pat. Pub. Nos. 2002/0140675, 2010/0274099, 2011/0213273, 2012/0226117,

2010/0030040; U.S. Patent Application Ser. Nos. 61/242,792, 61/387457, 61/645,570, 13/554,908 and U.S. Pat. Nos. 6,157,850, 6,334,065, and the like. The monitor **102** may communicate with a variety of noninvasive and/or minimally invasive devices such as optical sensors with light emission and detection circuitry, acoustic sensors, devices that measure blood parameters from a finger prick, cuffs, ventilators, and the like. The monitor **102** may include its own display **114** presenting its own display indicia **116**, discussed below with reference to FIGS. 19A-19J. The display indicia may advantageously change based on a docking state of the monitor **102**. When undocked, the display indicia may include parameter information and may alter orientation based on, for example, a gravity sensor or accelerometer.

In an embodiment, the docking station **106** of the hub **100** includes a mechanical latch **118**, or mechanically releasable catch to ensure that movement of the hub **100** doesn't mechanically detach the monitor **102** in a manner that could damage the same.

Although disclosed with reference to particular portable patient monitors **102**, an artisan will recognize from the disclosure herein a large number and wide variety of medical devices that may advantageously dock with the hub **100**. Moreover, the docking station **106** may advantageously electrically and not mechanically connect with the monitor **102**, and/or wirelessly communicate with the same.

FIG. 2 illustrates a simplified block diagram of an exemplary monitoring environment **200** including the hub **100** of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 2, the environment may include the portable patient monitor **102** communicating with one or more patient sensors **202**, such as, for example, oximetry optical sensors, acoustic sensors, blood pressure sensors, respiration sensors or the like. In an embodiment, additional sensors, such as, for example, a NIBP sensor or system **211** and a temperature sensor or sensor system **213** may communicate directly with the hub **100**. The sensors **202**, **211** and **213** when in use are typically in proximity to the patient being monitored if not actually attached to the patient at a measurement site.

As disclosed, the portable patient monitor **102** communicates with the hub **100**, in an embodiment, through the docking station **106** when docked and, in an embodiment, wirelessly when undocked, however, such undocked communication is not required. The hub **100** communicates with one or more multi-patient monitoring servers **204** or server systems, such as, for example, those disclosed with in U.S. Pat. Pub. Nos. 2011/0105854, 2011/0169644, and 2007/0180140. In general, the server **204** communicates with caregiver backend systems **206** such as EMR and/or ADT systems. The server **204** may advantageously obtain through push, pull or combination technologies patient information entered at patient admission, such as demographical information, billing information, and the like. The hub **100** accesses this information to seamlessly associate the monitored patient with the caregiver backend systems **206**. Communication between the server **204** and the monitoring hub **100** may be any recognizable to an artisan from the disclosure herein, including wireless, wired, over mobile or other computing networks, or the like.

FIG. 2 also shows the hub **100** communicating through its serial data ports **210** and channel data ports **212**. As disclosed in the forgoing, the serial data ports **210** may provide data from a wide variety of patient medical devices, including electronic patient bed systems **214**, infusion pump systems **216** including closed loop control systems, venti-

lator systems 218, blood pressure or other vital sign measurement systems 220, or the like. Similarly, the channel data ports 212 may provide data from a wide variety of patient medical devices, including any of the foregoing, and other medical devices. For example, the channel data ports 212 may receive data from depth of consciousness monitors 222, such as those commercially available from SEDLine, brain or other organ oximeter devices 224, noninvasive blood pressure or acoustic devices 226, or the like. In an embodiment, channel device may include board-in-cable (“BIC”) solutions where the processing algorithms and the signal processing devices that accomplish those algorithms are mounted to a board housed in a cable or cable connector, which in some embodiments has no additional display technologies. The BIC solution outputs its measured parameter data to the channel port 212 to be displayed on the display 104 of hub 100. In an embodiment, the hub 100 may advantageously be entirely or partially formed as a BIC solution that communicates with other systems, such as, for example, tablets, smartphones, or other computing systems.

Although disclosed with reference to a single docking station 106, the environment 200 may include stacked docking stations where a subsequent docking station mechanically and electrically docks to a first docking station to change the form factor for a different portable patient monitor as discussed with reference to FIG. 5. Such stacking may include more than 2 docking stations, may reduce or increase the form factor for mechanical compliance with mating mechanical structures on a portable device.

FIG. 3 illustrates a simplified exemplary hardware block diagram of the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 3, the housing 108 of the hub 100 positions and/or encompasses an instrument board 302, the display 104, memory 304, and the various communication connections, including the serial ports 210, the channel ports 212, Ethernet ports 305, nurse call port 306, other communication ports 308 including standard USB or the like, and the docking station interface 310. The instrument board 302 comprises one or more substrates including communication interconnects, wiring, ports and the like to enable the communications and functions described herein, including inter-board communications. A core board 312 includes the main parameter, signal, and other processor(s) and memory, a portable monitor board (“RIB”) 314 includes patient electrical isolation for the monitor 102 and one or more processors, a channel board (“MID”) 316 controls the communication with the channel ports 212 including optional patient electrical isolation and power supply 318, and a radio board 320 includes components configured for wireless communications. Additionally, the instrument board 302 may advantageously include one or more processors and controllers, busses, all manner of communication connectivity and electronics, memory, memory readers including EPROM readers, and other electronics recognizable to an artisan from the disclosure herein. Each board comprises substrates for positioning and support, interconnect for communications, electronic components including controllers, logic devices, hardware/software combinations and the like to accomplish the tasks designated above and others.

An artisan will recognize from the disclosure herein that the instrument board 302 may comprise a large number of electronic components organized in a large number of ways. Using different boards such as those disclosed above advantageously provides organization and compartmentalization to the complex system.

FIG. 4 illustrates a perspective view of an exemplary removable docking station 400 of the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 4, the docking station 400 provides a mechanical mating to portable patient monitor 102 to provide secure mechanical support when the monitor 102 is docked. The docking station 400 includes a cavity 402 shaped similar to the periphery of a housing of the portable monitor 102. The station 400 also includes one or more electrical connectors 404 providing communication to the hub 100. Although shown as mounted with bolts, the docking station 400 may snap fit, may use movable tabs or catches, may magnetically attach, or may employ a wide variety or combination of attachment mechanisms known to an artisan from the disclosure herein. In an embodiment, the attachment of the docking station 400 should be sufficiently secure that when docked, the monitor 102 and docking station cannot be accidentally detached in a manner that could damage the instruments, such as, for example, if the hub 100 was accidentally bumped or the like, the monitor 102 and docking station 400 should remain intact.

The housing 108 of the hub 100 also includes cavity 406 housing the docking station 400. To the extent a change to the form factor for the portable patient monitor 102 occurs, the docking station 400 is advantageously removable and replaceable. Similar to the docking station 400, the hub 100 includes within the cavity 406 of the housing 108 electrical connectors 408 providing electrical communication to the docking station 400. In an embodiment, the docking station 400 includes its own microcontroller and processing capabilities, such as those disclosed in U.S. Pat. Pub. No. 2002/0140675. In other embodiments, the docking station 400 passes communications through to the electrical connector 408.

FIG. 4 also shows the housing 108 including openings for channel ports 212 as universal medical connectors discussed in detail below.

FIG. 5 illustrates a perspective view of exemplary portable patient monitors 502 and 504 undocked from the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown in FIG. 5, the monitor 502 may be removed and other monitors, like monitor 504 may be provided. The docking station 106 includes an additional docking station 506 that mechanically mates with the original docking station 106 and presents a form factor mechanically mateable with monitor 504. In an embodiment, the monitor 504 mechanically and electrically mates with the stacked docking stations 506 and 106 of hub 100. As can be readily appreciated by an artisan from the disclosure herein, the stackable function of the docking stations provides the hub 100 with an extremely flexible mechanism for charging, communicating, and interfacing with a wide variety of patient monitoring devices. As noted above, the docking stations may be stacked, or in other embodiments, removed and replaced.

FIG. 6 illustrates a simplified block diagram of traditional patient electrical isolation principles. As shown in FIG. 6, a host device 602 is generally associated with a patient device 604 through communication and power. As the patient device 604 often comprises electronics proximate or connected to a patient, such as sensors or the like, certain safety requirements dictate that electrical surges of energy from, for example, the power grid connected to the host device, should not find an electrical path to the patient. This is generally referred to a “patient isolation” which is a term known in the art and includes herein the removing of direct uninterrupted electrical paths between the host device 602

11

and the patient device **604**. Such isolation is accomplished through, for example, isolation devices **606** on power conductors **608** and communication conductors **610**. Isolation devices **606** can include transformers, optical devices that emit and detect optical energy, and the like. Use of isolation devices, especially on power conductors, can be expensive component wise, expensive size wise, and drain power. Traditionally, the isolation devices were incorporated into the patient device **604**, however, the patient devices **604** are trending smaller and smaller and not all devices incorporate isolation.

FIG. **7A** illustrates a simplified block diagram of an exemplary optional patient isolation system according to an embodiment of the disclosure. As shown in FIG. **7A**, the host device **602** communicates with an isolated patient device **604** through isolation devices **606**. However, a memory **702** associated with a particular patient device informs the host **602** whether that device needs isolated power. If a patient device **708** does not need isolated power, such as some types of cuffs, infusion pumps, ventilators, or the like, then the host **602** can provide non-isolated power through signal path **710**. This power may be much higher than what can cost-effectively be provided through the isolated power conductor **608**. In an embodiment, the non-isolated patient devices **708** receive isolated communication as such communication is typically at lower voltages and is not cost prohibitive. An artisan will recognize from the disclosure herein that communication could also be non-isolated. Thus, FIG. **7A** shows a patient isolation system **700** that provides optional patient isolation between a host **602** and a wide variety of potential patient devices **604**, **708**. In an embodiment, the hub **100** includes the channel ports **212** incorporating similar optional patient isolation principles.

FIG. **7B** adds an exemplary optional non-isolation power levels for the system of FIG. **7A** according to an embodiment of the disclosure. As shown in FIG. **7B**, once the host **602** understands that the patient device **604** comprises a self-isolated patient device **708**, and thus does not need isolated power, the host **602** provides power through a separate conductor **710**. Because the power is not isolated, the memory **702** may also provide power requirements to the host **602**, which may select from two or more voltage or power levels. In FIG. **7B**, the host **602** provides either high power, such as about 12 volts, but could have a wide range of voltages or very high power such as about 24 volts or more, but could have a wide range of voltages, to the patient device **708**. An artisan will recognize that supply voltages can advantageously be altered to meet the specific needs of virtually any device **708** and/or the memory could supply information to the host **602** which provided a wide range of non-isolated power to the patient device **708**.

Moreover, using the memory **702**, the host **602** may determine to simply not enable any unused power supplies, whether that be the isolated power or one or more of the higher voltage non-isolated power supplies, thereby increasing the efficiency of the host.

FIG. **8** illustrates a simplified exemplary universal medical connector configuration process **800**, according to an embodiment of the disclosure. As shown in FIG. **8**, the process includes step **802**, where a cable is attached to a universal medical connector incorporating optional patient isolation as disclosed in the foregoing. In step **804**, the host device **602** or the hub **100**, more specifically, the channel data board **316** or EPROM reader of the instrument board, reads the data stored in the memory **702** and in step **806**, determines whether the connecting device requires isolated power. In step **808**, when the isolated power is required, the

12

hub **100** may advantageously enable isolated power and in step **810**, enable isolated communications. In step **806**, when isolated power is not needed, the hub **100** may simply in optional step **812** enable non-isolated power and in embodiments where communications remain isolated, step **810** enable isolated communications. In other optional embodiments, in step **806**, when isolated power is not needed, the hub **100** in step **814** may use information from memory **702** to determine the amount of power needed for the patient device **708**. When sufficient power is not available, because for example, other connected devices are also using connected power, in step **816** a message may be displayed indicating the same and power is not provided. When sufficient power is available, optional step **812** may enable non-isolated power. Alternatively, optional step **818** may determine whether memory **702** indicates higher or lower power is desired. When higher power is desired, the hub **100** may enable higher power in step **820** and when not, may enable lower power in step **822**. The hub **100** in step **810** then enables isolated communication. In an embodiment, the hub **100** in step **818** may simply determine how much power is needed and provide at least sufficient power to the self-isolated device **708**.

An artisan will recognize from the disclosure herein that hub **100** may not check to see if sufficient power is available or may provide one, two or many levels of non-isolated voltages based on information from the memory **702**.

FIGS. **9A** and **9B** illustrate simplified block diagrams of exemplary universal medical connectors **900** having a size and shape smaller in cross section than tradition isolation requirements. In an embodiment, the connector **900** physically separates non-isolated signals on one side **910** from isolated signals on another side **920**, although the sides could be reversed. The gap between such separations may be dictated at least in part by safety regulations governing patient isolation. In an embodiment, the distance between the sides **910** and **920** may appear to be too small.

As shown from a different perspective in FIG. **9B**, the distance between connectors “x” appears small. However, the gap causes the distance to include a non-direct path between conductors. For example, any short would have to travel path **904**, and the distance of such path is within or beyond such safety regulations, in that the distance is greater than “x.” It is noteworthy that the non-straight line path **904** occurs throughout the connector, such as, for example, on the board connector side where solder connects various pins to a PCB board.

FIG. **10** illustrates a perspective view of a side of the hub **100** of FIG. **1**, showing exemplary instrument-side channel inputs **1000** as exemplary universal medical connectors. As shown in FIG. **10**, the inputs include the non-isolated side **910**, the isolated side **920**, and the gap. In an embodiment, the memory **710** communicates through pins on the non-isolated side.

FIGS. **11A-11K** illustrate various views of exemplary male and mating female universal medical connectors, according to embodiments of the disclosure. For example, FIGS. **11G1** and **11G2** shows various preferred but not required sizing, and FIG. **11H** shows incorporation of electronic components, such as the memory **702** into the connectors. FIGS. **11I-11K** illustrate wiring diagrams and cabling specifics of the cable itself as it connects to the universal medical connectors.

FIG. **12** illustrates a simplified block diagram of a channel system for the hub of FIG. **1**, according to an embodiment of the disclosure. As shown in FIG. **12**, a male cable connector, such as those shown in FIG. **11** above, includes

13

a memory such as an EPROM. The memory advantageously stores information describing the type of data the hub 100 can expect to receive, and how to receive the same. A controller of the hub 100 communicates with the EPROM to negotiate how to receive the data, and if possible, how to display the data on display 104, alarm when needed, and the like. For example, a medical device supplier may contact the hub provider and receive a software developers' kit ("SDK") that guides the supplier through how to describe the type of data output from their device. After working with the SDK, a map, image, or other translation file may advantageously be loaded into the EPROM, as well as the power requirements and isolation requirements discussed above. When the channel cable is connected to the hub 100 through the channel port 212, the hub 100 reads the EPROM and the controller of the hub 100 negotiates how to handle incoming data.

FIG. 13 illustrates an exemplary logical channel configuration that may be stored in the EPROM of FIG. 12. As shown in FIG. 13, each incoming channel describes one or more parameters. Each parameter describes whatever the hub 100 should know about the incoming data. For example, the hub 100 may want to know whether the data is streaming data, waveform data, already determined parameter measurement data, ranges on the data, speed of data delivery, units of the data, steps of the units, colors for display, alarm parameters and thresholds, including complex algorithms for alarm computations, other events that are parameter value driven, combinations of the same or the like. Additionally, the parameter information may include device delay times to assist in data synchronization or approximations of data synchronization across parameters or other data received by the hub 100. In an embodiment, the SDK presents a schema to the device supplier which self-describes the type and order of incoming data. In an embodiment, the information advantageously negotiates with the hub 100 to determine whether to apply compression and/or encryption to the incoming data stream.

Such open architecture advantageously provides device manufacturers the ability to port the output of their device into the hub 100 for display, processing, and data management as disclosed in the foregoing. By implementation through the cable connector, the device manufacturer avoids any reprogramming of their original device; rather, they simply let the hub 100 know through the cable connector how the already existing output is formatted. Moreover, by describing the data in a language already understood by the hub 100, the hub 100 also avoids software upgrades to accommodate data from "new-to-the-hub" medical devices.

FIG. 14 illustrates a simplified exemplary process for configuring a channel according to an embodiment of the disclosure. As shown in FIG. 14, the hub provider provides a device manufacturer with an SDK in step 1402, who in turn uses the SDK to self-describe the output data channel from their device in step 1404. In an embodiment, the SDK is a series of questions that guide the development, in other embodiments, the SDK provides a language and schema to describe the behavior of the data.

Once the device provider describes the data, the hub provider creates a binary image or other file to store in a memory within a cable connector in step 1405; however, the SDK may create the image and simply communicated it to the hub provider. The cable connector is provided as an OEM part to the provider in step 1410, who constructs and manufactures the cable to mechanically and electrically mate with output ports on their devices in step 1412.

14

Once a caregiver has the appropriately manufactured cable, with one end matching the device provider's system and the other OEM'ed to match the hub 100 at its channel ports 212, in step 1452 the caregiver can connect the hub between the devices. In step 1454, the hub 100 reads the memory, provides isolated or non-isolated power, and the cable controller and the hub 100 negotiate a protocol or schema for data delivery. In an embodiment, a controller on the cable may negotiated the protocol, in an alternative embodiment, the controller of the hub 100 negotiates with other processors on the hub the particular protocol. Once the protocol is set, the hub 100 can use, display and otherwise process the incoming data stream in an intelligent manner.

Through the use of the universal medical connectors described herein, connection of a myriad of devices to the hub 100 is accomplished through straightforward programming of a cable connector as opposed to necessitating software upgrades to each device.

FIG. 15 illustrates a perspective view of the hub of FIG. 1 including an exemplary attached board-in-cable ("BIC") to form an input channel according to an embodiment of the disclosure. As shown in FIG. 15, a SEDLine depth of consciousness board communicates data from an appropriate patient sensor to the hub 100 for display and caregiver review. As described, the provider of the board need only use the SDK to describe their data channel, and the hub 100 understands how to present the data to the caregiver.

FIG. 16 illustrates a perspective view of a back side of the hub 100 of FIG. 1, showing an exemplary serial data inputs. In an embodiment, the inputs include such as RJ 45 ports. As is understood in the art, these ports include a data ports similar to those found on computers, network routers, switches and hubs. In an embodiment, a plurality of these ports are used to associate data from various devices with the specific patient identified in the hub 100. FIG. 16 also shows a speaker, the nurse call connector, the Ethernet connector, the USBs, a power connector and a medical grounding lug.

FIG. 17A illustrates an exemplary monitoring environment with communication through the serial data connections of the hub 100 of FIG. 1, according to an embodiment of the disclosure. As shown and as discussed in the foregoing, the hub 100 may use the serial data ports 210 to gather data from various devices within the monitoring environment, including an electronic bed, infusion pumps, ventilators, vital sign monitors, and the like. The difference between the data received from these devices and that received through the channel ports 212 is that the hub 100 may not know the format or structure of this data. The hub 100 may not display information from this data or use this data in calculations or processing. However, porting the data through the hub 100 conveniently associates the data with the specifically monitored patient in the entire chain of caregiver systems, including the foregoing server 214 and backend systems 206. In an embodiment, the hub 100 may determine sufficient information about the incoming data to attempt to synchronize it with data from the hub 100.

In FIG. 17B, a control screen may provide information on the type of data being received. In an embodiment, a green light next to the data indicates connection to a device and on which serial input the connection occurs.

FIG. 18 illustrates a simplified exemplary patient data flow process, according to an embodiment of the disclosure. As shown, once a patient is admitted into the caregiver environment at step 1802, data about the patient is populated on the caregiver backend systems 206. The server 214 may advantageously acquire or receive this information in step 1804, and then make it accessible to the hub 100. When the

15

caregiver at step 1806 assigns the hub 100 to the patient, the caregiver simply looks at the presently available patient data and selects the particular patient being currently monitored. The hub 100 at step 1808 then associates the measurement, monitoring and treatment data it receives and determines with that patient. The caregiver need not again associate another device with the patient so long as that device is communicating through the hub 100 by way of (1) the docking station, (2) the universal medical connectors, (3) the serial data connectors, or (4) other communication mechanisms known to an artisan. At step 1810, some or the entirety of the received, processed and/or determined data is passed to the server systems discussed above.

FIGS. 19A-19J illustrate exemplary displays of anatomical graphics for the portable patient monitor docked with the hub 100 of FIG. 1, according to embodiments of the disclosure. As shown in FIG. 19A, the heart, lungs and respiratory system are shown while the brain is not highlighted. Thus, a caregiver can readily determine that depth of consciousness monitoring or brain oximetry systems are not currently communicating with the hub 100 through the portable patient monitor connection or the channel data ports. However, it is likely that acoustic or other respiratory data and cardiac data is being communicated to or measured by the hub 100. Moreover, the caregiver can readily determine that the hub 100 is not receiving alarming data with respect to the emphasized body portions. In an embodiment, the emphasized portion may animate to show currently measured behavior or, alternatively, animate in a predetermined fashion.

FIG. 19B shows the addition of a virtual channel showing an indication of wellness. As shown in FIG. 19B, the indication is positive as it is a "34" on an increasingly severity scale to "100." The wellness indication may also be shaded to show problems. In contrast to FIG. 19B, FIG. 19C shows a wellness number that is becoming or has become problematic and an alarming heart graphic. Thus, a caregiver responding to a patient alarm on the hub 100 or otherwise on another device or system monitoring or treating the patient can quickly determine that a review of vital signs and other parameters relating to heart function is needed to diagnose and/or treat the patient.

FIGS. 19D and 19E show the brain included in the emphasized body portions meaning that the hub 100 is receiving data relevant to brain functions, such as, for example, depth of sedation data or brain oximetry data. FIG. 19E additionally shows an alarming heart function similar to FIG. 19C.

In FIG. 19F, additional organs, such as the kidneys are being monitored, but the respiratory system is not. In FIG. 19G, an alarming hear function is shown, and in FIG. 19H, an alarming circulatory system is being shown. FIG. 19I shows the wellness indication along with lungs, heart, brain and kidneys. FIG. 19J shows alarming lungs, heart, and circulatory system as well as the wellness indication. Moreover, FIG. 19J shows a severity contrast, such as, for example, the heart alarming red for urgent while the circulatory system alarms yellow for caution. An artisan will recognize other color schemes that are appropriate from the disclosure herein.

FIGS. 20A-20C illustrate exemplary displays of measurement data showing data separation and data overlap, respectively, according embodiments of the disclosure. FIGS. 21A and 21B illustrate exemplary displays of measurement data also showing data separation and data overlap, respectively, according embodiments of the disclosure.

16

For example, acoustic data from an acoustic sensor may advantageously provide breath sound data, while the plethysmograph and ECG or other signals can also be presented in separate waveforms (FIG. 20A, top of the screen capture). The monitor may determine any of a variety of respiratory parameters of a patient, including respiratory rate, expiratory flow, tidal volume, minute volume, apnea duration, breath sounds, riles, rhonchi, stridor, and changes in breath sounds such as decreased volume or change in airflow. In addition, in some cases a system monitors other physiological sounds, such as heart rate to help with probe off detection, heart sounds (S1, S2, S3, S4, and murmurs), and change in heart sounds such as normal to murmur or split heart sounds indicating fluid overload.

Providing a visual correlation between multiple physiological signals can provide a number of valuable benefits where the signals have some observable physiological correlation. As one example of such a correlation, changes in morphology (e.g., envelope and/or baseline) of the plethysmographic signal can be indicative of patient blood or other fluid levels. And, these changes can be monitored to detect hypovolemia or other fluid-level related conditions. A pleth variability index may provide an indication of fluid levels, for example. And, changes in the morphology of the plethysmographic signal are correlated to respiration. For example, changes in the envelope and/or baseline of the plethysmographic signal are correlated to breathing. This is at least in part due to aspects of the human anatomical structure, such as the mechanical relationship and interaction between the heart and the lungs during respiration.

Thus, superimposing a plethysmographic signal and a respiratory signal (FIG. 20B) can give operators an indication of the validity of the plethysmographic signal or signals derived therefrom, such as a pleth variability index. For example, if bursts in the respiration signal indicative of inhalation and exhalation correlate with changes in peaks and valleys of the plethysmographic envelope, this gives monitoring personnel a visual indication that the plethysmographic changes are indeed due to respiration, and not some other extraneous factor. Similarly, if the bursts in the respiration signal line up with the peaks and valleys in the plethysmographic envelope, this provides monitoring personnel an indication that the bursts in the respiration signal are due to patient breathing sounds, and not some other non-targeted sounds (e.g., patient non-breathing sounds or non-patient sounds).

The monitor may also be configured to process the signals and determine whether there is a threshold level of correlation between the two signals, or otherwise assess the correlation. However, by additionally providing a visual indication of the correlation, such as by showing the signals superimposed with one another, the display provides operators a continuous, intuitive and readily observable gauge of the particular physiological correlation. For example, by viewing the superimposed signals, users can observe trends in the correlation over time, which may not be otherwise ascertainable.

The monitor can visually correlate a variety of other types of signals instead of, or in addition to plethysmographic and respiratory signals. For example, FIG. 20C depicts a screen shot of another example monitoring display. As shown in the upper right portion of FIG. 20C, the display superimposes a plethysmographic signal, an ECG signal, and a respiration signal. In other configurations, more than three different types of signals may be overlaid onto one another.

In one embodiment, the hub 100 nothing provides an interface through which the user can move the signals

17

together to overlay on one another. For example, the user may be able to drag the respiration signal down onto the plethysmographic signal using a touch screen interface. Conversely, the user may be able to separate the signals, also using the touch screen interface. In another embodiment, the monitor includes a button the user can press, or some other user interface allowing the user to overlay and separate the signals, as desired. FIGS. 21A and 21B show similar separation and joining of the signals.

In certain configurations, in addition to providing the visual correlation between the plethysmographic signal and the respiratory signal, the monitor is additionally configured to process the respiratory signal and the plethysmographic signal to determine a correlation between the two signals. For example, the monitor may process the signals to determine whether the peaks and valleys in the changes in the envelope and/or baseline of the plethysmographic signal correspond to bursts in the respiratory signal. And, in response to the determining that there is or is not a threshold level of correlation, the monitor may provide some indication to the user. For example, the monitor may provide a graphical indication (e.g., a change in color of pleth variability index indicator), an audible alarm, or some other indication. The monitor may employ one or more envelope detectors or other appropriate signal processing componentry in making the determination.

In certain embodiments, the system may further provide an audible indication of the patient's breathing sounds instead of, or in addition to the graphical indication. For example, the monitor may include a speaker, or an earpiece (e.g., a wireless earpiece) may be provided to the monitoring personnel providing an audible output of the patient sounds. Examples of sensors and monitors having such capability are described in U.S. Pat. Pub. No. 2011/0172561 and are incorporated by reference herein.

In addition to the above described benefits, providing both the acoustic and plethysmographic signals on the same display in the manner described can allow monitoring personnel to more readily detect respiratory pause events where there is an absence of breathing, high ambient noise that can degrade the acoustic signal, improper sensor placement, etc.

FIGS. 22A-22B illustrate exemplary analog display indicia, according to an embodiment of the disclosure. As shown in FIGS. 22A and 22B, the screen shots displays health indicators of various physiological parameters, in addition to other data. Each health indicator can include an analog indicator and/or a digital indicator. In embodiments where the health indicator includes an analog and a digital indicator, the analog and digital indicators can be positioned in any number of formations, such as side-by-side, above, below, transposed, etc. In the illustrated embodiment, the analog indicators are positioned above and to the sides of the digital indicators. As shown more clearly in FIG. 22B, the analog displays may include colored warning sections, dashes indicating position on the graph, and digital information designating quantitate information from the graph. In FIG. 22B, for example, the pulse rate PR graph shows that from about 50 to about 140 beats per minute, the graph is either neutral or beginning to be cautionary, whereas outside those numbers the graph is colored to indicate a severe condition. Thus, as the dash moves along the arc, a caregiver can readily see where in the range of acceptable, cautionary, and extreme the current measurements fall.

Each analog indicator of the health indicator can include a dial that moves about an arc based on measured levels of monitored physiological parameters. As the measured physiological parameter levels increase the dial can move clock-

18

wise, and as the measured physiological parameter levels decrease, the dial can move counter-clockwise, or vice versa. In this way, a user can quickly determine the patient's status by looking at the analog indicator. For example, if the dial is in the center of the arc, the observer can be assured that the current physiological parameter measurements are normal, and if the dial is skewed too far to the left or right, the observer can quickly assess the severity of the physiological parameter levels and take appropriate action. In other embodiments, normal parameter measurements can be indicated when the dial is to the right or left, etc.

In some embodiments, the dial can be implemented as a dot, dash, arrow, or the like, and the arc can be implemented as a circle, spiral, pyramid, or other shape, as desired. Furthermore, the entire arc can be lit up or only portions of the arc can be lit up based on the current physiological parameter measurement level. Furthermore, the arc can turn colors or be highlighted based on the current physiological parameter level. For example, as the dial approaches a threshold level, the arc and/or dial can turn from green, to yellow, to red, shine brighter, flash, be enlarged, move to the center of the display, or the like.

Different physiological parameters can have different thresholds indicating abnormal conditions. For example, some physiological parameters may upper a lower threshold levels, while others only have an upper threshold or a lower threshold. Accordingly, each health indicator can be adjusted based on the physiological parameter being monitored. For example, the SpO2 health indicator can have a lower threshold that when met activates an alarm, while the respiration rate health indicator can have both a lower and upper threshold, and when either is met an alarm is activated. The thresholds for each physiological parameter can be based on typical, expected thresholds and/or user-specified thresholds.

The digital indicator can provide a numerical representation of the current levels of the physiological parameter the digital indicator may indicate an actual level or a normalized level and can also be used to quickly assess the severity of a patient condition. In some embodiments, the display includes multiple health indicators for each monitored physiological parameter. In certain embodiments, the display includes fewer health indicators than the number of monitored physiological parameters. In such embodiments, the health indicators can cycle between different monitored physiological parameters.

FIGS. 23A-23F illustrate exemplary displays of measurement data showing, for example, data presentation in FIGS. 23A-23D when a depth of consciousness monitor is connected to a channel port of the hub of FIG. 1. As shown in FIGS. 23A-23C, the hub 100 advantageously roughly bifurcates its display 104 to show various information from the, for example, SEDLine device, commercially available from Masimo Corp. of Irvine, Calif. In FIG. 23D, the hub 100 includes an attached PhaseIn device, commercially available by PHASEIN AB of Sweden, providing, for example, information about the patient's respiration. The hub 100 also includes the SEDLine information, so the hub 100 has divided the display 104 appropriately. In FIG. 23E, temperature and blood pressure sensors communicate with the hub of FIG. 1 and the hub 100 creates display real estate appropriate for the same. In FIG. 23F, an acoustic sensor is also communicating with the hub of FIG. 1, as well as the forgoing blood pressure and temperature sensor. Accordingly, the hub 100 adjust the display real estate to accommodate the data from each attached device.

19

The term “and/or” herein has its broadest least limiting meaning which is the disclosure includes A alone, B alone, both A and B together, or A or B alternatively, but does not require both A and B or require one of A or one of B. As used herein, the phrase “at least one of” A, B, and C should be construed to mean a logical A or B or C, using a non-exclusive logical or.

The term “plethysmograph” includes its ordinary broad meaning known in the art which includes data responsive to changes in volume within an organ or whole body (usually resulting from fluctuations in the amount of blood or air it contains).

The following description is merely illustrative in nature and is in no way intended to limit the disclosure, its application, or uses. For purposes of clarity, the same reference numbers will be used in the drawings to identify similar elements. It should be understood that steps within a method may be executed in different order without altering the principles of the present disclosure.

As used herein, the term module may refer to, be part of, or include an Application Specific Integrated Circuit (ASIC); an electronic circuit; a combinational logic circuit; a field programmable gate array (FPGA); a processor (shared, dedicated, or group) that executes code; other suitable components that provide the described functionality; or a combination of some or all of the above, such as in a system-on-chip. The term module may include memory (shared, dedicated, or group) that stores code executed by the processor.

The term code, as used above, may include software, firmware, and/or microcode, and may refer to programs, routines, functions, classes, and/or objects. The term shared, as used above, means that some or all code from multiple modules may be executed using a single (shared) processor. In addition, some or all code from multiple modules may be stored by a single (shared) memory. The term group, as used above, means that some or all code from a single module may be executed using a group of processors. In addition, some or all code from a single module may be stored using a group of memories.

The apparatuses and methods described herein may be implemented by one or more computer programs executed by one or more processors. The computer programs include processor-executable instructions that are stored on a non-transitory tangible computer readable medium. The computer programs may also include stored data. Non-limiting examples of the non-transitory tangible computer readable medium are nonvolatile memory, magnetic storage, and optical storage. Although the foregoing invention has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the reaction of the preferred embodiments, but is to be defined by reference to claims.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application was specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A medical monitoring hub configured to monitor physiological parameters of a single patient, the medical monitoring hub comprising:

20

a plurality of communication ports, wherein each of the plurality of communication ports is configured to:
accept data from respective electronic devices monitoring a single patient, and
provide isolated or non-isolated power to the respective electronic devices;

a display;

a housing positioning the display and the communication ports; and

one or more processors configured to execute instructions in order to:

receive, from an electronic memory, information indicating power requirements associated with an electronic device that is plugged into a communication port of the plurality of communication ports;

determine, based on the information, whether or not isolated power is required by the electronic device; and

provide, via the communication port and based on determining whether or not isolated power is required by the electronic device, isolated or non-isolated power to the electronic device.

2. The medical monitoring hub of claim 1, wherein one or more of the communication ports comprises a channel port.

3. The medical monitoring hub of claim 2, wherein the channel port provides optional non-isolated power.

4. The medical monitoring hub of claim 2, wherein the channel port communicates with the electronic memory to configure the medical monitoring hub to receive the information without reprogramming software of the medical monitoring hub.

5. The medical monitoring hub of claim 1, wherein the non-isolated power comprises a plurality of power levels, and wherein the one or more processors is further configured to execute instructions in order to:

determine, based on the information, a power level of the plurality of power levels required by the electronic device; and

provide, via the communication port and based on determining the power level, non-isolated power at the power level to the electronic device.

6. The medical monitoring hub of claim 5, wherein the communication port comprises a connector and wherein the connector includes a non-linear path between isolated and non-isolated conductors.

7. The medical monitoring hub of claim 5, wherein the communication port comprises a connector and wherein a distance between an isolated conductor and a non-isolated conductor of the connector is shorter than a periphery of a cable connector housing between the conductors.

8. The medical monitoring hub of claim 5, wherein the one or more processors are further configured to execute instructions in order to:

reorganize information on the display to include data from the communication port when the electronic device is connected thereto.

9. A method of configuring a medical monitoring hub, the method comprising:

receiving, from an electronic memory and at a medical monitoring hub comprising a plurality of communication ports, information indicating power requirements associated with an electronic device that is plugged into a communication port of the plurality of communication ports, wherein each of the plurality of communication ports is configured to:

accept data from respective electronic devices monitoring a single patient, and

21

provide isolated or non-isolated power to the respective electronic devices;

determining, based on the information, whether or not isolated power is required by the electronic device; and

providing, via the communication port and based on determining whether or not isolated power is required by the electronic device, isolated or non-isolated power to the electronic device.

10. The method of claim **9**, wherein one or more of the communication ports comprises a channel port.

11. The method of claim **10**, wherein the channel port is configured to provide optional non-isolated power.

12. The method of claim **10**, wherein the channel port communicates with the electronic memory to configure the medical monitoring hub to receive the information without reprogramming software of the medical monitoring hub.

13. The method of claim **9**, wherein the non-isolated power comprises a plurality of power levels, and wherein the method further comprises:

22

determining, based on the information, a power level of the plurality of power levels required by the electronic device; and

providing, via the communication port and based on determining the power level, non-isolated power at the power level to the electronic device.

14. The method of claim **13**, wherein the communication port comprises a connector and wherein the connector includes a non-linear path between isolated and non-isolated conductors.

15. The method of claim **13**, wherein the communication port comprises a connector and wherein a distance between an isolated conductor and a non-isolated conductor of the connector is shorter than a periphery of a cable connector housing between the conductors.

16. The method of claim **13** further comprising: reorganizing information on a display of the medical monitoring hub to include data from the communication port when the electronic device is connected thereto.

* * * * *