



US010799745B2

(12) **United States Patent**
Bayerlein et al.

(10) **Patent No.:** **US 10,799,745 B2**

(45) **Date of Patent:** ***Oct. 13, 2020**

(54) **MANUAL TREADMILL AND METHODS OF OPERATING THE SAME**

(71) Applicant: **Woodway USA, Inc.**, Waukesha, WI (US)

(72) Inventors: **Douglas G. Bayerlein**, Oconomowoc, WI (US); **Vance E. Emons**, Hartland, WI (US); **Nicholas A. Oblamski**, Waukesha, WI (US); **Scott D. Hoerig**, Brookfield, WI (US); **Matthew J. Zank**, Milwaukee, WI (US); **Robert L. Zimpel**, Menomonee Falls, WI (US); **Joel W. Richards**, Wauwatosa, WI (US)

(73) Assignee: **Woodway USA, Inc.**, Waukesha, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/792,426**

(22) Filed: **Feb. 17, 2020**

(65) **Prior Publication Data**

US 2020/0254293 A1 Aug. 13, 2020

Related U.S. Application Data

(63) Continuation of application No. 15/958,339, filed on Apr. 20, 2018, now Pat. No. 10,561,884, which is a (Continued)

(51) **Int. Cl.**

A63B 21/005 (2006.01)

A63B 22/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A63B 21/0053** (2013.01); **A63B 21/0054** (2015.10); **A63B 21/0055** (2015.10);

(Continued)

(58) **Field of Classification Search**

CPC **A63B 22/02-0292**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

X8308 I1 8/1851 Seymour

219,439 A 9/1879 Blend

(Continued)

FOREIGN PATENT DOCUMENTS

CN 3201120 9/2001

CN 2860541 1/2007

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 61/280,265, filed Nov. 2, 2009, Astilean, Aurel A.

(Continued)


Primary Examiner — Jennifer Robertson

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

A treadmill includes a frame; a front running belt pulley; a rear running belt pulley; a plurality of bearings coupled to the frame; a running belt at least partially supported by at least one of the front running belt pulley and the rear running belt pulley, the running belt including a running surface, at least a portion of which is curved; a support element coupled to the frame; and a safety device coupled to the running belt. The safety device is at least partly supported by the support element. The running belt freely rotates in a first direction of rotation relative to the frame, however, in a second direction of rotation, opposite the first direction of rotation, engage-

(Continued)



ment between the support element and at least a portion of the safety device substantially prevents rotation the running belt relative to the frame.

27 Claims, 20 Drawing Sheets

Related U.S. Application Data

continuation of application No. 14/832,708, filed on Aug. 21, 2015, now Pat. No. 10,265,566, which is a continuation of application No. 14/076,912, filed on Nov. 11, 2013, now Pat. No. 9,114,276, which is a continuation of application No. 13/235,065, filed on Sep. 16, 2011, now abandoned, which is a continuation-in-part of application No. PCT/US2010/027543, filed on Mar. 16, 2010.

(60) Provisional application No. 61/161,027, filed on Mar. 17, 2009.

(51) Int. Cl.

A63B 21/00 (2006.01)

A63B 22/02 (2006.01)

A63B 23/04 (2006.01)

(52) U.S. Cl.

CPC *A63B 21/157* (2013.01); *A63B 22/0017* (2015.10); *A63B 22/0023* (2013.01); *A63B 22/02* (2013.01); *A63B 22/0235* (2013.01); *A63B 22/0285* (2013.01); *A63B 23/04* (2013.01); *A63B 2230/06* (2013.01); *A63B 2230/75* (2013.01)

(56) References Cited

U.S. PATENT DOCUMENTS

411,986 A 10/1889 Frazeur et al.
641,424 A 1/1900 Taitel et al.
759,296 A 5/1904 Morairty
767,221 A 8/1904 Hagen
783,769 A 2/1905 Wright
931,394 A 8/1909 Day
1,211,765 A 1/1917 Schmidt
2,117,957 A 5/1938 Heller
2,399,915 A 5/1946 Drake
2,512,911 A * 6/1950 Benice A63B 21/153
482/72
2,842,365 A 7/1958 Kelley
3,637,206 A 1/1972 Chickering, III
3,642,279 A * 2/1972 Cutter A63B 22/02
482/54
3,870,297 A 3/1975 Elder
3,968,543 A 7/1976 Shino et al.
4,334,676 A * 6/1982 Schonenberger A63B 22/02
482/54
4,389,047 A 6/1983 Hall
4,406,451 A 9/1983 Gaetano
4,544,152 A 10/1985 Taitel
4,548,405 A 10/1985 Lee et al.
4,576,352 A 3/1986 Ogden
4,614,337 A 9/1986 Schonenberger
4,635,928 A 1/1987 Ogden et al.
4,659,074 A 4/1987 Taitel et al.
4,726,581 A 2/1988 Chang
4,886,266 A 12/1989 Trulaske
4,938,469 A 7/1990 Crandell
5,031,901 A 7/1991 Saarinen
5,094,447 A 3/1992 Wang
5,145,480 A 9/1992 Wang
5,162,988 A 11/1992 Semerau et al.
5,242,339 A 9/1993 Thornton

5,290,205 A 3/1994 Densmore et al.
5,310,392 A 5/1994 Lo
5,318,487 A 6/1994 Golen et al.
5,368,532 A 11/1994 Farnet
5,378,213 A 1/1995 Quint
5,411,279 A 5/1995 Magid
5,411,455 A 5/1995 Haber et al.
5,431,612 A 7/1995 Holden
5,470,293 A 11/1995 Schonenberger
5,492,517 A * 2/1996 Bostic A63B 21/015
482/110
5,575,740 A 11/1996 Piaget et al.
5,577,598 A 11/1996 Schoenenberger
5,607,376 A * 3/1997 Magid A47D 13/04
482/54
5,643,144 A 7/1997 Trulaske
5,669,856 A 9/1997 Liu
5,683,332 A 11/1997 Watterson et al.
5,688,209 A 11/1997 Trulaske et al.
5,709,632 A 1/1998 Socwell
5,856,736 A 1/1999 Rotunda et al.
5,887,579 A 3/1999 Eriksson et al.
5,897,461 A 4/1999 Socwell
6,042,514 A 3/2000 Abelbeck
6,053,848 A 4/2000 Eschenbach
6,095,952 A 8/2000 Ali et al.
6,146,315 A 11/2000 Schonenberger
6,152,854 A 11/2000 Carmein
6,180,210 B1 1/2001 Debus
6,328,676 B1 12/2001 Alessandri
6,334,836 B1 1/2002 Segasby
6,334,839 B1 1/2002 Lim et al.
6,348,025 B1 2/2002 Schonenberger
6,454,679 B1 9/2002 Radow
6,468,189 B2 10/2002 Alessandri
6,500,097 B1 12/2002 Hall
6,616,578 B2 9/2003 Alessandri
6,652,424 B2 11/2003 Dalebout
6,740,009 B1 5/2004 Hall
6,824,502 B1 11/2004 Huang
6,837,830 B2 1/2005 Eldridge
6,893,382 B1 5/2005 Moon et al.
6,923,746 B1 8/2005 Skowronski et al.
7,090,620 B1 8/2006 Barlow
7,115,073 B2 10/2006 Nizamuddin
7,179,205 B2 2/2007 Schmidt
D562,416 S 2/2008 Fedriga et al.
D566,209 S 4/2008 Alessandri et al.
7,410,449 B2 8/2008 Yeh
7,560,822 B1 7/2009 Hoffmann
7,608,023 B2 10/2009 Casagrande
7,618,345 B2 11/2009 Corbalis et al.
7,717,828 B2 5/2010 Simonson et al.
7,780,573 B1 8/2010 Carmein
7,789,800 B1 9/2010 Watterson et al.
7,806,805 B2 10/2010 Barufka et al.
7,837,596 B2 11/2010 Astilean
7,862,483 B2 1/2011 Hendrickson et al.
8,007,422 B2 8/2011 Zaccherini
8,075,450 B2 12/2011 Fabbri et al.
8,206,269 B2 6/2012 Fabbri et al.
8,241,187 B2 8/2012 Moon et al.
8,308,619 B1 11/2012 Astilean
D672,827 S 12/2012 Alessandri et al.
8,343,016 B1 1/2013 Astilean
D682,372 S 5/2013 Alessandri et al.
8,496,566 B2 7/2013 Casadei
8,512,209 B2 8/2013 Guidi et al.
8,585,561 B2 11/2013 Watt et al.
8,676,170 B2 3/2014 Porra et al.
8,690,738 B1 4/2014 Astillan
8,734,300 B2 5/2014 Piaget et al.
8,864,627 B2 10/2014 Bayerlein et al.
8,876,668 B2 11/2014 Hendrickson et al.
8,920,347 B2 12/2014 Bayerlein et al.
9,005,085 B2 4/2015 Astilean
9,044,635 B2 6/2015 Lull
D736,866 S 8/2015 Oblamski et al.
9,192,810 B2 11/2015 Beard et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,233,272 B2 1/2016 Villani et al.
 9,254,409 B2 2/2016 Dalebout et al.
 D751,156 S 3/2016 Tasca et al.
 9,305,141 B2 4/2016 Fabrizio
 9,314,667 B2 4/2016 Puerschel
 9,352,188 B2 5/2016 Astilean
 9,429,511 B1 8/2016 Kannel
 D788,792 S 6/2017 Alessandri et al.
 9,694,234 B2 7/2017 Dalebout et al.
 9,824,110 B2 11/2017 Giudici et al.
 9,914,015 B2 3/2018 Astilean et al.
 9,974,997 B2 5/2018 Cei
 D820,362 S 6/2018 Citterio
 10,010,748 B1 7/2018 Weinstein et al.
 D827,058 S 8/2018 Lisi et al.
 D837,312 S 1/2019 Lisi et al.
 10,183,191 B2 1/2019 Astilean et al.
 10,293,204 B2 5/2019 Astilean et al.
 10,478,666 B2 11/2019 Yoo
 10,561,883 B2* 2/2020 Bayerlein A63B 21/0053
 2002/0147079 A1 10/2002 Kalnbach
 2003/0148853 A1 8/2003 Alessandri et al.
 2003/0186787 A1 10/2003 Wu et al.
 2004/0018917 A1 1/2004 Corbalis et al.
 2004/0077465 A1 4/2004 Schmidt
 2004/0097341 A1 5/2004 Alessandri et al.
 2004/0241631 A1 12/2004 Nizamuddin
 2004/0242631 A1 12/2004 Garlich et al.
 2005/0009668 A1 1/2005 Savettieri et al.
 2005/0202936 A1 9/2005 Ota
 2005/0209059 A1 9/2005 Crawford et al.
 2005/0272562 A1 12/2005 Alessandri et al.
 2006/0003871 A1 1/2006 Houghton et al.
 2006/0003872 A1 1/2006 Chiles et al.
 2006/0122035 A1 6/2006 Felix
 2006/0287165 A1 12/2006 Pasqualin
 2007/0021278 A1 1/2007 Pan et al.
 2007/0027001 A1 2/2007 Alessandri et al.
 2007/0123396 A1 5/2007 Ellis
 2007/0167289 A1 7/2007 Alessandri et al.
 2007/0202995 A1 8/2007 Roman et al.
 2007/0225130 A1 9/2007 Maffei et al.
 2007/0298935 A1 12/2007 Badarneh et al.
 2008/0015094 A1 1/2008 Casagrande
 2008/0020907 A1 1/2008 Lin
 2008/0119332 A1 5/2008 Roman
 2008/0132385 A1 6/2008 Alessandri et al.
 2008/0287266 A1 11/2008 Smith
 2009/0105047 A1 4/2009 Guidi et al.
 2009/0156363 A1 6/2009 Guidi et al.
 2009/0170666 A1 7/2009 Chiang
 2009/0215589 A1 8/2009 Schoenenberger
 2009/0280960 A1 11/2009 Tian
 2010/0087298 A1 4/2010 Zaccherini
 2010/0216607 A1 8/2010 Mueller
 2010/0222182 A1 9/2010 Park
 2011/0027549 A1 2/2011 Boutaghou
 2011/0266091 A1 11/2011 Taylor
 2011/0275497 A1 11/2011 Lorusso
 2012/0010048 A1 1/2012 Bayerlein et al.
 2012/0019973 A1 1/2012 Ehrmantraut et al.
 2012/0157267 A1 6/2012 Lo
 2012/0231934 A1 9/2012 Lo
 2012/0264569 A1 10/2012 Escobedo et al.
 2012/0270705 A1 10/2012 Lo
 2014/0011642 A1 1/2014 Astilean
 2014/0080679 A1 3/2014 Bayerlein et al.
 2014/0087922 A1 3/2014 Bayerlein et al.
 2014/0171272 A1 6/2014 Hawkins et al.
 2015/0119202 A1 4/2015 Hendrickson et al.
 2015/0157895 A1 6/2015 Bettini
 2015/0306456 A1 10/2015 Pasini et al.
 2015/0367175 A1 12/2015 Alessandri et al.
 2016/0023039 A1 1/2016 Cei
 2016/0096064 A1 4/2016 Gatti

2016/0166877 A1 6/2016 Cei et al.
 2016/0263429 A1 9/2016 Wagner
 2016/0296789 A1 10/2016 Astilean et al.
 2016/0367851 A1 12/2016 Astilean et al.
 2017/0007886 A1 1/2017 Alessandri
 2017/0113093 A1 4/2017 Bellavista et al.
 2017/0182356 A1 6/2017 Cei et al.
 2017/0274248 A1 9/2017 Brown et al.
 2017/0312582 A1 11/2017 Root, Jr.
 2018/0001134 A1 1/2018 Bayerlein et al.
 2018/0014755 A1 1/2018 Alessandri et al.
 2018/0111023 A1 4/2018 Cei et al.
 2018/0229065 A1 8/2018 Leonardi et al.
 2019/0054344 A1 2/2019 Athey et al.
 2019/0083843 A1 3/2019 Del Monaco et al.
 2019/0168067 A1 6/2019 Bates et al.
 2020/0188760 A1 6/2020 Bandini et al.
 2020/0215391 A1 7/2020 Paganelli et al.

FOREIGN PATENT DOCUMENTS

CN 201006229 1/2008
 CN 201030178 3/2008
 CN 201333278 10/2009
 CN 102309835 A 1/2012
 DE 10 2005 009 414 9/2006
 DE 20-2006-005995 9/2006
 EP 1 466 651 A1 10/2004
 GB 2 223 685 A 4/1990
 JP 03-148743 6/1991
 JP 3148743 2/2009
 KR 2009007043 1/2009
 KR 10-2016-0150084 A 12/2016
 WO WO-2009/014330 A1 1/2009
 WO WO-2010/057238 A2 5/2010
 WO WO-2010/107632 9/2010
 WO WO-2014/160057 10/2014
 WO WO-2016/163680 A1 10/2016

OTHER PUBLICATIONS

Andrews et al., The Effect of an 80-Minute Intermittent Running Protocol on Hamstrings Strength Abstract, NSCA Presentation, Jul. 15, 2006, 1 page.
 Answer to Counterclaims filed Nov. 14, 2014 between Speedfit LLC and Aurel Astilean versus Woodway USA, Inc., 8 pages.
 Astilean, Alex, YouTube Video entitled "SpeedFit—Speedboard—First Curve Prototype" retrieved from the internet at: <https://www.youtube.com/watch?v=dO9h-F-JVCU> on Apr. 6, 2015, 49 pages of screenshots.
 Biodex Medical Systems, Inc., "The Biodex RTM Rehabilitation Treadmill Operation Manual", believed to have published 2002, 48 pages.
 Brughelli et al., Effects of Running Velocity on Running Kinetics and Kinematics, Journal of Strength and Conditioning Research, Apr. 2011, 7 pages.
 Buchheit et al., "Assessing Stride Variables and Vertical Stiffness with GPS-Embedded Accelerometers: Preliminary Insights for Monitoring of Neuromuscular Fatigue on the Field", Dec. 2015.
 Chapco, Inc. and Samsara Fitness LLC's notice pursuant to 34 U.S.C. §282, Case 3:15-cv-01665-JCH, Document 310, filed Sep. 14, 2018, 4 pps.
 Claim Construction Order, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:13-cv-01276-KAM-AKT, Nov. 20, 2017, 23 pages.
 Complaint for Declaratory Judgment of Patent Invalidity and Correction of Inventorship, *Woodway USA, Inc. v. Aurel A. Astilean*, Civ. Dkt. No. 2:13-cv-00681-WEC (E.D. WI), Jun. 13, 2013, 6 pages.
 Coolthings, "Woodway EcoMill: A Non-Motorized Treadmill with Electronic Displays", Jun. 4, 2009, <https://www.coolthings.com/woodway-ecomill-a-non-motorized-treadmill-with-electronic-displays/>, 1 page.
 Curvature, <http://en.wikipedia.org/wiki/Curvature>, Mar. 3, 2010, 1 page.

(56)

References Cited**OTHER PUBLICATIONS**

Decision and Order Denying Defendant's Motion to Dismiss or to Transfer and Staying Case Pending Decision from Eastern District New York District Court, *Woodway USA, Inc. v. Aurel A. Astilean*, Civ. Dkt. No. 2:13-cv-00681-WEC (E.D. WI), Dec. 18, 2013, 7 pages.

Declaration of Aurel A. Astilean filed Jun. 15, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.* and Exhibit A.

Declaration of Aurel A. Astilean, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Exhibit 1, Mar. 26, 2018, 5 pages.

Declaration of Dan Bostan filed Jun. 15, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.* and Exhibit A.

Declaration of John F. Vodopia filed Jun. 6, 2017.

Declaration of John F. Vodopia in Further Support of Plaintiffs' Motion for Leave to Amend filed Jul. 7, 2015 and Exhibits A-C.

Declaration of John F. Vodopia in Support of Plaintiffs' motion for Leave to Amend filed Jul. 7, 2017 and Exhibits A-F.

Declaration of John F. Vodopia in Support of Plaintiffs' Motion Under 35 USC 256 to Correct Inventorship of U.S. Pat. No. 8,308,619 and U.S. Pat. No. 8,342,016 filed Jun. 15, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.* and Exhibits A-H.

Declaration of Kadie M. Jelenchick filed Jul. 7, 2015 and Exhibits A-G.

Declaration of Kadie M. Jelenchick filed Jun. 15, 2015 and Exhibits A, B and E.

Declaration of Kadie M. Jelenchick filed Jun. 6, 2017.

Declaration of Matthew W. Peters, Case 2:13-cv-01276-KAM-AKT, Document 213, filed Aug. 8, 2018, 2 pps.

Declaration of Nicholas Oblamski filed Jun. 15, 2015, and Exhibit A, 11 pages.

Declaration of Nicholas Oblamski, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Exhibit 1, Mar. 26, 2018, 12 pages.

Declaration of Robert Giachetti, Case 3:15-CV-01665-JCH, Document 88-2, filed May 1, 2017, 20 pps., marked on its face as Exhibit 1.

Declaration of Thomas B. Decea filed Nov. 19, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*

Defendant Woodway USA, Inc.'s responses and objections to plaintiffs' first set of interrogatories, Case 3:15-CV-01665-JCH, Document 254-22, 17 pps., marked on its face as Exhibit 22.

Discovery Channel, "Wreckreation Nation", Season 1, Episode 8, first aired Feb. 24, 2009, 9 pages of screenshot excerpts.

Docket Report, *Speedfit LLC and Aurel A. Astilean v. Douglas G. Bayerlein*, Civ. Dkt. No. 2:13-cv-01276-KAM-AKT (E.D.N.Y.), Dec. 19, 2013, 8 pages.

Docket Report, *Woodway USA, Inc. v. Aurel A. Astilean*, Civ. Dkt. No. 2:13-cv-00681-WEC (E.D. WI), Dec. 19, 2013, 3 pages.

EMS-Grivory Grivory GV-5H Black 9915 Nylon Copolymer, 50% Glass Fiber Filled, as Conditioned, believed to be publically available before Sep. 16, 2011, 2 pages.

Excerpt from U.S. Appl. No. 14/076,912, Exhibit F, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Mar. 26, 2018, 4 pages.

Expert report of Dr. Robert Giachetti, Case 3:15-CV-01665-JCH, Document 216-2, filed Apr. 5, 2018, 31 pps., marked on its face as Exhibit 2.

Expert report of James D. Whelan, P.E., report dated Aug. 26, 2015, Case 2:13-cv-01276-KAM-AKT, Document 212-2, filed Aug. 8, 2018, 19 pps., marked on its face as Exhibit 2.

Expert report of James D. Whelan, P.E., report dated Jul. 27, 2015, Case 2:13-cv-01276-KAM-AKT, Document 212-1, filed Aug. 8, 2018, 62 pps., marked on its face as Exhibit 1.

Expert report of James D. Whelan, P.E., report dated Jun. 12, 2018, 30 pps.

Expert report of James D. Whelan, P.E., report dated Sep. 28, 2018, 10 pps.

Expert Report of Kim B. Blair, Ph.D., Case 3:15-CV-01665-JCH, Document 254-7, filed Jun. 8, 2018, 135 pps., marked on its face as Exhibit 7.

First Amended Complaint (Jury Trial Demanded), *Speedfit LLC and Aurel A. Astilean v. Douglas G. Bayerlein*, Civ. Dkt. No. 2:13-cv-01276-KAM-AKT (E.D.N.Y.), Jun. 17, 2013, 16 pages.

First Amended Complaint filed Jun. 17, 2013 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 16 pages.

Foreign Action other than Search Report on CA 3029593 dated Nov. 21, 2019.

Hall, The Rotary Treadwheel, available at least as early as Nov. 2011, 1 page.

HDT Expeditionary Systems, Inc., "KineAssist-MX Owner's Manual vG", 2015, 73 pages.

Hersher, Perfect Landing, <http://news.harvard.edu/gazette/story/2010/01/different-strokes/>, Jan. 27, 2010, 5 pages.

Hopker et al., Familiarisation and Reliability of Sprint Test Indices During Laboratory and Field Assessment, *Journal of Sports Science and Medicine*, Dec. 1, 2009, 5 pages.

<http://www.gettyimages.com/detail/463782507>, Animal treadmill c. 1872, Museum of Science and Industry, Chicago, 3 pps.

<http://www.gettyimages.com/license/542395667>, 1930 era treadmill, 1 page.

http://www.mpiwg-berlin.mpg.de/resrep00_01/Jahresbericht_2_2_section.html, 27 pps.

Integrated Performance Systems, LLC, Conditioning in a Professional Athlete Case Study, 2005, 1 page.

Integrated Performance Systems, LLC, Lower Extremity Rehabilitation & Assessment Case Study, 2005, 2 pages.

Integrated Performance Systems, LLC, Youth Athlete-Speed Training Case Study, 2005, 2 pages.

International Preliminary Report for Application No. PCT/US2010/026731, dated Sep. 29, 2011, 7 pages.

International Preliminary Report for Application No. PCT/US2010/027543, dated Sep. 29, 2011, 9 pages.

International Search Report and Written Opinion for Application No. PCT/US2010/026731, dated May 4, 2010, 8 pages.

International Search Report and Written Opinion for Application No. PCT/US2010/027543, dated May 12, 2010, 10 pages.

International Search Report and Written Opinion for International Application No. PCT/US2016/055572, dated Feb. 17, 2017, 9 pages.

International Search Report, PCT/US2017/040449, dated Oct. 11, 2017, 6 pages.

International Standard ISO 20957-6:2005(E), for Stationary training equipment—Part 6: Treadmills, additional specific safety requirements and test methods, First edition May 1, 2005, 18pps.

Introducing the New Force 3 Treadmill Advanced Analysis Package, www.fittech.com.au, believed to be publically available before Sep. 16, 2011, 3 pages.

Joint Disputed Claim filed Apr. 19, 2017 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 10 pages.

Lieberman et al., Running Barefoot, Forefoot Striking & Training Tips, <http://www.barefootrunning.fas.harvard.edu/5BarefootRunning&TrainingTips.html>, Feb. 26, 2010, 5 pages.

Lieberman et al., Running Barefoot: Biomechanics of Foot Strike, <http://www.barefootrunning.fas.harvard.edu/4BiomechanicsofFootStrike.html>, Feb. 26, 2010, 6 pages.

Lieberman et al., Running Barefoot: Biomechanics of Foot Strikes & Applications to Running Barefoot or in Minimal Footwear, <http://www.barefootrunning.fas.harvard.edu/index.html>, Feb. 26, 2010, 2 pages.

Lieberman et al., Running Barefoot: FAQ, <http://www.barefootrunning.fas.harvard.edu/6FAQ.html>, Feb. 26, 2010, 3 pages.

Lieberman et al., Running Barefoot: Heel Striking & Running Shoes, <http://www.barefootrunning.fas.harvard.edu/2FootStrikes&RunningShoes.html>, Feb. 26, 2010, 2 pages.

Lieberman et al., Running Barefoot: Running Before the Modern Shoe, <http://www.barefootrunning.fas.harvard.edu/3RunningBeforeTheModernShoe.html>, Feb. 26, 2010, 4 pages.

Lieberman et al., Running Barefoot: Why Consider Foot Strike, <http://www.barefootrunning.fas.harvard.edu/1WhyConsiderFootStrike.html>, Feb. 26, 2010, 1 page.

(56)

References Cited**OTHER PUBLICATIONS**

Liszewski, Andrew, "EcoMill Treadmill Generates Its Own Power", Jun. 1, 2009, <http://www.ohgizmo.com/2009/06/04/ecomill-treadmill-generates-its-own-power/>, 1 page.

Memorandum and Order filed Dec. 28, 2016 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 22 pages.

Memorandum and Order filed Oct. 10, 2014 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 39 pages.

Memorandum and Order filed Oct. 19, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 11 pages.

Memorandum of Law in Support of Plaintiffs' Motion for Leave to Amend the Second Amended Complaint filed Jul. 7, 2015, 13 pages.

Memorandum of Law in Support of Plaintiffs' Motion Under 35 USC 256 to Correct Inventorship of U.S. Pat. No. 8,308,619 and U.S. Pat. No. 8,342,016 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 14 pages.

Minute Entry and Order for Markman Hearing, dated Jun. 13, 2018, 2 pps.

Minute Entry for Proceedings on Nov. 10, 2015 and Exhibit G.

Minute Order Regarding Claim Construction, *Speedfit LLC v. Woodway*, Docket No. 2:17-cv-00768-KAM-AKT, Jun. 13, 2018, 2 pages.

Moody, The Effects Resisted Sprint Training on Speed, Agility and Power Production in Young Athletes, believed to be publically available before Dec. 31, 2006, 5 pages.

Motion to Dismiss filed Oct. 30, 2015 and Exhibits A-H.

NASA, "Combined Operational Load Bearing External Resistance Treadmill (COLBERT)", Aug. 2009, 3 pages.

NASA, "International Space Station: Combined Operational Load Bearing External Resistance Treadmill (COLBERT)", Jul. 19, 2017, https://www.nasa.gov/mission_pages/station/research/experiments/765.html, 4 pages.

NASA, "International Space Station: Do Tread on Me", Aug. 19, 2009, https://www.nasa.gov/mission_pages/station/behindscenes/colbert_feature.html, 2 pages.

NASA, "International Space Station: Treadmill with Vibration Isolation and Stabilization System (TVIS)", May 17, 2018, https://www.nasa.gov/mission_pages/station/research/experiments/976.html, 5 pages.

NASA, "Space Shuttle Mission STS-128: Racking Up New Science", Press Kit, Aug. 2009, 116 pages.

Nexus Resin Group, 10124 Antistat, believed to be publically available before Sep. 16, 2011, 2 pages.

Non-Final Office Action on U.S. Appl. No. 15/958,339 dated Aug. 5, 2019.

Notice of Motion filed Jul. 7, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 2 pages.

Notice of Motion Under 35 USC 256 to Correct Inventorship of U.S. Pat. No. 8,308,619 and U.S. Pat. No. 8,342,016 filed Jun. 15, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 3 pages.

Notice of Woodway USA, Inc.'s Motion for Summary Judgment of Invalidity of U.S. Pat. No. 8,308,619 and U.S. Pat. No. 8,343,016 filed Jun. 5, 2017, 9 pages.

Notice of Woodway USA, Inc.'s motion to preclude the testimony of plaintiffs' technical expert James Whelan, Case 2:13-cv-01276-KAM-AKT, Document 211, filed Aug. 8, 2018, 3 pps.

Opening expert report of Dr. Robert Giachetti re: invalidity of U.S. Pat. No. 8,986,169 and U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 216-1, filed Apr. 5, 2018, 67 pps., marked on its face as Exhibit 1.

Order Denying Motion for Reconsideration (Doc. No. 248), dated Jun. 20, 2018, 12 pps.

OSHA 1926.307, 9 pps.

Owners Manual for NordicTrack WalkFit Classic Treadmill, 30 pps.

Owners Manual, Force 1, Nov. 29, 2007, 44 pages.

Owners Manual, Force 3, Jan. 28, 2009, 45 pages.

Owners Manual, The Force, Dec. 18, 2008, 68 pages.

Photographs of public display of Speedfit Speedboard by Woodway presented at IHRSA Tradeshow on Mar. 17, 2009, 8 pages.

Photographs produced to Woodway at least by Nov. 10, 2014 in litigation, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, No. 2:13-cv-01276-KAM-AKT, 11 pages.

Plaintiff's memorandum in support of motion for summary judgment of non-infringement and invalidity on Claim 25 of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 253, filed Jun. 8, 2018, 45 pps.

Plaintiff's Reply to Defendant Woodway's Answer, Affirmative Defenses and Counterclaims to Plaintiff's Second Amended Complaint filed Mar. 27, 2015, 6 pages.

Plaintiff's Reply to Defendant Woodway's Answer, Affirmative Defenses and Counter-Claims to Plaintiffs' Supplemental Complaint filed Mar. 17, 2017, 8 pages.

Plaintiff's supplemental responses and objections to defendant's first set of interrogatories, Case 2:17-cv-00768-KAM-AKT, Document 38-3, filed Mar. 14, 2018, 22 pps., marked on its face as Exhibit C.

Plaintiffs Memorandum of Law in Opposition to Woodway's Motion for Summary Judgment of Invalidity and Opening Claim Construction Brief, Cross-Motion for Summary Judgment Upholding Validity, Cross-Motion for Summary Judgment for Infringement and Motion to Extend the Page Limitation for this Memorandum filed Jun. 6, 2017, 46 pages.

Plaintiffs' Initial Claims Construction Memorandum filed Jul. 31, 2017.

Plaintiffs' Local Rule 56(a)1 statement of undisputed material facts, Case 3:15-CV-01665-JCH, Document 254, filed Jun. 8, 2018, 14 pps.

Plaintiffs' Local Rule 56(a)2 statement of facts in opposition to summary judgment, Case 3:15-CV-01665-JCH, Document 265, filed Jun. 29, 2018, 17 pps.

Plaintiffs' Memorandum of Law in further Opposition to Defendant's Motion to Dismiss Certain of Plaintiffs' Claims filed Nov. 19, 2015, 19 pages.

Plaintiffs' memorandum of law in support of their motion for partial reconsideration, Case 3:15-CV-01665-JCH, Document 249, filed May 8, 2018, 9 pps.

Plaintiffs' motion for partial reconsideration, Case 3:15-CV-01665-JCH, Document 248, filed May 7, 2018, 3 pps.

Plaintiffs' motion for summary judgment of non-infringement and invalidity on Claim 25 of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 252, 2 pps.

Plaintiffs' Opposition to Woodway USA, Inc.'s motion for summary judgment of infringement on Claim 25 of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 264, filed Jun. 29, 2018, 35 pps.

Plaintiffs' preliminary invalidity contentions, Case 3:15-CV-01665-JCH, Document 254-16, filed Jun. 8, 2018, 205 pps., marked on its face as Exhibit 16.

Plaintiffs' preliminary non-infringement contentions, Case 3:15-cv-01165-JCH, Document 96-3, filed May 2, 2017, 56 pps.

Plaintiffs' Reply in Support of motion for partial reconsideration, Case 3:15-CV-01665-JCH, Document 251, filed May 29, 2018, 4 pps.

Plaintiffs' supplemental non-infringement contentions, Case 3:15-CV-01665-JCH, Document 98-8, filed May 2, 2017, 60 pps.

Plantar Fascia, http://en.wikipedia.org/wiki/Plantar_fascia, Mar. 3, 2010, 3 pages.

Rebuttal expert report of Kim B. Blair, Ph.D., Case 2:13-cv-01276-KAM-AKT, Document 213-3, filed Aug. 8, 2018, 24 pps., marked on its face as Exhibit C.

Rebuttal Expert Report of Kim B. Blair, Ph.D., Case 3:15-CV-01665-JCH, Document 254-15, 184 pps., marked on its face as Exhibit 15.

Reply in Opposition to D126 filed Nov. 6, 2015 and Exhibits A and B.

Reply Memorandum of Law in Further Support of Plaintiffs' Motion for Leave to Amend the Second Amended Complaint filed Jul. 7, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 13 pages.

Response in Opposition re [117] First Motion to Amend Second Amended Complaint filed Jul. 7, 2015, 2 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Response in Opposition to [110] Motion to Amend-Corret-Supplement filed Jun. 15, 2015, 2 pages.

Revised Answer to Counterclaims filed Dec. 12, 2014 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 5 pages.

Ross et al., The Effects of Treadmill Sprint Training and Resistance Training on Maximal Running Velocity and Power, National Strength and Conditioning Association, Mar. 2009, 10 pages.

Rule 56.1 Counter-Statement by Plaintiffs Speedfit LLC, and Aurel A. Astilean filed Jun. 6, 2017, 13 pages.

Ruling Re: Plaintiffs' Motion for Summary Judgment of Non-Infringement and Invalidity (Doc. No. 252) and Woodway's Motion for Summary Judgment of Infringement (Doc. No. 255), *Chapco, Inc. and Samsara Fitness, LLC v. Woodway USA, Inc.*, Docket No. 3:15-cv-01665-JCH, Jul. 24, 2018, 26 pages.

Second Amended Complaint filed Feb. 17, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*, 18 pages.

Second Supplemental Expert Report of Kim B. Blair, PhD., Case 3:15-CV-01665-JCH, Document 254-3, 41 pps., marked on its face as Exhibit 3.

Sirotic et al., Physiological and Performance Test Correlates of Prolonged, High-Intensity, Intermittent Running Performance in Moderately Trained Women Team Sport Athletes, *Journal of Strength and Conditioning Research*, 2007, 7 pages.

Sirotic et al., The Reliability of Physiological and Performance Measures During Simulated Team-Sport Running on a Non-Motorised Treadmill, *Journal of Science and Medicine in Sport*, Apr. 11, 2007, 10 pages.

Soccer International, The Red Devil's in the Details, dated Jun. 2010, 4 pages.

Southern Research et al., "AIMTech Project Brief", Oct. 20, 2015, 2 pages.

Southern Research et al., "Resist Force-Induced Treadmill", 2 pages.

Speedfit LLC's Opening Claim Construction Brief, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Mar. 26, 2018, 9 pages.

Speedfit, video produced to Woodway at least by Apr. 28, 2015 in litigation, which is submitted herewith on DVD, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*

Speedfit, video produced to Woodway at least by Nov. 10, 2014 in litigation, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, No. 2:13-cv-01276-KAM-AKT, 21 pages of screenshot excerpts.

Speedfit, video produced to Woodway at least by Nov. 10, 2014 in litigation, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, No. 2:13-cv-01276-KAM-AKT, 23 pages of screenshot excerpts.

Supplemental Complaint filed Feb. 10, 2017 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.*

Supplemental Declaration of Kadie M. Jelenchick filed Jun. 6.

Supplemental declaration of Matthew W. Peters, Case 2:13-cv-01276-KAM-AKT, Document 227, filed Aug. 8, 2018, 1 pg.

Supplemental Expert Report of Kim B. Blair, PhD., Case 3:15-CV-01665-JCH, Document 184-8, filed Mar. 16, 2018, 19 pps., marked on its face as Exhibit AA.

Supplemental rebuttal expert report of Dr. Robert Giachetti responsive to second supplemental expert report of Dr. Kim Blair dated Apr. 13, 2018, Case 3:15-CV-01665-JCH, Document 254-4, filed Jun. 8, 2018, 18 pps., marked on its face as Exhibit 4.

Supplemental rebuttal expert report of Dr. Robert Giachetti responsive to supplemental expert report of Dr. Kim Blair dated Mar. 15, 2018, dated May 14, 2018, 12 pps.

Tecmachine, "Sprint Club: User's Guide", believed to have published 2002, 33 pages.

The Australian Competition & Consumer Commission's Mandatory Safety Standard for Treadmills (Supplier Guide), 2009, 20 pps.

The Woodway Force Brochure, The Best Way to Train for Speed & Athletic Power, dated May 5, 2005, 2 pages.

Third Amended Complaint filed Oct. 23, 2015 between *Speedfit LLC and Aurel Astilean* versus *Woodway USA, Inc.* and Exhibits A-H.

Transcript of civil cause for evidentiary hearing before the Honorable Kiyo A. Matsumoto, United States District Judge, Case 2:13-cv-01276-KAM-AKT, Document 213-4, filed Aug. 8, 2018, 10 pps., marked on its face as Exhibit D.

Transcript of civil cause for evidentiary hearing before the Honorable Kiyo A. Matsumoto, United States District Judge, Case 2:13-cv-01276-KAM-AKT, Document 227-3, filed Aug. 8, 2018, 5 pps., marked on its face as Exhibit G.

Transcript of videotaped deposition of Alex Astilean taken Jul. 10, 2018 for Case 2:17-cv-00768-KAM-AKT, 75 pps.

Transcript of videotaped deposition of Dan Bostan, Case 2:13-cv-01276-KAM-AKT, Document 227-2, filed Aug. 8, 2018, 4 pps., marked on its face as Exhibit F.

Transcript of videotaped deposition of Speedfit LLC by Alex Astilean taken Jul. 10, 2018 for Case 2:17-cv-00768-KAM-AKT, 38 pps.

Video deposition transcript of James D. Whelan taken on Sep. 28, 2015, Case 2:13-cv-01276-KAM-AKT, Document 213-1, filed Aug. 8, 2018, 23 pps., marked on its face as Exhibit A.

Woodway USA, Inc., "Treadmill Owner's Manual", Oct. 2001, 56 pages.

Woodway USA, Inc., EcoMill Promotional Flyer, Oct. 18, 2011, 1 page.

Woodway USA, Inc., Owner's Manual: EcoMill Non-Motorized, Jun. 4, 2010, 35 pages.

Woodway USA, Inc.'s Amended Supplemental Counterclaims, Case 3:15-CV-01665-JCH, Document 309, filed Sep. 14, 2018, 28 pps.

Woodway USA, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiffs' First Amended Complaint filed Oct. 24, 2014 and Exhibits 1 and 2.

Woodway USA, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiffs' Second Amended Complaint filed Mar. 6, 2015, 17 pages.

Woodway USA, Inc.'s Answer, Affirmative Defenses, and Counterclaims to Plaintiffs' Supplemental Complaint filed Feb. 24, 2017, 18 pages.

Woodway USA, Inc.'s first supplemental responses and objections to plaintiff's first set of interrogatories (Nos. 1-7), Case 2:17-cv-00768-KAM-AKT, Document 38-1, filed Mar. 14, 2018, 18 pps., marked on its face as Exhibit A.

Woodway USA, Inc.'s List of Claim Terms to be Considered and Proposed Constructions, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Exhibit D, Mar. 26, 2018, 4 pages.

Woodway USA, Inc.'s local rule 56(a)1 statement of undisputed material facts in support of its motion summary judgment of infringement of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 257, 8 pps.

Woodway USA, Inc.'s local rule 56(a)2 statement of facts in opposition to plaintiff's motion for summary judgment, Case 3:15-CV-01665-JCH, Document 267, filed Jun. 29, 2018, 34 pps.

Woodway USA, Inc.'s Memorandum in response to Plaintiffs' Motion for Leave to Amend the Second Amended Complaint filed Jul. 7, 2015, 16 pages.

Woodway USA, Inc.'s Memorandum in Response to Plaintiffs' Motion Under 35 USC 256 to Correct Inventorship of U.S. Pat. No. 8,308,619 and U.S. Pat. No. 8,342,016 filed Jun. 15, 2015, 20 pages.

Woodway USA, Inc.'s memorandum in support of its motion to preclude the testimony of plaintiffs' technical expert James Whelan, Case 2:13-cv-01276-KAM-AKT, Document 212, filed Aug. 8, 2018, 37 pps.

Woodway USA, Inc.'s memorandum of law in opposition to plaintiffs' motion for summary judgment of non-infringement and invalidity of Claim 25 of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 266, filed Jun. 29, 2018, 42 pps.

Woodway USA, Inc.'s Memorandum of Law in support of its motion for summary judgment of infringement of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 256, 38 pps.

Woodway USA, Inc.'s Memorandum of Law in Support of Its Motions for Summary Judgment of Invalidity of U.S. Pat. No.

(56)

References Cited

OTHER PUBLICATIONS

8,308,619 and U.S. Pat. No. 8,343,016 and Opening Claim Construction Brief filed Jun. 6, 2017, 38 pages.
 Woodway USA, Inc.'s motion for summary judgment of infringement of U.S. Pat. No. 9,039,580, Case 3:15-CV-01665-JCH, Document 255, filed Jun. 8, 2018, 3 pps.
 Woodway USA, Inc.'s Opening Claim Construction Brief, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Mar. 26, 2018, 15 pages.
 Woodway USA, Inc.'s opposition to plaintiffs' motion for partial reconsideration, Case 3:15-CV-01665-JCH, Document 250, filed May 14, 2018, 19 pps.
 Woodway USA, Inc.'s Patents, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Exhibit B, Mar. 26, 2018, 3 pages.
 Woodway USA, Inc.'s Reply Claim Construction Brief, *Speedfit LLC and Aurel A. Astilean v. Woodway USA, Inc.*, Docket No. 2:17-cv-00768-KAM-AKT, Mar. 26, 2018, 9 pages.
 Woodway USA, Inc.'s reply memorandum in further support of its motion to preclude the testimony of Plaintiffs' technical expert James Whelan, Case 2:13-cv-01276-KAM-AKT, Document 226, filed Aug. 8, 2018, 16 pps.
 Woodway USA, Inc.'s Reply Memorandum in Support of Its Motion to Dismiss filed Nov. 25, 2015, 24 pages.

Woodway USA, Inc.'s Responsive Claim Construction Brief filed Jul. 28, 2017, 19 pages.
 Woodway, "Introducing the All New EcoMill Self Powered", published to YouTube on Mar. 25, 2010, <https://www.youtube.com/watch?v=NcPH92DAArc>.
 Woodway, Curve 3.0 Specification, May 25, 2011, 1 page.
 Woodway, Curve Specification, May 24, 2011, 1 page.
 Woodway, Curve Specification, May 25, 2011, 1 page.
 Woodway, Curve XL Specification, May 18, 2011, 1 page.
 Woodway, Force Specification, Apr. 8, 2008, 1 page.
 Woodway, Force Specification, May 2, 2011, 1 page.
 Woodway, Force Specification, May 2, 2012, 1 page.
 Woodway's USA, Inc.'s Reply in Support of its Motion for Summary Judgment of Invalidity of U.S. Pat. No. 8,308,619 and U.S. Pat. No. 8,343,016 and Reply Claim Construction Brief filed Jun. 6, 2017, 16 pages.
 Woodway's Opposition to Defendant's Notice of Motion and Motion to Dismiss Case and Transfer Litigation to EDNY, *Woodway USA, Inc. v. Aurel A. Astilean*, Civ. Dkt. No. 2:13-cv-00681-WERC (E.D. WI), Oct. 18, 2013, 22 pages.
 Woodways USA, Inc.'s Supplemental Rule 56.1 Statement of Undisputed Material Facts and Responses to Rule 56.1 Counterstatement by Plaintiffs Speedfit LLC and Aurel A. Astilean filed Jun. 6, 2017, 20 pages.

* cited by examiner




FIG. 1




FIG. 2






FIG. 3






FIG. 6




FIG. 7a




FIG. 7b




FIG. 7c




FIG. 7d




FIG. 7e




FIG. 7f




FIG. 7g




FIG. 7h




FIG. 7i






FIG. 7j






FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 17




FIG. 15








FIG. 16






FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 28




FIG. 27




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38

MANUAL TREADMILL AND METHODS OF OPERATING THE SAME

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 15/958,339, filed Apr. 20, 2018, which is continuation of U.S. patent application Ser. No. 14/832,708, filed Aug. 21, 2015, which is a continuation of U.S. patent application Ser. No. 14/076,912 now U.S. Pat. No. 9,114,276, filed Nov. 11, 2013, which is a continuation of U.S. patent application Ser. No. 13/235,065, filed Sep. 16, 2011, which is a continuation-in-part of prior international Application No. PCT/US2010/027543, filed Mar. 16, 2010, which claims priority to U.S. Provisional Application Ser. No. 61/161,027, filed Mar. 17, 2009, all of which are incorporated herein by reference in their entireties.

BACKGROUND

The present invention relates generally to the field of treadmills. More specifically, the present invention relates to manual treadmills. Treadmills enable a person to walk, jog, or run for a relatively long distance in a limited space. It should be noted that throughout this document, the term “run” and variations thereof (e.g., running, etc.) in any context is intended to include all substantially linear locomotion by a person. Examples of this linear locomotion include, but are not limited to, jogging, walking, skipping, scampering, sprinting, dashing, hopping, galloping, etc.

A person running generates force to propel themselves in a desired direction. To simplify this discussion, the desired direction will be designated as the forward direction. As the person's feet contact the ground (or other surface), their muscles contract and extend to apply a force to the ground that is directed generally rearward (i.e., has a vector direction substantially opposite the direction they desire to move). Keeping with Newton's third law of motion, the ground resists this rearwardly directed force from the person, resulting in the person moving forward relative to the ground at a speed related to the force they are creating.

To counteract the force created by the treadmill user so that the user stays in a relatively static fore and aft position on the treadmill, most treadmills utilize a belt that is driven by a motor. The motor operatively applies a rotational force to the belt, causing that portion of the belt on which the user is standing to move generally rearward. This force must be sufficient to overcome all sources of friction, such as the friction between the belt and other treadmill components in contact therewith and kinetic friction, to ultimately rotate the belt at a desired speed. The desired net effect is that, when the user is positioned on a running surface of the belt, the forwardly directed velocity achieved by the user is substantially negated or balanced by the rearwardly directed velocity of the belt. Stated differently, the belt moves at substantially the same speed as the user, but in the opposite direction. In this way, the user remains at substantially the same relative position along the treadmill while running. It should be noted that the belts of conventional, motor-driven treadmills must overcome multiple, significant sources of friction because of the presence of the motor and configurations of the treadmills themselves.

Similar to a treadmill powered by a motor, a manual treadmill must also incorporate some system or means to absorb or counteract the forward velocity generated by a user so that the user may generally maintain a substantially

static position on the running surface of the treadmill. The counteracting force driving the belt of a manual treadmill is desirably sufficient to move the belt at substantially the same speed as the user so that the user stays in roughly the same static position on the running surface. Unlike motor-driven treadmills, however, this force is not generated by a motor.

SUMMARY

One embodiment of the disclosure relates to a manually operated treadmill comprising a treadmill frame having a front end and a rear end opposite the front end, a front shaft rotatably coupled to the treadmill frame at the front end, a rear shaft rotatably coupled to the treadmill frame at the rear end, and a running belt including a curved running surface upon which a user of the treadmill may run. The running belt is disposed about the front and rear shafts such that force generated by the user causes rotation of the front shaft and the rear shaft and also causes the running surface of the running belt to move from the front shaft toward the rear shaft. The treadmill is configured to control the speed of the running belt to facilitate the maintenance of the contour of the curved running surface.

Another embodiment of the disclosure relates to a manually operated treadmill comprising a treadmill frame, a front support member rotatably coupled to the treadmill frame, a rear support member rotatably coupled to the treadmill frame, a running belt including a curved running surface upon which a user of the treadmill may run, wherein the running belt is supported by the front support member and the rear support member, and a synchronizing system configured to cause the front support member and the rear support member to rotate at substantially the same speeds. The force generated by the user causes rotation of the front support member and the rear support member and also causes the running belt to rotate relative to the treadmill frame.

Another embodiment of the disclosure relates to a manually operated treadmill comprising a treadmill frame, a front shaft rotatably coupled to the treadmill frame, a rear shaft rotatably coupled to the treadmill frame, a running belt including a contoured running surface upon which a user of the treadmill may run, wherein the running belt is disposed about the front and rear shafts such that force generated by the user causes rotation of the front shaft and the rear shaft and also causes the running belt to rotate about the front shaft and the rear shaft without the rotation of the running belt being generated by a motor, and a one-way bearing assembly configured to prevent rotation of the running surface of the running belt in one direction.

Another embodiment of the disclosure relates to manually operated treadmill comprising a treadmill frame, a running belt including a running surface upon which a user of the treadmill may run, a front support member rotatably coupled to the treadmill frame, the front support member comprising the forwardmost support for the running belt, a rear support member rotatably coupled to the treadmill frame, the rear support member comprising the rearwardmost support for the running belt. The running surface comprises at least in part a complex curve located intermediate the front support member and the rear support member and incorporating a minimum of two geometric configurations.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of an exemplary embodiment of a manual treadmill having a non-planar running surface.

3

FIG. 2 is a left-hand partially exploded perspective view of a portion of the manual treadmill according to the exemplary embodiment shown in FIG. 1.

FIG. 3 is a right-hand partially exploded perspective view of a portion of the manual treadmill according to the exemplary embodiment shown in FIG. 1.

FIG. 4 is a perspective view of the right-hand side of the manual treadmill of FIG. 1 with a portion of the rear of the treadmill cut-away to show a portion of the arrangement of elements.

FIG. 5 is a cross-sectional view of a portion of the manual treadmill taken along line 5-5 of FIG. 1.

FIG. 6 is an exploded view of a portion of the manual treadmill of FIG. 1 having the side panels and handrail removed.

FIG. 7a is a side schematic view of the profile of the running surface of the manual treadmill according to an exemplary embodiment.

FIGS. 7b-7j are sides schematic views of alternative profiles of the running surfaces of manual treadmills according to alternative exemplary embodiments.

FIG. 8 is a partially exploded, perspective view of a bearing rail for the manual treadmill according to the exemplary embodiment shown in FIG. 1.

FIG. 9 is a side elevation view of the bearing rail of FIG. 6.

FIG. 10 is a top elevation view of a front shaft assembly for the manual treadmill according to the exemplary embodiment shown in FIG. 1.

FIG. 11 is a top elevation view of a rear shaft assembly for the manual treadmill according to the exemplary embodiment shown in FIG. 1.

FIG. 12 is a partial, cross-sectional view of the manual treadmill taken along line 12-12 of FIG. 1.

FIG. 13 is an alternative exemplary embodiment of the partial, cross-sectional view of the manual treadmill similar to FIG. 12.

FIG. 14 is a perspective view of an alternative embodiment of a synchronizing system integrated into a manual treadmill.

FIG. 15 is a partial, cross-sectional view of a manual treadmill including an exemplary embodiment of a braking system taken along line 15-15 of FIG. 4.

FIG. 16 is a partial, cross-sectional view of a manual treadmill including another exemplary embodiment of a braking system taken along line 16-16 of FIG. 4.

FIG. 17 is a perspective side view of a portion of the manual treadmill according to the exemplary embodiment shown in FIG. 1 including a plurality of rollers used in place of bearing rails.

FIG. 18 is a side perspective view of a track system for use with the exemplary embodiment of a manual treadmill shown in FIG. 1 and configured to help induce and maintain a running belt in a desired non-planar shape to define a running surface.

FIG. 19 is a detail view of the track system of FIG. 18 taken along line 19-19.

FIG. 20 is a partial cross-sectional view of the track system of FIG. 18 taken along line 20-20.

FIG. 21 is a detail view of the track system of FIG. 20 taken along line 21-21.

FIG. 22 is a side perspective view of another exemplary embodiment of a track system for use with the exemplary embodiment of a manual treadmill shown in FIG. 1 and configured to help induce and maintain a running belt in a desired non-planar shape to define a running surface.

4

FIG. 23 is a detail view of the track system of FIG. 22 taken along line 23-23.

FIG. 24 is a partial cross-sectional view of the track system of FIG. 18 taken along line 24-24.

FIG. 25 is a side perspective view of another exemplary embodiment of a track system for use with the exemplary embodiment of a manual treadmill shown in FIG. 1 and configured to help induce and maintain a running belt in a desired non-planar shape to define a running surface.

FIG. 26 is a detail view of the track system of FIG. 25 taken along a line 26-26.

FIG. 27 is a partial cross-sectional view of the track system of FIG. 25 taken along line 27-27.

FIG. 28 is a detail view of the track system of FIG. 27 taken along line 28-28.

FIG. 29 is a partially exploded, right-hand perspective view of a track system for use with the exemplary embodiment of a manual treadmill shown in FIG. 1 and configured to help induce and maintain a running belt in a desired non-planar shape to define a running surface.

FIG. 30 is a detail view of the track system of FIG. 29 taken along line 30-30.

FIG. 31 is a side perspective view of another exemplary embodiment of a track system for use with the exemplary embodiment of a manual treadmill shown in FIG. 1 and configured to help induce and maintain a running belt in a desired non-planar shape to define a running surface.

FIG. 32 is a detail view of the track system of FIG. 31 taken along a line 32-32.

FIG. 33 is a partial cross-sectional view of the track system of FIG. 31 taken along a line 33-33.

FIG. 34 is a detail view of the track system of FIG. 32 taken along a line 34-34.

FIG. 35 is a perspective view of an exemplary embodiment of a manual treadmill according to another embodiment having a substantially planar running surface.

FIG. 36 is a perspective view of a one-way bearing for the manual treadmill according to the exemplary embodiment shown in FIG. 1.

FIG. 37 is a left-hand partially exploded perspective view of a portion of the manual treadmill according to the exemplary embodiment shown in FIG. 1 including an incline adjustment system.

FIG. 38 is a perspective view of a one-way bearing for the manual treadmill shown in FIG. 1, according to another embodiment.

DETAILED DESCRIPTION

Referring to FIG. 1, a manual treadmill 10 generally comprises a base 12 and a handrail 14 mounted to the base 12 as shown according to an exemplary embodiment. The base 12 includes a running belt 16 that extends substantially longitudinally along a longitudinal axis 18. The longitudinal axis 18 extends generally between a front end 20 and a rear end 22 of the treadmill 10; more specifically, the longitudinal axis 18 extends generally between the centerlines of a front shaft and a rear shaft, which will be discussed in more detail below.

A pair of side panels 24 and 26 (e.g., covers, shrouds, etc.) are preferably provided on the right and left sides of the base 12 to effectively shield the user from the components or moving parts of the treadmill 10. The base 12 is supported by multiple support feet 28, which will be described in greater detail below. A rearwardly extending handle 30 is provided on the rear end of the base 12 and a pair of wheels 32 are provided at the front of the base 12, however, the

wheels 32 are mounted so that they are generally not in contact with the ground when the treadmill is in an operating position. The user can easily move and relocate the treadmill 10 by lifting the rear of the treadmill base 12 a sufficient amount so that the multiple support feet 28 are no longer in contact with the ground, instead the wheels 32 contact the ground, thereby permitting the user to easily roll the entire treadmill 10. It should be noted that the left and right-hand sides of the treadmill and various components thereof are defined from the perspective of a forward-facing user standing on the running surface of the treadmill 10.

Referring to FIGS. 2-6, the base 12 is shown further including a frame 40, a front shaft assembly 44 positioned near a front end 48 of the frame 40, and a rear shaft assembly 46 positioned near the rear end 50 of frame 40, generally opposite the front end 48. Specifically, the front shaft assembly 44 is coupled to the frame 40 at the front end 48, and the rear shaft assembly 46 is coupled to the frame 40 at the rear end 50 so that the frame supports these two shaft assemblies.

The frame 40 comprises longitudinally-extending, opposing side members, shown as a left-hand side member 52 and a right-hand side member 54, and one or more lateral or cross-members 56 extending between and structurally connecting the side members 52 and 54 according to an exemplary embodiment. Each side member 52, 54 includes an inner surface 58 and an outer surface 60. The inner surface 58 of the left-hand side member 52 is opposite to and faces the inner surface 58 of the right-hand side member 54. According to other exemplary embodiments, the frame may have substantially any configuration suitable for providing structure and support for the manual treadmill.

Similar to most motor-driven treadmills, the front shaft assembly 44 includes a pair of front running belt pulleys 62 interconnected with, and preferably directly mounted to, a shaft 64, and the rear shaft assembly 46 includes a pair of rear running belt pulleys 66 interconnected with, and preferably directly mounted to, a shaft 68. The front and rear running belt pulleys 62, 66 are configured to facilitate movement of the running belt 16. The running belt 16 is disposed about the front and rear running belt pulleys 62, 66, which will be discussed in more detail below. As the front and rear running belt pulleys 62, 66 are preferably fixed relative to shafts 64 and 68, respectively, rotation of the front and rear running belt pulleys 62, 66 causes the shafts 64, 68 to rotate in the same direction. The front and rear running belt pulleys 62, 66 are formed of a material sufficiently rigid and durable to maintain shape under load. Preferably, the material is of a relatively light weight so as to reduce the inertia of the pulleys 62, 66. The pulleys 62, 66 may be formed of any material having one or more of these characteristics (e.g., metal, ceramic, composite, plastic, etc.). According to the exemplary embodiment shown, the front and rear running belt pulleys 62, 66 are formed of cast aluminum. According to another embodiment, the front and rear running belt pulleys 62, 66 are formed of a glass-filled nylon, for example, Grivory® GV-5H Black 9915 Nylon Copolymer available from EMS-GRIVORY of Sumter, S.C. 29151, which may save cost and reduce the weight of the pulleys 62, 66 relative to metal pulleys. To prevent a static charge due to operation of the treadmill 10 from building on a pulley 62, 66 formed of electrically insulative materials (e.g., plastic, composite, etc.), an antistatic additive, for example Antistat 10124 from Nexus Resin Group of Mystic, Conn. 06355, maybe may be blended with the GV-5H material.

As noted above, the manual treadmill disclosed herein includes a force translation system that incorporates a variety of innovations to translate the forward force created by the user into rotation of the running belt and permit the user to maintain a substantially static fore and aft position on the running belt while running. One of the ways to translate this force is to configure the running belt 16 to be more responsive to the force generated by the user. For example, by minimizing the friction between the running belt 16 and the other relevant components of the treadmill 10, more of the force the user applies to the running belt 16 to propel themselves forward can be utilized to rotate the running belt 16.

Another way to counteract the user-generated force and convert or translate it into rotational motion of the running belt 16 is to integrate a non-planar running surface, such as non-planar running surface 70. Depending on the configuration, non-planar running surfaces can provide a number of advantages. First, the shape of the non-planar running surface may be such that, when a user is on the running surface, the force of gravity acting upon the weight of the user's body helps rotate the running belt. Second, the shapes may be such that it creates a physical barrier to restrict or prevent the user from propelling themselves off the front end 20 of the treadmill 10 (e.g., acting essentially as a stop when the user positions their foot thereagainst, etc.). Third, the shapes of some of the non-planar running surfaces can be such that it facilitates the movement of the running belt 16 there along (e.g., because of the curvature, etc). Accordingly, the force the user applies to the running belt is more readily able to be translated into rotation of the running belt 16.

As seen in FIGS. 1 and 4-5, the running surface 70 is generally non-planar and shown shaped as a substantially complex curve according to an exemplary embodiment. The running surface can be generally divided up into three general regions each having a particular geometric configuration, the front portion 72, which is adjacent to the front shaft assembly 44, the rear portion 74, which is adjacent to the rear shaft assembly 46, and the central portion 76, which is intermediate the front portion 72 and the rear portion 74. In the exemplary embodiment seen in FIGS. 1 and 4, the running surface 70 includes a substantially concave curve 80 and a substantially convex curve 82. At the front portion 72 of the running surface 70, the relative height or distance of the running surface 70 relative to the ground is generally increasing moving forward along the longitudinal axis 18 from the central portion 76 toward the front shaft assembly 44. This increasing height configuration provides one structure to translate the forward running force generated by the user into rotation of the running belt 16. To initiate the rotation of the running belt 16, the user places her first foot at some point along the upwardly-inclined front portion 72 of the running surface 70. As the weight of the user is transferred to this first foot, gravity exerts a downward force on the user's foot and causes the running belt 16 to move (e.g., rotate, revolve, advance, etc.) in a generally clockwise direction as seen in FIG. 1 (or counterclockwise as seen in FIG. 4). As the running belt 16 rotates, the user's first foot will eventually reach the lowest point in the non-planar running surface 70 found in the central portion 76, and, at that point, gravity is substantially no longer available as a counteracting source to the user's forward running force. Assuming a typical gait, at this point the user will place her second foot at some point along the upwardly-inclined front portion 72 of the running belt 16 and begin to transfer weight to this foot. Once again, as weight shifts to this second foot, gravity acts on the user's foot to continue the rotation of the

7

running belt 16 in the clockwise direction as seen in FIG. 1. This process merely repeats itself each and every time the user places her weight-bearing foot on the running belt 16 at any position vertically above the lowest point of central portion 76 of the running surface 70 of the of the running belt 16. The upwardly-inclined front portion 72 of the running belt 16 also acts substantially as a physical stop, reducing the chance the user can inadvertently step off the front end 20 of the treadmill 10.

A user can generally utilize the force translation system of the treadmill 10 to control the speed of the treadmill 10 by the relative placement of her weight-bearing foot along the running belt 16 of the base 12. Generally, the rotational speed of the running belt 16 increases as greater force is applied thereto in the rearward direction. The generally upward-inclined shape of the front portion 72 thus provides an opportunity to increase the force applied to the running belt 16, and, consequently, to increase the speed of the running belt 16. For example, by increasing her stride and/or positioning her weight-bearing foot vertically higher on the front portion 72 relative to the lowest portion of the running belt 16, gravity will exert a greater and greater amount of force on the running belt 16 to drive it rearwardly. In the configuration of the running belt 16 seen in FIG. 1, this corresponds to the user positioning her foot closer to the front end 20 of the treadmill 10 along the longitudinal axis 18. This results in the user applying more force to the running belt 16 because gravity is pulling her mass downward along a greater distance when her feet are in contact with the front portion 72 of the running surface 70. As a result, the relative rotational speed of the running belt 16 and the relative running speed the user experiences is increased. Accordingly, the force translation system is adapted to convert a variable level of force generated by the user into a variable speed of rotation of the belt.

FIG. 5 illustrates a number of possible locations where a user may position her feet. A-C indicate locations along the front portion 72 of the running surface 70 where a user may place their weight bearing foot. When the user positions her weight bearing foot at location A, she will be running with greater speed than if her weight bearing foot was positioned at locations B or C based upon the fact that the force of gravity is able to have a greater effect as the user's weight bearing foot moves from location A towards the rear of the non-planar running surface 70 as the running belt 16 rotates. At location A, gravity is able to have the greatest impact on the user so that the greatest amount of force is translated into rotation of the running belt 16. A user can decrease her relative running speed by positioning her weight bearing foot at locations B or C. As location B is relatively higher along the front portion 72 than C, gravity is able to exert a greater force on the user and the running belt 16 than if the user's weight bearing foot was positioned at location C.

Another factor which will increase the speed the user experiences on the treadmill 10 is the relative cadence the user assumes. As the user increases her cadence and places her weight-bearing foot more frequently on the upwardly extending front portion 72, more gravitational force is available to counteract the user-generated force, which translates into greater running speed for the user on the running belt 16. It is important to note that speed changes in this embodiment are substantially fluid, substantially instantaneous, and do not require a user to operate electromechanical speed controls. The speed controls in this embodiment are generally the user's cadence and relative position

8

of her weight-bearing foot on the running surface. In addition, the user's speed is not limited by speed settings as with a driven treadmill.

In the embodiment shown in FIGS. 1-6, gravity is also utilized as a means for slowing the rotational speed of the running belt. At a rear portion 74 of the running surface 70, the distance of the running surface 70 relative to the ground generally increases moving rearward along the longitudinal axis 18 from the lowest point in the non-planar running surface 70. As each of the user's feet move rearward during her stride, the rear portion 74 acts substantially as a physical stop to discourage the user from moving too close to the rear end of the running surface. To this point, the user's foot has been gathering rearward momentum while moving from the front portion 72, into the central portion 76, and toward the rear portion 74 of the running surface 70. Accordingly, the user's foot is exerting a significant rearwardly-directed force on the running belt 16. Under Newton's first law of motion, the user's foot would like to continue in the generally rearward direction. The upwardly-inclined rear portion 74, interferes with this momentum and provides a force to counter the rearwardly-directed force of the user's foot by providing a physical barrier. As the user's non-leading foot moves up the incline (see position D in FIG. 5), the running surface 70 provides a force that counters the force of the user's foot, absorbing some of the rearwardly-directed force from the user and preventing it from being translated into increasing speed of the running belt 16. Also, gravity acts on the user's weight bearing foot as it moves upward, exerting a downwardly-directed force on the user's foot that the user must counter to lift their foot and bring it forward to continue running. In addition to acting as a stop, the rear portion 74 provides a convenient surface for the user to push off of when propelling themselves forward, the force applied by the user to the rear portion 74 being countered by the force the rear portion 74 applies to the user's foot.

One benefit of the manual treadmill according to the innovations described herein is positive environmental impact. A manual treadmill such as that disclosed herein does not utilize electrical power to operate the treadmill or generate the rotational force on the running belt. Therefore, such a treadmill can be utilized in areas distant from an electrical power source, conserve electrical power for other uses or applications, or otherwise reduce the "carbon footprint" associated with the operation of the treadmill 10.

A manual treadmill according to the innovations disclosed herein can incorporate one of a variety of shapes and complex contours in order to translate the user's forward force into rotation of the running belt or to provide some other beneficial feature or element. FIG. 7a generally depicts the curve defined by the running surface 70 of the exemplary embodiment shown in FIG. 1, specifically, substantially a portion of a curve defined by a third-order polynomial. The front portion 72 and the central portion 76 define a concave curve and the rear portion 74 of the running surface 70 defines a convex curve. As the central portion 76 of the running surface 70 transitions to the rear portion 74, the concave curve transitions to the convex curve. In the embodiment shown, the curvature of the front portion 72 and the central portion 76 is substantially the same; however, according to other exemplary embodiments, the curvature of the front portion 72 and the central portion 76 may differ. Please note, the description of the running surfaces as concave and convex provided herein is related to the relative curve which the user's foot would experience on the running surface 70.

FIGS. 7b-7h illustrate the side profiles of some exemplary non-planar, contoured running surfaces according to the innovations disclosed herein, each including a front portion, a central portion, and a rear portion. Each portion has a particular geometric configuration that is concave, convex, or linear; collectively, the portions define the non-planar running surface. For example, FIG. 7b shows an exemplary embodiment of the profile of a non-planar surface including a concave front portion 100, a concave central portion 102, and a concave rear portion 104 according to an exemplary embodiment. In this embodiment, the front portion 100, central portion 102, and rear portion 104 each have different curvatures. According to other exemplary embodiments, one or more of the front, central, and rear portions may have the same curvature.

FIG. 7c shows an exemplary embodiment of the profile of a non-planar surface including a convex front portion 110, a concave central portion 112, and a concave rear portion 114 according to an exemplary embodiment. Once again, this embodiment incorporates a smooth transition between the different curvatures of the front, central, and rear portions.

FIG. 7d shows an exemplary embodiment of the profile of a non-planar surface including a convex front portion 120, a concave central portion 122, and a convex rear portion 124 according to an exemplary embodiment. In this embodiment, the front portion 120 and the rear portion 122 have different curvatures, but these curvatures may be the same according to other exemplary embodiments.

FIG. 7e shows an exemplary embodiment of the profile of a non-planar surface including a convex front portion 130, a convex central portion 132, and a convex rear portion 134 according to an exemplary embodiment. In this embodiment, the front portion 130, the central portion 132, and the rear portion 134 each have the same convex curvature, but the curvature of one or more of the front portion 130, the central portion 132, and the rear portion 134 may differ according to other exemplary embodiments.

FIG. 7f shows an exemplary embodiment of the profile of a non-planar surface including a concave front portion 140, a convex central portion 142, and a convex rear portion 144 according to an exemplary embodiment. In this embodiment, the central portion 142 and the rear portion 144 having the same curvatures, but these curvatures may differ from each other according to other exemplary embodiments.

FIG. 7g shows an exemplary embodiment of the profile of a non-planar surface including a convex front portion 150, a convex central portion 152, and a concave rear portion 154 according to an exemplary embodiment. In this embodiment, the front portion 150 and the central portion 152 having the same curvatures, but these curvatures may differ from each other according to other exemplary embodiments.

FIG. 7h shows an exemplary embodiment of the profile of a non-planar surface including a concave front portion 160, a convex central portion 162, and a concave rear portion 164 according to an exemplary embodiment. In this embodiment, the front portion 160 and the rear portion 164 have different curvatures, but these curvatures may be the same according to other exemplary embodiments.

According to one exemplary embodiment, the non-planar running surface of the manual treadmill 10 is substantially curved, but that curve integrates one or more linear portions (e.g., that replace a "curved portion" or the curve or that are added/inserted into the curve). The linear portions may be substantially parallel to the longitudinal axis 18 or disposed at an angle relative thereto. FIG. 7i illustrates the profile of a non-planar surface wherein a substantially linear portion 170 has been integrated with a concave curve having a first

concave portion 174 to one side of the linear portion 170 and a second concave portion 176 to the opposite side of the linear portion 170 according to an exemplary embodiment. In addition to the linear portion 170, the first concave portion 174 and the second concave portion 176, the profile further includes a fourth portion shown as a convex portion 178. According to another exemplary embodiment, a linear portion may replace all or a portion of the curve. Alternatively, multiple linear portions may be included in a profile of a non-planar surface.

FIG. 7j illustrates a linear portion 180 provided at the front of the running surface which transitions into a concave curve 182 which then transitions into a convex curve 184.

According to an exemplary embodiment, the non-planar running surface of the manual treadmill 10 may include (or be so defined as to include) more or less than three portions. For example, FIG. 7g could be interpreted as defined two portions, the first portion including the front portion and the central portion, which comprise a convex curve having the same curvature throughout the front portion 150 and the central portion 152, and the second portion including the rear portion 154 which generally comprises a concave curve. According to some exemplary embodiments, some non-planar running surfaces include at least three or more portions.

According to an exemplary embodiment, the profile defined by the non-planar running surface is substantially a portion of a curve defined by any suitable second-order polynomial, but, as clearly demonstrated in FIGS. 7a-j, the profile defined by the non-planar running surface can be a portion of a curve that is a third-order polynomial or a fourth-order polynomial. According to yet another exemplary embodiment, the running surface profile can be substantially defined by a first-order polynomial, in other words, the running surface is substantially planar. An exemplary embodiment of a manual treadmill including a planar running surface will be discussed in more detail below (see e.g., FIG. 35).

According to an exemplary embodiment, the relative length of each portion of the running surface may vary. In the exemplary embodiment shown, the central portion is the longest. In other exemplary embodiments, the rear portion may be the longest, the front portion may be shorter than the intermediate portion, or the front portion may be longer than the rear portion, etc. It should be noted that the relative length may be evaluated based on the distance the portion extends along the longitudinal axis or as measured along the surface of the running belt itself. One of the benefits of integrating one or more of the various curves or contours into the running surface is that the contour of the running surface can be used to enhance or encourage a particular running style. For example, a curve integrated into the front portion of the running surface can encourage the runner to run on the balls of her feet rather than having the heel strike the running belt 16 first. Similarly, the contour of the running surface can be configured to improve a user's running biomechanics and to address common running induced injuries (e.g., plantar fasciitis, shin splints, knee pain, etc.). For example, integrating a curved contour on the front portion of the running surface can help to stretch the tendons and ligaments of the foot and avoid the onset of plantar fasciitis.

One of the difficulties associated with using a running surface that has a non-planar shape is inducing the running belt 16 to assume the non-planar shape and then maintaining the running belt 16 in that non-planar shape when the treadmill is being operated. In addition to discussing this

11

difficultly in more detail below, a number of running belt retention systems providing ways to induce and maintain a belt in a desired non-planar shape to define the running surface are discussed below. Generally, these running belt retention systems are adapted to control the relative contour of the running belt so that the running belt substantially follows the contour of the running surface

One embodiment of a running belt retention system used to induce the running belt 16 to take-on the non-planar shape and then maintaining that shape, as shown in FIG. 5, is discussed in reference to FIGS. 5-6 and 8-11 in which base 12 is shown further including a pair of opposed bearing rails 200 to support the running belt 16 along with a front synchronizing belt pulley 202, a rear synchronizing belt pulley 204, and a synchronizing belt 206 all of which are interconnected to the running belt 16. The front rear synchronizing belt pulleys 202, 204 may be formed of the same or different materials as the front and rear running belt pulleys 62, 66.

Referring to FIGS. 6 and 8-9, in particular, the bearing rails 200 are shown including a plurality of bearings 208 and an upper or top profile 210, shown shaped as a complex curve, according to an exemplary embodiment. The bearing rails 200 shown are supported by and preferably mounted to the frame 40 substantially between the front shaft assembly 44 and the rear shaft assembly 46, the support members or elements about which the running belt 16 is disposed. One bearing rail 200 is coupled to one or more of the cross-members 56 proximate to the inner surface 58 of the left-hand side member 52 and the other bearing rail 200 is coupled to one of more of the cross-members 56 proximate to the inner surface 58 of the right-hand side member 54 thereby fixing the position of the bearing rails 200 relative to the frame 40.

The bearing rails 200 are preferably configured to facilitate movement of the running belt 16. In the exemplary embodiment seen in FIGS. 8-9, the running belt 16 moves substantially along the top profile 210 of the bearing rails 200. The running belt 16 contacts and is supported in part by the bearings 208 of the bearing rails and bearing 208 are configured to rotate, thereby decreasing the friction experienced by the running belt 16 as the belt moves along the top profile 210. The bearing rails 200 are configured to help achieve the desired shape of the running surface. The shape of the top profile 210 of the bearing rails 200 at least partially corresponds to the desired shape for the running surface 70. The at least somewhat flexible running belt 16 substantially assumes the shape of top profile 210 of the bearing rails 200 by being maintained substantially thereagainst, as will be discussed in more detail later. Accordingly, the running surface 70 has a shape that substantially corresponds to the shape of the top profile 210 of the bearing rails 200. It should be noted that the front and/or rear running belt pulleys may also help define a portion of the shape of the running surface. Also, other suitable shape-providing components may be used in combination with the bearing rails.

FIG. 9 provides a side view of one of the bearing rails 200 to more clearly show the top profile 210 according to an exemplary embodiment. Similar to the running surface 70, discussed above, the top profile 210 of the bearing rails 200 can be generally divided up into three general regions, the front portion 212 which is adjacent to the front shaft assembly 44 (see e.g., FIG. 5), the rear portion 214 which is adjacent to the rear shaft assembly 46 (see e.g., FIG. 5), and the central portion 216, intermediate the front portion 212 and the rear portions 214. The central portion 216 is shown as a concave curve 218 that has a radius of curvature R1. The

12

front portion 212 is further shown as a continuation of the concave curve 218 of the central portion 216, and, thus, also has a radius of curvature of R1. The rear portion 214 is shown as a convex curve 220 that has a radius of curvature R2. The front portion 212 is shown disposed substantially tangential to the central portion 216, providing a smooth transition therebetween, and helping provide a smooth shape for the running surface 70. The shape of the rear portion 214 also helps provide a smooth transition for the running belt 16 from the bearing rails 200 onto the rear running belt pulleys 66, which helps ensure as much contact as possible between the running belt 16 and the rear running belt pulleys 66. As the shape of the running surface substantially corresponds to the shape of top profile the bearing rails, the shape of the top profile of the bearing rails can necessarily be any of the shapes and/or have any of the variations (e.g., in length of portions, etc.) discussed above in FIGS. 7a through 7j with reference to possible shapes of the running surface.

According to an exemplary embodiment, each portion of the top profile is disposed substantially tangential to the portions adjacent thereto. According to other exemplary embodiments, less than all of the adjacent portions are disposed substantially tangential to the portions adjacent thereto, meaning the profile does not have an entirely smooth contour.

According to an exemplary embodiment shown in FIG. 9, R1 is approximately 7.26 feet. However, it is understood that a radius anywhere from 5 feet to 100-plus feet can be used. The size of the radius which can be used is typically a function of the length of the treadmill which can be accommodated. The range of possible radii for a convex bearing rail depends on the shaft-to-shaft distance of the treadmill (see e.g., measurement "x" in FIG. 5, discussed in more detail below). Assuming that the radius of curvature of the curve is R_C , the radius of the front running belt pulley is R_f , and the radius of the rear running belt pulley is R_r , the range of possible radii is approximately: $\infty > R_C > (x - R_f - R_r)/2$. For most commercial-available treadmills, x is approximately between 14 inches and 10 feet but the treadmill can certainly be as great as 25 feet in length. According to the exemplary embodiment shown in FIG. 5, x is approximately 57.8 inches in length. According to another exemplary embodiment, x is approximately 77.2 inches in length, with a radius R1 of approximately 8.67 feet, wherein the greater length x and radius R1 may facilitate use of the treadmill 10 by users with a longer running gait. The limiting factors in the length are the available space to accommodate the treadmill and the relative cost of constructing such a large treadmill.

When the treadmill 10 is being operated, the running belt 16 is driven rearwardly and the goal is to ensure that the running belt 16 follows the profile defined by a portion of the circumference of the front running pulleys 62, the contoured profile defined by the bearings 208 supported on the bearing rails 200 and finally by a portion of the circumference of the rear running belt pulleys 66. The particular contour which the running belt 16 assumes on the bottom of the base 12 between the rear running belt pulleys 66 and front running belt pulleys 62 is not terribly critical provided that the running belt continues to move with minimal friction and is not subject to excessive wear or obstruction.

Following the shape of the bearing rails 200 is not the natural tendency of the running belt for the particular contour seen in FIG. 5. Rather, without more, the running belt 16 tends to be pulled upward, away from the curved bearing rails and across the central portion 76 of the treadmill 10. Under the force of gravity, the weight of the running

13

belt 16 coupled with the relative spacing between the front and rear running belt pulleys 62 and 66, respectively, would likely result in the top surface of the running belt 16 assuming a position of the shortest distance between the two pulleys, namely, a substantially straight line between the two pulleys with any excess length of the running belt 16 collecting on the bottom of the treadmill and hanging below the front and rear running belt pulleys 62 and 66, respectively. Therefore, a system of some sort needs to be integrated into a non-planar running surface treadmill to ensure that the running belt 16 follows the desired contour over the running surface.

Further referring to FIGS. 5-6 and 8-11, one way to ensure that the running belt 16 follows the contour of the bearing rails 200 and the front and rear running belt pulleys 62, 66 is to utilize the weight of the running belt 16 itself in addition to adjusting the relative size of the front and rear running belt pulleys 62, 66; and/or providing a synchronizing system 222 according to an exemplary embodiment.

As discussed above, the running belt 16 is disposed about the front and rear running belt pulleys 62, 66 which in turn are disposed about front and rear shafts 64, 68, respectively. Measured along the longitudinal axis 18 between the centerlines of the front and rear shafts 64, 68, the front and rear shafts 64, 68 are spaced a distance x from each other, as shown in FIG. 5. Accordingly, when positioning the running belt 16 about the front and rear running belt pulleys 62, 66, the length of the running belt 16 provided therebetween must be at least x (e.g., the straight-line distance therebetween). It follows that, when the profile of the running surface 70 is non-planar, the length of the running belt provided between the front and rear shafts 64, 68 will be greater than x .

In the exemplary embodiment shown in FIG. 5, when positioning the running belt 16 about the front and rear running belt pulleys 62, 66, a length of the running belt 16 sufficient to permit the running belt 16 to correspond to (e.g., follow, be positioned against or above, etc.) the desired contours of the bearing rails 200 and the front and rear running belt pulleys 62, 66 is generally disposed between the front and rear shafts 64, 68. At each location between the front and rear shafts 64, 68, the force of gravity pulls downward on the running belt 16. Generally, this force will help pull the running belt 16 downward and against the desired components of base 12. However, gravity can also cause slippage (e.g., over the front running belt pulley 62, over the rear running belt pulley 66, down along curves of the bearing rail 200, etc.) in an amount that is undesirable and the magnitude of these slippage-problems tends to increase when the treadmill 10 is being operated. Accordingly, the solution typically relies on more than the weight of the running belt alone.

Further referring to FIGS. 5-6 and 8-11, the preferred embodiment of the running belt 16 is shown including two reinforcing belts shown as endless belts 226 and a plurality of slats 228 according to an exemplary embodiment. The endless belts 226 are configured to provide support for the running belt 16 in order to support the weight of a user. The endless belts 226 are shown disposed on opposite sides of the running belt 16, generally interior to the outer, lateral edge of the slats 228. The endless belts 226 are themselves reinforced, and thus help stabilize the sides of the running belt and help prevent stretching of the running belt 16. For example, the endless belts may be reinforced with metal wiring, which is surrounded by a molded plastic coating. According to some exemplary embodiments, more or less than two endless belts may be used. According to other

14

exemplary embodiments, other suitable support elements may be used to provide support for the running belt. Further details regarding the structure of the running belt and endless belt structure are seen in U.S. Pat. No. 5,470,293, titled "Toothed-Belt, V-Belt, and Pulley Assembly, for Treadmills," which is incorporated by reference herein.

The endless belts 226 are further configured to interact with the front running belt pulleys 62 and the rear running belt pulleys 66. The location of each endless belt 226 laterally, along the width of the running belt 16, substantially corresponds to the location of a longitudinally aligned front running belt pulley 62 and rear running belt pulley 66. Each endless belt 226 includes a first or inner portion 230 and a second or outer portion 232 at an interior surface 236 according to an exemplary embodiment. The inner portion 230 is in contact with an exterior surface 234 of the corresponding running belt pulleys 62, 66. According to some exemplary embodiments, the outer portion 232 is also in contact with the exterior surface 234 of the corresponding running belt pulleys 62, 66.

FIG. 12 illustrates a running belt and running belt pulley combination wherein the exterior surfaces 234 of the front running belt pulleys 62 are substantially smooth and are in contact with the interior surface 236 of the endless belts 226, which is also substantially smooth according to an exemplary embodiment. The outer portion 232 is shown substantially not in contact with the exterior surfaces 234 of the front running belt pulleys 62. The outer portion 232 is further shown including a plurality of teeth 238 (e.g., being toothed); however, according to other exemplary embodiments, the outer portion may be smooth or have any suitable texture and/or configuration. In this embodiment, both of the running belt pulleys come in contact with the inner, substantially smooth portion of the endless belts, and a toothed portion of the endless belts is disposed to the outside of the running belt pulleys on both sides.

FIG. 13 illustrates an alternative running belt and running belt pulley combination according to an exemplary embodiment. In this exemplary embodiment, the front running belt pulleys 62' include a first or inner portion 230' and a second or outer portion 232'. The inner portion 230' of the front running belt pulleys 62' is substantially smooth, while the outer portion 232' includes a plurality of teeth, to correspond to the inner and outer portions 230', 232', of the endless belts 226', respectively. In this embodiment, both of the running belt pulleys include an inner, smooth portion and an outer, toothed portion. These portions correspond to an inner, smooth portion of the endless belt and an outer, toothed portion of the endless belt. This endless belt/front running belt pulley configuration is discussed in more detail in U.S. Pat. No. 5,470,293, titled "Toothed-Belt, V-Belt, and Pulley Assembly, for Treadmills," which is herein incorporated by reference in its entirety.

According to still another an exemplary embodiment, a combination of the endless belt/front running belt pulley configurations shown in FIGS. 12 and 13 is used. In this exemplary embodiment, the smooth belt and pulley configuration shown in FIG. 12 is used for the front running belt pulleys and the combination of smooth and toothed belt and pulley configuration shown in FIG. 13 is used for the rear running belt pulleys. In another exemplary embodiment, the configuration shown in FIG. 13 is used for the front running belt pulleys and the configuration shown in FIG. 12 is used for the rear running belt pulleys.

The slats 228 of the running belt 16 are configured to help support a user of the treadmill 10. The slats 228 may be made of substantially any suitably sturdy material (e.g.,

15

wood, plastic, metal, etc.) and extend generally laterally between the endless belts 226. Each slat 228 is coupled at its ends 252, 254 to the second portions 232 of the endless belts 226 using fasteners. According to other exemplary embodiments, the slats may be otherwise coupled to the endless belts (e.g., adhered, welded, etc.) in the manner disclosed in U.S. Pat. No. 5,470,293, titled "Toothed-Belt, V-Belt, and Pulley Assembly, for Treadmills," which is incorporated herein by reference. Each slat is shown to include a portion 229 (e.g., stem, web, etc.) extending inwardly from an interior surface 256 of the slat 228.

According to an exemplary embodiment, the running belt may be substantially any suitable, continuous loop element, including, but not limited to, a continuous urethane (e.g., polyurethane) loop, a continuous loop made of plastics other than polyurethane, a plastic belt reinforced with reinforcing elements (e.g., metal wire, a relatively harder plastic, wood, etc.), a continuous foam loop, a loop formed by a plurality of interconnected members (e.g., metallic members, wooden members, etc.) in a manner to provide at least some flexibility, etc.

Referring to FIGS. 6, 10 and 11, another aspect of the solution to ensuring the running belt 16 follows the desired contour involves the utilizing front running belt pulleys 62 that are slightly larger than the rear running belt pulleys 66. That is, the radius of the front running belt pulleys, R_f , is greater than the radius of the rear running belt pulleys, R_r . Assuming the front running belt pulleys 62 are rotating with the same rotational velocity (e.g., angular speed) as the rear running belt pulleys 66, the tangential velocity of the front running belt pulleys 62 is slightly greater than the tangential velocity of the rear running belt pulleys 66. Thus, as the running belt 16 is driven, the portion of the running belt 16 disposed proximate the front end 20 of the treadmill 10 will be moved over the front running belt pulleys 62 and rearward with slightly greater speed than the rear running belt pulleys 66 move the portion of the running belt 16 proximate thereto. Thus, the front running belt pulleys 62 essentially "push" the running belt 16 rearward, creating a slight amount of excess running belt 16 in the area between the front running belt pulleys 62 and the rear running belt pulleys 66, which helps to counter the force of gravity which would attempt to gather any excess length of running belt 16 on the bottom of the treadmill 10 thereby causing the top surface of the running belt 16 to assume a position of the shortest distance between the two pulleys, namely, a substantially straight line between the two pulleys. Obviously the system cannot tolerate too much excess length of running belt feeding off the front running belt pulley 62 so periodically, a portion of this excess running belt 16 will slip over the rear running belt pulley 66. By specifically balancing the excess running belt 16 coming off the front running belt pulley 62 against the slippage allowed on the rear running belt pulley 66, the running belt 16 will follow the desired concave, convex or linear (or combinations thereof) contours of the running surface.

If the difference between the radius of the front running belt pulleys 62 and the radius of the rear running belt pulleys 66 is too large, the running belt 16 will begin to bunch up atop the base 12 as too much excess is generated. Accordingly, there is a practical limit of differences between the radius of each of the front running belt pulleys 62 and the radius of each of the rear running belt pulleys 66. Generally, this range may be dependent on the length of the running surface, as measured along the running belt, and/or the shape of the running surface. According to an exemplary embodiment, the size difference between the radii of the front and

16

rear running belt pulleys, $R_f - R_r$, is within the range of approximately $0 < R_f - R_r < 0.100$ inches. Preferably, the size difference between the radii of the front and rear running belt pulleys, $R_f - R_r$, is within the range of approximately $0.005 < R_f - R_r < 0.035$ inches. In one embodiment, the radius of the front running belt pulleys is approximately $7.00" \pm 0.010"$ and the radius of the rear running belt pulleys is approximately $6.985" \pm 0.010$. According to another exemplary embodiment, instead of using front and rear running belt pulleys having a radial size difference, the synchronizing belt pulleys may have a radial size difference. Similar to the differently sized front and rear running belt pulleys, the differently sized front and rear synchronizing pulleys would be used to essentially "push" the running belt rearward, creating a slight amount of excess running belt 16 in the area between the front running belt pulleys and the rear running belt pulleys.

Another means for ensuring that the running belt 16 follows the desired complex curve is to match the rotational velocity of the front running belt pulleys 62 to that of the rear running belt pulleys 66 utilizing a synchronizing system 222. Further referring to FIGS. 5-6 and 8-11, the synchronizing system 222 is shown generally to comprise the front synchronizing belt pulley 202, the rear synchronizing belt pulley 204, and the synchronizing belt 206 according to an exemplary embodiment.

The front synchronizing belt pulley 202 is rotatably mounted relative to the front shaft 64, similar to the front running belt pulleys 62. Preferably, the front synchronizing belt pulley 202 is securely mounted directly to the front shaft 64. Similarly, the rear synchronizing belt pulley 204 is fixed relative to the rear shaft 68 and preferably securely mounted to the rear shaft 68. Accordingly, the front synchronizing belt pulley 202 will move with substantially the same rotational speed as the front running belt pulleys 62, and the rear synchronizing belt pulley 204 will move with the same rotational speed as the rear running belt pulleys 66. When the front shaft assembly 44 and the rear shaft assembly 46 are coupled to the frame 40, the front and rear synchronizing belt pulleys 202, 204 are shown disposed exterior to the outer surface 60 of the left-hand side member 52. According to another exemplary embodiment, the front and rear synchronizing belt pulleys may be placed exterior to the outer surface of the right-hand side member of the frame. According to other exemplary embodiments, the synchronizing system may be disposed substantially between the left-hand side member and the right-hand side member of the frame.

The synchronizing belt 206 is configured to provide a force that helps ensure that the front and rear shafts 64, 68 are rotating (e.g., moving, spinning, etc.) at the same rotational velocity. The synchronizing belt 206 is shown as an endless belt that is adapted to be supported in tension about the front synchronizing belt pulley 202 and the rear synchronizing belt pulley 204, as shown in FIGS. 4-5. As the running belt pulleys 62, 66 and the synchronizing belt pulleys 202, 204 are both substantially fixed relative to the front shaft 64 and the rear shaft 68, the rotation of the front shaft 64 and the rear shaft 68 causes the front synchronizing belt pulley 202 and the rear synchronizing belt pulley 204 to similarly rotate. In response to the motion of the front synchronizing belt pulley 202 and the rear synchronizing belt pulley 204, the synchronizing belt 206, which connects the front shaft assembly 44 and the rear shaft assembly 46, similarly rotates. Because of the tension in the synchronizing belt 206 and the fact that the synchronizing belt pulleys 202, 204 are the same size, the synchronizing belt 206 provides a counter force in response to any deviation in

17

rotational velocity between the front shaft assembly 44 and the rear shaft assembly 46. For example, if the rear shaft assembly 46 was induced to start moving with greater rotational velocity than the front shaft assembly 44, the tension in the upper portion of the synchronizing belt (i.e., that portion of the synchronizing belt that extends generally between the tops of the synchronizing pulleys) would resist any differential rotation between the front and rear synchronizing belt pulleys 202, 204. Continuing with the example, any discrepancy between the rotational velocity of the front and rear shafts 64, 68 is similarly resisted by the engagement of the synchronizing belt 206. Thus, by constraining the relative motion of the front shaft assembly 44 and the rear shaft assembly 46, the synchronizing system 222 keeps their rotational velocity in sync, substantially preventing the front and rear running belt pulleys 62, 66 from becoming unsynchronized and moving at different rotational velocities.

So, in practice, the running belt 16 is initially installed on the front and rear running belt pulleys 62, 66 and the running belt 16 is manually positioned in the desired position so that a sufficient length of the running belt 16 is positioned along the top of the treadmill and the running belt 16 assumes the desired contour. While the running belt 16 is maintained in this position, the synchronizing belt 206 is mounted to the synchronizing belt pulleys 202, 204 and once the synchronizing belt 206 is installed, it effectively resists differential rotation of the running belt pulleys 62, 66 which could result in loss of the desired contour of the running belt 16.

It should be noted that the tension in the synchronizing belt 206 also helps maintain the position of the synchronizing belt 206 relative to the synchronizing belt pulleys 202, 204. The tension helps enhance friction between an interior surface 244 of the synchronizing belt 206 and exterior surfaces 246 of the synchronizing belt pulleys 202, 204, making it less likely that the synchronizing belt 206 will slip relative to the synchronizing belt pulleys 202, 204.

One or more tensioning assemblies 248 may be provided to adjust the tension in the synchronizing belt 206 (see e.g., FIGS. 3 and 6 illustrating tensioning assemblies 248). Tensioning assemblies 248 are configured to move portions of the synchronizing belt 206 relative to one another, stretching the synchronizing belt 206 and maintaining this stretch so that the synchronizing belt 206 can provide the necessary resistance to differential rotation of the front and rear running belt pulleys 62, 66. Alternatively, the tensioning assemblies 248 can be adjusted to release some of the tension in the synchronizing belt 206. Releasing some of the tension may be desirable if the synchronizing belt 206 is too tight, causing excess friction between the synchronizing belt 206 that makes it too difficult to rotate the front and rear shaft assemblies 44, 46 (e.g., greater than desired by the user, too great to function, etc.). The tensioning assemblies 248 are also used when the synchronizing belt 206 is being installed and removed. According to another exemplary embodiment, a single tensioning assembly is used in conjunction with one or more stationary idlers. According to still another exemplary embodiments, any devices or elements suitable for maintaining and/or adjusting the tension in the synchronizing belt may be used.

Referring to FIG. 14, a synchronizing system 300 is shown according to another exemplary embodiment. The synchronizing system 300 would typically be used in lieu of the previously described synchronizing system 222. In this next exemplary embodiment, the synchronizing system 300 is shown comprising a synchronizing shaft 302 mechanically connected at a first end 304 to a front gear 306 and at a second end 308 to a rear gear 310. The front gear 306 is

18

interconnected with, and preferably directly mounted and fixed relative to, the front shaft 64, and the rear gear 310 is interconnected with, and preferably directly mounted and fixed relative to, the rear shaft 68. Accordingly, the front gear 306 will move with substantially the same rotational speed as the front running belt pulleys 62, and the rear gear 310 will move with the same rotational speed as the rear running belt pulleys 66. When the front shaft assembly 44 and the rear shaft assembly 46 are coupled to the frame 40, the front and rear gears 306, 310 are shown disposed exterior to the outer surface 60 of the right-hand side member 54. According to another exemplary embodiment, the front and rear gears 306, 310 may be placed exterior to the outer surface of the left-hand side member of the frame. According to other exemplary embodiments, the synchronizing system may be disposed substantially between the left-hand side member and the right-hand side member of the frame.

The synchronizing shaft 302 is configured to provide a force that helps ensure that the front and rear shafts 64, 68 are rotating (e.g., moving, spinning, etc.) at the same rotational velocity. The synchronizing shaft 302 is shown as an elongated, substantially cylindrical member that extends generally between the front shaft 64 and the rear shaft 68. A first threaded portion 312 including a plurality of threads 314 is shown located at the first end 304 of the synchronizing shaft 302 and is configured to mesh with a plurality of teeth 316 of the front gear 306 that is fixed relative to the front shaft 64. A second threaded portion 318 including a plurality of threads 320 is shown located at the second end 308 of the synchronizing shaft 302 and is configured to mesh with a plurality of teeth 322 of the rear gear 310 that is fixed relative to the rear shaft 68.

The synchronizing shaft 302 rotates in response to the motion of the front gear 306 and the rear gear 310. When the front shaft 64 and the rear shaft 68 rotate in response to the user driving the running belt 16, the front gear 306 and the rear gear 310, which are fixed relative to the front shaft 64 and the rear shaft 68, respectively, similarly rotate. The front gear 306 meshes with and imparts rotational motion to the first threaded portion 312, and, thereby, imparts rotational motion to the synchronizing shaft 302. The rear gear 310 meshes with and imparts rotational motion to the second threaded portion 318, and, thereby, imparts rotational motion to the synchronizing shaft 302.

Because the synchronizing shaft 302 is rigid and the front and rear gears 306, 310 are the same size, the synchronizing shaft 302 provides a counter force in response to any deviation in rotational velocity between the front shaft assembly 44 and the rear shaft assembly 46. For example, if the rear shaft assembly 46 was induced to start moving with greater rotational velocity than the front shaft assembly 44, the rear gear 310 would be prevented from moving with greater rotational velocity than the front gear 306 because of the synchronizing shaft 302. The second threaded portion 318 is meshed with the rear gear 310. The second threaded portion 318 is fixed relative to the first threaded portion 312. The first threaded portion 312 is meshed with the front gear 306, which is moving with less rotational velocity than the rear gear 310. The front gear 306, being fixed relative to the front shaft assembly 44 which is also traveling at the same rotational velocity, seeks to continue at this rotational velocity. Thus, the force transmitted to the front gear 306 from the rear gear 310 by the synchronizing shaft 302 is met with a counter force. Specifically, the teeth 322 of the front gear 306 counter the force applied thereto by the threads 314 of the first threaded portion 312 at the first end 304. This counter force substantially prevents the rotational velocity of

19

the synchronizing shaft 302, which includes the second threaded portion 318, from increasing. Stated otherwise, the force applied is sufficient to prevent the second end 308 of the synchronizing shaft 302 from rotationally advancing ahead of the first end 304. As the second threaded portion 318 is prevented from experiencing an increase in rotational velocity, the second threaded portion 318 provides a counter force to the rear gear 310. Specifically, the threads 320 of the second threaded portion 318 counter the force applied thereto by the teeth 322 of the rear gear 310. Thus, the synchronizing shaft 302 constrains the relative motion of the front gear 306 and rear gear 310, and, thereby constrains the relative motion of the front shaft assembly 44 and the rear shaft assembly 46.

Another embodiment of a running belt retention system used to induce and maintain the running belt in a desired non-planar shape to define the running surface is seen in FIG. 15, specifically a braking system 400 configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface is shown according to an exemplary embodiment. Please note, the section lines 15-15 shown in FIG. 4 do not necessarily suggest that the braking system 400 seen in FIG. 15 is integrated into the manual treadmill depicted in FIG. 4, rather, the section line 15-15 is included in FIG. 4 to show one potential location for the integration of a braking system into a manual treadmill according to the various innovations disclosed herein. The braking system 400 is shown in cooperation with the rear shaft assembly 402 and the synchronizing system 222. The rear shaft assembly 402 differs from the above-discussed rear shaft assembly 46 in that the rear shaft assembly 402 includes a pair of rear running belt pulleys 404 that are substantially the same size as the front running belt pulleys (not shown).

The braking system 400 has substantially the same effect as the differently sized front and rear running belt pulleys discussed above. That is, the braking system 400 causes a slight amount of excess running belt 16 in the area between the front running belt pulleys and the rear running belt pulleys. More specifically, the braking system 400 causes the rotational velocity of the rear shaft assembly 402 to be slightly lower than the rotational velocity of the front shaft assembly by applying a frictional force to the rear synchronizing belt pulley 204. Thus, the braking system 400 acts on the synchronizing system 222 to force (e.g., urge, push, move, etc.) the rear shaft assembly 402 out of synch with the front shaft assembly.

The braking system 400 includes a generally elongated member 406 in cooperation with the synchronizing system 222. The elongated member 406 is coupled to the rear shaft assembly 402 by a bracket 408 having a first side 410 spaced a distance apart from an outer surface 250 of the rear synchronizing belt pulley 204. The elongated member 406 is disposed through an aperture 412 of the bracket 408 and includes a first end 414 disposed to the inside of the first side 410 and a second end 416 disposed to the outside of the first side 410. The first end 414 includes a surface 418 configured to contact the outer surface 250 of the rear synchronizing belt pulley 204. The second end 416 includes a knob 420 configured to be gripped by a person (e.g., a user, a trainer, etc.) and to have a rotational force imparted thereto. An exterior surface of the elongated member 406 is at least partially threaded to correspond to threading at an interior surface defining the aperture 412. Rotating the knob 420, and, thereby, the elongated member 406, in one direction, causes the surface 418 to be advanced toward the outer surface 250 of the rear synchronizing belt pulley 204, and

20

rotating the knob 420 in the opposite direction causes the surface 418 to retreat or be moved away from the outer surface 250 of the rear synchronizing belt pulley 204.

During operation of the treadmill, the surface 418 of the elongated member 406 is substantially in contact with the outer surface 250 of the rear synchronizing belt pulley 204, creating friction therebetween. As the rear synchronizing belt pulley 204 of the synchronizing system 222 is fixed relative to the rear shaft assembly 402, some of the force directed to the rear shaft assembly 402 to impart rotation thereto must be used to overcome the frictional force between the surface 418 of the elongated member 406 and the outer surface of the rear synchronizing belt pulley 204. As the force needed to overcome the frictional force between the surface 418 of the elongated member 406 and the outer surface 250 of the rear synchronizing belt pulley 204 is no longer being directed into rotation of the rear shaft assembly 402, the rotational velocity of the rear shaft assembly 402 is less than the rotational velocity of the front shaft assembly. Thus, the front running belt pulleys of the front shaft assembly will “push” the running belt rearward, creating a slight amount of excess running belt 16 in the area between the front running belt pulleys and the rear running belt pulleys. This excess length of running belt 16 helps to counter the force of gravity, discussed in more detail above. It should be noted that, because the friction between the surface 418 of the elongated member 406 and the outer surface 250 of the rear synchronizing belt pulley 204 is substantially constant during operation, the rotational velocity will be substantially maintained at the lower rotational velocity.

The length of excess running belt “pushed” rearward by the front running belt pulleys can be varied by adjusting the position of the surface 418 relative to the outer surface 250 of the rear synchronizing belt pulley 204. If one moves the surface 418 laterally closer to the outer surface 250, the friction therebetween will increase, the differential between the rotational velocity of the rear shaft assembly and the front shaft assembly will increase, and the length of the excess will increase. If one moves the surface 418 away from the outer surface 250, the friction therebetween will decrease (or be removed if they are brought out of contact), the differential between the rotational velocity of the rear shaft assembly and the front shaft assembly will decrease, and the length of the excess will decrease.

According to another exemplary embodiment, the braking system 400 may be used with front and rear running belt pulleys that have a size differential. In such an embodiment, the braking system 400 would be used to fine tune the length of excess running belt pushed rearward with each rotation of the front and rear running belt pulleys.

FIG. 16 illustrates another exemplary embodiment of a braking system, shown as braking system 500, configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface. Please note, the section lines 16-16 shown in FIG. 4 do not necessarily suggest that the braking system 500 seen in FIG. 16 is integrated into the manual treadmill depicted in FIG. 4, rather, the section line 16-16 is included in FIG. 4 to show one potential location for the integration of a braking system into a manual treadmill according to the various innovations disclosed herein. The braking system 500 includes a pulley 502 mounted to a rear shaft assembly 504 generally opposite a front shaft assembly, both shaft assemblies having running belt pulleys that are substantially the same size. A belt 506 rotationally couples the pulley 502 to an idler pulley 508. The idler pulley 508 is configured to be adjustable so that it

21

may be moved towards or away from the pulley 502 along an axis generally parallel to the longitudinal axis 18. Though, it should be noted that the idler pulley may be moved relative to the pulley 502 mounted to the rear shaft assembly along an axis other than one generally parallel to the longitudinal axis 18.

By adjusting the position of the idler pulley 508 relative to the pulley 502, one can adjust the friction between the belt 506 and the pulleys 502, 508. Moving the idler pulley 508 away from the pulley 502, increases the tension in the belt 506, and, accordingly, increases the friction between the belt 506 and the pulleys 502, 508. Moving the idler pulley 508 toward the pulley 502, decreases the tension in the belt 506, and, accordingly, decreases the friction between the belt 506 and the pulleys 502, 508.

Similar to the discussion of braking system 400, increasing the friction between the belt 506 and the pulleys 502, 508, increases the differential between the rotation of the rear shaft assembly to which the braking system 500 is coupled and the front shaft assembly. As a corollary, decreasing the friction between the belt 506 and the pulleys 502, 508, decreases the differential between the rotational velocity of the rear shaft assembly 504 and the front shaft assembly. As discussed above, the greater the differential, the greater the length of the excess that the front running belt pulleys push rearward.

FIG. 17 illustrates another exemplary embodiment of a running belt retention system of the treadmill 10 used to help induce and maintain the running belt in a desired non-planar shape to define the running surface. The treadmill 10 is shown including a plurality of rollers 600 used to support the running belt 16 in place of bearing rails 200, discussed above.

The each roller 600 is shown extending laterally generally between the left-hand side member 52 and the right-hand side member 54 of the frame 40. Along the longitudinal axis 18, the rollers 600 are disposed adjacent to one another generally between one or more front running belt pulleys 604 and one or more rear running belt pulleys 606. Typically, the running belt used with this exemplary embodiment is a continuous polymer belt without slats; the use of a continuous polymer belt having greater flexibility in the lateral direction than running belt 16 improves the ease of movement of the running belt along the rollers 600. However, other suitable continuous belts may be used according to other exemplary embodiment

In the exemplary embodiment shown, the one or more front running belt pulleys is shown as a single, front running belt pulley 604 that is substantially a large roller, disposed at the front end 48 of the frame 40. Similarly, the one or more rear running belt pulleys is shown as a single, rear running belt pulley 606 that is a substantially a large roller, disposed at the rear portion of the frame 40. According to other exemplary embodiments, any multiple of running pulleys may be used at one or both of the front end and the rear end, such as front running belt pulleys 62.

Collectively, the rollers 600 define a top profile 608 similar to the top profile 210 defined by the bearing rails 200, discussed above, and provide for a running belt to move therealong. Similar to the top profile of the bearing rails, the top profile 608 defined by the rollers may be varied (e.g., may include a convex portion and a concave portion, may be modeled by a third-order polynomial, may be modeled by a fourth-order polynomial, etc.).

The front and rear running belt pulleys 604, 606 and the rollers 600 help define the running surface. In use, the running belt is disposed over the front running belt pulley

22

604, along the top profile 602 defined by the rollers 600, and over the rear running belt pulley 606. The running belt is maintained in a position substantially along these elements primarily by the weight of the running belt; however, according to other exemplary embodiments, a synchronizing system may also be used to ensure that the running belt is maintained in the desired position.

Referring to FIGS. 18-21, an embodiment of a running belt retention system including a track system 700 and configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface according to an exemplary embodiment.

A treadmill according to this exemplary embodiment does not include front and rear shaft assemblies or bearing rails, but, rather, includes a pair of opposed tracks 702 configured to provide for movement of a running belt 16 therealong. The tracks 702 are spaced apart, generally define the path that the running belt 16 will travel, and substantially replicate at least a portion of the running surface. Each track 702 includes a side support wall 708 and a guide portion 710 generally centrally-disposed along the side support wall 708. The guide portion 710 extends from an inner side 712 of the side support wall 708 towards the interior of the treadmill frame, defined generally between the left-hand side member and the right-hand side member. The guide portion 710 generally defines the contour of the running surface that is defined by the running belt 16 when coupled to the tracks 702. An outer side 714 each side support wall 708 is disposed substantially adjacent to an inner surface of one of the side members of the treadmill frame.

A plurality of roller or wheel assemblies 716 are connected with, preferably mounted directly to or integral with, each of a plurality of slats 228 of the running belt 16. Each a laterally-oriented slat 228 includes a left-hand end 252 generally opposite a right-hand end 254. One of a plurality of wheel assemblies 716 is coupled at each end 252, 254 of each slat 228 at an interior surface 256. The wheel assemblies 716 are configured to be mated with the tracks 702 and provide for motion of the running belt 16 along the tracks 702.

Each wheel assembly 716 is shown including first roller or wheel 720 and a second roller or wheel 722 rotatably coupled to a support shown as an elongated connecting member 724. The connecting member 724 connects each wheel assembly 716 to a slat 228 and maintains the relative position of the first wheel 720 and the second wheel 722. When coupled to the track 702, the first wheel 720 of a wheel assembly 716 is disposed to one side the guide portion 710 and rotatably movable therealong, and the second wheel 722 of the wheel assembly 716 is disposed generally opposite the first wheel 720 to the other side of the central guide portion 710.

The wheels 720, 722 and the tracks 702 are shaped such that when they are mated, the wheels 720, 722 cannot be pulled inwardly off of or pushed outwardly off of the track 702. In the exemplary embodiment shown, the guide portion 710 is shown having a substantially-circular cross section 724 and the wheels 720, 722 are shown having circumferentially-disposed arcuate depressions 726 that receive and travel along an outer curved portion 728 and an inner curved portion 730 of the guide portion 710 of the track 702. According to other exemplary embodiments, the wheels and the track guide portion can have substantially any corresponding shapes that provide for the wheels and the track to mate and that provide for movement of the wheels therealong.

23

When the running belt 16 is being driven by a user, the interaction of the guide portion 710 and the first and second wheels 720, 722 helps maintain the belt in the desired non-planar shape. As mentioned above, the tracks 702 generally defines the contour of the running surface defined by the running belt 16. Being coupled to the guide portion 710 of the track 702, each wheel assembly 716 rotates about the track 702, following the contour defined thereby.

If the running belt 16 began to deviate from the desired path, the interaction between the wheels 720, 722 and the guide portion 710 would substantially prevent undesirable shifting. While being rotatably coupled to the elongated connecting member 724, the axes 732 and 734 of the first wheel 720 and second wheel 722, respectively, are a fixed distance apart. Further, the arcuate depressions 726 of the wheels 720, 722 are in contact with the outer curved portion 728 and inner curved portion 730, respectively. Thus, as a result the interactions between the arcuate depressions 726 and the curved portions 728, 730, any movement of a wheel assembly 716 relative to the track 702 other than along the path defined by the track 702 is countered by a force from the guide portion 710. It should also be noted that the interactions between the depressions 726 of adjacent wheel assemblies 716 and the curved portions 728, 730 of the track 702 may also help keep a wheel assembly 716 in place.

Referring to FIGS. 22-24, the treadmill 10 is shown including another exemplary embodiment of a track system configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface, shown as a track system 800. Similar to track system 700, a treadmill according to this exemplary embodiment does not include front and rear shaft assemblies or bearing rails, but, rather, includes a pair of tracks 802 configured to provide for movement of a running belt 16 therealong. In this exemplary embodiment, each track 802 is shown as an elongated member having a substantially C-shaped cross section that defines a channel 804 having an opening 806 that faces the interior of the frame 40. An outer wall 808 each of the tracks 802 is disposed substantially adjacent to an inner surface of a left-hand or right-hand side member 52, 54 (shown, e.g., in FIG. 2) such that the openings 806 face each other. The outer wall 808 is substantially opposite an inner wall 810.

As discussed above, the running belt 16 includes a plurality of laterally-oriented slats 228 each having a left-hand end 252 generally opposite a right-hand end 254. One of a plurality of roller or wheel assemblies 812 is coupled at each end 252, 254 of each slat 228 to mate with the tracks 802 and to provide for motion of the running belt 16 along the tracks 802.

Each wheel assembly 812 is shown including a support shown as a mounting block 814 and a wheel 816 rotatably coupled to the mounting block 814. The mounting block 814 mounted to an interior surface 256 of a slat 228. The wheel 816 is supported relative to the mounting block 814 by an axis 818 that extends substantially parallel to the slats 228 to facilitate positioning the wheel 816 in the channel 804. The wheel 816 is received in the channel 804 and is rotatably movable therewithin to facilitate travel of the running belt 16 along the contour defined by the channel 804. The shape of the channel 804 generally corresponds to the shape of the wheel 816.

When the running belt 16 is being driven by a user, the walls of the track 802 defining the C-shaped channel 804 help forcibly retain the wheel 816 therein, preventing the wheel from moving in any direction other than along the contour defined by the channel 804, and, thereby, maintaining the running belt 16 in the desired non-planar shape to

24

define the running surface. The outer wall 808 and the inner wall 810 limit the side-to-side, lateral movement of the wheel 816 when it is disposed in the channel 804. Limiting the motion of the wheel 816, similarly limits the motion of the wheel assembly 812 and the slat 228 fixed relative thereto. Further, a first wall 820 substantially opposite a second wall 822 substantially limits the up-and-down motion of the wheel 816 relative to the channel 804. In circumstances where side-to-side and/or up-and-down motion of the wheel 816 occurs, the walls 808, 810, 820, 822 defining the channel 804, providing counter forces to maintain the wheel 816 in the desired position and help direct the wheel 816 along the desired path.

Referring to FIGS. 25-28, the treadmill 10 is shown including still another exemplary embodiment of a track system configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface, shown as a track system 900. Similar to track system 800, the treadmill according to this exemplary embodiment does not include bearing rails, but, rather, includes a pair of tracks 902 configured to provide for movement of a running belt 16 therealong. In this exemplary embodiment, each track 902 is shown as an elongated member having a substantially C-shaped cross section that defines a channel 904 having an opening 906 that faces the exterior of the track 902. Stated otherwise, each channels 904 extend about an outer periphery 908 of a tracks 902.

As discussed above, the running belt 16 includes a plurality of laterally-oriented slats 228 each having a left-hand end 252 generally opposite a right-hand end 254. One of a plurality of roller or wheel assemblies 910 is coupled at each end 252, 254 of each slat 228 to mate with the tracks 902 and to provide for motion of the running belt 16 along the tracks 902.

Each wheel assembly 910 is shown including a support shown as a connecting bar 912 that is substantially T-shaped and connected to a first wheel 914 and a second wheel 916. A first portion 918 of the connecting bar 912 is fixed relative to the interior surface 256 of a slat 228. A second portion 920 extends substantially perpendicular to the first portion 918 and away from the interior surface 256 of the slat 228. The first wheel 914 and the second wheel 916 are connected to the connecting bar 912 by an axis 922 that extends generally parallel to the first portion 918 and perpendicular to the second portion 920 of the connecting bar 912. The first wheel 914 is disposed to one side of the second portion 920 of the connecting bar 912 and the second wheel 916 is disposed opposite the first wheel 914 to the other side of the second portion 920.

When the wheel assemblies 910 are mated with the tracks 902, the second portion of the connecting bar 912 extends partially into the channel 904, the first wheel 914 is received within a first portion 924 of the channel 904 and the second wheel 916 is disposed within a second portion 926 of the channel 904. The first portion 924 of each channel 904 is disposed proximate to an outer surface 928 of the track 902 relative to the second portion 926.

When the running belt 16 is being driven by a user, the first wheel 914 and the second wheel 916 of a given wheel assembly rotate within the channel 904, facilitating moment of the running belt 16 in the path defined by the track 902. As the running belt 16 is rotated, the slats 228 are disposed generally exterior to the periphery 908 of the track 902. The walls of the track 902 defining the channel 904 help forcibly retain the wheels 914, 916. An outer wall 930 and an inner wall 932 limit the side-to side movement of the wheels 914, 916, either by coming into contact with the wheels 914, 916

25

themselves or by coming into contact with another part of the wheel assembly **910** (e.g., the connecting bar **912**). Limiting the motion of the wheels **914**, **916** and the wheel assembly **910** similarly limits the motion of the slat fixed relative thereto, helping each slat, and, thereby, the running belt **16** to follow the desired path. Further, a first wall **934** substantially opposite a second wall **936** substantially limits the up-and-down motion of the wheels **914**, **916** relative to the channel **904**. In circumstances where side-to-side and/or up-and-down motion of the wheel **916** occurs, the walls **930**, **932**, **934**, **936** defining the channel **904**, providing counter forces to maintain the wheels **914**, **916** in the desired position and help direct the wheels **914**, **916** along the desired path.

Referring to FIGS. **29-30**, the treadmill **10** is shown including another exemplary embodiment of a track system configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface, shown as a track system **1000**.

Instead of using wheel assemblies, such as **716** and **910**, discussed above, the treadmill according to this exemplary embodiment utilizes a plurality of magnets **1002** to maintain the running belt **16** in the desired position. One or more magnets **1002** are fixed relative to the interior surface **256** of the slats **228** at locations substantially corresponding to the position of a track **1004**, which is typically along the left-hand end **252** and the right-hand end **254** of the slats **228**. The magnets **1002** may be coupled by any variety of fasteners or fastening mechanisms. Generally, it is preferable that, when the magnets **1002** are fixed relative to the slats, the fasteners do not directly contact the periphery **1006** of the tracks **1004** to avoid scratching and damage thereto. While it is generally desirable to mount a magnet **1002** to each slat, **228**, the number of magnets used will vary depending upon a variety of factors such as the relative weight of the belt and the relative magnetic strength of each magnet.

The magnets **1002** are configured to magnetically couple the running belt **16** to the track **1004**, which is made of metal (e.g., steel) or includes a peripheral metal portion. The magnets **1002** have strength suitable to maintain the running belt **16** in close proximity to a periphery **1006** of the tracks **1004**.

When the treadmill is driven by a user, the force imparted to the running belt **16** is sufficient to permit the magnets to move relative bearing rails, but not to lose the magnetic connection therebetween. According to one exemplary embodiment, as the running belt **16** moves relative to the track **1004**, the magnets **1002** are generally spaced a small distance from the periphery **1006** of the track **1004**, helping to further reduce the noise associated with operation of the treadmill. According to other exemplary embodiments, the magnets **1002** are in physical contact with the periphery **1006** of the track **1004** in addition to being magnetically coupled thereto.

According to an exemplary embodiment similar to track system **1000**, a plurality of magnets may be positioned on the frame, track, or other fixed component of the treadmill base to apply a downwardly-directed force to the metal slats of the running belt as it passes over the magnets. For example, the magnets may be positioned on the cross-members **56**. As the running belt rotates, the portion passing above the magnets will be drawn downward by the force of the magnets, helping maintain that portion of the running belt (i.e., defining the running surface) in the desired shape.

Referring to FIGS. **31-34**, the treadmill **10** is shown including another exemplary embodiment of a track system

26

configured to help induce and maintain the running belt in a desired non-planar shape to define the running surface, shown as a track system **1100**.

The track system **1100** is substantially similar to track system **700**, but configured to be operable with a running belt **1102** that is a conventional running belt rather than a slatted running belt **16**. The track system **1100** includes a pair of tracks **702** and a wheel assemblies **1104** having substantially the same configuration as wheel assembly **716** with the exception that a securing device shown as a clip **1106** is used to connect the wheel assembly **1104** to the running belt **1102**, rather than the elongated connecting member **724**. The clip **1106** is shown extending and having a first portion **1108** and a second portion **1110** that opening towards the interior of the treadmill **10** before being secured. When the running belt **1102** shown as a continuous polymer (e.g., urethane) belt is in position, a first edge **1112** of the running belt **1102** is received between a first portion **1108** and a second portion **1110** of the clip **1106** and fixed relative thereto (e.g., by a fastener, etc.). The polymer belt is a urethane belt according to an exemplary embodiment. The urethane belt is desirable heavy enough to help assume the shape of the rollers, but not so thick or heavy that it undesirably impedes movement. The clips extend along the first edge **1112** and the second edge **1114** of the running belt **1102**, substantially suspending the belt between the tracks **702**. According to an exemplary embodiment, the securing device may be any securing device suitable for securing an edge portion of the running belt **1102** relative thereto (e.g., a bolt, a clamp, etc.).

According to still another exemplary embodiment, a treadmill has a track system including a pair of tracks and wheel assemblies. The wheel assemblies include hangers (e.g., magnetic hangers) that are received in channels that are interior to the track, the hangers being slidably movable within the channels. According to one exemplary embodiment, the hangers are substantially I-shaped, having one transverse portion received in the channel and the other transverse portion fixed to an interior side of a slat. According to some exemplary embodiments, the system further includes bearing rails that facilitate motion of the running belt itself and the hangers within the track. The hangers and the channel of the track may have any configuration suitable for facilitating movement of the running belt and maintaining the running belt in the desired non-planar shape.

The above-described ways of inducing and maintaining the running belt in the desired non-planar shape can also be used with or adapted to a manual treadmill having a planar running surface, such as treadmill **1200** having planar running surface **1202** shown in FIG. **35**. The treadmill **1200** is shown substantially similar to treadmill **10**, but the running surface is substantially planar. Accordingly, the ability to manually drive the treadmill is substantially dependent on the incline of the running surface **1202** relative to the ground. Ways to adjust this incline for any treadmill disclosed herein will be discussed in more detail later.

In the exemplary embodiment shown, the running surface **1202** is defined by a running belt **1204** that is disposed about front and rear running belt pulleys of a front and rear shaft assembly, respectively. The running belt **1204** also travels along a pair of bearing rails having a substantially linear top profile that facilitate motion of the running belt **1204**.

As discussed above, the speed controls for the manual treadmill **10** and the various embodiments thereof are generally the user's cadence and relative position of her weight-bearing foot on the running surface. More generally, the running belt **16** of the treadmill **10** is responsive to the

weight of the user mounting, dismounting, or running on the treadmill 10. While it is generally desirable for the running belt 16 to be moved rearward, the running belt is capable of rotating forward. Forward rotation of the running belt can create safety concerns. For example, if a user were to mount the treadmill by placing her weight bearing foot at a location (e.g., location D shown in FIG. 5) along the rear portion 74 of the running surface 70, the running belt 16 may move forward and cause them to lose their footing, resulting in an injury or simply an unpleasant user experience.

A number of safety devices may be used with the treadmill 10 to help prevent undesirable forward rotation of the running belt 16. FIG. 36 illustrates a safety device shown as a one-way bearing assembly 1300 according to an exemplary embodiment. The one-way bearing assembly 1300 is a motion restricting element that is configured to permit rotation of at least one of the front and rear shaft assemblies 44, 46 (and hence the running belt 16) in only one direction, preferably clockwise as seen in FIGS. 1 and 5.

In the exemplary embodiment shown, the one way bearing assembly 1300 is disposed about and cooperates with the rear shaft 68 as shown in FIG. 2. The one-way bearing assembly 1300 comprises a housing 1302 which supports an inner ring 1304 that cooperates with the rear shaft 68 and supports an outer ring 1306 fixed relative to the housing 1302. A plurality of sprags (not shown) are disposed between the inner ring 1304 and the outer ring 1306. The sprags are asymmetric, and, thus, provide for motion in one direction and prevent rotation in the opposite direction. The housing 1302 is fixed to a bracket 1310 that is connected to, and preferably directly mounted to, the frame 40 to fix the location of the housing 1302 and prevent movement of the housing 1302 in response to the rotation of the rear shaft 68. It should be noted that the location at which the bracket 1310 is mounted to the frame 40 can be adjusted depending on the location of the rear shaft 68, which may change depending on the shape of the non-planar running surface or the desired tension in the running belt. According to another exemplary embodiment, the one-way bearing may be transitionally fit into the housing, rather than press fit. According to yet another exemplary embodiment, the one-way bearing may include rollers in addition to sprags.

The one-way bearing assembly 1300 further includes a key 1312 that is fixed relative to the inner ring 1304 and configured to cooperate with a keyway 1314 formed in the rear shaft 68. Viewed from the perspective shown in FIGS. 1 and 5, when the running belt 16 is moving rearward, rotating in the clockwise direction, the rear shaft 68 similarly rotates in the clockwise direction. The inner ring 1304 of the one-way bearing assembly 1300 rotates with rotational velocity corresponding to the rotational velocity of the rear shaft 68 because of the interaction between the key 1312 and the keyway 1314. If a force is applied by the user to the running belt 16 that urges the rear shaft 68 to rotate counterclockwise, the one-way bearing assembly 1300 provides a counter force, preventing the counterclockwise rotation of the rear shaft 68 and the forward rotation of the running belt 16. Specifically, as the rear shaft 68 begins to move counterclockwise, the interaction of the key 1312 and the keyway 1314 begins to drive the inner ring 1304 of the one-way bearing assembly 1300 rearward. The sprags become wedged between the inner ring 1304 and the outer ring 1306, preventing the counterclockwise rotation of the inner ring and key 1312 disposed therein. The key 1312, by virtue of its inability to rotate, provides a counterforce to the keyway 1314 as the keyway continues to attempt to rotate counterclockwise. By preventing the keyway 1314 from

moving counterclockwise, the one-way bearing assembly 1300 thus prevents the rear shaft 68, the rear running belt pulleys 66, and running belt 16 from rotating counterclockwise as seen in FIGS. 1 and 5.

FIG. 38 illustrates another safety device that may be used with the treadmill 10, shown as a one-way bearing assembly 1500 according to an exemplary embodiment. The one-way bearing assembly 1500 is a motion restricting element that is configured to permit rotation of at least one of the front and rear shaft assemblies 44, 46 (and hence the running belt 16) in only one direction, preferably clockwise as seen in FIGS. 1 and 5.

In the exemplary embodiment shown, the one-way bearing assembly 1500 is disposed about and cooperates with the rear shaft 68. The one-way bearing assembly 1500 comprises a housing 1502 which supports an inner ring 1504 that cooperates with the rear shaft 68 and supports an outer ring 1506 fixed relative to the housing 1502. A plurality of sprags (not shown) are disposed between the inner ring 1504 and the outer ring 1506. The sprags are asymmetric, and, thus, provide for motion in one direction and prevent rotation in the opposite direction. The one-way bearing assembly 1500 is further shown to include a first snap ring 1532 and a second snap ring 1534, which are configured to seat in a first circumferential groove 1536 and a second circumferential groove 1538 on the rear shaft 68, respectively. When installed, the first snap ring 1532 is supported inboard of and adjacent to the inner ring 1504, and the second snap ring 1534 is supported outboard of and adjacent to the inner ring 1504, thereby further restricting axial motion of the one-way bearing assembly 1500 relative to the rear shaft 68.

The housing 1502 is supported by a stud 1520 which is coupled to the frame 40. The stud 1520 may be separated or spaced apart from the housing 1502 by a spacer 1522 and a sleeve 1523 which may be restrained on the stud 1520 by a nut 1524 and a washer 1526. The sleeve 1523 of the embodiment shown is formed of rubber and is configured to reduce noise, wear, and shock load between the housing 1502 and the stud 1520 and/or the spacer 1522. The housing 1502 includes a plurality of legs, shown as a first leg 1516 and a second leg 1518, which extend on either side of the stud 1520. Accordingly, the stud 1520 resists rotational motion of the housing 1502 in response to rotation of the rear shaft 68 and may provide sufficient reactive or counter force to the housing 1502 to enable the one-way bearing assembly 1500 to prevent counterclockwise rotation of the rear shaft 68. Supporting the one-way bearing assembly 1500 in this manner negates the need for fixing the housing 1502 to the frame 40 or an intermediary bracket. Accordingly, the housing 1502 may move with the rear shaft 68 (e.g., the housing 1502 may pivot about the stud 1520) as the rear shaft 68 flexes under load, thereby reducing side loading on the inner ring 1504, which in turn reduces wear on, and extends the life of, the one-way bearing assembly 1500.

It should be noted that the location at which the stud 1520 is mounted to the frame 40 can be adjusted depending on the location of the rear shaft 68, which may change depending on the shape of the non-planar running surface or the desired tension in the running belt. Furthermore, the stud 1520 need not be positioned below or downward from the rear shaft 68, as shown, but may be located in any direction relative to the rear shaft 68. According to another exemplary embodiment, the one-way bearing may be transitionally fit into the housing, rather than press fit. According to yet another exemplary embodiment, the one-way bearing may include rollers in addition to sprags.

29

The one-way bearing assembly **1500** further includes a key **1512** that is fixed relative to the inner ring **1504** and configured to cooperate with a keyway **1514** formed in the rear shaft **68**. Viewed from the perspective shown in FIGS. **1** and **5**, when the running belt **16** is moving rearward, rotating in the clockwise direction, the rear shaft **68** similarly rotates in the clockwise direction. The inner ring **1504** of the one-way bearing assembly **1500** rotates with rotational velocity corresponding to the rotational velocity of the rear shaft **68** because of the interaction between the key **1512** and the keyway **1514**. If a force is applied by the user to the running belt **16** that urges the rear shaft **68** to rotate counterclockwise as seen in FIGS. **1** and **5**, the one-way bearing assembly **1500** provides a counter force, preventing the counterclockwise rotation of the rear shaft **68** and the forward rotation of the running belt **16**. Specifically, as the rear shaft **68** begins to move counterclockwise, the interaction of the key **1512** and the keyway **1514** begins to drive the inner ring **1504** of the one-way bearing assembly **1500** rearward. The sprags become wedged between the inner ring **1504** and the outer ring **1506**, preventing the counterclockwise rotation of the inner ring and key **1512** disposed therein. The key **1512**, by virtue of its inability to rotate, provides a counterforce to the keyway **1514** as the keyway continues to attempt to rotate counterclockwise. By preventing the keyway **1514** from moving counterclockwise, the one-way bearing assembly **1500** thus prevents the rear shaft **68**, the rear running belt pulleys **66**, and running belt **16** from rotating counterclockwise as seen in FIGS. **1** and **5**.

Other safety devices to help prevent undesirable forward rotation of the running belt **16** may include cam locking systems, which may be particularly well-suited for use in conjunction with track systems **700**, **800**, and **900**. Also, taper locks, a user operated pin system, or a band brake system with a lever may be utilized.

Controlling the operation of the running belt **16** in ways in addition to preventing rearward rotation, can help improve the safety of the treadmill and/or help a user adjust the treadmill for a desirable level of performance. Including an incline or elevation adjustment system is one way to provide these benefits. As mentioned above, as the increasing or decreasing of the relative height or distance of the running surface relative to the ground is one way that the operation, most typically the speed, of the treadmill can be adjusted. Accordingly, adjusting the incline of the base of the treadmill results in an adjustment to the speeds a user can achieve and/or how easy or challenging it is for the user to achieve certain speeds.

Referring back to FIGS. **1-6**, a plurality of nuts **270** are fixed, and more preferably welded, to the bottom of the frame **40** allow the feet **28** to be adjusted. The feet **38** include a lower or base portion **272** and a threaded shaft **274** extending vertically upward from the base portion **272** according to an exemplary embodiment. Generally, by increasing the distance between the nuts **270** and the base portions **272** of the feet **28** at the front end **48** of the frame **40** relative to the rear end **50**, the incline of the base **12** will increase. Stated otherwise, the angle between the longitudinal axis **18** and the ground will increase. Similarly, the distance between the nuts **270** and the base portions **272** of the feet at the rear end **50** may be decreased relative to the feet **28** at the front end **48**, thereby increasing the incline. By increasing the incline, a user is typically able to achieve greater speeds on the treadmill **10**.

Treadmill **1200** shown in FIG. **35** preferably has at least some incline (i.e., the longitudinal axis of the treadmill to be other than parallel to the ground) when in operation as the

30

shape of the running surface, substantially planar, does not provide for increases and decreases in height in and of itself. On the other hand, the longitudinal axes of the treadmills having non-planar running surfaces may be parallel to the ground or at an incline thereto during operation. It should be noted that, while it is generally desirable to have the front shaft at a height at or above the height of the rear shaft, with some running surface configurations, desirable orientations can be achieved by raising the rear shaft to a location above the front shaft relative to the ground.

In some cases, the user may want to decrease the incline of the treadmill (e.g., to decrease the speeds the treadmill can achieve, etc.). For example, the user may want to utilize a relatively long stride, but does not want to be running at such high speeds. This can be accomplished by lowering the incline of the treadmill from the higher incline position. Once in the lowered position, the same stride the user was using at the higher incline position will typically result in the user running at lower speeds in the lower incline position. This same principle can also be applied for the purposes of safety. That is, keeping the front of the treadmill at a lower incline position or lowering the treadmill to a lower incline position can help prevent a user from achieving speeds that are too great for them (e.g., that would cause them to be off-balance, lose control, be injured, etc.).

Because the treadmill is preferably manually operated, it does not have an external power source which can be utilized to operate a height adjusting motor as is found in conventional treadmills. Therefore, a manual height adjusting system is preferably integrated into the treadmill. Referring to FIG. **37**, an example of a manual incline or elevation adjustment system **1400** is shown according to an exemplary embodiment. A hand crank **1402** configured to be operated by a person, such as the user, is provided allow a user to operate the incline adjustment system **1400** to adjust the incline of the base **12** of the treadmill **10** relative to the ground. The front shaft **64** may be lowered relative to the rear shaft **68** and/or the front shaft **64** may be raised relative to the rear shaft **68** using the hand crank **1402**. In an alternative exemplary embodiment, the front shaft may be maintained at a position above the ground, and the rear shaft may be raised or lowered relative thereto adjust the incline.

Generally, the hand crank **1402** includes a handle portion **1404** disposed parallel to and spaced a distance from a shaft **1406** that is coupled to the frame **40** (e.g., with a bracket). When assembled, a drive belt or chain **1407** is disposed about a gear **1408** that is positioned about the shaft **1406** of the hand crank **1402**. Rotational motion can be imparted to the gear **1408** by rotating the handle portion **1404**. In response to rotation of the gear **1408**, the drive belt **1407** causes a sprocket **1410** is fixed relative to an internal connecting shaft **1412** of the internal connecting shaft assembly **1414** to rotate. The internal connecting shaft assembly **1414** further includes a pair of drive belts or chains **1416** that are operably coupled to gears **1418** of rack and pinion blocks **1420**. The rotation of the internal connecting shaft **1412** causes the drive belts or chains **1416** to rotate gears **1418**. As the gears **1418** rotate, a pinion (not shown) disposed within the rack and pinion blocks **1420** imparts linear motion to the racks **1422**, thereby operably raising or lowering the base **12** of the treadmill **10** depending on the direction of rotation of the handle portion **1404** of the hand crank **1402**.

According to another exemplary embodiment, an incline adjustment system that is a gas assisted un-weighting incline adjustment system may be utilized. According to other

31

exemplary embodiments, any suitable linear actuator may serve as an incline adjustment system for the manual treadmill disclosed herein.

According to an exemplary embodiment, the incline of one or more portions of the running surface may be adjusted independent of adjusting the incline of the base. For example, one or more portions of a bearing rail may be configured to be movable relative to one or more other portion of the bearing rail. In one exemplary embodiment, a bearing rail is divided into a first portion and a second portion movable relative to each of the about a pivot point disposed therebetween. A person (e.g., a user, trainer, technician, etc.) can adjust the operational characteristics of the treadmill (similar to the discussion of using running surfaces having different curved profiles above) by merely adjusting the relative position of the bearing rail portions. If the user wants to achieve greater speeds, they may increase the incline of the front portion, while leaving the center and rear portions unchanged. If the user would like to alter the configuration of the treadmill to more strongly encourage running on the balls of their feet, they might increase the incline of the front and rear portions from a higher radius of curvature so that they collectively define a lower radius of curvature. Adjustments to the position of the bearing rails may be imparted using a crank, or other suitable device.

It is further contemplated that, because the treadmill **10** does not require an electric motor for operation, it is well suited for operation in an aquatic environment. For example, the treadmill **10** may be at least partially submerged in a pool, thereby providing added resistance due to hydrodynamic drag on a user and/or reducing footfall impact due to the buoyancy of the user. Accordingly, a submerged embodiment of the treadmill **10** may be used for training and/or rehabilitation purposes. Modifications may be made to the treadmill **10** for use in an aquatic environment. For example, the treadmill **10** may include sealed bearings and components formed of corrosion-resistant materials (e.g., plastic, composite, stainless steel, brass, etc.) to extend its useful life. Further, the shape of the running surface **70** may also be modified to compensate for the buoyancy of the user in water and to compensate for the effects of salinity on buoyancy. For example, it is contemplated that the shape of the running surface **70** may be different for a treadmill **10** used in a freshwater environment and a highly saline environment.

A number of other devices, both mechanical and electrical, may be used in conjunction with or cooperate with a treadmill according to this disclosure. FIG. 1, for example, shows a display **280** adapted to calculate and display performance data relating to operation of the treadmill according to an exemplary embodiment. The display **280** includes an independent power source (e.g., a battery) that provides for the display **280** to be electrically-operative. The feedback and data performance analysis from the display may include, but are not limited to, speed, time, distance, calories burned, heart rate, etc. For example, a the display may include a sensor that is responsive to the position of a magnet on one of the running belt pulleys. The sensor is configured to recognize every time the magnet rotates past (e.g., moves past, crosses, etc.) a certain location. With this data, the display may calculate the speed at which the user is running and then provide this data to them via a user interface. According to other exemplary embodiments, other displays, cup holders, cargo nets, heart rate grips, arm exercisers, TV mounting devices, user worktops, and/or other devices may be incorporated into the treadmill.

32

As utilized herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and are considered to be within the scope of the disclosure.

It should be noted that the term “exemplary” as used herein to describe various embodiments is intended to indicate that such embodiments are possible examples, representations, and/or illustrations of possible embodiments (and such term is not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

For the purpose of this disclosure, the term “coupled” means the joining of two members directly or indirectly to one another. Such joining may be stationary or moveable in nature. Such joining may be achieved with the two members or the two members and any additional intermediate members being integrally formed as a single unitary body with one another or with the two members or the two members and any additional intermediate members being attached to one another. Such joining may be permanent in nature or may be removable or releasable in nature.

It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

It is important to note that the constructions and arrangements of the manual treadmill as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited in the claims. For example, elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or position may be altered or varied. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes and omissions may also be made in the design, operating condition and arrangement of the various exemplary embodiments without departing from the scope of the present disclosure.

What is claimed:

1. A treadmill, comprising:

a frame;

a front running belt pulley coupled to the frame;

a rear running belt pulley coupled to the frame and spaced a distance from the front running belt pulley;

a plurality of bearings coupled to the frame;

a running belt at least partially supported by at least one of the front running belt pulley and the rear running belt

33

pulley, wherein the running belt includes a running surface, at least a portion of which is curved;

a support element coupled to the frame; and

a safety device coupled to the running belt, the safety device at least partially supported by the support element, wherein the safety device includes a first safety race element and a second safety race element, wherein at least one of the first and second safety race elements is adapted for rotation relative to the frame, and wherein one of the first and second safety race elements substantially surrounds the other of the one of the first and second safety race elements;

wherein one of the first and second safety race elements and the running belt freely rotates in a first direction of rotation relative to the frame, however, in a second direction of rotation, opposite the first direction of rotation, the one of the first and second safety race elements is substantially prevented from rotation relative to the frame to substantially prevent rotation of the running belt relative to the frame.

2. The treadmill of claim 1, wherein at least a portion of the support element defines a keyway.

3. The treadmill of claim 2, wherein the keyway is configured to receive a key such that the key engages with the support element and the safety device, the interaction between the key and keyway contributing to an engagement between the support element and at least a portion of the safety device.

4. The treadmill of claim 1, wherein the first and second safety race elements of the safety device at least partly form a one-way bearing.

5. The treadmill of claim 1, further comprising a braking system coupled to the frame and configured to selectively resist rotation of the running belt.

6. The treadmill of claim 5, wherein the braking system utilizes friction to apply a variable amount of force to resist the rotation of the running belt in the first direction of rotation.

7. The treadmill of claim 1, wherein the treadmill is a manually powered, non-motorized treadmill.

8. The treadmill of claim 1, further comprising at least one support foot coupled to the frame, wherein the at least one support foot is adjustable to adjust a relative vertical incline of at least a portion of the treadmill relative to a surface supporting the treadmill.

9. The treadmill of claim 1, wherein the frame comprises a left side member, a right side member, and at least one cross-member extending between the left side member and the right side member.

10. A treadmill, comprising:

a frame;

a rotatable element coupled to the frame;

a running belt at least partially supported by the rotatable element, wherein the running belt includes a running surface, at least a portion of which is curved; and

a first safety race element and a second safety race element, both of which are coupled to the running belt, wherein at least one of the first and second safety race elements is adapted for rotation relative to the frame, and wherein one of the first and second safety race elements substantially surrounds the other of the one of the first and second safety race elements;

wherein one of the first and second safety race elements and the running belt freely rotate in a first direction of rotation relative to the frame, however, in a second direction of rotation, opposite the first direction of rotation, the one of the first and second safety race

34

elements is substantially prevented from rotation relative to the frame to substantially prevent rotation of the running belt relative to the frame.

11. The treadmill of claim 10, wherein the treadmill is a manually powered, non-motorized treadmill.

12. The treadmill of claim 10, wherein the first and second safety race elements of the safety device at least partly form a one-way bearing.

13. The treadmill of claim 10, further comprising a braking system coupled to the frame and configured to selectively resist rotation of the running belt in the first direction of rotation.

14. The treadmill of claim 10, wherein the rotatable element comprises a running belt pulley coupled to the frame.

15. The treadmill of claim 10, wherein the running belt comprises a plurality of slats, and wherein at least one slat in the plurality of slats comprises a roller.

16. The treadmill of claim 15, wherein the at least one slat includes a top surface and wherein the roller is coupled to a member extending away from the top surface of the at least one slat.

17. The treadmill of claim 10, wherein the rotatable element comprises a plurality of bearings coupled to the frame, the plurality of bearings at least partially supporting the running belt.

18. A method, comprising:

providing a treadmill having a frame with a front end and a rear end;

providing a plurality of bearings coupled to the frame, wherein the plurality of bearings define at least a portion of a curved top profile;

disposing a running belt on the plurality of bearings such that the curved top profile of the plurality of bearings define at least a portion of a curved running surface of the running belt;

providing a first safety race element coupled to the frame and to the running belt and a second safety race element coupled to the frame, wherein at least one of the first and second safety elements is adapted for rotation relative to the frame, and wherein one of the first and second safety race elements substantially surrounds the other of the one of the first and second safety race elements;

permitting rotation of one of the first and second safety race elements and the running belt in a first direction of rotation; and

substantially preventing rotation of the running belt in a second direction, opposite the first direction, by, at least in part, the one of the first and second safety race elements.

19. The method of claim 18, further comprising providing for a selective application of a braking force to resist rotation of the running belt in the first direction.

20. The method of claim 18, wherein the treadmill is a manually powered, non-motorized treadmill.

21. A treadmill, comprising:

a frame;

a rotatable element coupled to the frame;

a running belt at least partially supported by the rotatable element, wherein the running belt includes a running surface, at least a portion of which is curved;

a support element coupled to the frame; and

a safety device coupled to the running belt, the safety device at least partially supported by the support element, wherein the safety device includes a first safety race element and a second safety race element, wherein

35

at least one of the first and second safety race elements is adapted for rotation relative to the frame, and wherein one of the first and second safety race elements substantially surrounds the other of the one of the first and second safety race elements;

wherein one of the first and second safety race elements and the running belt freely rotates in a first direction of rotation relative to the frame, however, in a second direction of rotation, opposite the first direction of rotation, the one of the first and safety race elements is substantially prevented from rotation relative to the frame to substantially prevent rotation of the running belt.

22. The treadmill of claim 21, wherein the rotatable element comprises at least one of a front running belt pulley coupled to the frame and a rear running belt pulley coupled to the frame and spaced apart from the front running belt pulley.

36

23. The treadmill of claim 21, wherein the rotatable element comprises at least one of a front rotatable shaft coupled to the frame and a rear rotatable shaft coupled to the frame and spaced apart from the front rotatable shaft.

24. The treadmill of claim 21, wherein the rotatable element comprises a running belt pulley coupled to the frame.

25. The treadmill of claim 21, wherein the first and second safety race elements of the safety device at least partly form a one-way bearing.

26. The treadmill of claim 21, wherein the support element comprises a rod.

27. The treadmill of claim 26, wherein at least a portion of the rod defines a keyway, wherein the keyway is configured to receive a key such that the key engages with the rod and the safety device.

* * * * *