

mptcp: UEK: disable mptcp protocol

[Browse files](#)

The protocol shall be disabled, and unable to be enabled via sysctl.

Orabug: 34821286

Signed-off-by: Jack Vogel <jack.vogel@oracle.com>

Reviewed-by: Qing Huang <qing.huang@oracle.com>

uek7/ga + uek7/u1

jfvogel committed on Jan 26

1 parent 4e178a8 commit 556818a

Showing 1 changed file with 8 additions and 0 deletions.

[Split](#) [Unified](#)

```

8 net/mptcp/ctrl.c
60 60
61 61     static void mptcp_pernet_set_defaults(struct mptcp_pernet *pernet)
62 62     {
63 63         + #ifndef WITHOUT_ORACLE_EXTENSIONS
64 64         +     pernet->mptcp_enabled = 0;
65 65         + #else
66 66         pernet->mptcp_enabled = 1;
67 67         + #endif /* !WITHOUT_ORACLE_EXTENSIONS */
68 68         pernet->add_addr_timeout = TCP_RTO_MAX;
69 69         pernet->checksum_enabled = 0;
70 70         pernet->allow_join_initial_addr_port = 1;
71 71         {
72 72             .procname = "enabled",
73 73             .maxlen = sizeof(u8),
74 74         + #ifndef WITHOUT_ORACLE_EXTENSIONS
75 75         +     .mode = 0444,
76 76         + #else
77 77         .mode = 0644,
78 78         + #endif /* !WITHOUT_ORACLE_EXTENSIONS */
79 79         /* users with CAP_NET_ADMIN or root (not and) can change this
80 80         * value, same as other sysctl or the 'net' tree.
81 81         */

```

0 comments on commit [556818a](#)

Please [sign in](#) to comment.