US 20120255018A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2012/0255018 A1**

(43) **Pub. Date: Oct. 4, 2012**

Sallam

(54) **SYSTEM AND METHOD FOR SECURING MEMORY AND STORAGE OF AN ELECTRONIC DEVICE WITH A BELOW-OPERATING SYSTEM SECURITY AGENT**

(75) Inventor: **Ahmed Said Sallam**, Cupertino, CA (US)

(73) Assignee: **MCAFEE, INC.**, Santa Clara, CA (US)

(21) Appl. No.: **13/077,270**

(22) Filed: **Mar. 31, 2011**

Publication Classification

(51) **Int. Cl.**
G06F 11/00 (2006.01)
G06F 12/14 (2006.01)

(52) **U.S. Cl.** **726/24**

(57) **ABSTRACT**

A security agent configured to execute on the electronic device at a level below all of the operating systems of the electronic device accessing the memory or a storage of the electronic device may be further configured to: (i) access one or more security rules to determine a criteria by which an attempted access involving a transfer of content between the memory and the storage of an electronic device will be trapped; (ii) if the criteria is met, trap, at a level below all of the operating systems of the electronic device, attempted access of data between memory and storage of an electronic device; and (iii) analyze, at a level below all of the operating systems of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware




100
RING3
APPLICATION
110
RING0/3
DRIVER
111
103
RING0
OPERATING SYSTEM
112
REQUEST
ALLOW/DENY
PROTECTION SERVER
102
TRIGGERED EVENT
104
RING-1
BELOW-OPERATING SYSTEM TRAPPING AGENT
ACTION
TRIGGERED EVENT HANDLER
108
106
RESOURCE
SECURITY RULES
114

FIG. 1


500
INPUT/OUTPUT DEVICE
FIRMWARE
510
INPUT/OUTPUT COMMANDS
512
DATA TRANSMISSION ENGINE
514
PROGRAMMING LOGIC
FIRMWARE SECURITY AGENT
516
REQUEST
TRIGGERED EVENT
504
PROCESSOR
MEMORY
SECURITY RULES
502
506
508
518

FIG. 5


200
244
PROTECTION SERVER
202
204
212
OPERATING SYSTEM
218
IN-OPERATING SYSTEM SECURITY AGENT
SECURITY RULES
220
216
SVMM
221
VMCS
222
SECURITY RULES
224
SECURED NETWORK INTERFACE
SVMM SECURITY AGENT 217
228
SYSTEM MEMORY
DEVICES
226
236
PROCESSOR REGISTERS
230
PROCESSOR RESOURCES
MEM SEG
FLAGS
234
DEBUG
INTERRUPTS
240
CONVENTIONAL
MEM PAGING
232
238
210
APPLICATION
DRIVER
211
206
MEMORY
PROCESSOR
208
SYSTEM RESOURCES
214
ELECTRONIC DEVICE

FIG. 2


300
305
AUTHENTICATE SECURITY AGENT, PROTECTION SERVER, AND SVMM
310
OBTAIN SECURITY RULES
315
INSTRUCT SVMM TO TRAP ACCESS TO SYSTEM RESOURCES
320
SET FLAGS INSIDE VIRTUAL MACHINE CONTROL STRUCTURE
325
SECURE MEMORY
345
SCAN MEMORY PAGES FOR PRESENCE OF MALWARE
330
TRAP ACCESS OF SYSTEM RESOURCES
YES
MALWARE PATTERN FOUND?
350
NO
IS ACCESS SUSPICIOUS?
NO
335
YES
340
BLOCK SUSPICIOUS ATTEMPT
NO
ARE MODIFICATIONS BEING ATTEMPTED?
355
YES
ARE SUCH MODIFICATIONS PERMISSIBLE?
NO
375
DENY ACCESS
365
YES
370
ALLOW ACCESS
REPORT SUSPICIOUS INFORMATION TO PROTECTION SERVER
380

FIG. 3


400
ELECTRONIC DEVICE
244
PROTECTION SERVER
202
404
BELOW-OPERATING SYSTEM AGENT
SECURITY RULES
422
450
428
PC FIRMWARE SECURITY AGENT
444
SECURITY RULES
438
MAIN PC FIRMWARE
214
SYSTEM RESOURCES
OPERATING SYSTEM
418
IN-OPERATING SYSTEM SECURITY AGENT
420
SECURITY RULES
STORAGE
426
FIRMWARE
432
SECURITY RULES
436
FIRMWARE SECURITY AGENT
442
408
PROCESSOR
412
DISPLAY
FIRMWARE
430
SECURITY RULES
434
FIRMWARE SECURITY AGENT
440
410
APPLICATION
411
DRIVER
406
MEMORY
424

FIG. 4


600
605
AUTHENTICATE IDENTITIES OF SECURITY AGENTS AND PROTECTION SERVER
610
OBTAIN SECURITY RULES
615
INSTRUCT FIRMWARE SECURITY AGENT TO TRAP ACCESS TO SYSTEM RESOURCES
620
SET FLAGS IN FIRMWARE SECURITY AGENT
680
630
TRAP ATTEMPTED ACCESS OF SYSTEM RESOURCE
SCAN MEMORY OF DEVICE FOR SUSPICIOUS CONTENTS
632
GENERATE TRIGGERED EVENT
TAKE CORRECTIVE ACTION FOR FOUND SUSPICIOUS CONTENTS
635
685
WILL TRIGGERED EVENT BE PRESENTLY HANDLED OR OFFLOADED FOR HANDLING?
PRESENTLY HANDLED
OFFLOADED
640
DETERMINE ACTIONS TO HANDLE TRIGGERED EVENT
655
PASS EVENT TO ANOTHER SECURITY AGENT FOR HANDLING
WAS TRIGGERED EVENT SUSPICIOUS?
NO
670
RECEIVE RESPONSE
645
675
TAKE ADVISED ACTION
YES
647
TAKE CORRECTIVE ACTION
650
ALLOW TRIGGERED EVENT
690
REPORT SUSPICIOUS EVENTS TO PROTECTION SERVER

FIG. 6


700
244
202
PROTECTION SERVER
701
ELECTRONIC DEVICE
BELOW-OPERATING SYSTEM AGENT
712
SECURITY RULES
723
MEMORY
703
ACTIONS
TRIGGERED EVENTS
OPERATING SYSTEM
719
IN-OPERATING SYSTEM SECURITY AGENT
713
SECURITY RULES
721
INSTRUCTION
702
PROCESSOR
INTERNAL PROCESSOR MEMORY
704
μC 706
SECURITY RULES
707
μC SECURITY AGENT
708
OUTPUTS
μC MODULES
710
APPLICATION
709
DRIVER
711
SYSTEM RESOURCES
724
PHYSICAL MEMORY
714
FLAGS
716
EXCEPTIONS
718
REGISTERS
720
INTERRUPTS
722

FIG. 7


800
805
AUTHENTICATE MICROCODE SECURITY AGENT
810
AUTHENTICATE BELOW-OPERATING SYSTEM SECURITY AGENT
815
OBTAIN SECURITY RULES
820
INITIATE SECURITY TRAPPING
825
SET TRAPPING FLAGS IN MICROCODE
830
RECEIVE INSTRUCTIONS TO BE EXECUTED
835
RECEIVE INFORMATION TO BE TRANSMITTED
840
WAS SOMETHING TRAPPED?
NO
YES
845
CREATE TRIGGERED EVENT
IS EVENT TO BE HANDLED WITHIN MICROCODE?
850
YES
NO
860
PASS EVENT TO SECURITY AGENT
TAKE ACTION DEFINED BY SECURITY RULE
855
865
GATHER CONTEXTUAL INFORMATION FOR EVENT
870
APPLY SECURITY RULE
875
SPECIFY AND TRANSFERS ACTIONS TO BE TAKEN
880
TAKE SPECIFIED ACTION

FIG. 8


900
202
244
PROTECTION SERVER
901
902
PROCESSOR
MEMORY
903
910
APPLICATION
DRIVER
911
921
OPERATING SYSTEM
919
913
SECURITY RULES
IN-OPERATING SYSTEM SECURITY AGENT
REQUEST/ INSTRUCTION
922
TRIGGERED EVENT
ACTION
TRIGGERED EVENT HANDLER
BELOW-OPERATING SYSTEM TRAPPING AGENT
920
926
PROCESSOR RESOURCE CONTROL STRUCTURE
SECURITY RULES
908
REQUEST/ INSTRUCTION
GENERATED INFORMATION
928
DATA REGISTERS
CONTROL REGISTERS
930
CACHES
934
936
FLAGS
924 PROCESSOR RESOURCES
CORE
938
940
EXCEPTIONS
INTERRUPTS
942

FIG. 9


PROCESSOR RESOURCE CONTROL STURCTURE
1000
1002
1004
1006
1008
1010
1012
ENTRIES 1014
TRIGGER FLAG
RESOURCE
TYPE
TRIGGER TYPE
WHEN TO TRIGGER
EXECUTION STAGE TO TRIGGER
ON | OFF
DATA REGISTER
REGISTER
SYNCHRONOUS / ASYNCHRONOUS
WHEN WRITTEN TO
BEFORE INSTRUCTION FETCH
ON | OFF
CONTROL REGISTER
REGISTER
SYNCHRONOUS / ASYNCHRONOUS
WHEN VALUE XXX IS WRITTEN
AFTER INSTRUCTION FETCH
ON | OFF
JMP
INSTRUCTION
SYNCHRONOUS / ASYNCHRONOUS
WHEN JMP IS EXECUTED
AFTER EXECUTE
ON | OFF
TLB
CACHE
SYNCHRONOUS / ASYNCHRONOUS
WHEN CACHE IS INVALIDATED
AFTER ACCESS MEMORY
ON | OFF
LOGICAL CORE N
PROCESSOR
SYNCHRONOUS / ASYNCHRONOUS
WHEN CORE IS IDLE
N/A
ON | OFF
TSC
COUNTER
SYNCHRONOUS / ASYNCHRONOUS
WHEN READ
AFTER WRITE BACK
ON | OFF
ZZZ MEMORY ADDRESS
PHYSICAL MEMORY ADDRESS
SYNCHRONOUS / ASYNCHRONOUS
WHEN READ
AFTER EXECUTE
ON | OFF
YYY MEMORY ADDRESS
VIRTUAL MEMORY ADDRESS
SYNCHRONOUS / ASYNCHRONOUS
WHEN EXECUTED
AFTER EXECUTE
ON | OFF
INTERRUPT-SLEEP
INTERRUPT
ASYNCHRONOUS
BEFORE SENT
N/A
. . .

FIG. 10

FIG. 11


1100
1105
ACCESS SECURITY RULES
1110
DETERMINE PROCESSOR RESOURCES AND COMMUNICATIONS TO TRAP
1115
ADD ENTRIES TO PRCS
1120
ENABLE/DISABLE ENTRIES IN PRCS
1125
MONITOR RESOURCE
1130
WAS AN ATTEMPT TRAPPED?
NO
YES
HAVE MALWARE SETTINGS OR CONDITIONS CHANGED?
NO
1135
YES
ADJUST ENTRIES IN PRCS
1140
IS THE TRIGGER TYPE SYNCHRONOUS?
YES
1145
NO
RETURN TO STEP 1125 IN PARALLEL
STORE INFORMATION REGARDING TRAPPED ATTEMPT
1150
1155
ARE ALL CONDITIONS OF TRIGGERING MET?
NO
YES
DETERMINE EXECUTION STAGE TO TRIGGER
1160
GENERATE TRIGGERED EVENT AT DETERMINED EXECUTION STAGE
1165
DETERMINE CONTEXTUAL INFORMATION FOR TRIGGERED EVENT
1170
SEND TRIGGERED EVENT TO HANDLER
1175
CONSULT SECURITY RULES USING EVENT AND CONTEXTUAL INFORMATION
1180
IS TRIGGERED EVENT SUSPICIOUS?
NO
1185
YES
SEND CORRECTIVE ACTION TO TRAPPING AGENT
1190
APPLY CORRECTIVE ACTION
1195


1200
ELECTRONIC DEVICE
APPLICATION
DRIVER
1211
1210
OPERATING SYSTEM
1213
IN-O/S SECURITY AGENT
SECURITY RULES
1221
1219
MEMORY REQUEST (R/W/E)
ALLOW/ DENY/SPOOF
202
PROTECTION SERVER
244
1220
BELOW-O/S SECURITY AGENT
SECURITY RULES
1208
MEMORY MAP
1206
R/W/E MEM. PAGE
MEMORY PAGES
1204
VIRTUALIZED MEMORY
0 1 2 3 4 5 6 7 8 9 • • •
R/W/E MEM. ADDRESS
MMU
1214
FFxFFF
(O)
(N)
(M)
(L)
(K)
(J)
(I)
(H)
(G)
(F)
(E)
(D)
(C)
(B)
(A)
R/W/E MEM. ADDRESS
1201
00x000 ADDRESS
1202
PROCESSOR
1203
PHYSICAL MEMORY

FIG. 12


1302
PAGE DIREC-TORY
PAGE DIREC-TORY
Fn1
Fn1
Fn1
SSDT PERM Fn2
Fn2
0
1
2
3
4
5
6
7
8
9
1304
FFxFFF
PAGE DIRECTORY SECTION #1
(O)
(N)
Fn1 SECTION #3
(M)
(L)
(K)
Fn1 SECTION #2
(J)
PAGE DIRECTORY SECTION #3
(I)
Fn2 SECTION #1
(H)
SSDT PERMISSIONS
(G)
PAGE DIRECTORY SECTION #2
(F)
(E)
(D)
(C)
Fn2 SECTION #2
(B)
Fn1 SECTION #1
(A)
00x000

FIG. 13


1400
1405
GENERATE MEMORY MAP
1410
ACCESS SECURITY RULES
1415
DETERMINE MEMORY ADDRESSES OR PAGES TO BE SECURED
1420
SET FLAG FOR TRAPPING ACCESS TO MEMORY
1425
MONITOR ACCESS TO MEMORY
HAS ACCESS TO MEMORY BEEN TRAPPED?
1430
NO
YES
DO FLAGS REQUIRE CHANGING?
1435
YES
NO
1440
EVALUATE ATTEMPTED ACCESS
IS ATTEMPTED ACCESS INDICATIVE OF MALWARE?
1445
YES
NO
TAKE CORRECTIVE ACTION
1450
1455
ALLOW THE REQUEST

FIG. 14


1500
APPLICATION
1510
1511
DRIVER
OPERATING SYSTEM
IN-OPERATING SYSTEM SECURITY AGENT
1518
1512
1504
RESOURCE REQUEST ACCESS
1516
BELOW-OPERATING SYSTEM SECURITY AGENT
SECURITY RULES
1522
1542
MEMORY TRACKING FACILITY
STORAGE TRACKING FACILITY
1544
REGISTER
NOTIFY
NOTIFY
REGISTER
MEMORY/STORAGE SECURITY LAYER
1546
RESOURCE REQUEST ACCESS
APPLICATION ASSETS
1548
RESOURCE REQUEST ACCESS
MEMORY
STORAGE
1508
1532
ACTIVITIES
ACTIVITIES
1534
1526
PROCESSOR
1506
PROTECTION SERVER
202
244

FIG. 15


1600
START
1605
MEMORY/STORAGE SECURITY LAYER COMMUNICATES SECURITY RULES TO MEMORY TRACKING FACILITY AND STORAGE TRACKING FACILITY
1610
MEMORY TRACKING FACILITY AND STORAGE TRACKING FACILITY MONITOR ACCESSES IN ACCORDANCE WITH SECURITY RULES
1615
MEMORY TRACKING FACILITY AND/OR STORAGE TRACKING FACILITY NOTIFY MEMORY/STORAGE SECURITY LAYER OF ATTEMPTED ACCESSES TO MEMORY AND/OR STORAGE
1620
MEMORY/STORAGE SECURITY LAYER DETERMINES IDENTITY OF ENTITY REQUESTING ATTEMPTED ACCESS
1625
MEMORY/STORAGE SECURITY LAYER VERIFIES ENTITY AND DETERMINES WHETHER ENTITY HAS BEEN COMPROMISED BY MALWARE
1630
MEMORY/STORAGE SECURITY LAYER DETERMINES WHETHER ENTITY IS AUTHORIZED TO MAKE REQUEST
1635
MEMORY/STORAGE SECURITY LAYER ANALYZES CONTENT ASSOCIATED WITH ATTEMPTED ACCESS
1640
MEMORY/STORAGE SECURITY LAYER ANALYZES HISTORY OF ACCESSES TO MEMORY AND/OR STORAGE
1645
BASED AT LEAST ON DETERMINATIONS AND ANALYSES, MEMORY/STORAGE SECURITY LAYER DETERMINES WHETHER ATTEMPTED ACCESS IS AFFECTED BY MALWARE, TAKES CORRECTIVE ACTION
1650
MEMORY/STORAGE SECURITY LAYER ADDS ACCESS TO A LOG OF ACCESSES TO MEMORY OR STORAGE

FIG. 16

SYSTEM AND METHOD FOR SECURING MEMORY AND STORAGE OF AN ELECTRONIC DEVICE WITH A BELOW-OPERATING SYSTEM SECURITY AGENT

TECHNICAL FIELD

[0001] The present invention relates generally to computer security and malware protection and, more particularly, a system and method for securing memory and storage of an electronic device with a below-operating system security agent.

BACKGROUND

[0002] Native operating system services can prevent security software from installing arbitrary hooking within the kernel of operating systems. Security software is thus prevented from filtering all behaviors of an electronic device, including potentially malicious actions by malware. Malware may include, but is not limited to, spyware, rootkits, password stealers, spam, sources of phishing attacks, sources of denial-of-service-attacks, viruses, loggers, Trojans, adware, or any other digital content that produces malicious activity.

[0003] The filtering functionality provided by the operating system may be limited, and only available on timelines decided by the operating system vendor. Malware can operate and reside at the same level as security software, particularly in the operating system kernel and thus compromise both the operating system and the integrity of the security software itself.

[0004] Many forms of aggressive kernel mode malware tamper with user mode memory to accomplish malicious tasks such as injecting malicious code dynamically, modifying user mode code sections to alter execution paths and redirect into malicious code, and modify user mode data structures to defeat security software. Additionally, some malware may attack anti-malware applications and processes from the kernel by tampering with process memory code and data sections to deceive the detection logic.

[0005] Kernel mode rootkits and other malware employ various methods to hide their presence from user mode applications and kernel mode device drivers. The techniques used may vary depending upon where the infection takes place. For example, malware attacking the kernel active process list of an operating system to delist or unlink a rootkit or other malware process. Other malware may tamper with the code sections of process access and enumeration functions.

[0006] In some instances, malware may attack via insertion of malware code into specific portions of memory or storage of an electronic device, particularly into portions of memory or storage having operating system components or other highly-privileged applications, programs, or resources.

SUMMARY

[0007] In accordance with one embodiment of the present disclosure, a method for securing an electronic device may include accessing one or more security rules to determine a criteria by which an attempted access involving a transfer of content between memory and storage of an electronic device will be trapped. The method may also include, trapping, if the criteria is met, at a level below all of the operating systems of the electronic device accessing a memory or a storage of an electronic device, attempted access of data between the memory and the storage of the electronic device. The method may further include analyzing, at a level below all of the operating systems of the electronic device accessing the memory or the storage of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware.

[0008] In accordance with another embodiment of the present disclosure, a system for securing an electronic device, may include a memory; a processor; one or more operating systems residing in the memory for execution by the processor; and a security agent configured to execute on the electronic device at a level below all of the operating systems of the electronic device accessing the memory or a storage of the electronic device. The security agent may be further configured to: (i) access one or more security rules to determine a criteria by which an attempted access involving a transfer of content between the memory and the storage of an electronic device will be trapped; (ii) if the criteria is met, trap, at a level below all of the operating systems of the electronic device, attempted access of data between memory and storage of an electronic device; and (iii) analyze, at a level below all of the operating systems of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware.

[0009] In accordance with a further embodiment of the present disclosure, an article of manufacture, may include a computer readable medium and computer-executable instructions carried on the computer readable medium, the instructions readable by a processor, the instructions, when executed, for causing the processor to, at a level below all of the operating systems of the electronic device accessing a memory or a storage of the electronic device: (i) access one or more security rules to determine a criteria by which an attempted access involving a transfer of content between the memory and the storage of an electronic device will be trapped; (ii) if the criteria is met, trap, at a level below all of the operating systems of the electronic device, attempted access of data between memory and storage of an electronic device; and (iii) analyze, at a level below all of the operating systems of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] For a more complete understanding of the present invention, and the advantages thereof, reference is now made to the following written description taken in conjunction with the accompanying drawings, in which:

[0011] FIG. **1** is an example embodiment of a system for protecting an electronic device from malware;

[0012] FIG. **2** is an example embodiment of a system for a virtual-machine-monitor-based and security-rule-based configurable security solution for protecting an electronic device from malware;

[0013] FIG. **3** is an example embodiment of a method for virtual machine monitor-based protection for an electronic device from malware;

[0014] FIG. **4** is an example embodiment of a firmware-based and security-rule-based system for protecting an electronic device from malware;

[0015] FIG. **5** is a more detailed view of an example embodiment of a firmware-based solution for protecting an electronic device from malware;

[0016] FIG. **6** is an example embodiment of a method for firmware-based protection for an electronic device from malware;

[0017] FIG. **7** is an example embodiment of a microcode-based system for protection of an electronic device against malware;

[0018] FIG. **8** is an example embodiment of a method for microcode-based protection for an electronic device from malware;

[0019] FIG. **9** is an example embodiment of a system for regulating software access to security-sensitive processor resources on an electronic device;

[0020] FIG. **10** is an example embodiment of a processor resource control structure;

[0021] FIG. **11** is an example embodiment of a method for regulating software access to security sensitive processor resources of an electronic device;

[0022] FIG. **12** an example embodiment of a system for regulating software access for securing memory using below-operating system trapping on an electronic device;

[0023] FIG. **13** is an illustration of example embodiments of memory maps;

[0024] FIG. **14** is an example embodiment of a method for securing memory using below-operating system trapping of attempted access of an electronic device;

[0025] FIG. **15** is an example embodiment of a system for securing memory and storage of an electronic device; and

[0026] FIG. **16** is an example embodiment of a method for securing memory and storage of an electronic device.

DETAILED DESCRIPTION OF THE INVENTION

[0027] FIG. **1** is an example embodiment of a system **100** for protecting an electronic device from malware. System **100** may include a below-operating system ("O/S") trapping agent **104** communicatively coupled to a triggered event handler **108**. Below-O/S trapping agent **104** may be configured to trap various attempted accesses of a resource **106** of an electronic device **103**. Below-O/S trapping agent **104** may be configured to create a triggered event associated with the trapped attempted access, and to send the triggered event to a triggered event handler **108**. Triggered event handler **108** may be configured to consult one or more security rules **114** or a protection server **102** to determine how to handle the triggered event. Triggered event handler **108** may also be configured to evaluate the triggered event's propensity to be an indication of malware, or a malicious attempt to subvert the resources or operation of electronic device **103**. Furthermore, triggered event handler **108** may be configured to provide a determination to below-O/S trapping agent **104** of whether the triggered event should be allowed or denied, or may be configured to yield another corrective action.

[0028] Below-O/S trapping agent **104** may be implemented at a lower functional level than the operating systems in electronic device **103**. For example, below-O/S trapping agent **104** may intercept attempted accesses of resource **106** by an operating system **112**, a driver **111**, or an application **110**. Below-O/S trapping agent **104** may be running on a processor of electronic device **103** without use of an operating system. In one embodiment, below-O/S trapping agent **104** may be operating on a bare-metal environment or execution level. In addition, below-O/S trapping agent **104** may be running at a higher execution priority, as defined by a processor of electronic device **103**, than all operating systems of electronic device **103**. For example, in the context of a hierarchical protection domain model using protection rings, wherein a lower number represents a higher priority, operating system **112** may be operating at "Ring0" while below-O/S trapping agent **104** may be operating at "Ring −1." Drivers **111** and applications **110** may be operating at "Ring0" or "Ring3." In some embodiments of processors, the concept of "Ring −1" may be known as "Ring0 privileged mode," and the concept of "Ring0" may be known as "Ring0 non-privileged mode." Operation in "Ring −1" or "Ring0 privileged mode" may entail additional overhead and expense than "Ring0" or "Ring0 privileged mode." Operating systems of electronic device **103** may run at Ring0.

[0029] Below-O/S trapping agent **104** may operate transparently to entities running at Ring0 or higher. Thus the attempted access of resource **106** may be requested by operating system **112** or another entity in the same manner whether below-O/S trapping agent **104** is present or not. Below-O/S trapping agent **104**, when enforcing a received action, may allow the request to happen, may deny the request, or take other corrective action. To deny the request, below-O/S trapping agent **104** may simply not pass the request to the resource **106** or processor, or may provide a spoofed or dummy reply to the request to convince operating system **112** that the action has occurred.

[0030] By running at "Ring −1," at a higher priority than the pertinent operating systems of electronic device **103**, or below the pertinent operating systems of electronic device **103**, below-O/S trapping agent **104** may avoid much of the malware that plagues operating systems such as operating system **112**. Malware may trick operating system **112** or even anti-malware software running at "Ring0," as malware may also be running at "Ring0" priority. However, malware on electronic device **103** must still make requests of resource **106** if it is to carry out malicious activities. Thus, trapping operations linked to sensitive resources may be better accomplished by a trapping agent running below the level of operating systems in electronic device **103**.

[0031] Below-O/S trapping agent **104** may be implemented in any suitable manner. In one embodiment, below-O/S trapping agent **104** may be implemented in a virtual machine monitor. Such an embodiment may operate below the level of operating systems as described for below-O/S trapping agent **104**. Descriptions of an example of such an embodiment may be found in, for example, discussions of FIG. **2**, below, of a security virtual machine monitor **216**. In another embodiment, below-O/S trapping agent **104** may be implemented in firmware. Such an embodiment may operate below the level of operating systems as described for below-O/S trapping agent **104**. Descriptions of an example of such an embodiment may be found in, for example, discussions of FIGS. **4** and **5**, below, of a firmware security agent **440**, **516**, or PC firmware security agent **444**. In yet another embodiment, below-O/S trapping agent **104** may be implemented in microcode. Such an implementation may operate below the level of operating systems as described for below-O/S trapping agent **104**. Descriptions of an example of such an embodiment may be found in, for example, discussions of FIG. **7**, below, of a microcode security agent **708**. Below-O/S trapping agent **104** may be implemented in a combination of these embodiments.

[0032] Triggered event handler **108** may be embodied by one or more event handlers or security agents communicatively coupled together. Triggered event handler **108** and below-O/S trapping agent **104** may be implemented in the same security agent. In one embodiment, triggered event

handler **108** may be operating at the same priority ring as below-O/S trapping agent. In another embodiment, triggered event handler **108** may be operating at the same priority as operating system **112**, driver **111**, or application **110**. In still yet another embodiment, triggered event handler **108** may be implemented by two or more triggered event handlers wherein at least one triggered event handler operates at the same priority ring as below-O/S trapping agent, and at least one triggered event handler operates at the level of operating system **112**, driver **111**, or application **110**. By running at the level of below-O/S trapping agent **104**, triggered event handler **108** may similarly avoid the problems of "Ring0" or "Ring3" malware infecting the agent itself. However, a triggered event handler **108** running at "Ring0" or "Ring3" with operating system **112**, driver **111**, or application **110** may be able to provide context information about an attempted access of resource **106** that may be unavailable from the viewpoint of "Ring −1" agents.

[0033] Triggered event handler **108** may be implemented in any suitable manner. In one embodiment, triggered event handler **108** may be implemented in a virtual machine monitor or virtual machine monitor security agent. Such an embodiment may operate below the level of operating systems as described for triggered event handler **108**. Descriptions of an example of such an embodiment may be found in, for example, discussions of FIG. **2**, below, of a security virtual machine monitor **216** or security virtual machine monitor security agent **217**. In another embodiment, triggered event handler **108** may be implemented fully or in part in firmware. Such an embodiment may operate below the level of operating systems as described for triggered event handler **108**. Descriptions of an example of such an embodiment may be found in, for example, discussions of FIGS. **4** and **5**, below, of a firmware security agent **440**, **516**, or PC firmware security agent **444**. Triggered event handler **108** may also be implemented in the below-O/S agent **450** in FIG. **4**, which may itself be implemented in such ways as in a virtual machine monitor, firmware, or microcode. In yet another embodiment, triggered event handler **108** may be implemented in microcode. Such an implementation may operate below the level of operating systems as described for triggered event handler **108**. Descriptions of an example of such an embodiment may be found in, for example, discussions of FIG. **7**, below, of a microcode security agent **708**. Triggered event handler **108** may also be implemented in the below-O/S agent **712** of FIG. **7**, which may itself be implemented in such ways as in a virtual machine monitor, firmware, or microcode. Triggered event handler **108** may be implemented in a combination of these embodiments.

[0034] In one embodiment, below-operating system trapping agent **104** and/or triggered event handler **108** may operate in a bare metal layer of electronic device **103**. Below-operating system trapping agent **104** and/or triggered event handler **108** may operate without use of an operating system between them and the resource **106** that they are configured to protect. The resource **106** may include a processor, features of the processor, memory, the entities residing in the memory such as data structures, or the entities residing in the memory for execution by the processor such as functions, processes, or applications. Below-operating system trapping agent **104** and/or triggered event handler **108** may operate directly on the hardware of electronic device **103**. Below-operating system trapping agent **104** and/or triggered event handler **108** may not require the use of an operating system such as operating system **112** to execute nor gain full access to resource **106**.

[0035] Other operating systems may exist on electronic device **103** which do not participate in the relationship between entities at the level operating system **112**, below-operating system trapping agent **104** and triggered event handler **108**, and resource **106**. For example, a pre-boot operating system may securely launch portions of electronic device, but not participate in the normal operation of electronic device in terms of handling requests from application **110**, driver **111**, and operating system **112** made of resource **106**. In another example, electronic device **103** may contain motherboard components, plug-in cards, peripherals, or other components which contain their own sets of operating systems and processors to perform functions outside of the relationship between entities at the level operating system **112**, below-operating system trapping agent **104** and triggered event handler **108**, and resource **106**. These operating systems may be embedded operating systems. Any of these operating systems might not be used for the execution of below-operating system trapping agent **104** and triggered event handler **108**. Further, any of these operating systems might not access the resource **106** protected by trapping agent **104** and triggered event handler **108**.

[0036] System **100** may include any combination of one or more below-operating system trapping agents **104** and one or more triggered event handlers **108**. Descriptions of the below-operating system trapping agents **104** and triggered event handlers **108** may be found in descriptions of trapping agents, event handlers, and security agents in the figures that follow.

[0037] Resource **106** may include any suitable resource of an electronic device. For example, resource **106** may include registers, memory, controllers, or I/O devices. Descriptions of example embodiments of resource **106** may be found in descriptions of, for example, the system resources **214** of FIG. **2**, components such as display **430** and storage **432** as shown in FIG. **4**, or the system resources **724** of FIG. **7** below.

[0038] Security rules **114** may include any suitable rules, logic, commands, instructions, flags, or other mechanisms for informing below-O/S trapping agent **104** about what actions to trap, or for informing triggered event handler **108** to handle an event based on a trapped action. Triggered event handler **108** may be configured to provide one or more of security rules **114** to below-O/S trapping agent. Descriptions of example embodiments of some or all of security rules **114** may be found, for example, in descriptions of security rules **222** of FIG. **2**, security rules **422**, **434**, **436**, **438** of FIG. **4**, security rules **518** of FIG. **5**, or security rules **707**, **723** of FIG. **7** below.

[0039] Kernel mode and user mode entities such as application **110**, driver **111**, and operating system **112** of system **100** may be implemented in any suitable manner. Descriptions of example embodiments of application **110**, driver **111**, and operating system **112** of system **100** may be found in descriptions of, for example, application **210**, driver **211** and operating system **212** of FIG. **2**; application **410**, driver **411**, and operating system **412** of FIG. **4**; and application **709**, driver **711**, and operating system **713** of FIG. **7** below.

[0040] Electronic device **103** may be implemented in any suitable manner, such as in a computer, a personal data assistant, a phone, mobile device, server, or any other device configurable to interpret and/or execute program instructions and/or process data. Descriptions of example embodiments of

electronic device **103** may be found in discussions of, for example, electronic device **204** of FIG. **2**, electronic device **404** of FIG. **4**, or electronic device **701** of FIG. **7**.

[0041] System **100** may be implemented in any suitable system for trapping attempted access of resources at a level underneath the operating systems of electronic device **103**. System **100** may also be implemented in any suitable means for handling the attempted access by consulting security rules to determine whether the attempted access is malicious or not. For example, system **100** may be implemented by the systems and methods **200**, **300**, **400**, **500**, **600**, **700**, and **800** as described in FIGS. **2-8** below.

[0042] FIG. **2** is an example embodiment of a system **200** for a virtual-machine-monitor-based and security-rule-based configurable security solution for protecting an electronic device from malware. System **200** may be an example embodiment of a system **100**, implementing certain elements of system **100** in a virtual machine monitor. System **200** may include an electronic device **204** which is to be protected against malware by a configurable security solution. The configurable security solution of system **200** may include a security agent running below all operating systems, a security virtual machine monitor, a cloud-based security agent and an in-O/S behavioral security agent. The below-O/S security agent and security virtual machine monitor may be configured to guard access to system resources of the electronic device **204**, including the resources used by the in-O/S behavioral security agent. The below-O/S security agent may be running in the security virtual machine monitor. The cloud-based security agent may be configured to provide malware detection information to the below-O/S security agent and to the in-O/S behavioral security agent, and to receive information regarding suspicious behavior possibly—associated with malware from the security virtual machine monitor and in-O/S behavioral security agent. The in-O/S behavioral security agent may be configured to scan the electronic device **204** for evidence of malware operating on the electronic device. System **200** may include one or more below-O/S security agents configured to trap attempted use of access to the resources of the electronic device **204**, generate a triggered event corresponding to the attempt, consult security rules regarding the triggered event, and take corrective action if necessary regarding the attempt.

[0043] In one embodiment, system **200** may include protection server **202** communicatively coupled to one or more in-O/S security agents **218** and a security virtual machine monitor ("SVMM") security agent **217**. SVMM security agent **217** may reside in a SVMM **216**. SVMM **216** may reside and operate upon electronic device **204**. In-O/S security agent **218** and SVMM security agent **217** may be communicatively coupled. Protection server **202**, in-O/S security agent **218**, SVMM security agent **217** and SVMM **216** may be configured to protect electronic device **204** from infections of malware.

[0044] SVMM security agent **217** may be an example embodiment of the triggered event handler **108** of FIG. **1**. SVMM **216** may be an example embodiment of the below-O/S trapping agent **104** of FIG. **1**.

[0045] Electronic device **204** may include a memory **208** coupled to a processor **206**. Electronic device **204** may include one or more applications **210** or drivers **211** executing on electronic device for any suitable purpose. Electronic device **204** may include an operating system **212**. Operating system **212** may be configured to provide access to system resources **214** of electronic device **204** to applications **210** or drivers **211**. SVMM **216** may be configured to intercept such calls of operating system **212** of system resources **214**. SVMM **216** and SVMM security agent **217** may operate below the level of operating system **212**. For example, SVMM **216** and SVMM security agent **217** may operate directly on processor **206** in a privileged mode such as "Ring −1."

[0046] Processor **206** may comprise, for example a microprocessor, microcontroller, digital signal processor (DSP), application specific integrated circuit (ASIC), or any other digital or analog circuitry configured to interpret and/or execute program instructions and/or process data. In some embodiments, processor **206** may interpret and/or execute program instructions and/or process data stored in memory **208**. Memory **208** may be configured in part or whole as application memory, system memory, or both. Memory **208** may include any system, device, or apparatus configured to hold and/or house one or more memory modules; for example, memory **208** may include read-only memory, random access memory, solid state memory, or disk-based memory. Each memory module may include any system, device or apparatus configured to retain program instructions and/or data for a period of time (e.g., computer-readable non-transitory media).

[0047] Protection server **202** may be operating on a network **244**. Protection server **202** operating on network **244** may implement a cloud computing scheme. Protection server **202** may be configured to communicate with elements of electronic device **204** to update malware detection rules and information. Protection server **202** may be configured to receive information regarding suspicious activities originating from electronic device **204** and determine whether or not such suspicious activities are indications of malware infection. Operating system **212** may include one or more in-O/S security agents **218**. In-O/S security agent **218** may be configured to receive monitoring and detection rules from protection server **202**, such as in-O/S security rules **220**. In-O/S security agent **218** may be configured to use the in-O/S security rules **220** received by protection server **202** to monitor and prevent suspicious activities on electronic device **204**. In-O/S security agent **218** may be configured to report detected suspicious activities back to protection server **202**. In-O/S security agent **218** may be configured to prevent malware operations and to report such preventions to protection server **202**. If more than one in-O/S security agent **218** is present in system **200**, each in-O/S security agent **218** may be configured to perform a designated portion of the trapping, validating, or other tasks associated with in-O/S security agent **218**. Such portions may be defined by below-operating-system security agents. For example, one in-O/S security agent **218** may validate or investigate MOV instructions, while another in-O/S security agent **218** may validate or investigate JMP instructions. In-O/S security agent **218** may be configured to determine the life cycle of a particular page in memory. For example, in-O/S security agent **218** may know the processes and steps typically used by operating system **212** to allocate a page of memory. Similarly, in-O/S security agent **218** may know the processes and steps typically used by operating system **212** to load an image of an application in its loader. Such processes may follow a static pattern of operation. Thus, in-O/S security agent **218** may be configured to track the operation of operating system **212** to determine whether for a given action standard procedures

were followed. In-O/S security agent **218** may communicate with SVMM security agent **217** to determine whether or not an operation trapped by SVMM security agent **217** generated the corresponding expected actions observed by in-O/S security agent **218**. A discrepancy may indicate that malware has attempted to perform a system function outside of the normal operation of the operating system **212**. Thus, for example in-O/S security agent **218** and SVMM security agent **217** may determine whether a page in question was loaded in memory directly by malware or was loaded by the operating system loader. Such a behavior may cause in-O/S security agent **218** or SVMM security agent **217** to report information to protection server **202**, employ more aggressive trapping and checking, or take any other corrective measures.

[0048] In one embodiment, in-O/S security agent **219** may be configured to provide contextual information by embedding itself within operating system **212**. For example, in-O/S security agent **219** may be configured to register itself or a subcomponent as a driver filter, and attach itself to a main driver to determine what the driver sees or does not see. By attached as a filter to NDIS.SYS, for example, in-O/S security agent **219** may be configured to report the file I/O operations seen by the operating system **212** drivers.

[0049] In another embodiment, in-O/S security agent **219** may be configured to provide such information observed from within operating system **219** to SVMM security agent **216** or other below-O/S security agents for comparison with information observed below the operating system. Discrepancies between the two sets of information may indicate a presence of malware attempting to hide itself. For example, in-O/S security agent **219** may hook or filter NDIS.SYS, and monitor for file writes to a particular file. SVMM security agent **216** may monitor input and output commands. If SVMM security agent **216** determined more writes than should have been seen based on the list of function calls seen by in-O/S security agent **219**, then malware may be clandestinely writing to disk outside of the functions provided by operating system **212**.

[0050] Network **244** may be implemented in any suitable network for communication, such as: the Internet, an intranet, wide-area-networks, local-area-networks, back-haul-networks, peer-to-peer-networks, or any combination thereof. Protection server **202** may use the reports submitted from various security agents **218** running on various electronic devices **204** to further detect malware by applying prevalence and reputation analysis logic. For example, a suspicious behavior identified on electronic device **204** may be synthesized into a rule for protection server **202** to proactively protect other electronic devices **204**. Such a rule may be determined, for example, based on the number of times that a suspicious driver has been reported. For example, an unknown driver with a narrow or slow distribution pattern may be associated with malware. On the other hand, an unknown driver with a wide and fast distribution may be associated with a patch of a popular and widely available application. In another example, such a detected driver may have been determined by security software running on another electronic device to have accessed a website known to host malware. Such a driver may be determined to be associated with malware.

[0051] SVMM **216** may implement some or all of the security virtual machine monitoring functions of system **200**. SVMM **216** may be configured to intercept access to system resources—such as registers, memory, or I/O devices—to one or more operating systems running on an electronic device. The security virtual machine monitoring functions of system **200** may be implemented using SVMM **216**, or any other virtual machine monitor configured to protect electronic device **204** according to the teachings of this disclosure. SVMM **216** may be configured to control and filter actions taken by operating system **212** while operating system **212** attempts to access system resources **214**, on behalf of itself or on behalf of applications **210** running through operating system **212**. SVMM **216** may run underneath operating system **212** on electronic device **204** and may have control over some or all processor resources made available to operating system **212** and application **210** or driver **211**. Application **210** may comprise any application suitable to run on electronic device **204**. Driver **211** may comprise any driver suitable to run on electronic device **204**. The processor resources made available for control by SVMM **216** may include those resources designated for virtualization. In one embodiment, SVMM **216** may be configured to virtualize system resources **214** for access by operating system **212**, application **210**, or driver **211**. As examples only, such system resources **214** may include input-output devices **226**, system memory **228**, or processor resources **230**. As examples only, processor resources **230** may include conventional registers **232**, debug registers **234**, memory segmentation **236**, memory paging **238**, interrupts **240** or flags **242**. I/O devices **226** may include access to such devices such as keyboard, display, mice, or network cards.

[0052] SVMM **216** may be configured to trap the execution of operations originating from operating system **212** to access system resources **214**. SVMM **216** may include a control structure configured to trap specific attempted accesses of system resources **214**. Any suitable control structure may be used. In one embodiment, such a control structure may include virtual machine control structure ("VMCS") **221**. SVMM **216** may be configured to trap such execution by manipulating flags inside of VMCS **221**. SVMM **216** may be configured to trap any suitable operation of operating system **212**, application **210**, or driver **211** involving an access of system resources **214**. Such trapped operations may include, for example: reading, writing and execution of particular pages of memory in system memory **228**; loading and storing a value to or from a processor register **230**; or reading and writing to or from I/O devices **226**. Any such operations may cause a Virtual Machine Exit ("VM Exit"), which may be trapped by SVMM **216**. SVMM **216** may be configured to trap the generation of interrupts **240**, which may be generated by the processor **208** or initiated by elements of operating system **212**. SVMM **216** may be configured to trap the attempted reading and writing to or from I/O device **226** by trapping IN and OUT instructions. SVMM may be configured to trap such instructions by trapping access to mechanisms, for example, of Virtualization Technology Directed I/O ("VTd"). VTd may allow I/O device virtualization according to processor **208**. By accessing VTd facilities, SVMM security agent **217** may be configured to determine devices connected by VTd, determine meta information from operating system **212**, ports on the I/O device, or other suitable information. SVMM security agent **217** may be configured to control or trap the operation of such virtualized device access. For example, SVMM security agent **217** may be configured to determine I/O permission maps, containing I/O assignments given to programmable I/O ports. SVMM security agent **217** may be configured to trap access to such permission maps,

which may be done by malware, or use such permission maps to determine the relationship of entities on operating system **212** and a request of an I/O device.

[0053] In one embodiment, SVMM security agent **217** may be operating in SVMM **216**. In another embodiment, SVMM security agent **217** may be operating outside of SVMM **216**, but may be communicatively coupled to SVMM **216**. In such an embodiment, SVMM security agent **217** may be operating below the level of operating systems of electronic device **204** such as operating system **212**. SVMM security agent **217** may be operating at the same level and/or the same priority of SVMM **216**. SVMM security agent **217** may be configured to handle events triggered by or trapped by SVMM **216**. SVMM security agent **217** may be configured to access contents of memory **228** or a disk at a level below the operating system **212** so as to examine the contents free of interference of kernel-level rootkits. Furthermore, some operations of SVMM security agent **217** may be implemented by SVMM **216**, and some operations of SVMM **216** may be implemented by SVMM security agent **217**.

[0054] SVMM security agent **217** may be configured to set the operation of SVMM **216** in terms of what actions will cause a trap or trigger. In one embodiment, SVMM **216** may be configured to communicate the detection of trapped actions to SVMM security agent **217**. SVMM security agent **217** may be configured to consult security rules **222** to determine whether the trapped actions indicate malware or malicious activities, and based upon security rules **222** may provide indications to SVMM **216** about what subsequent action to take. Such subsequent action may include allowing the attempted action, disallowing the attempted action, or taking other corrective steps.

[0055] The operation of trapping the attempted access and execution of system resources **214** by SVMM **216** and SVMM security agent **217** may be coordinated through information gathered by in-O/S security agent **218**. In-O/S security agent **218** may be configured to provide context to the trapping and handling operations of SVMM **216** and SVMM security agent **217**. For example, a particular operating system data structure may normally only be written to by a specific application or service. In-O/S security agent **218** may determine what applications or processes are currently visibly running on operating system **212** and communicate the information to SVMM security agent **217**. If the specific application or service is not listed as visibly running, then the attempted write to the data structure may have come from an unauthorized application or process.

[0056] In-O/S security agent **218** may be configured to communicate with SVMM **216** and/or SVMM security agent **217** via hypercalls. Hypercalls may be implemented with a descriptor table defining available requests that may be used, as well as associated input and output parameters. Such a descriptor table may define one or more requests possible for in-O/S security agent **218** to communicate with SVMM **216** and/or SVMM security agent **217**. Such a descriptor table may also define where input and output parameters for such a request may be located in memory.

[0057] In-O/S security agent **218**, SVMM security agent **217**, and protection server **202** may be configured to authenticate each other. Each of security agent **212**, SVMM security agent **217** and protection server **202** may be configured to not continue communications with each other unless each of the entities is authenticated. SVMM **216** may be configured to locate the in-O/S security agent **218** image in memory **206**, and use cryptographic signing algorithms to verify the in-O/S security agent **218** image in memory **206**. Authentication between protection server **202**, in-O/S security agent **218** and SVMM security agent **217** may use any suitable method, including cryptographic hashing and/or signing algorithms. In one embodiment, such authentication may involve the exchange of a private secret key. In-O/S security agent **218** may be configured to receive a secret key from protection server **202** to verify the instance of SVMM security agent **217**.

[0058] In-O/S security agent **218** may have contextual information regarding the operation of operating system **212**. In-O/S security agent **218** may be configured to communicate with SVMM security agent **217** to provide such contextual information. SVMM security agent **217** may instruct SVMM **216** on, for example, how to define certain pages of memory, or which registers to trap.

[0059] SVMM **216** may be configured to trap access attempts to system resources **214** defined by SVMM security agent **217**. For example, for traps of memory access, SVMM **216** may be configured to trap operations such as read, write or execute. For trapping access to processor registers **230**, SVMM **216** may be instructed to trap operations including load, store, or read register values. For trapping I/O operations, I/O devices **226**, SVMM **216** may be instructed to trap operations such as input or output to keyboards, mice, or other peripherals. SVMM security agent **217** and/or other below-operating system security agents in the figures below may, in conjunction with in-operating system security agents, may be configured to determine for an I/O operation, the identity of a target I/O device **226**, target operation to be performed upon the I/O device **226**, and the data to be transferred.

[0060] SVMM security agent **217** may be configured to determine contextual information, such as what entity of operating system **212** has attempted to access a resource of electronic device **204**, or to what entity of operating system **212** a resource may belong. SVMM security agent **217** may be configured to make such determinations through any suitable method. In one embodiment, SVMM security agent **217** may be configured to access contextual information for such determinations from in-operating system security agent **218**. In another embodiment, SVMM security agent **217** may be configured to, directly or indirectly, access a call stack of operating system **212** and/or an execution stack of processor **208** to determine the order of calls made by different processes or applications of operating system **212**. An Execution Instruction Pointer may point to the instruction causing the trigger, while an Execution Stack Pointer and Execution Base Pointer may point to the stack frames. By walking through the Execution Base Pointer through the stack, previous function calls may be identified providing context for the operation at hand. Such stacks may indicate the operation that was attempted as well as a source memory location. In yet another embodiment, SVMM security agent **217** may be configured to use a memory map in conjunction with security rules **222** to determine whether an attempt is malicious or indicative of malware. Such a memory map may, for example, indicate the entity that made an attempted access of resources, given a memory location of the attempted access. Such a memory map may be defined, for example, in virtual memory page identifiers and/or physical memory addresses. Such a memory map may, in another example, indicate the entity corresponding to the memory location of the target of the attempt. Using the memory map, SVMM security agent **217**

may be configured to determine the identities of the source and targets, or entity owners thereof, of an attempted access. The memory map may be created in part by SVMM security agent **217** or other below-O/S security agents in the figures below in conjunction with in-operating system security agents through monitoring the execution of the system. SVMM security agent **217** and/or other below-operating system security agents in the figures below may, in conjunction with in-operating system security agents, determine for a given memory page or physical address whether such a location belongs to a particular code section or data section; to which module, process, application, image, or other entity it belongs; or whether it is associated with user mode or kernel mode entries. SVMM security agent **217** and/or other below-operating system security agents in the figures below may, in conjunction with in-operating system security agents, determine metadata for the mapping of virtual memory and physical memory indicating the identification, location, and permissions of various entities running on the electronic device **204**. Similarly, SVMM security agent **217** and/or other below-operating system security agents in the figures below may use a mapping of sectors in a mass storage device to determine the location of images of such entities in the mass storage device. SVMM security agent **217** and/or other below-operating system security agents in the figures below may, in conjunction with in-operating system security agents, determine for a given entity the sectors, files, directories, and volumes on which they reside.

[0061] SVMM security agent **217** may be configured to allocate memory such as system memory **228** as required for operation of in-O/S security agent **218**, SVMM security agent **217**, and SVMM **216**. SVMM security agent **217** may be configured to request that SVMM **216** secure such allocated memory against unauthorized read and write operations. SVMM **216** may be configured to initialize the allocated memory after protection of the memory is established to eliminate the opportunity for malware to add malicious code between the time when the memory is allocated by in-O/S security agent **218** and the protection is established by SVMM **216**.

[0062] SVMM security agent **217** may be configured to communicate with protection server **202** to securely receive SVMM security rules **222**. SVMM security rules **222** may comprise instructions, logic, rules, shared libraries, functions, modules, or any other suitable mechanism for instructing SVMM **216** about what security policies to employ. SVMM security agent **217** may be configured to transfer information to protection server **202** regarding suspicious activities and detected malware from electronic device **204**.

[0063] In-O/S security agent **218** may be configured to communicate with protection server **202** to receive in-O/S security rules **220**. In-O/S security rules **220** may comprise instructions, logic, rules, shared libraries, functions, modules, or any other suitable mechanism for in-O/S security agent **218** to detect malware on electronic device **204**. In-O/S security agent **218** may be configured to transmit information to protection server **202** regarding suspicious activities and detected malware on electronic device **204**.

[0064] In-O/S security rules **220** and SVMM security rules **222** may each comprise protection rules for protecting electronic device **204** against malware infections, and for detecting suspicious activities that may comprise malware. In-O/S security agent security rules may contain rules executed by and within in-O/S security agent **218**. SVMM security rules **222** may contain rules executed by and within SVMM **216** and/or SVMM security agent **217**.

[0065] SVMM security rules **222** may be configured to provide information to SVMM security agent **217** with definitions of how to observe and detect malware infections of electronic device **204**. For example, SVMM security rules **222** may include categorizations of what types of function calls or behaviors from entities such as application **210** or driver **211** that SVMM security agent **217** may monitor for indications of malware. As another example, SVMM security rules **222** may include definitions of how SVMM security agent **217** may process such triggered function calls, including what parameters to use, how to extract values from such calls, or how to validate the operation of such calls. Furthermore, SVMM security rules **222** may include information for in-SVMM security agent **217** on how to monitor the behavior of entities electronic device such as application **210** or driver **211**, as well as exceptions to such behavioral detection rules. As yet another example, SVMM security rules **222** may include information for SVMM security agent **217** on how to prevent and repair malicious behaviors detected by such behavioral detection rules. SVMM security rules **222** may include details of what data that SVMM security agent **217** should monitor, collect, and send to protection server **202**.

[0066] Similarly, in-O/S security rules **220** may be configured to provide information to in-O/S security agent **218** with definitions of how to observe and detect malware infection of electronic device **204**, as well as how to coordinate such activities with SVMM security agent **217**.

[0067] SVMM security rules **222** may also include rules regarding what actions SVMM **216** will trap. SVMM security agent **217** may be configured to apply such rules to SVMM **216**. For example, SVMM security agent **217** may be configured to convert the address for a function to be trapped into an identifiable virtual or physical page of memory, create a request for SVMM **216** to trap the execution of such a page, and subsequently call the security agent **217** after trapping the execution. SVMM security agent **217** may be configured to receive SVMM security rules **222** through its interface with the SVMM **216**. Such an interface may comprise a hypercall-based interface. SVMM security agent **217** may be configured to push any resulting detections or reports to SVMM **216** through the same hypercall based interface.

[0068] In one embodiment, SVMM **216** may be configured to process triggered actions without consulting SVMM security agent **217**. In such an embodiment, SVMM **216** may be configured to install additional triggers that are processed within SVMM **216** which might not be passed to SVMM security agent **217**. Such additional triggers may be defined by SVMM security rules **222**. In one embodiment SVMM security rules **222** may define memory pages scanning rules for SVMM **216**. Such rules may include a listing of entities or modifications which are malicious and should not be allowed to reside in memory. Such rules may also include a whitelist, configured to include a listing of pages that are specifically allowed to exist within system memory **228**. In another embodiment, SVMM security rules **222** may define to the SVMM **216** memory pages access rules. Such rules may include definitions of what code pages are allowed, or conversely, prohibited to access a given code or data page. Consequently, SVMM security rules **222** may be configured to instruct SVMM **216** to act as a memory scanner, and/or control access to memory pages.

[0069] SVMM **216** may be configured to protect SVMM security agent **217**, SVMM **216**, and in-O/S security agent **218** by preventing unauthorized read and write access to their respective code and data pages in system resources **214**. For example, if application **210** or driver **211** make a request to a portion of system memory **228**, processor registers **230** or I/O devices **226** which would result in affecting the integrity or operation of SVMM security agent **217**, SVMM **216**, and in-O/S security agent **218**, then SVMM **216** may be configured to intercept such an attempted request, and subsequently re-route the request, deny it, or take other appropriate action. In another example, SVMM **216** may be configured to authorize read access for portions of system memory **228**, processor registers **230** or I/O devices **226** affecting SVMM security agent **217**, SVMM **216**, and in-O/S security agent **218** for memory security software applications, such as SVMM security agent **217** itself, or other corresponding or affiliated programs. Such an authorization may be defined within SVMM security rules **222**, which may define to SVMM **216** how to handle access to system resources **214** such as system memory **228**. In one embodiment, SVMM security rules **222** may include a whitelist of trusted security programs, which may include SVMM security agent **217**.

[0070] To communicate with protection server **202**, SVMM **216** may include a secured network interface **224**. Secured network interface **224** may be configured to provide secure access between a network server such as protection server **202** and an element of electronic device **204** such as SVMM **216** or SVMM security agent **217**. SVMM **216** may include a logical TCP/IP driver or other communication interface, which may implement secured network interface **224**. The protection server **202** may be configured to communicate via secured network interface **224** to instruct SVMM **216** or SVMM security agent **217** to update itself, as well as provide protection rules such as SVMM security rules **222** or in-O/S security rules **220**. Protection server **202** may be configured to deliver customized rules for a particular electronic device **204**, or a particular SVMM **216**. Such customization may include the type of malicious activities that have been reported on electronic device **204**, along with other protection mechanisms within electronic device **204** such as an anti-virus program, firewall, or other protection mechanism. In one embodiment, protection server **202** may be operated by an administrator of electronic device **204** on, for example, a local network. In such a case, the administrator may set global or personalized policies for handling suspicious behavior that may be implemented by rules received from protection server **202**. SVMM **216** may include an update engine that informs SVMM **216** or SVMM security agent **217** how to update itself through a new image delivered securely via protection server **202**.

[0071] In-O/S security rules **220** and SVMM security rules **222** may each be configured to request that particular or classes of observed actions or operations on electronic device **204** be passed to protection server **202**. There, protection server may examine and verify the observations before the action is allowed to proceed on electronic device **204**. Protection server **202** may be configured to accept such an action to be examined synchronously or asynchronously. In one embodiment, in-O/S security agent **218** may be configured to pass questionable activities, segments of code or data, or actions to SVMM **216** for verification by protection server **202**. For example, in-O/S security agent **218** may detect a suspected instance of malware by detecting an unsigned driver loaded within memory. SVMM **216** may receive the information about the suspicious software from in-O/S security agent **218**, and may provide it to protection server **202**.

[0072] SVMM security rules **222** may be configured to allow or deny access to any suitable system resource of electronic device. Such resources available to be monitored may depend upon the resources exposed by processor **206**. For example, in one embodiment SVMM security rules **222** may be configured to allow SVMM **216** to restrict access to system memory **228**, I/O devices **226**, and interrupts **140**. Such a restriction may prevent unauthorized access to I/O devices such as keyboard displays or removable discs. In another embodiment, SVMM security rules **222** may be configured to allow SVMM **216** to restrict access to interrupt descriptor table entries, including entries in processor registers such as interrupt **240**. In yet another embodiment, SVMM security rules **222** may be configured to allow SVMM **216** to restrict access to Extended Page Tables ("EPT"), or any other mechanism handling the mapping of virtual memory (real memory from the perspective of a guest operating system) to host physical memory.

[0073] If electronic device **204** contains one or more processors besides processor **208** that support virtualization, SVMM **216** or another instance of SVMM **216** may be configured to intercept attempts to access the virtualized resources of such other processors. If electronic device **204** contains, for example, a quad-processor containing processor **208**, the resources of the quad-processor may be protected by SVMM **216**. If the one or more other processors do not support virtualization, SVMM **216** might not be able to secure access to their resources. If the one or more other processors support a different virtualization technology from processor **208**, SVMM **216** may be configured to secure access to their resources if SVMM **216**, but in a different manner than as processor **208** is secured, since the manner in which resources are virtualized may differ.

[0074] In operation, protection server may be running on network **244**. In-O/S security agent **218** may be running on electronic device **204** to protect electronic device **204** from malware infections, by scanning electronic device **204** for malware, observing the behavior of entities such as application **210** and driver **211** on electronic device **204** for suspicious behavior, and by repairing any such infections that were found. In-O/S security agent **218** may be running at the same priority or level as operating system **212**, and may be running in operating system **212**. SVMM **216** may be operating on electronic device **204** to protect electronic device **204** from malware infection by trapping the attempted access of system resources of electronic device **204**. SVMM security agent **217** may be running on electronic device **204**, or another suitable electronic device, to set the trapping operation of SVMM **216** and to handle some or all of the trapped attempted accesses of system resources. SVMM **216** and SVMM security agent **217** may be running below the operating system **212** with a priority of "Ring −1." SVMM security agent **217** may be running on SVMM **216**.

[0075] Protection server **202** may send security rules, such as SVMM security rules **222** and in-O/S security rules **220**, to electronic device **204**. Such rules may be received by SVMM security agent **217**, which may provide in-O/S security rules **220** to SVMM **216**. Such rules may be received by in-O/S security agent **218**.

[0076] Protection server **202**, security agent **218** and SVMM security agent **217** may each authenticate each other.

SVMM security agent **217** may locate the image of security agent **218** in memory and use cryptographic signing algorithms to verify the image of security agent **218** resident in memory. Protection server **202** and SVMM security agent **217** may authenticate each other using cryptographic hashing and signing algorithms to correctly identify each other. SVMM security agent **217** and protection server **202** may also exchange a private secret key to authenticate the identity of each other. Security agent **218** may receive a secret key from protection server **202** to verify the instance of SVMM security agent **217**. Communication between security agent **218**, SVMM security agent **217**, and **202** may not be fully established unless each of the agents is authenticated with each other. Similarly, SVMM security agent **217** and SVMM **216** may verify and authenticate each other if they are running as separate entities.

[0077] SVMM **216** and SVMM security agent **217** may be running underneath operating system **212** and all operating systems of electronic device **204**. SVMM **216** may monitor access to system resources **214**, including I/O devices **226**, system memory **228**, and processor registers **230** by operating system **212**, security agent **218**, application **210**, and driver **211**. SVMM **216** may trap the execution of key operations requested by operating system **212**, security agent **218**, application **210**, driver **211**, or any other entity of electronic device **204**. SVMM **216** may trap such execution by manipulating flags inside of VMCS **221**. When VMCS **221** intercepts a request for a protected resource, operation may be handed off to SVMM **216** for further operation, diagnosis and repair. In one embodiment, operation may be subsequently handled by SVMM security agent **217**. In another embodiment, handling of the trapped operation may be conducted by SVMM **216** itself. SVMM **216** may trap any necessary operation of electronic device **204** to provide protection against malware. Such operations may include, but are not limited to: reading, writing and execution of particular code or data pages in system memory **228**; loading and storing of value from a system register and processor registers **230**; or reading to or from I/O devices **226**. The specific operations which will be trapped by SVMM **216** may be defined by SVMM security rule **222**.

[0078] Protection server **202** may communicate with SVMM security agent **217** or in-O/S security agent **218** to provide security rules to each. In one embodiment, protection server **202** may deliver SVMM security rules **222** to SVMM security agent **217**. In another embodiment, protection server **202** may deliver in-O/S security rules **220** to in-O/S security agent **218**. In yet another embodiment, protection server **202** may deliver in-O/S security rules **220** to SVMM security agent **217**, which may then provide the rules to in-O/S security agent **218**.

[0079] Application **210**, driver **211** or other entities operating an electronic device **204** may be observed by in-O/S security agent **218**. In-O/S security agent **218** may use in-O/S security rules **220** to observe the behavior of such processing entities to determine whether their behavior constitutes suspicious behavior indicating a possible infection of malware. Upon such a detection of suspicious activities, in-O/S security agent **218** may provide the suspicious information to protection server **202** for further analysis and instruction. In-O/S security rules **220** may indicate to in-O/S security agent **218** that such behaviors are suspicious, as well as indicate corrective action. For example, application **210** may communicate with a network destination which is known to host malware. In-O/S security agent **218** may notice the activity of application **210**, and subsequently block the network access of application **210** to the network destination. In-O/S security agent **218** may also scan electronic device **204** for malware. For example, in-O/S security agent **218** may examine the contents of memory **206**, or system memory **228** for patterns that correspond to signatures of malware. Such an examination may reveal that, for example, application **210** contains a block of code corresponding to a known segment of malware. In-O/S security agent **218** may then clean electronic device **204** of the infection of malware by repairing application **210**, removing application **210**, or taking any other suitable action. In-O/S security agent **218** may communicate with protection server **202** regarding any detected suspicious behaviors, or other indications of malware, and may receive instructions from protection server **202** on how to deal with such malware.

[0080] In one embodiment, SVMM security agent **217** may be configured to evaluate a trapped operation based on the origin of the entity that made the attempted operation. For example, if a driver was downloaded from an unknown domain, or has a certificate from an unknown guarantor, then the ability of the driver to subsequently operate may be limited. For example, a driver whose status is unknown may be denied the ability to attach itself to another driver. If the driver was downloaded from a domain known to host malware or contains fraudulent credentials, then the driver may be not permitted to even load. Similarly, if a driver is known to be from a particular domain or created by a particular author, then SVMM security agent **217** may be configured to recognize services in electronic device **204** authorized to update the driver, and to limit the ability to write or access the driver to those services. For example, a kernel driver from Company X may only be written to from Company X's update service software resident on electronic device **204**. SVMM security agent **217** may be configured to validate the operation and integrity of the update service. In another embodiment, SVMM security agent **217** may be configured to evaluate a trapped operation based on the target of the attempt. For example, an attempt to update software from a service may be trapped for kernel drivers, but not for application software.

[0081] Once an entity has been determined to be suspicious, or an attempt determined to indicate malware, the process causing the attempt and the memory housing the process may be linked. Other processes accessing the same portion of memory may similarly be determined to be malware. A trapped attempt to access a resource may be stored, and a subsequent attempt to access a protected resource may be evaluated in light of the original event. For example, a malicious operation may require that code be written to a data segment then executed. Thus, SVMM security agent **217** may trap the original write access to the data segment, allow the write, but record the source of the write access. Subsequently, SVMM security agent **217** may trap a subsequent attempt to execute the data segment, and evaluate the malicious status of the attempt in light of the previously trapped operation, the entity which attempted it, or other suitable forensic information.

[0082] SVMM security agent **217** may instruct SVMM **216** concerning which of system resources **214** that SVMM **216** is to trap through a control structure such as VMCS **221**. SVMM **216** may then trap access requests to system resources **214** originating from entities of electronic device **204** such as operating system **212**, application **210** or driver **211**. For example, if a request is made to read, write or execute portions

of system memory **228**, SVMM **216** may intercept such a request through a flag set for the designated portion of system memory in VMCS **221**. In another example, access requests made of I/O devices **226** may be intercepted by VMCS **221**, such as input or output operations. In yet another example, requests of process registers **230**, such as load or store commands, may be trapped by VMCS **221**. Any such traps may result in the notification of SVMM **216** of the attempted access. Once SVMM **216** has trapped an attempted operation upon system resources **214**, SVMM **216** may communicate such a trapped execution to SVMM security agent **217**.

[0083] In-O/S security agent **218** and SVMM security agent **217** may communicate to determine the context of operations conducted within operating system **212**. For example, a trapped system call from operating system **212** to a particular resource of electronic device **204** may have originated from a particular part of memory. SVMM security agent **217** may communicate with in-O/S security agent **218** to determine what application, process, or other entity resides within the particular part of memory.

[0084] Based on SVMM security rules **222**, and the trapped operation and/or contextual information from in-O/S security agent **218**, SVMM security agent **217** may then determine whether such an access constituted a suspicious action such as those indicative of an infection of malware. For example, an attempted change of system memory **228** of a protected memory space by an unauthorized application may be a suspicious activity, and thus such an attempted change detected by SVMM **216** may be interpreted by SVMM security agent **217** to be an operation of malware. Such an activity may be reported to protection server **202** for further instruction, or action may be directed by in-O/S security rules **220**. The result of such a detection may be to block the attempted change in system memory **228**, or triggering additional cleaning operations upon the entity of electronic device **204** which generated the attempted change.

[0085] SVMM **216** may monitor additional calls to system resources **214** to protect the integrity of the SVMM **216**, SVMM security agent **217** and/or in-O/S security agent **218**. SVMM **216** may conduct scanning operations, defined by SVMM security rules **222**, to scan portions of system memory **228** to determine whether portions of such memory have been modified by malware. SVMM **216** may make use of signatures, hashes, or other rules indicating that a given pattern of memory is known as unsafe or safe.

[0086] For example, SVMM **216** may protect in-O/S security agent **218** by preventing unauthorized read and write access to code and data pages corresponding to in-O/S security agent **218** in system memory **228**. Some malware may attempt to attack in-O/S security agent **218** by making memory modifications or other modifications to system resources **214** associated with system memory **228**. SVMM **216** may read a whitelist contained in SVMM security rules **222** of authorized applications and other entities of electronic device **204** that may be permitted to alter the code or data or other system resources **214** corresponding to in-O/S security agent **218**. If a modification originates from an entity not contained within the whitelist, then SVMM **216** may determine that such a modification is associated with malware. Unauthorized access to system resources **214** corresponding to in-O/S security agent **218** may be handled by SVMM in any suitable manner, including blocking access, creating a honeybot process, reporting violations to protection server **202**, or any other suitable remedy.

[0087] SVMM **216** may also trap access to system resources **214** belong to other entities of electronic device **204**. For example, a target memory page in system memory **228** may contain sample code or data belonging to a part of the kernel operation of operating system **212**. SVMM **216** and SVMM security rules **222** may limit access to such a target page to only code sections that are authorized. Consequently, if a code page in system memory **228** attempts to read or alter the target memory page, and the code page belongs to a non-authorized entity of electronic device **204**, such an access may be blocked by SVMM **216**. Thus, SVMM **216** may act to control access to memory pages in system memory **228**.

[0088] SVMM security agent **217** may be able to update SVMM security rules **222** or in-O/S security rules **220** by contacting protection server **202** for updated rules. Protection server **202** may configure the rules to be delivered to SVMM security agent **217** based upon the particular malware observed, administrator settings, or other characteristics of electronic device **204**. SVMM security agent **217** may update the rules of electronic device **204** upon demand by a user, periodically, or upon the occurrence of a significant event, such as the encounter of new suspicious activities that may be linked to malware.

[0089] SVMM security agent **217** may set flags in VMCS corresponding to compound conditions. Such flags may span across different types of resources to be trapped. For example, VMCS may be configured to trap the combination of a write of a certain value to page in memory, and a subsequent move of the page to a buffer of an I/O device.

[0090] System **200** may contain one or more advantages over other implementations of anti-malware systems and software. For example, some anti-malware solutions may hook various portions of an operating system to trap and evaluate low-level operations of the applications. However, these solutions themselves may operate inside of the operating system, or in another operating system in the case of two guest operating systems. By operating within the confines of the operating system, even at a kernel-level priority, the anti-malware solution may be susceptible to malware attacks from malware also running on the same operating system, perhaps running at the same priority. If trapping or triggering upon certain events is conducted at the level of an operating system, such trapping or triggering may be phished, hooked, reverse engineered, compromised, or otherwise defeated by malware running at the same or lower priority for the operating system. For example, an anti-malware solution running on an operating system that detects and removes a malicious hook in the operating system may be observed by malware running at the same priority. In another example, an anti-malware solution registering as a filter driver to detect the operation of a certain routine may be defeated by malware that registers a malicious filter driver lower on the driver stack than the anti-malware solution. Similarly, if handling of certain trapped or triggered events occurs at the level of an operating system, malware may be able to affect the such handling. For example, the malware may undo the corrections of the anti-malware solution, or even disable the operation of the anti-malware solution.

[0091] In another example, hypervisors may work to virtualize access to system resources such as system memory **228**, but may not conditionally guard access to the system resources and thus act as a security hypervisor. Such hypervisors may not have access to anti-malware rules, such as behavioral rules in security rules **222**, to identify malicious

activities, entities, or malicious attempted access of system resources. Such hypervisors may be running within an operating system themselves, which may be prone to malware running at the same priority level as the operating system. Such hypervisors may not be running in a "Ring0 privileged mode," because such a mode may require the hypervisor to intercept too many attempted accesses of system resources. The hypervisor may be tasked with virtualizing all aspects of a guest operating system, and the demands of such virtualization may be too expensive to simultaneously access security rules to check for malicious behavior.

[0092] FIG. **3** is an example embodiment of a method **300** for virtual machine monitor-based protection for an electronic device from malware. In step **305**, the identity and security of a below-O/S security agent, in-O/S security agent, protection server, and virtual machine monitor may be authenticated. Such authentication may be done through any suitable method, including by locating and verifying the images of each located in memory, cryptographic hashing, or secret keys. Until step **305** is completed, operation of other steps may be withheld.

[0093] In step **310**, a protection server may be accessed to determine security rules. Such security rules may be used to make decisions in steps **315-380**. In step **315**, the virtual machine monitor may be instructed to trap access to system resources. Such access may arise from applications, drivers, or operating systems running on the electronic device. The virtual machine monitor may be instructed as to what system resources of the electronic device are to be monitored. The virtual machine monitor may also be instructed as to what operations on the monitored system resources are to be trapped. For example, read, write or execute operations on system memory may be trapped. In another example, load or store operations on registers may be trapped. In yet another example, input or output actions on I/O devices may be trapped.

[0094] In step **320**, flags corresponding to such operations to be trapped may be set inside a control structure such as a virtual machine control structure. Such trapped operations may generate a VM exit, wherein a triggered event is created upon the access of the flagged resource. In step **325**, as system memory is allocated for the virtual machine monitor, the in-O/S security agent, and the below-O/S security agent, such memory may be secured against unauthorized read and write operations.

[0095] The electronic device may operate and be protected by one or more of the trapping of access of system resources in steps **330-340**, scanning memory for the presence of malware in steps **345-355**, and scanning memory for attempted memory modifications in steps **360-365**. Each of trapping the access of system resources, scanning memory for the presence of malware, and scanning memory for attempted memory modifications may be conducted in parallel. Further, each of these may be repeated as necessary to protect the operation of the electronic device.

[0096] In step **330**, the access of a system resource such as system memory, registers, or I/O devices may be trapped. The access may be trapped using a VMCS flag generating a VM exit. Such trapping may be conducted below the level of operating systems running on the electronic device. In step **335**, the access may be analyzed to determine whether the requesting entity has permission to access the requested resource. Contextual information associated with the attempted access may be accessed to make such a determination. Security rules may be accessed to make such a determination. An unauthorized access may be determined to be suspicious. Such handling and determinations may be made below the level of operating systems running on the electronic device. If the access is suspicious, then in step **340**, a suspicious attempted access of the system resources may be blocked. Such an attempt may be reported to the protection server. If the access is not suspicious, then the access may be allowed in step **370**.

[0097] In step **345**, memory pages of the electronic device may be scanned for the presence of malware. While scanning the memory of electronic device, a whitelist may be used to determine whether patterns of memory, reflecting entities resident on electronic device, are known to be safe. If a pattern of memory known to be safe is encountered, then in step **370**, the memory may be allowed to continue to have access to electronic device and may remain. While scanning the memory of electronic device, a blacklist may be used to determine whether patterns of memory are known to comprise or be associated with malware. The whitelist and blacklist may be accessed by accessing the security rules. In step **350**, if a pattern of memory known to be associated with malware is found, then in step **375** the pattern of memory may be denied access to electronic device by being repaired, removed, or neutralized.

[0098] In step **355**, memory may be scanned to determine whether modifications to memory have been or are being attempted. Such scanning may be conducted below the level of operating systems in the electronic device. Such memory may include kernel memory, system data structures, or any other portion of memory of the electronic device that may be modified by malware. For example, a list of active threads running on the electronic device may be modified to hide the presence of a malicious process. If a modification is detected, then in step **365** it may be determined whether such modifications are permissible. Whether such modifications are permissible may be defined by the security rules. For example, the code or data page of an anti-malware process may be protected against modification or access by any other process. If the memory modification is deemed as authorized, then in step **370**, the modification may be allowed. If the memory modification is determined to be unauthorized and not allowed, then in step **375**, the modification may be denied.

[0099] In step **370**, if an access or modification is allowed, then the access or modification may be stored for later reference. Some detections of malware may utilize information regarding past accesses or modifications to determine whether such past access and a presently detected access together comprise a malicious access of a resource.

[0100] In step **375**, if a modification, access, or other operation is denied, then such an event may be reported to the protection server in step **380**. Such a report may include information regarding any associated malware or suspicious behavior.

[0101] The steps of method **300** may be repeated as necessary to protect the electronic device continuously, periodically, or upon demand.

[0102] FIG. **4** is an example embodiment of a firmware-based and security-rule-based system **400** for protecting of an electronic device **404** from malware. System **400** may be an example embodiment of system **100**, wherein certain elements of system **100** are implemented in firmware. The trapping operations of system **400** may be conducted below the level of operating systems of electronic device **404**. System

400 may include one or more below-O/S security agents configured to trap requests, such as I/O commands, for use or access to resources of the electronic device 404. Such below-O/S security agents may be configured to manage the exchange of input and output data between devices or with the main processor of electronic device 404. Such below-O/S security agents may be embodied in firmware of components, such as device controllers, of electronic device 404 or in the firmware of electronic device 404 itself. Such firmware may reside in non-volatile memory. Such resources of electronic device 404 may include the system resources 106 of FIG. 1 or its various possible embodiments, or resources coupled to or embodied by devices in system 400. System 400 may include one or more below-O/S security agents configured to trap attempted use of access to the resources of the electronic device 404, generate a triggered event corresponding to the attempt, consult security rules regarding the triggered event, and take corrective action if necessary regarding the attempt.

[0103] In one embodiment, the below-O/S security agents of system 400 may be embodied only in firmware of components of electronic device 404, as described below and in the discussions of FIG. 5. In another embodiment, the below-O/S security agents of system 400 may be embodied in firmware of electronic device 404 itself such as main PC firmware 428. In such an embodiment, main PC firmware 428 may be implemented on a motherboard of electronic device 404. In yet another embodiment, the below-O/S security agents of system 400 may also be embodied in below-O/S agent 450. Below-O/S agent 450 may be implemented in any suitable manner for providing triggering of access of resources, or handling of such triggers, below the level of operating systems of electronic device 404 such as operating system 412. For example, below-O/S agent 450 may be an embodiment of SVMM 216 or SVMM security agent 217 of FIG. 2. Below-O/S agent 450 may include security rules 422.

[0104] Electronic device 404 may include one or more components for conducting input and output operations from electronic device 404. Electronic device 404 may include any suitable number of such components and types of components. Such components may be implemented by devices with their own processor, memory, and software embedded in firmware. An example embodiment of such a component may be the I/O device 502 of FIG. 5.

[0105] Electronic device 404 may include, for example, display 424 and storage 426. Each such component 424, 426 may include firmware 430, 432. Firmware 430, 432 may each embody the firmware 504 of FIG. 5. As described above, each such component 424, 426 may include a firmware-based security agent, such as firmware security agent 440, 442. Firmware security agents 440, 442 may each partially or fully embody the firmware security agent 516 of FIG. 5. In one embodiment, each of firmware security agents 440, 442 may be implemented in their respective firmware 430, 432. In another embodiment, each of firmware security agents 440, 442 may be implemented outside of firmware 430, 432 in each of their respective components 424, 426. Each of such device firmware security agents 440, 442 may be communicatively coupled to a respective set of security rules 434, 436. Each such security rules 434, 436 may embody the security rules 518 of FIG. 5.

[0106] Electronic device 404 may include firmware. In one embodiment, electronic device 404 may include main PC firmware 428. Main PC firmware 428 may be embodied by a Basic Input/Output System ("BIOS"). In one embodiment, main PC firmware 428 may be configured as the BIOS of a computer. In such cases, main PC firmware 428 may be configured to initialize the operation of the processor 406 of the computer. Main PC firmware 428 may be configured to allow the main processor 406 to communicate with I/O devices such as display 424 and storage 426. In such embodiments, the computer may also contain a programmable I/O controller, which may be programmed by the firmware or BIOS, and communicates with the firmware of the I/O devices such as 424 and storage 426.

[0107] Main PC firmware 428 may include a below-O/S security agent. In one embodiment, main PC firmware 428 may include a PC firmware security agent 444. PC firmware security agent 444 may be configured to intercept requests of system resources 414. To accomplish such functionality, PC firmware security agent 444 may embody fully or in part the functionality of the SVMM security agent 217 or SVMM 216 of FIG. 2, and/or firmware security agent 516 of FIG. 5. PC firmware security agent 444 may embody the functionality of SVMM security agent 217 or SVMM 216 of FIG. 2 to accomplish below-O/S triggering and handling of access to system resources 414, verification and validation of below-O/S agents and in-O/S security agents such as in-O/S security agent 418, and distribution of security rules such as security rules 420, 422. PC firmware security agent 444 may embody the functionality of firmware security agent 516 of FIG. 5 to accomplish below-O/S triggering and handling in firmware, updating of security rules, and to evaluate IN and OUT commands sent to portions of electronic device 404.

[0108] Electronic device 404 may include security rules 438. Security rules 438 may be an example embodiment of the security rules 114 of FIG. 1. In one embodiment, security rules 438 may reside in main PC firmware 428. In another embodiment, security rules 438 may reside outside main PC firmware 428, and PC firmware security agent 444 may be coupled to security rules 438.

[0109] The security agents of system 400 may be configured to work together to prevent malware and its malicious operations. Attempted access of resources may be trapped, and subsequent events triggered for handling in firmware security agents in devices such as display 424 or storage 426, or in main PC firmware 428. The firmware security agents in such devices or firmware may be configured to handle the triggered events or to pass the triggered event to another security agent for handling. Due to limited execution and update capabilities, some firmware security agents may be limited in handling their own triggered events, and thus it may be advantageous to pass such triggered events to other security agents. The security agents to which firmware security agents may pass events may include, for example, in-O/S security agents such as in-O/S security agent 418, a below-O/S security agent such as below-O/S security agent 450, or another firmware security agent such as PC firmware security agent 444. These other security agents may be configured to receive the triggered event, consult security rules, contextual information, or permissions, and send back a resulting action to be implemented.

[0110] Accordingly, while FIG. 4 illustrates an example number of elements for conducting below-O/S triggering and handling by firmware-based security agents, more or less elements may be used in various embodiments. As more or less elements are used, the functionality of each element and of system 400 may change accordingly. In one embodiment, the security agents of system 400 below the level of the

operating system **412** may be limited to one or more in-O/S security agents **418** and firmware security agents **440**, **442**. In such an example, the firmware security agents **440**, **442** may rely upon protection server **402** for updates to security rules **434**, **436**. Firmware security agents **440**, **442** may rely upon in-O/S security agent **418** for updates or handling of triggered events, but the operation of the in-O/S security agent **418** may be less secure unless a below-O/S security agent validates in-O/S security agent. Firmware security agents **440**, **442** may provide triggering based upon firmware security rules **434** established at installation, manufacture, or configuration. Such security rules may be relatively static. In such a case, firmware security agents **440**, **442** may be configured to provide relatively basic event triggering, with little analysis. Such firmware security agents **440**, **442** may nonetheless be useful, as such triggering is accomplished below the operating systems of electronic device **404**, thus better detecting some malicious or suspicious operations.

[0111] In another embodiment, the security agents of system **400** may include either PC firmware security agent **444** or below-O/S agent **450**, but not both. In such a case, the functionality of PC firmware security agent **444** may be implemented by below-O/S agent **450**, and vice-versa. Either PC firmware agent **444** or below-O/S agent **450** may be coupled to protection server **402** and configured to obtain information such as security rules **420**, **422**, **438**, **434**, **436**, and to share such information with other security agents in system **400**. Such security rules may be tailored to each respective security agent for the purposes of communication, update, or storage expense. Either PC firmware agent **444** or below-O/S agent **450** may be configured to receive triggered events from other security agents such as firmware security agents **440**, **442**, apply security rules and other information, and take corrective action such as sending a resulting event to the firmware security agents **440**, **442** or information to protection server **402**. Either PC firmware agent **444** or below-O/S agent **450** may be configured to trap attempted accesses of system resources **414**. Either PC firmware agent **444** or below-O/S agent **450** may be configured to communicate with in-O/S security agent **418** to determine the context of triggered events. If more than one in-O/S security agent **418** is present in system **400**, each in-O/S security agent **418** may be configured to perform a designated portion of the trapping, validating, or other tasks associated with in-O/S security agent **418**. Such portions may be defined by below-operating-system security agents. For example, one in-O/S security agent **418** may validate or investigate MOV instructions, while another in-O/S security agent **418** may validate or investigate JMP instructions.

[0112] In yet another embodiment, security agents of system **400** may include both PC firmware security agent **444** and below-O/S agent **450**. Nevertheless in such an embodiment, some or all of the functionality of PC firmware security agent **444** may be implemented by below-O/S agent **450**, and vice-versa. The delineation of tasks between PC firmware security agent **444** and below-O/S agent **450** may take into account several factors. For example, the operation of a security agent within firmware such as PC firmware security agent **444** may be more secure than the operation of another below-O/S agent **450**. However, updating the security rules and the software of below-O/S agent **450** may be simpler and faster than in a PC firmware security agent **444**.

[0113] In still yet another embodiment, one or more firmware security agents **440**, **442** may reside on system **400** independent of a PC firmware security agent **444** or a below-operating system agent **422**. In such an example, the firmware security agents **440**, **442** may validate the instance of in-operating system security agent **418**.

[0114] Each of firmware security agents **440**, **442**, **444** may be configured to reside within firmware logic sufficient to be able to monitor and control firmware logic for external communication. Firmware security agents **440**, **442**, **444** may thus be configured to trap and/or the communication of specific information or with specific other entities. Firmware security agents **440**, **442**, **444** may be configured to determine the operation request received, as well as the data to be sent or received. Furthermore, firmware security agents **440**, **442**, **444** may be configured to control the data to be sent or received, and may be configured to cause additional operations on the data, such as encryption, compression, embedding of watermarks, or decoding of watermarks in the data. Other security agents of system **400** in communication with firmware security agents **440**, **442**, **444** may be configured to embed watermarks in data to be trapped by firmware security agents **440**, **442**, **444**, or to decode watermarks put into data by firmware security agents **440**, **442**, **444**.

[0115] Communication with a firmware security agent **440**, **442** or PC firmware security agent **444** may be conducted, for example, through programmable input-output interrupts or programmable input-output registers. Such interrupts or registers may be defined and provided by the maker of the firmware or device in which the firmware security agent **440**, **442**, **444** resides.

[0116] One or more of the below-O/S security agents of system **400** may be configured to serve as a main security agent to coordinate the anti-malware activities of the firmware-based security agents of electronic device **404**. In one embodiment, PC firmware security agent **444** may be configured as the main security agent of system **400**. In another embodiment, below-O/S agent **450** may be configured to serve as the main security agent. The security agent may be configured to handle triggered events from firmware security agents **440**, **442**. The main security agent may be configured to validate the operation of firmware security agents **440**, **442**, as well as other security agents such as in-O/S security agent **418**. The main security agent may be configured to notify other security agents about whether one of the security agents has noticed suspicious behavior or detected malware, whether the system **400** is under a malware attack, or whether an administrator of system **400** has changed preferences or settings affecting security. The main security agent may share information about the attack with the other security agents of system **400**.

[0117] By trapping access to resources of system **400** and/or handling the resulting triggered events below the level of the operating systems of system **400**, system **400** may provide increased security against malware. Operation of a security agent in firmware may reduce the opportunity for malware to affect the operation of the security agent. Trapping operations in firmware or at the device level may reduce the ability of malware to spoof or phish elements of system **400** in order to disguise its operation. For example, no matter what portions of operating system **412** are compromised by malware, a request to a component **424**, **426** might not be disguised from the device itself.

[0118] FIG. **5** is a more detailed view of an example embodiment of a firmware-based solution for protecting an electronic device from malware. A device such as I/O device

502 may be configured to receive and trap requests for use or access to resources of the device. In one embodiment, I/O device **502** may be configured to process such trapped requests to determine whether the requests indicate a presence of malware. In another embodiment, I/O device **502** may be configured to pass such a trapped request as a triggered event to another portion of a system in which I/O device resides. Such another portion of the system may include a below-O/S security agent. I/O device **502** may include firmware **504** and a processor **506** coupled to a memory **508**, wherein the firmware **504** may include instructions that reside in memory **508** for execution by processor **506**.

[0119] I/O device **502** may include any suitable portion of an electronic device for controlling access to a resource for the electronic device. In one embodiment, I/O device **502** may embody some or all of a peripheral for an electronic device. I/O device **502** may be embodied by, for example, a display controller card, computer bus controller, cache device, I/O controller device, disk controller, memory device, network controller, motherboard, or keyboard controller. I/O device **502** may reside in an electronic device. In one embodiment, I/O device **502** may be coupled to physical components. Such physical components may include, as just examples, a display, a computer bus, memory, I/O controllers, a disk, a network card, or a keyboard. In another embodiment, I/O device **502** may reside separately from the coupled physical components. For example, a keyboard controller may be coupled through a serial interface with a keyboard. In such embodiments, I/O device **502** may reside in an electronic device while such physical components may be communicatively coupled to the electronic device but reside outside the electronic device.

[0120] Firmware **504** may be configured to control the operation of I/O device **502**. Firmware **504** may include a below-O/S security agent **516** configured to trap requests for resources, operate below the level of operating systems in I/O device **502** or in systems in which I/O device **502** resides. Below-O/S security agent **516** may be configured to handle events resulting from the trapped requests to determine whether to allow, deny, or otherwise handle the request, in order to protect I/O device **502** or systems in which I/O device **502** resides from malware. In one embodiment, firmware **504** may include a firmware security agent **516**. Firmware security agent **516** may incorporate some or all of the functionality of SVMM **216** or SVMM security agent **217** of FIG. **2**, but is embodied in firmware **504**. In such a case, the functionality of SVMM **216** or SVMM security agent **217**, such as trapping access to resources and/or handling the trapped request, may be conducted by firmware security agent **516**. In one embodiment, firmware security agent **516** may be configured to reside in firmware **504**.

[0121] Firmware **504** may include I/O commands **510**, a data transmission engine **512**, and programming logic **514**. I/O commands **510** may include instructions for sending or receiving information to the device. Such commands may include variations of IN or OUT commands. The execution of I/O commands **510** may be operable to perform the desired actions of the device. Requests received by the device may be translated into I/O commands. Trapping or triggering upon particular requests for resources may be accomplished by trapping or triggering upon the associated I/O commands **510**. Data transmission engine **512** may be configured to handle the communication of requests to the device, and subsequent responses. Data transmission engine **512** may be coupled to the processor **506** and to a programmable I/O controller over an I/O bus, over which I/O commands **510** and data are exchanged. Programmable logic **514** may be configured to provide instructions for firmware **504** to operate I/O commands **510** and data transmission engine **512**. The programming logic **514** may be loaded into a processor such as processor **506**.

[0122] Firmware security agent **516** may be configured to modify the operation of programming logic **514** to detect attempted malicious operations. Firmware security agent **516** may also be configured to monitor the communication of requests to the device to intercept requests of I/O device **502** through data transmission engine **512** and to determine whether such requests are malicious. Firmware security agent **516** may include a control structure in which flags may be set corresponding to operations that are to be trapped. In one embodiment, flags may be set in the structure according to memory address of commands which are to be trapped. Firmware security agent **516** may be configured to set flags for the interception of requests to I/O device **502**. Such flags may correspond to, for example, specific commands of I/O commands **510** or such specific commands in combination with specific parameters. Such flags may be configured to intercept particular requests or categories of requests. Upon the triggering of a particular flag corresponding to a trapped attempted operation of an I/O command **510**, firmware security agent **516** may be configured to process the event and take a resulting action, pass resulting information to another security agent through the data transmission engine **512**, or pass the triggered event through data transmission engine **512**.

[0123] I/O device **502** may also include security rules **518**. Security rules **518** may implement some or all of security rules **222** of FIG. **2**. Security rules **518** may be implemented in memory **508**. In one embodiment, security rules **518** may reside outside of firmware **504**. In another embodiment, security rules **518** may reside inside of firmware **504**. Firmware security agent **516** may be communicatively coupled to security rules **518** and configured to access security rules **518** to determine what flags to set in firmware **504** to trap particular requests or categories of requests made to I/O device **502** for access to its resources. For example, firmware security agent **516** may be configured to access security rules **518** to determine whether a triggered event is malicious or not. In one embodiment, security rules **518** may contain instructions for firmware security agent **516** to process the triggered event. Firmware security agent **516** may be configured to use such instructions to determine whether to allow or deny the request, or to take another corrective action. In another embodiment, firmware security agent **516** may be configured to use such instructions to determine whether to report the request to another security agent. Such corrective actions may also include waiting for a response from the other security agent, which may contain instructions on whether to allow or deny the request.

[0124] In some embodiments, firmware security agent **516** may reside in firmware **504**, which may make it relatively difficult to update firmware security agent **516**. In addition, the ever-changing nature of malware attacks may require anti-malware solutions to be flexible. Consequently, firmware security agent **516** may use any suitable mechanism for receiving information for determining what requests to I/O device to trap, and what subsequent actions to take.

[0125] In one such embodiment, such a mechanism may include accessing security rules **518** as described above.

Firmware security agent **516** may be configured to receive new and updated security rules **518** from other security agents or protection servers. To achieve flexibility, firmware security agent **516** may be configured to store security rules **518** in memory **508** separate from firmware **504**, if—for example—storage of such rules in firmware **504** would make updating security rules **518** difficult.

[0126] In another such embodiment, firmware security agent **516** may be configured to update security rules **518** upon an update or flash of firmware. In such an embodiment, the flexibility of updating the requests to be trapped may be limited. Consequently, security rules **518** may be directed to very specific, protected resources. For example, security rules **518** of a disk device may include instructions to trap all write requests to the boot sector of the device. In some cases, where communication with other security agents is inexpensive, security rules **518** may include instructions to trap a wide variety of requests, wherein processing may be largely off-loaded to other security agents.

[0127] In yet another such embodiment, firmware security agent **516** may be configured to receive instructions from other security agents. In one case such instructions may take the form of parameters to function calls of the firmware **504** or firmware security agent **516**. For example, another security agent may call a function of firmware security agent **516** named "UpdateRule(trigger, action)" wherein a request to trap for is detailed in trigger and a subsequent action to take is detailed in action. Firmware security agent **516** may thus update security rules **518** by receiving instructions concerning updates to security rules. In another case, another security agent may write updates for security rules **518** to a reserved memory space of device **502** which may be subsequently accessed by firmware security agent **516**. The instructions to be received from other security agents may also direct firmware security agent **516** to use specific sets of security rules **518**. For example, during a time-critical operation firmware security agent **516** may be configured by such instructions to use a minimal, core set of security rules **518**. If I/O device **502** is a disk device, such a minimal, core set of rules may include instructions to trap access to the boot sector of the disk. In another example, if time-critical operations are not being presently conducted, firmware security agent **516** may be configured by such instructions to employ rules from security rules **518** to trap a much broader range of access attempts and to send corresponding events to other security agents for handling.

[0128] Firmware security agent **516** may be configured to control I/O commands **510**, scan content or data received or to be sent, and apply access control over the commands and content. Firmware security agent **516** may be implemented as an extension of existing device firmware.

[0129] The implementation of firmware security agents **516** may depend upon the type of device **502**. For example, display devices and disk devices may trigger on different kinds of content or attempted commands. The creation of firmware security agents **516** in various devices may be tailored to the specific kind of interface with the device. For example, if device **502** is configured to communicate through a Serial Advanced Technology Attachment ("SATA") bus, it may be equipped with firmware security agents **516** similar to other devices communicating through SATA busses. Firmware security agent **516** may be customized to support the architecture of device **502**, support an external bus I/O of device **502**, or other interfaces of device **502**.

[0130] Firmware security agent **516** may be configured to trap attempted access of resources in device **502** by intercepting particular read and write commands, which may make up part of a request of a resource. A read or write command may be intercepted, evaluated, and blocked or allowed based on a rule such as one in security rules **518**. Security rules **518** for a firmware security agent **516** may include any suitable rules for detecting evidence of malware. Such a read and write command may be the result of, for example, a function call to a driver or an interrupt.

[0131] For example, security rules **518** may include rules for firmware security agent **516** to scan data to be written to the device. The content of the data, or a hash of the data, may be evaluated to determine whether the data corresponds to malware data or code. Such evaluations may be made by comparing the content against data or signatures in a whitelist or blacklist. Successive writes may have to be evaluated together to properly evaluate the full scope of the data or content to be written, in order to correctly identify the contents or data as malware or not. For example, a file may be written to in repeated successive calls to device **502**. The data to be written may be queued such that a proper scan of the contents of the write command may be evaluated.

[0132] In another example, security rules **518** may include rules for firmware security agent **516** to scan existing data in the device. The device **502** may contain content received from outside the system such as in a network card. The contents of the received information, as it resides with the device **502**, may be scanned for evidence of malware. Firmware security agent **516** may make evaluations by comparing the content against data or signatures in a whitelist or blacklist.

[0133] In yet another example, security rules **518** may include rules for firmware security agent **516** to evaluate a command based upon time or permissions. A device **502** such as a network device or disk may be protected from reads or writes during times when no legitimate activity should be conducted. For example, certain malware may attack disk drives during boot. Thus, firmware security agent **516** may prevent any writes to the device during the time that the disk is being booted. Similarly, permissions may be set by an administrator of the system in which device **502** resides about when or how devices or systems can be used. For example, an administrator of the system in which device **502** resides may set a device to be unusable outside of business hours. A network device on the system may have no legitimate purpose to transport activity outside of business hours, and thus based on the permissions in security rules **518**, reads and writes of the network device may be blocked by firmware security agent **516**. Such use may block, for example, deliberate activity by an actual user of the device, or by malware using the network device to conduct a denial-of-service attack.

[0134] In still yet another example, security rules **518** may include rules for firmware security agent **516** to evaluate a command based upon parameters used with the I/O commands. Such parameters may include, for example, the address to which a write command will write. Security rules **518** may include a rule indicating that a particular portion of a disk device is read-only. Thus, firmware security agent **516** may examine the parameters associated with an OUT command for writing data to the disk to determine the address to which the data will be written, and block the command if the attempted write is to a portion of disk that is write-protected by a rule in security rules **518**. Firmware security agent **516** may consider such a parameter in conjunction with other

bases such as content or the entity which originated the call. For example, scanning the content of data to be written may be expensive, and accordingly a security rule **518** may configure firmware security agent **516** to scan data to be written only if data is to be written to certain ranges of addresses. In another example, security rules such as security rule **518** may only allow certain calling entities to write or read from certain portions of the disk device. Thus, firmware security agent **516** may trap the attempted write or read and not allow the attempt until the identity of the calling entity may be securely determined. Such a determination may be made by evaluating information in the parameters used to call the device function, as some such functions may identify the calling device driver or application. In such a case, firmware security agent **516** may take any appropriate steps to determine the validity of the call. In one embodiment, firmware security agent **516** may consult a whitelist or blacklist in security rules **518** to determine whether the calling entity is authorized to make such a call. In another embodiment, firmware security agent **516** may communicate with other security agents in the system containing device **502** to determine whether the calling application or device driver is valid. Such other security agents may have validated the operation of the calling application or device driver, or may communicate with in-O/S security agents that may have verified such operations. In yet another example, the existing driver calls to a device such as device **502** may not identify the calling entity. Accordingly, no parameters may be available. In such an example, firmware security agent **516** may be configured to pass the triggered event or otherwise consult with other security agents in the system to determine the context of the call which resulted in the attempted access. Such other security agents may be able to provide suitable context for the call to determine whether an authorized entity made the attempt.

[0135] In a further example, security rules **518** may include rules for firmware security agent **516** to evaluate a command based on information from the environment in which device **502** resides. Other security agents in the system may have detected a malware infection that is difficult to remove, or may require direct intervention from an administrator to clean. The other security agents in the system may have observed suspicious behavior, and the nature of the behavior has not yet been completely analyzed. In such a case, firmware security agent **516** may receive notification of such an existing threat from the other security agents. Security rules **518** may thus dictate preventative actions for firmware security agent **516** depending upon the type of infection. For example, firmware security agent **516** in a keyboard device may receive notification that evidence of a particular type of malware known for keylogging has been detected but cannot yet be removed. Security rules **518** may thus dictate that firmware security agent **516** disallow all reads and writes from the keyboard device to prevent a compromise of the information being communicated with the keyboard.

[0136] Firmware security agents **516** may protect the I/O of different types of devices in different ways. For example, a firmware security agent **516** of a display device may shut down portions of the display, depending upon the malware threat. Firmware security agent **516** may block the display of certain patterns, causing a watermark to be produced on the screen. Firmware security agent **516** may trap the attempted display of a particular pattern. Firmware security agent **516** may intercept attempted reads of information from the device in order to prevent screen-captures.

[0137] In another example, a firmware security agent **516** for a keyboard device may optionally encode or decode its results in communication with the rest of the system. Such encryption may be set by the firmware security agent **516** upon notification that a malware threat such as a keylogger is present.

[0138] In yet another example, a firmware security agent **516** for a network device may trap based upon source Internet Protocol ("IP") address, source port number, data to be sent or received, destination IP address, or destination port number. Once such an attempt to use the network device is trapped, firmware security agent **516** may scan the data payload of packets to be sent or received for evidence of malware. In one embodiment, such data payloads may be sent to another security agent or a protection server, wherein the contents may be scanned for evidence of malware. The contents of the data payload may be encrypted such that a packet sniffer may not successfully intercept the contents. Attempted operations on the network device may be trapped due to security risks associated with communicating with unsafe network destinations, wherein network communication with a malicious destination may compromise the security of the system in which device **502** resides. Attempted operations may be trapped due to the sensitive nature of particular sets of data, such as a banking website. In such a case, upon receipt of data from such a website, the data may be encrypted by firmware security agent **516** before being passed to another security agent or to the calling entity. Such encryption may prevent a packet sniffer or filter in the system of device **502** from successfully intercepting the information.

[0139] The specific I/O commands **510** to be trapped may depend on the specific device and the operations of that device. Thus, the maker of device **502** may decide how to configure the operation of a firmware security agent **516** for a particular device **502**. The maker of device **502** may decide how much to expose the functionality of device **502** to other security agents. For example, device **502** may be configured to require validation with other security agents before handing off triggered events to such security agents.

[0140] In operation, one or more below-O/S security agents may be running in the firmware of system **400** or of the components of system **400**. Firmware security agent **440** may be operating in display **424**, firmware security agent **442** may be operating in storage **426**, and PC firmware security agent **444** may be operating in main PC firmware **408**. Below-O/S agent **450** and in-O/S agent **412** may be operating in system **400**. Each security agent may communicate with one or more other security agents in system **400**. Each such security agent may validate the instance of another security agent before accepting communication. Protection server **402** may communicate with one or more of the security agents after validating the security agent.

[0141] PC firmware security agent **444** or below-O/S agent may be designated as a main security agent. The main security agent may communicate with protection server **402** to determine security rules. The main security agent may store the security rules locally to the main security agent. The main security agent may distribute security rules to each of the security agents, wherein the security rules may be stored locally to the security agent. The security rules may be customized for the type, make, or model of the device to reduce the expense of a large set of security rules.

[0142] Upon receipt of security rules such as rules **434**, a device such as display **424** may set flags in a control structure

within the device firmware **430** corresponding to operations of the device that are to be trapped. Similar tasks may be performed by storage **426**.

[0143] An application **410** or driver **411** may try to access a device such as display **424** or storage **426**. Application or driver **411** may make such an attempt by calling the kernel of operating system **412**, which in turn may call operating system device drivers, which in turn may send the request to the component **424**, **426**.

[0144] The request may arrive at a device such as storage **426**. Firmware security agent **442** running on the device may filter such a request through monitoring data transmission engine **412** of the storage **426** with a control structure. The request may take the form of an I/O command **510** made available by the storage **426**. If the request matches any flags that have been set by firmware security agent **442**, the request may be trapped and a resulting event may be triggered. Firmware security agent **442** may consult security rules **436** to determine how to handle the triggered event.

[0145] In one embodiment, the triggered event may be handled by firmware security agent **442**, and based upon the information available such as associated data, the command, contextual information, time, or environmental information, corrective action many be taken. Such corrective action may include allowing or denying the request, removing malicious code or data, or encrypting data to be transferred. Other corrective action may include sending information to be passed to protection server **402** concerning the trapped event. Firmware security agent **442** may inform other security agents about the status of the trapped event, so that other such agents may also take corrective action after consulting their respective security rules. For example, if firmware security agent **442** detects a malware attack of unknown origin, firmware security agent **440** may lock out additional access to the display **424**.

[0146] In another embodiment, the triggered event may be transferred to another security agent for handling, such as in-O/S security agent **418**, PC firmware security agent **444**, or below-O/S agent **450**. The receiving security agent, for example, PC firmware security agent, **444**, may handle the triggered event by consulting security rules **438**. Based upon the information available such as the data, command, contextual information, time, or environmental information, the request represented by the triggered event may be allowed or denied by PC firmware security agent **444**. PC firmware security agent **444** may communicate with in-O/S security agent **418** to determine contextual information concerning the attempted access of resources. PC firmware security agent **444** may communicate with protection server **402** for additional information on how to handle the triggered event. PC firmware security agent **444** may send instructions for resulting action back to the originating firmware security agent **442**. PC firmware security agent **444** may send information concerning the triggered event to protection server **402** to be analyzed or recorded. Such analysis or recording may be conducted when the malicious nature of a triggered event is unknown. PC firmware security agent **444** may notify the security agents of system **400** that a particular kind of malware has been detected, a kind of suspicious activity has been detected, or that the system **400** is under a malware attack.

[0147] Upon receipt of information from PC firmware security agent **444**, firmware security agent **440** may take corrective action. Such action may include allowing or denying the attempted access, encrypting data to be transferred, or removing malicious code or data.

[0148] FIG. **6** is an example embodiment of a method **600** for firmware-based configurable protection for an electronic device from malware. In step **605**, the identity and security of a below-O/S security agent, in-O/S security agent, protection server, and firmware security agent may be authenticated. Such authentication may be done through any suitable method, including by locating and verifying the images of each located in memory, cryptographic hashing, or secret keys. Until step **605** is completed, operation of other steps may be withheld.

[0149] In step **610**, a protection server may be accessed to determine security rules. Such security rules may be used to make decisions in the following steps. In step **615**, the firmware security agent may be instructed to trap access to system resources. Such access may arise from applications, drivers, or operating systems running on the electronic device. The firmware security agent may be instructed as to what system resources of the electronic device are to be monitored. The firmware security agent may also be instructed as to what operations on the monitored system resources are to be trapped. For example, read and write commands to a device on which the firmware security agent is running may be identified to be trapped. In step **620**, flags corresponding to such operations to be trapped may be set in a control structure. Such trapped operations may generate a triggered event.

[0150] The electronic device may operate and be protected by one or more of the trapping of access of system resources in steps **630**-**675**, or scanning data for the presence of malware in steps **680**-**685**. Each of trapping the access of system resources and scanning data for the presence of malware may be conducted in parallel. Further, each of these may be repeated as necessary to protect the operation of the electronic device.

[0151] In step **630**, the access of a system resource such as system memory, registers, or I/O devices may be trapped. Such trapping may be conducted below the level of operating systems running on the electronic device. Such trapping may be conducted within firmware. In step **632**, a resulting triggered event may be generated associated with the trapped attempt, as well as any associated information. In step **635**, it may be determined whether the triggered event should be presently handled or passed to another security agent for handling. Such a determination may be made by accessing one or more security rules. If the triggered event should be presently handled, then in step **640** the security rules may be accessed to determine what actions to take based on the trapped event and other information, such as associated data, the command, contextual information, time, or environmental information. For example, the data to be written or read may be scanned for sensitive or malicious content; the calling entity may be identified to see if the entity has permission; the parameters used to call the command may be examined; or alerts about malware in the system from other security agents may be referenced.

[0152] In step **642** it may be determined whether the attempted access was suspicious or not. If accessing the security rules in combination with information associated with the attempted access yields a determination that the attempted access is not suspicious, then in step **645** the attempt may be allowed. If it is determined that such an attempt is suspicious, then in step **647** corrective action may be taken. Such corrective action may include removing malicious content from

data, informing a protection server or other security agents about the presence of a malicious attempt, disallowing the attempted access, or encrypting data to be transferred. If the attempt is not suspicious, then in step **650** the triggered event may be allowed.

[0153] In step **655**, if it is determined that another security agent is to handle the triggered event, the triggered event is passed to another security agent for handling. In step **670**, a response from the security agent may be received indicating appropriate action to be taken. In step **675**, such action may be taken, such as corrective action or allowing the operation of the triggered event.

[0154] In step **680**, memory of a device may be scanned for the presence of malware. Such memory may contain contents that have arrived from another entity, such as another network card or the results of a previously executed file read. If the contents of the memory are known to be malicious, suspicious, or unknown, then in step **685**, the contents of the memory may be removed.

[0155] In step **690**, if an attempted access was denied, or if suspicious contents were found, then such an event may be reported to another security agent or a protection server. Such a report may include information regarding any associated malware or suspicious behavior.

[0156] The steps of method **600** may be repeated as necessary to protect the electronic device continuously, periodically, or upon demand.

[0157] FIG. **7** is an example embodiment of a microcode-based system **700** for protection of an electronic device **204** against malware. System **700** may be an example embodiment of system **100**, implementing certain elements of system **100** in a microcode. The trapping operations of system **700** may be conducted below the operating systems of electronic device **701**. System **700** may include one or more below-O/S security agents configured to trap attempted use of access to the resources of the electronic device **204**, generate a triggered event corresponding to the attempt, consult security rules regarding the triggered event, and take corrective action if necessary regarding the attempt. Such below-O/S security agents may be configured to intercept information generated from resources of the electronic device **701**, generate a triggered event corresponding to the generation, consult security rules regarding the triggered event, and take corrective action if necessary regarding the attempt. One or more of such below-O/S security agents may be implemented fully or in part in a processor of system **700**. The below-O/S security agents may be implemented fully or in part in microcode ("μC") of such a processor. The system resources **724** of electronic device **701** that may be protected by system **700** may include, for example, resources similar to the system resources **224** of FIG. **2**, physical memory **714**, processor flags **716**, exceptions **718**, registers **720**, or interrupts **722**.

[0158] System **700** may include a microcode-based below-O/S security agent such as microcode security agent **708**. Microcode security agent **708** may reside within the microcode **708** of a processor such as processor **704**. In one embodiment, microcode security agent **708** may be configured to trap attempted access of system resources **724** made by portions of system **700** such as application **710**, driver **711**, or operating system **713**. Microcode security agent **708** may be configured to create a triggered event based on such an attempted access of system resources **724**. For example, operating system **713** may attempt to launch a program by attempting to execute a segment of code in an address in physical memory **714**. In another example, operating system **713** may attempt to read or write an address in physical memory **714**. Although physical memory **714** is shown, microcode security agent may be configured to trap an attempt to access virtual memory. In another embodiment, microcode security agent **708** may be configured to trap attempted communication of information from other portions of processor **702**, such as microcode modules **710**. Microcode modules **710** may include other portions of processor **702** configured to conduct the operation of processor **702** to execute instructions. Such attempted communication of information may include the results of operations from system resources **724**. For example, during the processing of code, and divide-by-zero operation may be intercepted by a microcode module **710** and may attempt to generate and communicate an exception **718**.

[0159] Microcode **706** may include hardware-level instructions for carrying out higher-level instructions received from elements of system **700** such as operating system **713**. Microcode **706** may translate such higher-level instructions into circuit-level instructions to be executed by processor **702**. Microcode **706** may be specific to the electronic circuitry or type of processor embodied by processor **702**. Microcode **706** may be configured with the specific contents of microcode **706** upon the creation of processor **702**. The ability to update or reprogram microcode **706** on processor **702** may be limited. Microcode **706** may reside in an internal processor memory **704**. Internal processor memory **704** may be a high-speed memory separate from the system memory of system **700**, such as memory **703**. In one embodiment, internal processor memory **704** may be read-only-memory. In another embodiment, microcode **706** may reside in a programmable logic array included in internal processor memory **704**. In yet another embodiment, internal processor memory **704** may include or be implemented as a memory store or a control store. In such an embodiment, internal processor memory **704** may be implemented partially or in full by static-random-access-memory or flash memory. In such an embodiment, microcode **706** may be configured to be loaded into the memory store from some other storage medium, such as memory **703**, as part of the initialization of the processor **702**, and may be configured to be updated, reinstalled, or receive new information such as security rules or machine instructions through data written to the memory store.

[0160] Microcode security agent **708** may be configured to access security rules **707** to determine what operations, commands, communications, or other actions to trap. Security rules **707** may reside within microcode **706**, or another suitable portion of processor **702** or system **700**. Security rules **707** may be implemented by functional calls from entities outside processor **702**, such as other security agents making calls to microcode security agent **708** and passing information through parameters. Microcode security agent **708** may be communicatively coupled to security rules **707**. In one example, a security rule **707** may have logic such as:

[0161] If address (x) is executed by code in virtual memory range (X**1**-->X**2**) or physical memory range (Y**1**-->Y**2**), then generate a triggered event to below-O/S agent for handling;

[0162] If address (x) is executed by code in physical memory range (Z**1**-->Z**2**), then skip instruction;

[0163] If A, B, and C; then memory range (Y**1**-->Y**2**) may access memory range (X**1**-->X**2**); and

[0164] Only code from memory ranges (Y**1**->Y**2**) and (T**1**->T**2**) may write to (Z**1**-->Z**2**).

[0165] Microcode **706** may include a state machine to understand the context of instructions that have been received. Such information may be needed to carry out certain security rules **707** which, for example, evaluate successive operations within the context of each other. Such information may be passed with a triggered event.

[0166] One or more of the below-O/S security agents of system **700** may also be embodied in below-O/S agent **712**. Below-O/S agent **712** may be implemented in any suitable manner for providing triggering of access of resources, or handling of such triggers, below the level of operating systems of electronic device **701** such as operating system **713**. Below-O/S agent **712** may embody some or all of the functionality of SVMM **216** or SVMM security agent **217** of FIG. **2**; firmware security agent **440**, **442** or PC firmware security agent **444** of FIG. **4**; or firmware security agent **516** of FIG. **5**. Below-O/S agent **712** may be communicatively coupled to security rules **723**.

[0167] In one embodiment, one or more of the below-O/S security agents of system **700** such as below-O/S agent **712** may be configured to handle triggered events generated by microcode-based security agents such as microcode security agent **708**. Below-O/S agent **712** may be configured to also trap access to resources or handle triggered events in a similar fashion as below-O/S agents in FIGS. **1-2** and **4-5**. Below-O/S agent **712** and microcode security agent **708** may be communicatively coupled. Microcode security agent **708** may be configured to send triggered events to below-O/S agent **712**. Below-O/S agent **712** may be communicatively coupled to other security agents such as in-O/S security agent **719**, and may be communicatively coupled to protection server **202**. Below-O/S agent **712** may be configured to receive contextual information from other security agents such as in-O/S security agent **719**. Such information may provide information about the entity which generated an attempted access to system resources **724**. If more than one in-O/S security agent **719** is present in system **700**, each in-O/S security agent **719** may be configured to perform a designated portion of the trapping, validating, or other tasks associated with in-O/S security agent **719**. Such portions may be defined by below-operating-system security agents. For example, one in-O/S security agent **719** may validate or investigate MOV instructions, while another in-O/S security agent **719** may validate or investigate JMP instructions.

[0168] Below-O/S agent **712** may also be configured to receive security rules or just-in-time information from protection server **202**. Furthermore, below-O/S agent **712** may be configured to consult security rules such as security rules **723**, any received contextual information from other security agents such as in-O/S security agent **719**, or protection server **202** in order to determine how to handle a received triggered event from microcode security agent **708**.

[0169] In particular embodiments, below-O/S agent **712** may contain a behavioral state machine, to understand the context of operations encountered in system **700**. Below-O/S agent **712** may then be configured to determine an appropriate action to be executed by microcode security agent **708** based upon the context. Such action may include a corrective action, allowing an operation, denying an operation, or taking other steps in furtherance of the requirements of a security rule. Microcode security agent **708** may be configured to take such actions as received from below-O/S agent **712**.

[0170] Below-O/S agent **712** may be also be configured to determine an appropriate action to be executed by another security agent, such as in-O/S security agent **719**. For example, if a triggered event from microcode security agent **708** indicates a particular kind of malware threat, or a threat to a particular portion of the kernel or user mode of electronic device **701**, below-O/S agent **712** may be configured to instruct in-O/S security agent **719** to take a corrective action. Thus, below-O/S agent **712** may control in-O/S security agent **719**.

[0171] Below-O/S agent **712** may be configured to validate the instance of microcode security agent **708**, and vice-versa. Below-O/S agent **712** may be configured to communicate with microcode security agent **708** to share or set security rules such as those from security rules **723** to be implemented in security rules **707**, status information regarding system **700**, administrator or environmental settings and preferences, or other suitable information for microcode security agent **708** to trap operations, generate triggers, and handle such triggers or send them to other security agents.

[0172] Below-O/S agent **712** may be configured to communicate such information to microcode security agent **708** through any suitable mechanism. Below-O/S agent **712** may call functions of the processor **702**, microcode **706**, or microcode security agent **708**, and pass information as parameters to the functions. Such functions may be created specifically to pass such changes to microcode security agent **708**. For example, to ban the access of a range of physical memory "A" from any entity operating from the memory from another range of physical memory "B," a function such as "Bar_Memory(A, B)" could be used. Microcode security agent **708**, as a result of this function being called, may be configured to set parameters within microcode **706**. Calling such microcode instructions may be privileged, such that microcode security agent **708** may be configured to validate below-O/S agent **712** before calling such microcode instructions on behalf of below-O/S agent **712**. In another example, below-O/S agent **712** or microcode security agent **708** may communicate such information by writing data to a memory store, control store, or other writeable portions of processor **702** or microcode **706**.

[0173] Processor **702** may have limited resources for microcode security agent **708** to fully implement all necessary trapping and handling to protect system **700** from malware. In one embodiment, microcode security agent **708** may be configured to implement only trapping of actions to be conducted by processor **702**, and may offload triggers associated with such trapping to other security agents or components of system **700** for subsequent handling. Microcode security agent **708** may take subsequent action, such as allowing or disallowing a request or communication, or may take other action such as reporting information. In another embodiment, microcode security agent **708** may be configured to implement handling of a small portion of triggered events. Suitable triggered events for such handling may include those not requiring significant contextual information. For example microcode security agent **708** may receive information through security rules **707** that a particular range of memory addresses is to be protected from all reads and writes, unless an instance of below-O/S agent **712** has been validated. Such a security rule may be implemented because the contents are quite sensitive, and without the operational assistance of below-O/S agent **712**, the identity of the entity accessing the memory contents cannot be identified. Thus, after validating the instance and operation of below-O/S agent, microcode security agent **708** may set a bit indicating

such validation. If an attempted access of the memory is triggered, and the bit has not yet been set, then microcode security agent **708** may be configured to disallow the reading, writing, or execution of the contents of the memory range. If the bit has been set, then microcode security agent **708** may be configured to then trap the attempted access to the memory range, generate a triggered event to be sent to below-O/S agent **712**, which would evaluate from contextual information and other settings whether the calling entity was allowed to access the memory range. Below-O/S agent **712** may then send a resulting action back to microcode security agent **708**, perhaps indicating whether to allow or deny the access.

[0174] A triggered event may include any suitable information that may be used for identification of the source, method, or destination of the attempted action. The triggered event may be used by microcode security agent **708** or below-O/S security agent **712** to apply security rules. The triggered event may be generated by microcode security agent **708**. For example, the triggered event may detail precisely what resource was accessed, what instruction was called, what instruction operands were used, from what memory address the attempt or instruction came from (i.e. the source memory), into what memory the operation's result was to be stored in (i.e. the target memory) or what memory will be affected, or any other information leading to identification of the source, method, or destination of the attempted action. Microcode security agent **708** may also be configured to include information regarding processor **702** such as processor states of active, sleep, idle, halt, and reset; interprocessor communications; and power consumption.

[0175] Another security agent such as below-O/S agent **712** may be configured to use such information in a triggered event to determine the scope of the event when applying a security rule **722**. Below-O/S agent **712** may have access to additional clues such as information about the entities operating in operating system **713**, new information in protection server **202**, malware or other threats detected by other security agents, administrator settings, etc. For example, given a trapped request originating from a particular address in physical memory, below-O/S agent **712** may be able to determine the thread, process or application associated with the particular address. Then, below-O/S agent **712** may be configured to determine whether such an entity is authorized to take the action in question. Below-O/S agent **712** may be configured to determine the identity of the entity. Below-O/S agent **712** may be configured to classify the entity as known to be safe (e.g., by consulting a whitelist), known to be malicious (e.g., by observing behavior or consulting a blacklist of known malware), or unknown. Below-O/S agent **712** may be configured to report information about unknown and malicious entities to protection server **202**.

[0176] Microcode security agent **708** may have access—for trapping purposes—to certain processor **702** resources and other system resources **724** that may be unavailable to other security agents. In one embodiment, implementation of microcode security agent **708** within the microcode **706** may avoid limitations created by limited exposure of such resources to calling entities outside of the processor. For example, a virtual machine monitor may be limited to trapping operations on resources which have been exposed by processor **702** for virtualization purposes. Take as a further example the ability to trap an attempted read, write, or execute upon memory. A virtual-machine-monitor-based security agent may only have access to memory as it is available to be virtualized, and, as a consequence, may only be able to trace attempted read, write, or execution attempts to a memory page. In contrast, microcode security agent **708** may be able to intercept and handle a read, write, or execute request to a specific physical memory address, and evaluate the request based upon security rules **707**. The smaller granularity may provide greater flexibility in providing security solutions in system **700**. The instruction-level awareness of what instruction was used in context with a specific physical memory address informs system **700** of which entity called what resource, and not merely that a memory page was accessed. This flexibility may be very valuable. For example, microcode security agent **708** may monitor two adjacent memory addresses for read, write, or execute attempts, but may be directed by security rules **707** to take completely different actions based upon which of the two memory addresses were accessed. With a view only into the memory page on which an attempt is made, such a distinction in rules may fail to be applied. In another example, other methods by hypervisors for monitoring and setting debug registers did not have the context of the instructions which were used to access the debug registers, as does system **700**. In addition, some other entities for setting or watching such debug registers do not run below the level of the operating system, making them more prone to malware. Finally, some other entities for setting or watching such debug registers are not directed towards security, and are not capable of accessing security rules, evaluating the access, and taking a corrective action.

[0177] Corrective actions to be taken by microcode security agent **708** may include any suitable action determined by security rules **707** or received from below-O/S agent **712**. Commands or instructions may be allowed or denied. Information generated from microcode modules **710** may be allowed or suppressed. Any such commands, instruction, or information may be modified.

[0178] Microcode security agent **708** may be configured to trap the generation of interrupts. The interrupts may be trapped by trapping, for example, an execution of an "INT" instruction, followed by reading relevant registers known to host information associated with an interrupt. For example, general purpose registers may be read to learn the code identifier of the interrupt, as well as the parameters used to call it. For example, interrupt **13** may be a disk interrupt, and a known set of registers may identify the interrupt as a read or write, as well as relevant sectors and locations of data.

[0179] Microcode security agent **708** may be configured to trap values being written to input and output ports of processor **702**. Microcode security agent **708** may be configured to trap values being written to input and output devices by processor **702**. Microcode security agent **708** may be configured to trap on instructions for making such writes or reads.

[0180] Microcode security agent **708** may also be configured to trap certain operations of an arithmetic logic unit ("ALU") of processor **702**. A series of operations on the processor corresponding to the steps of a protected hashing algorithm may be trapped to determine unauthorized access of the function. Some arithmetic operations are used by malware to disguise or morph themselves. Certain arithmetic instructions, bitwise instructions, or MOV instructions are all instructions that might cause a change in the content of a memory page or address range. By trapping such instructions, changes to a code section or data section may be recorded. If subsequent analysis shows that the code section or data section was modified as part of self-modifying malware, then the

trapped and recorded instructions may be used to track the encryption algorithm used by the malware. For example, it may be determined that the malware uses an XOR function with a particular key to morph itself. Such information may yield better security rules for detecting self-modifying malware. Further, by keeping track of memory modifications, repair logic may be achieved by reversing the application of the instructions.

[0181] In addition, microcode security agent **708** may be configured to conduct digital-rights-management operations. For example, microcode security agent **708** may be configured to receive a security rule **707** indicating that authorization to run a particular program is required. The particular program may be located at a specific address in memory. Such an authorization may take the form of the microcode security agent **708** receiving, for example, an authorization code, key, or byte from below-O/S security agent **712**. Such an authorization may be accomplished by microcode security agent **708** trapping attempted access on the memory or loading of the programs instructions, and sending the triggered event to below-O/S security agent **712**, which in turn may have access to the authorization code, key, or byte. The below-O/S security agent **712** may return the decision to the microcode security gent **712**. Thus, operation of the program may be allowed or disallowed based on the authorization code.

[0182] Furthermore, microcode security agent **708** may be configured to stop the execution of specific code in memory based upon a hash or a checksum of the memory. Such a hash or checksum may be indicated by a security rule **707** as malicious. As the code is loaded from memory, microcode security agent **708** may conduct the hash or checksum of the contents, compare it with those of known malicious code, and then deny the attempt to load and load a repair function to eliminate the offending code.

[0183] Below-O/S agent **712** may be configured to inform other security agents of system **700**, including microcode security agent **706** that it has been determined that system **700** has been infected with malware, encountered suspicious behavior, or otherwise been compromised. In such a case, microcode security agent **706** may be configured to disable operation of portions of processor **702**. Microcode security agent **706** may be configured to disable such operations by trapping and denying requests to specific system resources **724**, or generated communication from microcode modules **710**. Portions of processor **702** may be disabled because they are sensitive, or likely to be misused by malware.

[0184] Microcode security agent **706** may be configured to protect a memory address or a range of memory addresses from attempts to load, read, write, or execute attempts. Such memory may include sensitive data, or may be the initialization point for a restricted, sensitive, or protected function. Microcode security agent **706** may prevent access to such memory where there is no verification that the accessing software is safe or neutral. In such a case, security agents such as below-O/S agent **712** may identify specific memory addresses to be protected, perhaps because such memory addresses may correspond to the example sensitive information or protected routines. Below-O/S agent **712** may send microcode security agent **708** information such as security rules **707** regarding which addresses to protect. Microcode security agent **708** may trap attempted loading, executing, reading or writing to such memory addresses and send a corresponding triggered event to below-O/S agent **712**. Below-O/S agent **712** may determine whether the calling software is safe or neutral according to security rules **723**, information from protection server **202**, a whitelist, or any other suitable information source. Below-O/S agent **712** may return an action to be implemented back to microcode security agent **708**. Microcode security agent **706** may be configured to protect a page or range in virtual memory and/or an address or range in physical memory. Microcode security agent **706** may be configured to translate virtual memory pages, locations, or addresses into physical memory locations or addresses. Thus, given a virtual memory location to trap, or a virtual memory location from where an attempt originated, microcode security agent **706** may be configured to determine the corresponding physical memory locations, or vice-versa.

[0185] Furthermore, microcode security agent **708** may be configured to protect the access of sensitive code. In one embodiment, microcode security agent **708** may be configured to protect the access of sensitive code in the manner described above by monitoring access of a particular address, wherein the address represents the beginning of the code as it is stored in memory. In another embodiment, microcode security agent **708** may be configured to monitor the execution of "JMP" or similar branching instructions which would move the operation of processor **304** into the middle of sensitive data or code. In such a case, microcode security agent **708** may be configured to trap the execution of "JMP" instructions in combination with the sensitive memory ranges. Microcode security agent **708** may be configured to analyze from where the "JMP" instruction originated. The microcode security agent **708** may be configured to generate a triggered event corresponding to the trapped "JMP" attempted execution, which may be handled by below-O/S agent **712**. The below-O/S agent **712** may be configured to take into account where the "JMP" instruction originated, and whether such memory where the "JMP" instruction originated is authorized to access the memory in question.

[0186] Microcode security agent **708** itself, or the trapping functionality therein may also be configured to be enabled or disabled by other portions of system **700**. Such capabilities may be useful if trapping and handling events are expensive, thus possibly harming system performance. Such enabling and disabling may be based upon the use of particularly sensitive programs or data, detection of a malware threat, administration preferences, or any other suitable reason. In one embodiment, microcode security agent **706** may be configured to receive a MSAOn signal, VMXOn signal, or other instruction from below-O/S agent **712** to begin security processing and trapping. Microcode security agent **708** may receive an MSAOff signal, "VMWrite VMXOff" signal, or other instruction to stop security processing and trapping. Before beginning or stopping security processing and trapping, microcode security agent **708** may validate the identity and instance of the security agent making the request.

[0187] Furthermore, microcode security agent **708** may be configured to intercept interprocessor messages and commands between processor **702** and other processors of electronic device **701**. Such interprocessor commands may be received by an appropriate microcode module **710** or be attempted by an entity of electronic device **701** accessing particular system resources **724**. In one embodiment, interprocessor commands may be sent from software accessing processor **702** from operating system **713** by way of a machine state register. Malware may try to send such messages, for example, to turn off processors or put them in sleep mode. Microcode security agent **708** may be configured to

trap the attempted writes to, for example, the MSR register that correspond to interprocessor commands. A triggered event for the trapped command may be sent to below-O/S agent **712** for handling to verify the source of the attempt.

[0188] Microcode security agent **708** may be configured to intercept the generation and communication of messages from the processor such as software interrupts **722**. Microcode security agent **708** may be configured to control the execution of an interrupt such that they may be accessed by authorized software only. For example, drivers without a known identity (such as determined by hashes, source of driver in memory, etc.) or a malicious identity will not be allowed to execute software interrupts. Microcode security agent **708** may trap the access of the interrupt and pass the triggered event to the below-O/S agent **712** for handling.

[0189] In another example, microcode security agent **708** may be configured to trap the generation of exceptions **718** by processor **702**. Exceptions may include, for example, divide-by-zero operations, page faults, and debug signals. Read access to the memory addresses containing these may be trapped by microcode security agent **708** and handled by below-O/S agent **712**.

[0190] Microcode security agent **708** may be configured to protect various data structures of the processor **702**. For example, malware may attack the Interrupt Descriptor Table ("IDT"). In one embodiment, microcode security agent **708** may trap write access attempts to memory locations containing the IDT itself. In another embodiment, microcode security agent **708** may protect the memory locations where functions for changing the IDT are stored, such as "LOAD IDT" and "STORE IDT." In another example, microcode security agent **708** may be configured to protect the EFLABS or similar data structure, or flags associated with interrupt handlers. Malware may attempt to subvert the operation of interrupt handlers through the alteration of such resources by unauthorized sources.

[0191] Although microcode security agent **708** may be specific to the particular instances of a specific type of processor, as different circuitry arrangements may necessitate different microcode instructions, a set of security rules **707** may be valid for all processors using a given instruction set. This may be possible because microcode security agent **708** may trap certain instructions, which would not change between different processors implementing the same instruction set, but the circuitry where the associated resources may vary and depend upon the circuitry. For example, a main desktop central processing unit ("CPU") and an embedded system CPU may both be ISA processors from the same manufacturer, and thus security rules **707** may be shared at least in part between the two types of processors. In contrast, a graphics processing unit on a graphics processor or an automobile embedded processor with a different instruction set may not be able to share security rules **707**.

[0192] In operation, microcode security agent **708** may be running in the processor **702** of electronic device **701** and below-O/S agent **712** may be running below the level of operating system of electronic device **104**. Microcode security agent **708** and below-O/S agent **712** may authenticate each other. Microcode security agent **708** may initiate trapping of access to system resources **724** and outputs or communication generated by microcode modules **710**. Microcode security agent **708** may be so initiated upon demand from below-O/S agent **712**, upon a security rule **707**, or upon startup of processor **702**. Below-O/S agent **712** may send a security enablement request to microcode security agent **708** because of an occurrence in system **700**, an administrator or system setting, or because of a triggered security rules **723**. Such a request may be generated, for example, because a particular program is to be executed, sensitive data is to be accessed, or a malware threat has been detected elsewhere in system **700**. In-O/S security agent **719** and/or below-O/S system agent **712** may authenticate itself to microcode security agent **708**. To authenticate itself, in-O/S security agent **719** and/or below-O/S system agent may call a privileged instruction provided by processor **702** to initiate the authentication process. The call may cause microcode security agent **708** measure and authenticate, with a signature or hash, for example, in-O/S security agent **719** and/or below-O/S system agent **712**.

[0193] Microcode security agent **708** may receive security rules **707** from below-O/S agent **712**. Microcode security agent **708** may be updated by function calls, or by writes to shared memory such as a memory store. Microcode security agent **708** may apply flags based on security rules **707** to a control structure of microcode **706** configured to trap specific instructions, operands to such instructions, target addresses, source addresses, or any combination thereof. Microcode security agent **708** may trap attempted accesses of system resources by entities running above the processor, such as operating system **713**, application **710**, or driver **711**. The operation of microcode security agent **708** may be transparent to such entities. Microcode security agent **708** may trap the generation of information such as outputs from instances of other microcode modules **710**. Such microcode modules **710** may include other portions of microcode configured to perform various tasks for processor **702**. For example, some of microcode modules **710** may detect when a processor exception or interrupt is to be generated, how to route input and output data, or perform mathematical operations. The operation of microcode security agent **708** may be transparent to such modules. Microcode security agent **708** may use a state machine to perform certain trapping predicated on previous events observed.

[0194] Upon trapping an access to a resource or a generation of information, microcode security agent **708** may created a triggered event associated with the trapping. Such a triggered event may contain information about the trapping, including contextual information such as the instruction trapped, parameters used, originating memory locations, and target memory locations.

[0195] In one embodiment, microcode security agent **708** may handle the triggered event. In another embodiment, microcode security agent **708** may pass the triggered event to below-O/S agent **712** or another security agent for handling. Microcode security agent **708** may consult security rules **707** to determine whether and how to handle the triggered event, or to pass the triggered event to below-O/S agent **712**. Microcode security agent **708** may wait for a reply from below-O/S agent **712**, or may allow the trapped action if no follow-up is required by security rules **707**. Microcode security agent **708** may take corrective action based on security rules **707**, such as allowing or denying an instruction, or replacing a value or parameter to be executed.

[0196] Below-O/S agent **712** may receive a triggered event from microcode security agent **708**. Below-O/S agent **712** may consult security rules such as security rules **723** to determine an appropriate action to take based on the triggered event. Below-O/S agent **712** may use triggered event infor-

mation from microcode security agent **708**, contextual information from in-O/S security agent **719**, information from protection server **202**, determinations from other security agents, administrator settings, time, or other information to determine the appropriate action that should be taken. Below-O/S agent **712** may send actions to be taken to in-O/S security agent **719** and/or microcode security agent **708**. Below-O/S agent **712** may send information regarding the triggered event and resultant actions to protection server **202**.

[0197] Microcode security agent **708** may receive an action to be taken from another security agent, such as below-O/S agent **712**. Microcode security agent **708** may execute the received action, such as allowing or denying an instruction, or replacing a value or parameter to be executed.

[0198] FIG. **8** is an example embodiment of a method **800** for microcode-based, personalized and configurable protection for an electronic device from malware. In step **805**, an instance of a microcode security agent may be validated. In step **810**, an instance of another security agent may be validated. Such a security agent may include a below-O/S security agent. In step **815**, one or more security rules for trapping at microcode level within a processor may be obtained, sent or received. Such security rules may be communicated by, for example, function calls or by writing parameters to a shared memory space. In step **820**, security trapping of resources at the microcode level may be initiated. In one embodiment, such initiation may arise from receiving a signal to begin security trapping. In such an embodiment, a signal may be received because a malicious attack on a system has been detected, or because sensitive data may be present in a system. In another embodiment, such initiation may arise from consultation of a security rule. In yet another embodiment, such initiation may arise from the startup of a processor.

[0199] In step **825**, flags corresponding to operations to be trapped may be set in microcode. Such flags may correspond to specific instructions, operands to such instructions, target addresses, source addresses, or any combination thereof. Such flags may be defined by security rules that were received. In step **830**, instructions to be executed may be received and compared against the trapping flags. In step **835**, information generated and to be sent from microcode may be received and compared against the trapping flags. Steps **830** and **835** may be implemented by way of a state machine, wherein the steps may be repeated, and the results from multiple iterations of step may be remembered and compared together against a flag or security rule.

[0200] In step **840**, it may be determined whether an instruction or information has been trapped. If nothing was trapped, the method may return to monitoring instructions and generated information in steps **830** and **835**. If something was trapped, then in step **845** a triggered event associated with the trapping may be created. Such a triggered event may contain information about the trapping, including contextual information such as the instruction trapped, parameters used, originating memory locations, and target memory locations.

[0201] In step **850**, it may be determined whether the triggered event is to be handled within microcode, or whether a security agent outside microcode should handle the triggered event. If the triggered event is to be handled within microcode, then in step **855** an appropriate action for the triggered event may be taken. Such an action may be defined by consulting a security rule. Such an action may include allowing an instruction to be executed or information to be sent, denying the instruction or communication, replacing values in memory or in parameters, or any other corrective action required. The method **800** may then continue security monitoring in steps **830** and **835**.

[0202] If the triggered event is to be handled outside of the microcode, then in step **860** the triggered event may be sent to a security agent for handling the triggered event. In step **865**, additional information related to the triggered event may be gathered. Such information may include settings, preferences, contextual information, or malware status. Such information may be used in step **870** to apply a security rule to the triggered event. Such an application may yield a course of action to be taken with respect to the triggered event. In step **875** such a course of action may be specified and transferred to various security agents which may implement the specified action. Such actions may include corrective actions, allowing an operation or communication to take place, reporting the event to a protection sever, or any other suitable result. In step **880**, the actions specified in step **875** may be taken. The method **800** may then continue security monitoring in steps **830** and **835**.

[0203] FIG. **9** is an example embodiment of a system **900** for regulating software access to security-sensitive processor resources on an electronic device **901**. System **900** may include a below-O/S trapping agent **920** and a triggered event handler **922** configured to operate on electronic device **901** to detect malicious attempts to access processor resources **924** from software-based entities running in operating systems of electronic device **901** such as operating system **913**. Furthermore, below-O/S trapping agent **920** and triggered event handler **922** may be configured to use one or more security rules **908** to determine what attempted operations or generation of information to trap and how to handle a triggered event created corresponding to the trapped operation or information. Below-O/S trapping agent **920** and triggered event handler **922** may be configured to allow, deny, or take other corrective action for the triggered event.

[0204] Electronic device **901** may be implemented wholly or in part by or configured to implement the functionality of the electronic device **103** of FIG. **1**, electronic device **204** of FIG. **2**, electronic device **404** of FIG. **4**, electronic device **701** of FIG. **7**, and/or any combination thereof. Electronic device **901** may include one or more processors **902** coupled to a memory **903**. Processor **902** may be implemented wholly or in part by or configured to implement the functionality of processor **208** of FIG. **2**, processor **408** of FIG. **4**, processor **702** of FIG. **7**, or any combination thereof. Memory **903** may be implemented wholly or in part by or configured to implement the functionality of memory **206** of FIG. **2**, memory **406** of FIG. **4**, memory **703** of FIG. **7**, and/or any combination thereof. Electronic device **901** may include an operating system **913**, which may include an in-O/S security agent **919** coupled to one or more security rules **921**. Operating system **913** may be implemented wholly or in part by or configured to implement the functionality of operating systems **112** of FIG. **1**, operating system **212** of FIG. **2**, operating system **412** of FIG. **4**, operating system **713** of FIG. **7**, and/or any combination thereof. In-O/S security agent **919** may be implemented wholly or in part by or configured to implement the functionality of in-O/S security agent **218** of FIG. **1**, in-O/S security agent **418** of FIG. **4**, and/or in-O/S security agent **719** of FIG. **7**, or any suitable combination thereof.

[0205] Below-O/S trapping agent **920** may be implemented by or configured to implement the functionality of below-O/S trapping agent **104** of FIG. **1**, SVMM **216** of FIG. **2**, firmware

security agents **440**, **442** or PC firmware security agent **444** of FIG. **4**, firmware security agent **516** of FIG. **5**, microcode security agent **708** of FIG. **7**, and/or any combination thereof. Triggered event handler **922** may be implemented by or configured to implement the functionality of triggered event handler **108** of FIG. **1**, SVMM security agent **217** of FIG. **2**, below-O/S agent **450** of FIG. **4**, below-O/S agent **712** of FIG. **7**, and/or any combination thereof. In various embodiments, some of the functionality of below-O/S trapping agent **920** may be accomplished by triggered event handler **922**, or some of the functionality of triggered event handler **922** may be accomplished by below-O/S trapping agent **920**. Furthermore, below-O/S trapping agent **920** and triggered event handler **922** may be implemented in the same software module.

[0206] Security rules **908** may be implemented by or configured to implement the functionality of security rules **114** of FIG. **1**, security rules **222** of FIG. **2**, security rules **434**, **436**, **438** of FIG. **4**, security rules **518** of FIG. **5**, security rules **707**, **723** of FIG. **7**, and/or any combination thereof. Security rules **921** may be implemented by or configured to implement the functionality of security rules **220** of FIG. **2**, security rules **420** of FIG. **4**, security rules **721** of FIG. **7**, and/or any combination thereof.

[0207] Below-O/S trapping agent **920** may be configured to intercept access to or information from any suitable resource, such as processor resources **924**. For example, processor resources **924** may be implemented by or configured to implement the functionality of resource **106** of FIG. **1**, system resources **214** of FIG. **2**, portions of components such as display **424** and storage **426** of FIG. **4**, or system resources of FIG. **7**. Processor resources **924** may include resources available to a processor such as processor **902** for enabling the processor to load and execute instructions. Such resources may include, for example, data registers **928**, control registers **930**, caches **934**, processor flags **936**, processor cores **938**, processor exceptions **940**, or processor interrupts **942**. An attempted access of such a resource may include an instruction such as an assembly language instruction with operands. The processor resources **924** on which trapping may be available may depend upon the resources exposed by the processor **902**. For example, if below-O/S trapping agent **920** is implemented in a virtual machine monitor, the processor resources **924** available for the below-O/S trapping agent **920** to trap may be limited to processor resources **924** exposed by processor **902** for the purposes of virtualization. In such a case, processor **902** may include virtualization extensions for some of processor resources **924**. In another example, if below-O/S trapping agent **920** is implemented in a microcode security agent, then processor **902** may have made nearly all resources of the processor **902** available for trapping.

[0208] Below-O/S trapping agent **920** may include a processor resource control structure ("PRCS") **926**. PRCS **926** may be implemented in a record, data structure, table, or any other suitable structure. PRCS **926** may contain information specifying which instructions, information, or attempted access of processor resources **924** are to be trapped. Below-O/S trapping agent **920** or triggered event handler **922** may be configured to set flags in PRCS **926** corresponding to sensitive operations, information, or resources that are to be trapped. Below-O/S trapping agent **920** or triggered event handler **922** may be configured to set such flags in PRCS **926** according to information contained within security rules **908**.

[0209] FIG. **10** is an example embodiment of a PRCS **1000**. PRCS **1000** may be an example embodiment of the PRCS **926** of FIG. **9**. PRCS **1000** may include a table of entries **1014** of various processor resources that are to be trapped. Each entry may have one or more fields **1004**, **1006**, **1008**, **1010**, **1012** identifying the resource and the conditions which may yield a triggered event. For example, PRCS **1000** may have fields for a trigger flag **1002**, an identifier **1004** of a resource, a type **1006** associated with the resource, a trigger type **1008**, when-to-trigger conditions **1010** about when to trigger an event, and an execution stage **1012** in which to trigger an event. The implementation of PRCS **1000** may depend upon the nature of the processor whose resources are identified, including the architecture (such as Industry Standard Architecture "ISA") or the resources exposed by the processor **902**.

[0210] Trigger flag **1002** may include an indication of whether trapping and triggering for the associated entry **1014** is turned on or off. Such a flag may allow a trapping condition to be loaded in PRCS **1000** as an entry **1014** but yet remain dormant. Thus, PRCS **1000** may be loaded with embodiments of security rules without actively enforcing them. Trigger flag **1002** may be configured to be set by an entity such as the below-O/S trapping agent **920** of FIG. **9**. Such an operation may enable an anti-malware system using PRCS **1000** to operate much faster in contrast to a system which would require PRCS **1000** to be populated and depopulated each time trapping for a particular resource or condition was to be enabled or disabled. The ability to turn on and turn off an entry **1014** may enable an anti-malware system to selectively trap certain operations. Such selectivity may be advantageous if a particular trapping operation is expensive in terms of time or execution, and thus an entry **1014** might be enabled only when particular conditions are detected. For example, if a system normally writes many times to a particular register, trapping on access to that register may be turned off until another part of the antimalware system detects suspicious behavior indicating a possible malware infection. In such a case, the trigger flag **1002** of an entry **1014** corresponding to writes of the register may be set to "ON" to catch any additional malicious attempts to attack resources.

[0211] Resource identifiers **1004** may include an identification of a particular resource of the processor that is to be trapped. For example, an identifier **1004** may show that the resource is a register such as a particular data register, address registers such as EAX, a stack register, a control register, a vector register, stack pointers such as ESP, an instruction register, a program counter, an instruction register, a program status word, a constant register, a floating point register, or a conditional register. As other examples, identifier **1004** may identify that the resource is an instruction such as "JMP," "JZ" (jump if condition is equal to zero), "JNZ" (jump if condition is not equal to zero), "MOV" (move a value), or "SysEnter" (a fast call to a Ring 0 procedure). As yet further examples, identifier **1004** may identify that the resource is one of other resources like a cache such as a translation lookaside buffer; a counter such as a time stamp counter; a logical core such as processor**0**, processor**1** . . . processorN of the system; or processor exceptions such as "DIV/0" or interrupts such as an interprocessor interrupt or other global variables. Resource identifier **1004** may be translated into a representation of the address of the instruction, register, or other resource represented by resource identifier **1004**. Resource type **1006** may include an identification of the class or type of resource that the entry **1014** includes. Some entries of PRCS **1000** may apply to all resources of a particular type.

[0212] Trigger type **1008** may include an identification of whether the handling of a resulting triggered event is synchronous or asynchronous. Synchronous triggers may cause the execution or communication of the trapped resource to halt until, for example, it is determined whether the attempt is indicative of malware. Asynchronous triggers may allow the execution or communication of the trapped resource to continue, while the trigger is, for example, recorded for future evaluation. In one embodiment, attempted accesses of resources triggered asynchronously may be used to build an evaluation of a larger series of actions, and the proper evaluation of such a series of actions may require multiple data points before a determination can be made. For example, whether a particular read of an instruction pointer register may not itself be malicious, but a subsequent use of the information returned may be malicious. Thus, a state machine may be used to first asynchronously trap the read of the instruction pointer register, but then synchronously trap its usage in another instruction.

[0213] When-to-trigger conditions **1010** may include logical rules or conditions under which a triggered event will be generated based on the access of the resource. For example, triggered events may be generated for a register when the resource is written to or read. Triggered events may be generated for an instruction such as "JMP" when the instruction is executed. Triggered events may be generated for a cache such as a Translation Lookaside Buffer when the cache is invalidated. Triggered events may be generated for a processor core depending upon the state of the processor, such as when the core is idle. An processor exception or processor flag may be triggered when the flag or exception is set or written. When-to-trigger conditions **1010** may include compound logical conditions, such as multiple conditions on a single resource (such as a value range), conditions on multiple resource (thus tying in multiple entries **1014**), or a combination of both.

[0214] When-to-trigger conditions **1010** may contain conditions according to the type of resource that is to be trapped. For example, a register may be triggered when it is written, written with a particular value, or read. In another example, a cache or pointer may be similarly triggered when it is written, written with a particular value, or read. In yet another example, a processing core may be triggered when the core is idle. In still yet another example, interprocessor interrupts such as one used to command processor cores to halt, sleep, or activate may be triggered before the interrupt is sent (upon attempted access of the global space of the interrupt table) or after the interrupt is sent (after the interrupt table is written).

[0215] Execution stage to trigger **1012** may include an indication of in which stage of the execution of an instruction the attempted access will be trapped and a triggered event generated. Execution stage to trigger **1012** may be used in combination with when-to-trigger conditions **1010** as an additional requirement to trap a given resource. To trap a given entry, when-to-trigger conditions **1010** may be evaluated when the associated instruction reaches the stage of execution specified in execution stage to trigger **1012**. Execution stage to trigger **1012** may include entries corresponding to, for example, five stages or steps of the execution of an instruction by a processor. In one embodiment, five such stages of execution of an instruction may include 1) fetching the instruction, 2) decoding of the instruction, 3) execution, 4) accessing a memory location for the results, and 5) writing a return value back to memory, register, or another location. In such an embodiment, execution stage to trigger **1012** may include the ability to trigger before or after any of the five stages. This provides a total of six different example triggering options—before fetching, after decoding (and thus before execution), after execution (and thus before accessing a memory location), after accessing a memory location (and thus before writing a return value), and after writing a return value. The ability to trap based upon the stage of execution may provide significant flexibility unavailable in other anti-malware systems. For example, the result of executing a particular instruction may be unknown beforehand, and thus an anti-malware system may set the value of execution stage to trigger **1012** to be after accessing a memory location for the results, but before writing a return value back to a register as commanded by the instruction. This may allow the anti-malware system to evaluate the results of the operation without allowing it to be written. If the results indicate a malicious operation, then a dummy value may be written back to the register instead of the value returned from the fourth stage of execution. Information about the attempted execution may be provided to a handler of the triggered event based on the attempted execution to help determine whether the attempt is malicious.

[0216] Each resource **1004** of PRCS **1000** may have multiple entries corresponding to combinations of the access of the resource **1004** with another **1004**. Such combination of accesses may include a two-step or more process to be trapped. For example, entries **1014** may include separate entries for a) the access of a memory location corresponding to an interrupt descriptor table ("IDT") in combination with an access of control registers, and b) the access of a memory location corresponding to an interrupt descriptor table in combination with an access of general purpose registers. Furthermore, in FIG. **9** such separate entries may be handled by separate portions of system **900**. For example, specific in-O/S trapping agents **919** may handle gathering contextual information for trapped IDT-general register access, while other in-O/S trapping agents **919** may handle gathering contextual information for trapped IDT-control register access.

[0217] Returning to FIG. **9**, below-O/S trapping agent **920** may be configured to set flags or add entries in PRCS **926**. Below-O/S trapping agent **920** may be configured to access one or more security rules such as security rules **908** to determine such flags or entries. In one embodiment, below-O/S trapping agent **920** may be configured to receive instructions to set such flags or entries from triggered event handler **922**, which may call below-O/S trapping agent **920** after consulting security rules **908** or protection server **202**. A set of specific privileged routines may be provided by processor **902** and/or below-O/S trapping agent **920** for setting flags or adding entries to PRCS **926**.

[0218] If electronic device **901** includes more than one processor, each such processor may have a corresponding PRCS **926**. In one embodiment, system **900** may include a below-O/S trapping agent **920** for each such PRCS **926**. In another embodiment, below-O/S trapping agent **920** may be configured to trap resources represented in each such PRCS **926**.

[0219] If system **900** supports virtualization, then PRCS **926** itself may be virtualized. The contents of a virtualized PRCS **926** may be limited to those resources which are virtualized by the corresponding processor **902**. Such a virtualized PRCS **926** may be included in a virtual machine monitor. In such a case, below-O/S trapping agent **920** or triggered event handler **922** may be configured to control PRCS **926** in

such a virtual machine monitor. In another embodiment, below-O/S trapping agent **920** may be configured to trap resources represented in each such PRCS **926**. Furthermore, entries **1014** may be created in and trigger flags **1002** set in each such virtualized PRCS **926**, on a per-PRCS or per-virtualized processor basis.

[0220] Below-O/S trapping agent **920** may be configured to send a triggered event resulting from a trapped attempt or communication to triggered event handler **922**. Triggered event handler **922** may be configured to perform any suitable subsequent action based on the information of the triggered event and one or more security rules **908**. For example, triggered event handler **922** may be configured to allow execution of an attempted instruction, but require notification of the results after execution. In another example, triggered event handler **922** may be configured to skip the execution of a command or communication altogether. Such an example may be applied if no return value is required. In yet another example, execution may be transferred to a new location by, for example, by using a "JMP" instruction to send execution to the address of a repair routine.

[0221] In operation, below-O/S trapping agent **920** and triggered event handler **922** may be operating on electronic device **901**. Below-O/S trapping agent **920** may be operating below the level of the operating systems of electronic device **901**. Furthermore, triggered event handler **922** may also be operating below the level of the operating systems of electronic device **901**. Triggered event handler **922** may consult security rules **908** or protection server **202** to determine what flags **1002** or entries **1014** to set in PRCS **926**. Triggered event handler **922** may instruct below-O/S trapping agent **920** what flags **1002** or entries **1014** to set in PRCS **926**. Depending upon various conditions detected, such as applications **910** in use, other indications of malware detected, previously triggered events, or administrator settings for electronic device **901**, below-O/S trapping agent **920** and triggered event handler **922** may change the trigger flags **1002** or add new entries **1014** in PRCS **926** dynamically during the operation of electronic device **901**. Information to base such dynamic changes may come from, for example, below-O/S trapping agent **920** or in-O/S agent **919**. Entries **1014** in PRCS **926** may be identified according to the resource **1004** or resource type **1006**. The trigger type **1008** may be set to configure a subsequent trapped event to be synchronous or asynchronous. When-to-trigger conditions **1010** may be set to configure under what circumstances an intercepted request will generate a triggered event, as may execution stage to trigger **1012**.

[0222] Entries in PRCS **926** may be dynamically enabled or disabled, depending upon various conditions encountered by system **900**. For example, below-O/S trapping agent **920** may disable a trapping operation that is expensive because the attempted access that is trapped occurs frequently with many false-positives, until such a time that triggered event handler **922** receives an indication that the electronic device **901** is under a malware attack. Then, below-O/S trapping agent **920** may enable the trapping operation. In one embodiment, under such conditions extensive trapping on one or more processor resources **924** may be enabled to prevent unknown malware actions from harming electronic device **901** further. Such extensive trapping may extend to essentially shutting down the entire execution environment of a processor, virtualized processor, thread, process or application.

[0223] A request for a processor resource **924** may arise from an entity at the level of operating systems in system **900**, such as from application **910**, driver **911**, or operating system **913**. The request may be passed through to processor resources **924** but intercepted by below-O/S trapping agent **920**. Furthermore, information or communication may be generated from the processor through various processor resources **924**. The information or communication may be intercepted by below-O/S trapping agent **920**.

[0224] Below-O/S trapping agent **920** may use PRCS **926** to trap an access of a resource if the information or communication matches any when-to-trigger **1010** fields of entries **1014** in PRCS **926**, and subsequently generate a triggered event. Entries **1014** which have been enabled by trigger flags **1002** being set to "ON" may be matched to the attempted access or information or communication. The resource to be accessed may be compared to the resource field **1004** and/or resource type field **1006**. If the resource to be accessed matches such fields, then when-to-trigger conditions **1010** may be evaluated. If the when-to-trigger conditions **1010** match system information or information about the request, then PRCS **926** may generate a triggered event. Execution stage to trigger **1012** may be used to determine when to generate the triggered event. For example, the triggered event may be created before an instruction fetch, after an instruction fetch, after execution, after memory is accessed for a subsequent write, or after another resource such as a register is accessed for a write back. Furthermore, a triggered event may be generated for an attempted communication or generation of information such as an interprocessor interrupt like "Interrupt Sleep" before or after the interrupt is sent or written to an interrupt table. A generated triggered event may be synchronous or asynchronous, depending upon trigger type **1008**. Below-O/S trapping agent **920** may halt execution of the attempted access of the resource or generation of the communication if a synchronous triggered event is generated, pending handling of the event. Below-O/S trapping agent **920** may allow execution of the attempted access of the resource or generation of the communication if an asynchronous triggered event is generated. Below-O/S trapping agent **920** may add additional context information about the attempt into the triggered event, such as the memory address from which the attempt originated, where results were to be written, or any other suitable information.

[0225] Below-O/S trapping agent **920** may include information related to the triggered event for the purposes of deciding whether the triggered event is suspicious. For example, below-O/S trapping agent **920** may determine information such as determining from what portion of memory the attempted access was made. The portion of memory may be correlated by triggered event handler **922** against known processes, applications, or programs running on electronic device **903**. If the attempted access arose from an unknown or unauthorized process, application or program, then the attempt may be suspicious. Triggered event handler **922** may use information from in-O/S security agent **919** to determine such a correlation. In another example, below-O/S trapping agent **920** may provide information regarding previously triggered events, such as those recorded in a state machine. Such previously triggered events that are related to the presently triggered events may provide contextual information about whether the attempts are suspicious.

[0226] Below-O/S trapping agent **920** may pass the triggered event to triggered event handler **922**, which may handle the event by evaluating information in the triggered event and/or contextual information from in-O/S agent **919** accord-

ing to security rules **908**. A resulting appropriate action may be determined and sent back to below-O/S trapping agent **920** to apply to the trapped attempt. Such an action may include allowing the attempt, denying execution of an instruction, or substituting different data or instructions to circumvent operation of malware.

[0227] Below-O/S trapping agent **920** may store triggered events for subsequent reference in trapping future attempted access. For example, a malicious operation may require multiple instructions to be executed by processor resources **924**. Thus, each step of such malicious behavior may be reflected in a separate entry **1014** in PRCS **926**. Below-O/S trapping agent **920** may trap a first step of a malicious operation, which by itself may not be malicious but only when in combination with subsequent steps. In such a case, the entry **1014** for such a step may be set to trigger asynchronously, as the condition is merely recorded into a state machine so that below-O/S trapping agent **920** or PRCS **926** may be aware of previously handled attempts. The trapping of a second step of a malicious operation may have as a when-to-trigger condition **1010** the trapping of the first step.

[0228] FIG. **11** is an example embodiment of a method **1100** for regulating software access to security sensitive processor resources of an electronic device. In step **1105**, security rules may be accessed to determine in step **1110** what processor resources or processor communications are to be secured. A trapping agent operating below the level of operating systems in the electronic device may determine what resources and communications to trap. Such a trapping agent may operate in, for example, a virtual machine monitor, firmware, or microcode of a processor.

[0229] In step **1115**, entries corresponding to the resources or communications to be trapped may be written to a processor resource control structure, which may be configured to trap the operation, access, or other use of designated resources or communications under specified conditions. The entries in the PRCS may be written with identifications of the resource, the resource type, the conditions under which an event will be triggered, whether the trigger would be asynchronous or synchronous, and in/at what, if any, execution stage the attempted access or communication should yield a triggered event. In step **1120**, entries in the PRCS may also be written with a trigger or enablement flag which indicates whether or not the entry is activated for trapping or not. If the trigger flag is not set, then the entry may be dormant and not be used to trap attempted accesses of resources.

[0230] In step **1125**, access to resources or generation of communications may be monitored. Such a monitoring may take place through the PRCS. Entities in the electronic device may try to attempt to generate processor communications or attempt to access a processor resource. Such attempts to access a resource may originate from the level of operating systems of the electronic device. If an instruction, command, or other attempt to access the resource matches a resource identifier of an entry in the PRCS wherein the entry has been activated, then the attempt may be trapped. Similarly, if a processor communication is generated that matches a resource identifier of an entry in the PRCS wherein the entry has been activated, then the attempt may be trapped. In one embodiment, the attempt to access a resource or generate communication may be trapped if the additional criteria specifying when to trigger are met. For example, an attempted write of a control register may be trapped when the control register is ever written. In another example, an attempted write of a control register may be trapped when the control register is written with a specific value.

[0231] In step **1130**, it may be determined whether an attempted access or communication was trapped. If no attempt has been trapped, then in step **1140** it may be determined whether entries in PRCS need to be adjusted. Such an adjustment may include enabling or disabling such entries, adding new entries, or adjusting criteria or settings of entries. Method **1100** may then return to step **1125**. Such adjustment could be based on, for example, new malware threats detected in the electronic device, passage of time, previously trapped attempts, or an administrator's settings.

[0232] In step **1145**, if an attempt has been trapped, it may be determined whether a resulting triggered event should be synchronous or asynchronous. If the trigger type is not synchronous, then method **1100** may return to step **1125** in parallel with proceeding to step **1150**. If the trigger type is synchronous, then in step **1150** information about the trapped attempt may be stored. Such information may be used, for example, by a state machine in a future determination of whether a trapped attempt should yield a triggered event. In step **1155**, it may be determined whether all conditions of the trigger are met. Such conditions may require, for example, certain values to be written to the resource, or the request originate (or not originate) from particular locations in memory. Furthermore, such conditions may require that other attempts were previously trapped. Information about such attempts may be accessed and stored in a state machine. If all conditions of triggering are not met, then method **1100** may return to step **1125**.

[0233] If all conditions of triggering are met, then in step **1155** it may be determined in which, if any, specific stage of execution should the triggered event be generated. Such stages may include, for example, before an instruction in the attempt is fetched, after the instruction is fetched, after the instruction is executed, after memory is accessed to read a result, or after a value is written back. Furthermore, such stages may include before or after an interprocessor interrupt is executed. Once the designated execution stage is accomplished, a triggered event for the attempt may be generated in step **1165**. Contextual information, such as source or destination address of the attempt, or the resources involved may be included with the triggered event in step **1170** for delivery to a handler in step **1175**.

[0234] In step **1180**, security rules may be consulted to determine in step **1185** whether the triggered event is suspicious, not permitted by administrator settings, or indicative of malware. Contextual information, such as that of the triggered event, other events in the operating system of the electronic device, or administrator settings may be used to evaluate the application of the security rules to the triggered event. If the triggered event is not suspicious, then in step **1187** the trapping agent may be notified and method **1100** may return to step **1125**. If the triggered event is suspicious, then in step **1190** a resulting corrective action may be sent to the trapping agent. Such a corrective action may depend upon the specific attempt to access resources or generate processor communication. For example, a malicious instruction may have a value to be read or written spoofed, or a jump instruction may be redirected to a repair routine. In step **1195**, the corrective action may be applied. The method **1100** may return to step **1125**.

[0235] FIG. **12** is an example embodiment of a system **1200** for regulating software access for securing memory using

below-operating system trapping on an electronic device **1201**. System **1200** may include a below-O/S security agent **1220** configured to operate on electronic device **1201** to detect malicious attempts to access memory from software-based entities running in operating systems of electronic device **1201**, such as operating system **1213**. Furthermore, below-O/S security agent **1220** may be configured to use one or more security rules **1208** and a memory map **1206** to determine what attempted accesses of memory to trap and how to handle a triggered event created corresponding to the trapped operation. Below-O/S security agent **1220** may be configured to allow, deny, or take other corrective action for the triggered event.

[0236] Electronic device **1201** may be implemented wholly or in part by or configured to implement the functionality of the electronic device **103** of FIG. **1**, electronic device **204** of FIG. **2**, electronic device **404** of FIG. **4**, electronic device **701** of FIG. **7**, electronic device **901** of FIG. **9**, and/or any combination thereof. Electronic device **1201** may include one or more processors **1202** coupled to a memory such as physical memory **1203**. Processor **1202** may be implemented wholly or in part by or configured to implement the functionality of processor **208** of FIG. **2**, processor **408** of FIG. **4**, processor **702** of FIG. **7**, processor **902** of FIG. **9**, or any combination thereof. Physical memory **1203** may be implemented wholly or in part by or configured to implement the functionality of memory **206** of FIG. **2**, memory **406** of FIG. **4**, memory **703** of FIG. **7**, memory **903** of FIG. **9**, and/or any combination thereof. Electronic device **1201** may include an operating system **1213**, which may include an in-O/S security agent **1219** coupled to one or more security rules **1221**. Operating system **1213** may be implemented wholly or in part by or configured to implement the functionality of operating systems **112** of FIG. **1**, operating system **212** of FIG. **2**, operating system **412** of FIG. **4**, operating system **713** of FIG. **7**, operating system **913** of FIG. **9**, and/or any combination thereof. In-O/S security agent **1219** may be implemented wholly or in part by or configured to implement the functionality of in-O/S security agent **218** of FIG. **1**, in-O/S security agent **418** of FIG. **4**, and/or in-O/S security agent **719** of FIG. **7**, in-O/S security agent **919** of FIG. **9**, or any suitable combination thereof.

[0237] Below-O/S security agent **1220** may be implemented by or configured to implement the functionality of below-O/S trapping agent **104** or triggered event handler **108** of FIG. **1**, SVMM **216** or SVMM security agent **217** of FIG. **2**, firmware security agents **440**, **442**, below-O/S agent **450**, or PC firmware security agent **444** of FIG. **4**, firmware security agent **516** of FIG. **5**, or microcode security agent **708** or below-O/S agent **712** of FIG. **7**, below-O/S trapping agent **920** or triggered event handler **922** of FIG. **9**, and/or any combination thereof.

[0238] Security rules **1208** may be implemented by or configured to implement the functionality of security rules **114** of FIG. **1**, security rules **222** of FIG. **2**, security rules **434**, **436**, **438** of FIG. **4**, security rules **518** of FIG. **5**, security rules **707**, **723** of FIG. **7**, security rules **908** of FIG. **9**, and/or any combination thereof. Security rules **1221** may be implemented by or configured to implement the functionality of security rules **220** of FIG. **2**, security rules **420** of FIG. **4**, security rules **721** of FIG. **7**, security rules **921** of FIG. **9**, and/or any combination thereof.

[0239] Below-O/S security **1220** may be configured to intercept access to memory of electronic device **1201**. Such memory may include, for example, attempted access of addresses of physical memory **1203** or attempted access of pages of virtualized memory **1204**. Such an attempted access may originate from operating system **1213** or entities utilizing operating system **1213** to run on electronic device **1201**, such as application **1210** or driver **1211**.

[0240] In one embodiment, memory secured by below-O/S security **1220** may include virtualized memory **1204**. Virtualized memory **1204** may include memory available to entities, such as operating system **1213**, application **1210**, or driver **1211**, that have been abstracted from physical memory and/or storage. Virtualized memory **1204** may appear as a contiguous block of memory to entities such as operating system **1213**, application **1210**, or driver **1211**, although the actual spaces used may be spread disparately across actual physical memory, such as physical memory **1203**, and/or in storage such as on a disk. Virtualized memory **1204** may be virtualized according to extensions of processor **1202**. The address space of virtualized memory **1204** may be divided into memory pages. The memory pages may be each of equal size, such as four kilobytes. Electronic device **1201** may be configured to use page tables to translate the virtual addresses of virtualized memory **1204** into physical addresses of memory such as physical memory **1203** or addresses of storage. Electronic device **1201** may include a memory management unit **1214** ("MMU") configured to translate virtual addresses of virtual memory **1204** into physical addresses of memory such as physical memory **1203** and/or into addresses of a storage. The pages of virtual memory **1204** may be indexed. An attempted access of virtual memory **1204** pages may include an attempted read, write, or execution of the page, and below-O/S security agent **1220** may be configured to trap the attempt. In one embodiment, a page of virtual memory **1204** may correspond to a physical memory address or an address of a storage. In another embodiment, each page of virtual memory **1204** may correspond to a physical memory address. In yet another embodiment, pages containing certain contents such as specific portions of operating system **1213** may be pinned and may not change during the operation of electronic device **1201**.

[0241] In another embodiment, memory secured by below-O/S security agent **1220** may include physical memory **1203**. Physical memory **1203** may be accessed through addresses of the physical memory, as shown by markers (A), (B), (C), (D), (E), (F), (G), (H), (I), (J), and (K), which denote specific addresses in physical memory **1203** that may be the base address of a memory range containing a defined element. Physical memory **1203** may be accessed through an attempted read, write, or execution of a specific memory address, and below-O/S security agent **1220** may be configured to trap the attempt. For example, an attempted write may take the form of an instruction "MOV Addr**1**, Value" wherein a value represented by the variable "Value" is written to a specific memory address represented by "Addr**1**." Any instruction writing to a physical memory **1203** address may be used. An attempted read may take the form of an instruction such as "MOV Value, Addr**1**" wherein a value represented by the variable "Value" is read from a specific memory address represented by "Addr**1**." Any instruction reading from a physical memory **1203** address may be used. An attempted execution may take the form of an instruction loading an instruction pointer register such as "EIP" with a physical memory **1203** address, such as "MOV EIP, Addr**1**." Such an instruction may be configured to execute the code begin-

ning at the address represented by "Addr**1**." Any instruction for executing an address in memory may be used.

[0242] Below-O/S security agent **1220** may be configured to intercept attempted access to virtual memory **1204**. Furthermore, below-O/S security agent **1220** may be configured to intercept attempted access to physical memory **1203**. In one embodiment, a request for virtual memory **1204** may not be intercepted, but a subsequent corresponding attempted access of physical memory **1203** after MMU has translated the virtual memory **1204** page to a physical memory **1203** address, below-O/S security agent **1220** may be configured to intercept the attempted access to physical memory. In another embodiment, an attempted access may be made directly of physical memory **1203** without being translated through virtual memory **1204**, and below-O/S security agent **1220** may be configured to intercept the attempted access. In still yet another embodiment, an attempted access made to virtual memory **1204** may be intercepted, but below-O/S security agent **1220** may not be configured to intercept a subsequent access of a physical memory **1203** address.

[0243] Below-O/S security agent **1220** may be communicatively coupled to in-O/S security agent **1219**. Below-O/S security agent **1220** may be configured to receive contextual information about an attempted access of memory of electronic device **1201** from in-O/S security agent **1219**. The contextual information provided by in-O/S security agent **1219** may include the identity of entities that have attempted a particular access of memory of electronic device **1201**.

[0244] Below-O/S security agent **1220** may be communicatively coupled to or include a memory map **1206**. Memory map **1206** may be implemented in a file, record, data structure, or other suitable entity. Memory map **1206** may include information regarding the location of various entities of electronic device **1201** in memory. For example, if a process is loaded in memory of electronic device **1201** for execution, memory map **1206** may include information regarding which memory pages in virtualized memory **1204** or address ranges in physical memory **1203** contain the process. Depending upon the implementation of virtualization of memory in electronic device **1201**, all of the contents of the process may or may not be loaded in physical memory **1203**, as some contents may be loaded in storage such as a disk. For such contents to be accessed, they may be loaded into physical memory **1203**. In such a case, memory map **1206** may contain information about addresses where the contents are stored, whether in physical memory **1203** or in a storage such as a disk. Below-O/S security agent **1220** may be configured to use memory map **1206** to determine the identity or the owner of any given content in a virtual memory **1204** page or a physical memory **1203** address. Below-O/S security agent **1220** may build memory map **1206** by, for example, profiling the operation of the operating system **1213**, and then determining where in memory various sensitive components are located. As attempts to access memory are made—such as loading the operating system **1213** kernel, or executing kernel mode instructions—below-O/S security agent **1220** may be configured to communicate with in-O/S security agent **1219** to determine what portion of operating system **1213** is loading or being executed. In another example, below-O/S security agent **1220** may be configured to determine a hash or digital signature of the contents of a memory range of such a virtual memory **1204** page. The hash or digital signature may be compared against known values, which may be contained in security rules **1208** or obtained from protection server **202**. The known values may be the result of a previous characterization, in which portions of, for example, operating system **1213** have been identified. Elements to be mapped may be determined by security rules **1208**. Below-O/S security agent **1220** may be configured to track the movement of elements in memory map **1206** as the elements are copied from one place to another in the memory of electronic device **1201**.

[0245] FIG. **13** is an illustration of example embodiments of memory maps. In one embodiment, virtual memory map **1302** may include a mapping of elements to be tracked through their position in virtual memory. In another embodiment, physical memory map **1304** may include a mapping of elements to be tracked through their position in physical memory. In various embodiments, virtual memory map **1302** and physical memory map **1304** may be mapped together so that an element may be tracked in both mappings.

[0246] Virtual memory map **1302** may reflect ten different virtual memory pages. Virtual memory map **1302** may illustrate, for example, that a kernel operating system data structure such a page directory may be found in memory page **1** and memory page **2**. In another example, the elements of a particular process, function, or routine called "Fn**1**," may be found in memory pages **4-6**. In yet another example, data structures for permissions for a system service dispatch table ("SSDT") may be found in page **8**. In still yet another example, elements of a particular process, function or routine called "Fn**2**" may be found in memory page **8** and memory page **9**.

[0247] Physical memory map **1304** may reflect the location of elements with physical memory. Portions of elements in physical memory may be spread across the memory in non-contiguous segments or blocks. Furthermore, portions of elements in physical memory may be spread across the memory in arbitrary order. The size of each segment may vary in size. The segment may begin at an address at an offset from the base address. The example base address shown in FIG. **13** is 00x000, terminating at address FFxFFF. Addresses denoting the start of various segments of the physical memory are denoted (A)-(O). For elements that are contained within multiple segments of the physical memory, the order of the elements may be noted. In physical memory multiple segments of an element may be linked together by pointers where the end of one segment of an element may point to the next segment of the element.

[0248] For example, Fn**1** may be mapped to the segments between (A) and (B), (J) and (K), and (M) and (N). In another example, SSDT permissions may be mapped to the segment between (G) and (H). In yet another example, the page directory data structure may be mapped to the segments between (O) and FFxFFF, (F) and (G), and (I) and (J). In still yet another example, Fn**2** may be mapped to the segments between (H) and (I), and (B) and (C).

[0249] Returning to FIG. **12**, below-O/S security agent **1220** may be configured to consult security rules **1208** to determine what portions of memory to protect, and how to protect them. For example, security rules **1208** may be configured to indicate that the page directory data structure may only be written to by certain privileged entities of electronic device **1201**. Thus, attempts to write to the page directory data structure may be trapped, and elements attempting the write may be examined to determine whether they are safe, unknown, or known to be unsafe. Below-O/S security agent **1220** may be configured to consult memory map **1206** to determine where the page directory data structure is located

in memory. If below-O/S security agent **1220** is implemented, for example, fully or in part in a virtual machine monitor, below-O/S security agent **1220** may be configured to set a flag in a control structure to trap any attempted write to memory pages **1** and/or **2** of virtual memory **1204**. If below-O/S security agent **1220** is implemented, in another example, fully or in part in microcode, below-O/S security agent **1220** may be configured to set a flag in a control structure to trap any attempted write to memory addresses within the address ranges between addresses (O) and FFxFFF, (F) and (G), and (I) and (J) of physical memory **1203**.

[0250] In another example, security rules **1208** may be configured to indicate that Fn**1** may only be called by certain privileged entities of electronic device. Thus, attempts to execute Fn**1** may be trapped, and elements calling Fn**1** may be examined to determine whether they are safe, unknown, or known to be unsafe. Below-O/S security agent **1220** may be configured to consult memory map **1206** to determine where Fn**1** resides in memory. If below-O/S security agent **1220** is implemented, for example, fully or in part in a virtual machine monitor, below-O/S security agent **1220** may be configured to set a flag in a control structure to trap an attempted execution of memory pages **4**, **5**, and/or **6** of virtual memory **1204**. If below-O/S security agent **1220** is implemented, in another example, fully or in part in microcode, below-O/S security agent **1220** may be configured to set a flag in a control structure to trap any attempted execution of memory address (A) of physical memory **1203**. In some cases, wherein different portions of Fn**1** may be separately executed, below-O/S security agent **1220** may be configured to trap attempted execution of any memory address within the ranges between (A) and (B), (M) and (N), the addresses (O) and FFxFFF, (F) and (G), (J) and (K), or (I) and (J) of physical memory **1203**.

[0251] In one embodiment, below-O/S security agent **1220** may be configured to consult in-O/S security agent **1219** to determine what entity has made the call to write to memory, which is then used to determine whether the entity is authorized or not to make the write. In another embodiment, below-O/S security agent **1220** may be configured to determine the memory page of virtualized memory **1204** from which the request came and consult memory map **1206** to determine whether such a memory page is associated with any elements mapped therein. In yet another embodiment, below-O/S security agent **1220** may be configured to determine a hash or signature of a memory page of the requesting element and compare it against hashes and signatures of known entities.

[0252] If below-O/S security agent **1220** is implemented fully or in part by microcode, below-O/S security agent **1220** may be configured to determine the address of the instruction which attempted the write. In one embodiment, below-O/S security agent **1220** may be configured to make such a determination by examining an instruction pointer to determine where in physical memory **1203** the instruction was made. In another embodiment, by accessing memory map **1206**, below-O/S security agent **1220** may be configured to determine an element from the memory map **1206** associated with the address. In yet another embodiment, below-O/S security agent **1220** may be configured to determine a hash or signature of the requesting element and compare it against hashes and signatures of known entities.

[0253] Once an attempted access of memory has been trapped, below-O/S security agent **1220** may be configured to access security rules **1208** to determine how to handle the trapped attempt based on the identified requesting entity. Security rules **1208** may define that, for example, only certain specified kernel portions of operating system **1213** may call and execute Fn**1** or that only entities that are known to be safe and on a whitelist may write to the permissions of the SSDT. Below-O/S security agent **1220** may then be configured to take any appropriate action, such as allowing the request to proceed, denying the request, spoofing a response or written value, or executing a corrective process.

[0254] In operation, below-O/S security agent **1220** may be running below the level of operating systems of electronic device **1201** such as operating system **1213**. Below-O/S security agent **1220** may access security rules **1208** to determine what memory resources of electronic device **1201** to protect. Below-O/S security agent **1220** may determine, develop, and/or populate the contents of memory map **1206**. To do so, below-O/S security agent **1220** may access security rules **1208**, protection server **202**, or any other suitable source of information for populating information in memory map **1206**. Below-O/S security agent **1220** may intercept requests of physical memory **1203** or virtual memory **1204** from entities at the operating system level, such as operating system **1213**, application **1210**, or driver **1211**, to map the ownership and contents of memory in memory map **1206**. Below-O/S security agent **1220** may access in-O/S security agent **1219** to determine what entities are being loaded into memory so that memory map **1206** may be populated. Memory map **1206** may contain memory mapping for physical memory **1203**, virtual memory **1204**, and/or mappings between the two.

[0255] Below-O/S security agent **1220** may consult security rules **1208** to determine what portions of virtual memory **1204** and/or physical memory **1203** to protect. Security rules **1208** may specify that some portions of memory are to be secured on a dynamic basis, wherein protection for the memory may be enabled or disabled by below-O/S security agent **1220** depending upon a variety of considerations. Such considerations may include, for example, administrator settings, detection of malicious or suspicious behavior, time, previously detected accesses of memory, or any other suitable criteria. If protecting memory of electronic device **1201** is expensive in terms of computational resources, such dynamic enabling and disabling may allow below-O/S security agent **1220** to better secure critical portions of the memory of electronic device **1201** while lessening side affects on the ability of electronic device **1201** to carry out other tasks. For example, memory containing the contents of the kernel code of operating system **1213** may always be protected by below-O/S security agent **1220**, while the memory containing the contents of the code of a third-party application **1210** may be protected only upon other indications that malware is present or may affect the third-party application **1210**.

[0256] Below-O/S security agent **1220** may set a flag in a control structure to trap attempted access of physical memory **1203** and/or virtual memory **1204**. In one embodiment, as a request is made from an entity in operating system **1213** for a memory page in virtual memory **1204** designated to be trapped, below-O/S security agent **1220** may intercept the attempted request. In another embodiment, as a request is made for a memory page in virtual memory **1204**, below-O/S security agent may allow the request to be translated by MMU **1214** into a request for an address in physical memory **1203**, whereupon below-O/S security agent may intercept the attempted request. In yet another embodiment, as a request from an entity in operating system **1213** may be made for an

address in physical memory **1203** directly, below-O/S security agent **1220** may intercept the attempted request.

[0257] Once a request has been intercepted, below-O/S security agent **1220** may use any suitable mechanism to evaluate the intercepted request of memory. Security rules **1208** may be used to determine whether the attempt is suspicious, indicating a malicious attempt by malware to use the resources of electronic device **1201**. Security rules **1208** may include considerations of, for example, whether a read, write, or execution was attempted; what entity made the attempt; the memory address or page that was accessed; previous attempts or actions by the same requestor; security settings by an administrator of electronic device **1201**, such as rules that are more or less restrictive based upon the user of electronic device **1201**; or the identity of the requestor, as determined by memory location and/or digital signature or hash, or upon related pages or memory addresses.

[0258] For example, an attempted write of the page directory data structure in page **2** of virtual memory **1204** or at address (J) of physical memory **1203** may be intercepted by below-O/S security agent **1220**. If the write has come from a portion of memory of a process that is unknown, the write may be determined to be suspicious by below-O/S security agent **1220**. However, if the attempted write has come from a known, verified part of the operating system **1213** kernel, then the attempt may be determined to not be suspicious. Likewise, an attempted execution of Fn**2** at page **8** of virtual memory **1204** or at address (H) of physical memory **1203** may be intercepted. If the attempted execution was made from a user input, then the execution may be determined to not be suspicious. If the attempted execution was made from the memory of another program, and the program is not on an approved list, then the attempt may be determined to be suspicious or malicious.

[0259] In another example, if Fn**1** is a web browser that normally exposes its cache to other applications for purposes of interoperability, below-O/S security agent **1220** may allow a specified portion of the memory pages or memory addresses of Fn**1** to be read by other applications. However, if Fn**1** contains metadata or other information that should be kept private, then below-O/S security agent **1220** may secure those portions of the memory pages or memory addresses of Fn**1** from being read from any process other than Fn**1** itself.

[0260] Once a program has been determined to be suspicious, malicious, or otherwise indicative of malware, then below-O/S security agent **1220** may take any suitable corrective action. Below-O/S security agent **1220** may, for example, deny a write request to memory page **2** of virtual memory **1204** or address (J) of physical memory **1203**, yet return a result indicating that the value was written. The process generating the request may be monitored for additional attempts to access the resources of electronic device **1201**, may be stopped, or may be cleaned from electronic device **1201**. In another example, the attempted execution of page **8** of virtual memory **1204** or address (H) of physical memory **1203** may instead be directed to the execution of a honeybot process or a cleanup process.

[0261] The contents of the memory which are secured by below-O/S security agent **1220** may include data, code, or any other useful system resources which may be attacked by malware. Below-O/S security agent **1220** may protect the contents of memory against malware attempting to, for example, read, write, or hook mechanisms showing the processes running on electronic device **1201**, inject its code into portions of applications loaded in memory, or change permission and access flags of mapping tables for virtual memory **1204**. By operating below the level of operating system **1213**, below-O/S security agent **1220** may avoid malware running at the kernel mode level in operating system **1213**. Below-O/S security agent **1220** may accomplish zero-day detection, as in some cases it may not need knowledge that the identity of a requesting entity has been previously determined to be malicious—the fact that the entity is unknown may be used to deny access to some parts of the memory of electronic device **1201**. If the operating system **1213** or antivirus or antimalware measures running in the operating system **1213** are completely compromised, the memory may be completely locked from entities running at the level of the operating system.

[0262] One application of below-O/S security agent **1220** may be to detect an attempted access of the contents of virtual memory **1204** even before a read, write, or execute of the specific contents is attempted by detecting a change to the permissions of the particular memory page. The memory tables used by MMU **1214** may be resident in memory, in a page of virtual memory **1204** itself, and/or address of physical memory **1203**. An attempt to change the values of the memory table, for example, to change the permissions of a code section of a process from "read" to "write," may itself be trapped by below-O/S security agent **1220**. The memory page of virtual memory **1204** or the address of physical memory **1203** may be secured by below-O/S security agent **1220**, and upon a trapped attempt to write a new value to the permissions in such a location, below-O/S security agent **1220** may determine whether the requestor of the attempt is allowed to make such changes. For example, if the request to change the permissions of a code section of a process arose from a different process, the attempted change in permissions may be denied.

[0263] FIG. **14** is an example embodiment of a method **1400** for securing memory using below-operating system trapping of attempted access of an electronic device. In step **1405**, the virtual or physical memory of the electronic device may be mapped to determine the identity or owner of the contents of memory. In order to map the memory, for example, a protection server may be accessed; reads, writes, and execution of memory may be tracked; and/or contents of memory scanned and signatures generated for the contents.

[0264] In step **1410**, security rules may be accessed to determine in step **1415** addresses of physical memory or pages of virtual memory to be secured. The memory to be secured may depend, for example, upon the security rules, the user of the electronic device, other observed behavior in electronic device such as indications of malware, previous attempts to access secured memory, or administrator settings. The memory to be secured may change dynamically, as conditions of the operation of the electronic device may change. The security rules may specify entities of electronic device to be protected, and the location in physical or virtual memory of the entities may be determined by accessing the memory map.

[0265] In step **1420**, flags may be set in a control structure to trap attempted access of memory according to the requirements of the security rules. Such flags may be set for pages of virtual memory and/or addresses of physical memory. Flags may contain an indication of the memory that is to be secured, as well as the kind of access method (for example—read, write, or execute) that is to be flagged. In step **1425**, access to the secured memory may be monitored to see if an attempted

access of the designated type has been made to a designated address or page. In step **1430**, it may be determined whether an attempt to access the memory has been trapped. If not, then in step **1435** it may be determined whether flags of the memory to be secured require changing. If so, then the method **1400** may return to step **1410** to access security rules to update the flags for guarding access to memory. If not, then the method **1400** may return to step **1425** to monitor for attempted access of secured memory.

[0266] If an attempt to access the memory has been trapped, then beginning in step **1440** the trapped attempt may be evaluated. To evaluate the attempt, the memory map may be consulted to determine from where the request was made, and identify the requestor. The values of data to be written may be determined and evaluated for their contents. The nature of the attempt—read, write, or execute—may be considered. These example considerations may be used in conjunction with the security rules to determine whether or not the attempted access is indicative of malware in step **1445**. If the attempted access is indicative of malware, then in step **1450**, corrective action may be taken. Such corrective action may include denying the requested access, returning a spoofed value, or initiating a honeybot or corrective process. If the attempted access in not indicative of malware, then in step **1455** the request may be allowed. Method **1400** may return to step **1425** as required to continue securing the memory of the electronic device.

[0267] FIG. **15** is an example embodiment of a system **1500** for securing memory and storage of an electronic device **1504**. System **1500** may include a below-O/S security agent **1516** configured to operate on electronic device **1504** to protect against malicious attempts to access memory **1508** and storage **1526** of electronic device **1504**. Furthermore, below-O/S security agent **1516** may be configured to use one or more security rules **1522** to determine what attempted operations to trap, and how to response to such trapped operation. Below-O/S security agent may be configured to allow, deny, or take other corrective action for the trapped operation.

[0268] As shown in FIG. **15**, electronic device **1504** may include a processor **1506** coupled to a memory **1508**, an application **1510**, a driver **1511**, an operating system **1512**, a below-operating system security agent **1516**, storage **1526**, and application assets **1548**. Electronic device **1504** may be implemented wholly or in part by or configured to implement the functionality of electronic device **103** of FIG. **1**, electronic device **204** of FIG. **2**, electronic device **404** of FIG. **4**, electronic device **701** of FIG. **7**, electronic device **901** of FIG. **9**, electronic device of FIG. **1201** of FIG. **12**, and/or any combination thereof. Processor **1506** may be implemented wholly or in part by or configured to implement the functionality of processor **208** of FIG. **2**, processor **408** of FIG. **4**, processor **702** of FIG. **7**, processor **902** of FIG. **9**, processor **1202** of FIG. **12**, and/or any combination thereof. Memory **1508** may be implemented wholly or in part by or configured to implement the functionality of memory **206** of FIG. **2**, memory **406** of FIG. **4**, memory **703** of FIG. **7**, memory **903** of FIG. **9**, physical memory **1203** or virtualized memory of FIG. **12**, and/or any combination thereof. Application **1510** may be implemented wholly or in part by or configured to implement the functionality of application **110** of FIG. **1**, application **210** of FIG. **2**, application **410** of FIG. **4**, application **709** of FIG. **7**, application **910** of FIG. **9**, application **1210** of FIG. **12**, and/or any combination thereof. Driver **1511** may be implemented wholly or in part by or configured to implement the functionality of driver **111** of FIG. **1**, driver **211** of FIG. **2**, driver **411** of FIG. **4**, driver **711** of FIG. **7**, driver **911** of FIG. **9**, driver **1211** of FIG. **12**, and/or any combination thereof. Operating system **1512** may be implemented wholly or in part by or configured to implement the functionality of operating systems **112** of FIG. **1**, operating system **212** of FIG. **2**, operating system **412** of FIG. **4**, operating system **713** of FIG. **7**, operating system **913** of FIG. **9**, operating system **1213** of FIG. **12**, and/or any combination thereof. Below-O/S security agent **1516** may be implemented wholly or in part by or configured to implement the functionality of below-O/S trapping agent **104** of FIG. **1**, SVMM security agent **217** or SVMM **216** of FIG. **2**, firmware security agents **440**, **442**, PC firmware security agent **444**, or below-O/S system agent **450** of FIG. **4**, firmware security agent **516** of FIG. **5**, microcode security agent **708** of FIG. **7**, below-O/S trapping agent **920** of FIG. **9**, below-O/S security agent **1220** of FIG. **12**, and/or any combination thereof. In-O/S security agent **1518** may be implemented wholly or in part by or configured to implement the functionality of in-O/S security agent **218**, in-O/S security agent **418** of FIG. **4**, in-O/S security agent **718** of FIG. **7**, in-O/S security agent **919** of FIG. **9**, in-O/S security agent **1219**, and/or any combination thereof. Storage **1526** may implemented wholly or in part by or configured to implement the functionality of storage **426** of FIG. **4**.

[0269] Security rules **1522** may be implemented by or configured to implement the functionality of security rules **114** of FIG. **1**, security rules **222** of FIG. **2**, security rules **434**, **436**, **438** of FIG. **4**, security rules **518** of FIG. **5**, or security rules **707**, **723** of FIG. **7**, security rules **908** of FIG. **9**, security rules **1208** of FIG. **12**, and/or any combination thereof. Security rules **1522** may be established in any suitable manner (e.g., policies set by a user of electronic device **1504**, policies set by an administrator of an enterprise including electronic device **1504**, policies set by a creator of below-O/S security agent **1516**, etc.). In some embodiments, below-O/S security agent **1516** may request and/or receive updates or modifications to security rules **1522** from protection server **202** via network **244** (e.g., on account of updates to malware definitions).

[0270] Below-O/S security agent **1516** may include memory tracking facility **1542**, storage tracking facility **1544**, and memory/storage security layer **1546**. Memory tracking facility **1542** may interface with memory **1508** to monitor access to memory **1508**. For example, memory tracking facility **1542** may be implemented wholly or in part by or configured to implement the functionality of below-O/S trapping agent **104** of FIG. **1**, SVMM security agent **217** or SVMM **216** of FIG. **2**, firmware security agent **442** of FIG. **4**, microcode security agent **708** of FIG. **7**, below-O/S security agent **920** of FIG. **9**, and/or below-O/S security agent **1220** of FIG. **12** in order to trap or trigger upon an attempted access by application **1510**, driver **1511**, and/or operating system **1512** to read, write, or execute a particular page in memory **1508** (e.g., as indicated by page table flags and/or bit flags). As another example, memory tracking facility **1542** may be implemented wholly or in part by or configured to implement the functionality of below-O/S security agent **712** and/or microcode security agent **708** in order to trap or trigger upon an attempted access by application **1510**, driver **1511**, and/or operating system **1512** to read, write, or execute a particular address in memory **1508**. Accordingly, memory tracking facility **1542** may track movements of content from one location to another location in memory **1508** (e.g., from one page to another or from one address to another) or movements

between memory **1508** and storage **1526** (e.g., in connection with a virtual memory context swap or loading of executable code from storage **1526**). In addition, memory tracking facility **1542** may store information regarding tracked movements in a log, list, cache, or other suitable data structure accessible by memory tracking facility **1542** and/or memory/storage security layer **1546**.

[0271] Storage tracking facility **1544** may interface with storage **1526** to monitor movements of content from one location to another location in storage **1526** or movements between memory **1508** and storage **1526**. For example, storage tracking facility **1544** may be implemented wholly or in part by or configured to implement the functionality of below-O/S trapping agent **104** of FIG. **1**, SVMM security agent **217** or SVMM **216** of FIG. **2**, firmware security agent **442** of FIG. **4**, microcode security agent **708** of FIG. **7**, below-O/S security agent **920** of FIG. **9**, and/or below-O/S security agent **1220** of FIG. **12** in order to trap or trigger upon an attempted access by application **1510**, driver **1511**, and/or operating system **1512** to read, write, or execute a particular sector in storage **1526**. As another example, storage tracking facility **1544** may be implemented wholly or in part by or configured to implement the functionality of below-O/S security agent **712** and/or microcode security agent **708** in order to trap or trigger upon an attempted access by application **1510**, driver **1511**, and/or operating system **1512** to read, write, or execute a particular address in storage **1526**. Accordingly, storage tracking facility **1544** may track movements of content from one location to another location in storage **1526** (e.g., from one sector to another or from one address to another) or movements between memory **1508** and storage **1526** (e.g., in connection with a virtual memory context swap or loading of executable code from storage **1526**).

[0272] In operation, memory/storage security layer **1546** may receive security rules **1522** and communicate security rules **1522** to memory tracking facility **1542** and storage tracking facility **1544**. Thus, monitoring by memory tracking facility **1542** and storage tracking facility **1544** may be based on security rules **1522**, which may indicate whether monitoring is enabled and/or identify which portions of memory **1508** and/or storage **1526** is to be monitored.

[0273] Memory tracking facility **1542** and storage tracking facility **1544** may notify memory/storage security layer **1546** of attempted accesses of memory **1508** and/or storage **1526** (e.g., attempted movements of content within memory **1508** or storage **1526** or between memory and storage **1526**). Memory/storage security layer **1546** may be implemented wholly or in part by or configured to implement the functionality of below-O/S trapping agent **104** of FIG. **1**, SVMM security agent **217** or SVMM **216** of FIG. **2**, firmware security agents **440**, **442**, PC firmware security agent **444**, or below-O/S system agent **450** of FIG. **4**, firmware security agent **516** of FIG. **5**, microcode security agent **708** of FIG. **7**, below-O/S trapping agent **920** of FIG. **9**, below-O/S security agent of FIG. **12**, and/or any combination thereof. Memory/storage security layer **1546** may analyze the attempted accesses of memory **1508** and/or storage **1526** reported by memory tracking facility **1542** and/or storage tracking facility **1544** in accordance with security rules **1522** and/or application assets **1548** to determine if such attempted accesses are indicative of a malware attack, as described in greater detail below. In some embodiments, memory/storage security layer **1546** may store to memory **1508** and/or storage **1526** a log, list, or other indication of accesses reported by memory tracking facility **1542** and storage tracking facility **1544** as indicated by activities **1532** and activities **1534** of FIG. **15**. Thus, in addition to analyzing individual attempted accesses to memory **1508** and/or storage **1526**, memory/storage security layer **1546** may analyze a history of activities embodied in activities **1532** and/or activities **1534** in light of security rules **1522** to determine if a historical behavior of accesses indicates the presence of malware.

[0274] In a particular embodiment, memory/storage security layer **1546** may be implemented wholly or in part by or configured to implement the functionality of SVMM **216** of FIG. **2**, memory tracking facility **1542** may be implemented wholly or in part by or configured to implement the functionality of microcode security agent **708** of FIG. **7**, and storage tracking facility **1544** may be implemented wholly or in part by or configured to implement the functionality of firmware security agent **442** of FIG. **4**. In such embodiments, memory tracking facility **1542** may trap upon particular memory accesses and storage tracking facility **1544** may trap upon particular storage accesses, and each may notify memory/storage security layer **1546** of such trapped events. Memory/storage security layer **1546** may then analyze individual attempted accesses to memory and/or storage, and/or analyze a history of activities in light of security rules **1522** to determine if a historical behavior of accesses indicates the presence of malware.

[0275] In another particular embodiment, each of memory/storage security layer **1546**, memory tracking facility **1542**, and storage tracking facility **1544** may be all implemented wholly or in part by or configured to implement the functionality of a single SVMM **216** of FIG. **2**. In such an embodiment, SVMM **216** may trap upon particular memory accesses, trap upon particular storage accesses, and analyze individual attempted accesses to memory and/or storage, and/or analyze a history of activities in light of security rules **1522** to determine if a historical behavior of accesses indicates the presence of malware.

[0276] Application assets **1548** for application **1510**, driver **1511**, operating system **1512**, and/or another entity may represent a map, table, list, and/or other data structure indicative of how such entity and its components are resident within memory **1508** and/or storage **1526**. Application assets **1548** may identify portions of memory **1508** and/or storage **1526** to which an entity may be stored (e.g., memory page, memory address range, disk sector, disk address rank, etc.). As described above, based on application assets **1548** and/or security rules **1522**, memory/storage security agent **1516** may determine if notifications from memory tracking facility **1542** and/or storage tracking facility **1544** regarding attempted accesses of memory **1508** and/or storage **1526** are indicative of a malware attack. For example, in embodiments in which application **1510** is a portable executable file, application assets **1548** may identify portions of application **1510** stored in memory **1508** and/or storage **1526** that comprise executable code of application **1510** and/or identify portions of application **1510** stored in memory **1508** and/or storage **1526** that comprise data of application **1510**, including locations of memory **1508** and/or storage **1526** in which components of application **1510** are stored. Security rules **1522** may dictate that for such an example of application **1510**, write accesses originating from programs other than application **1510** to the portions of memory **1508** and/or storage **1526** that comprise executable code of application **1510** indicate a malware attack. In addition or alternatively, security rules **1522** may

dictate that for such an example of application **1510**, read or write accesses originating from programs other than application **1510** to the portions of memory **1508** and/or storage **1526** that comprise data of application **1510** indicate a malware attack.

[0277] As another example, in embodiments in which application **1510** is a word processing program, application assets **1548** may identify portions of application **1510** stored in memory **1508** and/or storage **1526** that comprise executable code of application **1510**, identify portions of application **1510** stored in memory **1508** and/or storage **1526** that comprise scripts, images, formatted text, notes, and other data of application **1510**, including locations of memory **1508** and/or storage **1526** in which components of application **1510** are stored. Security rules **1522** may dictate that for such an example of application **1510**, read or write accesses originating from a particular set of programs other than application **1510** to the portions of memory **1508** and/or storage **1526** that comprise data of application **1510** may be allowed (e.g., accesses originating from an operating system, anti-malware application, etc.), and access by programs other than the particular set of programs may indicate a malware attack.

[0278] Application assets **1548** may be created or defined by a creator of an application **1510**, driver **1511**, operating system **1512**, and/or other program (e.g., the application vendor, programmer, or creator), by a user of electronic device **1504**, by an administrator of an enterprise including electronic device **1504**, by a creator of below-O/S security agent **1516**, and/or another suitable individual. In some embodiments, application assets **1548** may, for a program, include relationships between the on-storage structure of the program and in-memory structure of the program (e.g., a mapping between components of the program in memory **1508** and in storage **1526**).

[0279] In order to assemble application assets **1548**, in-O/S security agent **1518** and/or below-O/S security agent **1516** may use any number of suitable techniques. For example, in-O/S security agent **1518** and/or below-O/S security agent **1516** may collect information associated with virtual memory page swaps that may be generated by operating system **1512** in connection with virtual memory operations. For example, in Windows™, in-O/S security agent **1518** may access the Prototype Page Table Entry (PTE) and communicate such information to below-O/S security agent **1516**. In other embodiments, below-O/S security agent **1516** may generate a hash, fingerprint, or other unique identifier for pages in memory **1508** and/or sectors **1526** on disk anytime an access is performed, and maintain a cache of such identifiers (e.g., such cache to be stored in memory **1508** and/or storage **1526**). In such scenario, below-O/S security agent **1516** may apply a simple comparison to determine which sector of storage **1526** is loaded in which page of memory **1508**, and vice versa. Such mapping may allow for security agent **1516** and/or **1518** to track the locations of particular information of entities in memory **1508** and/or storage **1526**.

[0280] Because the monitoring and analysis performed by memory/storage security layer **1546**, memory tracking facility **1542**, and/or storage tracking facility **1544** may consume a significant portion of the processing resources of electronic device **1504** if applied to all accesses of memory **1508** and storage **1526**, monitoring and analysis of memory **1508** and storage **1526** may be enabled only in particular defined situations. For example, in some embodiments, security rules **1522** may provide that memory tracking facility **1542** and/or storage tracking facility **1544** monitor only particular portions of memory **1508** and/or storage **1526** (e.g., those comprising operating systems, or critical drivers or applications). As another example, in the same or alternative embodiments, security rules **1522** may provide that memory tracking facility **1542** and/or storage tracking facility **1544** monitor a program in a particular portion of memory **1508** and/or storage **1526** if other indications show that the program is suspicious and/or other indications show that a malware attack may have occurred. As a further example, memory tracking facility **1542** and/or storage tracking facility **1544** may forgo memory trapping and storage trapping except when content is loaded from memory **1508** to storage **1526** or vice versa, as in the case of the virtual memory context swap or loading of executable code from storage **1526**.

[0281] In operation, as mentioned above, memory/storage security layer **1546** may secure memory **1508** and/or storage **1526** by analyzing reported accesses to memory **1508** and/or storage **1526** in light of security rules **1522** and/or application assets **1548**. After receiving notification of an attempted access to memory **1508** and/or storage **1526**, memory/storage security layer **1546** may determine the identity of the entity (e.g., operating system **1512**, driver **1511**, or application **1510**) requesting the attempted access. For example, in-O/S security agent **1518** may gather contextual information from operating system **1512** relating to a requesting entity of a particular memory **1508** and/or storage request **1526** and communicate such information to memory/storage security layer **1546**. In addition, memory/storage security layer **1546** may verify the identity of the requesting entity and determine whether the entity has been compromised by malware (e.g., by comparing a map or hash for the entity stored in memory to a known, expected map or hash for the entity or scanning the entity as stored in memory for presence of malware). Furthermore memory/storage security layer **1546** may determine whether the entity is authorized to make the request (e.g., a determination based on security rules **1522** and/or application assets **1548** whether the entity is authorized to access the specific portion of memory **1508** or storage **1526**). Moreover, memory/storage security layer **1546** may scan the content related to the attempted access (e.g., data or executable code being read, written, or executed) to determine whether the content contains malware. Also, memory/storage security layer **1546** may determine if a behavioral analysis of a history of accesses (e.g., as stored in activities **1532** and/or activities **1534**) indicates a presence of malware (e.g., attempted accesses of protected portions of O/S **1512** by unauthorized entities). Memory/storage security layer **1546** may take corrective action if the attempted access is determined to be malware-related. Corrective action may include preventing the attempted access, terminating the requesting entity, repairing the requesting entity, communicating occurrence of a malware-related event to protection server **202**, and/or any other suitable action.

[0282] As a specific example, in response to a request to a particular sector of storage **1526** (as indicated by a notification from storage tracking facility **1544**), memory/storage security layer **1546** may determine whether the particular sector is to be accessed based at least on security rules **1522**. In addition, memory/storage security layer **1546** may scan content related to the attempted access (e.g., data or executable code to be read, written, or executed in connection with the attempted access) to determine whether the content is free from potential malware infections. Furthermore, memory/

storage security layer **1546** may, based at least on security rules **1522**, determine whether an entity requesting the attempted access is authorized to access the particular sector. If such determinations indicate the attempted access is not malware-related, memory/storage security layer **1546** may permit the attempted access.

[0283] As another specific example, in response to a request to a particular page of memory (as indicated by a notification from memory tracking facility **1542**), memory/storage security layer **1546** may scan content related to the attempted access (e.g., data or executable code to be read, written, or executed in connection with the attempted access) to determine whether the content is free from potential malware infections. In addition, memory/storage security layer **1546** may, based at least on security rules **1522**, determine whether an entity requesting the attempted access is authorized to access the particular page. Furthermore, if the attempted access is a transfer from storage **1526** to memory **1508**, memory/storage security layer **1546** may, based at least on security rules **1522**, determine if the particular portion of storage **1526** from which the content is to be transferred is a trusted source. If such determinations indicate the attempted access is not malware-related, memory/storage security layer **1546** may permit the attempted access.

[0284] In addition, security rules **1522** and protection applied to a particular portion of memory **1508** or storage **1526** may be applied transitively as content is transferred between memory **1508** and storage **1526**, between different portions of memory **1508**, or between different portions of storage **1526**. Thus, for example, if a particular set of security rules **1522** apply to content in a specific portion of memory **1508**, upon a transfer of such content to another portion of memory **1508** or to storage **1526**, memory/storage security layer **1546** may update security rules **1522** to apply to the destination portion of memory **1508** or storage **1526**.

[0285] FIG. **16** is an example embodiment of a method **1600** for securing memory and storage of an electronic device. In step **1605**, a memory/storage security layer may communicate security rules to a memory tracking facility and a storage tracking facility. Because the systems and methods disclosed herein for protection of memory and storage from malware may consume significant processor, memory, and/or other resources, it may be desirable to only employ such systems and methods only when a particular location of memory or storage may be particularly susceptible to malware attacks. A portion of memory or storage may be susceptible to malware attack if, for example, it includes a portion of an operating system or a security application, or if previous indication of attack has been seen or detected on the electronic device.

[0286] In step **1610**, the memory tracking facility and the storage tracking facility may monitor accesses in accordance with security rules. To monitor, memory tracking facility and the storage tracking facility may trap or trigger upon attempted accesses (e.g., attempted reads, writes, or executions) to particular portions of the memory or the storage identified by the security rules received from the memory/storage security layer.

[0287] In step **1615**, memory tracking facility and/or the storage tracking facility may communicate to the memory/storage security layer notifications of attempted accesses to the memory and/or storage.

[0288] In step **1620**, the memory/storage security layer may determine the identity of the entity (e.g., operating system, driver, or application) requesting the attempted access identified in a notification to the memory/storage security layer. For example, an in-O/S security agent in communication with memory/storage security layer may gather contextual information from an operating system relating to a requesting entity of a particular memory and/or storage request and communicate such information to the memory/storage security layer.

[0289] In step **1625**, the memory/storage security layer may verify the identity of the requesting entity and determine whether the entity has been compromised by malware. For example, memory/storage security layer may compare a map or hash for the entity stored in memory to a known, expected map or hash for the entity. As another example, memory/storage security layer may scan the entity as stored in memory for presence of malware.

[0290] In step **1630**, the memory/storage security layer may determine whether the entity is authorized to make the request. For example, the memory/storage security layer may consult security rules and/or application assets to determine whether the entity is authorized to access a specific portion of memory **1508** or storage **1526**. In step **1635**, the memory/storage security layer may analyze content (e.g., data or executable code being read, written, or executed) associated with the attempted access. For example, the memory/storage security layer may scan the content related to the attempted access to determine whether the content contains malware.

[0291] In step **1640**, the memory/storage security layer may analyze a history of accesses to memory and/or storage. Such history may be stored as log or list in a memory and/or storage of an electronic device. Such analysis may include a behavioral analysis of the history of accesses to the memory and/or storage to determine if the history indicates a presence of malware.

[0292] In step **1645**, the memory/storage security layer may determine (e.g., based on the analyses and determinations of one or more of steps **1620**-**1640**), whether the attempted access to memory and/or storage reported by the memory tracking facility and/or the storage tracking facility indicates that the attempted access is affected by malware. In addition, if the memory/storage security layer determines the modified content was affected by malware-like behavior, the memory/storage security layer may take corrective action (e.g., action to remove, quarantine, and/or otherwise neutralize the malware). In addition, in some embodiments, the memory/storage security layer may communicate information (e.g., forensic information) regarding occurrence of malware-like behavior to a protection server.

[0293] In step **1650**, the memory/storage security layer may add notification of the access to a log or list of accesses stored on a memory and/or storage of an electronic device. To perform behavioral analysis of a history of accesses, the memory/storage security layer may later access the stored log or list. After completion of step **1650**, method **1600** may return again to step **1605**.

[0294] Although FIGS. **3**, **6**, **8**, **11**, **14**, and **16** disclose a particular number of steps to be taken with respect to example methods **300**, **600**, **800**, **1100**, **1400**, and **1600**, methods **300**, **600**, **800**, **1100**, **1400**, and **1600** may be executed with more or fewer steps than those depicted in FIGS. **3**, **6**, **8**, **11**, **14**, and **16**. In addition, although FIGS. **3**, **6**, **8**, **11**, **14**, and **16** disclose a certain order of steps to be taken with respect to methods **300**, **600**, **800**, **1100**, **1400**, and **1600**, the steps comprising these methods may be completed in any suitable order. Fur-

thermore, some or all steps of methods **300**, **600**, **800**, **1100**, **1400**, and **1600** may be combined with steps from other methods of methods **300**, **600**, **800**, **1100**, **1400**, and **1600**.

[0295] Methods **300**, **600**, **800**, **1100**, **1400**, and **1600** may be implemented using the systems of FIGS. **1-2**, **4-5**, **7**, **9**, **12**, **13**, and **15**. In certain embodiments, methods **300**, **600**, **800**, **1100**, **1400**, and **1600** may be implemented partially or fully in software embodied in computer-readable media.

[0296] For the purposes of this disclosure, computer-readable media may include any instrumentality or aggregation of instrumentalities that may retain data and/or instructions for a period of time. Computer-readable media may include, without limitation, storage media such as a direct access storage device (e.g., a hard disk drive or floppy disk), a sequential access storage device (e.g., a tape disk drive), compact disk, CD-ROM, DVD, random access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), and/or flash memory; as well as non-transitory communications media; and/or any combination of the foregoing.

[0297] One or more of systems **100**, **200**, **400**, **500**, **700**, **900**, **1200**, **1300**, and **1500** may be combined with other portions of systems **100**, **200**, **400**, **500**, **700**, **900**, **1200**, **1300**, and **1500**.

[0298] Although the present disclosure has been described in detail, it should be understood that various changes, substitutions, and alterations can be made hereto without departing from the spirit and the scope of the disclosure as defined by the appended claims.

What is claimed is:

1. A method for securing an electronic device, comprising:

accessing one or more security rules to determine a criteria by which an attempted access involving a transfer of content between memory and storage of an electronic device will be trapped;

if the criteria is met, trapping, at a level below all of the operating systems of the electronic device accessing a memory or a storage of an electronic device, attempted access of data between the memory and the storage of the electronic device; and

analyzing, at a level below all of the operating systems of the electronic device accessing the memory or the storage of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware.

2. The method of claim **1**, wherein analyzing information associated with the attempted access to determine if the attempted access was affected by malware comprises determining an identity of an entity requesting the attempted access.

3. The method of claim **2**, wherein analyzing information associated with the attempted access to determine if the attempted access was affected by malware further comprises determining if the entity has been affected by malware.

4. The method of claim **2**, wherein analyzing information associated with the attempted access to determine if the attempted access was affected by malware further comprises determining if the entity is authorized to request the attempted access.

5. The method of claim **1**, wherein analyzing information associated with the attempted access to determine if the attempted access was affected by malware further comprises analyzing content associated with the attempted access to determine if the content has been affected by malware.

6. The method of claim **1**, further comprising storing a record of the attempted access in a log of previous attempted accesses.

7. The method of claim **1**, wherein the criteria defines a particular portion of memory for which the attempted access to the particular portion of memory will be trapped.

8. The method of claim **1**, wherein the criteria defines a particular portion of storage for which the attempted access to the particular portion of storage will be trapped.

9. The method of claim **1**, the attempted access comprising a transfer of content from the storage to the memory in connection with loading of executable code from the storage.

10. The method of claim **1**, the attempted access comprising a transfer of content from the memory to the storage in connection with a virtual memory page swap.

11. A system for securing an electronic device, comprising:

a memory;

a processor;

one or more operating systems residing in the memory for execution by the processor;

a security agent configured to execute on the electronic device at a level below all of the operating systems of the electronic device accessing the memory or a storage of the electronic device, the security agent configured to:

access one or more security rules to determine a criteria by which an attempted access involving a transfer of content between the memory and the storage of an electronic device will be trapped;

if the criteria is met, trap, at a level below all of the operating systems of the electronic device, attempted access of data between memory and storage of an electronic device; and

analyze, at a level below all of the operating systems of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware.

12. The system of claim **11**, the security agent further configured to analyze information associated with the attempted access to determine if the attempted access was affected by malware by determining an identity of an entity requesting the attempted access.

13. The system of claim **12**, the security agent further configured to analyze information associated with the attempted access to determine if the attempted access was affected by malware by determining if the entity has been affected by malware.

14. The system of claim **12**, the security agent further configured to analyze information associated with the attempted access to determine if the attempted access was affected by malware by determining if the entity is authorized to request the attempted access.

15. The system of claim **11**, the security agent further configured to analyze information associated with the attempted access to determine if the attempted access was affected by malware by analyzing content associated with the attempted access to determine if the content has been affected by malware.

16. The system of claim **11**, the security agent further configured to store a record of the attempted access in a log of previous attempted accesses.

17. The system of claim **11**, wherein the criteria defines a particular portion of memory for which the attempted access to the particular portion of memory will be trapped.

18. The system of claim **11**, wherein the criteria defines a particular portion of storage for which the attempted access to the particular portion of storage will be trapped.

19. The system of claim **11**, the attempted access comprising a transfer of content from the storage to the memory in connection with loading of executable code from the storage.

20. The system of claim **11**, the attempted access comprising a transfer of content from the memory to the storage in connection with a virtual memory page swap.

21. An article of manufacture, comprising:

a computer readable medium;

computer-executable instructions carried on the computer readable medium, the instructions readable by a processor, the instructions, when executed, for causing the processor to, at a level below all of the operating systems of the electronic device accessing a memory or a storage of the electronic device:

access one or more security rules to determine a criteria by which an attempted access involving a transfer of content between the memory and the storage of an electronic device will be trapped;

if the criteria is met, trap, at a level below all of the operating systems of the electronic device, attempted access of data between memory and storage of an electronic device; and

analyze, at a level below all of the operating systems of the electronic device, information associated with the attempted access to determine if the attempted access was affected by malware.

22. The article of claim **21**, the processor further caused to analyze information associated with the attempted access to determine if the attempted access was affected by malware by determining an identity of an entity requesting the attempted access.

23. The article of claim **22**, the processor further caused to analyze information associated with the attempted access to determine if the attempted access was affected by malware by determining if the entity has been affected by malware.

24. The article of claim **22**, the processor further caused to analyze information associated with the attempted access to determine if the attempted access was affected by malware by determining if the entity is authorized to request the attempted access.

25. The article of claim **21**, the processor further caused to analyze information associated with the attempted access to determine if the attempted access was affected by malware by analyzing content associated with the attempted access to determine if the content has been affected by malware.

26. The article of claim **21**, the processor further caused to store a record of the attempted access in a log of previous attempted accesses.

27. The article of claim **21**, wherein the criteria defines a particular portion of memory for which the attempted access to the particular portion of memory will be trapped.

28. The article of claim **21**, wherein the criteria defines a particular portion of storage for which the attempted access to the particular portion of storage will be trapped.

29. The article of claim **21**, the attempted access comprising a transfer of content from the storage to the memory in connection with loading of executable code from the storage.

30. The article of claim **21**, the attempted access comprising a transfer of content from the memory to the storage in connection with a virtual memory page swap.

* * * * *