Patents 7,634354

Location signposting and orientation

Abstract

A signposting and orientation technology is presented. This technology employs signposts superimposed on map images in order to convey otherwise undisplayable information on a map image. With signposting, zoomed-in maps can convey relationships between items on the map image, even though some of those item are not directly displayed on the map images. For example, a signpost can convey the distance between an anchoring object of reference and an item that is some distance and direction away from the object. Any relationships between objects and/or items can be dynamically maintained even though both the objects and item are moving about a map image. Additionally, orientation marks can be used in conjunction with signposts to orient users of the technology. Orientation marks may employ directional vectors, beginning at with the object of reference and ending with the orientation mark, whether the mark is celestial in nature or otherwise.

Images (15)



Classifications

G01C21/20 Instruments for performing navigational calculations

View 3 more classifications

US7634354B2

United States

Download PDF Find Prior Art Similar

Inventor: Ivo William Salmre

Current Assignee : Microsoft Technology Licensing LLC

Worldwide applications

2005 US 2006 WO CN EP KR

Application US11/217,638 events

2005-08-31	Application filed by Microsoft Corp
2005-08-31	Priority to US11/217,638
2007-03-01	Publication of US20070050129A1
2009-12-15	Publication of US7634354B2
2009-12-15	Application granted
Status	Active
2027-03-17	Adjusted expiration

Show all events

Info: Patent citations (54), Non-patent citations (20), Cited by (80), Legal events, Similar documents, Priority and Related Applications

External links: USPTO, USPTO PatentCenter, USPTO Assignment, Espacenet, Global Dossier, Discuss

Claims (16)

Hide Dependent

1. A computer-implemented method for providing location and orientation information when displayed on a mobile device, comprising:

using a map in the mobile device;

displaying a viewed portion of the map in a display screen of the mobile device; and

if an item on the map is outside the viewed portion of the map, then displaying a signpost for the item superimposed on the viewed portion of the map, wherein the item is anchored to an object of reference that is configured to change dynamically upon a request.

2. The computer-implemented method of claim 1, further comprising displaying an orientation mark, wherein the orientation mark is anchored to the object of reference.

3. The computer-implemented method of claim 1, wherein a vector appears between the object of reference and at least one of (a) the item and (b) an orientation mark.

4. The computer-implemented method of claim 2, wherein the orientation mark is a celestial body.

5. The computer-implemented method of claim 2, wherein the orientation mark is a grounded body.

6. The computer-implemented method of claim 1, wherein the map is any arbitrary map configured to be displayed in the mobile device obviating the need to be a pre-stored map of the mobile device.

7. The computer-implemented method of claim 1, wherein the signpost comprises a name of the item.

8. The computer-implemented method of claim 1, wherein the signpost comprises a distance between the item and the object of reference.

9. The computer-implemented method of claim 1, wherein the signpost comprises an orientation reference substantially corresponding to a direction from the object of reference to the item.

10. The computer-implemented method of claim 1, wherein at least one of (a) the item and (b) the object of reference is stationary on the map.

11. The computer-implemented method of claim 1, wherein at least one of (a) the item and (b) the object of reference is moving about the map.

12. The computer-implemented method of claim 1, wherein the request is made by a developer interacting with an application programming interface for building a location and orientation information application.

13. The computer-implemented method of claim 1, wherein the request is made by a user of the mobile device.

14. The computer-implemented method of claim 1, wherein at least one of (a) the object of reference and (b) the item is substantially in the center of the viewed portion of the map.

15. The computer-implemented method of claim 1, wherein at least one of (a) the object of reference and (b) the item is away from the center of the viewed portion of the map.

16. The computer-implemented method of claim 1, wherein the mobile device is a cell phone.

Description

CROSS-REFERENCE TO RELATED APPLICATIONS

This application relates to U.S. application Ser. No. 10/998,081 filed Nov. 26, 2004, entitled "LOCATION AWARE MOBILE-DEVICE SOFTWARE DEVELOPMENT."

BACKGROUND

Mapping and location determination technology plays as increasing role in mobile device software applications. The ability to display dynamic maps on mobile devices and to draw spatial relationships between objects onto arbitrary maps (e.g. street maps, topographical maps, transportation system maps, indoor maps) is important to facilitate their effective usage. There are several conflicting priorities that make the effective use of maps on mobile devices difficult.

For example, there is a need for fitting high-resolution local maps and distant data on the same map. Usually users want zoomed in maps that show their immediate vicinity, or the immediate vicinity of an item they are interested in (e.g. is there parking spot near the movie theater I am going to?). At the same time, users are often interested in the relationship between the location they are looking at and items that do not fit on the current map (e.g. in what direction and how far is the closest exit to the shopping mall I am standing in?—with the current map showing all the stores in my immediate vicinity).

This problem is exacerbated because mobile devices have much smaller screen surface areas than most desktop/laptop computers and paper maps, and also have more limited input mechanisms for navigating maps. The problem exists even on a desktops which have relatively large screens and rich mouse (with buttons, roller wheels, drag/drop capabilities) and keyboard inputs, but extremely difficult on a mobile phone with its screen being 5-10% the size of a desktop screen and having only a simple keypad (or sometime touch screen) for input.

Another example of the aforementioned conflicting priorities involves the need for orientation of maps displayed on mobile devices. Mobile devices can display maps on their screens, however it is problematic for end user's to understand which way they must orientate the maps. As above, this is greatly exacerbated by the relatively small screens of the devices. The utility of having a mobile device near-instantly display a convenient map is largely defeated if the device's user must walk around trying to look at street signs and other near-range markers in an effort to orientate themselves. For a stationary desktop computer people make abstract decisions about maps so the user's physical orientation to the map is not particularly important. On mobile devices people want to make instantaneous decisions and physically orientate themselves and the digital map just as they would a map printed on paper. They will want to turn their bodies and point the mobile devices in orientations where the maps match their surroundings.

Finally, a third example of the conflicting priorities is based on the need for orientation of others based on map information. A user of a mobile device may need to guide remote individuals and give them orientation information. It is difficult and frustrating to do this if the person giving these directions can not provide the other individual with useful distance and orientation cues. Allowing the viewer of the map to easily "put themselves in the shoes of others" and relate the directions they give them to the remote users' surroundings (e.g. "Do you see the Eiffel tower in the distance in front of you? OK. Walk 4 blocks and keep the Eiffel tower on your left.)

These are but only three examples among a myriad of situations that arise when trying to display dynamic maps on mobile devices and to draw spatial relationships between objects onto arbitrary maps. Software developers building mobile applications for both indoor and outdoor usage (as well as hybrid usage indoors and outdoors) need to be able to provide the applications' users with easy to use and highly accurate distance and orientation information.

SUMMARY

The various aspects of signposting and orientation technology discussed herein provide an applications' users and developers with easy to use and highly accurate distance and orientation data and tools, respectively. For example in one aspect, location and orientation is used for signposting information that could not otherwise be conveyed in a mobile device. Items that cannot be displayed on a mobile device display are signposted. These items can include people, places, or just about any object of interest. Such signposts contain a variety of information, including but not limited to, the distance between an object of reference and the item in question, the general direction of the item to the object, and even the name of the item.

In another aspect of signposting, signposts are dynamically updated when either the object or the item moves about the map. Moreover, the object can serve to anchor the item and other items of interest, thus keeping track of items that are not in the immediate view of a mobile device display. Anchoring can be dynamically changed depending on user or developer input. In the case of the user, that input may be made via the mobile device; in the case of the developer, a programming framework can be used to develop a desired signposting (and orientation) program. The framework allows signposting on any existing or dynamically rendered map; easy and dynamic designation of the anchor point form which signposts are measured and rendered in relation to; and easy and dynamic selection of any number of objects for signposting.

In one aspect of orientation, reference marks can be superimposed on a map (in addition to signposts) in order to help mobile device user to orient themselves. Various reference mark can be used, whether the sun, the moon, or the stars. Ground-and air-based marks can also be used, such a monuments, mountains, buildings, aircraft and the like. These marks can either be moving or stationary. Additionally, vectors from an object of reference to a reference mark can be used to help a user align with the proper geographical heading.

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing Summary, as well as the following Detailed Description, is better understood when read in conjunction with the appended drawings. In order to illustrate the present disclosure, various aspects of the disclosure are shown. However, the disclosure is not limited to the specific aspects discussed. The following figures are included:

FIG. 1 illustrates typical areas of interest to a user on a map image;

FIG. 2A illustrates a typical limited portion of a map image;

FIG. 2B uses signposting to help with the knowledge of relatively located marks and orientation of a user;

FIG. 3 illustrates exemplary orientation marks;

FIG. 4 illustrates at least two items moving about an image map;

FIG. 5A illustrates what happens if a first user is trying to track the movement of a second user via a mobile device display screen;

FIG. 5B illustrates signposting that keeps track of relationships between moving items on a map image display screen;

FIG. 6 illustrates that the center of attention or display can also be changed while maintaining signposted items relationships;

FIG. 7A illustrates an indoor signposting scenario;

FIG. 7B illustrates, in relation to FIG. 7A, that relationships between items can dynamically change and be updated;

FIG. 8 illustrates the off-center aspect of items displayed on a typical display;

FIG. 9 presents a flow chart that shows in block form how one, merely exemplary and in no way dispositive, implementation might be set-up;

FIG. 10 presents in more detail on signposting information discussed with reference to FIG. 9;

FIG. 11 presents in more detail on orientation mark information discussed with reference to FIG. 9;

FIG. 12A presents in more detail on item of interest information discussed with reference to FIG. 9;

FIG. 12B presents in more detail on object of reference information discussed with reference to FIG. 9;

FIG. 13 illustrates a flexible programming framework for the signposting and orientation technology;

FIG. 14 illustrates an exemplary computing environment where aspects of the disclosed technology can be implemented.

DETAILED DESCRIPTION

Overview

Signposting and orientation technology is presented. At the outset, a general description of signposting (for example, displaying information via a signpost for items that do not fit on a map image) and orientation information (for example, allowing users to orient themselves in a given environment) is presented. This general description is then fleshed out by focusing on the following aspects: directional vectors and orientation marks employed in unison with signposting; location signposting and orientation with stationary and moving items; dynamically changing the anchoring point (or center of attention) of signposted items; a varying environment for signposting and orientation (whether outdoor or indoor); centering of items on a given image map; various exemplary scenarios employing the technology; an exemplary implementation; a flexible programming framework; and finally a suitable computing environment.

Aspects of Location Signposting and Orientation

There are various aspects to location signposting and orientation. In one aspect, FIG. 1 illustrates typical areas of interest to a user on a map image **100**. For example, a map image **100** of the city of Paris is shown with the following areas of interest: The Arch De Triomphe **102**, the Eiffel Tower **104**, Notre Dame **106**, the Louvre **108**, and Montmare **110**. A typical user **112** (in the map image **100** referred to as "Jane") of the location signposting and orientation technology is located near the center of the map image **100**, near the Jardin des Tuileries.

The user **112**, when looking at a map image **100** in a mobile device, such as a cell phone or any other device capable of displaying map images, is usually confined to seeing a very limited portion **200** of the map image **100**. This occurs because of the typical small size of the map image **100** that can be displayed in a mobile device.

Thus, in another aspect, FIG. 2A illustrates a typical limited portion **200** of the map image **100**. In this limited display **200**, only the user ("Jane") **112** can be seen and the other areas of interest cannot be fit unto the limited display **200** while maintaining the desired resolution. Thus, the Arch De Triomphe **102**, the Eiffel Tower **104**, Notre Dame **106**, the Louvre **108**, and Montmare **110** are no longer present in the limited image **200**, and as a result, the user **112** has a more difficult time knowing where these areas of interest are located with respect to the user **112**. A natural consequence of this is that the user **112** has a more difficult orienting himself or herself, and the displayed map is itself of limited use because while it displays zoomed in details it says nothing about important destinations the user cares about. Moreover, proper orientation lends support to signposting which helps a user to understand spatial relationship to off-map items.

In contrast to FIG. 2A, FIG. 2B uses signposting to help with the knowledge of relatively located landmarks (but not just landmarks, as will be discussed below) and orientation of the user **112**. Thus, in another aspect, signposts **204** are used in an enhanced map image **202** (enhanced to the limited image **200** of FIG. 2A) when the areas of interest (or alternatively, "items") are outside the limited digital map image **200**.

A typical signpost **204** is shown: it has the name of the landmark, such as the "Eiffel Tower" **206**, the distance **208** of the user **112** from the landmark, and an direction arrow **210** showing in which direction the user **112** should head to get to the landmark. In FIG. 2B, in one of the signposts **102**, the user **112** is 2.3 kilometers (km) from the Arch De Triomphe. To get to the Arch, the user **112** should be heading to the left. In other words, the user **112** should be heading due East, if the Map is oriented towards the North and the user **112** is facing North—but this is not required, since map orientation could vary (as could the orientation of the user **112**). This is just a simple example used herein for illustrative purposes, and those skilled in the art will readily recognize that the map orientation could easily be made to vary in directional orientation-and of course, the user orientation can vary almost constantly, as anyone (not even needing to be skilled in the art) can understand from personal life experience.

In FIG. 2B, with signposting in place, some of the areas of interest discussed with reference to FIG. 1 are shown in FIG. 2B in the following manner: the Arch De Triomphe **102** is due west and 2.3 km away from the user **112**; the Eiffel Tower **140** is 2.5 km southwest of the user **112**; the Louve **108** is 0.9 km southeast of the user **112**; and finally, Montmarte **110** is 2.5 km northeast of the user **112**.

Of course, these directional designations, such as “west” or “northeast”, etc., are merely exemplary, and other more accurate designation could be used such as “north by northeast” or “south by south east” and so on. Also alternative descriptions could be used such as “left,” “right,” “up,” “down,” “in the bottom left corner (of the screen)” and so on. The directional arrow **210** attempts to substantially indicate the direction the user **112** should be heading to get to the area of interest.

Moreover, the display of signposts can vary also. For example, supposing there are twenty items of interest on mobile device screen map image **202**, it would not be a good idea to display all twenty signposts—at least for readability purposes. Therefore, selected signposts can be displayed. For example, in FIG. 2B, only four signposts are displayed (signposts **102**, **104**, **108**, and **110**), even though the user **112** may have specified five areas of interest—as is shown in FIG. 1: areas **102**, **104**, **106**, **108**, and **110**). In comparison to FIG. 1, FIG. 2B omits showing a signpost to Notre Dame **106**. In short, the user **112** (or a developer using an interface to program this location signposting and orientation technology) can specify the display parameters, and assign them weights for display importance based on a variety of factors, such as, visibility, importance, closeness of distance, the desired density of signposts, and so on.

Likewise, it goes without saying that the information contained within the signposts can also be altered. The depicted signposts in FIG. 2B are merely exemplary. Thus, if for example, a user **112** wanted to fit in more information in a signpost he could easily do that. Thus, taking the Arch De Triomphe **102** signpost as an example, in addition to having the name, the distance, and the directional arrow, a user **112** or a developer could easily add a time display using a simple algorithm: The Arch De Triomphe is 2.3 km away, assuming a typical human walks 6.8 km per hour, the user should get to the Arch in about 30 minutes (distance divided by speed equals time, or, put another way: 2.3 km÷6.8 km per hr=30 minutes). Alternatively, miles instead of kilometers could be used, and so on. In short more or less information can be used depending on what is desired: if a lot of information is desirable to be displayed per signpost, fewer signposts will fit onto a screen.

Aspects of Directional Vectors and Orientation Marks in Unison with Signposting

Directional vectors and orientation marks may be used in unison with signposting in order to at least orient the user **112**. Thus, in another aspect, in FIG. 3, the user **112** is near the “Jardin des Tuileries” and sees on a display screen **300** that the Eiffel Tower is 2.5 km west-southwest of her position. Similarly, Notre Dame **106** is roughly southeast of her. However, the user **112** may have a problem figuring out how to align herself in the first place. She may not know which way is west-southwest.

Thus, orientation marks or “cues” may be used, such as the sun. Actually, any celestial body may be used, whether the sun, the moon, the stars (the kind visible at night, thus excluding the sun), etc. Likewise, ground-based marks can be used, such as the Eiffel Tower itself—which, interestingly enough, may be both an area of interest and an orientation mark.

In FIG. 3, the sun **308** is used as an orientation mark. The user **112** can align herself with the sun **308** and then walk towards, for example, the Eiffel Tower by keeping the sun on her northwest side (or to the upper left of her as she is walking). Helpfully, directional vectors **302**, **304**, and **306** are provided that allow the user **112** to align the display screen or map image therein **300** with the subject of interest, such as the sun, thus aligning an imaginary line from the user **112** to the sun **308** with the directional vector **302**. The directional vectors are not only available for the orientation marks **308** but also for the other signposts **104** and **106**. Thus, the Eiffer Tower signpost **104** has its own directional vector **302** anchored to the user **112**, and the Notre Dame signpost **106** has its own directional vector **306**. These directional vectors and orientation marks can be display or not displayed depending on the needs and desires of the user **112** or a developer coding a location signposting and orientation program.

Aspects of Location Signposting and Orientation with Stationary and Moving Items

Thus far, the target areas of interest, such as those displayed in FIG. 1, for instance, the Arch De Triomphe and the Eiffel Tower, were stationary. These areas of interest (in other words, “items” on a display screen of a map image) were in one place and the user **112** was moving toward them. However, any items (even all items) that are displayed on a map image, can be moving about the map image, whether inside the displayable boundaries or outside the boundaries. These items can maintain dynamic relationships, such as a distance relationship between one item and another item that is dynamically update as the item move, either towards each other or away from each other.

FIG. 4 illustrates at least two items moving about an image map **400**. A first user **402**, “Jane”, and a second user **404**, “Brian”. As the first user **402** or the second user **404** moves about, such a user may either enter into a display screen of a mobile device used by a user or go beyond such a display screen (in which case signposting is an option to keep track of the other user).

FIG. 5A illustrates what happens if a first user **404** is trying to track the movement of a second user **406** via a mobile device display screen **500**. In short, the second user **406** is not visible—for the reasons already discussed above, with reference to FIGS. 1, **2**A and **2**B. To remedy this problem, FIG. 5B illustrates signposting that keeps track of relationships between moving items on a map image display screen **502**. Thus, user one **404** is the object reference that anchors the second user **406** (although either user could be the anchor—as well as a third item, separate from the first two items—and neither item has to be in the center of the display screen **502**, that is, either item could be off-center) as the second user **406** moves about outside the display screen **502**.

However, user one **404** keeps track of user two **406** via signposting. As either of the users moves about, their relationships are dynamically updated. For instance, the distance between the two users is dynamically updated. In FIG. 5B, that distance is 2.2 km, as can be seen in the “Brian” (i.e. user two) signpost **506**. The signpost tells user one **404** that user two **406** is 2.2 km northeast of user one **406**. Likewise, stationary items on the display screen **502** are also tracked. The Eiffel Tower **508** is 3.1 km west by northwest from user one **404**, and Notre Dame is 1.2 km east by northeast from user two **404**. Of course, as user one **404** moves about, these latter distances are also dynamically updated.

Aspects of Dynamically Changing the Center of Attention of Signposted Items

Building on FIG. 5B, FIG. 6 illustrates that the center of attention (which can be an anchor point) or display can also be dynamically changed while maintaining signposted items relationships. Thus, in contrast to FIG. 5B where user one **404** is the center of attention (i.e. in the middle of the display screen **502**), now the second user is displayed preferentially near the center of the display screen **600**. Thus, now the signposts are calculated from the second user's **406** point of view. This means that user two **406** is now the anchor to any related items.

For example, user two **406**, or “Brian”, is 4.3 km away from the Eiffel Tower **608** and 1.2 km away from Notre Dame **610**. Although the signpost for the first user **404** is not shown in FIG. 6, this could be easily accomplished in the manner discussed with reference to FIG. 5B.

As will be readily appreciated by those skilled in the art, numerous aesthetic improvements could be made to the display **600** in FIG. 6. For example, in the current configuration, both signposts **608** and **610** are at the edge of the display **600**. However, one could easily move these signposts around, so that items further away, say, 100 km away appear on the edge of the screen, while those closer, say, 1 km away, appear close to the anchoring object of reference. Likewise, the size of any signpost could vary depending on the distance, as could the color—say, faded color for objects far away and bold, conspicuous color for those near (yet off the display screen **600**). There are many such touches that may be implemented to make the relationships displayed on the screen **600** more intelligible for any user.

Furthermore, the image maps used so far have been two dimensional (2-D) image maps, because such maps are easier to visualize and discuss. However, the aforementioned and following aspects are also applicable to three dimensional (3-D) maps. Thus, not only horizontal, i.e., x and y coordinate relationships (in a Cartesian sense) may be maintained via signposting and orientation, but also vertical or z coordinate relationships may also be maintained. Those skilled in the art will readily

NorthStar's Exhibit No. 2002, IPR2023-00934
Page 004

appreciate that for such 3-D signposts, merely more information would have to be displayed in the signposts. Thus, a signpost might display that the Eiffel Tower is not only 4.3 km away **608**, but also that to get there, user two **506** has to go uphill (or, additionally, climb 300.51 meters or 986 feet to get to the top of the tower). For the persnickety user, a signpost might even inform the user that the Eiffel tower changes in height by about 15 centimeters, depending on the temperature, thus there might be an extra, albeit small, climb in store for the user.

Aspects of a Varying Environment for Signposting and Orientation

The aspects of signposting and orientation technology discussed so far have been confined to an outside environment, but they could just as easily be used in an indoor environment (including transportation system environments). FIG. 7A illustrates an indoor signposting scenario. A user **704**, "Jane", is at the center of a mobile device display **700**, and the user **707** is 12 m (meters) away from the copier_X **706** and 28 m away from copier_C**1** **710**. Thus, if the user **704** wants to make copies, for instance, she can go the nearest copier, namely, copier_X **708**. Likewise, the user **704** is shown the distance of other individuals (a subspecies of "items") in the indoor environment. Thus, "Doug" **708** is located 10 m away from the user **704**, "Jane".

FIG. 7B illustrates, in relation to FIG. 7A, that relationships between items, such as the user **704**, the copiers **706** and **710**, and other individuals **708**, can dynamically change and be updated. Thus, in FIG. 7B, as the user **704** moves about the office, the distances change (other relationships may also change). Now, Copier_X **712** is 10 m away from the user **704** and Copier_C**1** is 29 m away from the user **704**. Interestingly, now that the user has come closer to other items on the display **702**, signposting is turned off. Thus, now "Doug" **709** fits in the display **708** and his signpost **708** is turned off. However, if the user wishes to do so, the signpost **708** can be kept turned on (or alternatively, with respect to FIG. 7A, even though "Doug" **709** maybe off screen his signpost **708** can be turned off anyway, especially if the user **704** is not interested in Doug's position).

Aspects of Centering of Items

The above discussion alluded to the notion that items do not have to be centered on any particular screen display. For example, with regard to FIG. 8, a display **800** has the same items as the previous figure, namely, FIG. 7B, however, the difference is that neither of the items are in the center **802** of the display **800** (the center **802** of the display **800** is indicated by a dashed circle). Thus, as "Jane" **704** moves closer to Copier_X **802**, now only 5 m away from her, as an item on the display **800**, she moves off center **802**. Likewise, her distance relationship to the other copier, Copier_C**1** **804**, has now increased to 34 m.

Various Exemplary Scenarios

The aforementioned technology may be used in various exemplary (i.e. sample) scenarios. For example, with regard to orientation, a user may be looking at a detailed street-map in a neighborhood of Paris he is not familiar with. His location is displayed on the map because his mobile device as global positioning (GPS) hardware. However, he is disoriented because the streets are windy and not well signposted. He's trying to find his way to "Le Petit Café" to meet some people. It may be night-time, but he can see the Eiffel tower several miles away. He would like to know the orientation of the Eiffel tower relative to the "zoomed in" map he's looking at. At the same time he wants the map to show the distance & orientation to "Le Petit Café". Based on the line or vectors on the map pointing to the Eiffel tower, he's able to physically orientate himself and the device. He sees that "Le Petit Café" is "up and to the left" about 2.5 km. Based on this information he's able to start his walking journey going in the right direction.

As hinted already above, the present technology also assists in orientating others, remote from their location. Again, using the same example of a user as above, the user is in Paris and receives a phone call from his friend Sue. Sue is supposed to meet him at "Le Petit Café" but is currently at the Notre Dame church. Based on this information, the user can place her on a map of Paris (at Notre Dame). (Alternately, if she had a device that supported it, she could have electronically sent the user her location). The user is able to look at her location on a detailed (i.e. zoomed-in) street map, but at the same time see her distance and orientation to other landmarks (e.g. to the Eiffel Tower, to the Louvre, the Pompidou museum), to the sun, which is shining brightly this day. He can also see her location relative to "Le Petit Café" which is where he's currently standing. Based on this information he's able to tell her which way to face (based on landmarks she can see, and also based on the sun, e.g. "the sun should be to your right"), and how far she should walk to come meet the user.

Furthermore, the aforementioned technology can assist in making location aware decisions, and pivoting orientation data, based on multiple locations. Again, focusing on the exemplary user, he's in London and speaking with a friend, Brian, on the phone who is somewhere several miles away. The user and Brian agree to meet for coffee, but have not decided on where yet to meet. The user is able to place both Brian and himself onto a map, and also bring up the locations of the coffee shops in the neighborhood. He's able to look at the coffee shops and see their relationship to himself and Brian. He's able also to see the locations of Tube stops (a.k.a subway stations) in the neighborhood. Very quickly he's able to visually pivot on several pieces of information: he can see his location and the coffee shops near him (displayed on the map if they are close, otherwise indicated by distance and direction with a signpost of they are off the map); he can see Brian's location and the coffee shops near him (displayed on the map if they are close, otherwise indicated by distance and direction with a signpost of they are off the map); he can pick a tube stop (quite possibly by switching rapidly from a street map to a tube schematic; both having appropriate signposts displayed on them as required), and see the coffee shops near it. He can see that there is a good coffee shop, "The Queen's Beans", near the "Notting Hill" station. The Notting Hill station however has four different exits on different street corners and can be confusing to navigate from. The user is able to choose the tube stop and see its distance to the coffee shop, and both its and the coffee shops orientation relative to the afternoon sun. He sees that the when exiting the tube stop it is necessary to walk three blocks with the "sun to his left" (north) to arrive at the coffee shop. He's able to relay this information to Brian, and they agree to meet there in 30 minutes.

Another scenario involves orientating oneself while hiking in the mountains. A user may be hiking in the mountains and have a GPS receiver with him. Friends of his have indicated a GPS location where they would like to meet that evening. The user can see Mount Rainer off in the distance but is interested in looking at a much more zoomed in map that shows 15 km of hiking trails. His electronic map is able to show him the zoomed in map with three directional signposts, one shows the direction and distance to the meeting point. The second shows the direction to Mt. Rainier. The third shows the direction to the sun. Based on these cues, he is easily able to orientate himself and head to meet his friends.

In addition to these outdoor scenarios, there are various indoor scenarios. For example, a user may ask herself where there are multiple exits to a building relative to where she is standing? Which of these exits is closest? If the user is facing the elevators, which way does she need to spatially orientate her device in order to make sense of the map? If the user can see the sun outside the window of the office she standing in, what way should she orientate her device relative to this in order to have a correctly orientated map of the building she's in? If the user is speaking to someone on the phone in another building, and they have sent their indoor location to her, what exit of their building should she tell them to go out of to meet her outside? All of these questions can easily answered by the signposting and orientation technology.

It should be noted, that all of these features discussed in the exemplary scenarios above, such as the use of GPS technology in conjunction with the present signposting and orientation technology, is merely exemplary discussion but not limited to such technologies. Other equivalent and complementary technologies may also be employed, as will be appreciated by those skilled in the art.

Aspects of an Exemplary Implementation

There are numerous implementations of the above discussed aspects. For example, FIG. 9 presents a flow chart that shows in block form how one, merely exemplary and in no way dispositive, implementation might be set-up. Thus, at block **900** a map image is acquired. The image may be acquired from a pre-stored source in the

mobile device that displays the image, or from an outside source, whether some kind of memory device or a result of downloading (either from some map source or even from another user).

Block **901** addresses the notion that the acquired map **900** can be any arbitrary map image derived from any source—as mentioned above. Thus, the maps that are displayed on a screen of a mobile device may have various resolutions and be stored in various formats. So long as signposting and orientation information can be superimposed on the map image, any arbitrary map will do.

At block **902**, at least a portion of the acquired or dynamically rendered (by a rendering engine) map image is displayed on the mobile device. Since mobile devices, such as cell phones, pagers, or personal digital assistants, typically have small display screens, the entire map image cannot be displayed (although, it should be noted that if the display is big enough or the map small enough, the entire map image or a substantial portion thereof could potentially be displayed). Thus, a portion of the map is displayed, where that portion may have several items, such a people or landmarks, displayed on it.

At block **904**, such an item is displayed on the map image. In one aspect, it can be superimposed on the map image, such that the item's relation to the surrounding geography can be seen. Also, as mentioned, multiple items, either those moving about the map image or those that are stationary, can be displayed. In another aspect, one item, the anchoring item with respect to other items on the map image, the so called "object of reference", can be displayed in the center of the map image, and any item that do not fit on the display can be signposted. It goes without saying, that the more a user of a mobile device zooms in on any given map, the more signposts will appear (if so desired), since signposts attempt to remedy at least the problem of maintaining a map at a certain level of particularity while maintaining information regarding relationships about items that could not fit on a display at that level of particularity.

At block **906**, once the item of interest is displayed, an object of reference to anchor that item is established. Just to underscore that FIG. 9 is a mere exemplary implementation of the aspects discussed so far, the anchoring object of reference could be established first and then the item could be displayed (i.e. blocks **904** and **906** could switch temporal order). However, in this particular implementation, once the item is displayed it is anchored to an object of reference. This object can be located anywhere on the display screen (it can even be located outside the screen, if so desired, in which case it would have a signpost to it—again, if a signpost were desired in the first place). The anchoring of the item to the object allows for signposting to maintain certain relationships between the item and the object. For example, a distance relationship and a directional relationship can be displayed. Interestingly, in one aspect, the anchoring is still maintained even though items and objects move about, or appear of disappear from the display screen.

At block **910**, one the anchoring is complete, a decision is made whether the anchored item, for example, its on the display screen of the mobile device. Although, any one skilled in the art will quickly recognize that different decisions could be made at this point. For instance, a decision could be made as to whether the object of reference fits on a display screen. Alternative, a decision could be made as to whether both the item of interest and the object of reference fit on the display screen, and so on.

At block **912**, if the answer to the question posed at block **910** was yes, namely, that the anchored item does indeed fit on the display screen, then the item is just displayed as before. And it is kept displayed as long as it fits onto the display screen. Now, it should be recognized that a user of a mobile device may change this situation by either zooming in or zooming out of a map image. For instance, suppose a user is looking at an item on the map image and suddenly decides to zoom in on a particular portion of the map away from where the item is displayed. If the user zooms in enough, the item will no longer fit onto the display (that is, it will still be located on the map image itself, but it may no longer be displayable of a mobile device screen).

In such a scenario, at block **914**, once the item is no longer displayable, a signpost is maintained for it so long as it is off the screen. Signposting is either turned on or off depending whether the item is displayable for not, thus, with reference to the flow chart, the signposting and orientation system keeps alternating states between blocks **912** and **914**.

Moreover, when the system is at block **914**, there is the option of implementing block **916**. At block **916**, an orientation mark is created for the user, either upon request (as illustrated) or upon some other condition, such as a developer setting up the system to display orientation mark and corresponding direction vectors to help user to orientate themselves. As mentioned above, and as is discussed in more detail below, these orientation marks may take on a variety of forms, from celestial bodies to grounded bodies.

FIG. 10 expounds in more detail on block **914** briefly discussed with reference to FIG. 9, above. Thus following block **914** that maintains a signpost for an item so long as it is off the display screen, at block **1002** a decision has to be made as to which information is to be displayed.

Numerous choices abound, and in one case, at block **1004**, the name of the off-screen item is displayed. A name, of course, is just an example, and numbers could be used instead or just about any identifying symbol for an item. Moreover, at block **1006** the distance of the item to an anchoring object of reference is also displayed, although other relationships could also be displayed, such as the temporal relationship between the object and the item. Finally, at block **1008**, an orientation reference is used to point in what direction an object of reference must be moving in order to reach the item. The orientation reference need not be pointing exactly in that direction, i.e., as would a vector, but can point substantially in that direction. Of course, as mentioned above, for a more accurate depiction, orientation mark with vectors to objects of reference could easily be used if the user or developer wished to do so.

At block **1010**, such a vector between an object of reference and an item and/or an orientation mark can be created. This type of vector allows a user to use the vector to align himself with an orientation mark, such as the sun. It also helps to clarify special relationships between signposted items, orientation marks, and objects of reference.

Lastly, at block **1012**, any of the discussed or other relationships displayable in signposts can be dynamically updated. Thus, items could change names, if for example one item corresponds to a user with a mobile device and then hands off that mobile device to a second user who will be tracked via the mobile device (say, for example, "Jane" hands of her mobile device to "Brian", in which case the signpost name would have to be updated—if the tracking is being done person-by-person). However, tracking can also be done mobile device-by-mobile device, so that even if the device is handed off from one person to the next, the name remains the same. All of this, of course, presupposes that the mobile device is the item on the map image—and it could easily be so, especially if it can send its location information to another mobile device—a feat easily accomplishable and knowable by those skilled in the art. But, additionally, a user could merely tell another user of her location and tracking could be done in this manner (although dynamic updating might be more challenging, since such updating would depend on the former user's updates).

FIG. 11 expounds on orientation mark creation briefly discussed with reference to FIG. 9. Thus, following block **916**, at block **1102**, an antecedent question might be which orientation mark to create in the first place. Numerous choices are provided by the system mentioned above. For example, at block **1104**, celestial bodies may be used to orientate a user as to his position. At block **1108**, a sun may be used, or if the user is using the system at night, at block **1110** stars may be used. Or alternatively, if the user is in a city at night and stars are not visible, at block **1112** a moon can be used as an orientation mark. Or, if in this latter situation, it is a city moonless night, other marks can be used such as lighted towers, and so on.

In addition to some of the celestial bodies discussed above with reference to blocks **1108**, **1110**, and **1112**, at block **1106** grounded bodies can also be used. As mentioned, on a moonless city night lighted towers can be used, but in reality any visible building or monument can be used. Thus, at block **1112** buildings such as the Louvre museum can be used or at block **1114** monuments such as the Eiffel tower can be used. In short, as far as orientation marks go, any visible object that can be leveraged by the user for orientation purposes can be used.

FIG. 12A illustrates the various item location combinations, building on discussions with reference to FIG. 9. In FIG. 12A, at block **904**, once an item is displayed on a map image, as can be seen at block **1202**, a stationary item can be displayed, or as can be seen at block **1204**, a moving item can be displayed. In the latter case, such a moving item can either be centered on a display screen (block **1210**) or it can be displayed off-center (block **1212**). Similarly, in the former case, a stationary item (block **1202**) can be either centered (block **1210**) or be off-center (block **1212**).

What holds true for items, also may hold true for objects of reference. In FIG. 12B, at block **906**, once an object of reference is established and displayed, such an object can either be stationary (block **1206**) and centered (block **1214**) or stationary (block **1206**) and off-center (block **1216**). Similarly, an object can be moving (block **1208**) can either be stationary (block **1206**) and centered (block **1214**) or stationary (block **1206**) and off-center (block **1216**).

Aspects of a Flexible Programming Framework

In one aspect of this signposting and orientation technology, a flexible programming framework can be implemented for use by application developers (and especially for the development of software running on mobile devices) in order to take advantage of this technology. With reference to FIG. 13, the framework **1300** consists of a set of programming interfaces **1302**, **1304**, **1306**, and **1308** for both application developers and software developers building map-rendering technology (but it can be used by end-users also through user interface elements that expose access to this interface). These interfaces allow for each item that can potentially be displayed on top of a map to be associated with data structures. For example, one data structure, such as "MapItemDisplayInfo" **1302**, contains properties that describe the rendering characteristics (e.g. color and visibility) of the item if it is to be drawn onto the map. This data structure also has a property called "SignpostWhenOffscreen" **1304** that determines if the item should have a signpost drawn to it if it cannot be displayed on the screen displayable portion of a map.

The following is a high level description of the code from "MapItemDisplayInfo" **1302**:

MapItemDisplayInfo
Namespace: using EMIC.LocationServices.LocationUIControls
Assembly: EMIC.LocationServices.LocationUIControls.DLL
EMIC.LocationServices.LocationUIControls
This class wraps access to an ItemOfInterest or AreaOfInterest object
and controls its display characteristics within a MapDisplay control.
An instance of this object is returned when an ItemOfInterest or
AreaOfInterest is added to a MapDisplay control.
Properties that dicate how the map item will be visually displayed:
Visible property
TRUE = the items should be attempted to be rendered onto map images.
FALSE = do not render the item onto map images.
SignpostWhenOffscreen (1304) property
If set to TRUE, if this item/area can not fit into the screen of the
current map, a signpost is drawn to indicate what direction and how
far the item is.
Emphasis property
Returns the visual emphasis of the item. (e.g. Enabled/Disabled/
Selected). If the MapDisplay supports highlighting, this property
is used, otherwise it is ignored.
PreferredFont property
The preferred Font to be used when rendering text for the item.
. . . <a host of other properties> . . .
Properties that dicate the relative importance of the item
relative to other items to be dislayed on map:
MapWeight property
Returns the relative map weighting this item has when new maps are
queried for. Items/Areas with higher MapWeight values will be more
likely to be on, and in the center of selected maps.
. . . <a host of other properties> . . .
Additional properties that allow access to other aspects of
the map item:
AsItemOfInterest property
If the contained Item or Area can be cast to an ItemOfInterest, the
object pointer is returned. Otherwise NULL is returned
. . . <a host of other properties> . . .

As can be seen directly above, one of the properties **1304** deals with signposting. Given a sample object, such as "Jane", the following code could be implemented to signpost the object if it is off the edge of a map being displayed:

```
m_displayInfo_areaJane.SignpostWhenOffScreen=true;
```

Through the "MapItemDisplayInfo" **1302** interface, either the developer **1312** or even an end-user **1310** can set the signposting properties described throughout this description.

There are numerous other interfaces in the aforementioned framework. For example, an object that displays a map can have a "SignpostBase" property **1306**. This property indicates what Item should be used as the anchor point to measure distance and orientation form. If the property is not set (i.e. set to a value of NULL) then the center of the current map is used. For example, the following code could be used:

```
//-----------------------------------------------------------------
// Make the signposting center item the user "Jane"
//-----------------------------------------------------------------
                    mapDisplay1.SignpostBase=m_displayInfo_itemJane.AsItemOfInterest;
```

Moreover, a developer employing the framework can show the sun's orientation on a current map by setting a MapDisplay object, namely "ShowSunOrientation" **1308**, in the following manner:

```
//-----------------------------------------------------------------
// Display the sun
//-----------------------------------------------------------------
                    mapDisplay1.ShowSunOrientation=true;
```

On an implementation level, when the MapDisplay object is asked to render a map, it chooses the best map (based on user or application developer specified criteria) from a set of available maps (e.g. indoor maps, outdoor maps, floor-plans, subway maps, street maps, other different kinds of maps). It then chooses the best resolution to use to render the map, and the best boundary areas of the map to ensure the most important items get displayed. When the right map as been selected, each of the Items (or Areas) of interest is attempted to be rendered onto this map image. If the Item or Area is found to be outside the bounds of the current map, but still relevant to the map, a "signpost" is rendered onto the map image indicating its relative distance and orientation to the designated item on the map.

To render this map, the direction vector drawn to it, and a compass icon the points in the direction of the object, vector mathematics are used to calculate the directional relationship between the SignpostBase object and the object whose signpost is being drawn. First a vector (v_direction) is calculated between the two objects. Second the "dot product" is calculated between this direction vector (v_direction) and the map's normalized North (v_north) and East (v_east) vectors (where the magnitude of both of these vectors should be the same, and the direction vector can be any magnitude. Thus, from this point, an x_component and a y_components can be determined relative to an object of reference (i.e. an anchoring point): x_component=v_direction*v_north; y_component=v_direction*v_east. From this, a compass heading is determined. Finally the signpost graphics and data are rendered onto the map image.

Furthermore, if a request is made that the sun's orientation is to be displayed on the map, this orientation is calculated by using the Universal Time (Greenwhich Mean Time) and the map objects Longitude and Latitude values. Based on these values, the correct position of the sun on the maps orientation can be determined.

Further flexibility is built into the system described above by: (a) allowing the providers of various maps to indicate whether their map knows which direction on their map corresponds to "Earth's North". If the map does not know where Earth's North is, no reference to the sun's orientation will be drawn; (b) allowing the providers of various maps to indicate their orientation to a "relative north" that may be used on local coordinate systems such as indoor coordinate systems that may not care about Earth orientation (e.g. some indoor location systems may not care where "true north" is).

Aspects of a Suitable Computing Environment

The signposting and orientation technology can be employed in various computing environments, which may be implemented inside the aforementioned mobile devices or outside such devices but working in cooperation with them. And, moreover, in software form, the technology can be stored on various media, not just computer readable media bearing computer executable instructions for use in a computing system.

FIG. 14 and the following discussion are intended to provide a brief general description of a suitable computing environment in connection with which the technology may be implemented. It should be understood, however, that handheld, portable and other computing devices and computing objects of all kinds are contemplated for use in connection with the present technology, i.e., anywhere where that it is desirable to flexibly, or quickly process data in a computing environment. While a general purpose computer is described below, this is but one example, and the present technology may be implemented with a thin client having network/bus interoperability and interaction. Thus, the present technology may be implemented in an environment of networked hosted services in which very little or minimal client resources are implicated, e.g., a networked environment in which the client device serves merely as an interface to the network/bus, such as an object placed in an appliance. In essence, anywhere that data may be stored or from which data may be retrieved or transmitted to another computer is a desirable, or suitable, environment for operation of the techniques for downloading algorithmic elements to a coprocessor in accordance with the technology.

Although not required, the technology can be implemented via an operating system, for use by a developer of services for a device or object, and/or included within application software that operates in connection with the methods for coordinating wireless traffic in accordance with the technology. Software may be described in the general context of computer-executable instructions, such as program modules, being executed by one or more computers, such as client workstations, servers or other devices. Generally, program modules include routines, programs, objects, components, data structures and the like that perform particular tasks or implement particular abstract data types. Typically, the functionality of the program modules may be combined or distributed as desired in various embodiments. Moreover, those skilled in the art will appreciate that the herein described technology may be practiced with other computer system configurations and protocols. Other well known computing systems, environments, and/or configurations that may be suitable for use with the technology include, but are not limited to, personal computers (PCs), automated teller machines, server computers, hand-held or laptop devices, multi-processor systems, microprocessor-based systems, programmable consumer electronics, network PCs, appliances, lights, environmental control elements, minicomputers, mainframe computers, and of course the above discussed mobile devices. The technology may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network/bus or other data transmission medium. In a distributed computing environment, program modules may be located in both local and remote computer storage media including memory storage devices, and client nodes may in turn behave as server nodes, as described above.

FIG. 14 thus illustrates an example of a suitable computing system environment **100** in which the signposting and orientation technology may be implemented, although as made clear above, the computing system environment **100** is only one example of a suitable computing environment and is not intended to suggest any limitation as to the scope of use or functionality of the technology. Neither should the computing environment **100** be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary operating environment **100**.

With reference to FIG. 14, an exemplary system for implementing the technology includes a general purpose computing device in the form of a computer **110**. Components of computer **110** may include, but are not limited to, a processing unit **120**, a system memory **130**, and a system bus **121** that couples various system components including the system memory to the processing unit **120**. The system bus **121** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and/or a local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus (also known as Mezzanine bus).

Computer **110** typically includes a variety of computer readable media. Computer readable media can be any available media that can be accessed by computer **110** and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer storage media includes both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data. Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CDROM, digital versatile disks (DVD) or other optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer **110**. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared and other wireless media. Combinations of any of the above should also be included within the scope of computer readable media.

The system memory **130** includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) **131** and random access memory (RAM) **132**. A basic input/output system **133** (BIOS), containing the basic routines that help to transfer information between elements within computer **110**, such as during start-up, is typically stored in ROM **131**. RAM **132** typically contains data and/or program modules that are immediately accessible to and/or presently being operated on by processing unit **120**. By way of example, and not limitation, FIG. 14 illustrates operating system **134**, application programs **135**, other program modules **136**, and program data **137**.

The computer **110** may also include other removable/non-removable, volatile/nonvolatile computer storage media. By way of example only, FIG. 14 illustrates a hard disk drive **141** that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive **151** that reads from or writes to a removable, nonvolatile magnetic disk **152**, and an optical disk drive **155** that reads from or writes to a removable, nonvolatile optical disk **156**, such as a CD-ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM and the like. The hard disk drive **141** is typically connected to the system bus **121** through a non-removable memory interface such as interface **140**, and magnetic disk drive **151** and optical disk drive **155** are typically connected to the system bus **121** by a removable memory interface, such as interface **150**. All of these storage media are capable of storing the signposting and orientation instructions, but this is not an exclusive list.

The drives and their associated computer storage media discussed above and illustrated in FIG. 14 provide storage of computer readable instructions, data structures, program modules and other data for the computer **110**. In FIG. 14, for example, hard disk drive **141** is illustrated as storing operating system **144**, application programs **145**, other program modules **146** and program data **147**. Note that these components can either be the same as or different from operating system **134**, application programs **135**, other program modules **136** and program data **137**. Operating system **144**, application programs **145**, other program modules **146** and program data **147** are given different numbers here to illustrate that, at a minimum, they may be different copies. A user may enter commands and information into the computer **110** through input devices such as a keyboard **162** and pointing device **161**, commonly referred to as a mouse, trackball or touch pad. Other input devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit **120** through a user input interface **160** that is coupled to the system bus **121**, but may be connected by other interface and bus structures, such as a parallel port, game port or a universal serial bus (USB). A graphics interface **182**, such as Northbridge, may also be connected to the system bus **121**. Northbridge is a chipset that communicates with the CPU, or host processing unit **120**, and assumes responsibility for accelerated graphics port (AGP) communications. One or more coprocessors, such as graphics processing units (GPUs) **184**, may communicate with graphics interface **182**. In this regard, GPUs **184** generally include on-chip memory storage, such as register storage and GPUs **184** communicate with a video memory **186**, wherein the methods for downloading algorithmic elements to a coprocessor of the technology have particular impact. GPUs **184**, however, are but one example of a coprocessor and thus a variety of coprocessing devices may be included in computer **110**, and may include a variety of procedural shaders, such as pixel and vertex shaders. A monitor **191** or other type of display device is also connected to the system bus **121** via an interface, such as a video interface **190**, which may in turn communicate with video memory **186**. In addition to monitor **191**, computers may also include other peripheral output devices such as speakers **197** and printer **196**, which may be connected through an output peripheral interface **195**.

The computer **110** may operate in a networked or distributed environment using logical connections to one or more remote computers, such as a remote computer **180**. The remote computer **180** may be a personal computer, a server, a router, a network PC, a peer device or other common network node, and typically includes many or all of the elements described above relative to the computer **110**, although only a memory storage device **181** has been illustrated in FIG. 14. The logical connections depicted in FIG. 14 include a local area network (LAN) **171** and a wide area network (WAN) **173**, but may also include other networks/buses. Such networking environments are commonplace in homes, offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer **110** is connected to the LAN **171** through a network interface or adapter **170**. When used in a WAN networking environment, the computer **110** typically includes a modem **172** or other means for establishing communications over the WAN **173**, such as the Internet. Data communications device **172**, such as a modem, which may be internal or external, may be connected to the system bus **121** via the user input interface **160**, or other appropriate mechanism. In a networked environment, program modules depicted relative to the computer **110**, or portions thereof, may be stored in the remote memory storage device. By way of example, and not limitation, FIG. 14 illustrates remote application programs **185** as residing on memory device **181**. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used. All of these networked components may be implemented in using the signposting and orientation technology.

While the present disclosure has been described in connection with the preferred aspects, as illustrated in the various figures, it is understood that other similar aspects may be used or modifications and additions may be made to the described aspects for performing the same function of the present disclosure without deviating therefrom. For example, in one aspect of the disclosure, signposting and orientation technology was discussed. However, other equivalent mechanisms to these described aspects are also contemplated by the teachings herein. Therefore, the present disclosure should not be limited to any single aspect, but rather construed in breadth and scope in accordance with the appended claims.

Patent Citations (54)

Publication number	Priority date	Publication date	Assignee	Title
FR2343300A1 *	1976-03-01	1977-09-30	Decaux Paris J C	Sign post incorporating street maps - has vertical support post and outer curved sleeve on which maps are displayed
DE3512000A1 *	1985-04-02	1986-10-02	Alwin 7500 Karlsruhe Traub	Information display guide
JPS63222215A *	1987-03-11	1988-09-16	Nissan Motor Co Ltd	Position detector for vehicle

US4937570A *	1987-02-26	1990-06-26	Mitsubishi Denki Kabushiki Kaisha	Route guidance display device
JPH04366991A *	1991-06-14	1992-12-18	Fujitsu Ten Ltd	Navigation device for automatic display of vehicle position or the like
JPH06118870A *	1992-10-05	1994-04-28	Matsushita Electric Ind Co Ltd	Map information accumulating method and map terminal and plotting method
JPH08211830A *	1995-02-06	1996-08-20	Sanwa Plast Kk	Fixing structure of display to support
US5631642A *	1993-03-12	1997-05-20	Austec Electronic Systems Limited	Mobile object tracking systems
US5774829A *	1995-12-12	1998-06-30	Pinterra Corporation	Navigation and positioning system and method using uncoordinated beacon signals in conjunction with an absolute positioning system
WO2000049530A1	1999-02-17	2000-08-24	Telia Ab	Mobile information service
WO2001032480A1	1999-11-05	2001-05-10	Netstar (Proprietary) Limited	A mobile object monitoring system
US6233523B1 *	1997-10-02	2001-05-15	Ibs Integrierte Business Systeme Gmbh	Method of collection and linking of positional data from satellite localization and other data
US6252544B1 *	1998-01-27	2001-06-26	Steven M. Hoffberg	Mobile communication device
US6321158B1 *	1994-06-24	2001-11-20	Delorme Publishing Company	Integrated routing/mapping information
US20020049533A1	2000-08-16	2002-04-25	Manabu Kusano	Navigation device
US6442483B1 *	2001-08-21	2002-08-27	Arthur George Doglione	System and method for defining and creating surrogate addresses for township and range quarter sections
US20020118118A1	2001-02-26	2002-08-29	International Business Machines Corporation	Wireless communication system and method to provide geo-spatial related event data
GB2374763A	2001-04-18	2002-10-23	E Lead Electronic Co Ltd	Road navigation system using electronic map route calculating software satellite positioning devices and the mobile telephone network
EP1318379A1 *	2000-09-11	2003-06-11	Matsushita Electric Industrial Co., Ltd.	Path guide system
US6615134B2 *	2000-05-25	2003-09-02	Sony Corporation	Data communication system and method, and mobile body apparatus
US20030184654A1	2002-03-29	2003-10-02	Fuji Photo Film Co., Ltd.	Shooting equipment communicating system
US20040008138A1	2002-07-15	2004-01-15	Hockley George O.	Apparatus and method of position determination using shared information
US6697734B1	2002-04-17	2004-02-24	Nokia Corporation	System and method for displaying a map having two scales
US6710774B1 *	1999-05-12	2004-03-23	Denso Corporation	Map display device
US20040073356A1	2002-10-09	2004-04-15	Craine Dean A.	Personal traffic congestion avoidance system
US20040073361A1	2002-10-15	2004-04-15	Assimakis Tzamaloukas	Enhanced mobile communication device, and transportation application thereof
US20040153238A1 *	2003-01-22	2004-08-05	Increment P Corporation	Data structure of feature guidance information, recording medium storing feature guidance information, navigation device, navigation system, navigation method, navigation program and recording medium storing the navigation program
US20040204063A1	2002-02-22	2004-10-14	Julian Van Erlach	Enhanced telecommunication services
US20040220726A1 *	2001-01-24	2004-11-04	Televigation, Inc.	Real-time navigation system for mobile environment
JP2004310717A *	2003-04-07	2004-11-04	Toshiyuki Nishimitsu	Present location information retrieval system
US20040243307A1 *	2003-06-02	2004-12-02	Pieter Geelen	Personal GPS navigation device
US20040255718A1	2003-06-18	2004-12-23	Steers Jerome Andrew	Turbine powered flywheel
US6857016B1	2000-09-25	2005-02-15	Ricoh Company Limited	Method and system of data collection and mapping from a remote position reporting device
US6879909B2	2001-01-11	2005-04-12	Xanavi Informatics Corporation	Map display control apparatus, map information update apparatus, map information update system and control method thereof
US20050149251A1 *	2000-07-18	2005-07-07	University Of Minnesota	Real time high accuracy geospatial database for onboard intelligent vehicle applications

US6944679B2 *	2000-12-22	2005-09-13	Microsoft Corp.	Context-aware systems and methods, location-aware systems and methods, context-aware vehicles and methods of operating the same, and location-aware vehicles and methods of operating the same
US20060064243A1 *	2004-06-30	2006-03-23	Pioneer Corporation	Output control device, method thereof, program thereof, and recording medium storing the program
US20060287819A1 *	2005-01-18	2006-12-21	Christian Brulle-Drews	Navigation system with intersection and three-dimensional landmark view
US20070050129A1 *	2005-08-31	2007-03-01	Microsoft Corporation	Location signposting and orientation
EP1435600B1	2002-12-30	2007-07-18	Motorola, Inc.	Method and apparatus for determining the location of a wireless device
US20070185651A1 *	2006-02-07	2007-08-09	Masaki Motoyama	Navigation system utilizing XML/SVG map data converted from geographic map data and layered structure of XML/SVG map data based on administrative regions
US20070203643A1 *	2006-02-27	2007-08-30	Xanavi Informatics Corporation	Vehicle navigation system and method for displaying waypoint information
US20070203641A1 *	2005-12-31	2007-08-30	Diaz Melvin B	In-vehicle navigation system with removable navigation unit
US20070203646A1 *	2005-12-31	2007-08-30	Diaz Melvin B	Image correction method and apparatus for navigation system with portable navigation unit
US20070233367A1 *	2006-03-31	2007-10-04	Geospot, Inc.	Methods for Interaction, Sharing, and Exploration over Geographical Locations
CN201000710Y *	2007-01-08	2008-01-02	白晓斌	Solar energy electronic guidepost for bus station
WO2008019879A2 *	2006-08-15	2008-02-21	Tomtom International B.V.	A method of generating improved map data for use in navigation devices, map data and navigation device therefor
AU2007231862A1 *	2006-11-07	2008-05-22	Sun, Ronald Mr	Process and methods of improved navigation and advertising systems
US7519470B2 *	2006-03-15	2009-04-14	Microsoft Corporation	Location-based caching for mobile devices
Family To Family Citations				
JP3727854B2 *	2001-01-30	2005-12-21	株式会社東芝	Road guide generation method, road guide device, server device, map information editing support device, and program
US6765528B2 *	2001-10-25	2004-07-20	Audiovox Corporation	Mobile radio with GPS capability
AU2003205831A1 *	2002-01-23	2003-09-02	M-Spatial Limited	Schematic generation
JP2003240567A *	2002-02-13	2003-08-27	Mitsubishi Electric Corp	Navigation apparatus and method therefor
JP4225029B2	2002-10-18	2009-02-18	日産自動車株式会社	Map image display device and map image display program

* Cited by examiner, † Cited by third party

Non-Patent Citations (20)

Title
Avoiding Static and Dynamic Objects in Navigation; Han Li; Yili Fu; He Xu; Yulin Ma; Intelligent Robots and Systems, 2006 IEEE/RSJ International Conference on; Oct. 9-15, 2006 pp. 639-644; Digital Object Identifier 10.1109/IROS.2006.282547. *
Bahl, P., et al., "A software system for locating mobile users: design, evaluation, and lessons," Microsoft Research, downloaded Oct. 4, 2005, http://research.microsoft.com/~bahl/Papers/Pdf/radar.pdf, 1-13.
Developing landmark-based pedestrian navigation systems; Millonig, A.; Schechtner, K.; Intelligent Transportation Systems, 2005. Proceedings. 2005 IEEE; Sep. 13-15, 2005 pp. 197-202; Digital Object Identifier 10.1109/ITSC.2005.1520046. *
Dynamic stereo in visual navigation; Tistarelli, M.; Grosso, E.; Sandini, G., Computer Vision and Pattern Recognition, 1991. Proceedings CVPR '91., IEEE Computer Society Conference on; Jun. 3-6, 1991 pp. 186-193; Digital Object Identifier 10.1109/CVPR.1991.139685. *
Effects of battlefield display frames of reference on navigation tasks, spatial judgements, and change detection; Lisa C. Thomas; Christopher D. Wickens; Ergonomics, 1366-5847, vol. 49, Issue 12, 2006, pp. 1154 - 1173. *
F. Ledermann and D. Schmalstieg, "April-A High Level Framework for Creating Augmented Reality Presentations," Proc. IEEE VR, IEEE CS Press, 2005, pp. 187-194 (cited by others). *
G. Reitmayr and D. Schmalstieg, "Dat Management Strategies for Mobile Augmented Reality," Proc. Int'l Workshop Software Technology for Augmented Reality Systems, IEEE CS Press, 2003, pp. 47-52 (cited by others). *
G. Reitmayr and D. Schmalstieg, "Location Based Applications for Mobile Augmented Reality," Proc. Australasian User Interface Conf. (AUIC), IEEE CS Press, 2003, pp. 65-73 (cited by others). *
G. Reitmayr and D. Schmalstieg, "OpenTracker-A Flexible Software Design for Three-Dimensional Interaction," Virtual Reality, vol. 9, No. 1, 2005, pp. 79-92 (cited by others). *

G. Schall et al., "Construction and Maintenance of Augmented Reality Environments Using a Mixture of Autonomous and Manual Surveying Techniques," Proc. 7th Conf. Optical 3-D Measurement Techniques, vol. 1, A. Grün and H. Kahmen, eds., 2005; http://www.icg.tu-graz.ac.at/Members/schall/optical3dpaper.pdf/download (cited by others). *

G. Schall et al., "Handheld Geospatial Augmented Reality Using Urban 3D Models," Proc. Mobile Spatial Interaction Workshop, Computer-Human Interaction Conf., Springer, 2007 (cited by others). *

Hand-held windows: towards effective 2D interaction in immersive virtual environments; Lindeman, R.W.; Sibert, J.L.; Hahn, J.K.; Virtual Reality, 1999. Proceedings., IEEE, Mar. 13-17, 1999 pp. 205-212, Digital Object Identifier 10.1109/VR.1999.756952. *

Hermann, F., et al., "Egocentric maps on mobile devices," Fraunhofer Institute for Industrial Engineering, Germany, 2003, downloaded Oct. 4, 2005, http://www.hci.iao.fraunhofer.de/uploads/tx-publications/HermannBieberDuesterhoeft2003-Egocentric-Maps-IMC-03-Rost-.pdf, 7 pages.

In the United States Patent and Trademark Office, Non-Final Office Action, in re:. U.S. Appl. No. 10/998,081, Filed Nov. 26, 2004, Dated Oct. 16, 2008, 9 Pages.

Low Cost and Low Weight Technologies for Planetary Surface Exploration; Innocenti, M.; Pollini, L.; Recent Advances in Space Technologies, 2007. RAST '07. 3rd International Conference on; Jun. 14-16, 2007 pp. 562-567; Digital Object Identifier 10.1109/RAST.2007.4284056. *

Microsoft speech application SDK, downloaded Oct. 4, 2005, http://msdn.microsoft.com/library, 2 pages.

Rendering in object interference detection on conventional graphics workstations; Baciu, G.; Wingo Sai-Keung Wong; Computer Graphics and Applications, 1997. Proceedings., The Fifth Pacific Conference on, Oct. 13-16, 1997 pp. 51-58, 218; Digital Object Identifier 10.1109/PCCGA. 1997.626171. *

Sighted automation and fine resolution imaging; Brown, W.M.; Walker, J.L.; Boario, W.R.; Aerospace and Electronic Systems, IEEE Transactions on; vol. 40, Issue 4, Oct. 2004 pp. 1426-1445, Digital Object Identifier 10.1109/TAES.2004.1386898. *

The effect of 3D widget representation and simulated surface constraints on interaction in virtual environments; Lindeman, R.W.; Sibert, J.L.; Templeman, J.N.; Virtual Reality, 2001. Proceedings. IEEE, Mar. 13-17, 2001 pp. 141-148; Digital Object Identifier 10.1109/VR.2001.913780. *

The Progress of AMTICS-Advanced Mobile Traffic Information and Communication System; H Okamoto, M Hase - Electronics, 1990. Vehicle Electronics in the 90's: 1990 - From http://www.ieeexplore.ieee.org. *

* Cited by examiner, † Cited by third party

Cited By (80)

Publication number	Priority date	Publication date	Assignee	Title
US20090300122A1 *	2008-05-30	2009-12-03	Carl Johan Freer	Augmented reality collaborative messaging system
US20100008265A1 *	2008-07-14	2010-01-14	Carl Johan Freer	Augmented reality method and system using logo recognition, wireless application protocol browsing and voice over internet protocol technology
US20100009713A1 *	2008-07-14	2010-01-14	Carl Johan Freer	Logo recognition for mobile augmented reality environment
US20120088526A1 *	2010-10-08	2012-04-12	Research In Motion Limited	System and method for displaying object location in augmented reality
US20140032181A1 *	2012-07-24	2014-01-30	Dassault Systemes	Design Operation In An Immersive Virtual Environment
US8682350B2	2006-06-01	2014-03-25	Loopt Llc	Location-based advertising message serving for mobile communication devices
US8874144B1 *	2013-10-07	2014-10-28	Google Inc.	Selecting location-based content
US20150029214A1 *	2012-01-19	2015-01-29	Pioneer Corporation	Display device, control method, program and storage medium
US9560479B2	2006-06-01	2017-01-31	Green Dot Corporation	Secure and private location sharing for location-aware mobile communication devices
US10282916B2 *	2013-06-01	2019-05-07	Apple Inc.	Intelligently placing labels
US10546402B2 *	2014-07-02	2020-01-28	Sony Corporation	Information processing system, information processing terminal, and information processing method
US10706405B2	2012-06-28	2020-07-07	Green Dot Corporation	Wireless client transaction systems and related methods
US10937088B2	2012-07-13	2021-03-02	Green Dot Corporation	Mobile account data access systems and methods
US11216810B2	2015-08-06	2022-01-04	Green Dot Corporation	Systems and methods for fund transfers
US11715154B2	2018-09-20	2023-08-01	Green Dot Corporation	Systems and methods for managing accounts in a financial services system
Family To Family Citations				
US7245923B2 *	2003-11-20	2007-07-17	Intelligent Spatial Technologies	Mobile device and geographic information system

				background and summary of the related art
US8060112B2	2003-11-20	2011-11-15	Intellient Spatial Technologies, Inc.	Mobile device and geographic information system background and summary of the related art
US7634354B2 *	2005-08-31	2009-12-15	Microsoft Corporation	Location signposting and orientation
US7418341B2 *	2005-09-12	2008-08-26	Intelligent Spatial Technologies	System and method for the selection of a unique geographic feature
US7698061B2	2005-09-23	2010-04-13	Scenera Technologies, Llc	System and method for selecting and presenting a route to a user
US7649534B2 *	2006-02-01	2010-01-19	Microsoft Corporation	Design of arbitrary linear and non-linear maps
EP1840511B1 *	2006-03-31	2016-03-02	BlackBerry Limited	Methods and apparatus for retrieving and displaying map-related data for visually displayed maps of mobile communication devices
US7702456B2 *	2006-04-14	2010-04-20	Scenera Technologies, Llc	System and method for presenting a computed route
US8688375B2 *	2006-05-31	2014-04-01	Trx Systems, Inc.	Method and system for locating and monitoring first responders
US8538676B2 *	2006-06-30	2013-09-17	IPointer, Inc.	Mobile geographic information system and method
US8060499B2 *	2006-09-25	2011-11-15	Nokia Corporation	Simple discovery UI of location aware information
US9395190B1	2007-05-31	2016-07-19	Trx Systems, Inc.	Crowd sourced mapping with robust structural features
US9733091B2	2007-05-31	2017-08-15	Trx Systems, Inc.	Collaborative creation of indoor maps
JP5024668B2 *	2007-07-10	2012-09-12	富士ゼロックス株式会社	Image forming apparatus and information processing apparatus
WO2009021068A1 *	2007-08-06	2009-02-12	Trx Systems, Inc.	Locating, tracking, and/or monitoring personnel and/or assets both indoors and outdoors
US8339399B2 *	2007-10-31	2012-12-25	Microsoft Corporation	Declustering point-of-interest icons
US8032297B2 *	2008-05-08	2011-10-04	Gabriel Jakobson	Method and system for displaying navigation information on an electronic map
US8014943B2 *	2008-05-08	2011-09-06	Gabriel Jakobson	Method and system for displaying social networking navigation information
US8478527B2	2008-05-08	2013-07-02	Neske Research K.G. L.L.C.	Method and system for displaying navigation information and mapping content on an electronic map
JP4675995B2 *	2008-08-28	2011-04-27	株式会社東芝	Display processing apparatus, program, and display processing method
JP4393565B1 *	2008-08-28	2010-01-06	株式会社東芝	Display processing apparatus, display processing method, and program
US20100058173A1 *	2008-08-28	2010-03-04	Kabushiki Kaisha Toshiba	Display processing apparatus, display processing method, and computer program product
DE102008045994A1 *	2008-09-05	2010-03-11	Volkswagen Ag	Method and device for displaying information in a vehicle
US20100115459A1 *	2008-10-31	2010-05-06	Nokia Corporation	Method, apparatus and computer program product for providing expedited navigation
EP2368174A4 *	2008-12-22	2014-05-07	Intelligent Spatial Technologies Inc	System and method for initiating actions and providing feedback by pointing at object of interest
US8483519B2 *	2008-12-22	2013-07-09	Ipointer Inc.	Mobile image search and indexing system and method
CA2748024A1 *	2008-12-22	2010-07-01	Intelligent Spatial Technologies, Inc.	System and method for exploring 3d scenes by pointing at a reference object
CA2748031A1	2008-12-22	2010-07-01	Intelligent Spatial Technologies, Inc.	System and method for linking real-world objects and object representations by pointing
US7961674B2 *	2009-01-27	2011-06-14	Sony Corporation	Multi-tier wireless home mesh network with a secure network discovery protocol
US8904177B2 *	2009-01-27	2014-12-02	Sony Corporation	Authentication for a multi-tier wireless home mesh network

GB2467577A	2009-02-06	2010-08-11	Sony Corp	Handheld electronic device configured to display location of another electronic device when tilted
US8964634B2 *	2009-02-06	2015-02-24	Sony Corporation	Wireless home mesh network bridging adaptor
US8335638B2 *	2009-02-20	2012-12-18	Aviation Communication & Surveillance Systems Llc	Systems and methods for displaying off screen traffic
US7990897B2 *	2009-03-11	2011-08-02	Sony Corporation	Method and apparatus for a wireless home mesh network with network topology visualizer
US20100241987A1 *	2009-03-19	2010-09-23	Microsoft Corporation	Tear-Drop Way-Finding User Interfaces
US20100241999A1 *	2009-03-19	2010-09-23	Microsoft Corporation	Canvas Manipulation Using 3D Spatial Gestures
US8121640B2	2009-03-19	2012-02-21	Microsoft Corporation	Dual module portable devices
US8849570B2 *	2009-03-19	2014-09-30	Microsoft Corporation	Projected way-finding
US20120047087A1	2009-03-25	2012-02-23	Waldeck Technology Llc	Smart encounters
DE102009052862A1 *	2009-11-09	2011-06-09	Skobbler Gmbh	Mobile navigation system
US20110239163A1 *	2009-12-04	2011-09-29	Daisuke Mochizuki	Display screen control method, graphical user interface, information processing apparatus, information processing method, and program
US9697751B2	2010-03-09	2017-07-04	Microsoft Technology Licensing, Llc	Interactive representation of clusters of geographical entities
US9361729B2 *	2010-06-17	2016-06-07	Microsoft Technology Licensing, Llc	Techniques to present location information for social networks using augmented reality
DE202011110851U1	2010-12-07	2016-11-09	Google Inc.	Device of route guidance
JP2012252529A *	2011-06-03	2012-12-20	Sony Corp	Information processor, information processing method and program
JP5747673B2 *	2011-06-10	2015-07-15	ソニー株式会社	Information processing apparatus, information processing method, and program
US9542241B2 *	2011-07-12	2017-01-10	Harman International Industries, Incorporated	Navigation application interface
CN102495893A *	2011-12-09	2012-06-13	北京北方烽火科技有限公司	Using method of map in wireless road test software and equipment
JP5818672B2 *	2011-12-21	2015-11-18	インターナショナル・ビジネス・マシーンズ・コーポレーションInternational Business Machines Corporation	Information processing apparatus, display processing method, program, and recording medium
US9552129B2	2012-03-23	2017-01-24	Microsoft Technology Licensing, Llc	Interactive visual representation of points of interest data
US8635021B2	2012-05-04	2014-01-21	Google Inc.	Indicators for off-screen content
CN103017759B *	2012-12-22	2015-06-17	中国人民解放军第四军医大学	Method to overcome space unorientation and delusions
US8589818B1	2013-01-03	2013-11-19	Google Inc.	Moveable viewport for indicating off-screen content
US11156464B2	2013-03-14	2021-10-26	Trx Systems, Inc.	Crowd sourced mapping with robust structural features
US11268818B2	2013-03-14	2022-03-08	Trx Systems, Inc.	Crowd sourced mapping with robust structural features
CN104103211B *	2013-04-09	2016-08-24	广东美晨通讯有限公司	The construction method of indoor electronic map and system
US9417777B2 *	2013-07-09	2016-08-16	Google Inc.	Enabling quick display transitions between indoor and outdoor map data
US9645221B1 *	2013-12-17	2017-05-09	Booie LLC	Communication system and method
US9684425B2	2014-08-18	2017-06-20	Google Inc.	Suggesting a target location upon viewport movement
US9903735B2 *	2015-03-30	2018-02-27	International Business Machines Corporation	Route stabilization scrolling mode
US20170301232A1 *	2016-04-13	2017-10-19	Here Global B.V.	Intersection Map Message Creation for Vehicle Communication

JP2018051807A *	2016-09-26	2018-04-05	カシオ計算機株式会社	Printing device, printing method and program
EP3454073A1 *	2017-09-08	2019-03-13	SPIE SAG GmbH	System and method for locating within buildings
US11250697B2 *	2018-12-26	2022-02-15	Uatc, Llc	Missing traffic face detector
US11483393B1 *	2020-08-06	2022-10-25	Cpacket Networks Inc.	Apparatus and method for passive detection of middleboxes within computer networks

* Cited by examiner, † Cited by third party, ‡ Family to family citation

Similar Documents

Publication	Publication Date	Title
US7634354B2	2009-12-15	Location signposting and orientation
US10878637B2	2020-12-29	Directional and x-ray view techniques for navigation using a mobile device
USRE46737E1	2018-02-27	Method and apparatus for an augmented reality user interface
US8954275B2	2015-02-10	Schematic maps
Dünser et al.	2012	Exploring the use of handheld AR for outdoor navigation
US20130176384A1	2013-07-11	Method and System for Displaying Panoramic Imagery
US8326530B2	2012-12-04	System and apparatus for processing information, image display apparatus, control method and computer program
EP3147759B1	2019-06-26	A method and apparatus to browse and access downloaded contextual information
JP2012068481A	2012-04-05	Augmented reality expression system and method
CN108337664A	2018-07-27	Tourist attraction augmented reality interaction guide system based on geographical location and method
US8380427B2	2013-02-19	Showing realistic horizons on mobile computing devices
JP5912329B2	2016-04-27	Terminal device, icon output method, and program
Simon et al.	2006	Beyond location based–the spatially aware mobile phone
Ranasinghe et al.	2018	Pedestrian navigation and GPS deteriorations: User behavior and adaptation strategies
JP2007051878A	2007-03-01	Navigation system and mapping method
JP2002108204A	2002-04-10	Map data distributing device and terminal device
Fröhlich et al.	2007	Adding space to location in mobile emergency response technologies
Simon et al.	2007	Enabling spatially aware mobile applications
Neun et al.	2007	Techniques for LBS Cartography
Preston et al.	2012	GPS and Google Maps
JPH11148838A	1999-06-02	Portable guide device
JP2002181559A	2002-06-26	Scene display device
JP2002162240A	2002-06-07	Landscape display unit

Priority And Related Applications

Priority Applications (5)

Application	Priority date	Filing date	Title
US11/217,638	2005-08-31	2005-08-31	Location signposting and orientation
KR1020087004659A	2005-08-31	2006-08-03	Location signposting and orientation
EP06789495.6A	2005-08-31	2006-08-03	Location signposting and orientation
PCT/US2006/030643	2005-08-31	2006-08-03	Location signposting and orientation
CN200680031686.4A	2005-08-31	2006-08-03	Location signposting and orientation

Applications Claiming Priority (1)

Application	Filing date	Title
US11/217,638	2005-08-31	Location signposting and orientation

Legal Events

Date	Code	Title	Description
2005-09-28	AS	Assignment	**Owner name**: MICROSOFT CORPORATION, WASHINGTON **Free format text**: ASSIGNMENT OF ASSIGNORS INTEREST;ASSIGNOR:SALMRE, IVO WILLIAM;REEL/FRAME:016597/0607 **Effective date**: 20050831
2009-11-24	STCF	Information on status: patent grant	**Free format text**: PATENTED CASE
2012-12-03	FEPP	Fee payment procedure	**Free format text**: PAYOR NUMBER ASSIGNED (ORIGINAL EVENT CODE: ASPN); ENTITY STATUS OF PATENT OWNER: LARGE ENTITY
2013-03-18	FPAY	Fee payment	**Year of fee payment**: 4
2014-12-09	AS	Assignment	**Owner name**: MICROSOFT TECHNOLOGY LICENSING, LLC, WASHINGTON **Free format text**: ASSIGNMENT OF ASSIGNORS INTEREST;ASSIGNOR:MICROSOFT CORPORATION;REEL/FRAME:034543/0001 **Effective date**: 20141014
2017-06-01	FPAY	Fee payment	**Year of fee payment**: 8
2021-06-02	MAFP	Maintenance fee payment	**Free format text**: PAYMENT OF MAINTENANCE FEE, 12TH YEAR, LARGE ENTITY (ORIGINAL EVENT CODE: M1553); ENTITY STATUS OF PATENT OWNER: LARGE ENTITY **Year of fee payment**: 12

Data provided by IFI CLAIMS Patent Services

About Send Feedback Public Datasets Terms Privacy Policy Help