IEEE 100
The Authoritative Dictionary of IEEE Standards Terms

Seventh Edition



IEEE
Published by
Standards Information Network
IEEE Press

INTEL-1020
11,212,146

Trademarks and disclaimers

IEEE believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. IEEE is not responsible for any inadvertent errors.

Other tradenames and trademarks in this document are those of their respective owners.

The Institute of Electrical and Electronics Engineering, Inc.
3 Park Avenue, New York, NY, 10016-5997, USA

Copyright © 2000 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published December 2000. Printed in the United States of America.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

To order IEEE Press publications, call 1-800-678-IEEE.

Print: ISBN 0-7381-2601-2 *SP1122*

PDF ON CD-ROM
ISBN: 0-7381-3926-2 *SE127*

See other standards and standards-related product listings at: http://standards.ieee.org/

The publisher believes that the information and guidance given in this work serve as an enhancement to users, all parties must rely upon their own skill and judgement when making use of it. The publisher does not assume any liability to anyone for any loss or damage caused by any error or omission in the work, whether such error or omission is the result of negligence or any other cause. Any and all such liability is disclaimed.

This work is published with the understanding that the IEEE is supplying information through this publication, not attempting to render engineering or other professional services. If such services are required, the assistance of an appropriate professional should be sought. The IEEE is not responsible for the statements and opinions advanced in this publication.

Contents

Introduction v

How to Use This Dictionary vi

Categories vi

Trademarks ix

The Authoritative Dictionary of IEEE Standards Terms 1

Abstracts and Sources 1294

Non-IEEE Standards Sources 1351

Introduction

IEEE standards establish an authoritative common language that defines quality and sets technical criteria. By guaranteeing consistency and conformity through open consensus, IEEE standards add value to products, facilitate trade, drive markets, and ensure safety. That's why leading companies, organizations, and industries around the globe rely on them.

Critical components of this common language are the terms and definitions that are at the foundation of the vast body of IEEE standards. In the past decade alone, hundreds of terms—describing the latest tools, techniques, and best practices—have been added to the lexicon of IEEE standards.

In this newly updated *Authoritative Dictionary of IEEE Standards Terms,* professional experts and students alike will gain an in-depth understanding and appreciation for the breadth of coverage of IEEE standards terms and definitions not found in any other single source.

The seventh edition of IEEE 100 has been revised to include nearly 35 000 technical terms and definitions from over 800 standards—covering areas such as power and energy, communications, information technology, and transportation systems. In addition to an extensive list of widely used acronyms and abbreviations, this new edition also contains detailed abstracts of each term's associated standard(s). What's more, all definitions are augmented by a combination of indispensable information, including:

- Preferred and popular usage of each term
- Variations in meanings among different technical specialties
- Cross-indexing to related works
- Key explanatory notes for further term clarification

In preparing this latest edition of the Dictionary, we realized that the standards community desired more than just a compilation of IEEE standardized terms and definitions. They needed an authoritative resource created by the organization that develops and produces the standards from which the terms and definitions are derived—the IEEE. In addition, we determined the Dictionary needed to be not only user friendly, but also rich in information. In other words, it needed to be the *Authoritative Dictionary of IEEE Standards Terms.*

Susan K. Tatiner
Director, IEEE Standards Publishing Programs

IEEE Standards Project Editors for the seventh edition:
Kim Breitfelder
Don Messina

Additional assistance was provided by the IEEE Standards editorial staff.

How to Use This Dictionary

The terms defined in the Dictionary are listed in *letter-by-letter* alphabetical order. Spaces are ignored in this style of alphabetization, so *cable value* will come before *cab signal*. Descriptive categories associated with the term in earlier editions of the Dictionary will follow the term in parentheses. New categories appear after the definitions (see Categories, below), followed by the designation of the standard or standards that include the definition. If a standard designation is followed by the letter *s,* it means that edition of the standard was superseded by a newer revision and the term was not included in the revision. If a designation is followed by the letter *w,* it means that edition of the standard was withdrawn and not replaced by a revision. A bracketed number refers to the non-IEEE standard sources given in the back of the book.

Abstracts of the current set of approved IEEE standards are provided in the back of the book. It should be noted that updated information about IEEE standards can be obtained at any time from the IEEE Standards World Wide Web site at http://standards.ieee.org/.

Categories

The category abbreviations that are used in this edition of the Dictionary are defined below. This information is provided to help elucidate the context of the definition. Older terms for which no category could be found have had the category *Std100* assigned to them. Note that terms from sources other than IEEE standards, such as the National Electrical Code® (NEC®) or the National Fire Protection Association, may not be from the most recent editions; the reader is cautioned to check the latest editions of all sources for the most up-to-date terminology.

Categories sorted by abbreviation

AES	aerospace and electronic systems
AHDL	computer—Analog Hardware Descriptive Language
AMR	automatic meter reading and energy management
AP	antennas and propagation
ATL	computer—Abbreviated Test Language for All Systems
BA	computer—bus architecture
BT	broadcast technology
C	computer
CAS	circuits and systems
CE	consumer electronics
CHM	components, hybrids, and manufacturing technology
COM	communications
CS	control systems
DA	computer—design automation
DEI	dielectrics and electrical insulation
DESG	dispersed energy storage and generation
DIS	computer—distributed interactive simulation
ED	electron devices
EDU	education
EEC	electrical equipment and components
ELM	electricity metering
EM	engineering management
EMB	engineering in medicine and biology
EMC	electromagnetic compatibility
GRS	geoscience and remote sensing
GSD	graphic symbols and designations
IA	industry applications
IE	industrial electronics
II	information infrastructure
IM	instrumentation and measurement
IT	information theory

IVHS	intelligent vehicle highway systems
LEO	lasers and electro-optics
LM	computer—local and metropolitan area networks
MAG	magnetics
MIL	military
MM	computer—microprocessors and microcomputers
MTT	microwave theory and techniques
NEC	National Electrical Code
NESC	National Electrical Safety Code
NFPA	National Fire Protection Association
NI	nuclear instruments
NIR	non-ionizing radiation
NN	neural networks
NPS	nuclear and plasma sciences
ODM	computer—optical disk and multimedia platforms
OE	oceanic engineering
PA	computer—portable applications
PE	power engineering
PEL	power electronics
PQ	power quality
PSPD	power surge protective devices
PV	photovoltaics
QUL	quantities, units, and letter symbols
R	reliability
RA	robotics and automation
REM	rotating electrical machinery
RL	roadway lighting
S&P	computer—security and privacy
SB	stationary batteries
SE	computer—software engineering
SMC	systems, man, and cybernetics
SP	signal processing
Std100	Standard 100 legacy data
SUB	substations
SWG	power switchgear
T&D	transmission and distribution
TF	time and frequency
TRR	transformers, regulators, and reactors
TT	test technology
UFFC	ultrasonics, ferroelectrics, and frequency control
VT	vehicular technology

Categories sorted by name

aerospace and electronic systems	AES
antennas and propagation	AP
automatic meter reading and energy management	AMR
broadcast technology	BT
circuits and systems	CAS
communication	COM
components, hybrids, and manufacturing technology	CHM
computer	C
computer—Abbreviated Test Language for All Systems	ATL
computer—Analog Hardware Descriptive Language	AHDL
computer—bus architecture	BA
computer—design automation	DA
computer—distributed interactive simulation	DIS
computer—local and metropolitan area networks	LM
computer—microprocessors and microcomputers	MM
computer—optical disk and multimedia platforms	ODM
computer—portable applications	PA
computer—security and privacy	S&P
computer—software engineering	SE
consumer electronics	CE

control systems	CS
dielectrics and electrical insulation	DEI
dispersed energy storage and generation	DESG
education	EDU
electrical equipment and components	EEC
electricity metering	ELM
electromagnetic compatibility	EMC
electron devices	ED
engineering in medicine and biology	EMB
engineering management	EM
geoscience and remote sensing	GRS
graphic symbols and designations	GSD
industrial electronics	IE
industry applications	IA
information infrastructure	II
information theory	IT
instrumentation and measurement	IM
intelligent vehicle highway systems	IVHS
lasers and electro-optics	LEO
magnetics	MAG
microwave theory and techniques	MTT
military	MIL
National Electrical Code	NEC
National Electrical Safety Code	NESC
National Fire Protection Association	NFPA
neural networks	NN
non-ionizing radiation	NIR
nuclear and plasma sciences	NPS
nuclear instruments	NI
oceanic engineering	OE
photovoltaics	PV
power electronics	PEL
power engineering	PE
power quality	PQ
power switchgear	SWG
quantities, units, and letter symbols	QUL
reliability	R
roadway lighting	RL
robotics and automation	RA
rotating electrical machinery	REM
signal processing	SP
Standard 100 legacy data	Std100
stationary batteries	SB
substations	SUB
surge-protective devices	PSPD
systems, man, and cybernetics	SMC
test technology	TT
time and frequency	TF
transformers, regulators, and reactors	TRR
transmission and distribution	T&D
ultrasonics, ferroelectrics, and frequency control	UFFC
vehicular technology	VT

Trademarks

The following is a list of trademarks that may be used in *IEEE 100: The Authoritative Dictionary of IEEE Standards Terms.*

802 is a registered trademark of the Institute of Electrical and Electronics Engineers, Inc.

ABBET is a registered trademark of the Institute of Electrical and Electronics Engineers, Inc.

Adobe is a trademark of Adobe Systems Incorporated.

Analog devices is a trademark of Analog Devices, Inc.

Appletalk is a registered trademark of Apple Computer, Inc.

BOCA is a registered trademark of Building Officials and Code Administrators International, Inc.

BOOM is a registered trademark of Fakespace, Inc.

Centronics is a registered trademark of Genicom Corporation.

CompactPCI is a registered trademark of the PCI Industrial Computer Manufacturers Group.

Cray is a registered trademark of Cray Research, Inc.

DSSI is a registered trademark of Discreet Surveillance Systems.

Futurebus+ is a registered trademark of the Institute of Electrical and Electronics Engineers, Inc.

IBM is a registered trademark of International Business Machines, Inc.

Intel386 is a trademark of Intel Corporation.

Life Safety Code is a registered trademark of the National Fire Protection Association.

Mylar is a registered trademark of E.I. du Pont de Nemours and Company.

National Electrical Code is a registered trademark of the National Fire Protection Association.

NEC is a registered trademark of the National Fire Protection Association.

National Electrical Safety Code is a registered trademark and service mark of the Institute of Electrical and Electronics Engineers, Inc.

NESC is a registered trademark and service mark of the Institute of Electrical and Electronics Engineers, Inc.

Netbios is a registered trademark of International Business Machines, Inc.

Nomex is a registered trademark of E. I. Dupont de Nemours and Company.

NuBus is a registered trademark of Texas Instruments, Inc.

OpenBoot is a trademark of Sun Microsystems, Inc.

Open Software Foundation, OSF, and the OSF logo are registered trademarks of the Open Software Foundation, Inc.

PostScript is a trademark of Adobe Systems Incorporated.

POSIX is a registered certification mark of the Institute of Electrical and Electronics Engineers, Inc.

PS/2 is a registered trademark of International Business Machines, Inc.

SCSI is a registered trademark of SCSI Solutions.

SDI is a registered trademark of Maurice Siebenberg.

SPARC is a registered trademark of SPARC International, Inc.

SPARCstation is a trademark of SPARC International, Inc.

SPAsystem is a registered trademark of the Institute of Electrical and Electronics Engineers, Inc.

Stylized 8 (Futurebus+) is a registered trademark of the Institute of Electrical and Electronics Engineers, Inc.

Sun Microsystems is a registered trademark of Sun Microsystems, Inc.

TURBOchannel is a registered trademark of Digital Equipment Corporation.

Uniform Building Code is a trademark of the International Conference of Building Officials (ICBO).

UNIX is a registered trademark in the United States and other countries, licensed exclusively through X/Open Company Limited.

VAX is a registered trademark of Digital Equipment Corporation.

VAXBI is a registered trademark of Digital Equipment Corporation.

Verilog is a registered trademark of Cadence Design Systems, Inc.

Velcro is a registered trademark of Velcro Industries B. V.

Windows is a trademark of Microsoft Corporation.

X/Open is a registered trademark and the “X” device is a trademark of X/Open Company, Ltd.

H channel A wideband channel (i.e., a channel that contains multiples of 64 kbit/s).
(C/COM/LM) 8802-9-1996, 802.9a-1995w

HCI *See:* human/computer interface.

HCL *See:* relay, high, common, low.

HCP Horizontal coupling plane. *See also:* coupling plane.
(EMC) C63.16-1993

HC threshold voltage *See:* high conduction threshold voltage.

HDA *See:* head/disk assembly.

HDAM *See:* hierarchical direct access method.

HDBH *See:* high day busy-hour load.

HDBH load *See:* high day busy-hour load; time-consistent traffic measures.

H-display (1) (navigation aid terms) A type of radar display format. (AES/GCS) 172-1983w
(2) A B-display modified to include an indication of angle of elevation. The target appears as two closely spaced blips approximating a short bright line, the slope of which is in proportion to the tangent of the angle of target elevation.



H-display

(AES) 686-1997, [42]

HDL *See:* hardware description language; hardware design language.

HDLC *See:* high-level data link control.

head (1) A device that reads, records, or erases data on a storage medium. *Note:* For example, a small electromagnet used to read, write, or erase data on a magnetic drum or tape, or the set of perforating, reading, or marking devices used for punching, reading, or printing on paper tape.
(C) [20], [85]
(2) (hydroelectric power plants) The difference in hydraulic energy between two points, which includes the elevation head, pressure head, and velocity head.
(PE/EDPG) 1020-1988r
(3) (data management) The first data item in a list. *Synonym:* header. (C) 610.5-1990w
(4) (A) A device that reads, writes, or erases data on a storage medium. For example, a small electromagnet (magnetic head) used to read, write, or erase data on a magnetic drum or magnetic tape, or a device such as a laser that reads and writes data on an optical storage medium. *See also:* write head; read/write head; read head; magnetic head. **(B)** A device within an output device, such as a printer or display device, that controls the creation of images on the device. *See also:* scan head; plotting head; display head; print head. (C) 610.10-1994
(5) *See also:* head water benefits; gross head; rated head; critical head; net head.

head and torso simulator (HATS) A device that accurately reproduces the sound transmission and pick-up characteristics of the median head and torso of adult humans.
(COM/TA) 1206-1994, 1329-1999

head crash The sudden and complete failure of a disk drive caused by a physical collision between the read/write head and the surface of the recording medium. *Note:* Usually results in destruction of the head and part or all of the data on the medium. *See also:* disk crash. (C) 610.10-1994w

head/disk assembly In a magnetic disk device, an assembly that includes the magnetic disk, magnetic head, and an access mechanism. (C) 610.10-1994w

headed brush (rotating machinery) A brush having a top (cylindrical, conical, or rectangular) with a smaller cross section than the cross section of the body of the brush. *Note:* The length of the head shall not exceed 25 percent of the overall length. *See also:* brush. (EEC/LB) [101]

headend (1) (A) (broadband local area networks) The central location that has access to signals traveling in both inbound and outbound directions. The logical root of the broadband coaxial cable system. **(B) (broadband local area networks)** The physical location where the inbound and outbound paths are accessible. The headend is also called the central retransmission facility. (LM/C) 802.7-1989
(2) A point where two or more half-duplex data paths are joined on the communications network. (C) 610.7-1995
(3) In 10BROAD36, the location in a broadband system that serves as the root for the branching tree comprising the physical medium; the point to which all inbound signals converge and the point from which all outbound signals emanate.
(C/LM) 802.3-1998

headend port (broadband local area networks) (or ports) An interface where connection(s) may be made to insert signals or remove signals from the cable plant. The headend ports are usually referred to with a direction (inbound or outbound). Headend ports provide central access to the cable system.
(LM/C) 802.7-1989r

head-end system (railways) A system in which the electrical requirements of a train are supplied from a generator or generators, located on the locomotive or in one of the cars, customarily at the forward part of the train. *Note:* The generators may be driven by steam turbine, internal-combustion engine, or, if located in one of the cars, by a mechanical drive from a car axle. *See also:* axle-generator system.
(EEC/PE) [119]

header (1) A transverse raceway for electric conductors, providing access to predetermined cells of a cellular metal floor, thereby permitting the intallation of electric conductors from a distribution center to the cells. (NESC/NEC) [86]
(2) (A) (software) A block of comments placed at the beginning of a computer program or routine. **(B) (software)** Identification or control information placed at the beginning of a file or message. *Contrast:* trailer. (C) 610.12-1990
(3) (A) (data management) Pertaining to data that describes and pertains to other data. For example, the header record for a file might describe the format for the remaining records in the file. **(B) (data management)** *See also:* head.
(C) 610.5-1990
(4) *See also:* running header. (C) 610.2-1987
(5) A structure attached to or integral to the top of the heatsink used for structural performance and marking.
(C/BA) 1101.3-1993
(6) The contiguous control bits preceding a frame, packet, block, or other data stream of bits that contain information about the message such as the address, type of frame, and/or sequencing. *Contrast:* trailer. (C) 610.7-1995

header card A punch card that contains information identifying data in the cards that follow. *Contrast:* trailer card.
(C) 610.10-1994w

header hub (HH) The highest-level hub in a hierarchy of hubs. The HH broadcasts signals transmitted to it by lower level hubs or DTEs such that they can be received by all DTEs that may be connected to it either directly or through intermediate hubs. (LM/C) 802.3-1998, 610.7-1995

header label An internal label, immediately preceding the first record of a file, that identifies the file and contains data used in file control. (C) 610.5-1990w

HEADER packet A packet originating in the MTM-Bus Master that is the first packet of an MTM-Bus message. The HEADER packet includes an address and a command field. The address identifies which S-module(s) are to interpret and

IEEE 100
The Authoritative Dictionary of IEEE Standards Terms

Seventh Edition

IEEE
Published by
Standards Information Network
IEEE Press

Trademarks and disclaimers

IEEE believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. IEEE is not responsible for any inadvertent errors.

Other tradenames and trademarks in this document are those of their respective owners.

The Institute of Electrical and Electronics Engineering, Inc.
3 Park Avenue, New York, NY, 10016-5997, USA

Copyright © 2000 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published December 2000. Printed in the United States of America.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

To order IEEE Press publications, call 1-800-678-IEEE.

Print: ISBN 0-7381-2601-2 *SP1122*

See other standards and standards-related product listings at: http://standards.ieee.org/

The publisher believes that the information and guidance given in this work serve as an enhancement to users, all parties must rely upon their own skill and judgement when making use of it. The publisher does not assume any liability to anyone for any loss or damage caused by any error or omission in the work, whether such error or omission is the result of negligence or any other cause. Any and all such liability is disclaimed.

This work is published with the understanding that the IEEE is supplying information through this publication, not attempting to render engineering or other professional services. If such services are required, the assistance of an appropriate professional should be sought. The IEEE is not responsible for the statements and opinions advanced in this publication.

Library of Congress Cataloging-in-Publication Data

IEEE 100 : the authoritative dictionary of IEEE standards terms.—7th ed.
p. cm.
ISBN 0-7381-2601-2 (paperback : alk. paper)
1. Electric engineering—Dictionaries. 2. Electronics—Dictionaries. 3. Computer engineering—Dictionaries. 4. Electric engineering—Acronyms. 5. Electronics—Acronyms. 6. Computer engineering—Acronyms. I. Institute of Electrical and Electronics Engineers.

TK9 .I28 2000
621.3'03—dc21 00-050601

plicitly in a transaction-initiation message and returned in a transaction-completion message. (C/MM) 1212.1-1993

transaction initiation (request) A request generated by the initiator to start an action by the responder. An initiation message usually transfers a command and sometimes data. For a disk read I/O transaction, for example, the initiation transfers the address and command. (C/MM) 1212.1-1993

transaction, I/O *See:* I/O transaction.

transaction layer (1) The layer above the packet layer for use by applications. It is unspecified in this standard. *See also:* transaction. (C/BA) 1355-1995

(2) The layer, in a stack of three protocol layers defined for the Serial Bus, that defines a request-response protocol to perform bus operations of type read, write, and lock. (C/MM) 1394-1995

transaction matrix A matrix that identifies possible requests for database access and relates each request to information categories or elements in the database. (C) 610.12-1990

transaction record A record, representing one transaction, used to process data stored in a master file. *See also:* update transaction; null transaction; change transaction; delete transaction; add transaction. (C) 610.2-1987

transactor A magnetic device with an air-gapped core having an input winding which is energized with an alternating current and having an output winding which produces a voltage that is a function of the input current. *Note:* The term "transactor" is a contraction of the words "transformer" and "reactor." (SWG/PE/PSR) C37.110-1996, C37.100-1992

transadmittance For harmonically varying quantities at a given frequency, the ratio of the complex amplitude of the current at one pair of terminals of a network to the complex amplitude of the voltage across a different pair of terminals. *See also:* interelectrode transadmittance. (IM/HFIM) [40]

transadmittance compression ratio (electron tube) The ratio of the magnitude of the small-signal forward transadmittance of the tube to the magnitude of the forward transadmittance at a given input signal level. (ED) 161-1971w

transadmittance, forward *See:* forward transadmittance.

transceiver (1) (data transmission) The combination of radio transmitting and receiving equipment in a common housing, usually for portable or mobile use, and employing common circuit components for both transmitting and receiving. (PE) 599-1985w

(2) (navigation aids) A combination transmitter and receiver in a single housing, with some components being used by both parts. *See also:* transponder. (AES/GCS) 172-1983w

(3) (A) A device that both transmits and receives data. **(B)** A device that connects a host interface to a network. **(C)** A device that applies electronic signals to the cable and may sense collisions. *Note:* Definition (C) is contextually specific to IEEE Std 802.3. (C) 610.7-1995

transceiver cable A four-pair, shielded cable which interconnects a workstation to a transceiver or fan-out box. *Note:* This term is contextually specific to IEEE Std 802.3. *See also:* coaxial cable; trunk cable; drop cable; attachment unit interface cable. (C) 610.7-1995

transceiver chatter *See:* chatter.

transconductance The real part of the transadmittance. *Note:* Transconductance is, as most commonly used, the interelectrode transconductance between the control grid and the plate. At low frequencies, transconductance is the slope of the control-grid-to-plate transfer characteristic. *See also:* interelectrode transconductance; electron-tube admittances. (ED) 161-1971w

transconductance meter (mutual-conductance meter) An instrument for indicating the transconductance of a grid-controlled electron tube. *See also:* instrument. (EEC/PE) [119]

transcribe (electronic computation) To convert data recorded in a given medium to the medium used by a digital computing machine or vice versa. (C) 162-1963w

transcriber (electronic computation) Equipment associated with a computing machine for the purpose of transferring input (or output) data from a record of information in a given language to the medium and the language used by a digital computing machine (or from a computing machine to a record of information). (Std100) 270-1966w

transducer (1) (electrical heating applications to melting furnaces and forehearths in the glass industry) A device that is actuated by power from one system and supplies power in any other form to a second system. (IA) 668-1987w

(2) (communication and power transmission) A device by means of which energy can flow from one or more transmission systems or media to one or more other transmission systems or media. *Note:* The energy transmitted by these systems or media may be of any form (for example, it may be electric, mechanical, or acoustical), and it may be of the same form or different forms in the various input and output systems or media. (MIL/C/AP/ANT) [2], [85], 145-1983s

(3) (metering) A device to receive energy from one system and supply energy (of either the same or of a difference kind) to another system, in such a manner that the desired characteristics of the energy input appear at the output. (ELM) C12.1-1988

(4) (thyristor) A device which under the influence of a change in energy level of one form or in one system, produces a specified change in energy level of another form or in another system. (IA/IPC) 428-1981w

(5) A device for converting energy from one form to another. (C) 610.10-1994w

(6) A device converting energy from one domain into another. The device may either be a sensor or an actuator. (IM/ST) 1451.2-1997

(7) A device converting energy from one domain into another, calibrated to minimize the errors in the conversion process. A sensor or an actuator. (IM/ST) 1451.1-1999

transducer, active *See:* active transducer.

Transducer Block An instance of a subclass of `IEEE1451_TransducerBlock`. (IM/ST) 1451.1-1999

transducer conversion loss The ratio of the SAW power generated in the substrate at the transducer output to the power available in the circuit at the transducer input in decibels. (UFFC) 1037-1992w

Transducer Electronic Data Sheet (TEDS) (1) A data sheet describing a transducer stored in some form of electronically readable memory. (IM/ST) 1451.2-1997

(2) Several of the IEEE 1451.X standards use TEDS to provide a machine-readable specification of the characteristics of the transducer interface. (IM/ST) 1451.1-1999

transducer gain (1) The ratio of the power that the transducer delivers to the specified load under specified operating conditions to the available power of the specified source. *Notes:* 1. If the input and/or output power consist of more than one component, such as multifrequency signals or noise, then the particular components used and their weighting must be specified. 2. This gain is usually expressed in decibels. *See also:* transducer. (Std100) 270-1966w

(2) (two-port linear transducer) At a specified frequency, the ratio of the actual signal power transferred from the output port of the transducer to its load, to the available signal power from the source driving the transducer. (ED) 161-1971w

transducer, ideal *See:* ideal transducer.

Transducer Independent Interface The digital interface used to connect a Smart Transducer Interface Module to a Network Capable Application Processor. (IM/ST) 1451.2-1997

transducer interface The physical connection by which a transducer communicates with the control or data systems that it is a member of, including the physical connector, the signal wires used and the rules by which information is passed across the connection. (IM/ST) 1451.2-1997

transducer, line *See:* line transducer.

transducer loss The ratio of the available power of the specified source to the power that the transducer delivers to the speci-

PERKINS COIE BROWN & BAIN LIBRARY