


EX. 2005



US 20090015075A1

(19) **United States**(12) **Patent Application Publication**
Cook et al.(10) **Pub. No.: US 2009/0015075 A1**(43) **Pub. Date: Jan. 15, 2009**(54) **WIRELESS ENERGY TRANSFER USING
COUPLED ANTENNAS**(75) Inventors: **Nigel P. Cook**, El Caion, CA (US);
Paul Meier, Hamilton (NZ); **Lukas
Sieber**, Olten (CH); **Marc Secall**,
Fribourg (CH); **Hanspeter
Widmer**, Wohlenschwil (CH)Correspondence Address:
Law Office of Scott C Harris Inc
PO Box 1389
Rancho Santa Fe, CA 92067 (US)(73) Assignee: **Nigel Power, LLC**(21) Appl. No.: **11/775,168**(22) Filed: **Jul. 9, 2007****Publication Classification**(51) **Int. Cl.**
H02J 17/00 (2006.01)(52) **U.S. Cl.** **307/149**(57) **ABSTRACT**

A power transmission system produces a magnetic field at a source that is wirelessly coupled to a receiver. Both the source and receiver are capacitively coupled LC circuits, driven at or near resonance.






FIG. 1




FIG. 2





FIG. 3






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B

APPROXIMATE DISTANCE [INCH]	APPROXIMATE POWER [W]
39	0.006
35.5	0.008
31.5	0.013
27.5	0.022
23.5	0.050
20	0.100
16	0.350
12	0.790
10	1.260
8	1.258
6	1.000
4	0.560

USABLE
RANGE

FIG. 10C

WIRELESS ENERGY TRANSFER USING COUPLED ANTENNAS

BACKGROUND

[0001] It is desirable to transfer electrical energy from a source to a destination without the use of wires to guide the electromagnetic fields. This wireless transfer of energy has been attempted historically by many electromagnetic field experts—most notably Nikola Tesla in the early 20th century. A difficulty of these previous attempts has been low efficiency together with an inadequate amount of power delivered.

SUMMARY

[0002] The present application teaches a wireless electrical energy transfer, and teaches specific techniques for that energy transfer.

[0003] Aspects describe the specific antennas, and specific types of coupling between the transmitter and receiver.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] These and other aspects will now be described in detail with reference to the accompanying drawings, wherein:

[0005] FIG. 1 shows a block diagram of a magnetic wave based wireless power transmission system;

[0006] FIG. 2 illustrates circuit diagrams of the circuits in the FIG. 1 diagram;

[0007] FIG. 3 illustrates an exemplary near field condition plot;

[0008] FIGS. 4-8 illustrate exemplary transmit antennas;

[0009] FIG. 9 illustrates an exemplary receiving antenna; and

[0010] FIGS. 10A-10C illustrate data plots of that receiving antenna.

DETAILED DESCRIPTION

[0011] The present application describes transfer of energy from a power source to a power destination via electromagnetic field coupling. Embodiments describe techniques for new coupling structures, e.g., transmitting and receiving antennas.

[0012] A preferred embodiment is shown in which the main coupling occurs via inductive coupling, using primarily a magnetic field component. In the embodiment shown in FIG. 1, for example, energy is formed as a stationary magnetic wave in the area of the transmitting antenna. The energy that is produced is at least partly a non-radiative, stationary magnetic field. The produced field is not entirely magnetic, nor entirely stationary, however at least a portion is. Unlike a traveling electromagnetic wave, which would continue propagating into space and have its energy wasted, at least a portion of the stationary magnetic wave remains in the area of the transmitting antenna and is rendered usable by the disclosed techniques.

[0013] Other embodiments may use similar principles of the embodiments are equally applicable to primarily electrostatic and/or electrodynamic field coupling as well. In general, an electric field can be used in place of the magnetic field, as the primary coupling mechanism.

[0014] One aspect of the embodiment is the use of a high efficiency via increasing the so-called Q factor of the coupling structures (primarily the antennas) at the self-resonant frequency used for the sinusoidal waveform of the electromagnetic field, voltage or current used. We have discovered

that the efficiency and amount of power is superior for a system which uses a single, substantially un-modulated sine wave. In particular, the performance is superior to a wide-band system which attempts to capture the power contained in a wideband waveform or in a plurality of distinct sinusoidal waveforms of different frequencies. Other embodiments may use less pure waveforms, in recognition of the real-world characteristics of the materials that are used.

[0015] Techniques are described herein which enable small resonant antennas with relatively high Q factors. The Q of a resonant device is the ratio of the resonant frequency to the so-called “three dB” or “half power” bandwidth of the resonant device. While there are several “definitions,” all are substantially equivalent to each other, to describe Q in terms of measurements or the values of resonant circuit elements.

[0016] A basic embodiment is shown in FIG. 1. A power transmitter assembly 100 receives power from a source, for example, an AC plug 102. A frequency generator 104 is used to couple the energy to an antenna 110, here a resonant antenna. The antenna 110 includes an inductive loop 111, which is inductively coupled to a high Q resonant antenna part 112. The resonant antenna includes a number N of coil loops 113 each loop having a radius R_L . A capacitor 114, here shown as a variable capacitor, is in series with the coil 113, forming a resonant loop. In the embodiment, the capacitor is a totally separate structure from the coil, but in certain embodiments, the self capacitance of the wire of forming the coil can form the capacitance 114.

[0017] The frequency generator 104 can be preferably tuned to the antenna 110, and also selected for FCC compliance.

[0018] This embodiment uses a multidirectional antenna. 115 shows the energy as output in all directions. The antenna 100 is non-radiative, in the sense that much of the output of the antenna is not electromagnetic radiating energy, but is rather a magnetic field which are more stationary. Of course, part of the output from the antenna will in fact radiate.

[0019] Another embodiment may use a radiative antenna.

[0020] A receiver 150 includes a receiving antenna 155 placed a distance D away from the transmitting antenna 110. The receiving antenna is similarly a high Q resonant coil antenna 151 having a coil part and capacitor, coupled to an inductive coupling loop 152. The output of the coupling loop 152 is rectified in a rectifier 160, and applied to a load. That load can be any type of load, for example a resistive load such as a light bulb, or an electronic device load such as an electrical appliance, a computer, a rechargeable battery, a music player or an automobile.

[0021] The energy can be transferred through either electrical field coupling or magnetic field coupling, although magnetic field coupling is predominantly described herein as an embodiment.

[0022] Electrical field coupling provides an inductively loaded electrical diode that is an open capacitor or dielectric disk. Extraneous objects may provide a relatively strong influence on electric field coupling.

[0023] Magnetic field coupling may be preferred, since it has a weak influence on any extraneous objects and many extraneous objects have the same magnetic properties as “empty” space.

[0024] The embodiment describes a magnetic field coupling using a capacitively loaded magnetic dipole. Such a dipole is formed of a wire loop forming at least one loop or

turn of a coil, in series with a capacitor that electrically loads the antenna into a resonant state.

[0025] FIG. 2 shows an equivalent circuit for the energy transfer. The transmit circuit **100** is a series resonant circuit with RLC portions that resonate at the frequency of the high frequency generator **205**. The transmitter includes a series resistance **210**, and inductive coil **215**, and the variable capacitance **220**. This produces the magnetic field **M** which is shown as magnetic lines of force **225**.

[0026] The signal generator **205** has an internal resistance that is preferably matched to the transmit resonator's resistance at resonance by the inductive loop. This allows transferring maximum power from the transmitter to the receiver antenna.

[0027] The receive portion **150** correspondingly includes a capacitor **250**, transformer coil **255**, rectifier **260**, and regulator **261**, to provide a regulated output voltage. The output is connected to a load resistance **265**. FIG. 2 shows a half wave rectifier, but it should be understood that more complex rectifier circuits can be used. The impedance of the rectifier **260** and regulator **261** is matched to the resistance of the receive resonator at resonance. This enables transferring a maximum amount of power to the load. The resistances take into account skin effect/proximity effect, radiation resistance, as well as both internal and external dielectric loss.

[0028] A perfect resonant transmitter will ignore, or minimally react with, all other nearby resonant objects having a different resonant frequency. However, when a receiver that has the proper resonant frequency encounters the field of the transmitting antenna **225**, the two couple in order to establish a strong energy link. In effect, the transmitter and receiver operate to become a loosely coupled transformer.

[0029] The inventors have discovered a number of factors that improve the transfer of power from transmitter to receiver.

[0030] Q factor of the circuits, described above, can assist with certain efficiencies. A high Q factor allows increased values of current at the resonant frequency. This enables maintaining the transmission over a relatively low wattage. In an embodiment, the transmitter Q may be **1400**, while the receiver Q is around **300**. For reasons set forth herein, in one embodiment, the receiver Q may be much lower than the transmitter Q, for example $\frac{1}{4}$ to $\frac{1}{5}$ the transmitter Q. However, other Q factors may be used.

[0031] High Q has a corresponding disadvantage of narrow bandwidth effects. Such narrow bandwidth have typically been considered as undesirable for data communications. However, the narrow bandwidth can be used in power transfer. When a high Q is used, the transmitter signal is sufficiently pure and free of undesired frequency or phase modulation to allow transmission of most of its power over this narrow bandwidth.

[0032] For example, an embodiment may use a resonant frequency of 13.56 MHz and a bandwidth of around 9 kHz. This is highly usable for a substantially un-modulated fundamental frequency. Some modulation on the fundamental frequency may be tolerated or tolerable, however, especially if other factors are used to increase the efficiency. Other embodiments use lower Q components, and may allow correspondingly more modulation on the fundamental.

[0033] An important feature may include use of a frequency which is permitted by regulation, such as FCC regulations. The preferred frequency in this exemplary embodiment is 13.56 MHz but other frequencies may be used as well.

[0034] In addition, the capacitors should be able to withstand high voltages, for example as high as 1000 V, since the resistance may be small in relation to the capacitive reactance. A final important feature is the packaging: the system should be in a small form factor. The Q factor can be expressed as:

$$Q = \frac{1}{R} \cdot \sqrt{\frac{L}{C}}$$

$R = R_{\text{rad}} + R_{\text{loss}}$
 $C = C_{\text{self}} + C_{\text{ed}}$

[0035] Where:

[0036] The value L represents the inductance of the resonator. This inductance is given by the geometry of the resonator and its antenna.

[0037] The value C represents capacitance, including an inherent capacitance which stores energy in the electric field. Both the self capacitance of the inductor, as well as an external capacitor form part of the total capacitance.

[0038] The value R represents the resistance of the resonator, formed by the coil resistance of the inductor, and the radiation resistance. These collectively lower the Q of the resonator as R increases.

[0039] All of these values together form the Q or quality factor of the resonator. Q represents in general how well the resonator generates and receives magnetic energy. By keeping C and R low, the L of the coil may be the most predominant factor.

[0040] It is desirable to increase the Q as much as possible in an embodiment. Accordingly, certain values should be considered.

[0041] As previously described, high resistance brings down the Q, since the Q is inversely proportional to R. R has two parts, the radiation resistance, as well as an ohmic loss process.

[0042] For a loop antenna, the radiation resistance equals

$$R_{\text{rad}} = 320 \cdot \pi^4 \left(\frac{\pi \cdot r_A^2}{\lambda^2} \right)^2 \cdot N^2$$

where r_A represents the radius of the coil.

[0043] Therefore, the radiation is dependent on frequency to the fourth power, radius to the fourth power, and the number of turns squared.

[0044] Loss resistance can be evaluated as

$$R_{\text{loss}} = \frac{N}{2 \cdot b} \cdot \sqrt{\frac{f \cdot \mu_0}{\sigma \cdot \pi}} \cdot 2 \cdot \pi \cdot r_A \cdot (1 + \alpha)$$

Note that this is dependent on the square root of frequency, the wire dimensions and material, and the so-called proximity effect.

[0045] The values for capacitance are:

$$C_e C_H = \frac{2 \cdot \pi^2 \cdot b \cdot \epsilon_0}{\ln \left(\frac{P}{2 \cdot b} + \sqrt{\left(\frac{P}{2 \cdot b} \right)^2 - 1} \right)}$$

$$C_{self} = \frac{C_H}{N - 1}$$

Note that this is also dependent on the physical dimensions of the wires, as well as the number of turns.

[0046] For a plate capacitor, the external capacitance is approximately equal to

$$C_{ext} = \frac{\epsilon_0 \cdot \epsilon_r \cdot A}{d}$$

which is dependent on the area of the plates, as well as the distance d between the two plates.

[0047] Finally, the inductance

$$L = \frac{\mu_0 \cdot \pi \cdot N^2 \cdot r_A^2}{0.9 \cdot r_A + l_A}$$

which is dependent on number of turns squared and radius squared.

[0048] As explained above, the high Q may create high voltages, e.g., up to 5 KV. These reactive voltages may be evaluated according to:

$$U_{L,C} = Q \cdot \sqrt{P \cdot R}$$

[0049] An important feature of an embodiment is based on the relationship between the power source, e.g., the transmitter, and the load, e.g. the receiver. The efficiency of the coupling between source and load is based on the Q factors of the circuits, mechanical characteristics of the circuits (mostly, wire sizing), and the distance therebetween.

[0050] For an efficiency p less than 0.3, the efficiency can theoretically be expressed as

$$\eta(d) \cong \frac{r_{A,i}^2 \cdot r_{A,r}^2 \cdot Q_i \cdot Q_r \cdot K_r \cdot K_t}{16d^6}$$

[0051] Note that this is proportional to the Q², inversely proportional to the sixth power of distance, and positively proportional to the radius.

[0052] For energy transfer in the near field, a special kind of analysis must be considered. The inventors found that usable power can be harvested from the stationary wave that is set up in the near field of an RF coil. For purposes of this embodiment, the near field is considered to be $\lambda/2$ for the frequency of interest. FIG. 3 illustrates how the near field for 13.56 MHz extends approximately 3.5 m from the center of the transmit antenna.

[0053] Another constraint may be imposed by radiation exposure limits.

[0054] At the 13.56 MHz frequency, the exposure must be kept below 60 dBuA/m [express in W/m² instead of dBuA/m]. Another objective, therefore, requires maintaining this value or less at 10 m.

[0055] Another important issue is attributable to the specific antenna type.

[0056] FIG. 4 illustrates a first embodiment that uses a circular loop on a wooden frame. The loop is connected to a capacitor 400, which may be a variable capacitor with a varying part 405, in series with the main loop 410. This may be formed of one or several loops of wire, preferably, coaxially wound. The coil is mounted to a wooden frame 415, by mount devices 418.

[0057] This antenna was demonstrated to have a Q of around 90 at 3 MHz. It has high losses due to its small copper surface.

[0058] FIG. 5 illustrates a solenoid antenna which can operate between 9 and 15 MHz, and has been demonstrated to have a Q of 1300. The Q may be greatly increased, for example up to 2200, if suspended in air via insulating strings away from solid objects. The loop portion of this antenna 500 induces power into the solenoid portion 505. The solenoid antenna of FIG. 5 may produce the best performance in certain circumstances.

[0059] A rectangular loop antenna is shown in FIG. 6. This antenna is formed of a loop portion 700, capacitive portions 705, 706, which may be variable capacitors. This antenna has a Q of about 700, over its tunable range of 12 to 14 MHz. Note that both the inducing part and the regular loop are substantially coplanar, and hence that this form factor is usable in a laptop computer, for example.

[0060] FIG. 7 illustrates a shielded flat-panel antenna, formed by a number of separate loops 700, 702, 704 all held together. Each loop 700 has a corresponding variable capacitor 706. This antenna produced a Q of about 100 between 8 and 10 MHz. While it may have a low L/C ratio due to the capacitance of the coax cable, it has other packaging advantages.

[0061] An unshielded flatbed antenna is shown in FIG. 8 comprising the inductive loop 800, and the flat-panel antenna 805 formed of a single loop 805, in series with capacitor 810. This has a Q of about 450, and is tunable between around 9 and 15 MHz.

[0062] Based on all of these tests and experiments, applicants have concluded that wireless power coupling using antennas of this type allows a transfer efficiency of 10% or greater for short range application, less than 2 m. At the same time, the transferable power under the legal exposure constraints is less than 5 W. For a given Q factor, the transfer efficiency becomes independent of frequency. However, there may be an optimum frequency for each antenna form factor.

[0063] An embodiment showing a receive antenna is shown in FIG. 9. It is a very small manually tunable antenna on a 40×90 mm flat panel. The antenna has multiple coils of wires, in series with two variable capacitors 900, 902. Other analogous sizes may also be used—for example, another embodiment describes a small antenna of 60×100 mm, flat-panel, manually tunable. Yet another is a medium antenna 120×200 mm, flat-panel, manually tunable. A large antenna is 240×310 mm, also manually tunable.

[0064] FIGS. 10A-10C illustrates graphically the actual results for use with the FIG. 9 antenna. FIG. 10A illustrates the measured resonance frequency of 13.9 MHz. FIG. 10B illustrates how this antenna has a 3 dB point at about 1 foot.

Note, unexpectedly, however, that below 10 inches, the received power value goes down, not up. This is because the receiving antenna, being in the near field of the transmitting antenna actually interacts with the transmitting antenna field by detuning the transmitter. An important feature, therefore, is to maintain this detuning within a determinate limit and design the system intending to maintain the distance between and transmitter and receiver far enough apart so that the antenna can avoid or minimize undesired de-tuning. However, the antenna systems are intentionally allowed to have both maximum and minimum usable distances. FIG. 10C shows a chart with values, thereby illustrating the usable range within which these exemplary antennas can be used. Here that distance range is between approximately 0.15 to 0.2 m (6-8 inches) and 0.5 m (20 inches). However, with other antenna pairs, the minimum distance may be as low as 0.05 m (2 inches), or as high as 0.3 m (12 inches).

[0065] The general structure and techniques, and more specific embodiments which can be used to effect different ways of carrying out the more general goals are described herein.

[0066] Although only a few embodiments have been disclosed in detail above, other embodiments are possible and the inventors intend these to be encompassed within this specification. The specification describes specific examples to accomplish a more general goal that may be accomplished in another way. This disclosure is intended to be exemplary, and the claims are intended to cover any modification or alternative which might be predictable to a person having ordinary skill in the art. For example, where a variable capacitor is mentioned, a fixed capacitor may be substituted.

[0067] The preferred implementation described here utilizes a single, dipole series resonant antenna for the sake of simplicity, but in general an array of multiple antennas may be used to shape or direct most of the electromagnetic power in the wave towards the receive antenna and not towards "empty" space.

[0068] Methods for control of directionality via adjustment of sinusoidal wave phase and amplitude in each antenna is well known to those skilled in the other embodiments may optionally make use of the completely different process that we call "sniffing" to determine where the receiver is located before transmitting full power to it. Before full power flow is established, we turn on the transmitter for limited time intervals to scan the space surrounding the transmitter by means of directive beam for the purpose of determining the presence and location of a receiver, if any.

[0069] Furthermore, when comparing the techniques of generating an intentionally partially evanescent wave vs. the technique of generating a partially non-evanescent wave, in many configurations there may be little practical difference between the two results. Partly because portions of near field are evanescent even when the design intent is to produce a non-evanescent wave. Therefore, the mere presence of evanescent waves in a portion of the space near the transmit antenna is a historically well-known phenomenon and does not imply that we are utilizing the properties of evanescent waves in any particular way.

[0070] Also, the inventors intend that only those claims which use the words "means for" are intended to be interpreted under 35 USC 112, sixth paragraph. Moreover, no limitations from the specification are intended to be read into any claims, unless those limitations are expressly included in the claims. The computers described herein may be any kind of computer, either general purpose, or some specific purpose

computer such as a workstation. The computer may be an Intel (e.g., Pentium or Core 2 duo) or AMD based computer, running Windows XP or Linux, or may be a Macintosh computer. The computer may also be a handheld computer, such as a PDA, cellphone, or laptop.

[0071] The programs may be written in C or Python, Java, Brew or any other programming language. The programs may be resident on a storage medium, e.g., magnetic or optical, the computer hard drive, a removable disk or media such as a memory stick or SD media, wired or wireless network based or Bluetooth based Network Attached Storage (NAS), or other removable medium. The programs may also be run over a network, for example, with a server or other machine sending signals to the local machine, which allows the local machine to carry out the operations described herein.

[0072] Where a specific numerical value is mentioned herein, it should be considered that the value may be increased or decreased by 20%, while still staying within the teachings of the present application, unless some different range is specifically mentioned. Where a specified logical sense is used, the opposite logical sense is also intended to be encompassed.

What is claimed is:

1. A method of transmitting power wirelessly, comprising: driving a series resonant antenna at a value near its resonant frequency to produce a magnetic field output, said non radiative antenna formed of a combination of resonant parts, including at least an inductive part formed by a wire loop, and a capacitor part that is separate from a material forming the inductive part; and maintaining at least one characteristic of said antenna such that its usable range has a minimum usable distance over which power can be received, which minimum distance is set by a detuning effect when a receiver gets too close to said antenna.
2. A method as in claim 1, further comprising receiving the magnetic field in a receiving antenna, said receiving antenna also having a series resonant part, and producing usable power from said receiving antenna, and coupling said usable power to a load.
3. A method as in claim 1, wherein said minimum useable distance is between 6 and 8 inches.
4. A method as in claim 1, wherein said minimum usable distance is between 2 and 4 inches.
5. A method as in claim 1, further comprising setting the resonant frequency to a value of approximately 13.56 MHz.
6. A method as in claim 1, wherein said non-radiative antenna has a Q value of approximately 1400.
7. A method as in claim 1, further comprising using a capacitor part which is capable of withstanding at least 1000 V.
8. A method as in claim 1, further comprising using a signal generator to produce said driving, and matching an impedance of the signal generator to a resistance of the antenna at resonance.
9. A method as in claim 1, wherein said antenna has a substantially round outer form factor.
10. A method as in claim 1, wherein said antenna has a substantially rectangular outer form factor.
11. A method as in claim 1, wherein said antenna is a dipole that includes a first inductive part, coupled to receive said driving, and a second part, which is physically separated from said inductive part, said second part formed of at least one loop of wire in series with said capacitor.

12. A method as in claim 11, wherein said an inductive part and said second part have different outer form factors.

13. A method as in claim 11, wherein said inductive part and said outer part have substantially the same outer form factors.

14. A method as in claim 11, wherein said second part is electrically connected to said capacitor part.

15. A method as in claim 13, wherein said capacitor part is a variable capacitor.

16. A method, comprising:
transmitting a magnetic field using a first resonant transmission part;
receiving said magnetic field in a second resonant transmission part; and
in said second resonant transmission part, using power from the magnetic field.

17. A method as in claim 16, further comprising using said power in said second resonant transmission part to drive a load.

18. A method as in claim 16, further comprising detuning at least one of said transmitting or said receiving when said second resonant transmission part gets closer than a predetermined amount to said first resonant transmission part.

19. A method as in claim 16, wherein said transmitting comprises using a capacitively loaded magnetic dipole for transmitting the magnetic field.

20. A method, comprising:
forming a magnetic field using a first part;
coupling said magnetic field to a second part that forms a loosely coupled transformer with said first part, where said second part is further than 6 inches from said first part; and
in said second part, recovering power from the coupled magnetic field.

21. A method as in claim 20, further comprising using said power in said second part to drive a load.

22. A method as in claim 20, further comprising detuning at least one of said transmitting or said receiving when said second part gets closer than a predetermined amount to said first part.

23. A method as in claim 20, wherein said transmitting comprises using a capacitively loaded magnetic dipole for transmitting the magnetic field.

24. A system comprising:
a series resonant antenna;
a driving part for said series resonant antenna, driving said antenna at a value near its resonant frequency to produce a magnetic field output, said antenna formed of a combination of series resonant parts, including at least an inductive part formed by a wire loop, and a capacitor part that is separate from a material forming the inductive part, and

wherein said series resonant antenna has at least one characteristic such that its usable range has a minimum usable distance over which power can be received, which minimum distance is set by a detuning effect when a receiver gets too close to said antenna.

25. A system as in claim 24, further comprising a receiving antenna, also having a series resonant part that has a corresponding resonance to said resonant frequency of said antenna, and has a connection outputting usable power to a load.

26. A system as in claim 25, wherein said minimum bound useable distance is between 6 and 8 inches.

27. A system as in claim 24, wherein said minimum usable distance is between 2 and 4 inches.

28. A system as in claim 24, wherein the resonant frequency is set to a value of approximately 13.56 MHz.

29. A system as in claim 24, wherein said antenna has a Q value of approximately 1400.

30. A system as in claim 24, wherein said capacitor part is capable of withstanding at least 1000 V.

31. A system as in claim 24, further comprising signal generator that drives said antenna, said signal generator having an impedance of the signal generator that is matched to a resistance of the non radiative antenna at resonance.

32. A system as in claim 24, wherein said antenna has a substantially round outer form factor.

33. A system as in claim 24, wherein said antenna has a substantially rectangular outer form factor.

34. A system as in claim 24, wherein said antenna is a dipole that includes a first inductive part, coupled to receive said driving, and a second part, which is physically separated from said inductive part, said second part loop, formed of at least one loop of plural coils of wire in series with said capacitor.

35. A system as in claim 34, wherein said an inductive part and said second part have different outer form factors.

36. A system as in claim 34, wherein said inductive part and said outer part have substantially the same outer form factors.

37. A system as in claim 34, wherein said second part is electrically connected to said capacitor part.

38. A system as in claim 13, wherein said capacitor part is a variable capacitor.

39. A system, comprising:
a first resonant transmission part formed of a capacitively loaded magnetic dipole antenna;
a second resonant reception part, tuned to have similar resonant characteristics to said first resonant transmission part, receiving a magnetic field therefrom, and producing a power output from the magnetic field.

40. A system, comprising:
a first LC circuit, connected to receive a signal that forms a magnetic field; and
a second LC circuit that forms a loosely coupled transformer with said first LC circuit, where said second part is further than 6 inches from said first part, and has a connection for recovering power from the coupled magnetic field.

41. A system as in claim 40, wherein said first LC circuit includes a capacitively loaded magnetic dipole for transmitting the magnetic field.

* * * * *