

Independent Claim Comparison

U.S. 10,494,251 (baseline) vs. U.S. 10,974,955 (marked revisions)

1. A distribution station comprising:

~~a mobile trailer;~~

a container including first and second opposed side walls that join first and second opposed end walls;

a pump ~~on~~in the ~~mobile trailer~~container;

first and second manifolds ~~on~~in the ~~mobile trailer~~container and fluidly connected with the pump;

a plurality of reels ~~on~~in the ~~mobile trailer~~container;

a plurality of hoses, each said hose connected with a different one of the reels, wherein a portion of the reels are connected to be fed from the first manifold and another portion of the reels are connected to be fed from the second manifold;

a plurality of valves ~~on~~in the ~~mobile trailer~~container, each said valve situated between one of the first or second manifolds and a respective different one of the reels;

a plurality of fluid level sensors, each said fluid level sensor being associated with a different one of the hoses; and

a controller configured to individually open and close the valves responsive to the fluid level sensors.

11. A distribution station comprising:

~~a mobile trailer;~~

a container including first and second opposed side walls that join first and second opposed end walls;

at least one pump ~~on~~in the ~~mobile trailer~~container;

at least one manifold ~~on~~in the ~~mobile trailer~~container and fluidly connected with the at least one pump;

a plurality of reels ~~on~~in the ~~mobile trailer~~container, each said reel individually connected with the at least one manifold;

a plurality of hoses, each said hose connected with a different one of the reels;

a plurality of valves ~~on~~in the ~~mobile trailer~~container, each said valve situated between the at least one manifold and a respective different one of the reels;

a plurality of fluid level sensors, each said fluid level sensor connectable to an end of a different one of the hoses; and

a controller configured to individually open and close the valves responsive to the fluid level sensors.

19. A distribution station comprising:

~~a mobile trailer;~~

a container including first and second opposed side walls that join first and second opposed end walls;

at least one pump ~~on~~in the ~~mobile trailer~~container;

at least one manifold ~~on~~in the ~~mobile trailer~~container and fluidly connected with the at least one pump;

a register between the at least one pump and the at least one manifold;

a plurality of reels ~~on~~in the ~~mobile trailer~~container and connected with the at least one manifold;

a plurality of hoses, each said hose connected with a different one of the reels;

a plurality of valves ~~on~~in the ~~mobile trailer~~container, each said valve situated between the at least one manifold and a respective different one of the reels;

a plurality of fluid level sensors, each said fluid level sensor being associated with a different one of the hoses; and

a controller configured to individually open and close the valves responsive to the fluid level sensors.

20. The distribution station as recited in claim 19, wherein the register is configured to generate measurement data representative of an amount of fluid provided from the at least one pump, and the register is in communication with the controller to send the measurement data to the controller.