US 20190216373A1

(19) **United States**

(12) **Patent Application Publication**

(10) **Pub. No.: US 2019/0216373 A1**

(43) **Pub. Date: Jul. 18, 2019**

Harper

(54) **METHODS AND SYSTEMS FOR EARLY SIGNAL ATTENUATION DETECTION AND PROCESSING**

(71) Applicant: **ABBOTT DIABETES CARE INC.**, Alameda, CA (US)

(72) Inventor: **Wesley Scott Harper**, Alameda, CA (US)

(21) Appl. No.: **16/228,910**

(22) Filed: **Dec. 21, 2018**

Related U.S. Application Data

(63) Continuation of application No. 15/061,774, filed on Mar. 4, 2016, now Pat. No. 10,194,844, which is a continuation of application No. 13/925,694, filed on Jun. 24, 2013, now Pat. No. 9,310,230, which is a continuation of application No. 12/769,635, filed on Apr. 28, 2010, now Pat. No. 8,483,967.

(60) Provisional application No. 61/173,600, filed on Apr. 29, 2009.

Publication Classification

(51) **Int. Cl.**

A61B 5/145	(2006.01)
G01N 31/22	(2006.01)
G01N 33/66	(2006.01)
G01D 18/00	(2006.01)
A61B 5/1473	(2006.01)
G16H 40/40	(2006.01)
A61B 5/1495	(2006.01)

(52) **U.S. Cl.**

CPC ***A61B 5/14532*** (2013.01); ***G01N 31/22*** (2013.01); ***G01N 33/66*** (2013.01); ***A61B 5/1495*** (2013.01); ***A61B 5/1473*** (2013.01); ***G16H 40/40*** (2018.01); ***G01D 18/00*** (2013.01)

(57) **ABSTRACT**

Provided are methods and apparatus for receiving sensor data from an analyte sensor of a sensor monitoring system, processing the received sensor data with time corresponding calibration data, outputting the processed sensor data, detecting one or more adverse conditions associated with the sensor monitoring system, disabling the output of the sensor data during the adverse condition time period, determining that the one or more detected adverse conditions is no longer present in the sensor monitoring system, retrieving the sensor data during the adverse condition time period, processing the retrieved sensor data during the adverse condition time period, and outputting the processed retrieved sensor data.



DEXCOM EXHIBIT 1208


100
101
SENSOR UNIT
102
TRANSMITTER UNIT
103
104
PRIMARY RECEIVER UNIT
105
DATA PROCESSING TERMINAL/INFUSION SECTION
106
SECONDARY RECEIVER UNIT

FIG. 1


To Receiver 104
205
207
SERIAL COMMUNICATION SECTION
206
RF TRANSMITTER
POWER SUPPLY
102
208
209
PROCESSOR
CLOCK
204
ANALOG INTERFACE
LEAK DETECTION
USER INPUT
TEMPERATURE MEASUREMENT SECTION
201
W
G
R
C
210
211
212
213
214
202
203

FIG. 2


104
TO DATA PROCESSING TERMINAL 105
309
SERIAL COMMUNICATION SECTION
OUTPUT/DISPLAY
310
306
POWER SUPPLY
307
PROCESSING & STORAGE
POWER CONVERSION AND MONITORING SECTION
308
TEST STRIP INTERFACE
RF RECEIVER
USER INPUT
TEMPERATURE MONITOR SECTION
CLOCK
301
FROM TRANSMITTER 102
302
303
304
305

FIG. 3


START
RECEIVE ANALYTE RELATED SENSOR DATA 410
CALIBRATED? 420
N
Y
PROCESS SENSOR DATA 430
STORE ANALYTE RELATED SENSOR DATA 450
DISPLAY PROCESSED SENSOR DATA 440
END

FIG. 4


START
RECEIVE ANALYTE RELATED SENSOR DATA 510
CALIBRATED? 520
N
Y
PROCESS SENSOR DATA 530
STORE ANALYTE RELATED SENSOR DATA 550
DISPLAY PROCESSED SENSOR DATA 540
DISABLE DISPLAY 560
END

FIG. 5


START
DETECT PERIOD OF DISABLED OUTPUT OF SENSOR DATA
610
PROCESS SENSOR DATA FROM PERIOD OF DISABLED OUTPUT
620
DISPLAY BACKFILLED PROCESSED SENSOR DATA
630
END

FIG. 6


Glucose (mg/dL)
400
350
300
250
200
150
100
50
0
ET (hr)
0
12
24
36
48
60
72

FIG. 7A


Glucose (mg/dL)
400
350
300
250
200
150
100
50
0
ET (hr)
0
12
24
36
48
60
72

FIG. 7B

METHODS AND SYSTEMS FOR EARLY SIGNAL ATTENUATION DETECTION AND PROCESSING

RELATED APPLICATIONS

[0001] The present application is a continuation of U.S. patent application Ser. No. 15/061,774, filed Mar. 4, 2016, which is a continuation of U.S. patent application Ser. No. 13/925,694, filed Jun. 24, 2013, now U.S. Pat. No. 9,310,230, which is a continuation of U.S. patent application Ser. No. 12/769,635, filed Apr. 28, 2010, now U.S. Pat. No. 8,483,967, which claims the benefit of U.S. Provisional Patent Application No. 61/173,600, filed Apr. 29, 2009, the disclosures of all of which are incorporated herein by reference in their entireties for all purposes.

BACKGROUND

[0002] Analyte, e.g., glucose monitoring systems including continuous and discrete monitoring systems generally include a small, lightweight battery powered and microprocessor controlled system which is configured to detect signals proportional to the corresponding measured glucose levels using an electrometer. RF signals may be used to transmit the collected data. One aspect of certain analyte monitoring systems include a transcutaneous or subcutaneous analyte sensor configuration which is, for example, at least partially positioned through the skin layer of a subject whose analyte level is to be monitored. The sensor may use a two or three-electrode (work, reference and counter electrodes) configuration driven by a controlled potential (potentiostat) analog circuit connected through a contact system.

[0003] An analyte sensor may be configured so that a portion thereof is placed under the skin of the patient so as to contact analyte of the patient, and another portion or segment of the analyte sensor may be in communication with the transmitter unit. The transmitter unit may be configured to transmit the analyte levels detected by the sensor over a wireless communication link such as an RF (radio frequency) communication link to a receiver/monitor unit. The receiver/monitor unit may perform data analysis, among other functions, on the received analyte levels to generate information pertaining to the monitored analyte levels.

SUMMARY

[0004] Devices and methods for analyte monitoring, e.g., glucose monitoring, and/or therapy management system including, for example, medication infusion device are provided. Embodiments include transmitting information from a first location to a second, e.g., using a telemetry system such as RF telemetry. Systems herein include continuous analyte monitoring systems, discrete analyte monitoring system, and therapy management systems.

[0005] Embodiments include receiving sensor data from an analyte sensor of a sensor monitoring system, processing the received sensor data with time corresponding calibration data, outputting the processed sensor data, detecting one or more adverse conditions associated with the sensor monitoring system, disabling the output of the sensor data during a adverse condition time period, determining that the one or more detected adverse conditions is no longer present in the sensor monitoring system, retrieving the sensor data during the adverse condition time period, processing the retrieved sensor data during the adverse condition time period, and outputting the processed retrieved sensor data.

[0006] Embodiments include detecting a condition unsuitable for calibration of an analyte sensor for a predetermined time period, disabling output of information associated with the analyte sensor, determining a successful calibration of the analyte sensor, retrieving one or more parameters associated with the successful calibration, processing sensor data during the time period of disabled output of information with the one or more parameters associated with the successful calibration, and displaying the processed sensor data for the time period of disabled information output.

[0007] Embodiments include an interface configured to receive sensor data, a first memory configured to store the received sensor data, a processor coupled to the memory and configured to process the stored sensor data, a second memory coupled to the processor and configured to store the processed sensor data, and a display unit coupled to the second memory and configured to display the processed sensor data, where the processor is further configured to detect a condition unsuitable for calibration of a sensor for a predetermined time period, disable display of processed sensor data, determine a successful calibration of the sensor, retrieve one or more parameters associated with the successful calibration, process the sensor data during the time period of disabled display of sensor data with the one or more parameters associated with the successful calibration, and display the processed sensor data for the time period of disabled information output.

[0008] These and other objects, features and advantages of the present disclosure will become more fully apparent from the following detailed description of the embodiments, the appended claims and the accompanying drawings.

INCORPORATION BY REFERENCE

[0009] The following patents, applications and/or publications are incorporated herein by reference for all purposes: U.S. Pat. Nos. 4,545,382; 4,711,245; 5,262,035; 5,262,305; 5,264,104; 5,320,715; 5,509,410; 5,543,326; 5,593,852; 5,601,435; 5,628,890; 5,820,551; 5,822,715; 5,899,855; 5,918,603; 6,071,391; 6,103,033; 6,120,676; 6,121,009; 6,134,461; 6,143,164; 6,144,837; 6,161,095; 6,175,752; 6,270,455; 6,284,478; 6,299,757; 6,338,790; 6,377,894; 6,461,496; 6,503,381; 6,514,460; 6,514,718; 6,540,891; 6,560,471; 6,579,690; 6,591,125; 6,592,745; 6,600,997; 6,605,200; 6,605,201; 6,616,819; 6,618,934; 6,650,471; 6,654,625; 6,676,816; 6,730,200; 6,736,957; 6,746,582; 6,749,740; 6,764,581; 6,773,671; 6,881,551; 6,893,545; 6,932,892; 6,932,894; 6,942,518; 7,167,818; and 7,299,082; U.S. Published Application Nos. 2004/0186365; 2005/0182306; 2007/0056858; 2007/0068807; 2007/0227911; 2007/0233013; 2008/0081977; 2008/0161666; and 2009/0054748; U.S. patent application Ser. Nos. 11/831,866; 11/831,881; 11/831,895; 12/102,839; 12/102,844; 12/102,847; 12/102,855; 12/102,856; 12/152,636; 12/152,648; 12/152,650; 12/152,652; 12/152,657; 12/152,662; 12/152,670; 12/152,673; 12/363,712; 12/131,012; 12/242,823; 12/363,712; 12/393,921; 12/495,709; 12/698,124; 12/699,653; 12/699,844; 12/714,439; 12/761,372; and 12/761,387 and U.S. Provisional Application Nos. 61/230,686 and 61/227,967.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. **1** illustrates a block diagram of a data monitoring and management system for practicing one or more embodiments of the present disclosure;

[0011] FIG. **2** is a block diagram of the transmitter unit of the data monitoring and management system shown in FIG. **1** in accordance with one embodiment of the present disclosure;

[0012] FIG. **3** is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. **1** in accordance with one embodiment of the present disclosure;

[0013] FIG. **4** illustrates analyte sensor data processing in accordance with one embodiment of the present disclosure;

[0014] FIG. **5** illustrates analyte sensor data processing in accordance with one embodiment of the present disclosure;

[0015] FIG. **6** illustrates backfilling gaps in sensor data in one embodiment of the present disclosure; and

[0016] FIGS. **7**A and **7**B illustrate backfill of gaps of a period of uncalibrated sensor data in one embodiment.

DETAILED DESCRIPTION

[0017] Before the present disclosure is described in additional detail, it is to be understood that this disclosure is not limited to particular embodiments described, as such may, of course, vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present disclosure will be limited only by the appended claims.

[0018] Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the disclosure. The upper and lower limits of these smaller ranges may independently be included in the smaller ranges is also encompassed within the disclosure, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the disclosure.

[0019] Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure belongs. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present disclosure, the preferred methods and materials are now described. All publications mentioned herein are incorporated herein by reference to disclose and describe the methods and/or materials in connection with which the publications are cited.

[0020] It must be noted that as used herein and in the appended claims, the singular forms "a", "an", and "the" include plural referents unless the context clearly dictates otherwise.

[0021] The publications discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the present disclosure is not entitled to antedate such publication by virtue of prior disclosure. Further, the dates of publication provided may be different from the actual publication dates which may need to be independently confirmed.

[0022] As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present disclosure.

[0023] The figures shown herein are not necessarily drawn to scale, with some components and features being exaggerated for clarity.

[0024] As described in further detail below, in accordance with the various embodiments of the present disclosure, there is provided a method and system for positioning a controller unit within a transmission range for close proximity communication, transmitting one or more predefined close proximity commands, and receiving a response packet in response to the transmitted one or more predefined close proximity commands. For example, in one aspect, close proximity communication includes short range wireless communication between communication components or devices, where the communication range is limited to about 10 inches or less, about 5 inches or less, or about 2 inches or less, or other suitable, short range or distance between the devices. The close proximity wireless communication in certain embodiments includes a bi-directional communication where a command sending communication device, when positioned within the short communication range or in close proximity to the command receiving communication device, is configured to transmit one or more commands to the command receiving communication device (for example, when a user activates or actuates a transmit command button or switch). In response, the command receiving communication device may be configured to perform one or more routines associated with the received command, and/or return or send back a response data packet or signal to the command sending communication device. Example of such functions and or commands may include, but not limited to activation of certain functions or routines such as analyte related data processing, and the like.

[0025] FIG. **1** illustrates a data monitoring and management system such as, for example, analyte (e.g., glucose) monitoring system **100** in accordance with one embodiment of the present disclosure. The subject invention is further described primarily with respect to a glucose monitoring system for convenience and such description is in no way intended to limit the scope of the invention. It is to be understood that the analyte monitoring system may be configured to monitor a variety of analytes, e.g., lactate, and the like.

[0026] Analytes that may be monitored include, for example, acetyl choline, amylase, bilirubin, cholesterol, chorionic gonadotropin, creatine kinase (e.g., CK-MB), creatine, DNA, fructosamine, glucose, glutamine, growth hormones, hormones, ketones, lactate, peroxide, prostate-specific antigen, prothrombin, RNA, thyroid stimulating hormone, and troponin. The concentration of drugs, such as, for example, antibiotics (e.g., gentamicin, vancomycin, and the like), digitoxin, digoxin, drugs of abuse, theophylline, and warfarin, may also be monitored. More than one analyte may be monitored by a single system, e.g. a single analyte sensor.

[0027] The analyte monitoring system **100** includes a sensor unit **101**, a data processing and transmitter unit **102** coupleable to the sensor unit **101**, and a primary receiver unit **104** which is configured to communicate with the data processing and transmitter unit **102** via a bi-directional communication link **103**. The primary receiver unit **104** may be further configured to transmit data to a data processing terminal **105** for evaluating the data received by the primary receiver unit **104**. Moreover, the data processing terminal **105** in one embodiment may be configured to receive data directly from the data processing and transmitter unit **102** via a communication link which may optionally be configured for bi-directional communication. Accordingly, data processing and transmitter unit **102** and/or receiver unit **104** may include a transceiver.

[0028] Also shown in FIG. **1** is an optional secondary receiver unit **106** which is operatively coupled to the communication link and configured to receive data transmitted from the data processing and transmitter unit **102**. Moreover, as shown in the Figure, the secondary receiver unit **106** is configured to communicate with the primary receiver unit **104** as well as the data processing terminal **105**. Indeed, the secondary receiver unit **106** may be configured for bi-directional wireless communication with each or one of the primary receiver unit **104** and the data processing terminal **105**. As discussed in further detail below, in one embodiment of the present disclosure, the secondary receiver unit **106** may be configured to include a limited number of functions and features as compared with the primary receiver unit **104**. As such, the secondary receiver unit **106** may be configured substantially in a smaller compact housing or embodied in a device such as a wrist watch, pager, mobile phone, PDA, for example. Alternatively, the secondary receiver unit **106** may be configured with the same or substantially similar functionality as the primary receiver unit **104**. The receiver unit may be configured to be used in conjunction with a docking cradle unit, for example for one or more of the following or other functions: placement by bedside, for re-charging, for data management, for night time monitoring, and/or bi-directional communication device.

[0029] In one aspect sensor unit **101** may include two or more sensors, each configured to communicate with data processing and transmitter unit **102**. Furthermore, while only one, data processing and transmitter unit **102**, communication link **103**, and data processing terminal **105** are shown in the embodiment of the analyte monitoring system **100** illustrated in FIG. **1**. However, it will be appreciated by one of ordinary skill in the art that the analyte monitoring system **100** may include one or more sensors, multiple transmitter units **102**, communication links **103**, and data processing terminals **105**. Moreover, within the scope of the present disclosure, the analyte monitoring system **100** may be a continuous monitoring system, or semi-continuous, or a discrete monitoring system. In a multi-component environment, each device is configured to be uniquely identified by each of the other devices in the system so that communication conflict is readily resolved between the various components within the analyte monitoring system **100**.

[0030] In one embodiment of the present disclosure, the sensor unit **101** is physically positioned in or on the body of a user whose analyte level is being monitored. The sensor unit **101** may be configured to continuously sample the analyte level of the user and convert the sampled analyte level into a corresponding data signal for transmission by the data processing and transmitter unit **102**. In certain embodiments, the data processing and transmitter unit **102** may be physically coupled to the sensor unit **101** so that both devices are integrated in a single housing and positioned on the user's body. The data processing and transmitter unit **102** may perform data processing such as filtering and encoding on data signals and/or other functions, each of which corresponds to a sampled analyte level of the user, and in any event data processing and transmitter unit **102** transmits analyte information to the primary receiver unit **104** via the communication link **103**. Examples of such integrated sensor and transmitter units can be found in, among others, U.S. patent application Ser. No. 12/698,124, incorporated herein by reference.

[0031] In one embodiment, the analyte monitoring system **100** is configured as a one-way RF communication path from the data processing and transmitter unit **102** to the primary receiver unit **104**. In such embodiment, the data processing and transmitter unit **102** transmits the sampled data signals received from the sensor unit **101** without acknowledgement from the primary receiver unit **104** that the transmitted sampled data signals have been received. For example, the data processing and transmitter unit **102** may be configured to transmit the encoded sampled data signals at a fixed rate (e.g., at one minute intervals) after the completion of the initial power on procedure. Likewise, the primary receiver unit **104** may be configured to detect such transmitted encoded sampled data signals at predetermined time intervals. Alternatively, the analyte monitoring system **100** may be configured with a bi-directional RF (or otherwise) communication between the data processing and transmitter unit **102** and the primary receiver unit **104**.

[0032] Additionally, in one aspect, the primary receiver unit **104** may include two sections. The first section is an analog interface section that is configured to communicate with the data processing and transmitter unit **102** via the communication link **103**. In one embodiment, the analog interface section may include an RF receiver and an antenna for receiving and amplifying the data signals from the data processing and transmitter unit **102**, which are thereafter, demodulated with a local oscillator and filtered through a band-pass filter. The second section of the primary receiver unit **104** is a data processing section which is configured to process the data signals received from the data processing and transmitter unit **102** such as by performing data decoding, error detection and correction, data clock generation, and data bit recovery.

[0033] In operation, upon completing the power-on procedure, the primary receiver unit **104** is configured to detect the presence of the data processing and transmitter unit **102** within its range based on, for example, the strength of the detected data signals received from the data processing and transmitter unit **102** and/or a predetermined transmitter identification information. Upon successful synchronization with the corresponding data processing and transmitter unit **102**, the primary receiver unit **104** is configured to begin receiving from the data processing and transmitter unit **102** data signals corresponding to the user's detected analyte level. More specifically, the primary receiver unit **104** in one embodiment is configured to perform synchronized time hopping with the corresponding synchronized data processing and transmitter unit **102** via the communication link **103** to obtain the user's detected analyte level.

[0034] Referring again to FIG. **1**, the data processing terminal **105** may include a personal computer, a portable computer such as a laptop or a handheld device (e.g., personal digital assistants (PDAs)), and the like, each of which may be configured for data communication with the receiver via a wired or a wireless connection. Additionally, the data processing terminal **105** may further be connected to a data network (not shown) for storing, retrieving and updating data corresponding to the detected analyte level of the user.

[0035] Within the scope of the present disclosure, the data processing terminal **105** may include an infusion device such as an insulin infusion pump (external or implantable) or the like, which may be configured to administer insulin to patients, and which may be configured to communicate with the receiver unit **104** for receiving, among others, the measured analyte level. Alternatively, the receiver unit **104** may be configured to integrate or otherwise couple to an infusion device therein so that the receiver unit **104** is configured to administer insulin therapy to patients, for example, for administering and modifying basal profiles, as well as for determining appropriate boluses for administration based on, among others, the detected analyte levels received from the data processing and transmitter unit **102**.

[0036] Additionally, the data processing and transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may each be configured for bi-directional wireless communication such that each of the data processing and transmitter unit **102**, the primary receiver unit **104** and the data processing terminal **105** may be configured to communicate (that is, transmit data to and receive data from) with each other via the wireless communication link **103**. More specifically, the data processing terminal **105** may in one embodiment be configured to receive data directly from the data processing and transmitter unit **102** via the communication link **103**, where the communication link **103**, as described above, may be configured for bi-directional communication.

[0037] In this embodiment, the data processing terminal **105** which may include an insulin pump, may be configured to receive the analyte signals from the data processing and transmitter unit **102**, and thus, incorporate the functions of the receiver **104** including data processing for managing the patient's insulin therapy and analyte monitoring. In one embodiment, the communication link **103** may include one or more of an RF communication protocol, an infrared communication protocol, a Bluetooth® enabled communication protocol, an 802.11x wireless communication protocol, or an equivalent wireless communication protocol which would allow secure, wireless communication of several units (for example, per HIPPA requirements) while avoiding potential data collision and interference.

[0038] FIG. **2** is a block diagram of the transmitter of the data monitoring and detection system shown in FIG. **1** in accordance with one embodiment of the present disclosure. Referring to the Figure, the data processing and transmitter unit **102** in one embodiment includes an analog interface **201** configured to communicate with the sensor unit **101** (FIG. **1**), a user input **202**, and a temperature measurement section **203**, each of which is operatively coupled to a transmitter processor **204** such as a central processing unit (CPU). As can be seen from FIG. **2**, there are provided four contacts, three of which are electrodes—work electrode (W) **210**, guard contact (G) **211**, reference electrode (R) **212**, and counter electrode (C) **213**, each operatively coupled to the analog interface **201** of the data processing and transmitter unit **102** for connection to the sensor unit **101** (FIG. **1**). In one embodiment, each of the work electrode (W) **210**, guard contact (G) **211**, reference electrode (R) **212**, and counter electrode (C) **213** may be made using a conductive material that is either printed or etched or ablated, for example, such as carbon which may be printed, or a metal such as a metal foil (e.g., gold) or the like, which may be etched or ablated or otherwise processed to provide one or more electrodes. Fewer or greater electrodes and/or contact may be provided in certain embodiments.

[0039] Further shown in FIG. **2** are a transmitter serial communication section **205** and an RF transmitter **206**, each of which is also operatively coupled to the transmitter processor **204**. Moreover, a power supply **207** such as a battery is also provided in the data processing and transmitter unit **102** to provide the necessary power for the data processing and transmitter unit **102**. In certain embodiments, the power supply **207** also provides the power necessary to power the sensor **101**. In other embodiments, the sensor is a self-powered sensor, such as the sensor described in U.S. patent application Ser. No. 12/393,921, incorporated herein by reference. Additionally, as can be seen from the Figure, clock **208** is provided to, among others, supply real time information to the transmitter processor **204**.

[0040] In one embodiment, a unidirectional input path is established from the sensor unit **101** (FIG. **1**) and/or manufacturing and testing equipment to the analog interface **201** of the data processing and transmitter unit **102**, while a unidirectional output is established from the output of the RF transmitter **206** of the data processing and transmitter unit **102** for transmission to the primary receiver unit **104**. In this manner, a data path is shown in FIG. **2** between the aforementioned unidirectional input and output via a dedicated link **209** from the analog interface **201** to serial communication section **205**, thereafter to the processor **204**, and then to the RF transmitter **206**. As such, in one embodiment, via the data path described above, the data processing and transmitter unit **102** is configured to transmit to the primary receiver unit **104** (FIG. **1**), via the communication link **103** (FIG. **1**), processed and encoded data signals received from the sensor unit **101** (FIG. **1**). Additionally, the unidirectional communication data path between the analog interface **201** and the RF transmitter **206** discussed above allows for the configuration of the data processing and transmitter unit **102** for operation upon completion of the manufacturing process as well as for direct communication for diagnostic and testing purposes.

[0041] As discussed above, the transmitter processor **204** is configured to transmit control signals to the various sections of the data processing and transmitter unit **102** during the operation of the data processing and transmitter unit **102**. In one embodiment, the transmitter processor **204** also includes a memory (not shown) for storing data such as the identification information for the data processing and transmitter unit **102**, as well as the data signals received from the sensor unit **101**. The stored information may be retrieved and processed for transmission to the primary receiver unit **104** under the control of the transmitter processor **204**. Furthermore, the power supply **207** may include a commercially available battery, which may be a rechargeable battery.

[0042] In certain embodiments, the data processing and transmitter unit **102** is also configured such that the power supply section **207** is capable of providing power to the transmitter for a minimum of about three months of continuous operation, e.g., after having been stored for about eighteen months such as stored in a low-power (non-operating) mode. In one embodiment, this may be achieved by the transmitter processor **204** operating in low power modes in the non-operating state, for example, drawing no more than approximately 1 μA of current. Indeed, in one embodiment, a step during the manufacturing process of the data processing and transmitter unit **102** may place the data processing and transmitter unit **102** in the lower power, non-operating state (i.e., post-manufacture sleep mode). In this manner, the shelf life of the data processing and transmitter unit **102** may be significantly improved. Moreover, as shown in FIG. **2**, while the power supply unit **207** is shown as coupled to the processor **204**, and as such, the processor **204** is configured to provide control of the power supply unit **207**, it should be noted that within the scope of the present disclosure, the power supply unit **207** is configured to provide the necessary power to each of the components of the data processing and transmitter unit **102** shown in FIG. **2**.

[0043] Referring back to FIG. **2**, the power supply section **207** of the data processing and transmitter unit **102** in one embodiment may include a rechargeable battery unit that may be recharged by a separate power supply recharging unit (for example, provided in the receiver unit **104**) so that the data processing and transmitter unit **102** may be powered for a longer period of usage time. Moreover, in one embodiment, the data processing and transmitter unit **102** may be configured without a battery in the power supply section **207**, in which case the data processing and transmitter unit **102** may be configured to receive power from an external power supply source (for example, a battery) as discussed in further detail below.

[0044] Referring yet again to FIG. **2**, the temperature measurement section **203** of the data processing and transmitter unit **102** is configured to monitor the temperature of the skin near the sensor insertion site. The temperature reading is used to adjust the analyte readings obtained from the analog interface **201**. In certain embodiments, the RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of approximately 315 MHz to approximately 322 MHz, for example, in the United States. In certain embodiments, the RF transmitter **206** of the transmitter unit **102** may be configured for operation in the frequency band of approximately 400 MHz to approximately 470 MHz. Further, in one embodiment, the RF transmitter **206** is configured to modulate the carrier frequency by performing Frequency Shift Keying and Manchester encoding. In one embodiment, the data transmission rate is about 19,200 symbols per second, with a minimum transmission range for communication with the primary receiver unit **104**.

[0045] Referring yet again to FIG. **2**, also shown is a leak detection circuit **214** coupled to the guard electrode (G) **211** and the processor **204** in the transmitter unit **102** of the data monitoring and management system **100**. The leak detection circuit **214** in accordance with one embodiment of the present disclosure may be configured to detect leakage current in the sensor unit **101** to determine whether the measured sensor data are corrupt or whether the measured data from the sensor **101** is accurate. Exemplary analyte systems that may be employed are described in, for example, U.S. Pat. Nos. 6,134,461, 6,175,752, 6,121,611, 6,560,471, 6,746,582, and elsewhere, the disclosure of each of which are incorporated by reference for all purposes.

[0046] FIG. **3** is a block diagram of the receiver/monitor unit of the data monitoring and management system shown in FIG. **1** in accordance with one embodiment of the present disclosure. Referring to FIG. **3**, the primary receiver unit **104** includes an analyte test strip, e.g., blood glucose test strip, interface **301**, an RF receiver **302**, an input **303**, a temperature monitor section **304**, and a clock **305**, each of which is operatively coupled to a receiver processor **307**. As can be further seen from the Figure, the primary receiver unit **104** also includes a power supply **306** operatively coupled to a power conversion and monitoring section **308**. Further, the power conversion and monitoring section **308** is also coupled to the receiver processor **307**. Moreover, also shown are a receiver serial communication section **309**, and an output **310**, each operatively coupled to the receiver processor **307**.

[0047] In one embodiment, the test strip interface **301** includes a glucose level testing portion to receive a manual insertion of a glucose test strip, and thereby determine and display the glucose level of the test strip on the output **310** of the primary receiver unit **104**. This manual testing of glucose may be used to calibrate the sensor unit **101** or otherwise. The RF receiver **302** is configured to communicate, via the communication link **103** (FIG. **1**) with the RF transmitter **206** of the transmitter unit **102**, to receive encoded data signals from the transmitter unit **102** for, among others, signal mixing, demodulation, and other data processing. The input **303** of the primary receiver unit **104** is configured to allow the user to enter information into the primary receiver unit **104** as needed. In one aspect, the input **303** may include one or more keys of a keypad, a touch-sensitive screen, or a voice-activated input command unit. The temperature monitor section **304** is configured to provide temperature information of the primary receiver unit **104** to the receiver processor **307**, while the clock **305** provides, among others, real time information to the receiver processor **307**.

[0048] Each of the various components of the primary receiver unit **104** shown in FIG. **3** is powered by the power supply **306** which, in one embodiment, includes a battery. Furthermore, the power conversion and monitoring section **308** is configured to monitor the power usage by the various components in the primary receiver unit **104** for effective power management and to alert the user, for example, in the event of power usage which renders the primary receiver unit **104** in sub-optimal operating conditions. An example of such sub-optimal operating condition may include, for example, operating the vibration output mode (as discussed below) for a period of time thus substantially draining the power supply **306** while the processor **307** (thus, the primary receiver unit **104**) is turned on. Moreover, the power conversion and monitoring section **308** may additionally be configured to include a reverse polarity protection circuit such as a field effect transistor (FET) configured as a battery activated switch.

[0049] The serial communication section **309** in the primary receiver unit **104** is configured to provide a bi-directional communication path from the testing and/or manufacturing equipment for, among others, initialization,

testing, and configuration of the primary receiver unit **104**. Serial communication section **104** can also be used to upload data to a computer, such as time-stamped blood glucose data. The communication link with an external device (not shown) can be made, for example, by cable, infrared (IR) or RF link. The output **310** of the primary receiver unit **104** is configured to provide, among others, a graphical user interface (GUI) such as a liquid crystal display (LCD) for displaying information. Additionally, the output **310** may also include an integrated speaker for outputting audible signals as well as to provide vibration output as commonly found in handheld electronic devices, such as mobile telephones presently available. In a further embodiment, the primary receiver unit **104** also includes an electro-luminescent lamp configured to provide backlighting to the output **310** for output visual display in dark ambient surroundings.

[0050] Referring back to FIG. **3**, the primary receiver unit **104** in one embodiment may also include a storage section such as a programmable, non-volatile memory device as part of the processor **307**, or provided separately in the primary receiver unit **104**, operatively coupled to the processor **307**. The processor **307** may be configured to synchronize with a transmitter, e.g., using Manchester decoding or the like, as well as error detection and correction upon the encoded data signals received from the transmitter unit **102** via the communication link **103**.

[0051] Periodic calibration of the sensor unit **101** (FIG. **1**) of an analyte monitoring system **100**, in some embodiments, may be required for accurate calculation of a user's analyte level. Calibration, in some aspects, is used to ensure the analyte related data signals received at a transmitter unit **102** (and further transmitted to a receiver unit, such as the primary receiver unit **104**) are correctly converted to corresponding analyte levels. Exemplary calibration protocols, routines and techniques are described, for example, in U.S. Pat. No. 7,299,082, U.S. patent application Ser. No. 11/537,991 filed Oct. 2, 2006, U.S. patent application Ser. No. 12/363,706 filed Jan. 30, 2009 and in U.S. patent application Ser. No. 12/363,712 filed Jan. 30, 2009, the disclosures of each of which are herein incorporated by reference for all purposes.

[0052] There are time periods where the sensor characteristics or the user's physiological condition renders the condition unsuitable for a sensor calibration event. For example, the sensor may be configured for periodic calibration, such as, after 2 hours after insertion, 10 hours after insertion, 12 hours after insertion, 24 hours after insertion, 48 hours after insertion, or 72 hours after insertion, or one or more combinations thereof. If a predetermined calibration event is triggered but a successful calibration does not result, after a certain time period (for example, a predetermined grace period during which to calibrate), the receiver unit may no longer display the monitored and processed glucose information.

[0053] Other conditions may also result in rendering the condition unsuitable for sensor calibration including, but not limited to, detection of a failure mode of a sensor, sensor data values being outside a predetermined range, rate of change of sensor data values being above a predetermined threshold, a temperature measurement outside a predetermined range, or any combination thereof.

[0054] FIG. **4** illustrates analyte sensor data processing in accordance with one embodiment of the present disclosure. Referring to FIG. **4**, a transmitter unit **102** (FIG. **1**) in operational contact with a sensor **101** receives analyte related sensor data (**410**) corresponding to a measured level of a biological fluid of the user. For example, the sensor **101** (FIG. **1**) may be an analyte sensor configured to detect and measure the concentration of an analyte in a biological fluid, such as the blood of a user. Upon receipt of the analyte related sensor data, the transmitter unit **102** further transmits the analyte related sensor data to a receiver unit, such as primary receiver unit **104** (FIG. **1**). It is to be noted that the reference to analyte related sensor data herein and throughout specification includes, for example, current signal received from the analyte sensor, as well as the current signal which has undergone predetermined data processing routines including, for example, filtering, clipping, digitizing, and/or encoding, and/or any other further processing and/or conditioning. In one aspect, the primary receiver unit **104** determines whether the sensor is calibrated and is in acceptable condition for further data processing (**420**). When sensor related conditions are unsuitable for calibration, the analyte related sensor data is stored (**450**) in a memory, for example, in the primary receiver unit **104**.

[0055] Referring still to FIG. **4**, if the sensor data is calibrated and in condition for further data processing, the sensor data is further processed (**430**) and output for display (**440**) to a user on a display unit **310** (FIG. **3**) of the primary receiver unit **104**. In one embodiment, the display of the processed sensor data comprises a graphical representation of the processed sensor data. In other embodiments, the processed sensor data may be displayed as numerical values, visual indicators, auditory outputs, or combinations thereof. In one aspect, the processing routine described in conjunction with FIG. **4** is performed or executed in, for example, the transmitter unit **102**, the secondary receiver unit **106** (FIG. **1**), or the data processing terminal **105** (FIG. **1**) of the analyte monitoring system **100** (FIG. **1**) based on analyte data received from the sensor **101**.

[0056] FIG. **5** illustrates analyte sensor data processing in accordance with one embodiment of the present disclosure. Referring to FIG. **5**, in one embodiment, transmitter unit **102** (FIG. **1**) receives analyte related sensor data (**510**) from a sensor **101** (FIG. **1**). Upon receipt of the analyte related sensor data, the transmitter unit **102** transmits the analyte related sensor data (or processed, digitized, and/or filtered signals) to the primary receiver unit **104** (FIG. **1**). The primary receiver unit **104** is configured to determine if calibration of the sensor data is suitable—that is, whether the conditions necessary for sensor calibration are met (**520**).

[0057] Still referring to FIG. **5**, if it is determined that the sensor **101** is not calibrated or calibration condition for calibrating the sensor **101** is not met, in one aspect, the primary receiver unit stores the analyte related sensor data in a memory (**550**) and temporarily disables display of the sensor data (**560**) to the user (for example, if a calibration event has not occurred and the calibration grace period has expired). On the other hand, if the sensor **101** is calibrated, the sensor data is processed (**530**) by the primary receiver unit **104** and the processed sensor data is output to the user (**540**), for example via a display unit **310** (FIG. **3**) of the primary receiver unit **104**. In one aspect, the processing routine described in conjunction with FIG. **5** is performed or executed in, for example, the transmitter unit **102**, the secondary receiver unit **106**, or the data processing terminal **105** of the analyte monitoring system **100** based on analyte data received from the sensor **101** (FIG. **1**).

[0058] In one aspect, the display or output of processed sensor data may be disabled if a required calibration event is unsuccessful over a permitted time period (for example, including a predetermined grace period measured from the scheduled calibration). Thereafter, upon successful calibration, the system resumes display of the processed and calibrated analyte sensor data. However, there may be a time period or a gap in the output display during which the necessary calibration did not occur in a timely manner. For example, as shown in FIG. **7**A, if sensor data is displayed as a graphical display, during time periods where the analyte monitoring system **100** was not properly calibrated, analyte related sensor data was not processed and/or displayed, resulting in a gap in the graphical display.

[0059] FIG. **6** illustrates backfilling gaps in sensor data in one embodiment of the present disclosure. Referring to FIG. **6**, when a scheduled calibration event fails and the associated grace period for calibration does not occur, the output display of the processed, calibrated sensor data is disabled (**610**). Referring to FIG. **6**, once the system recovers after a successful calibration event, the calibrated sensor data is once again displayed (and stored). Furthermore, in one aspect, based on the parameters associated with the successful calibration, the previously unprocessed data during the display time out period may be retrieved (for example, the previously stored analyte related sensor signals during this period) and processed using calibration data, such as a sensitivity ratio for conversion of analyte related sensor data to analyte levels. For example, in one aspect, the subset of analyte related sensor data that were previously unprocessed or uncalibrated due to unsuccessful contemporaneous calibration may be processed using, for example, calibration data such as the sensitivity ratio determined from the most recent successful calibration event, and thereafter, the gap in output display illustrating the processed and calibrated signals may be filled.

[0060] In one aspect, once successful calibration of the sensor data occurs, the calibration parameters from this calibration event may be used to process the sensor data during the period of disabled output or display (**620**). Upon successful processing of the sensor data during the period of disabled output, the processed sensor data during this time period is backfilled, or the gap in the processed continuous sensor data are filled in the display (**630**). By way of an example, FIGS. **7**A and **7**B illustrate the replacement of a period of unprocessed sensor data with corresponding backfilled processed sensor data, in one embodiment.

[0061] In one embodiment, the backfilled processed sensor data is displayed immediately upon calculation. In another embodiment, the backfilled processed sensor data is not displayed immediately, but rather, after waiting a predetermined period of time. The backfilled processed sensor data may not be displayed immediately to avoid possible unnecessary or incorrect action by a user in response to the backfilled processed sensor data. In this manner, in one aspect, the user or a healthcare provider may be provided with a continuous set of analyte data from the analyte monitoring system without any gaps in the processed signals for further analysis and/or therapy management.

[0062] In this manner, in accordance with the embodiments of the present disclosure, gaps in monitored analyte levels using an analyte monitoring system due to, for example, inability to promptly calibrate the sensor, system malfunction, sensor dislodging, signal errors associated with the sensor, transmitter unit, receiver unit, and the like, or any other variables or parameters that result in the inability of the analyte monitoring system to display or output the real-time monitored analyte level, may be retrospectively filled or reprocessed so that the data gap is closed and the continuously monitored analyte level does not have any or substantially missing data. That is, in embodiments of the present disclosure, upon correction or rectification of the condition or conditions/parameters which resulted in the analyte monitoring system disabling the output results associated with the monitored real time analyte levels, the parameters associated with the correction or rectification may be used to retrospectively correct or process data or signals so that the missing gaps in analyte related data may be processed and backfilled.

[0063] In this manner, advantageously, in aspects of the present disclosure, additional robustness may be provided to the user and/or the healthcare provider to improve therapy or health management decisions.

[0064] In one embodiment, a method may include receiving sensor data from an analyte sensor of a sensor monitoring system, processing the received sensor data with time corresponding calibration data, outputting the processed sensor data, detecting one or more adverse conditions associated with the sensor monitoring system, disabling the output of the sensor data during an adverse condition time period, determining that the one or more detected adverse conditions is no longer present in the sensor monitoring system, retrieving the sensor data during the adverse condition time period, processing the retrieved sensor data during the adverse condition time period, and outputting the processed retrieved sensor data.

[0065] In one aspect, outputting the processed sensor data may include displaying the sensor data in one or more of a graphical, numerical, pictorial, audible, vibratory, or one or more combinations thereof.

[0066] The one or more detected adverse conditions may include one or more of a sensor instability condition, a calibration failure condition, or a monitoring system failure condition.

[0067] The sensor instability condition may include one or more of an early signal attenuation condition of the sensor, sensor misposition error, sensor communication error, temperature measurement outside a predetermined range, or a combination thereof.

[0068] The calibration failure condition may include one or more of an analyte level exceeding a predetermined threshold, a rate of change of analyte level exceeding a predetermined threshold, a signal error associated with the reference data, a data unavailability condition, or a combination thereof.

[0069] Furthermore, the method may include storing the processed sensor data with the associated time information based on the analyte level detection time by the sensor.

[0070] In another embodiment, a method may include detecting a condition unsuitable for calibration of an analyte sensor for a predetermined time period, disabling output of information associated with the analyte sensor, determining a successful calibration of the analyte sensor, retrieving one or more parameters associated with the successful calibration, processing sensor data during the time period of disabled output of information with the one or more param-

eters associated with the successful calibration, and displaying the processed sensor data for the time period of disabled information output.

[0071] The sensor data may be analyte concentration data.

[0072] The analyte concentration data may include blood glucose concentration data.

[0073] The sensor data may be processed in substantially real-time.

[0074] The condition unsuitable for calibration may include one or more of a failure mode of a sensor, sensor data outside a predetermined acceptable range, a rate of change of sensor data above a predetermined level, a requirement for calibration of a sensor, a temperature measurement outside a predetermined range, or any combination thereof.

[0075] The processed sensor data for the time period of disabled information output may be displayed substantially immediately upon processing.

[0076] The processed sensor data for the time period of disabled information output may be displayed only after waiting a predetermined period of time.

[0077] In another embodiment, an apparatus may include an interface configured to receive sensor data, a first memory configured to store the received sensor data, a processor coupled to the memory and configured to process the stored sensor data, a second memory coupled to the processor and configured to store the processed sensor data, and a display unit coupled to the second memory and configured to display the processed sensor data, wherein the processor is further configured to detect a condition unsuitable for calibration of a sensor for a predetermined time period, disable display of processed sensor data, determine a successful calibration of the sensor, retrieve one or more parameters associated with the successful calibration, process the sensor data during the time period of disabled display of sensor data with the one or more parameters associated with the successful calibration, and display the processed sensor data for the time period of disabled information output.

[0078] The sensor may be an analyte sensor.

[0079] The analyte sensor may be a glucose sensor.

[0080] The sensor data may correspond to analyte concentration data.

[0081] The analyte concentration data may include blood glucose concentration data.

[0082] Furthermore, the apparatus may be configured to process and display the sensor data substantially in real-time.

[0083] In one aspect, the condition unsuitable for calibration may include one or more of a failure mode of a sensor, sensor data outside a predetermined acceptable range, a rate of change of sensor data above a predetermined level, a requirement for calibration of a sensor, a temperature measurement outside a predetermined range, or any combination thereof.

[0084] The display unit may be configured to display the processed sensor data for the time period of disabled information output substantially immediately upon processing the sensor data.

[0085] The display unit may be configured to display the processed sensor data for the time period of disabled information output only after waiting a predetermined period of time.

[0086] Various other modifications and alterations in the structure and method of operation of this invention will be apparent to those skilled in the art without departing from the scope and spirit of the invention. Although the invention has been described in connection with specific preferred embodiments, it should be understood that the invention as claimed should not be unduly limited to such specific embodiments. It is intended that the following claims define the scope of the present disclosure and that structures and methods within the scope of these claims and their equivalents be covered thereby.

1-22. (canceled)

23. A method of backfilling one or more sensor data gaps in an analyte monitoring system comprising one or more processors and an analyte sensor, the method comprising:

detecting, with the one or more processors, a failure mode condition, wherein the failure mode condition causes the one or more sensor data gaps to be outputted to a display of the analyte monitoring system;

storing sensor data received from the analyte sensor for a time period associated with the failure mode condition; and

in response to a correction of the failure mode condition,

processing, with the one or more processors, the stored sensor data for the time period associated with the failure mode condition, and

outputting the processed stored sensor data to the display of the analyte monitoring system such that the one or more sensor data gaps are at least partially filled by the processed stored sensor data.

24. The method of claim **23**, wherein the failure mode condition comprises signal errors associated with a transmitter unit of the analyte monitoring system or a receiver unit of the analyte monitoring system.

25. The method of claim **23**, wherein the failure mode condition comprises one or more of an inability to calibrate the sensor, a system malfunction, or a sensor dislodgement.

26. The method of claim **23**, wherein the failure mode condition comprises one or more of a sensor data value being outside a predetermined sensor data value range, a rate of change of one or more sensor data values being above a predetermined rate-of-change threshold, or a temperature measurement outside a predetermined temperature range.

27. The method of claim **23**, further comprising, in response to the correction of the failure mode condition, receiving the stored sensor data for the time period associated with the failure mode condition.

28. The method of claim **23**, wherein outputting the processed stored sensor data to the display of the analyte monitoring system occurs immediately after the stored sensor data is processed.

29. The method of claim **23**, further comprising, in response to the correction of the failure mode condition, waiting a predetermined period of time before outputting the processed stored sensor data to the display of the analyte monitoring system.

30. The method of claim **23**, wherein processing the stored sensor data is performed by one or more processors of a transmitter unit of the analyte monitoring system.

31. The method of claim **23**, wherein processing the stored sensor data is performed by one or more processors of a receiver unit of the analyte monitoring system.

32. The method of claim **23**, wherein storing sensor data received from the analyte sensor includes storing time information associated with the failure mode condition.

33. The method of claim 23, further comprising:
receiving current sensor data from the analyte sensor;
outputting a first graphical representation to the display of the analyte monitoring system, wherein the first graphical representation includes the current sensor data and the one or more sensor data gaps associated with the failure mode condition.

34. The method of claim 33, wherein outputting the processed stored sensor data to the display of the analyte monitoring system comprises outputting a second graphical representation to the display of the analyte monitoring system, wherein the second graphical representation comprises the processed stored sensor data, and wherein the one or more sensor data gaps associated with the failure mode condition are at least partially filled in the second graphical representation.

35. An analyte monitoring system comprising:
an analyte sensor;
one or more processors; and
a memory device for storing instructions which, when executed by the one or more processors, causes the one or more processors to:
detect a failure mode condition, wherein the failure mode condition causes one or more sensor data gaps to be outputted to a display of the analyte monitoring system,
store sensor data received from the analyte sensor for a time period associated with the failure mode condition, and
in response to a correction of the failure mode condition,
process the stored sensor data for the time period associated with the failure mode condition, and
output the processed stored sensor data to the display of the analyte monitoring system such that the one or more sensor data gaps are at least partially filled by the processed stored sensor data.

36. The system of claim 35, wherein the failure mode condition comprises signal errors associated with a transmitter unit of the analyte monitoring system or a receiver unit of the analyte monitoring system.

37. The system of claim 35, wherein the memory device stores instructions which, when executed by the one or more processors, further causes the one or more processors to wait a predetermined period of time before outputting the processed stored sensor data to the display of the analyte monitoring system.

38. The system of claim 35, further comprising a transmitter unit, and wherein the memory device stores instructions which, when executed by the one or more processors of the transmitter unit, further causes the one or more processors of the transmitter unit to, in response to the correction of the failure mode condition, process the stored sensor data for the time period associated with the failure mode condition.

39. The system of claim 35, further comprising a receiver unit, and wherein the memory device stores instructions which, when executed by the one or more processors of the receiver unit, further causes the one or more processors of the receiver unit to, in response to the correction of the failure mode condition, process the stored sensor data for the time period associated with the failure mode condition.

40. The system of claim 35, wherein the memory device stores instructions which, when executed by the one or more processors, further causes the one or more processors to store time information associated with the failure mode condition.

41. The system of claim 35, further comprising a receiver unit configured to receive current sensor data,
and wherein the memory device stores instructions which, when executed by the one or more processors of the receiver unit, further causes the one or more processors of the receiver unit to output a first graphical representation to the display of the analyte monitoring system,
and wherein the first graphical representation comprises the current sensor data and the one or more sensor data gaps associated with the failure mode condition.

42. The system of claim 41, wherein the memory device stores instructions which, when executed by the one or more processors of the receiver unit, further causes the one or more processors of the receiver unit to output a second graphical representation to the display of the analyte monitoring system,
wherein the second graphical representation comprises the processed stored sensor data, and wherein the one or more sensor data gaps associated with the failure mode condition are at least partially filled in the second graphical representation.

* * * * *