

Conferences > The IEEE symposium on Comput...

Graph based automatic centralized PCI assignment in LTE

Publisher: IEEE

Cite This

PDF

Yanguang Liu ; Wenjing Li ; Heng Zhang ; Weihao Lu

All Authors

10

Paper Citations

523

Full Text Views

Alerts

Manage Content Alerts

Add to Citation Alerts

Abstract

Document Sections

I. Introduction

II. PCI Assignment Mechanism

III. PCI Assignment Algorithm

IV. Simulations

V. Conclusion

Authors

Figures

References

Citations

Keywords

Download PDF

Abstract:Physical Cell Identity (PCI) is cell identifier on the physical layer which can be used to create synchronization signals. There is a mapping between synchronization sign... **View more**

► Metadata
Abstract:
Physical Cell Identity (PCI) is cell identifier on the physical layer which can be used to create synchronization signals. There is a mapping between synchronization signals and physical cell identity, and then User Equipment (UE) can search cells through this mapping. Traditionally, PCI was configured during network planning process. While with 3G Long Term Evolution (LTE) has been prevalent in the future network, auto configuration of radio parameters has become a necessity. This paper proposed an automatic centralized PCI assignment mechanism using OAM as central server to collect cell information of the network, and create an abstract graph using information given which reflects the relationship in real-world network. After that, an enhanced graph-coloring algorithm which can greatly reduce time complexity while keeping a high PCI utility ratio was provided to create a collision and confusion free PCI for the new cell.

Published in: The IEEE symposium on Computers and Communications

Date of Conference: 22-25 June 2010

INSPEC Accession Number: 11474613

DOI: 10.1109/ISCC.2010.5546812

Date Added to IEEE Xplore: 12 August 2010

More Like This

► ISBN Information:

► ISSN Information:

Publisher: IEEE

Conference Location: Riccione

Contents

I. Introduction

LTE is well known for self-sensing, self-configuration, self-optimizing and self-healing without much human intervention and great operational expenditure (OPEX) and capital expenditure (CAPEX) reduction. In self-configuration phase, when a new evolved NodeB (eNB) is introduced into the network, a series of parameters such as antenna tilt, pilot power need to be configured. PCI is one of the radio parameters which ranges from 0 to 503 [1] and is used to scramble the data to help the mobile separate information from different transmitters. While in most cases, cells in a network are more than 504, the PCI need to be used more than once. During the assignment of PCI, it must fulfill both collision and confusion free with respective neighbor cells [2].

Authors	▼
Figures	▼
References	▼
Citations	▼
Keywords	▼
Metrics	▼

Need
Full-Text

access to IEEE Xplore
for your organization?

REQUEST A FREE TRIAL >

More Like This

A Synchronization-Based Hybrid-Memory Multi-Core Architecture for Energy-Efficient Biomedical Signal Processing
IEEE Transactions on Computers
Published: 2017

Small-group learning projects to make signal processing more appealing: From speech processing to OFDMA synchronization
2009 IEEE International Conference on Acoustics, Speech and Signal Processing
Published: 2009

Show More

Loading [MathJax]/extensions/MathZoom.js

IEEE
Signal
Processing
Society

IEEE

Get Published in the
IEEE Open Journal of
Signal Processing

Learn More

CHANGE
USERNAME/PASSWORD

PAYMENT OPTIONS
VIEW PURCHASED
DOCUMENTS

COMMUNICATIONS
PREFERENCES
PROFESSION AND
EDUCATION
TECHNICAL INTERESTS

US & CANADA: +1 800
678 4333
WORLDWIDE: +1 732
981 0060
CONTACT & SUPPORT



About IEEE Xplore Contact Us Help Accessibility Terms of Use Nondiscrimination Policy IEEE Ethics Reporting Sitemap
IEEE Privacy Policy

IEEE Account

- » Change Username/Password
- » Update Address

Purchase Details

- » Payment Options
- » Order History
- » View Purchased Documents

Profile Information

- » Communications Preferences
 - » Profession and Education
- Loading [MathJax]/extensions/MathZoom.js

» Technical Interests

Need Help?

» US & Canada: +1 800 678 4333

» Worldwide: +1 732 981 0060

» Contact & Support

[About IEEE Xplore](#) [Contact Us](#) [Help](#) [Accessibility](#) [Terms of Use](#) [Nondiscrimination Policy](#) [Sitemap](#) [Privacy & Opting Out of Cookies](#)

A not-for-profit organization, IEEE is the world's largest technical professional organization dedicated to advancing technology for the benefit of humanity.
© Copyright 2023 IEEE - All rights reserved. Use of this web site signifies your agreement to the terms and conditions.

Loading [MathJax]/extensions/MathZoom.js