

A/PROV

1c660 U.S. PTO
05/21/99

Please type a plus sign (+) inside this box → ☐

PTO/SB/16 (3-97)
Approved for use through 1/31/98. OMB 0651-0037
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (b)(2).

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Nancy Charles Peter		Benovich Gilby Evet Fearey			
☒ Additional inventors are being named on the <u>1</u> separately numbered sheets attached hereto (back)					
TITLE OF THE INVENTION (280 characters max)					
CUSTOMER LEAD MANAGEMENT SYSTEM					
Direct all correspondence to:					
☐ Customer Number				Place Customer Number Bar Code Label here	
OR Type Customer Number here					
☐ Firm or Individual Name		Fish & Richardson P.C.			
Address		225 Franklin Street			
Address					
City	Boston	State	MA	ZIP	02110
Country	USA	Telephone	617-542-5070	Fax	617-542-8906
ENCLOSED APPLICATION PARTS (check all that apply)					
☒	Specification Number of Pages	14	☐	Small Entity Statement	
☒	Drawing(s) Number of Sheets	5	☒	Other (specify) Appendix A (190 pgs)	
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
☐ A check or money order is enclosed to cover the filing fees		FILING FEE AMOUNT (\$)			
☐ The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:		\$75.00			
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
☒ No.					
☐ Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE Ten Robin Rohlicek

Date 5/21/99

TYPED or PRINTED NAME J. Robin Rohlicek

REGISTRATION NO. 43,349
(if appropriate)

TELEPHONE 617-542-5070

Docket Number: 10844/002001

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, DC 20231.

1c541 U.S. PTO
60/135521
05/21/99

PROVISIONAL APPLICATION COVER SHEET
Additional Page

Approved for use through 1/31/98. PTO/SB/16 (3-97)
 OMB 0651-0037
 Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Docket Number		10844/002001	Type a plus sign (+) inside this box →	+
INVENTOR(S)/APPLICANT(S)				
Given Name (first and middle (if any))	Family or Surname	Residence (City and either State or Foreign Country)		
Gregory	Erman			
David	Tiu			
John	Mandel			

SCANNED

Number 1 of 1

PROVISIONAL APPLICATION

UNDER 37 CFR 1.53(b)(2)

TITLE: CUSTOMER LEAD MANAGEMENT SYSTEM

APPLICANTS: NANCY BENOVIH GILBY, CHARLES EVETT,
PETER FEAREY, GREGORY ERMAN, DAVID TIU
and JOHN MANDEL

"EXPRESS MAIL" Mailing Label Number EL266438027US

Date of Deposit May 21, 1999

I hereby certify under 37 CFR 1.10 that this correspondence is being deposited with the United States Postal Service as "Express Mail Post Office To Addressee" with sufficient postage on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 2023.

Ma G Gray
USA & Gray

CUSTOMER LEAD MANAGEMENT SYSTEMBackground

5 This invention relates to a system for processing customer leads.

10 Today, lead management is largely a paper-based manual process in which customer leads are received as a result of marketing activities, and distributed to particular sales organizations. For example, names and other information about customer leads may be obtained at a trade show. A subset of these leads may then be selected and passed to sales groups based on the geographic region of the lead, the product or service involved, or other lead-related
15 criteria. In general, there is little or no automated feedback regarding the outcome of the lead, such as whether a sale actually occurred or if the lead was not properly routed.

Summary

20 In a general aspect, the invention provides an automated system for accepting, prioritizing and routing customer leads. The system provides feedback regarding the routing and ultimate outcome of a lead, thereby allowing lead tracking and performance measurement. The invention
25 can feature a hierarchical delegation approach in which users specify rules according to which leads routed to them are processed, for example, by routing the lead to other users. The invention can also feature a distributed architecture in which several servers are coupled, for
30 example, over the Internet. Leads are provided from one

server to another, and feedback regarding the disposition of the lead is provided in return.

In one aspect, in general, the invention is a method for processing customer leads. The method includes
5 accepting a lead that includes a number of data fields, such as the lead name, the lead's address, or a marketing campaign associated with the lead. The method also includes inputting, or otherwise accepting, a number of rule specification for each of a number of users. The lead
10 is routed to a first of the users, and one or more of the rules that were inputted for that user are applied to the lead. Based on application of those rules, the lead is routed to a second of the users. The second user is notified of the routed lead. Then an acceptance of the
15 lead is received from the second user.

The invention has the advantage of providing feedback regarding the processing of a lead, thereby allowing tracking and, if necessary, re-routing of a lead that is not being handled effectively.

20 The hierarchical delegation of rule specification allows users to more precisely tailor the rule for their particular circumstances, rather than relying only on a centralized administration approach.

Coupling of multiple servers allows different servers
25 to be administered by different organization, such as a vendor and multiple resellers. When leads are passed from one server to another, the configurable amount of feedback provides desirable security and privacy to the organizations which maintaining efficient processing of the
30 leads. By maintaining the leads on multiple servers administered by different organizations, each organization can make use of its own leads database, while maintaining a degree of sharing of information between the organizations.

Other features and advantages are apparent from the following description and from the claims.

Description of Drawings

FIG. 1 is block diagram of lead management system;

5 FIG. 2 shows the interconnection of computers used to implement the lead management system over the Internet;

FIG. 3 is a block diagram showing logical modules of a lead management server;

10 FIG. 4 shows a set of lead boxes coupled to user interfaces and to a rules engine; and

FIG. 5 illustrates exemplary handling of leads through the system.

Description

15 Referring to FIG. 1, a lead management system includes a lead management server 100 that accepts leads 162 from one or more lead sources 160, and routes those leads to particular users through user interfaces 110. Lead sources 160 can include email, Web forms, telephone call centers, business card or badge scanners at trade shows, or
20 purchased mailing lists. In the description that follows, leads 162 refer to customer lead that relate to potential purchases of products or services offered by a commercial organization, and the users are typically sales representatives, or managers of organizations that include
25 sales representatives. The organization makes use of the lead management system to direct the leads to appropriate users, such as sales representatives, who interact with the potential customers for the purpose of actually selling the products or services. Although the description that
30 follows refers to such customer leads, in alternative embodiments, rather than leads, other types of records or

requests are routed to appropriate individuals using such a system.

Lead management server 100 routes a lead 162 to a particular user based on an internal configuration, which
5 includes, for instance, rules for handling leads with different attributes and preferences for particular users.

In this embodiment, the lead management server is configured in a decentralized manner. That is, an administrator of the server may set global configurations
10 using administration interface 105, while individual users set individual configurations using user interfaces 110. The global configuration typically handles a first level of routing of leads to particular users. When a lead is routed to a particular user, the configuration provided by
15 that user generally determines how the lead is further handled. For instance, in the case that the user is a sales representative, the user may have specified a preferred method of being notified of a new lead, for example notification by email or by pager. Some users may
20 also have configured the lead management system to automatically route some or all leads sent to them to other users. For example, a sales manager may configure his lead box to automatically route leads to particular sales representations based on the geographic region of the lead.

25 When a lead is sent to a user, the user must in generally provide feedback to the lead management system indicating that the lead is accepted, that it is rejected, or that it should be forwarded to another user. Various approaches are used to encourage a user to provide this
30 feedback. For example, some information related to the lead may be withheld until the user provides feedback that indicates that the user is accepting the lead. The status of each lead is tracked by lead management server 100 and this status can be accessed by the users of the system.

In addition to routing leads when they arrive, lead management server 100 has the capability of re-routing leads after they have been routed to a particular user. For example, the server can periodically re-route leads that have been sent to particular users but have not yet been accepted or rejected. Also, the lead management server can adaptively modify its routing of leads based, for example, on the number of outstanding leads assigned to a particular user, or based on a statistical criterion, such as the responsiveness of a particular user, of their success in obtaining actual sales from leads that have been assigned to them.

In one mode of routing leads, lead management server 100 assigns a lead to a class of users, and then chooses a particular user in that class in a round robin manner such that successive leads assigned to the class are routed to different users. In another mode, leads are routed to multiple users, or multiple secondary servers (e.g., corresponding to multiple resellers), in an "up for grabs" mode. In this mode, although multiple users are initially assigned a lead, only the first to accept the lead keeps it. The others then receive notifications that the lead is no longer available.

Lead management server maintains a history of activity related to a lead, and in particular maintains a history of the rules applied to a lead, the sequence of users to whom the lead has been routed, and changes of state of a lead. This history is used to "progressively close the loop" by associating the progress of a lead, for example its generation of an actual sale, with its history. For example, this allows sales to be associated with particular marketing activities. In addition, the history is used to optimize the rules by determining the effectiveness of routing leads with particular attributes to particular

users. Also, in alternative embodiments, the history is used to determine statistics that are used to affect further lead routing.

5 A user that has accepted a lead may update the status of the lead as he or she interacts with the lead. In some instances, a lead does not result in a sale, but the user indicates that the lead should be reactivated after an "incubation" period. After the lead is later reactivated, it is re-routed in the same manner as a new lead entering
10 the system.

Referring still to FIG. 1, lead management server 100 is also optionally coupled to one or more secondary lead management servers 150. These servers are similar to lead management server 100, and optionally may be restricted to
15 received leads only from the lead management server, and not directly from other lead sources. After the lead is routed to the secondary server, it is essentially replicated in the lead storage of both servers, although the fields of the two stored leads may not be identical, since some details regarding the lead may be withheld by
20 the secondary server. The lead management server updates the lead based on feedback from the secondary server when it updates its copy of the lead, for example when the lead is assigned to a user. An exemplary application of the lead management system has a vendor operating lead
25 management server 100 and resellers operating secondary lead management servers 150. The vendor has users 100, such as direct sales representatives, who receive leads directly from lead management server 100. Some leads are sent to a reseller by transferring lead information to the
30 secondary server. The secondary server may provide some feedback information regarding the status of the lead to the lead management server 100. However, for example for competitive business reasons, some information such as the

identity of a particular user assigned a lead by secondary lead management server 150 or contact information related to the lead may be kept private to the secondary system.

Leads may also be routed to users by lead management server 100 through other information systems 130. For example, lead management server 100 can route leads to a opportunity management tool provided by Siebel Systems Inc.

Lead management system 100 is also coupled to a secondary information source 120. This information source is used to augment the information associated with a lead 162 that it receives from lead source 160. For example, Dunn and Bradstreet information, product literature, or sales tools may be associated with a lead and routed to a user along with the lead.

Referring still to FIG. 1, a user interacts with lead management server 100 through a user interface 110, which may include a computer, a pager, or a telephone. In general, a user provides configuration 112 to the server, for example specifying rules for routing leads provided to that user, and configuring the method for notifying that user when leads are available. The user receives notifications and leads 114 from the server, and in return provides explicit acceptances 116 for the leads back to the server.

Referring to FIG. 2, the lead management system is implemented using a number of computers coupled to one another through Internet 210. In alternative embodiments, other communication interconnections are also feasible, for example, relying on dedicated or "dial-up" connections between computers. Lead management server 100 is implemented on a lead management server computer 200 that is coupled to Internet 210. Lead management server computer 200 executes a number of software processes. In particular, server computer 200 executes a Web client 211

for accessing other computers over Internet 210 using the
http (hyper-text transport protocol) application protocol,
a Web server 202 for providing other computer access to it
over Internet 210 using the http protocol, and a mail
5 interface 203 for accessing users at other computers using
electronic mail that is transferred over the Internet. In
addition, lead management server computer 200 is coupled to
batch input/output devices 204, for example magnetic tape
drives, that are used to import or export data from the
10 server computer. The lead management server computer is
optionally coupled to other systems over other
communication links 205, for example over dedicate data
connections.

Each user typically interacts with the system using a
15 user computer 210. For instance, user computer 210
executes a mail interface 212 that accepts messages from
mail interface 203 at lead management server computer 200
and that is used to send messages back to the lead
management server computer. User computer 210 also
20 includes a Web browser 211 for accessing Web server 202 at
lead management server computer 200. In some embodiments,
user computer 210 may include only a mail interface or a
Web browser, rather than both. In other embodiments,
client computer 210 is coupled to lead management server
25 computer 200 in any of a number of well-known techniques,
for example using a dedicated client application which
executes on the client computer and which communicates with
a server application at the lead management server
computer.

30 In this embodiment, users can also be notified using a
wireless paging system. In this case, lead management
server computer 200 sends a electronic mail message through
its mail interface 203 to a pager server 218 over the

Internet, and the pager server sends a wireless message to the user's pager 215.

Lead management server computer 200 can also communicate with other lead management systems 230 over the Internet, for example to route leads to those systems, or to accept leads from those systems. Lead management server computer 200 can also communicate with secondary lead management server computers 250 over the Internet, for instance using the http protocol, for the purpose of passing leads to the secondary servers and for receiving feedback regarding the status of leads that it previously passed.

Referring to FIG. 3, lead management server 100 logically has several modules which are implemented using physical storage devices, or as processes executing on a computer processor according to a program stored on program storage 310. Leads 162 are accepted by a lead import module 310. Lead import module 310 performs initial processing functions to input the lead into the system. Leads are passed to a data cleansing and enhancement module 320, which corrects errors in the imported lead, for instance based on secondary information sources 120, and augments the lead, for example by attaching company information from a secondary information source.

The lead is then passed to rules engine 330 and the lead is stored in lead storage 340. Lead storage 340 is logically implemented as an object database, which is then actually implemented using relational database techniques. Rules engine 330 is also coupled to a rules and profile storage 350 that hold rules specified by an administrator to the system as a whole, or by users for leads that are delivered to them. Rules engine 330 makes use of the rules in rules and profile storage 350 to modify the leads in lead storage 340, thereby logically routing the lead to

particular users. Lead management system 100 includes a notification, delivery, and tracking module 370 that notifies users of leads, provides lead information to the users, and accepts responses, such as acceptances, rejections, and rerouting of the leads provided to the user. When rules engine 330 routes a lead to a secondary lead management system, the lead is passed to a server-server lead module 380 which provides the lead information to the secondary server, and accept notifications regarding routing and changes of state of the lead from the secondary system.

Referring to FIG. 4, logically, the leads stored in lead storage 340 (FIG. 3) logically flow through a succession of lead boxes, which are somewhat analogous to mail boxes. Initially, a lead is placed in a system lead box 410, and as it is routed to the final user, the lead may pass through a succession of user lead boxes 420. Each lead box is associated with configuration data, which includes rules to apply to leads that are routed to that lead box. Each lead has a number of attributes, such as the name of the lead, the lead's organization, the organization's address, the product involved, the marketing campaign involved, and the likelihood of a sale. Rules are defined in terms of the attributes. There are several types of rules that are applied to a lead.

A prioritization rule assigns a numeric or categorical priority to a lead based on other attributes of the lead. Note that this prioritization may be different in different lead boxes. An assignment rule determines which next lead box the lead should be routed to, again based on the attributes associated with the lead. An attachment rule, which is also based on the particular attributes of a lead, determines what additional information should be attached to the lead prior to routing it further. For example,

product specifications can be attached and delivered to a user with the lead. Note that the information attached to the lead may be provided to enable a user to better service a lead, rather than simply provide more information about the lead itself. An example of such information is documentation of a promotional program that could be used to encourage a customer to buy a product or service. Other examples include training presentations (e.g., video presentations) to better prepare the user for selling a particular product, order forms, or rebate information. These attachments may be provides as references to documents (e.g., URLs) that the user then accesses over the Internet, rather than being provided in their entirety.

A user specifies a particular rule to apply to leads in his or her lead box 420 through user interface 110. This specification is typically based on a selection from a small number of types of rules, and selection from a constrained set of parameters for the rule. The system includes a "wizard" mode that specifies a rule by presenting a sequence of selections to be made or questions to be answered by the user, for example having the user select which attribute to use in determining where to route leads. The system holds definitions for these types (or classes) of rules, and specifications of the wizard modes for rule selection. A user with appropriate access privileges can specify the types of rules that another user may choose from, and the wizard mode that the other user can use to select a particular rule. The wizard is specified using XML (eXtensible Markup Language) and essentially forms a template for the particular rules that the users that make use of the wizard can choose. In some embodiments, the users are arranged in a hierarchy or tree and a user has the privilege to specify a wizard for the users branching from that user's node in the tree (i.e.,

below that user's node if the root of the tree is at the top). For example, a user who supervises a set of other users may configure their lead boxes with a wizard that allows those users to specify particular rules from a class
5 of rules specified by that supervisor.

Referring to FIG. 5, logically, based on an exemplary application of rules by rules engine 330 (FIGS. 3, 4) a lead passes through a branching tree of lead boxes. Initially at system lead box 410, leads are routed based on
10 system-wide routing rules to a user lead box 420, for instance by routing the lead to a lead box associated with a geographic region, such as the eastern US. Based on the rules at that lead box, the lead may be routed again to another lead box 410, for instance one associated with a
15 smaller geographic region, such as a particular state in the US, and finally to a user interface 110, for instance associated with a sales representative for that state. Alternatively, in another exemplary application of the rules, a lead may be passed to a system lead box 410 at a
20 secondary lead management system, where it is passed through user lead boxes 420 and finally to a user interface 110.

Each lead is tracked by lead management system 100 as it is routed from lead box to lead box, and as it is
25 provided and then later accepted or rejected by a user. Therefore, users can determine the status of leads. Referring back to FIG. 1, lead management server 100 is coupled to a reporting interface 140. Based on the information regarding routing and status of lead in the
30 lead management system, detailed reports regarding aspects of sets of leads can be directly determined. For example, statistics regarding completion of sales from a particular marketing campaign, or in a particular geographic region can be prepared. These reports provide feedback from sales

activities, for example, to determine the effectiveness of particular marketing campaigns or the effectiveness of particular rules in the system.

5 The following additional documents are attached as an appendix to this description:

1. Press release, dated May 24, 1999 (4 sheets)
2. "Marketsoft Corporation Architectural Overview,"
viewgraphs dated May 18, 1999 (24 sheets)
- 10 3. "Navigating Through Marketsoft," a user manual,
including images of a graphical user interface (36
sheets)
4. "Rule Explanation," a document describing types of
rules with examples (13 sheets)
- 15 5. "Marketsoft Architectural Blueprint," (7 sheets)
6. "Launch Product Plan 5/6/99" (2 sheets)
7. "Feature Profiles M2.1 Pilot," (8 sheets)
8. "Feature Profiles M2.2," (22 sheets)
9. "Feature Profiles M3: V1.0 / FCS," (24 sheets)
- 20 10. Database schema, (50 sheets)

It is to be understood that the foregoing description is intended to illustrate and not to limit the scope of the invention, which is defined by the scope of the appended claims. Other embodiments are within the scope of the
25 following claims.

What is claimed is:

1 1. A method for processing customer leads
2 comprising:
3 accepting a lead that includes a plurality of
4 data fields;
5 for each of a plurality of users, accepting a
6 plurality of rule specification for that users;
7 routing the lead to a first of the users;
8 applying one or more of the rules that were
9 accepted for that user to the lead;
10 routing the lead to a second of the users based
11 on the application of the rules;
12 notifying the second of the users of the routed
13 lead; and
14 receiving from the second user an acceptance of
15 the routed lead.
16




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5