


1996 IEEE ICASSP

VOL. 6





# **The 1996 IEEE International Conference on Acoustics, Speech, and Signal Processing Conference Proceedings**

**Sponsored by the Signal Processing Society of the Institute of Electrical and  
Electronics Engineers**

**May 7-10, 1996  
Marriott Marquis Hotel  
Atlanta, Georgia, USA**

---

## **The 1996 IEEE International Conference on Acoustics, Speech, and Signal Processing Conference Proceedings**

Copyright and Reprint Permission: Abstracting is permitted with credit to the source. Libraries are permitted to photocopy beyond the limit of U.S. copyright law for private use of patrons those articles in this volume that carry a code at the bottom of the first page, provided the per-copy fee indicated in the code is paid through Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923. For other copying, reprint or republication permission, write to IEEE

Copyrights Manager, IEEE Service Center, 445 Hoes Lane, P.O. Box 1331, Piscataway, NJ 08855-1331. All rights reserved. Copyright 1996 by the Institute of Electrical and Electronics Engineers, Inc.

IEEE Catalog Number: 96CH35903  
IEEE Catalog Number 96CH35903  
ISBN 0-7803-3192-3 (softbound)  
ISBN 0-7803-3193-1 (casebound)  
ISBN 0-7803-3194-X (microfiche)  
ISBN 0-7803-3195-8 (CD-Rom)  
Library of Congress: 84-645139

IEEE Service Center  
445 Hoes Lane  
P.O. Box 1331  
Piscataway, NJ 08855-1331  
1-800-678-IEEE

## Volume VI

### UA1 Detection Classification and Localization

|                                                                                                       |         |
|-------------------------------------------------------------------------------------------------------|---------|
| <b>IER Clutter Reduction In Shallow Water</b> .....                                                   | VI-3041 |
| <i>F. Shin, D. Kil - Loral Defense Systems, USA</i>                                                   |         |
| <i>R. Wayland - Naval Air Warfare Center, USA</i>                                                     |         |
| <b>A Modified Eckart Post-Beamformer Filter for Improved Detection Using Broadband Features</b> ..... | VI-3045 |
| <i>S. Mehta, J. Fay, P. Maciejewski - Naval Undersea Warfare Center Division Newport, USA</i>         |         |
| <b>Feature Extraction and Sufficient Statistics in Detection and Classification</b> .....             | VI-3049 |
| <i>E. Real - Sanders, A Lockheed-Martin Co., USA</i>                                                  |         |
| <b>Gerschgorin Radii Based Source Number Detection for Closely Spaced Signals</b> .....               | VI-3053 |
| <i>J. Yang, H. Wu - National Cheng Kung University, ROC</i>                                           |         |
| <b>A Wavelet Transform Frequency Classifier for Stochastic Transient Signals</b> .....                | VI-3057 |
| <i>F. Garcia, I. Lourtie - ISR/IST, Portugal</i>                                                      |         |
| <b>Classification with a Combined Information Test</b> .....                                          | VI-3061 |
| <i>R. Lynch - Naval Undersea Warfare Center, USA</i>                                                  |         |
| <i>P. Willett - University of Connecticut, USA</i>                                                    |         |
| <b>3-D MUSIC with Polynomial Rooting for Near-Field Source Localization</b> .....                     | VI-3065 |
| <i>H. Hung, S. Chang, C. Wu - National Taiwan Ocean University, Taiwan</i>                            |         |
| <b>Closed-Form Elliptic Location with an Arbitrary Array Topology</b> .....                           | VI-3069 |
| <i>U. Hanebeck, G. Schmidt - Technical University of Munich, Germany</i>                              |         |
| <b>Source Localisation with Recurrent Neural Networks</b> .....                                       | VI-3073 |
| <i>B. Colnet, J. Di Martino - CRIN-INRIA CNRS, France</i>                                             |         |

### UA2 Matched Field Processing and Special Environments

|                                                                                                                                    |         |
|------------------------------------------------------------------------------------------------------------------------------------|---------|
| <b>A Test for Detection of Local Modeling Mismatches in Shallow Water</b> .....                                                    | VI-3077 |
| <i>G. Fostik, J. Tabrikian, H. Messer - Tel Aviv University, Israel</i>                                                            |         |
| <b>Broadband Matched Field Processing Using Robust Prewhitening and Multiple Window Techniques</b> .....                           | VI-3081 |
| <i>C. Mecklenbrauker, M. Geravanchizadeh, J. Bohme - Ruhr-University of Bochum, Germany</i>                                        |         |
| <b>Focalization in the Gulf of Mexico</b> .....                                                                                    | VI-3085 |
| <i>Z. Michalopoulou, M. Porter - New Jersey Institute of Technology, USA</i>                                                       |         |
| <b>Robust ML Source Localization by Exploiting Predictable Acoustic Modes</b> .....                                                | VI-3089 |
| <i>J. Tabrikian - Tel-Aviv University, Israel</i>                                                                                  |         |
| <i>J. Krolik - Duke University, USA</i>                                                                                            |         |
| <i>H. Messer - Tel-Aviv University, Israel</i>                                                                                     |         |
| <b>A Sub-Space Method for High Resolution Bathymetry</b> .....                                                                     | VI-3093 |
| <i>A. Antoniou, R. Pillai - University of Victoria, Canada</i>                                                                     |         |
| <b>Multiresolution Stochastic Models for the Efficient Solution of Large-Scale Space Time Estimation Problems</b> .....            | VI-3097 |
| <i>T. Ho, P. Fieguth, A. Willsky - LIDS, MIT, USA</i>                                                                              |         |
| <b>A Comparison of Two Techniques for Detecting Seizure in Newborn EEG Data</b> .....                                              | VI-3101 |
| <i>M. Roessgen - Queensland University of Technology, Australia</i>                                                                |         |
| <b>Classification of Radar Returns Using Wigner-Ville Distribution</b> .....                                                       | VI-3105 |
| <i>P. Kumar, K. Prabhu - Indian Institute of Technology, India</i>                                                                 |         |
| <b>On the Design of a Transversal Filter Bank for Parallel Processing Multiple Image Lines in Real-Time Acoustic Imaging</b> ..... | VI-3109 |
| <i>J. Shen, E. Ebbini - The University of Michigan, USA</i>                                                                        |         |
| <b>A Minimax Optimization Approach to Sidelobe Suppression Filter Design</b> .....                                                 | VI-3113 |
| <i>S. Park, J. Doherty - Iowa State University, USA</i>                                                                            |         |

## Volume VI

### UA3 Time-Delay Estimation

- An EM Algorithm for Multisensor TDOA/DD Estimation in a Multipath Propagation Environment** .....VI-3117  
*S. Belanger - Loral Federal Systems, USA*
- Adaptive Realization of a Maximum Likelihood Time Delay Estimator** .....VI-3121  
*P. Hahn, V. Mathews, T. Tsen - University of Utah, USA*
- Robust Time Delay Estimation Using Lower-Order Statistics** .....VI-3125  
*X. Ma, C. Nikias - University of Southern California, USA*
- New Perspectives for Maximum-Likelihood Parameter and Time Delay Estimation Using Two Channels** .....VI-3129  
*J. Stuller, N. Hubing - University of Missouri-Rolla, USA*
- Iterative Maximum-Likelihood/Cross-Correlation Algorithm for Reflection and Pulse T.O.A. Estimation** .....VI-3133  
*A. Doser, P. Delaney, L. Schooley - University of Arizona, USA*
- The Issue of Phase in Specular Multipath Parameter Estimation** .....VI-3137  
*Z. Mitrovski, E. Titlebaum - University of Rochester, USA*
- Short Time Correlator Delay Estimation in the Presence of Interfering Sources** .....VI-3141  
*B. Daku - University of Saskatchewan, USA*  
*C. McIntyre - Defense Research Establishment Atlantic, USA*
- Estimation of Delay and Doppler by Wavelet Transform** .....VI-3145  
*K. Ho, Y. Chan, M. Johnson - Royal Military College of Canada, Canada*
- Blind Deconvolution of Echosounder Envelopes** .....VI-3149  
*D. Caughey, R. Kirlin - University of Victoria, Canada*
- The Bootstrap Applied to Passive Acoustic Aircraft Parameter Estimation** .....VI-3153  
*D. Reid, A. Zoubir, B. Boashash - Queensland University of Technology, Australia*

### UA4 Sonar Beamforming

- Capability of Minimum Variance Beamformer for Direction Finding for Fast Perturbations of Array Sensors** .....VI-3157  
*G. Serebryakov - State University, Russia*
- Linear Programming in Spectral Estimation: Application to Array Processing** .....VI-3161  
*J. Fuchs - IRISA - Universite de Rennes I, France*
- Interpolated Array Minimum Variance Beamforming For Correlated Interference Rejection** .....VI-3165  
*A. Zeira - Signal Processing Technology, USA*  
*B. Friedlander - University of California at Davis, USA*
- Surface-Mounted Acoustic Vector-Sensor Array Processing** .....VI-3169  
*M. Hawkes, A. Nehorai - Yale University, USA*
- Spatial Processing Technique Adaptive Beamforming (SPTABF) Via Compactly Supported Orthonormal Wavelets** .....VI-3173  
*S. Chang, C. Chang, C.L. Chang, W. Fang - National Taiwan Ocean University, Taiwan*
- Beamforming Design with Partially Adaptive and Minimum Redundancy Arrays** .....VI-3177  
*L. Lo Presti, G. Montalbano, G. Povero - Politecnico di Torino, Italy*
- Rank Enhancement for Eigenstructure Based Direction Finding Using Arrays with Non-Uniform Element Responses** ...VI-3181  
*B. Jeffs - Brigham Young University, USA*
- Coarray Analysis of Wideband Pulse-Echo Imaging Systems** .....VI-3185  
*F. Ahmad, S. Kassam - University of Pennsylvania, USA*
- A Novel High-Resolution Algorithm for Complex-Direction Search** .....VI-3189  
*R. Qiu, I. Lu - Polytechnic University, USA*
- Broadband Eigenvector Methods for Towed Array Shape Estimation with a Single Source** .....VI-3193  
*J. Smith, Y. Leung, A. Cantoni - Australian Telecommunications Research Institute, Australia*

## VLSI1 Novel Approaches Towards DSP Application

- A High Performance Microphone Array System for Hearing Aid Applications** .....VI-3197  
*A. Wang, K. Yao, R. Hudson, D. Korompis - University of California at Los Angeles, USA*
- Control and Data Flow Aspects in the Design of a Wireless Data Radio Modem: A Case Study** .....VI-3201  
*G. Post, O. Mauss - Aachen University of Technology, Germany*
- Variance Mismatch: Identifying Random Test Resistance in DSP Datapaths** .....VI-3205  
*L. Goodby, A. Orailoglu - University of California at San Diego, USA*
- Digital Oscillators Over Finite Fields** .....VI-3209  
*W. Chren - Grand Valley State University, USA*  
*B. Wyman - Ohio State University, USA*
- Simultaneous Speech Segmentation and Phoneme Recognition Using Dynamic Programming** .....VI-3213  
*R. Bajwa, R. Owens - Pennsylvania State University, USA*  
*T. Kelliher - Westminster College, USA*
- Engineering Multirate Convolutions for Radar Imaging** .....VI-3217  
*L. Bierens, E. Deprettere - Delft University of Technology, The Netherlands*
- A Fast Full-Search Motion Estimation Method for Programmable Processors with a Multiply-Accumulator** .....VI-3221  
*Y. Naito, T. Miyazaki, I. Kuroda - NEC Corporation, Japan*
- Parallel Computation of Discrete Legendre Transforms** .....VI-3225  
*M. Aburdene - Bucknell University, USA*  
*J. Dorband - Goddard Space Flight Center, USA*
- New Look-Ahead Algorithm for Pipelined Implementation of Recursive Digital Filters** .....VI-3229  
*A. Shaw, M. Imtiaz - Wright State University, USA*
- Telekom's MAGENTA Algorithm for En-/Decryption in the Gigabit/sec Range** .....VI-3233  
*K. Huber, S. Wolter - German Telekom, Germany*

## VLSI2 Architectures for Video, Speech, and Filtering Applications

- Optoelectronic Image Processor for Multiresolution Gabor Filtering** .....VI-3236  
*H. Urey, W. Rhodes, S. DeWeerth, T. Drabik - Georgia Institute of Technology, USA*
- Low-Power Video Encoder-Decoder Using Wavelet/TSVQ with Conditional Replenishment** .....VI-3240  
*W. Namgoong, N. Chaddha, T. Meng - Stanford University, USA*
- Low-Complexity Algorithm and Architecture for Block-Based Motion Estimation via One-Bit Transforms** .....VI-3244  
*B. Natarajan, V. Bhaskaran, K. Konstantinides - Hewlett-Packard Laboratories, USA*
- A Binary Block Matching Architecture with Reduced Power Consumption and Silicon Area Requirement** .....VI-3248  
*M. Mizuki, U. Desai, I. Masaki, A. Chandrakasan - MIT, USA*
- A Programmable Application-Specific CELP Processor with Parallel Architectures** .....VI-3252  
*A. Suen, J. Wang, B. Liu - National Cheng Kung University, ROC*
- Efficient Realizations of Analysis and Synthesis Filters Based on the 2-D Discrete Wavelet Transform** .....VI-3256  
*C. Chakrabarti, C. Mumford - Arizona State University, USA*
- Design Tradeoffs in CMOS FIR Filters** .....VI-3260  
*C. Nagendra, M. Irwin - Pennsylvania State University, USA*
- M-Array VLSI Architecture for Order Statistic Filters** .....VI-3264  
*C. Lin, C. Kuo - National Chung Cheng University, Taiwan*
- Time-Area Efficient Multiplier-free Recursive Filter Architectures for FPGA Implementations** .....VI-3268  
*M. Shajaan, J. Sorensen - Technical University of Denmark, Denmark*

## VLSI3 DSP Architectures

- Comparison of Two Architectures for Implementation of the Discrete Cosine Transform** .....VI-3272  
*I. Sundsbo, G. Lokken Hansen, E. Aas - The Norwegian Institute of Technology, Norway*
- Multidimensional Systolic Arrays for Multidimensional DFTs** .....VI-3276  
*H. Lim, E. Swartzlander - University of Texas at Austin, USA*
- ASAP-A 2-D DFT Processor and Architecture** ..... VI-3280  
*J. Mellott, M. Lewis, F. Taylor - University of Florida, USA*  
*P. Coeffield - USAF Wright Labs, USA*
- A New Survivor Memory Management Method in Viterbi-Decoders: Trace-Delete Method and its Implementation** .....VI-3284  
*S. Jung, H. Choi - Sung-Kyun-Kwon University, Korea*  
*M. Lee - Samsung Electronics, Korea*
- Efficient Standard Basis Reed-Solomon Encoder** .....VI-3287  
*S. Jain - Intel Corporation, USA*  
*K. Parhi - University of Minnesota, USA*
- An Area-Efficient VLSI Architecture for Decoding of Reed-Solomon Codes** .....VI-3291  
*J. Hsu, C. Wang - National Tsing Hua University, ROC*
- High-Speed Parallel Hard and Soft-Decision Golay Decoder: Algorithm and VLSI-Architecture** .....VI-3295  
*W. Cao - Fraunhofer-Institute for Integrated Circuits, Germany*
- Granularly-Pipelined Cordic Processors for Sine and Cosine Generators** .....VI-3298  
*S. Wang - University of Texas at Austin, USA*  
*V. Piuri - Politecnico di Milano, Italy*  
*E. Swartzlander - University of Texas at Austin, USA*
- RNIW: A Novel General-Purpose DSP Architecture** .....VI-3302  
*H. Qing, H. Chao-Huan - Chinese Academy of Sciences, China*

## VLSI4 Design Aids for Signal Processing Systems

- An Extension of Multi Dimensional Synchronous Dataflow to Handle Arbitrary Sampling Lattices** .....VI-3306  
*P. Murthy, E. Lee - University of California at Berkeley, USA*
- On Retiming of Multirate DSP Algorithms** .....VI-3310  
*V. Zivojnovic, R. Schoenen, H. Meyr - Aachen University of Technology, Germany*
- Real-Time Scheduling for Pipelined Execution of Data Flow Graphs on a Realistic Multiprocessor Architecture** .....VI-3314  
*J. Jonsson, J. Vasell - Chalmers University of Technology, Sweden*
- Optimal Communication Scheduling Based on Collision Graph Model** .....VI-3318  
*D. Surma, S. Tongsim, E. Sha - University of Notre Dame, USA*
- Hierarchization of a Priori Defined Dataflow Subgraphs** .....VI-3322  
*M. Willems, V. Zivojnovic, S. Ritz - Aachen University of Technology, Germany*
- Instruction-Level Power Profiling** .....VI-3326  
*H. Mehta, R. Owens, M. Irwin - Pennsylvania State University, USA*
- Two-Dimensional Retiming with Low Memory Requirements** .....VI-3330  
*T. Denk, M. Majumdar, K. Parhi - University of Minnesota, USA*
- Knowledge-Based Transformation Ordering: Implementing a Linear Computation Using an Arbitrary Low Power at an Arbitrary High Throughput** .....VI-3334  
*M. Srivastava - AT&T Bell Laboratories, USA*  
*M. Potkonjak - NEC USA, USA*
- A Hierarchical Approach to Transistor-Level Power Estimation of Arithmetic Units** .....VI-3338  
*J. Satyanarayana, K. Parhi - University of Minnesota, USA*
- Calypso: An Implementation of the Order Graph Method** .....VI-3342  
*G. Cato, D. Reeves - North Carolina State University, USA*

## PRNN1 Neural Networks for Speech Processing

|                                                                                                                                                      |                |
|------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>A Telephone-Based Directory Assistance System Adaptively Trained Using Minimum Classification Error / Generalized Probabilistic Descent .....</b> | <b>VI-3346</b> |
| <i>E. McDermott - ATR HIP Research Laboratories, Japan</i>                                                                                           |                |
| <i>E. Woudenberg - ATR International, Japan</i>                                                                                                      |                |
| <i>S. Katagiri - ATR IT Research Laboratories, Japan</i>                                                                                             |                |
| <b>REMAP - Experiments with Speech Recognition .....</b>                                                                                             | <b>VI-3350</b> |
| <i>Y. Konig, H. Bourlard, N. Morgan - ICSI, USA</i>                                                                                                  |                |
| <b>Strategies for Reducing the Complexity of a RNN Based Speech Recognizer .....</b>                                                                 | <b>VI-3354</b> |
| <i>K. Kasper, H. Reininger, H. Wust - Institut fur Agewandte Physik, Germany</i>                                                                     |                |
| <b>Environment-Independent Continuous Speech Recognition Using Neural Networks and Hidden Markov Models .....</b>                                    | <b>VI-3358</b> |
| <i>D. Yuk, C. Che, L. Jin, Q. Lin - Rutgers University, USA</i>                                                                                      |                |
| <b>Comparison Between Two Hybrid HMM/MLP Approaches in Speech Recognition .....</b>                                                                  | <b>VI-3362</b> |
| <i>C. Ris, V. Fontaine, H. Leich - Faculte Polytechnique de Mons, Belgium</i>                                                                        |                |
| <b>GPD Training of the State Weighting Functions in Hidden Control Neural Network .....</b>                                                          | <b>VI-3366</b> |
| <i>K. Na, S. Chae - Seoul National University, ROK</i>                                                                                               |                |
| <b>Continuous Mandarin Speech Recognition Using Heirarchical Recurrent Neural Networks .....</b>                                                     | <b>VI-3370</b> |
| <i>Y. Liao, W. Chen, S. Chen - National Chiao Tung University, ROC</i>                                                                               |                |
| <b>Probabilistic Mapping Networks for Speaker Recognition .....</b>                                                                                  | <b>VI-3374</b> |
| <i>H. Li, Y. Gong - CRIN-CNRS/INRIA - Lorraine, France</i>                                                                                           |                |
| <b>Shift-Tolerant K-Subspaces for Phoneme Recognition .....</b>                                                                                      | <b>VI-3378</b> |
| <i>D. Wu, J. Gowdy - Clemson University, USA</i>                                                                                                     |                |
| <b>Speaker-Adaptation in a Hybrid HMM-MLP Recognizer .....</b>                                                                                       | <b>VI-3382</b> |
| <i>J. Neto, C. Martins, L. Almeida - INESC/IST, Portugal</i>                                                                                         |                |

## PRNN2 Neural Network Techniques for Image Processing and Analysis

|                                                                                                                         |                |
|-------------------------------------------------------------------------------------------------------------------------|----------------|
| <b>Automatic Target Recognition Using Modularly Cascaded Vector Quantizers and Multilayer Perceptrons .....</b>         | <b>VI-3386</b> |
| <i>L. Chan, N. Nasrabadi, V. Mirelli - SUNY at Buffalo, USA</i>                                                         |                |
| <b>Distortion Equalized Fuzzy Competitive Learning for Image Data Vector Quantization .....</b>                         | <b>VI-3390</b> |
| <i>D. Butler - Bolton Institute, UK</i>                                                                                 |                |
| <i>J. Jiang - Loughborough University, UK</i>                                                                           |                |
| <b>Revisiting Boltzmann Learning: Parameter Estimation in Markov Fields .....</b>                                       | <b>VI-3394</b> |
| <i>L. Hansen, L. Andersen, U. Kjems, J. Larsen - Technical University of Denmark, Denmark</i>                           |                |
| <b>Morphological/Rank Neural Networks and their Adaptive Optimal Design for Image Processing .....</b>                  | <b>VI-3398</b> |
| <i>L. Pessoa, P. Maragos - Georgia Institute of Technology, USA</i>                                                     |                |
| <b>Nonlinear Color Image Restoration using Extended Redial Basis Function Networks .....</b>                            | <b>VI-3402</b> |
| <i>I. Cha, S. Kassam - University of Pennsylvania, USA</i>                                                              |                |
| <b>A Unification of Relaxation Labeling and Associative Memory .....</b>                                                | <b>VI-3406</b> |
| <i>X. Zhuang - University of Missouri- Columbia, USA</i>                                                                |                |
| <i>Y. Zhao - University of Illinois- Urbana- Champaign, USA</i>                                                         |                |
| <b>Motion-Based Segmentation by Principal Singular Vector (PSV) Clustering Method .....</b>                             | <b>VI-3410</b> |
| <i>S. Kung, Y. Lin, Y. Chen - Princeton University, USA</i>                                                             |                |
| <b>Multiplierless Neural Networks for Application to Digital Video .....</b>                                            | <b>VI-3414</b> |
| <i>M. Cavanagh, V. Jain - University of South Florida, USA</i>                                                          |                |
| <b>Neural Network Object Recognition for Inspection of Patient Setup in Radiation Therapy Using Portal Images .....</b> | <b>VI-3418</b> |
| <i>S. Young, C. Sibata, A. Ho, K. Shin - Roswell Park Cancer Institute, USA</i>                                         |                |
| <b>Efficient Learning of Standard Finite Normal Mixtures for Image Quantification .....</b>                             | <b>VI-3422</b> |
| <i>Y. Wang - Georgetown University Medical Center, USA</i>                                                              |                |
| <i>T. Adali - University of Maryland at College Park, USA</i>                                                           |                |

## PRNN3 Neural Networks and Pattern Recognition 1

|                                                                                                           |         |
|-----------------------------------------------------------------------------------------------------------|---------|
| <b>A Chain Coding Approach for Real-Time Recognition of On-line Handwritten Characters</b> .....          | VI-3426 |
| <i>H. Yuen - Hong Kong Polytechnic University, Hong Kong</i>                                              |         |
| <b>A Unified Approach to Hierarchical Classification</b> .....                                            | VI-3430 |
| <i>D. Kil, F. Shin - Loral Defense Systems, USA</i>                                                       |         |
| <b>A Soft-Decision Approach for Symbol Segmentation Within Handwritten Mathematical Expressions</b> ..... | VI-3434 |
| <i>S. Lehmborg, H. Winkler, M. Lang - Munich University of Technology, Germany</i>                        |         |
| <b>HMM-Based Handwritten Symbol Recognition Using On-Line and Off-Line Features</b> .....                 | VI-3438 |
| <i>H. Winkler - Munich University of Technology, Germany</i>                                              |         |
| <b>From Characters to Words: Dynamical Segmentation and Predictive Neural Networks</b> .....              | VI-3442 |
| <i>S. Garcia-Salicetti - Institut National des Telecommunications, France</i>                             |         |
| <i>P. Gallinari - LAFORIA National des Telecommunications, France</i>                                     |         |
| <i>B. Dorizzi, Z. Wimmer, J. Gentric - Institut National des Telecommunications, France</i>               |         |
| <b>A New Data Reduction Algorithm for Pattern Classification</b> .....                                    | VI-3446 |
| <i>H. Tahani, B. Plummer, N. Hamamali - University of Missouri, USA</i>                                   |         |
| <b>Fast Online Video Image Sequence Recognition with Statistical Methods</b> .....                        | VI-3450 |
| <i>M. Schuster, G. Rigoll - University of Duisburg, Germany</i>                                           |         |
| <b>Handwritten Word Recognition Using Dynamic Matching with Variable Duration</b> .....                   | VI-3454 |
| <i>G. Kim, V. Govindaraju, S. Srihari - CEDAR/State University of New York at Buffalo, USA</i>            |         |
| <b>Scale and Rotational Invariant Object Recognition Using Fractal Transformations</b> .....              | VI-3458 |
| <i>G. Neil, K. Curtis - University of Nottingham, UK</i>                                                  |         |
| <b>Optimal Discriminant Feature-Based Waveform Recognition with Neural Networks</b> .....                 | VI-3462 |
| <i>J. Miao, M. Clements - Georgia Institute of Technology, USA</i>                                        |         |

## PRNN4 Neural Networks and Pattern Recognition 2

|                                                                                                                          |         |
|--------------------------------------------------------------------------------------------------------------------------|---------|
| <b>Parsing in Attributed Grammars: Application to Automatic Sleep Analysis</b> .....                                     | VI-3466 |
| <i>A. Fred, J. Leitao - Instituto Superior Tecnico, Portugal</i>                                                         |         |
| <b>Affine Invariant Shape Representation and Recognition Using Gaussian Kernels and Multi-dimensional Indexing</b> ..... | VI-3470 |
| <i>J. Ben-Arie - University of Illinois at Chicago, USA</i>                                                              |         |
| <i>Z. Wang, K. Rao - Illinois Institute of Technology, USA</i>                                                           |         |
| <b>Road Scene Analysis from Perspective Image</b> .....                                                                  | VI-3474 |
| <i>J. Yang, S. Ozawa - Keio University, Japan</i>                                                                        |         |
| <b>Writer Dependent Recognition of On-Line Unconstrained Handwriting</b> .....                                           | VI-3478 |
| <i>J. Subrahmonia, K. Nathan, M. Perrone - IBM T.J. Watson Research Center, USA</i>                                      |         |
| <b>Duration Modelling Results for an On-Line Handwriting Recognizer</b> .....                                            | VI-3482 |
| <i>A. Senior, J. Subrahmonia, K. Nathan - IBM T.J. Watson Research Center, USA</i>                                       |         |
| <b>Properties of a Hand-Printed Chinese Character Recognizer Based on Contextual Vector Quantization</b> .....           | VI-3486 |
| <i>P. Chee, S. Leung, P. Wong, C. Chan - The University of Hong Kong, Hong Kong</i>                                      |         |
| <b>Optimized Consensus Theory</b> .....                                                                                  | VI-3490 |
| <i>J. Benediktsson, J. Sveinsson, P. Swain - University of Iceland</i>                                                   |         |
| <b>Chinese All Syllables Recognition Using Combination of Multiple Classifiers</b> .....                                 | VI-3494 |
| <i>L. Zhou, S. Imai - Tokyo Institute of Technology, Japan</i>                                                           |         |
| <b>Similarity Analysis of Cardiac Signals Using Temporal Features</b> .....                                              | VI-3498 |
| <i>B. de Jesus, L. Lucke - University of Minnesota, USA</i>                                                              |         |
| <b>Initialization of Hidden Markov Models for Unconstrained On-Line Handwriting Recognition</b> .....                    | VI-3502 |
| <i>K. Nathan, A. Senior, J. Subrahmonia - IBM T.J. Watson Research Center, USA</i>                                       |         |

## PRNN5 Nonlinear System Identification

- Diagnosing and Correcting System Anomalies with a Robust Classifier** .....VI-3506  
*J. Hampshire - Carnegie Mellon University, USA*  
*D. Watola - Jet Propulsion Laboratory, USA*
- Blind Separation of Delayed Sources Based on Information Maximization** .....VI-3509  
*K. Torkkola - Motorola, USA*
- Modeling Nonlinear Systems With Cellular Neural Networks** .....VI-3513  
*F. Puffer, R. Tetzlaff, D. Wolf - Institut für Angewandte Physik, Germany*
- Energy Demodulation of Two-Component AM-FM Signals with Application to Speaker Separation** .....VI-3517  
*B. Santhanam, P. Maragos - Georgia Institute of Technology, USA*
- Adaptive Non-linear System Identification Using Minimal Radial Basis Function Neural Network** .....VI-3521  
*L. Yingwei, N. Sundararajan, P. Saratchandran - Nanyang Technological University, Singapore*
- Expanding Gaussian Kernels for Multivariate Conditional Density Estimation** .....VI-3525  
*D. Davis, J. Hwang - University of Washington, USA*
- Fast Adaptive IIR-MLP Neural Networks for Signal Processing Applications** .....VI-3529  
*P. Campolucci, A. Uncini, F. Piazza - University of Ancona, Italy*
- Information Geometry of Maximum Partial Likelihood Estimation for Channel Equalization** .....VI-3533  
*J. Xuan, T. Adali, X. Liu - University of Maryland at College Park, USA*
- Statistical Analysis of the Single-Layer Backpropagation Algorithm with Bias Terms: Mean Weight Behavior** .....VI-3537  
*N. Bershad, J. Shynk - University of California, USA*
- Fast Nonlinear Adaptive Filtering Using a Partial Window Conjugate Gradient Algorithm** .....VI-3541  
*A. Birkett, R. Goubran - Carleton University, Canada*

## PRNN6 Modeling Theory and Architecture in Neural Networks

- Building an Application Framework for Speech and Pen Input Integration in Multimodal Learning Interfaces** .....VI-3545  
*M. Vo, C. Wood - Carnegie Mellon University, USA*
- TOM, A New Temporal Neural Net Architecture for Speech Signal Processing** .....VI-3549  
*S. Durand, F. Alexandre - Crin-CNRS/ INRIA Lorraine, France*
- A Probabilistic Decision-Based Neural Network for Locating Deformable Objects and its Applications to Surveillance System and Video Browsing** .....VI-3553  
*J. Lin, Y. Chan, S. Kung - Princeton University, USA*
- Self-Organizing Feature Maps with Perfect Organization** .....VI-3557  
*L. Owsley, L. Atlas - University of Washington, USA*  
*G. Bernard - Boeing Commercial Airplane Group, USA*
- Partial Likelihood for Real-Time Signal Processing** .....VI-3561  
*T. Adali - University of Maryland at College Park, USA*  
*K. Sonmez - University of Maryland Baltimore County, USA*  
*X. Liu - University of Maryland at College Park, USA*
- Robust Learning Algorithms for Nonlinear Filtering** .....VI-3565  
*D. Neumerkel, R. Shorten - Daimler-Benz AG, Germany*  
*A. Hambrecht - CEGELEC AEG, Germany*
- Advances in Using Hierarchical Mixture of Experts for Signal Classification** .....VI-3569  
*V. Ramamurti, J. Ghosh - The University of Texas at Austin, USA*
- Comparison of a Neural Network Detector vs Neyman-Pearson Optimal Detector** .....VI-3573  
*D. Andina, J. Sanz-Gonzalez - Universidad Politecnica Madrid, Spain*
- An Algorithm to Determine Hidden Markov Model Topology** .....VI-3577  
*R. Vasko, A. El-Jaroudi, J. Boston - University of Pittsburgh, USA*
- Wreath Products for Image Processing** .....VI-3581  
*D. Healy, Jr., G. Mirchandani, T. Olson, D. Rockmore - Dartmouth College, USA*

# BUILDING AN APPLICATION FRAMEWORK FOR SPEECH AND PEN INPUT INTEGRATION IN MULTIMODAL LEARNING INTERFACES

*Minh Tue Vo and Cindy Wood*

Interactive Systems Laboratories  
Carnegie Mellon University  
Pittsburgh, PA 15213-3890, U.S.A.  
Email: {tue, caw}@cs.cmu.edu

## ABSTRACT

While significant advances have been made in recent years to improve speech recognition performance, and more recently, gesture and handwriting recognition as well, speech- and pen-based systems have still not found broad acceptance in everyday life. One reason for this is the inflexibility of each input modality when used alone. Human communication is very natural and flexible because we can take advantage of a multiplicity of communication signals working in concert to supply complementary information or increase robustness with redundancy. In this paper we present a multimodal interface capable of jointly interpreting speech, pen-based gestures, and handwriting in the context of an appointment scheduling application. The interpretation engine based on semantic frame merging correctly interprets 80% of a multimodal data set assuming perfect speech and gesture/handwriting recognition; in the presence of recognition errors the interpretation performance is in the range of 35-62%. A dialog processing scheme uses task domain knowledge to guide the user in supplying information and permits human-computer interactions to span several related multimodal input events.

## 1. INTRODUCTION

Speech recognition is coming of age and is being incorporated into modern computer systems. Although pen input processing is still in its infancy compared to speech, pen-based systems have begun to appear in the form of personal digital assistants (PDAs) and pen laptops. However, current speech and pen systems are still not very popular and did not live up to the promise of bringing the power of computing to the population at large. Their failure is partly due to users' frustrations generated by inadequate recognition performance, especially for handwriting recognition. However, this failure is also an indication that current systems are too inflexible for the important task of facilitating the use of computers for everyone, especially people who may not be computer-literate. PDA users frustrated by gesture and handwriting recognition errors would naturally wish they could talk to their machines to correct the errors or simply to avoid having to write everything. Likewise users of speech-enabled systems quickly find out that there are tasks that cannot be conveniently expressed by spoken commands but would be enormously simplified by the ability to point to or circle objects on the screen in addition to speaking commands. These intuitive assertions were confirmed by a user study [1] conducted at Carnegie Mellon University, in which people interacting with a computer much preferred a combination of both speech and gestures over speech or gestures alone. Our own experiments with a calendar interface also show that when given a choice, people tend to use the communication method (or meth-

ods) most suitable for the task at hand and freely switch among available methods.

Research efforts at our Interactive Systems Laboratories (Carnegie Mellon University and University of Karlsruhe) are focused on producing a sensible and useful user interface by integrating multiple input modalities, rather than building better speech and gesture recognizers alone. An interface supporting the kind of highly flexible interaction we envision must be capable of integrating information from both speech and non-verbal input sources to arrive at a correct understanding of complete multimodal events. Some of our initial works along this line have been reported in previous publications [2][3][4][5]. This paper presents an approach to integrating speech, pen-based gestures, and handwriting, in the context of an appointment scheduling application. A multimodal interpretation engine jointly interprets information from all input sources by merging semantic frames. A domain-independent dialog processor maintains context information across input events. We evaluated the system with data collected in a user study conducted using the Wizard-of-Oz paradigm [6].


## 2. JEANIE: A MULTIMODAL CALENDAR

We have developed a prototype of a multimodal interface for an appointment scheduling program. A person using our Jeanie multimodal calendar can employ any combination of spoken input, gesturing with a pen on a touch-sensitive screen, or handwritten words to interact with the system. In typical scenarios, the user might say "Schedule a meeting on Monday" while at the same time drawing a box on the calendar to indicate where the new meeting should be inserted; write words on the newly scheduled meeting to annotate it; draw a cross on another meeting to cancel it; or point to a meeting and say "Reschedule this on Tuesday" or simply draw an arrow from that meeting to the new time slot on Tuesday.

An earlier version of this system was described in [4]. The interpretation engine in that system was based on an information-theoretic connectionist network [7] capable of incremental learning during use. Although that approach worked well for the preliminary system designed to explore multimodal interpretation, we found that the connectionist network was difficult to scale up when the task domain representation was significantly expanded in the new version. A semantic frame merging scheme was found to work much better on the larger and more complex action space, although we had to sacrifice the incremental learning capability.

Figure 1 shows a block diagram of the Jeanie system. The individual modality components (speech, gesture, and handwriting recognizers) are separate modules that can be replaced with ease. The calendar interface embodies domain knowledge and serves to isolate task-specific components. The heart of the system is the multimodal agent which interprets user input and performs

**FIGURE 1: The Jeanie multimodal calendar**



requested operations through the calendar interface. This section describes the calendar interface and the modality processors. The next section presents the multimodal agent and the multimodal interpretation algorithm.

### 2.1. Calendar Interface

The object-oriented calendar interface is based on ICAL, a public domain calendar program developed by Sanjay Ghemawat at MIT. We extended ICAL to support a weekly view and client/server operations. The multimodal agent acting as a client of the calendar interface can query it for information such as gesture contexts (see Section 2.2) and ask the interface to carry out scheduling operations which include adding, removing, and changing appointments and notes.

### 2.2. Modality Processors

Inputs captured by a speech recorder and a touch-sensitive screen are processed by separate recognizers for each modality. Semantic frames extracted from recognizer outputs are merged by the multimodal interpreter to arrive at a unified interpretation as described in Section 3.

**Speech.** Our speech recognition subsystem is based on the recognition front-end of the JANUS speech translation system [8][9] which is capable of processing speaker-independent, spontaneous speech and was trained on human-human dialogs in the appointment scheduling domain. On a small data set of 128 utterances collected in user study experiments, the word recognition rate was 82%; if we take into account insertion, substitution, and deletion errors, the word accuracy is 76%.

**Gesture.** In earlier implementations we employed a gesture recognition module [2] based on a TDNN classifier [10]. The present implementation increases flexibility by decomposing gestures into sequences of strokes recognized as basic shapes such as lines, arcs, arrows, circles, crosses... Each gesture component is augmented by *gesture contexts* indicating spatial relationships between the gesture and nearby objects in the calendar interface. The current implementation of the gesture recognizer uses simple

template matching and does not perform well on noisy input. A version based on the handwriting recognition algorithm described below is being developed and should greatly improve recognition performance.

**Handwriting.** Our handwriting recognizer developed by Stefan Manke at University of Karlsruhe based on the MS-TDNN [11] is capable of processing writer-independent, continuous (cursive) handwriting [12] at a recognition rate of over 90% on a 20,000-word vocabulary. Handwriting recognition is performed only when the gesture recognizer cannot identify the input strokes as basic shapes. This simple heuristic works fine for true cursive handwriting but can mistake writing strokes for gestures when it encounters printed block letters. This was unfortunately the case for some of the data collected in our user study; in addition most of the collected handwriting included uppercase letters for which the recognizer was not trained. These facts combined with gestures that were not adequately covered by templates led to a combined gesture/handwriting recognition rate of only 32%.

## 3. MULTIMODAL INTERPRETATION BY SEMANTIC FRAME MERGING

The multimodal interpreter is responsible for producing an interpretation of user intent (i.e., a command to send to the calendar interface) from the output of the modality processors. We represent this interpretation as a frame consisting of slots specifying pieces of information such as the action to carry out or the date and time of a meeting. Recognition output from the modality processors are parsed into partially filled frames that are merged together to produce the combined interpretation. The underlying algorithm is domain-independent although the encoding of information in frames must necessarily depend on the task domain.


This frame merging technique represents a much extended and improved implementation of the approach sketched in [2]. It leads to uniform handling of high-level information from all input sources, which is very important for modularity and extensibility. To add another input modality we need only provide a module to convert low-level recognizer output to a partially filled frame to be merged with others. In addition, context information can be retained across input events by merging with previous interpretation frames as implemented in our dialog processor (Section 3.3).

### 3.1. Parsing Inputs From Individual Modalities

The text string output from the speech recognizer is processed by the Phoenix semantic parser developed by Ward [13]. The parser compiles a grammar specifying semantically meaningful fragments of text into an efficient recurrent transition network that identifies these fragments in the recognized utterance. It is capable of skipping unknown words and unmatched fragments and can therefore deal gracefully with ungrammatical sentences. The concepts identified by the parser serve to determine which slots of the speech frame should be filled and what scores should be assigned to the slot values.

The gesture/handwriting recognizers produce a sequence of gesture/handwriting components. The same gesture shape may mean different things depending on the calendar context surrounding it; for instance, a line across an appointment may indicate deletion but the same line falling on an empty time slot may visually describe a new meeting to be scheduled. In the present implementation of Jeanie, gestures and handwritten words are encoded into frames according to simple hard-coded heuristics. The development of a grammar to drive this process may become necessary for more complex gestures and operations.

**FIGURE 2: Example of interpretation using frames**



### 3.2. Merging Frames and Extracting Hypotheses

Frames are merged by taking the union of the sets of values filling each slots and adding corresponding scores. Embedded frames are merged recursively. This produces an aggregate frame encoding all alternative interpretation hypotheses. The multimodal interpreter extracts these hypotheses in descending order of aggregate scores and sends the best ones to the dialog processor. Figure 2 shows an example taken from our actual test data.

### 3.3. Dialog Processing

A dialog between a user and the system can span several related multimodal events, where each event may contain one or more spoken utterances and/or pen gestures. The dialog processor maintains a single frame per dialog to hold all information obtained since the start of the dialog; new information from each additional input event is merged into this frame and the scores are weighted appropriately so that frames produced by different input events in the same dialog contribute equally to the end result.

The domain-independent dialog processor also consults the domain interface (i.e., the calendar in this case) to filter out hypotheses that would cause domain errors such as missing or conflicting parameters. If it fails to find an acceptable hypothesis with a high enough score, it uses the error information returned by the domain interface to construct an appropriate feedback message to guide the user (only this process depends on the task domain). As soon as a good hypothesis is found, the dialog processor sends it to the domain interface as the operation to carry out and starts a new dialog. The user has the option of undoing the operation just performed if it is incorrect.

## 4. USER STUDY AND DATA COLLECTION

In order to create a useful and robust multimodal system, we need to find out how people would use a system with such capabilities. We have begun a series of experiments following the Wizard-of-Oz paradigm [6], in which the test subjects were presented with

the Jeanie calendar interface and a hidden operator takes place of the real system in interpreting and carrying out multimodal commands. In parallel with the design of Jeanie, we conducted pilot experiments that contributed to the design of the frame representation for our task domain and yielded preliminary test data to evaluate the system.

Before the pilot experiment we conducted some small preliminary experiments to find out the types of gestures and speech people would use to make changes to a schedule, and to see if one modality was preferred over the other for certain tasks. That information was used to design pilot experiments that would illicit a mixture of speech and gestures from the test subjects. To get a variety of gestures that people might use the test subjects were first asked to make changes to a schedule using gestures only in any way they like. The same experiment was then repeated asking subjects to use speech only.

For the pilot experiments subjects were asked to make the changes by either giving voice commands or drawing on the touch screen or any combination of the two. Based on observations from the preliminary experiments we settled on instructing subjects by giving them a printed calendar with handwritten changes using as few words as possible and varying the wording to avoid speech contamination.

8 test subjects were used and a total of 13 trials were done for the preliminary and first set of pilot tests. The second pilot experiment consisted of 8 trials for 4 subjects using two completely different calendars to include a greater variety of tasks. In the pilot tests it was observed that some subjects preferred to use gestures more often, some preferred speech, others mixed the two. It was also observed that some tasks proved to be much easier to do by one method or the other; in those cases subjects chose the easier method regardless of general preference.

The pilot experiments showed, among other things, that test subjects often referred to a calendar event by using the name of a person or event, not just by a date and time; in addition, some subjects gave implied commands such as "On Tuesday I'm meeting with Bill, Tony, and Melanie" instead of "Add Tony and Melanie to the meeting with Bill on Tuesday". Test subjects with little computer experience tended to use implied commands most often, although we still do not have enough data to confirm such trends. The above observations significantly influenced the design of the frame representation.

## 5. PRELIMINARY PERFORMANCE EVALUATION

From our pilot Wizard-of-Oz experiments we obtained a small data set consisting of 185 multimodal events (77 speech-alone events, 57 pen-alone events, and 51 combination events). We transcribed each spoken utterance and pen gesture/handwriting as well as passing them through the modality recognizers. Results for all-transcribed inputs give us an idea of the performance of the multimodal interpreter, while results for recognized inputs offer some indication of performance degradation due to recognition errors.

The top-scored hypothesis produced by the interpreter for each input event is classified as *perfect*, *ok* (producing the intended result despite not being strictly correct), *ambiguous* (score too close to the next best hypothesis), *partially bad* (mostly correct except for one parameter), or *bad*. Table 1 shows the performance results for the pilot data. The pen data from the first pilot experiment could be transcribed but was unusable for recognition because of a flaw in the recording module which was cor-

**TABLE 1: Multimodal interpretation performance**  
(TS/TP: transcribed speech/pen, RS/RP: recognized speech/pen)

|       | number<br>of inputs | perfect<br>(%) | ok<br>(%) | ambi.<br>(%) | partially<br>bad (%) | bad<br>(%) |
|-------|---------------------|----------------|-----------|--------------|----------------------|------------|
| TS/TP | 185                 | 78             | 2         | 7            | 3                    | 10         |
| RS/TP | 185                 | 57             | 5         | 16           | 6                    | 16         |
| TS/RP | 100                 | 49             | 2         | 26           | 9                    | 14         |
| RS/RP | 100                 | 28             | 7         | 29           | 12                   | 24         |

rected for the second pilot experiment; because of this the bottom half of the table shows results for only the data set collected in this second experiment.

In the absence of recognition errors the multimodal interpreter will do the right thing 80% of the time (total of the *perfect* and *ok* columns), which is adequate for a usable system. At the other end of the spectrum the interpretation rate for all-recognized inputs is only 35%, a direct result of the poor 32% gesture/handwriting recognition rate.

The second row of the table shows that with a 76% word accuracy in speech recognition the interpretation rate drops to 62%. A closer analysis reveals that of the 18% that went from good to bad, about 15% occurred on speech-only events and only 3% occurred on combined speech/pen events. To put it another way, 27 of 77 (=35%) speech-only events caused interpretation errors due to speech recognition errors, compared to only 6 of 51 (=12%) combined events. On the pen-input side (only for the second data set of 100 input events), 11 of 18 (=61%) pen-only events caused interpretation errors due to gesture/handwriting recognition errors, compared to 19 of 39 (=49%) combined events. The sample is too small to assert any statistical significance, but this may be an indication of cross-modal redundancy at work.

We also observe that one significant effect of recognition errors is to increase the number of ambiguous outputs, more than the number of incorrect outputs. Recognition errors obviously reduce the amount of information available for interpretation, thereby causing more confusion. In interactive mode, the dialog processor can prompt the user with judicious guidance messages to supply clarifying information that could resolve ambiguities.

## 6. CONCLUSION

We have presented an architecture capable of joint interpretation of multimodal inputs and an example of a speech- and pen-enabled application using that architecture. The interpretation engine combines multiple input sources in a uniform and flexible way. The dialog processor maintains context information across input events and produces context-sensitive feedback to the user. The interpretation error rate is not unduly high but recognition errors may degrade performance significantly; however, we have seen indications that cross-modal redundancy can partly compensate for this degradation.

The pilot experiments have shown that the type of tasks we used in our Wizard setup will provide data for gesture, speech and a mixture of the two and will therefore be useful for the development and training of the Jeanie system. We are working on collecting more data to evaluate the system more fully, improve recognition rates, and refine parsing grammars. Experiments with the actual system in the loop rather than a Wizard operator are also being planned. Future studies should include experiments to investigate further the effect of cross-modal synergy in the pres-

ence of recognition errors to prove conclusively our intuitive assertions about the benefits of multimodal integration.

## 7. ACKNOWLEDGEMENTS

This research was sponsored by the Department of the Navy, Office of Naval Research under Grant number N00014-93-1-0806.

The views and conclusions contained in this document are those of the authors and should not be interpreted as necessarily representing the official policies or endorsements, either expressed or implied, of the Navy or the U.S. Government.

The authors would like to thank Dr. Alex Waibel for his guidance in this research and for his help in preparing this paper.

## 8. REFERENCES

- [1] Hauptmann, A.G., "Speech and Gestures for Graphic Image Manipulation," *Proc. CHI'89* (Austin, Texas).
- [2] Vo, M.T. and Waibel, A., "A Multimodal Human-Computer Interface: Combination of Speech and Gesture Recognition," *Adjunct Proc. InterCHI'93* (Amsterdam, The Netherlands).
- [3] Vo, M.T. and Waibel, A., "Multimodal Human-Computer Interaction," *Proc. ISSD'93* (Waseda, Japan).
- [4] Vo, M.T., Houghton, R., Yang, J., Bub, U., Meier, U., Waibel, A., and Duchnowski, P., "Multimodal Learning Interfaces," *Proc. ARPA SLT Workshop 95* (Austin, Texas).
- [5] Waibel, A., Vo, M.T., Duchnowski, P., and Manke, S., "Multimodal Interfaces," *Artificial Intelligence Review, Special Volume on Integration of Natural Language and Vision Processing*, McKevitt, P. (Ed.), Vol. 10, Nos. 3-4, 1995.
- [6] Salber, D. and Coutaz, J., "Applying the Wizard of Oz Technique to the Study of Multimodal Systems," *Proc. EWHCI'93* (Moscow, Russia).
- [7] Gorin, A.L., Levinson, S., Gertner, A., and Goldman, E., "Adaptive Acquisition of Language," *Computer, Speech and Language*, Vol. 5, No. 2, pp. 101-132, April 1991.
- [8] Woszczyna, M., Aoki-Waibel, N., Bug, F.D., Coccaro, N., Horiguchi, K., Kemp, T., Lavie, A., McNair, A., Polzin, T., Rogina, I., Rose, C.P., Schultz, T., Suhm, B., Tomita, M., and Waibel, A., "JANUS 93: Towards Spontaneous Speech Translation," *Proc. ICASSP'94* (Adelaide, Australia).
- [9] Suhm, B., Geutner, P., Kemp, T., Lavie, A., Mayfield, L., McNair, A., Rogina, I., Schultz, T., Sloboda, T., Ward, W., Woszczyna, M., and Waibel, A., "JANUS: Towards Multilingual Spoken Language Translation," *Proc. ARPA SLT Workshop 95* (Austin, Texas).
- [10] Waibel, A., Hanazawa, T., Hinton, G., Shikano, K., and Lang, K., "Phoneme Recognition Using Time-Delay Neural Networks," *IEEE Transactions on Acoustics, Speech, and Signal Processing*, Vol. 37, No. 3, 1989, pp. 328-339.
- [11] Haffner, P. and Waibel, A., "Multi-State Time Delay Neural Networks for Continuous Speech Recognition," *Advances in Neural Network Information Processing Systems 4*, Morgan Kaufmann Publishers, 1992, pp. 135-142.
- [12] Manke, S., Finke, M., and Waibel, A., "The Use of Dynamic Writing Information in a Connectionist On-Line Cursive Handwriting Recognition System," *Advances in Neural Network Information Processing Systems 6*, Morgan Kaufmann, 1994.
- [13] Ward, W., "Understanding Spontaneous Speech: the Phoenix System," *Proc. ICASSP'91* (Toronto, Canada).