BAZOOKA • FARMSTAR

WOLVERINE AGITATION BOAT

POWER AND EFFICIENCY. THE PERFECT MIX.

Meet the Wolverine: the legendary agitation boat equipped with two high-powered, articulating propellers to circulate massive amounts of liquid manure at a high velocity. It consistently lifts, suspends and mixes solids and liquids together to provide the perfect nutrient balance, resulting in an unrivaled agitation process.

- Easy maintenance
- Efficient & propeller-based
- Horsepower for next-level performance
- Highly maneuverable
- Simple transport, load & unload

FEATURES

ACHIEVE 24,000+ GPM

On average, it takes the Wolverine agitation boat 21 hours to turn over a 10 million gallon liquid manure lagoon three times at 24,000 GPM.

A RUGGED, LOW-COST SOLUTION

The Wolverine agitation boat was designed with durability, efficiency and ease of maintenance at the forefront. With zero gate valves, no mechanical seals and only eight hydraulic cylinders, the streamlined design simplifies the maintenance and cleaning process, saving you time and money.

UNMATCHED CLIMBING ABILITY

The high-torque drive system that complements the sheer size of its aggressive tires produces climbing ability that can't be matched. This is also thanks to the traction control system that ensures equal flow to each wheel.

REMOTE FUNCTIONALITY

All boat functions are proportionally controlled for a smooth operation. That means no more stopping, backing up and realigning your boat when entering awkward or tight manure storage structures. With Wolverine's intuitive remote, you can operate multiple functions at the same time.

WWW.BAZOOKAFARMSTAR.COM

QUALITY. INNOVATION. SERVICE.

800.775.7448 | 319.653.5080 Washington, IA

BAZOOKA • FARMSTAR

WOLVERINE AGITATION BOAT

SPECIFICATIONS

STANDARD

- Length – 21’ 4”
- Width – 11’ 3”
- Height – 11’
- 13’ tall loaded on the Bazooka Farmstar-made Wolverine trailer
- Weight – 15,750 lbs. [filled w/ fuel and liquids] (Dependent on engine options)
- [4] Rice tires, 23.1-26, 12 ply [68” DIA x 24” wide]
- 4-wheel steering
- High-torque planetary wheel drives – Freewheel capable
- Double-acting steering cylinders
- 18” White Iron Bazooka Submersible Pump
- Cummins 6.7 L, 310 HP, Tier 4 Final Engine
- 150-gallon steel fuel tank with an innovative baffle system
- [2] 20” diameter, Hardox 500 TUF steel, 5-bladed ragless propellers
- Custom-made prop bearing housing with hardened, nickel-plated 2.25” DIA shaft
- Gear oil bath with a quadruple lip seal arrangement
- Dual hydrostat Linde piston pumps
- Innovative hydraulic reservoir
- 8 fully proportional hydraulic cylinders
- Integrated GPS technology
- TEC-10 engine controller
- Dual-battery, Eaton Omnex remote control
- Integrated shutdown safety and protective features
- 6” pipe to high-abrasion 5” vacuum hose, connected by an HSG coupler

UPGRADES

- CAT 7.1L Engine |310 HP | Tier 4
- CAT 9L Engine | 455 HP | Tier 4
- John Deere 6.8L | 300HP | Tier 4
- Lift Kit: Spreader bar, Lifting slings, Bolt-on lifting lugs, Anchor shackles, U-bolts

WOLVERINE TRAILER

- Length – 32’ 6”
- Width – 11’ 2”
- Height – 2’
- Weight – 7,300 lbs.
- Electric brakes
- Dual tires [8 total]
- Tandem 12K springs on 16K axles [24K total axle capacity]
- Built-in rear ramps and storage area
- Combo clevis hitch (Pintle hitch available)

WWW.BAZOOKAFARMSTAR.COM

QUALITY. INNOVATION. SERVICE.

800.775.7448 | 319.653.5080 Washington, IA