






US 20060236014A1

(19) **United States**(12) **Patent Application Publication****Yin et al.**(10) **Pub. No.: US 2006/0236014 A1**(43) **Pub. Date: Oct. 19, 2006**(54) **METHOD AND SYSTEM OF COUPLING A PERSONAL DIGITAL ASSISTANT TO A PORTABLE COMPUTER**(22) Filed: **Apr. 19, 2005****Publication Classification**(76) Inventors: **Memphis-Zhihong Yin**, Tomball, TX (US); **Paul J. Doczy**, Cypress, TX (US); **Stacy L. Wolff**, Cypress, TX (US); **W. Caldwell Crosswy**, The Woodlands, TX (US)(51) **Int. Cl.**
G06F 13/00 (2006.01)(52) **U.S. Cl.** **710/303**(57) **ABSTRACT**

A method and system of coupling a personal digital assistant to a portable computer. Some of the illustrative embodiments may be a system comprising a portable computer comprising a docking receptacle on an outer portion of the portable computer, and a personal digital assistant (PDA) (comprising a display device). The docking receptacle couples the PDA to the portable computer, and the PDA reads data from the portable computer to be displayed on the display device of the PDA.

Correspondence Address:

HEWLETT PACKARD COMPANY
P O BOX 272400, 3404 E. HARMONY ROAD
INTELLECTUAL PROPERTY
ADMINISTRATION
FORT COLLINS, CO 80527-2400 (US)(21) Appl. No.: **11/109,547**








FIG 2






FIG 5

METHOD AND SYSTEM OF COUPLING A PERSONAL DIGITAL ASSISTANT TO A PORTABLE COMPUTER

BACKGROUND

[0001] Portable computers, such as laptop and/or notebook computers, have revolutionized access to computing functionality when outside the office environment. Because portable computers provide approximately the same functionality as their desktop brethren, they also may suffer from the same shortcomings, such as the amount of time it takes to boot the computer. For example, a portable computer user may need to access a particular piece of information, such as the time of an appointment. If the user's portable computer is powered-off, it may take several minutes for that portable computer to boot to a state sufficient for the user to retrieve the information.

BRIEF DESCRIPTION OF THE DRAWINGS

[0002] For a detailed description of illustrative embodiments of the invention, reference will now be made to the accompanying drawings in which:

[0003] **FIG. 1A** illustrates a system comprising a portable computer and a personal digital assistant (PDA) in accordance with embodiments of the invention;

[0004] **FIG. 1B** illustrates a different view of the PDA of **FIG. 1A**;

[0005] **FIG. 2** illustrates an alternative embodiment of a system comprising a portable computer and PDA;

[0006] **FIG. 3** illustrates a PDA worn on the wrist of a user in accordance with embodiments of the invention;

[0007] **FIG. 4** illustrates a PDA worn by a user by way of a lanyard in accordance with embodiments of the invention; and

[0008] **FIG. 5** illustrates an electrical block diagram of a portable computer and a PDA in accordance with embodiments of the invention.

NOTATION AND NOMENCLATURE

[0009] Certain terms are used throughout the following description and claims to refer to particular system components. As one skilled in the art will appreciate, computer companies may refer to a component by different names. This document does not intend to distinguish between components that differ in name but not function.

[0010] In the following discussion and in the claims, the terms "including" and "comprising" are used in an open-ended fashion, and thus should be interpreted to mean "including, but not limited to . . ." Also, the term "couple" or "couples" is intended to mean either an indirect or direct connection. Thus, if a first device couples to a second device, that connection may be through a direct connection, or through an indirect connection via other devices and connections.

DETAILED DESCRIPTION

[0011] The following discussion is directed to various embodiments of the invention. Although one or more of these embodiments may be preferred, the embodiments

disclosed should not be interpreted, or otherwise used, as limiting the scope of the disclosure. In addition, one skilled in the art will understand that the following description has broad application, and the discussion of any embodiment is meant only to be exemplary of that embodiment, and not intended to intimate that the scope of the disclosure is limited to that embodiment.

[0012] **FIG. 1A** illustrates a system **1000** comprising a portable computer **10** and a personal digital assistant (PDA) **12**. The portable computer **10** comprises a base chassis **11**, within which the processor and other electrical functionality is located (discussed more fully below with respect to **FIG. 5**). The illustrative portable computer **10** also comprises a display chassis **14** hinged to the base chassis **11**, such as by hinge **16**. The display chassis **14** houses a display device that is visible when the display chassis is rotated about the illustrative hinge **16** to an open position.

[0013] A portable computer **10** in accordance with embodiments of the invention further comprises a docking receptacle **18** on an outer portion of the portable computer **10**, and as illustrated in **FIG. 1A** on an outer portion of the display chassis **14**. The PDA **12** couples to the portable computer **10** by way of docking receptacle **18**. Although any suitable mechanism may be used, in accordance with at least some embodiments the docking receptacle **18** comprises two tabs **20**, and a latch **22** that also has a tab (though the tab is not visible in **FIG. 1**). Correspondingly, the PDA **12** has a slot **24** that mates with the tab on the latch **22**. **FIG. 1B** shows the illustrative PDA **12** in a different perspective view, and in this view the slots **26** that mate with the tabs **20** (of **FIG. 1A**) are visible. Referring again to **FIG. 1A**, a user may thus selectively mechanically couple and decouple the PDA **12** to the portable computer **10** by way of the docking receptacle **18**.

[0014] In the coupled configuration the PDA **12** electrically couples to components of the portable computer **10** by way of a docking connector **28** on the display chassis **14** of the portable computer **10**, and by way of a corresponding docking connector **30** (**FIG. 1B**) on a side of the PDA **12**. The electrical connections through the docking connectors **28**, **30** will be discussed more fully with respect to **FIG. 5**.

[0015] **FIG. 2** illustrates alternative embodiments of the system **1000**. In illustrative system **1000**, the display chassis **14** comprises a docking receptacle **19**. In these embodiments the PDA **12** mechanically couples with the docking receptacle **19** by sliding into the receptacle, as indicated by arrow **13**, for example by sliding along illustrative rail **15**. The PDA in the illustrative case of **FIG. 2** electrically couples to the components within the portable computer **10** by way of docking connector **29** and a corresponding docking connector (not specifically shown) in a proximal end **31** of the PDA **12**. In the embodiments illustrated in **FIG. 2**, the slot configuration, as well as configuration of the electrical docking connector **29** may be such as described in the PCI Express™ Wireless Form-Factor (WFF) card electromechanical specification available from the PCI-SIG working group.

[0016] In accordance with at least some embodiments of the invention, when the PDA **12** is mechanically and/or electrically coupled (herein referred to as docked) to the portable computer **10**, the PDA **12** reads data from the portable computer **10**, and in further embodiments the PDA

12 and the portable computer **10** exchange data. For example, while docked the PDA **12** reads the user's task list from the portable computer and/or reads user's calendar from the portable computer. This illustrative data may then be shown on a display device **32** of the PDA **12**.

[0017] There are several modes of operation of the system **1000** comprising the portable computer **10** and PDA **12**. In a first mode of operation, the portable computer **10** is powered-on and operational (even though the display chassis **14** may be closed), and thus the PDA **12** docked thereto exchanges data with the portable computer **10**, and displays data on the display device **32**. In this mode, a battery and/or charging system of the portable computer **10** may supply sufficient power to run the PDA **12** and/or charge a battery of the PDA.

[0018] In a second mode of operation, the PDA **12** is docked to the portable computer **10**, but the portable computer **10** is powered-off. In this mode of operation, data previously sent to and/or read by the PDA **12** is displayed on the display device **32** of the PDA **12**. Thus, in the illustrative case of task items or calendar events, a user need not boot to the portable computer **10**, as the desired information is available by way of the display device **32** of the PDA **12**. In this mode of operation, the PDA **12** may still draw operational and charging power from the battery and/or charging system of the portable computer **10**.

[0019] In yet another mode of operation, the illustrative PDA **12** is mechanically and/or electrically decoupled (herein referred to as undocked or not docked) from the portable computer **10** and used as a standalone device. Prior to undocking the PDA **12** from the portable computer **10**, a user may send data to the PDA **12**. In this way, needed data, e.g., task items or calendar events, may be viewed by way of the PDA **12**. Further, a PDA **12** in accordance with at least some embodiments, has a user interface, such as a mouse control button **34** and/or a digitizer that overlays the display device **32**. Using these or other user interfaces, a user may add data to the PDA **12** or change existing data. Upon the next docking of the PDA **12** to the portable computer **10**, the additional and/or changed data is communicated to the portable computer **10**.

[0020] **FIG. 3** illustrates that a PDA **12** in accordance with embodiments of the invention, when not docked to the portable computer **10**, may be separately carried by the user, such as by attaching the PDA **12** to a wrist band **36**. **FIG. 4** illustrates alternative embodiments of the invention where the user wears the PDA **12**, such as by a lanyard **38** placed around the user's neck.

[0021] **FIG. 5** illustrates, in block diagram form, the various electrical components of a portable computer **10** and PDA **12** of a system **1000** in accordance with embodiments of the invention. Portable computer **10** comprises a processor **40** coupled to a main memory array **42** by way of a bridge device **44**. The processor **40** may be any currently available or after-developed processor. Main memory array **42** may be random access memory (RAM), possibly in the form of a single RAM device, or an array of RAM devices. Bridge device **44** couples to the processor **40** by way of a host bus **46** and to the main memory array **42** by way of a memory bus **48**. The bridge device **44** controls the processor's access to the main memory array **42**.

[0022] Portable computer **10** further comprises a graphics adapter **50** which couples to the processor **40**, possibly by

way of the bridge device **44**. In some embodiments, the graphics adapter **50** couples to the bridge device **44** by way of an Advanced Graphics Port (AGP) bus **52**, although any currently available or after-developed bus may be used. The graphics adapter **50** receives graphics primitives generated by a program executing on the processor **40**, and translates those graphics primitives into images suitable for display on the display device **54**.

[0023] Processor **40** also couples to one or more long term storage devices, such as memory device **56**, by way of bridge device **44** and an expansion bus **58**. In accordance with at least some embodiments of the invention, the memory device **56** may be a disk drive or other type of nonvolatile memory storage, such as a universal serial bus (USB) accessible solid state memory device.

[0024] Still referring to **FIG. 5**, illustrative PDA **12** comprises a processor **60** coupled to a main memory array **62**, possibly by way of a memory bus **64**. In accordance with at least some embodiments of the invention, processor **60** is a microcontroller, and thus the processor functionality and memory functionality may reside on a single semiconductor die. In accordance with alternative embodiments of the invention, the processor **60** and main memory array **62** are implemented using individual processor and memory components. Processor **60** of the PDA **12** further couples to the display device **32** by way of a graphics adapter **66**. Much like the graphics adapter **50** of the portable computer **10**, graphics adapter **66** receives graphics primitives generated by a program executing on processor **60**, and translates those graphics primitives into images suitable for display on the display device **32**.

[0025] Illustrative PDA **12** also comprises a user interface **74** coupled to the processor **60**. The user interface **74** may take many forms. In some embodiments, the user interface **74** is a full or reduced size keyboard. In alternative embodiments, the user interface **74** is a mouse control device, to enable cursor control, and therefore entry of information, by way of the display device **32**. In yet further alternative embodiments, the user interface **74** is a digitizer overlaying the display device **32**. In these embodiments, data may be provided to the PDA **12** by a "writing" on the display device **32** overlaid by the illustrative digitizer. In yet further alternative embodiments, the user interface **74** may be a combination of a keyboard, mouse control and/or digitizer devices.

[0026] As discussed with respect to **FIGS. 1A and 2**, in accordance with embodiments of the invention the portable computer **10** electrically couples to the PDA **12** when the PDA **12** is docked. The illustrative drawing of **FIG. 5** shows the electrical docking connectors **28, 29**, and the mating electrical docking connectors **30, 31**. The portable computer **10** comprises a docking logic **70** coupled to the expansion bus **58**. Docking logic **70** is responsible for ensuring that in the docking and undocking of the PDA **12** no damage occurs to the electrical components of the portable computer **10**, such as by electrical arcing. Likewise, the PDA **12** comprises a docking logic **72**, and it too is responsible for ensuring that no damage occurs to the electrical components of the PDA **12** during docking and undocking procedures. In accordance with at least some embodiments of the invention, each of the docking logics **70, 72** provide electrical isolation to their respective expansion buses **58, 68**. Once

the portable computer **10** and PDA **12** are docked, the docking logics **70**, **72** are transparent to communications between the coupled components. In accordance with alternative embodiments, the bus structures as between the expansion bus **58** of the portable computer **10** and the expansion bus **68** of the portable computer **12** may not be directly compatible, and thus one or more of the docking logics **70**, **72**, in addition to ensuring that no electrical damage occurs, may also perform protocol translation as between the busses.

[0027] Still referring **FIG. 5**, in a mode of operation where the portable computer **10** is docked to the PDA **12** and the portable computer is on and operational, programs executing on the processor **40** of the portable computer **10** may communicate to programs executing on the processor **60** of the PDA **12**. Alternatively, programs executing on processor **60** may read data from the memory device **56**, and/or may read data, by way of direct memory access techniques, from the main memory array **42**. It is by one or more of these communication mechanisms that the PDA **12** and portable computer **10** exchange data, such as the illustrative task items or calendar events.

[0028] Still referring to **FIG. 5**, in the mode of operation where the portable computer **10** is powered-off, yet the PDA **12** is docked to the portable computer **10**, the PDA **12** may be operational and display various pieces of data on the display device **32**. Moreover, the PDA **12**, in accordance with at least some embodiments, may still be able to read data stored within devices of the portable computer **10** in spite of its powered-off condition. For example, in embodiments where the memory device **56** is a solid state nonvolatile memory device, such as a USB-accessible solid-state memory device, the PDA **12** exchanges information with memory device **56** in spite of the fact that other components of the portable computer **10** are powered-off. In this illustrative situation where the memory device **56** is a USB-accessible solid-state memory device, the PDA **12** supplies operational power to the memory device **56** from the PDA's battery **76**.

[0029] As illustrated in **FIG. 5**, the PDA **12** thus comprises battery **76**. Though the battery **76** is shown to couple only to the electrical connectors **30**, **31**, inherently the battery **76** couples to and provides power to all devices within the PDA **12**. Likewise, portable computer **10** comprises a battery **78**, shown to couple only to the electrical connectors **28**, **29**; however, the battery **78** inherently couples to and provides power to all components of the portable computer **12**. **FIG. 5** further illustrates that when the portable computer **10** and the PDA **12** are docked, their respective batteries **78** and **76** may, in some embodiments, likewise be coupled. Thus, PDA **12** may draw operational and/or charging power from battery **78** of the portable computer **10**.

[0030] Still referring to **FIG. 5**, in accordance with at least some embodiments of the invention, the PDA **12** comprises a local area network (LAN) wireless transceiver **82**. In these embodiments, when the PDA **12** is docked to the portable computer **10**, the PDA **12** may additionally couple the portable computer **10** to a wireless LAN. The wireless transceiver **82** may take any suitable form, such as an electromagnetic wave communication device that imple-

ments communication protocols, such as the Institute of Electrical and Electronics Engineers (IEEE) 802(11) protocols.

[0031] In yet further illustrative embodiments, the portable computer **10** may also comprise a LAN wireless transceiver **80**, and in these embodiments the portable computer **10** and PDA **12** communicatively couple even when the devices are not electrically coupled by way of the electrical connectors **28**, **29** and **30**, **31**. Thus, the PDA **12** and portable computer **10** may exchange data, e.g., task items and/or calendar events, by way of their respective wireless transceivers **80**, **82**. In these alternative embodiments the PDA **12** need only be proximate to the portable computer **10** for data to be exchanged.

[0032] Still referring to **FIG. 5**, in yet further alternative embodiments the PDA **12** comprises a wide area network (WAN) wireless transceiver **81**, and when the PDA is coupled to the portable computer, the PDA couples the portable computer to the WAN. Alternatively, when the PDA **12** and portable computer **10** are communicating wirelessly by way of their respective LAN wireless transceivers **80**, **82**, the PDA **12** may still provide WAN connectivity for the portable computer **10**. In yet further embodiments, the PDA and portable computer may not be proximate to each other, yet they may be communicatively coupled through a communication relay, such as a satellite. In at least some embodiments, the WAN wireless transceiver **81** is a cellular network wireless transceiver, thus enabling the PDA **12** standing alone, or the PDA **12** and portable computer **10** if communicatively coupled, access to various WAN networks even if both devices are outside the range of their LAN wireless transceiver networks. In embodiments where the WAN wireless transceiver is a cellular network wireless transceiver, the PDA **12** may also implement cellular telephone functionality.

What is claimed is:

1. A system comprising:

portable computer comprising a docking receptacle on an outer portion of the portable computer;

a personal digital assistant (PDA) comprising a display device;

wherein the docking receptacle couples the PDA to the portable computer, and wherein the PDA reads data from the portable computer to be displayed on the display device of the PDA.

2. The system as defined in claim 1 wherein the portable computer further comprises a display chassis comprising a display, and wherein the docking receptacle is on an outer portion of the display chassis of the portable computer.

3. The system as defined in claim 1 further comprising:

wherein the PDA comprises an electrical docking connector and a processor, the processor electrically coupled to the electrical docking connector;

wherein the docking receptacle further comprises an electrical docking connector, and wherein when the PDA is docked, the processor of the PDA electrically couples to the processor of the portable computer through the electrical docking connector.

4. The system as defined in claim 1 further comprising:
wherein the portable computer comprises a local area network (LAN) wireless transceiver;
wherein the PDA comprises a LAN wireless transceiver;
and
wherein the PDA reads data from the portable computer using the LAN wireless transceivers.
5. The system as defined in claim 4 wherein PDA reads data from the portable computer using the wireless transceivers when the PDA is mechanically coupled to the portable computer.
6. The system as defined in claim 4 wherein the PDA reads data from the portable computer when the PDA is proximate to the portable computer.
7. The system as defined in claim 1 further comprising:
wherein the PDA further comprises a wide area network (WAN) wireless transceiver, and wherein the PDA, when coupled to the portable computer, couples the portable computer to the WAN.
8. The system as defined in claim 1 further comprising:
wherein the PDA comprises a wireless transceiver; and
wherein the PDA, when coupled to the portable computer, wirelessly couples the portable computer to a network.
9. The system as defined in claim 8 wherein the PDA, when coupled to the portable computer, wirelessly couples the portable computer to a cellular telephone network.
10. The system as defined in claim 1 wherein the PDA comprises a user interface that accepts data from a user.
11. The system as defined in claim 10 wherein the user interface of the PDA further comprises a keyboard.
12. The system as defined in claim 10 wherein the user interface further comprises a digitizer at least partially overlaying the display of the PDA.
13. The system as defined in claim 1 wherein the PDA reads data from a memory device of the portable computer when the portable computer is powered-off.
14. The system as defined in claim 1 wherein the PDA further comprises a battery, and wherein the portable computer charges the battery of the PDA.
15. A portable computer comprising:
a base chassis comprising a processor;
a display chassis comprising a display hinged to the base chassis; and
a docking receptacle on an outer portion of the display chassis, the docking receptacle mechanically couples a

personal digital assistant (PDA) to the portable computer and enables the PDA to read data from the portable computer.

16. The portable computer as defined in claim 15 wherein the docking receptacle further comprises an electrical connector, and wherein when the PDA is mechanically coupled to the portable computer, the electrical connector electrically couples the PDA to the processor.

17. The portable computer as defined in claim 15 wherein the PDA reads data from the portable computer when the portable computer is powered-off.

18. The portable computer as defined in claim 15 further comprising a wireless transceiver coupled to the processor, wherein the portable computer supplies data to the PDA by way of the wireless transceiver.

19. A personal digital assistant (PDA) comprising:

a display device;

a user interface; and

a processor electrically coupled to the display device;

wherein the PDA is configured to mechanically couple to an outer portion of a chassis of a portable computer and to read data from the portable computer, and wherein when not mechanically coupled the PDA is configured to be worn by a user.

20. The PDA as defined in claim 19 wherein the PDA couples the user by at least one of the group: a lanyard; and a wrist band.

21. The PDA as defined in claim 19 further comprising a wireless transceiver, and wherein the PDA reads data from the portable computer using the wireless transceiver.

22. The PDA as defined in claim 21 wherein the PDA reads data using the wireless transceiver when the PDA is mechanically coupled to the portable computer.

23. The PDA as defined in claim 21 wherein the PDA reads data using the wireless transceiver when the PDA is proximate to the portable computer.

24. The PDA as defined in claim 19 further comprising:

a battery coupled to the processor; and

user interface coupled to the processor.

25. The PDA as defined in claim 24 wherein the battery of the PDA is charged by the portable computer when the PDA is mechanically coupled to the portable computer.

26. The PDA as defined in claim 19 further comprising a wireless transceiver, and wherein the PDA couples the portable computer to a network using the wireless transceiver.

* * * * *