

Heat Shrink Wrap FAQ

How strong is Heat Shrink Wrap?

- Withstands over 250 PSF for 6 mil and 900 PSF for 12 mil
- Holds up under extreme weather conditions
 - Strong enough to handle freeway and railway speeds

Why does Heat Shrink Wrap work better for containment?

Seams bond through heat, creating a seamless containment.

How long will Heat Shrink Wrap last in fully exposed outdoor conditions?

Depending on formulation and thickness it will last up to 2 years.

Is Heat Shrink Wrap recyclable?

Yes.

Is Heat Shrink Wrap difficult to install?

No, Heat Shrink Wrap is normally easier to install than competing materials, and in less time.



Photos provided by PCI Shrinkwrap Services

Is there a reason Americover's Heat Shrink Wrap is generally bright white?

Yes, the white color creates a clean, professional appearance. In addition, the translucent color allows light into the area being contained or covered.

What happens if Heat Shrink Wrap is damaged?

Repairs are simple and can be made using Heat Shrink Tape, or by applying a patch using heat to bond the patch.

Why does Heat Shrink Wrap Stand up better in the elements than C&A Film?

Once the film shrinks tightly around object, it will not flutter or buffet in the wind, reducing the chance of damage. Additionally, this film is engineered for this specific type of application, so additives and better quality resins are used to help it withstand the elements.

Are there any other benefits that may not be apparent to one considering this film for the first time?



Yes:

- Work can be performed during conditions that would otherwise shut the job down.
- Jobsite safety is increased
- Productivity is often improved - Workers are not distracted by outside activities in the area
- Enclosed areas can be heated
- Noise is reduced in most cases
- Extends construction season
- Chance of particulates or debris escaping worksite is reduced
- Theft and vandalism are reduced
- Jobsite cleanup is easier and normally less expensive
- Increases customer's perception of quality
- Decreases chances of community complaints in reference to jobsite

Commercial & Residential Uses | Sizes | C&A Film Comparison | Accessories

:: Back ::

For more information, please contact us at:

Phone: (800) 747-6095 Dept. 17 or
(760) 747-6095 Dept. 17


**International
Calls:** +1-760-747-6095 Dept. 17

Fax: 1-760-747-1920

E-mail: heatshrinkwrap@americover.com

Snail Mail: Americover Inc.
P.O. Box 270198
San Diego, CA 92198

If you have trouble viewing any part of this site please let us know at [troubleshoot](#).



[Home](#) | [Technical Support](#) | [Customer Service](#) | [Free Catalog](#) | [U.S. Navy Approval Letter](#)

Web Site Design by JDS Productions ©2006 Americover, Inc. All Rights Reserved.

