



US 20160238796A1

(19) **United States**

(12) **Patent Application Publication**
Nguyen et al.

(10) **Pub. No.: US 2016/0238796 A1**

(43) **Pub. Date: Aug. 18, 2016**

(54) **SPRING PUSH AND PUSH-PULL TAB FOR
TIGHTLY SPACED FIBER OPTIC
CONNECTORS**

Publication Classification

(51) **Int. Cl.**
G02B 6/38 (2006.01)

(52) **U.S. Cl.**
CPC **G02B 6/389** (2013.01); **G02B 6/381**
(2013.01)

(71) Applicant: **US Conec, Ltd.**, Hickory, NC (US)

(72) Inventors: **Hiep V. Nguyen**, Fort Mill, SC (US);
Joseph P. Howard, Hickory, NC (US)

(21) Appl. No.: **15/047,501**


(22) Filed: **Feb. 18, 2016**

Related U.S. Application Data

(60) Provisional application No. 62/117,490, filed on Feb.
18, 2015.

(57) **ABSTRACT**

A spring push for a fiber optic connector includes an engagement member having a slot to receive a handle that also engages a distal portion of the engagement member. The spring push, along with the handle, allows for fiber optic connectors to be installed and removed from adapters in high density applications. The spring push can be installed into a connector housing and, along with other components, be a fiber optic connector. The engagement member may also originate from other parts of the fiber optic connector.







Fig. 1
(Prior Art)






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12

SPRING PUSH AND PUSH-PULL TAB FOR TIGHTLY SPACED FIBER OPTIC CONNECTORS

REFERENCE TO RELATED CASE

[0001] This application claims priority under 35 U.S.C. §119 (e) to provisional application No. 62/117,490 filed on Feb. 18, 2015, the contents of which are hereby incorporated by reference in their entirety.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] Fiber optic connectors, and the locations where they are installed, are becoming smaller and smaller. This is especially true in high density applications. The fiber optic connectors are now smaller than a person's finger and they are spaced such that a person can not easily grasp individual fiber optic connectors mounted in an adapter in the high density areas. Thus, it can be very difficult to install a fiber optic connector in, and uninstall from, its respective adapter. Adjacent fiber optic connectors are generally located too close to allow manual insertion and removal of a single fiber optic connector using the connector's outer housing as intended, particularly, when used in higher density applications. To facilitate these processes, a component was desired that possessed a smaller cross section that could be grasped to install and uninstall a fiber optic connector when in a high density application.

SUMMARY OF THE INVENTION

[0003] The present invention is directed to a spring push for use with a fiber optic connector that includes a main body having a forward facing surface, a rearward facing surface, and at least one side portion, two generally parallel extensions extending from the forward facing surface of the main body away from the rearward facing surface; the two generally parallel extensions configured to engage an elastic member therebetween and each of the parallel extensions having a projection to engage a connector housing of the fiber optic connector, a crimp portion extending from the rearward facing surface of the main body and away from the forward facing surface, the crimp portion having a central opening to allow optical fibers to pass therethrough and between the two generally parallel extensions, and an engagement member having a first portion and a second portion, the first portion extending from the at least one side portion away from the main body and orthogonal to the central opening, the first portion having a slot, and the second portion extending from a distal end of the first portion and away from the rearward facing surface.

[0004] In some embodiments, the second portion is substantially parallel to the two generally parallel extensions.

[0005] In some embodiments, the spring push further includes a handle, the handle having an insert portion configured to be inserted into the slot of the engagement member.

[0006] In other embodiments, the engagement member and one of the two generally parallel extensions form an opening therebetween, the opening configured for receiving a portion of a connector housing and a portion of a handle that can be inserted into the slot.

[0007] According to another aspect of the present invention, there is a fiber optic connector that includes a connector

housing, the connector housing further comprising a ferrule holder and a spring push, the spring push inserted into an opening from a back end of the ferrule holder and the connector housing having a latch disposed on a side surface, a ferrule disposed within the opening of the connector housing, an engagement member having a first portion extending away from the connector housing, the first portion having a slot, and a second portion extending from the first portion in a direction away from the back end of the ferrule holder, and a handle, the handle having an insert portion configured to be inserted into the slot of the engagement member.

[0008] It is to be understood that both the foregoing general description and the following detailed description of the present embodiments of the invention are intended to provide an overview or framework for understanding the nature and character of the invention as it is claimed. The accompanying drawings are included to provide a further understanding of the invention and are incorporated into and constitute a part of this specification. The drawings illustrate various embodiments of the invention and, together with the description, serve to explain the principles and operations of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a prior art sleeve used to insert and remove fiber optic connectors in high density applications;

[0010] FIG. 2 is a perspective view of one embodiment of a spring push and handle according to the present invention;

[0011] FIG. 3 is a perspective view of the spring push of FIG. 2 from the opposite side;

[0012] FIG. 4 is a cross section view of the spring push of FIG. 2;

[0013] FIG. 5 is a perspective view of the spring push of FIG. 2 installed in a connector housing to make one embodiment of a fiber optic connector according to the present invention;

[0014] FIG. 6 is a perspective view of the fiber optic connector of FIG. 5 with a handle inserted into the engagement member of the spring push;

[0015] FIG. 7 is a perspective view of the fiber optic connector of FIG. 6 from the opposite side;

[0016] FIG. 8 is a cross-sectional view of the fiber optic connector of FIG. 5;

[0017] FIG. 9 is an exploded view of the fiber optic connector of FIG. 5 in cross-section;

[0018] FIG. 10 is a cross-sectional view of the fiber optic connector of FIG. 5 installed in an adapter;

[0019] FIG. 11 is a cross-sectional view of the fiber optic connector of FIG. 9 with the handle disposed within the spring push; and

[0020] FIG. 12 is a cross-sectional view of the fiber optic connector of FIG. 9 with the handle being pulled rearwardly.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0021] Reference will now be made in detail to the present preferred embodiment(s) of the invention, examples of which are illustrated in the accompanying drawings. Whenever possible, the same reference numerals will be used throughout the drawings to refer to the same or like parts.

[0022] FIG. 1 illustrates a prior art push-pull sleeve that also assists in inserting and removing fiber optic connectors. The illustrated sleeve is disclosed and claimed in U.S. Pat. No. 8,559,781 and is assigned to the same applicant as the

present application. The sleeve, having an integral handle, is disposed over the inner and outer connector housings of the fiber optic connector. As described in detail below, the present invention is more integral with a fiber optic connector.

[0023] One embodiment of a spring push **100** according to the present invention is illustrated in FIGS. 2-4. The spring push **100** can be used as a part of a fiber optic connector **200**, illustrated in the later figures. The spring push **100** has a main body **102**, the main body having a forward facing surface **104**, a rearward facing surface **106**, and side portions **108** (generally there are four side portions, but there could be more or fewer depending on the configuration of the connector housing). Extending from the forward facing surface **104** of the main body **102** are two generally parallel extensions **110,112**. The two generally parallel extensions **110,112** are spaced to allow for an elastic member, preferably a coil spring, to bias a fiber optic ferrule (see, e.g., FIG. 8) toward the front (away from the spring push **100**) of the fiber optic connector **200**. Each of the two generally parallel extensions **110,112** have a front end **114**. A forward facing surface **116** is disposed on each of the two generally parallel extensions **110,112** to engage the elastic member disposed therebetween. See FIGS. 3 & 4. The term “front” and/or “forward” as used herein means that direction where the fiber optic connector would mate with another fiber optic connector or device, while the term rear is used to mean the direction from which the optical fibers come. So turning to FIGS. 2 & 4, front is the direction shown by the arrow and “back” or “rearward” is the opposite direction.

[0024] Each of the two generally parallel extensions **110,112** also have a projection **118** on an outside surface **120** to engage a corresponding opening in the fiber optic connector **200** to engage recesses or openings **202** to retain the spring push **100** within the connector housing **204** of the fiber optic connector **200**. See FIGS. 5, 8, and 10-11. The projections **118** may also have a chamfered leading edge **122** that allows for the front end **114** of the two generally parallel extensions **110,112** to more easily enter into the central opening **206** of the connector housing **204**.

[0025] Extending from the rearward facing surface **106** is a crimp portion **130**. The crimp portion **130** allows for the Kevlar cords and cable jacket (or other structural members) to be secured to the spring push **100** and the fiber optic connector **200** as is known in the art. As illustrated in the figures, the crimp portion **130** has an outer surface **132** that is preferably round and a round central opening **134**. However, the shape of the outer surface **132** and the central opening **134** may take other shapes, including oval, hexagonal, rectangular, etc. and still fall within the scope of the present invention.

[0026] An engagement member **140** extends from one of the side portions **108** of the main body **102** of the spring push **100**. The engagement member **140** has a first portion **142** generally extends upward (or outward and away from the main body **102**) between the crimp portion **130** and the two generally parallel extensions **110,112** to a distal portion **144**. See FIG. 3. The engagement member **140** also includes a second portion **146**, with a proximal portion **148** that extends from the distal portion **144** of the first portion **142** toward the front end **114** of the two generally parallel extensions **110,112**.

[0027] The first portion **142** of engagement member **140** has a slot **150** that extends into the engagement member **140**. The slot **150** receives a handle **300**, which is described in more detail below, both in structure and function. The slot **150**

preferably makes an opening on another side of the main body **102**—in this case about 90 degrees from side portion **108** from which the engagement member extends. See FIG. 5. For obvious reasons, the slot **150** can not come in from the bottom because of the main body **102**, and coming in from the top presents other issues, including the presence of the second portion **146** and its function, described in detail below. As would be obvious to one of skill in the art, the slot **150** could also come in from the side opposite to that shown in the figures. The slot **150** has a portion **152** with a generally rectangular configuration that begins at the edge of the first portion **142** and then transitions into a circular portion **154**, which corresponds to the configuration of the handle **300**. See FIG. 2. If the handle **300** had a different configuration, the portion **154** could have a corresponding configuration.

[0028] The first portion **142** of engagement member **140** is illustrated as having a rear surface **156** that is flush with the rearward facing surface **106**. See, e.g., FIG. 9. While this allows for the spring push **100** to be clean and streamlined, it is not necessary and there could be a step between the engagement member **140** and the rearward facing surface **106**, or even a smooth transition between the two.

[0029] At the distal portion **144** of the first portion **142**, the engagement member makes a turn of about 90 degrees to begin the second portion **146**. The second portion extends forward, in the direction of the front ends **114** of the two generally parallel extensions **110,112**. Preferably the second portion **146** is parallel to the two generally parallel extensions **110,112**, but could be oriented somewhat differently if desired. The second portion **146** terminates at a distal end **160** and a terminal surface **162**, which faces downwards toward the two generally parallel extensions **110,112**. See FIGS. 8 and 10-12. As can be seen in FIGS. 5 & 6, there is a space **164** between the second portion **146** and the extension **112**. This space **164** is sufficient to accommodate the handle **300** and the connector housing **204**.

[0030] The engagement member **140**, when the spring push **100** is inserted into the connector housing **204**, extends partially over the connector housing **204** and the terminal surface **162** is near the latch **208** on the connector housing **204**, reasons for which will be clear below. As is known in the art, the latch **208** secures the connector housing **204** into an adapter, such as the adapter **350** illustrated in FIG. 10, to keep the fiber optic connector **200** from being inadvertently removed from the adapter **350**.

[0031] A handle **300** is illustrated in FIGS. 2, 6-7, and 10-12. A majority of the handle **300** lies along an axis A-A. A grasping portion **302** is at a first or proximal end **304**. The handle then has middle portion **306** that is substantially circular in cross section and has an expanded portion (or hub) **308** extending radially outward from the middle portion **306**. Between the expanded portion (or hub) **308** and the distal end **310** is an insert portion **312** that is configured to be inserted into the slot **150**. As illustrated, the insert portion **312** is circular in cross section and matches the configuration of the circular portion **154**. When the insert portion **312** is inserted into the slot **150** (see, e.g., FIGS. 6 & 10-11), the expanded portion (or hub) **308** engages the rear surface **156** of first portion **142** of engagement member **140**. Thus, an operator can push on the handle **300** and the force is translated to the engagement member **140** and the fiber optic connector through the rear surface **156** of first portion **142**.

[0032] The distal end **310** of the handle **300** extends upward (in the figures, but away from the two generally parallel

extensions 110,112 and out of the axis A-A) so that it extends beyond the terminal surface 162 of the distal end 160 of second portion 146 and rests on the latch 208 when the handle 300 is disposed within the slot 150. The top surface 320 of the distal end 310 engages or touches the terminal surface 162 of the distal end 160 of second portion 146 while a bottom surface 322 engages or touches the latch 208. See FIGS. 6-7 and 10-12. When an operator wants to remove a fiber optic connector with the spring push 100 and handle 300, the operator grasps the grasping portion 302 of the handle 300 at a first or proximal end 304 and pulls rearwardly (to the left in FIG. 9), and the handle 300 moves slightly rearwardly relative to the spring push 100 and engagement member 140. As a result, the top surface 320 engages the terminal surface 162 of the distal end 160 of second portion 146, which forces the distal end 320 of the handle 300 to move downward toward the spring push 100 and simultaneously on the latch 208. See FIG. 12. The movement of the latch 208 from the distal end 320 is sufficient to allow the fiber optic connector 200 to be removed from the adapter with the handle 300. The distal end 310 is configured so that it cannot flex enough so that the top surface 320 disengages from the terminal surface 162 of the second portion 146. Thus, the distal end 310 engages the second portion 146 with enough force to allow the operator to remove the fiber optic connector from the adapter.

[0033] As referenced to above and illustrated in FIGS. 5-6 & 8-9, one embodiment of a fiber optic connector 200 that can be used with the inventive spring push 100 includes the connector housing 204, a ferrule 210, a spring 212, the spring push 100, and a boot 214. A crimp ring 216, disposed between the crimp portion 130 and the boot 214 is also illustrated in FIGS. 8 and 10 for completeness. Additional fiber optic connector elements may also be included but are not illustrated herein, such as guide pins, a pin keeper, etc. These fiber optic connector elements may also have other configuration and still come within the scope of the present invention and the appended claims. For example, the spring could have a configuration other than the rectangular shape illustrated herein. [0034] It will be apparent to those skilled in the art that various modifications and variations can be made to the present invention without departing from the spirit and scope of the invention. Thus it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

We claim:

1. A spring push for use with a fiber optic connector comprising:

- a main body having a forward facing surface, a rearward facing surface, and at least one side portion;
- two generally parallel extensions extending from the forward facing surface of the main body away from the rearward facing surface; the two generally parallel extensions configured to engage an elastic member therebetween and each of the parallel extensions having a projection to engage a connector housing of the fiber optic connector;
- a crimp portion extending from the rearward facing surface of the main body and away from the forward facing surface, the crimp portion having a central opening to allow optical fibers to pass therethrough and between the two generally parallel extensions; and
- an engagement member having a first portion and a second portion, the first portion extending from the at least one

side portion away from the main body and orthogonal to the central opening, the first portion having a slot, and the second portion extending from a distal end of the first portion and away from the rearward facing surface.

2. The spring push according to claim 1, wherein the second portion is substantially parallel to the two generally parallel extensions.

3. The spring push according to claim 1, wherein the slot has a rounded opening to receive a portion of a handle.

4. The spring push according to claim 1, further comprising a handle, the handle having an insert portion configured to be inserted into the slot of the engagement member.

5. The spring push according to claim 1, wherein a distal end of the second portion has a terminal surface that faces the two generally parallel extensions.

6. The spring push according to claim 5, wherein the terminal surface engages a portion of a handle inserted into the slot of the engagement member.

7. The spring push according to claim 1, wherein the slot opens from a side other than the side portion on which the engagement member is disposed.

8. The spring push according to claim 1, wherein the engagement member and one of the two generally parallel extensions form an opening therebetween, the opening configured for receiving a portion of a connector housing and a portion of a handle that can be inserted into the slot.

9. The spring push according to claim 1, wherein at least a portion of the engagement member is flush with the rearward facing surface of the main body.

10. A fiber optic connector comprising:

a connector housing, the connector housing further comprising a ferrule holder and a spring push, the spring push inserted into an opening from a back end of the ferrule holder and the connector housing having a latch disposed on a side surface;

a ferrule disposed within the opening of the connector housing;

an engagement member having a first portion extending away from the connector housing, the first portion having a slot, and a second portion extending from the first portion in a direction away from the back end of the ferrule holder; and

a handle, the handle having an insert portion configured to be inserted into the slot of the engagement member.

11. The fiber optic connector according to claim 10, wherein the handle engages the latch.

12. The fiber optic connector according to claim 10, wherein the handle extends between a proximal end and a distal end and having a middle portion, the middle portion having an expanded portion extending radially outward from the middle portion proximally from the insert portion, the distal end having a flat surface to engage the latch.

13. The fiber optic connector according to claim 10, wherein the handle has a longitudinal axis and the distal end of the handle curves away from the longitudinal axis to engage the second portion of the engagement member and the latch.

14. The fiber optic connector according to claim 10, wherein pulling the proximal end of the handle away from the connector housing causes the distal end of the handle to flex after engaging a forward facing surface of the engagement member thereby causing the distal end to push on the latch.

15. The fiber optic connector according to claim **10**, wherein the slot has a rounded opening to receive the insert portion of the handle.

16. The fiber optic connector according to claim **15**, wherein the rounded opening of the engagement member has a first diameter and the expanded portion of the handle has a second diameter, the first diameter being smaller than the second diameter.

17. The fiber optic connector according to claim **10**, wherein the engagement member extends from a portion of the spring push.

* * * * *