



IEC 61754-20

Edition 2.0 2012-04

# INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components – Fibre optic  
connector interfaces –  
Part 20: Type LC connector family**

IEC 61754-20:2012(E)

Customer: TSUYOSHI HAMAGUCHI - No. of User(s): 1 - Company: SENKO ADVANCED COMPONENTS(Hong Kong)Ltd.  
Order No.: WS-2012-011775 - IMPORTANT: This file is copyright of IEC, Geneva, Switzerland. All rights reserved.  
This file is subject to a licence agreement. Enquiries to Email: [custserv@iec.ch](mailto:custserv@iec.ch) - Tel.: +41 22 919 02 11

Senko Advanced Components, Inc., EX2001  
IPR2024-00122  
U.S. Patent No. 11,061,190



## THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2012 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
Fax: +41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

### About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

#### Useful links:

IEC publications search - [www.iec.ch/searchpub](http://www.iec.ch/searchpub)

The advanced search enables you to find IEC publications by a variety of criteria (reference number, text, technical committee,...).

It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)

Stay up to date on all new IEC publications. Just Published details all new publications released. Available on-line and also once a month by email.

Electropedia - [www.electropedia.org](http://www.electropedia.org)

The world's leading online dictionary of electronic and electrical terms containing more than 30 000 terms and definitions in English and French, with equivalent terms in additional languages. Also known as the International Electrotechnical Vocabulary (IEV) on-line.

Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [csc@iec.ch](mailto:csc@iec.ch).



IEC 61754-20

Edition 2.0 2012-04

# INTERNATIONAL STANDARD

**Fibre optic interconnecting devices and passive components – Fibre optic  
connector interfaces –  
Part 20: Type LC connector family**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE

U

ICS 33.180.20

ISBN 978-2-88912-986-7

**Warning! Make sure that you obtained this publication from an authorized distributor.**

Customer: TOSYOSHIMA AB, Helsingfors, Finland. Company: SENKO ADVANCED COMPONENTS(Hong Kong)Ltd.  
Order No.: WS-2012-011775 - IMPORTANT: This file is copyright of IEC, Geneva, Switzerland. All rights reserved.  
This file is subject to a licence agreement. Enquiries to Email: [custserv@iec.ch](mailto:custserv@iec.ch) - Tel.: +41 22 919 02 11

## CONTENTS

|                                                                                                          |    |
|----------------------------------------------------------------------------------------------------------|----|
| FOREWORD.....                                                                                            | 3  |
| INTRODUCTION.....                                                                                        | 5  |
| 1 Scope.....                                                                                             | 6  |
| 2 Normative references.....                                                                              | 6  |
| 3 Description .....                                                                                      | 6  |
| 4 Interfaces .....                                                                                       | 6  |
| Annex A (informative) Additional adaptor dimensional information.....                                    | 22 |
| Bibliography .....                                                                                       | 26 |
| Figure 1 – Plug connector interface reference planes .....                                               | 8  |
| Figure 2 – Detail A of Figure 1 – Plug connector interface – Expanded view drawings<br>not-to-scale..... | 9  |
| Figure 3 – Plug connector interface .....                                                                | 10 |
| Figure 4 – APC plug connector interface.....                                                             | 11 |
| Figure 5 – Duplex plug interface .....                                                                   | 12 |
| Figure 6 – Simplex adaptor interface .....                                                               | 14 |
| Figure 7 – Junior (Jr.) adaptor interface (optional – note g of Table 3) .....                           | 15 |
| Figure 8 – Duplex adaptor interface.....                                                                 | 16 |
| Figure 9 – Active device receptacle interface.....                                                       | 18 |
| Figure 10 – Duplex active device receptacle interface.....                                               | 19 |
| Figure 11 – Pin gauge for active device receptacle .....                                                 | 20 |
| Figure A.1 – Simplex adaptor .....                                                                       | 22 |
| Figure A.2 – Duplex square flange adaptor.....                                                           | 23 |
| Figure A.3 – Duplex rectangular flange adaptor .....                                                     | 24 |
| Figure A.4 –Quad rectangular flange adaptor.....                                                         | 25 |
| Table 1 – Plug to Adaptor/Receptacle Intermateability .....                                              | 7  |
| Table 2 – Plug to Plug Intermateability.....                                                             | 8  |
| Table 3 – Dimensions of the plug connector interface .....                                               | 12 |
| Table 4 – Plug connector interface – Ferrule grade.....                                                  | 13 |
| Table 5 – Dimensions of the adaptor interface.....                                                       | 16 |
| Table 6 – Dimensions of the active device receptacle .....                                               | 19 |
| Table 7 – Active device receptacle interface – Alignment sleeve grade .....                              | 20 |
| Table 8 – Pin gauge grade .....                                                                          | 21 |
| Table A.1 – Dimensions of simplex adaptor .....                                                          | 22 |
| Table A.2 – Dimensions of duplex square flange adaptor.....                                              | 23 |
| Table A.3 – Dimensions of duplex rectangular flange adaptor .....                                        | 24 |
| Table A.4 – Dimensions for quad rectangular flange adaptor .....                                         | 25 |

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**FIBRE OPTIC INTERCONNECTING DEVICES  
AND PASSIVE COMPONENTS –  
FIBRE OPTIC CONNECTOR INTERFACES –****Part 20: Type LC connector family**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

International Standard IEC 61754-20 has been prepared by subcommittee SC86B: Fibre optic interconnecting devices and passive components.

This second edition cancels and replaces the first edition published in 2002. It constitutes a technical revision. The changes with respect to the previous edition are to reconsider the whole document and to add Interface IEC 61754-20-9 to IEC 61754-20-16 for a plastic optical fibre (POF).

The text of this standard is based on the following documents:

| FDIS          | Report on voting |
|---------------|------------------|
| 86B/3343/FDIS | 86B/3393/RVD     |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The list of all parts of IEC 61754 series, published under the general title, *Fibre optic interconnecting and passive components – Fibre optic connector interfaces* can be found on the IEC website.

Future standards in this series will carry the new general title as cited above. Titles of existing standards in this series will be updated at the time of the next edition.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

## INTRODUCTION

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning IEC 61754-20.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

OFS Fitel LLC, Inc.,  
2000 NE Expressway,  
Norcross, GA 30071  
USA

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO ([www.iso.org/patents](http://www.iso.org/patents)) and IEC ([http://www.iec.ch/tctools/patent\\_decl.htm](http://www.iec.ch/tctools/patent_decl.htm)) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

# **FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS – FIBRE OPTIC CONNECTOR INTERFACES –**

## **Part 20: Type LC connector family**

### **1 Scope**

This International Standard defines the standard interface dimensions for the type LC family of connectors.

### **2 Normative references**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61755-3 series, *Fibre optic interconnecting devices and passive components – Fibre optic connector optical interfaces*

### **3 Description**

The parent connector for type LC connector family is a simplex plug connector set of plug/adaptor/plug configuration which is characterized by:

- A 1,25 mm nominal diameter ferrule or, in the case of 1 mm OD POF, the fibre acts as the ferrule.
- The connector includes a single coupling latch and a ferrule spring loaded in the direction of the optical axis
- The plug has a single male key, which may be used to orient and limit the relative position between the connector and the component to which it is mated.
- The optical alignment mechanism of the connectors is a rigid bore sleeve or a resilient sleeve.

Drawings and dimensions provided consist of those minimum features that are functionally critical during the mating and unmating sequences of the plug with its adapter/receptacle counterpart component. The provided dimensions might cause intermateability problems with plugs not compliant to the standard.

### **4 Interfaces**

This standard contains the following standard interfaces:

Interface 20-1: simplex plug connector interface – PC

Interface 20-2: simplex adaptor interface

Interface 20-3: simplex active device receptacle interface

Interface 20-4: duplex plug connector interface – PC

Interface 20-5: duplex adaptor interface

Interface 20-6: duplex active device receptacle interface

Interface 20-7: simplex plug connector interface – APC 8 °

Interface 20-8: duplex plug connector interface – APC 8 °

Interface 20-9: simplex plug connector interface – POF 1,25 mm jacketed OD

Interface 20-10: duplex plug connector interface – POF 1,25 mm jacketed OD

Interface 20-11: simplex plug connector interface – POF 1 mm

Interface 20-12: duplex plug connector interface – POF 1 mm

Interface 20-13: simplex adaptor interface – POF 1 mm

Interface 20-14: duplex adaptor interface – POF 1 mm

Interface 20-15: simplex active device receptacle interface – POF 1 mm

Interface 20-16: duplex active device receptacle interface – POF 1 mm

- The plug of interface IEC 61754-20-1 and interface IEC 61754-20-4 has a ferrule with a spherically polished endface (PC) shown in Figure 2a.
- The plug of interface IEC 61754-20-7 and interface IEC 61754-20-8 has a ferrule with a spherically polished angled endface (APC) shown in Figure 2c.
- The plug interfaces IEC 61754-20-9 through IEC 61754-20-12 have a flat smooth endface shown in Figure 2b (POF only).
- Plug interfaces IEC 61754-20-9 and IEC 61754-20-10 (POF 1,25 mm jacketed OD) have a POF fibre of up to 0.750 mm in a 1,25 mm OD ferrule.
- Plug interfaces IEC 61754-20-11 and IEC 61754-20-12 is the 1 mm POF without the use of a ferrule (see Table 3, Note f).
- The plug connector interfaces and associated details are given in Figures 1, 2, 3, 4, and 5 along with Tables 3 and 4.
- The adaptor interfaces and associated details are given in Figures 6, 7, and, 8 along with Table 5.
- The active device receptacle interfaces and associated details are given in Figures 9, 10, and 11 along with Tables 6, 7, and 8.
- The intermateability between plugs, adaptors, and receptacles are given in Table 1.
- The intermateability between the different plug interfaces are given in Table 2.

**Table 1 – Plug to Adaptor/Receptacle Intermateability**

| Plug Interfaces<br>IEC 61754 | Adaptor/Active Device Receptacle Interfaces IEC 61754 |          |          |          |          |          |          |          |
|------------------------------|-------------------------------------------------------|----------|----------|----------|----------|----------|----------|----------|
|                              | 20-2                                                  | 20-3     | 20-5     | 20-6     | 20-13    | 20-14    | 20-15    | 20-16    |
| 20-1                         | Mate                                                  | Mate     | Mate     | Mate     | Not mate | Not mate | Not mate | Not mate |
| 20-4                         | Not mate                                              | Not mate | Mate     | Mate     | Not mate | Not mate | Not mate | Not mate |
| 20-7                         | Mate                                                  | Not mate | Mate     | Not mate | Not mate | Not mate | Not mate | Not mate |
| 20-8                         | Not mate                                              | Not mate | Mate     | Not mate | Not mate | Not mate | Not mate | Not mate |
| 20-9                         | Mate                                                  | Mate     | Mate     | Mate     | Not mate | Not mate | Not mate | Not mate |
| 20-10                        | Not mate                                              | Not mate | Mate     | Mate     | Not mate | Not mate | Not mate | Not mate |
| 20-11                        | Not mate                                              | Not mate | Not mate | Not mate | Mate     | Mate     | Mate     | Mate     |
| 20-12                        | Not mate                                              | Not mate | Not mate | Not mate | Not mate | Mate     | Not mate | Mate     |

**Table 2 – Plug to Plug Intermateability**

| Plug Interfaces<br>IEC 61754 | Plug Interface IEC 61754 |          |          |          |          |          |          |          |
|------------------------------|--------------------------|----------|----------|----------|----------|----------|----------|----------|
|                              | 20-1                     | 20-4     | 20-7     | 20-8     | 20-9     | 20-10    | 20-11    | 20-12    |
| 20-1                         | Mate                     | Mate     | Not mate | Not mate | Not Mate | Not Mate | Not mate | Not mate |
| 20-4                         | Mate                     | Mate     | Not mate | Not mate | Not Mate | Not Mate | Not mate | Not mate |
| 20-7                         | Not mate                 | Not Mate | Mate     | Mate     | Not mate | Not mate | Not mate | Not mate |
| 20-8                         | Not mate                 | Not mate | Mate     | Mate     | Not mate | Not mate | Not Mate | Not mate |
| 20-9                         | Not Mate                 | Not Mate | Not mate | Not mate | Mate     | Mate     | Not mate | Not mate |
| 20-10                        | Not Mate                 | Not Mate | Not mate | Not mate | Mate     | Mate     | Not mate | Not mate |
| 20-11                        | Not mate                 | Not mate | Not mate | Not mate | Not mate | Not mate | Mate     | Mate     |
| 20-12                        | Not mate                 | Not mate | Not mate | Not mate | Not mate | Not mate | Mate     | Mate     |





**Figure 1 – Plug connector interface reference planes**




IEC 205/12

**Key**

See Table 3.

**Figure 2 – Detail A of Figure 1 – Plug connector interface –  
Expanded view drawings not-to-scale**

Refer to IEC 61755-3 series documents for information on the end-face geometry requirements of PC and APC interfaces, respectively.




IEC 287112


**Key**

See Table 3.


**Figure 3 – Plug connector interface**



a) – Expanded view from front



b) – APC ferrule endface geometry




c) – Top view

IEC 268/12

**Key**

See Table 3.

**Figure 4 – APC plug connector interface**



IEC 269/12

**Key**

See Table 3.

**Figure 5 – Duplex plug interface**

**Table 3 – Dimensions of the plug connector interface**

| Reference                   | Dimensions in millimeters |         | Remarks              |
|-----------------------------|---------------------------|---------|----------------------|
|                             | Minimum                   | Maximum |                      |
| A                           | -                         | -       | Table 4 <sup>1</sup> |
| B <sup>a</sup>              | 10,3                      | 10,5    |                      |
| C                           | 4,2                       | 4,4     |                      |
| D                           | 3,2                       | 3,35    |                      |
| E                           | 2,2                       | 2,4     |                      |
| F                           | 0,3                       | 0,5     | Radius               |
| G                           | 4,88                      | 5,00    | Ferrule extension    |
| H <sub>1</sub> <sup>e</sup> | 4,42                      | 4,52    |                      |
| H <sub>2</sub> <sup>e</sup> | 4,42                      | 4,52    |                      |
| I                           | 3,0                       | 3,2     | Diameter             |
| J                           | H/2                       | H/2     |                      |
| K                           | 6,25                      |         | Basic dimension      |
| L <sup>e</sup>              | -                         | 0,2     | Degrees              |
| M                           | -                         | 1,0     |                      |
| N                           | -                         | 0,5     |                      |
| O                           | 1,1                       | 1,3     |                      |
| P                           | 21                        |         | Degrees, typical     |
| Q                           | 8,5                       | 8,7     |                      |
| R                           | 0,4                       | 0,6     | Radius               |
| S                           | 30                        |         | Degrees, typical     |
| T                           | 1,4                       | 1,6     |                      |
| U                           | 5,0                       | 5,1     |                      |
| V                           | 12,1                      | -       |                      |

**Table 3 – Dimensions of the plug connector interface (continued)**

| Reference       | Dimensions in millimeters |         | Remarks                               |
|-----------------|---------------------------|---------|---------------------------------------|
|                 | Minimum                   | Maximum |                                       |
| W               | 14                        |         | Degrees, typical                      |
| X               | 0,5                       | 0,7     |                                       |
| Y               | 3,3                       | –       |                                       |
| Z               | 5,6                       | 5,7     |                                       |
| AA              | 5,2                       | 5,4     |                                       |
| AB              | 0,3                       | 0,5     |                                       |
| AC              | 0,8                       | 1,0     |                                       |
| AD              | 1,2                       | 1,4     |                                       |
| AE              | 0,6                       | 0,85    | Pedestal diameter                     |
| AG              | –                         | 1,0     |                                       |
| AH              | 0,6                       | 0,85    | Pedestal diameter                     |
| AI <sup>c</sup> | 5                         | 12      | Radius                                |
| AM <sup>d</sup> | 90                        |         | Basic dimension, degrees <sup>d</sup> |
| AN              | 8                         |         | Basic dimension, degrees              |

<sup>a</sup> Dimension B is given for a plug endface when not mated. The ferrule is movable by a certain axial compression force, with direct contacting endface, and therefore dimension B is variable. Ferrule compression force shall be 5,0 N to 6,0 N when the position of the optical datum target, dimension B is moved to the range 9,8 mm to 10,0 mm. Forces are for buffered fibre only, different cord constructions can result in higher forces, see IEC 60794-2-50.

<sup>b</sup> A chamfer or radius is allowed to a maximum depth of 0,5 mm from the ferrule endface.

<sup>c</sup> These dimensional requirements apply to the finished ferrule, after all polishing procedures have been completed.

<sup>d</sup> Dimension AM is defined as an angle between two planes: One plane, plane A, passes through the axis of the ferrule and the axis of symmetry of the key of the angled endface connector plug. The other plane, plane B, passes through the axis of the ferrule and the plane normal to the angled PC reference plane.


<sup>e</sup> Taper, dimension L, is applied to the surfaces associated with dimensions/features H<sub>1</sub> and H<sub>2</sub>.

<sup>f</sup> For 1 mm POF and 1,25 mm jacketed POF the fibre or the fibre jacket will act as the connector ferrule/alignment feature.


<sup>g</sup> Drawings and dimensions provided consist of those minimum features that are functionally critical during the mating and unmating sequences of the plug with its adapter/receptacle counterpart component. The provided dimensions might cause intermateability problems with plugs not compliant to the standard.

**Table 4 – Plug connector interface – Ferrule grade**

| Grade | ØA<br>Dimensions in millimeters |         | Remarks                 |
|-------|---------------------------------|---------|-------------------------|
|       | Minimum                         | Maximum |                         |
| 1     | 1,2485                          | 1,2495  |                         |
| 2     | 1,2483                          | 1,2495  |                         |
| 3     | 1,2467                          | 1,2495  |                         |
| 4     | 1,200                           | 1,250   | 1,25 mm OD jacketed POF |
| 5     | 0.90                            | 1.00    | 1 mm OD POF             |




a) Simplex adapter interface dimensions



b) - Section a-a

c) - Section b-b




d) - Section b-b (POF Rigid bore)


IEC 290/12

**Key**  
See Table 5.

**Figure 6 – Simplex adaptor interface**



a) Junior adapter interface dimensions



b) – Section a-a


c) Section b-b

**Key**

See Table 5.

IEC 291/12

**Figure 7 – Junior (Jr.) adaptor interface (optional – note g of Table 3)**



IEC 292/12

**Key**


See Table 5.

**Figure 8 – Duplex adaptor interface**

**Table 5 – Dimensions of the adaptor interface**

| Reference               | Dimensions in millimeters |         | Remarks          |
|-------------------------|---------------------------|---------|------------------|
|                         | Minimum                   | Maximum |                  |
| A <sup>a, b, c, d</sup> | –                         | –       | Diameter         |
| B                       | 9,9                       | 10,0    |                  |
| C                       | 4,5                       | –       |                  |
| D                       | 3,4                       | 3,5     |                  |
| E                       | 2,6                       | 2,7     |                  |
| F                       | 0,2                       | 0,3     | Radius           |
| G                       | 4,0                       | 4,1     |                  |
| H <sub>1</sub>          | 4,60                      | 4,75    |                  |
| H <sub>2</sub>          | 4,60                      | 4,75    |                  |
| I                       | 2,87                      | 2,97    | Diameter         |
| J                       | 2,29                      |         | Basic dimension  |
| K                       | 6,25                      |         | Basic dimension  |
| L <sup>e</sup>          | –                         | 0,2     | Degrees          |
| M                       | 1,0                       | 1,1     |                  |
| N                       | 0,5                       | 0,6     |                  |
| O                       | –                         | 1,3     |                  |
| P                       | 15                        |         | Degrees, typical |
| R                       | 60                        |         | Degrees, typical |
| AK                      | 0,5                       | 0,6     |                  |
| AL                      | 1,7                       | 1,8     |                  |
| AO                      | 11,0                      | 12,8    |                  |
| AP                      | 14,5                      | 14,7    |                  |

| Reference                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Dimensions in millimeters |         | Remarks  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|---------|----------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Minimum                   | Maximum |          |
| AQ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2,2                       | 2,4     | Radius   |
| AR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1,1                       | 1,2     |          |
| AS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 6,6                       | 6,8     |          |
| AT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 0,6                       | 0,7     |          |
| AV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1,0                       | 1,1     |          |
| AW                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1,4                       | 1,5     | Diameter |
| AX                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 1,9                       | –       |          |
| AY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 5,3                       | 5,4     |          |
| <p><sup>a</sup> The connector alignment feature is a resilient (split) alignment sleeve, and the sleeve may be either fixed or floating. Rigid bore for POF. For a fixed sleeve the positional tolerance of dimension I applies to both A and I dimensions. For a floating sleeve, a gauge pin inserted in the sleeve must be capable of moving freely into a position such that it is coincident with datum B. Dimension A defines the inner diameter of the alignment feature.</p> <p><sup>b</sup> The connector alignment feature is a resilient (split) alignment sleeve. The feature must accept a pin gauge to the centre of the adaptor with a force of 1,0 N to 2,5 N under the condition that another pin gauge is inserted into the feature from the other side until both pin gauges butt against each other. The pin gauge shall be 1,2490 mm as shown in Figure 11 and Table 8. The centre of the adaptor is defined by the left side position of dimension B.</p> <p><sup>c</sup> For POF the connector alignment feature is a rigid bore as depicted in Figure 6d. See Table 7 for gauge pin measurements of dimension A. All positional tolerances apply.</p> <p><sup>d</sup> Each of the units in the duplex adaptor shall comply with all of dimensions of Figures 6, Figure 7 and Figure 8</p> <p><sup>e</sup> Taper, dimension L, is applied to the surfaces associated with dimensions/features H1 and H2.</p> <p><sup>f</sup> Additional information for different port configurations, panel cut-outs and outside dimensions can be found in Informative Annex A, Figures A.1 to A.4 and Tables A.1 to A.4 of this document.</p> <p><sup>g</sup> The Jr. adaptor configuration is optional for one half of an adaptor. The distance from the optical plane to the mechanical plane (dimension B) is the same for all adaptors and receptacles. The Jr. configuration does not use feature/dimension AP. The Jr. side of the adaptor is ONLY for protected environments such as inside of a cabinet or shelf. The Jr. side of an adaptor shall NEVER protrude through to the "user" side of a panel.</p> <p><sup>h</sup> Drawings and dimensions provided consist of those minimum features that are functionally critical during the mating and unmating sequences of the plug with its adapter/receptacle counterpart component. The provided dimensions might cause intermateability problems with plugs not compliant to the standard.</p> |                           |         |          |




IEC 293/12

**Key**

See Table 6.

**Figure 9 – Active device receptacle interface**

**Key**

See Table 6.

**Figure 10 – Duplex active device receptacle interface****Table 6 – Dimensions of the active device receptacle**

| Reference            | Dimensions in millimeters |         | Remarks          |
|----------------------|---------------------------|---------|------------------|
|                      | Minimum                   | Maximum |                  |
| A <sup>a, b, c</sup> | –                         | –       | Grade, Table 7   |
| B                    | 9,9                       | 10,0    |                  |
| C                    | 4,5                       | –       |                  |
| D                    | 3,4                       | 3,5     |                  |
| E                    | 2,6                       | 2,7     |                  |
| F                    | 0,2                       | 0,3     | Radius           |
| G                    | 4,0                       | 4,1     |                  |
| H <sub>1</sub>       | 4,60                      | 4,75    |                  |
| H <sub>2</sub>       | 4,60                      | 4,75    |                  |
| I                    | 2,87                      | 2,97    | Diameter         |
| J                    | 2,29                      |         | Basic dimension  |
| K                    | 6,25                      |         | Basic dimension  |
| L <sup>d</sup>       | –                         | 0,2     | Degrees          |
| M                    | 1,0                       | 1,1     |                  |
| N                    | 0,5                       | 0,6     |                  |
| O                    | –                         | 1,3     |                  |
| P                    | 15                        |         | Degrees, typical |
| AO                   | 11,0                      | 12,8    |                  |
| AP                   | 14,5                      | 14,7    |                  |
| AQ                   | 2,2                       | 2,4     | Radius           |
| AR                   | 1,1                       | 1,2     |                  |
| AS                   | 6,6                       | 6,8     |                  |

| Reference | Dimensions in millimeters |         | Remarks        |
|-----------|---------------------------|---------|----------------|
|           | Minimum                   | Maximum |                |
| AT        | 0,6                       | 0,7     |                |
| AV        | 1,0                       | 1,1     |                |
| AW        | 0,5                       | 0,6     | Grade, Table 7 |
| AX        | 1,9                       | –       |                |

<sup>a</sup> The connector alignment feature is a rigid bore sleeve or a resilient alignment sleeve. Dimension A defines the inner diameter of the alignment feature.

<sup>b</sup> The sleeve may be fixed or floating. For a fixed sleeve, the positional tolerance applies. For a floating sleeve, a gauge pin, as shown in Figure 11, inserted in the sleeve must be capable of moving freely into a position such that it is coincident with datum B.

<sup>c</sup> Each of the units in the duplex receptacle shall comply with all of dimensions of Figures 9 and 10.

<sup>d</sup> Taper, dimension L, is applied to the surfaces associated with dimension/feature H<sub>1</sub> and H<sub>2</sub>.

<sup>e</sup> Drawings and dimensions provided consist of those minimum features that are functionally critical during the mating and unmating sequences of the plug with its adapter/receptacle counterpart component. The provided dimensions might cause intermateability problems with plugs not compliant to the standard.


**Table 7 – Active device receptacle interface – Alignment sleeve grade**

| Grade                       | Reference A<br>Dimensions in millimeters |         | Remarks                                    |
|-----------------------------|------------------------------------------|---------|--------------------------------------------|
|                             | Minimum                                  | Maximum |                                            |
| 1                           | 1,251                                    | 1,252   | Rigid bore sleeve <sup>a, b</sup>          |
| 2                           | 1,251                                    | 1,254   |                                            |
| 3                           | 1,251                                    | 1,257   |                                            |
| 4 (POF 1,25 mm jacketed OD) | 1,251                                    | 1,265   |                                            |
| 5 (POF 1mm)                 | 1,070                                    | 1,200   |                                            |
| 6                           |                                          |         | Resilient alignment sleeve <sup>b, c</sup> |

<sup>a</sup> The connector alignment feature is a rigid bore sleeve. The dimension A shall be tested using two pin gauges. One pin gauge has the pin gauge grade number 1  $\mu\text{m}$  larger than the maximum value of dimension A, the other pin gauge has the pin gauge grade number 1  $\mu\text{m}$  smaller than the minimum value of dimension A. The appropriate pin gauge shall be selected from the pin gauge grade table.

<sup>b</sup> The connector alignment feature is a resilient (split) alignment sleeve. The feature must accept a pin gauge completely to the left side of dimension G with a force of 1,0 N to 2,5 N. Insert the pin gauge completely, from only one side, the connector side of the active device receptacle interface. The pin gauge is defined in Table 8

<sup>c</sup> Add grade number to the interface reference number.



**Key**

See Table 8.


**Figure 11 – Pin gauge for active device receptacle**

**Table 8 – Pin gauge grade**

| Pin gauge grade                                                                         | CK diameter<br>Dimensions in millimeters |         | CN<br>Dimensions in millimeters |         | Remarks                       |
|-----------------------------------------------------------------------------------------|------------------------------------------|---------|---------------------------------|---------|-------------------------------|
|                                                                                         | Minimum                                  | Maximum | Minimum                         | Maximum |                               |
| 1,249                                                                                   | 1,2488                                   | 1,2492  | 4,2                             | 15      | Resilient sleeve <sup>a</sup> |
| <sup>a</sup> Surface roughness should be < 0,2 µm Ra; cylindricity is less than 0,5 µm. |                                          |         |                                 |         |                               |

## Annex A (informative)

### Additional adaptor dimensional information



a) Simplex adaptor dimensions

b) Panel cutout

IEC 296/12

#### Key


See Table A.1.

Figure A.1 – Simplex adaptor

Table A.1 – Dimensions of simplex adaptor

| Ref. | Dimensions in millimeters |      | Remarks |
|------|---------------------------|------|---------|
|      | Min.                      | Max. |         |
| DA   | 25,5                      | 27,5 |         |
| DB   | 11,5                      | 11,6 |         |
| DC   | 6,9                       | 7,0  |         |
| DD   | 7,1                       | 7,2  |         |
| DE   | 11,7                      | 11,8 |         |
| DF   | –                         | 13,3 |         |
| DH   | –                         | 3,8  |         |
| DI   | 1,7                       | 2,0  |         |
| DJ   | 12,6                      | 12,9 |         |
| DK   | 13,0                      | 13,4 |         |

NOTE Panel cutout: panel thickness should be between 1,0 and 1,5 mm.



IEC 297/12


**Key**

See Table A.2.

**Figure A.2 – Duplex square flange adaptor****Table A.2 – Dimensions of duplex square flange adaptor**

| Ref. | Dimensions in millimeters |       | Remarks |
|------|---------------------------|-------|---------|
|      | Min.                      | Max.  |         |
| EA   | 25,5                      | 27,5  |         |
| EB   | 13,0                      | 13,15 |         |
| EC   | 13,0                      | 13,15 |         |
| ED   | 13,2                      | 13,4  |         |
| EE   | 13,2                      | 13,4  |         |
| EF   | –                         | 15,3  |         |
| EH   | –                         | 3,8   |         |
| EI   | 1,7                       | 2,0   |         |
| EJ   | 12,6                      | 12,9  |         |
| EK   | 14,5                      | 15,3  |         |

NOTE Panel cutout: panel thickness should be between 1,0 and 1,5 mm.



**Key**

See Table A.3.


IEC 298/12

**Figure A.3 – Duplex rectangular flange adaptor**

**Table A.3 – Dimensions of duplex rectangular flange adaptor**

| Ref. | Dimensions in millimeters |      | Remarks                |
|------|---------------------------|------|------------------------|
|      | Min.                      | Max. |                        |
| FA   | 25,5                      | 27,5 |                        |
| FB   | 9,2                       | 9,45 |                        |
| FC   | 12,6                      | 13,0 |                        |
| FD   | 13,1                      | 13,5 |                        |
| FE   | 9,5                       | 10,0 |                        |
| FF   | -                         | 15,6 |                        |
| FG   | 17,9                      | 18,1 |                        |
| FH   | 2,8                       | 3,2  |                        |
| FI   | 1,7                       | 2,0  |                        |
| FJ   | 15,95                     | 16,6 |                        |
| FK   | 14,5                      | 14,9 | Dimension over latches |
| FP   | 2,4                       | 2,6  | Holes optional         |
| FQ   | 21,5                      | 22,5 | Flange Optional        |
| FR   | 17,5                      | 18,5 | Flange Optional        |
| FS   | 2,2                       | 2,5  | Flange Optional        |

NOTE Panel cutout: panel thickness should be between 1,0 and 1,5 mm.



IEC 299/12

**Key**  
See Table A.4.

**Figure A.4 –Quad rectangular flange adaptor**

**Table A.4 – Dimensions for quad rectangular flange adaptor**

| Ref. | Dimensions in millimeters |      | Remarks        |
|------|---------------------------|------|----------------|
|      | Min.                      | Max. |                |
| GB   | 9,35                      | 9,45 | Holes optional |
| GC   | 25,6                      | 25,9 |                |
| GD   | 26,0                      | 26,5 |                |
| GE   | 9,5                       | 10,0 |                |
| GG   | 30,6                      | 30,8 |                |
| GP   | 2,39                      | 2,59 |                |

NOTE 1 Dimensions same as duplex rectangular flange adaptors (A.3) except as noted. Flange not shown.

NOTE 2 Panel cutout: panel thickness should be between 1,0 and 1,5 mm.

### Bibliography

IEC 60793-2-40, *Optical fibres – Part 2-40: Product specifications – Sectional specification for category A multimode fibres*

IEC 60794-2-50, *Optical fibre cables – Part 2-50: Indoor cables – Family specification for simplex and duplex cables for use in terminated cable assemblies*

---



INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

3, rue de Varembe  
PO Box 131  
CH-1211 Geneva 20  
Switzerland

Tel: + 41 22 919 02 11  
Fax: + 41 22 919 03 00  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)