

http://multimedia.3m.com/mws/media/446191O/3mtm-fire-barrier-pass-through-device.pdf

Go

OCT

NOV

DEC



2014

2015

2016

About this capture

1 capture

23 Nov 2015



3mtm-fire-barrier-pa...


1 / 2



33%



1



2

3M™ Fire Protection Products
3M™ Fire Barrier Pass-Through Devices

Accessible Flexible & Organized

3M™ Fire Barrier Pass-Through Devices are your solution for a wide variety of through-penetration firestop assemblies.

3M™ Fire Barrier Pass-Through Devices are designed for easy installation and re-entrability, helping to reduce construction costs and meet code requirements. From cables to pipes and more, 3M™ Fire Barrier Pass-Through Devices offer you a hassle-free firestop method to help you protect your building and the precious lives and resources within it.

3M

Flexible firestop solutions for a wide variety of system requirements.

Finally, a device for penetrating structures where electrical, data and communication cables or plumbing pipes through fire-rated floors and walls. 3M™ Fire Barrier Pass-Through Devices install in a few simple steps and help keep penetrations organized. Plus, device re-entrability provides flexibility for future additions.

3M™ Fire Barrier Pass-Through Devices meet the ASTM E 814 (UL 1013, 1017) Fire Test Standard and are fire-rated for up to 4 hours (dependent upon system application). 3M™ Fire Barrier Pass-Through Devices use a fluid intumescent material expands with heat which works in conjunction with a foam plug and optional mounting bracket. In the event of a fire, intumescent material expands to seal the inside of the device, helping to prevent the spread of smoke and fire into other compartments.

- Springs for round devices can easily be created with a standard hole saw
- UL classified 1, 2, 3 and 4 hour fire (F) rating
- UL classified L rating, Hot and Cold Smoke Seal with installable gasket installed at both ends of device
- Suitable for general versatility
- Can be used from 0% to 100% cable fill
- Designed for easy retrofit installation
- Inside range inside devices help prevent cables or pipes from getting damaged during installation

Device Ordering Information

Device Number	Description	QFC Number	Std.	Qty. Per Case	Case (F) Rating
PT0000	2" Round Device	000 01710 10010-0	Each	6	Up to 1 hour
PT0001	2" Round Device	000 01710 10000-0	Each	6	Up to 1 hour
PT0002	2" Square Device	000 01710 10001-0	Each	6	Up to 1 hour
PT0003	2" Round Mounting Bracket (Pkg)	000 01710 10010-0	Pkg	24	NA
PT0004	2" Round Mounting Bracket (Pkg)	000 01710 10010-0	Pkg	24	NA
PT0005	2" Square Single Mounting Bracket (Pkg)	000 01710 10010-0	Pkg	24	NA
PT0006	2" Square Single Mounting Bracket (Pkg)	000 01710 10010-0	Pkg	24	NA
PT0007	2" Square Single Mounting Bracket (Pkg)	000 01710 10010-0	Pkg	24	NA
PT0008	2" Round Device Foam Plug	000 01710 10010-0	Each	1	NA
PT0009	2" Round Device Foam Plug	000 01710 10010-0	Each	1	NA
PT0010	2" Square Device Foam Plug	000 01710 10010-0	Each	1	NA

Product Information

3M is a trademark of 3M. Used under license in Canada. Please recycle. Printed in U.S.A. © 2015 3M. All rights reserved. 3M 01710 10010-0

3M

Building and Commercial
Security Division
3M Center
St. Paul, MN 55144-0001
U.S.A. 651.321.3000
www.3m.com

UL

UL

UL

UL