




US 20040228479A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0228479 A1**
(43) **Pub. Date:** **Nov. 18, 2004**(54) **MICROPROCESSOR APPARATUS AND
METHOD FOR PERFORMING BLOCK
CIPHER CRYPTOGRAPHIC FUNCTIONS****Publication Classification**(51) **Int. Cl.⁷** **H04K 1/00**(52) **U.S. Cl.** **380/28**(75) **Inventors:** **Thomas A. Crispin**, Austin, TX (US);
G. Glenn Henry, Austin, TX (US);
Terry Parks, Austin, TX (US)**Correspondence Address:**
HUFFMAN LAW GROUP, P.C.
1832 N. CASCADE AVE.
COLORADO SPRINGS, CO 80907-7449 (US)(57) **ABSTRACT**

The present invention provides an apparatus and method for performing cryptographic operations on a plurality of input data blocks within a processor. In one embodiment, an apparatus for performing cryptographic operations is provided. The apparatus includes a cryptographic instruction and execution logic. The cryptographic instruction is received by logic within a processor, wherein said cryptographic instruction prescribes one of the cryptographic operations. The execution logic is coupled to said logic. The execution logic performs the one of the cryptographic operations.

(73) **Assignee:** **IP-First, LLC**, Fremont, CA(21) **Appl. No.:** **10/674,057**(22) **Filed:** **Sep. 29, 2003****Related U.S. Application Data**(60) **Provisional application No. 60/464,394**, filed on Apr. 18, 2003.




FIG. 1




FIG. 2




FIG. 3




FIG. 4

Table 500 maps BCM values to cipher modes. The table has two columns: 'BCM VALUE' and 'MODE'. The rows are as follows:

BCM VALUE	MODE
0xC8	ELECTRONIC CODE BOOK (ECB)
0xD0	CIPHER BLOCK CHAINING (CBC)
0xE0	CIPHER FEEDBACK (CFB)
0xE8	OUTPUT FEEDBACK (OFB)
ALL OTHER VALUES	RESERVED

An arrow points from the label 500 to the table.

FIG. 5




FIG. 6




FIG. 7

VALUE	OPERATION
000	RESERVED
001	RESERVED
010	LOAD CONTROL WORD (CW) REGISTER
011	RESERVED
100	LOAD INPUT-0 (IN-0) REGISTER AND START CRYPTOGRAPHY UNIT
101	LOAD INPUT-1 (IN-1) REGISTER
110	LOAD CRYPTO KEY-0 REGISTER (LOWER 128 BITS OF KEY)
111	LOAD CRYPTO KEY-1 REGISTER (UPPER 128 BITS OF KEY)

FIG. 8

VALUE	OPERATION
000	RESERVED
001	RESERVED
010	RESERVED
011	RESERVED
100	STORE OUTPUT-0 (OUT-0) REGISTER
101	STORE OUTPUT-1 (OUT-1) REGISTER
110	RESERVED
111	RESERVED

FIG. 9




FIG. 10




FIG. 11




FIG. 12

MICROPROCESSOR APPARATUS AND METHOD FOR PERFORMING BLOCK CIPHER CRYPTOGRAPHIC FUNCTIONS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 60/464394 (Docket CNTR.2222), filed on Apr. 18, 2003, which is herein incorporated by reference for all intents and purposes.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] This invention relates in general to the field of microelectronics, and more particularly to an apparatus and method for performing cryptographic operations in a microprocessor.

[0004] 2. Description of the Related Art

[0005] An early computer system operated independently of other computer systems in the sense that all of the input data required by an application program executing on the early computer system was either resident on that computer system or was provided by an application programmer at run time. The application program generated output data as a result of being executed and the output data was generally in the form of a paper printout or a file which was written to a magnetic tape drive, disk drive, or other type of mass storage device that was part of the computer system. The output file could then be used as an input file to a subsequent application program that was executed on the same computer system or, if the output data was previously stored as a file to a removable or transportable mass storage device, it could then be provided to a different, yet compatible, computer system to be employed by application programs thereon. On these early systems, the need for protecting sensitive information was recognized and, among other information security measures, cryptographic application programs were developed and employed to protect the sensitive information from unauthorized disclosure. These cryptographic programs typically scrambled and unscrambled the output data that was stored as files on mass storage devices.

[0006] It was not many years thereafter before users began to discover the benefits of networking computers together to provide shared access to information. Consequently, network architectures, operating systems, and data transmission protocols commensurately evolved to the extent that the ability to access shared data was not only supported, but prominently featured. For example, it is commonplace today for a user of a computer workstation to access files on a different workstation or network file server, or to utilize the Internet to obtain news and other information, or to transmit and receive electronic messages (i.e., email) to and from hundreds of other computers, or to connect with a vendor's computer system and to provide credit card or banking information in order to purchase products from that vendor, or to utilize a wireless network at a restaurant, airport, or other public setting to perform any of the aforementioned activities. Therefore, the need to protect sensitive data and transmissions from unauthorized disclosure has grown dramatically. The number of instances during a given computer session where a user is obliged to protect his or her sensitive

data has substantially increased. Current news headlines regularly force computer information security issues such as spam, hacking, identity theft, reverse engineering, spoofing, and credit card fraud to the forefront of public concern. And since the motivation for these invasions of privacy range all the way from innocent mistakes to premeditated cyber terrorism, responsible agencies have responded with new laws, stringent enforcement, and public education programs. Yet, none of these responses has proved to be effective at stemming the tide of computer information compromise. Consequently, what was once the exclusive concern of governments, financial institutions, the military, and spies has now become a significant issue for the average citizen who reads their email or accesses their checking account transactions from their home computer. On the business front, one skilled in the art will appreciate that corporations from small to large presently devote a remarkable portion of their resources to the protection of proprietary information.

[0007] The field of information security that provides us with techniques and means to encode data so that it can only be decoded by specified individuals is known as cryptography. When particularly applied to protecting information that is stored on or transmitted between computers, cryptography most often is utilized to transform sensitive information (known in the art as "plaintext" or "cleartext") into an unintelligible form (known in the art as "ciphertext"). The transformation process of converting plaintext into ciphertext is called "encryption," "enciphering," or "ciphering" and the reverse transformation process of converting ciphertext back into plaintext is referred to as "decryption," "deciphering," or "inverse ciphering."

[0008] Within the field of cryptography, several procedures and protocols have been developed that allow for users to perform cryptographic operations without requiring great knowledge or effort and for those users to be able to transmit or otherwise provide their information products in encrypted forms to different users. Along with encrypted information, a sending user typically provides a recipient user with a "cryptographic key" that enables the recipient user to decipher the encrypted information thus enabling the recipient user to recover or otherwise gain access to the unencrypted original information. One skilled in the art will appreciate that these procedures and protocols generally take the form of password protection, mathematical algorithms, and application programs specifically designed to encrypt and decrypt sensitive information.

[0009] Several classes of algorithms are currently used to encrypt and decrypt data. Algorithms according to one such class (i.e., public key cryptographic algorithms, an instance of which is the RSA algorithm) employ two cryptographic keys, a public key and a private key, to encrypt or decrypt data. According to some of the public key algorithms, a recipient's public key is employed by a sender to encrypt data for transmission to the recipient. Because there is a mathematical relationship between a user's public and private keys, the recipient must employ his private key to decrypt the transmission in order to recover the data. Although this class of cryptographic algorithms enjoys widespread use today, encryption and decryption operations are exceedingly slow even on small amounts of data. A second class of algorithms, known as symmetric key algorithms, provide commensurate levels of data security and can be executed much faster. These algorithms are called

symmetric key algorithms because they use a single cryptographic key to both encrypt and decrypt information. In the public sector, there are currently three prevailing single-key cryptographic algorithms: the Data Encryption Standard (DES), Triple DES, and the Advanced Encryption Standard (AES). Because of the strength of these algorithms to protect sensitive data, they are used now by U.S. Government agencies, but it is anticipated by those in the art that one or more of these algorithms will become the standard for commercial and private transactions in the near future. According to all of these symmetric key algorithms, plaintext and ciphertext is divided into blocks of a specified size for encryption and decryption. For example, AES performs cryptographic operations on blocks 128 bits in size, and uses cryptographic key sizes of 128-, 192-, and 256-bits. Other symmetric key algorithms such as the Rijndael Cipher allow for 192- and 256-bit data blocks as well. Accordingly, for a block encryption operation, a 1024-bit plaintext message is encrypted as eight 128-bit blocks.

[0010] All of the symmetric key algorithms utilize the same type of sub-operations to encrypt a block of plaintext. And according to many of the more commonly employed symmetric key algorithms, an initial cryptographic key is expanded into a plurality of keys (i.e., a “key schedule”), each of which is employed as a corresponding cryptographic “round” of sub-operations is performed on the block of plaintext. For instance, a first key from the key schedule is used to perform a first cryptographic round of sub-operations on the block of plaintext. The result of the first round is used as input to a second round, where the second round employs a second key from the key schedule to produce a second result. And a specified number of subsequent rounds are performed to yield a final round result which is the ciphertext itself. According to the AES algorithm, the sub-operations within each round are referred to in the literature as SubBytes (or S-box), ShiftRows, MixColumns, and AddRoundKey. Decryption of a block of ciphertext is similarly accomplished with the exceptions that the ciphertext is the input to the inverse cipher and inverse sub-operations are performed (e.g., Inverse MixColumns, Inverse ShiftRows) during each of the rounds, and the final result of the rounds is a block of plaintext.

[0011] DES and Triple-DES utilize different specific sub-operations, but the sub-operations are analogous to those of AES because they are employed in a similar fashion to transform a block of plaintext into a block of ciphertext.

[0012] To perform cryptographic operations on multiple successive blocks of text, all of the symmetric key algorithms employ the same types of modes. These modes include electronic code book (ECB) mode, cipher block chaining (CBC) mode, cipher feedback (CFB) mode, and output feedback (OFB) mode. Some of these modes utilize an additional initialization vector during performance of the sub-operations and some use the ciphertext output of a first set of cryptographic rounds performed on a first block of plaintext as an additional input to a second set of cryptographic rounds performed on a second block of plaintext. It is beyond the scope of the present application to provide an in depth discussion of each of the cryptographic algorithms and sub-operations employed by present day symmetric key cryptographic algorithms. For specific implementation standards, the reader is directed to Federal Information Processing Standards Publication 46-3 (FIPS-46-3), dated Oct. 25,

1999 for a detailed discussion of DES and Triple DES, and *Federal Information Processing Standards Publication 197 (FIPS-197)*, dated Nov. 26, 2001 for a detailed discussion of AES. Both of the aforementioned standards are issued and maintained by the National Institute of Standards and Technology (NIST) and are herein incorporated by reference for all intents and purposes. In addition to the aforementioned standards, tutorials, white papers, toolkits, and resource articles can be obtained from NIST’s Computer Security Resource Center (CSRC) over the Internet at <http://csrc.nist.gov/>.

[0013] One skilled in the art will appreciate that there are numerous application programs available for execution on a computer system that can perform cryptographic operations (i.e., encryption and decryption). In fact, some operating systems (e.g. Microsoft® WindowsXP®, Linux) provide direct encryption/decryption services in the form of cryptographic primitives, cryptographic application program interfaces, and the like. The present inventors, however, have observed that present day computer cryptography techniques are deficient in several respects. Thus, the reader’s attention is directed to **FIG. 1**, whereby these deficiencies are highlighted and discussed below.

[0014] **FIG. 1** is a block diagram **100** illustrating present day computer cryptography applications. The block diagram **100** depicts a first computer workstation **101** connected to a local area network **105**. Also connected to the network **105** is a second computer workstation **102**, a network file storage device **106**, a first router **107** or other form of interface to a wide area network (WAN) **110** such as the Internet, and a wireless network router **108** such as one of those compliant with IEEE Standard 802.11. A laptop computer **104** interfaces to the wireless router **108** over a wireless network **109**. At another point on the wide area network **110**, a second router **111** provides interface for a third computer workstation **103**.

[0015] As alluded to above, a present day user is confronted with the issue of computer information security many times during a work session. For example, under the control of a present day multi-tasking operating system, a user of workstation **101** can be performing several simultaneous tasks, each of which require cryptographic operations. The user of workstation **101** is required to run an encryption/decryption application **112** (either provided as part of the operating system or invoked by the operating system) to store a local file on the network file storage device **106**. Concurrent with the file storage, the user can transmit an encrypted message to a second user at workstation **102**, which also requires executing an instance of the encryption/decryption application **112**. The encrypted message may be real-time (e.g., an instant message) or non-real-time (i.e. email). In addition, the user can be accessing or providing his/her financial data (e.g., credit card numbers, financial transactions, etc.) or other forms of sensitive data over the WAN **110** from workstation **103**. Workstation **103** could also represent a home office or other remote computer **103** that the user of workstation **101** employs when out of the office to access any of the shared resources **101, 102, 106, 107, 108, 109** on local area network **105**. Each of these aforementioned activities requires that a corresponding instance of the encryption/decryption application **112** be invoked. Furthermore, wireless networks **109** are now being routinely provided in coffee shops, airports, schools, and other public

venues, thus prompting a need for a user of laptop **104** to encrypt/decrypt not only his/her messages to/from other users, but to encrypt and decrypt all communications over the wireless network **109** to the wireless router **108**.

[**0016**] One skilled in the art will therefore appreciate that along with each activity that requires cryptographic operations at a given workstation **101-104**, there is a corresponding requirement to invoke an instance of the encryption/decryption application **112**. Hence, a computer **101-104** in the near future could potentially be performing hundreds of concurrent cryptographic operations.

[**0017**] The present inventors have noted several limitations to the above approach of performing cryptographic operations by invoking one or more instances of an encryption/decryption application **112** on a computing system **101-104**. For example, performing a prescribed function via programmed software is exceedingly slow compared to performing that same function via dedicated hardware. Each time the encryption/decryption application **112** is required, a current task executing on a computer **101-104** must be suspended from execution, and parameters of the cryptographic operation (i.e., plaintext, ciphertext, mode, key, etc.) must be passed through the operating system to the instance of the encryption/decryption application **112**, which is invoked for accomplishment of the cryptographic operation. And because cryptographic algorithms necessarily involve many rounds of sub-operations on a particular block of data, execution of the encryption/decryption applications **112** involves the execution of numerous computer instructions to the extent that overall system processing speed is disadvantageously affected. One skilled in the art will appreciate that sending a small encrypted email message in Microsoft® Outlook® can take up to five times as long as sending an unencrypted email message.

[**0018**] In addition, current techniques are limited because of the delays associated with operating system intervention. Most application programs do not provide integral key generation or encryption/decryption components; they employ components of the operating system or plug-in applications to accomplish these tasks. And operating systems are otherwise distracted by interrupts and the demands of other currently executing application programs.

[**0019**] Furthermore, the present inventors have noted that the accomplishment of cryptographic operations on a present day computer system **101-104** is very much analogous to the accomplishment of floating point mathematical operations prior to the advent of dedicated floating point units within microprocessors. Early floating point operations were performed via software and hence, they executed very slowly. Like floating point operations, cryptographic operations performed via software are disagreeably slow. As floating point technology evolved further, floating point instructions were provided for execution on floating point co-processors. These floating point co-processors executed floating point operations much faster than software implementations, yet they added cost to a system. Likewise, cryptographic co-processors exist today in the form of add-on boards or external devices that interface to a host processor via parallel ports or other interface buses (e.g., USB). These co-processors certainly enable the accomplishment of cryptographic operations much faster than pure software implementations. But cryptographic co-processors

add cost to a system configuration, require extra power, and decrease the overall reliability of a system. Cryptographic co-processor implementations are additionally vulnerable to snooping because the data channel is not on the same die as the host microprocessor.

[**0020**] Therefore, the present inventors recognize a need for dedicated cryptographic hardware within a present day microprocessor such that an application program that requires a cryptographic operation can direct the microprocessor to perform the cryptographic operation via a single, atomic, cryptographic instruction. The present inventors also recognize that such a capability should be provided so as to limit requirements for operating system intervention and management. Also, it is desirable that the cryptographic instruction be available for use at an application program's privilege level and that the dedicated cryptographic hardware comport with prevailing architectures of present day microprocessors. There is also a need to provide the cryptographic hardware and associated cryptographic instruction in a manner that supports compatibility with legacy operating systems and applications. It is moreover desirable to provide an apparatus and method for performing cryptographic operations that is resistant to unauthorized observation, that can support multiple cryptographic algorithms, that supports verification and testing of the particular cryptographic algorithm that is embodied thereon, that allows for user-provided keys as well as self-generated keys, that supports multiple data block sizes and key sizes, and that provides for programmable block encryption/decryption modes such as ECB, CBC, CFB, and OFB.

SUMMARY OF THE INVENTION

[**0021**] The present invention, among other applications, is directed to solving these and other problems and disadvantages of the prior art. The present invention provides a superior technique for performing cryptographic operations within a microprocessor. In one embodiment, an apparatus in a microprocessor is provided for accomplishing cryptographic operations. The apparatus includes translation logic and execution logic. The translation logic receives a cryptographic instruction from a source therefrom, where the cryptographic instruction prescribes one of the cryptographic operations. The translation logic also translates the cryptographic instruction into a sequence of micro instructions specifying sub-operations required to accomplish the one of the cryptographic operations. The execution logic is operatively coupled to the translation logic. The execution logic receives the sequence of micro instructions and performs the sub-operations.

[**0022**] One aspect of the present invention contemplates a microprocessor apparatus for performing cryptographic operations. The microprocessor apparatus has a cryptographic instruction and translation logic. The cryptographic instruction is provided to a microprocessor as part of an instruction flow. The cryptographic instruction prescribes one of the cryptographic operations. The translation logic translates the cryptographic instruction into associated micro instructions that specify sub-operations required to accomplish the one of the cryptographic operations.

[**0023**] Another aspect of the present invention provides an apparatus for performing cryptographic operations. The apparatus includes a cryptographic instruction and execution

logic. The cryptographic instruction is received by logic within a processor, wherein said cryptographic instruction prescribes one of the cryptographic operations. The execution logic is coupled to said logic. The execution logic performs the one of the cryptographic operations.

[0024] A further aspect of the present invention comprehends a method for performing cryptographic operations in a processor. The method includes receiving a cryptographic instruction, where the cryptographic instruction prescribes one of the cryptographic operations; and executing the one of the cryptographic operations.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] These and other objects, features, and advantages of the present invention will become better understood with regard to the following description, and accompanying drawings where:

[0026] **FIG. 1** is a block diagram illustrating present day cryptography applications;

[0027] **FIG. 2** is a block diagram depicting techniques for performing cryptographic operations;

[0028] **FIG. 3** is a block diagram featuring a microprocessor apparatus according to the present invention for performing cryptographic operations;

[0029] **FIG. 4** is a block diagram showing one embodiment of an atomic cryptographic instruction according to the present invention;

[0030] **FIG. 5** is a table illustrating exemplary block cipher mode field values according to the atomic cryptographic instruction of **FIG. 4**;

[0031] **FIG. 6** is a block diagram detailing a cryptography unit within an x86-compatible microprocessor according to the present invention;

[0032] **FIG. 7** is a diagram illustrating fields within an exemplary micro instruction for directing cryptographic sub-operations within the microprocessor of **FIG. 6**;

[0033] **FIG. 8** is a table depicting values of the register field for an XLOAD micro instruction according to the format of **FIG. 7**;

[0034] **FIG. 9** is a table showing values of the register field for an XSTOR micro instruction according to the format of **FIG. 7**;

[0035] **FIG. 10** is diagram highlighting an exemplary control word format for prescribing cryptographic parameters of a cryptography operation according to the present invention;

[0036] **FIG. 11** is a block diagram featuring details of a cryptography unit according to the present invention; and

[0037] **FIG. 12** is a block diagram illustrating an embodiment of block cipher logic according to the present invention for performing cryptographic operations in accordance with the Advanced Encryption Standard (AES).

DETAILED DESCRIPTION

[0038] The following description is presented to enable one of ordinary skill in the art to make and use the present invention as provided within the context of a particular

application and its requirements. Various modifications to the preferred embodiment will, however, be apparent to one skilled in the art, and the general principles defined herein may be applied to other embodiments. Therefore, the present invention is not intended to be limited to the particular embodiments shown and described herein, but is to be accorded the widest scope consistent with the principles and novel features herein disclosed.

[0039] In view of the above background discussion on cryptographic operations and associated techniques employed within present day computer systems to encrypt and decrypt data, the discussion of these techniques and their limitations will now be continued with reference to **FIG. 2**. Following this, the present invention will be discussed with reference to **FIGS. 3-12**. The present invention provides an apparatus and method for performing cryptographic operations in a present day computer system that exhibits superior performance characteristics over prevailing mechanisms and furthermore satisfies the above noted goals of limiting operating system intervention, atomicity, legacy and architectural compatibility, algorithmic and mode programmability, hack resistance, and testability.

[0040] Now turning to **FIG. 2**, a block diagram **200** is presented depicting techniques for performing cryptographic operations in a present day computer system as discussed above. The block diagram **200** includes a microprocessor **201** that fetches instructions and accesses data associated with an application program from an area of system memory called application memory **203**. Program control and access of data within the application memory **203** is generally managed by operating system software **202** that resides in a protected area of system memory. As discussed above, if an executing application program (e.g., an email program or a file storage program) requires that a cryptographic operation be performed, the executing application program must accomplish the cryptographic operation by directing the microprocessor **201** to execute a significant number of instructions. These instructions may be subroutines that are part of the executing application program itself, they may be plug-in applications that are linked to the execution application program, or they may be services that are provided by the operating system **202**. Regardless of their association, one skilled in the art will appreciate that the instructions will reside in some designated or allocated area of memory. For purposes of discussion, these areas of memory are shown within the application memory **203** and comprise a cryptographic key generation application **204** that typically generates or accepts a cryptographic key and expands the key into a key schedule **205** for use in cryptographic round operations. For a multi-block encryption operation, a block encryption application **206** is invoked. The encryption application **206** executes instructions that access blocks of plaintext **210**, the key schedule **205**, cryptographic parameters **209** that further specify particulars of the encryption operation such as mode, location of the key schedule, etc. If required by specified mode, an initialization vector **208** is also accessed by the encryption application **206**. The encryption application **206** executes the instructions therein to generate corresponding blocks of ciphertext **211**. Similarly, a block decryption application **207** is invoked for performing block decryption operations. The decryption application **207** executes instructions that access blocks of ciphertext **211**, the key schedule **205**, cryptographic parameters **209** that further specify par-

ticalars of the block decryption operation and, if mode requires, an initialization vector **208** is also accessed. The decryption application **207** executes the instructions therein to generate corresponding blocks of plaintext **210**.

[0041] It is noteworthy that a significant number of instructions must be executed in order to generate cryptographic keys and to encrypt or decrypt blocks of text. The aforementioned FIPS specifications contain many examples of pseudo code enabling the approximate number of instructions that are required to be estimated, therefore, one skilled in the art will appreciate that hundreds of instructions are required to accomplish a simple block encryption operation. And each of these instructions must be executed by the microprocessor **201** in order to accomplish the requested cryptographic operation. Furthermore, the execution of instructions to perform a cryptographic operation is generally seen as superfluous to the primary purposes (e.g., file management, instant messaging, email, remote file access, credit card transaction) of a currently executing application program. Consequently, a user of the currently executing application program senses that the currently executing application is performing inefficiently. In the case of stand-alone or plug-in encryption and decryption applications **206**, **207**, invocation and management of these applications **206**, **207** must also be subject to the other demands of the operating system **202** such as supporting interrupts, exceptions, and like events that further exacerbate the problem. Moreover, for every concurrent cryptographic operation that is required on a computer system, a separate instance of the applications **204**, **206**, **207** must be allocated in memory **203**. And, as noted above, it is anticipated that the number of concurrent cryptographic operations required to be performed by a microprocessor **201** will continue to increase with time.

[0042] The present inventors have noted the problems and limitations of current computer system cryptographic techniques and furthermore recognize a need to provide apparatus and methods for performing cryptographic operations in a microprocessor which do not exhibit disadvantageous program delays to users. Accordingly, the present invention provides a microprocessor apparatus and associated methodology for performing cryptographic operations via a dedicated cryptographic unit therein. The cryptographic unit is activated to perform cryptographic operations via programming of a single cryptographic instruction. The present invention will now be discussed with reference to **FIGS. 3-12**.

[0043] Referring to **FIG. 3**, a block diagram **300** is provided featuring a microprocessor apparatus according to the present invention for performing cryptographic operations. The block diagram **300** depicts a microprocessor **301** that is coupled to a system memory **321** via a memory bus **319**. The microprocessor **301** includes translation logic **303** that receives instructions from an instruction register **302**. The translation logic **303** comprises logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to translate instructions into associated sequences of micro instructions. The elements employed to perform translation within the translation logic **303** may be shared with other circuits, microcode, etc., that are employed to perform other functions within the microprocessor **301**. According to the scope of the

present application, microcode is a term employed to refer to a plurality of micro instructions. A micro instruction (also referred to as a native instruction) is an instruction at the level that a unit executes. For example, micro instructions are directly executed by a reduced instruction set computer (RISC) microprocessor. For a complex instruction set computer (CISC) microprocessor such as an x86-compatible microprocessor, x86 instructions are translated into associated micro instructions, and the associated micro instructions are directly executed by a unit or units within the CISC microprocessor. The translation logic **303** is coupled to a micro instruction queue **304**. The micro instruction queue **304** has a plurality of micro instruction entries **305**, **306**. Micro instructions are provided from the micro instruction queue **304** to register stage logic that includes a register file **307**. The register file **307** has a plurality of registers **308-313** whose contents are established prior to performing a prescribed cryptographic operation. Registers **308-312** point to corresponding locations **323-327** in memory **321** that contain data which is required to perform the prescribed cryptographic operation. The register stage is coupled to load logic **314**, which interfaces to a data cache **315** for retrieval of data for performance of the prescribed cryptographic operation. The data cache **315** is coupled to the memory **321** via the memory bus **319**. Execution logic **328** is coupled to the load logic **314** and executes the operations prescribed by micro instructions as passed down from previous stages. The execution logic **328** comprises logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to perform operations as prescribed by instructions provided thereto. The elements employed to perform the operations within the execution logic **328** may be shared with other circuits, microcode, etc., that are employed to perform other functions within the microprocessor **301**. The execution logic **328** includes a cryptography unit **316**. The cryptography unit **316** receives data required to perform the prescribed cryptographic operation from the load logic **314**. Micro instructions direct the cryptography unit **316** to perform the prescribed cryptographic operation on a plurality of blocks of input text **326** to generate a corresponding plurality of blocks of output text **327**. The cryptography unit **316** comprises logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to perform cryptographic operations. The elements employed to perform the cryptographic operations within the cryptography unit **316** may be shared with other circuits, microcode, etc., that are employed to perform other functions within the microprocessor **301**. In one embodiment, the cryptography unit **316** operates in parallel to other execution units (not shown) within the execution logic **328** such as an integer unit, floating point unit, etc. One embodiment of a "unit" within the scope of the present application comprises logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to perform specified functions or specified operations. The elements employed to perform the specified functions or specified operations within a particular unit may be shared with other circuits, microcode, etc., that are employed to perform other functions or operations within the microprocessor **301**. For example, in one embodiment,

an integer unit comprises logic, circuits, devices, or micro-code (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to execute integer instructions. A floating point unit comprises logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to execute floating point instructions. The elements employed execute integer instructions within the integer unit may be shared with other circuits, microcode, etc., that are employed to execute floating point instructions within the floating point unit. In one embodiment that is compatible with the x86 architecture, the cryptography unit **316** operates in parallel with an x86 integer unit, an x86 floating point unit, an x86 MMX® unit, and an x86 SSE® unit. According to the scope of the present application, an embodiment is compatible with the x86 architecture if the embodiment can correctly execute a majority of the application programs that are designed to be executed on an x86 microprocessor. An application program is correctly executed if its expected results are obtained. Alternative x86-compatible embodiments contemplate the cryptography unit operating in parallel with a subset of the aforementioned x86 execution units. The cryptography unit **316** is coupled to store logic **317** and provides the corresponding plurality of blocks of output text **327**. The store logic **317** is also coupled to the data cache **315**, which routes the output text data **327** to system memory **321** for storage. The store logic **317** is coupled to write back logic **318**. The write back logic **318** updates registers **308-313** within the register file **307** as the prescribed cryptographic operation is accomplished. In one embodiment, micro instructions flow through each of the aforementioned logic stages **302, 303, 304, 307, 314, 316-318** in synchronization with a clock signal (not shown) so that operations can be concurrently executed in a manner substantially similar to operations performed on an assembly line.

[0044] Within the system memory **321**, an application program that requires the prescribed cryptographic operation can direct the microprocessor **301** to perform the operation via a single cryptographic instruction **322**, referred to herein for instructive purposes as an XCRYPT instruction **322**. In a CISC embodiment, the XCRYPT instruction **322** comprises an instruction that prescribes a cryptographic operation. In a RISC embodiment, the XCRYPT instruction **322** comprises a micro instruction that prescribes a cryptographic operation. In one embodiment, the XCRYPT instruction **322** utilizes a spare or otherwise unused instruction opcode within an existing instruction set architecture. In one x86-compatible embodiment, the XCRYPT instruction **322** is a 4-byte instruction comprising an x86 REP prefix (i.e., 0xF3), followed by unused x86 2-byte opcode (e.g., 0x0FA7), followed by a byte detailing a specific block cipher mode to be employed during execution of a prescribed cryptographic operation. In one embodiment, the XCRYPT instruction **322** according to the present invention can be executed at the level of system privileges afforded to application programs and can thus be programmed into a program flow of instructions that are provided to the microprocessor **301** either directly by an application program or under control of an operating system **320**. Since there is only one instruction **322** that is required to direct the microprocessor **301** to perform the prescribed cryptographic operation, it is

contemplated that accomplishment of the operation is entirely transparent to the operating system **320**.

[0045] In operation, the operating system **320** invokes an application program to execute on the microprocessor **301**. As part of the flow of instructions during execution of the application program, an XCRYPT instruction **322** is provided from memory **321** to the fetch logic **302**. Prior to execution of the XCRYPT instruction **322**, however, instructions within the program flow direct the microprocessor **301** to initialize the contents of registers **308-312** so that they point to locations **323-327** in memory **321** that contain a cryptographic control word **323**, an initial cryptographic key **324** or a key schedule **324**, an initialization vector **325** (if required), input text **326** for the operation, and output text **327**. It is required to initialize the registers **308-312** prior to executing the XCRYPT instruction **322** because the XCRYPT instruction **322** implicitly references the registers **308-312** along with an additional register **313** that contains a block count, that is the number of blocks of data within the input text area **326** to be encrypted or decrypted. Thus, the translation logic **303** retrieves the XCRYPT instruction from the fetch logic **302** and translates it into a corresponding sequence of micro instructions that directs the microprocessor **301** to perform the prescribed cryptographic operation. A first plurality of micro instructions **305-306** within the corresponding sequence of micro instructions specifically directs the cryptography unit **316** to load data provided from the load logic **314** and to begin execution of a prescribed number of cryptographic rounds to generate a corresponding block of output data and to provide the corresponding block of output data to the store logic **317** for storage in the output text area **327** of memory **321** via the data cache **315**. A second plurality of micro instructions (not shown) within the corresponding sequence of micro instructions directs other execution units (not shown) within the microprocessor **301** to perform other operations necessary to accomplish the prescribed cryptographic operation such as management of non-architectural registers (not shown) that contain temporary results and counters, update of input and output pointer registers **311-312**, update of the initialization vector pointer register **310** (if required) following encryption/decryption of a block of input text **326**, processing of pending interrupts, etc. In one embodiment, registers **308-313** are architectural registers. An architectural register **308-313** is a register that is defined within the instruction set architecture (ISA) for the particular microprocessor that is implemented.

[0046] In one embodiment, the cryptography unit **316** is divided into a plurality of stages thus allowing for pipelining of successive input text blocks **326**.

[0047] The block diagram **300** of FIG. 3 is provided to teach the necessary elements of the present invention and thus, much of the logic within a present day microprocessor **301** has been omitted from the block diagram **300** for clarity purposes. One skilled in the art will appreciate, however, that a present day microprocessor **301** comprises many stages and logic elements according to specific implementation, some of which have been aggregated herein for clarity purposes. For instance, the load logic **314** could embody an address generation stage followed by a cache interface stage, following by a cache line alignment stage. What is important to note, however, is that a complete cryptographic operation on a plurality of blocks of input text **326** is directed according to the present invention via a

single instruction **322** whose operation is otherwise transparent to considerations of the operating system **320** and whose execution is accomplished via a dedicated cryptography unit **316** that operates in parallel with and in concert with other execution units within the microprocessor **301**. The present inventors contemplate provision of alternative embodiments of the cryptography unit **316** in embodiment configurations that are analogous to provision of dedicated floating point unit hardware within a microprocessor in former years. Operation of the cryptography unit **316** and associated XCRPYT instruction **322** is entirely compatible with the concurrent operation of legacy operating systems **320** and applications, as will be described in more detail below.

[0048] Now referring to **FIG. 4**, a block diagram is provided showing one embodiment of an atomic cryptographic instruction **400** according to the present invention. The cryptographic instruction **400** includes an optional prefix field **401**, which is followed by a repeat prefix field **402**, which is followed by an opcode field **403**, which is followed by a block cipher mode field **404**. In one embodiment, contents of the fields **401-404** comport with the x86 instruction set architecture. Alternative embodiments contemplate compatibility with other instruction set architectures.

[0049] Operationally, the optional prefix **401** is employed in many instruction set architectures to enable or disable certain processing features of a host microprocessor such as directing 16-bit or 32-bit operations, directing processing or access to specific memory segments, etc. The repeat prefix **402** indicates that the cryptographic operation prescribed by the cryptographic instruction **400** is to be accomplished on a plurality of blocks of input data (i.e., plaintext or ciphertext). The repeat prefix **402** also implicitly directs a computing microprocessor to employ the contents of a plurality of architectural registers therein as pointers to locations in system memory that contain cryptographic data and parameters needed to accomplish the specified cryptographic operation. As noted above, in an x86-compatible embodiment, the value of the repeat prefix **402** is 0xF3. And, according to x86 architectural protocol, the cryptographic instruction is very similar in form to an x86 repeat string instruction such as REP.MOVS. For example, when executed by an x86-compatible microprocessor embodiment of the present invention, the repeat prefix implicitly references a block count variable that is stored in architectural register ECX, a source address pointer (pointing to the input data for the cryptographic operation) that is stored in register ESI, and a destination address pointer (pointing to the output data area in memory) that is stored in register EDI. In an x86-compatible embodiment, the present invention further extends the conventional repeat-string instruction concept to further reference a control word pointer that is stored in register EDX, a cryptographic key pointer that is stored in register EBX, and a pointer to an initialization vector (if required by prescribed cipher mode) that is stored in register EAX.

[0050] The opcode field **403** prescribes that the microprocessor accomplish a cryptographic operation as further specified within a control word stored in memory that is implicitly referenced via the control word pointer. The present invention contemplates preferred choice of the opcode value **403** as one of the spare or unused opcode

values within an existing instruction set architecture so as to preserve compatibility within a conforming microprocessor with legacy operating system and application software. For example, as noted above, an x86-compatible embodiment of the opcode field **403** employs value 0x0FA7 to direct execution of the specified cryptographic operation. The block cipher mode field **404** prescribes the particular block cipher mode to be employed during the specified cryptographic operation, as will now be discussed with reference to **FIG. 5**.

[0051] **FIG. 5** is a table **500** illustrating exemplary block cipher mode field values according to the atomic cryptographic instruction of **FIG. 4**. Value 0xC8 prescribes that the cryptographic operation be accomplished using electronic code book (ECB) mode. Value 0xD0 prescribes that the cryptographic operation be accomplished using cipher block chaining (CBC) mode. Value 0xE0 prescribes that the cryptographic operation be accomplished using cipher feedback (CFB) mode. And value 0xE8 prescribes that the cryptographic operation be accomplished using output feedback (OFB) mode. All other values of the block cipher mode field **404** are reserved. These modes are described in the aforementioned FIPS documents.

[0052] Now turning to **FIG. 6**, a block diagram is presented detailing a cryptography unit **617** within an x86-compatible microprocessor **600** according to the present invention. The microprocessor **600** includes fetch logic **601** that fetches instructions from memory (not shown) for execution. The fetch logic **601** is coupled to translation logic **602**. The translation logic **602** comprises logic, circuits, devices, or microcode (i.e., micro instructions or native instructions), or a combination of logic, circuits, devices, or microcode, or equivalent elements that are employed to translate instructions into associated sequences of micro instructions. The elements employed to perform translation within the translation logic **602** may be shared with other circuits, microcode, etc., that are employed to perform other functions within the microprocessor **600**. The translation logic **602** includes a translator **603** that is coupled to a microcode ROM **604**. Interrupt logic **626** couples to the translation logic **602** via bus **628**. A plurality of software and hardware interrupt signals **627** are processed by the interrupt logic **626** which indicates pending interrupts to the translation logic **628**. The translation logic **602** is coupled to successive stages of the microprocessor **600** including a register stage **605**, address stage **606**, load stage **607**, execute stage **608**, store stage **618**, and write back stage **619**. Each of the successive stages include logic to accomplish particular functions related to the execution of instructions that are provided by the fetch logic **601** as has been previously discussed with reference like-named elements in the microprocessor of **FIG. 3**. The x86-compatible embodiment **600** depicted in **FIG. 6** features execution logic **632** within the execute stage **608** that includes parallel execution units **610**, **612**, **614**, **616**, **617**. An integer unit **610** receives integer micro instructions for execution from micro instruction queue **609**. A floating point unit **612** receives floating point micro instructions for execution from micro instruction queue **611**. An MMX® unit **614** receives MMX micro instructions for execution from micro instruction queue **613**. An SSE® unit **616** receives SSE micro instructions for execution from micro instruction queue **615**. In the exemplary x86 embodiment shown, a cryptography unit **617** is coupled to the SSE unit **616** via a load bus **620**, a stall signal

621, and a store bus 622. The cryptography unit 617 shares the SSE unit's micro instruction queue 615. An alternative embodiment contemplates stand-alone parallel operation of the cryptography unit 617 in a manner like that of units 610, 612, and 614. The integer unit 610 is coupled an x86 EFLAGS register 624. The EFLAGS register includes an X bit 625 whose state is set to indicate whether or not cryptographic operations are currently in process. In one embodiment the X bit 625 is bit 30 of an x86 EFLAGS register 624. In addition, the integer unit 610 access a machine specific register 628 to evaluate the state of an E bit 629. The state of the E bit 629 indicates whether or not the cryptography unit 617 is present within the microprocessor 600. The integer unit 610 also accesses a D bit 631 in a feature control register 630 to enable or disable the cryptography unit 617. As with the microprocessor embodiment 301 of FIG. 3, the microprocessor 600 of FIG. 6 features elements essential to teach the present invention in the context of an x86-compatible embodiment and for clarity aggregates or omits other elements of the microprocessor. One skilled in the art will appreciate that other elements are required to complete the interface such as a data cache (not shown), bus interface unit (not shown), clock generation and distribution logic (not shown), etc.

[0053] In operation, instructions are fetched from memory (not shown) by the fetch logic 601 and are provided in synchronization with a clock signal (not shown) to the translation logic 602. The translation logic 602 translates each instruction into a corresponding sequence of micro instructions that are sequentially provided in synchronization with the clock signal to subsequent stages 605-608, 618, 619 of the microprocessor 600. Each micro instruction within a sequence of micro instructions directs execution of a sub-operation that is required to accomplish an overall operation that is prescribed by a corresponding instruction such as generation of an address by the address stage 606, addition of two operands within the integer unit 610 which have been retrieved from prescribed registers (not shown) within the register stage 605, storage of a result generated by one of the execution units 610, 612, 614, 616, 617 in memory by the store logic 618, etc. Depending upon the instruction that is being translated, the translation logic 602 will employ the translator 603 to directly generate the sequence of micro instructions, or it will fetch the sequence from the microcode ROM 604, or it will employ the translator 603 to directly generate a portion of the sequence and fetch the remaining portion of the sequence from the microcode ROM 604. The micro instructions proceed sequentially through the successive stages 605-608, 618, 619 of the microprocessor 600 in synchronization with the clock. As micro instructions reach the execute stage 608, they are routed by the execution logic 632 along with their operands (retrieved from registers within the register stage 605, or generated by logic within the address stage 606, or retrieved from a data cache by the load logic 608) to a designated execution unit 610, 612, 614, 616, 617 by placing the micro instructions in a corresponding micro instruction queue 609, 611, 613, 615. The execution units 610, 612, 614, 616, 617 execute the micro instructions and provide results to the store stage 618. In one embodiment, the micro instructions include fields indicating whether or not they can be executed in parallel with other operations.

[0054] Responsive to fetching an XCRYPT instruction as described above, the translation logic 602 generates associ-

ated micro instructions that direct logic within subsequent stages 605-608, 618, 619 of the microprocessor 600 to perform the prescribed cryptographic operation. A first plurality of the associated micro instructions are routed directly to the cryptography unit 617 and direct the unit 617 to load data provided over the load bus 620, or to load a block of input data and begin execution of a prescribed number of cryptographic rounds to produce a block of output data, or to provide a produced block of output data over the store bus 622 for storage in memory by the store logic 618. A second plurality of the associated micro instructions are routed to other execution units 610, 612, 614, 616 to perform other sub-operations that are necessary to accomplish the prescribed cryptographic operation such as testing of the E bit 629, enabling the D bit 631, setting the X bit 625 to indicate that a cryptographic operation is in process, updating registers (e.g., count register, input text pointer register, output text pointer register) within the register stage 605, processing of interrupts 627 indicated by the interrupt logic 626, etc. The associated micro instructions are ordered to provide for optimum performance of specified cryptographic operations on multiple blocks of input data by interlacing integer unit micro instructions within sequences of cryptography unit micro instructions so that integer operations can be accomplished in parallel with cryptography unit operations. Micro instructions are included in the associated micro instructions to allow for and recover from pending interrupts 627. Because all of the pointers to cryptographic parameters and data are provided within x86 architectural registers, their states are saved when interrupts are processed and the states are restored upon return from interrupts. Upon return from an interrupt, micro instructions test the state of the X bit 625 to determine if a cryptographic operation was in progress. If so, the operation is repeated on the particular block of input data that was being processed when the interrupt occurred. The associated micro instructions are ordered to allow for the pointer registers and intermediate results of a sequence of block cryptographic operations on a sequence of input text blocks to be updated prior to processing interrupts 627.

[0055] Now referring to FIG. 7, a diagram is presented illustrating fields within an exemplary micro instruction 700 for directing cryptographic sub-operations within the microprocessor of FIG. 6. The micro instruction 700 includes a micro opcode field 701, a data register field 702, and a register field 703. The micro opcode field 701 specifies a particular sub-operation to be performed and designates logic within one or more stages of the microprocessor 600 to perform the sub-operation. Specific values of the micro opcode field 701 designate that the micro instruction is directed for execution by a cryptography unit according to the present invention. In one embodiment, there are two specific values. A first value (XLOAD) designates that data is to be retrieved from a memory location whose address is specified by contents of an architectural register denoted by contents of the data register field 702. The data is to be loaded into a register within the cryptography unit that is specified by contents of the register field 703. The retrieved data (e.g., cryptographic key data, control word, input text data, initialization vector) is provided to the cryptography unit. A second value (XSTOR) of the micro opcode field 701 designates that data generated by the cryptography unit is to be stored in a memory location whose address is specified by contents of an architectural register denoted by contents of the data register field 702. In a multi-stage embodiment of

the cryptography unit, contents of the register field **703** prescribe one of a plurality of output data blocks for storage in memory. The output data block is provided by the cryptography unit in the data field **704** for access by store logic. More specific details concerning XLOAD and XSTOR micro instructions for execution by a cryptography unit according to the present invention will now be discussed with reference to **FIGS. 8 and 9**.

[0056] Turning to **FIG. 8**, a table **800** is presented depicting values of the register field **703** for an XLOAD micro instruction according to the format **700** of **FIG. 7**. As was previously discussed, a sequence of micro instructions is generated in response to translation of an XCRPYT instruction. The sequence of micro instructions comprises a first plurality of micro instructions that are directed for execution by the cryptography unit and a second plurality of micro instructions that are executed by one or more of the parallel functional units within the microprocessor other than the cryptography unit. The second plurality of micro instructions direct sub-operations such as updating of counters, temporary registers, architectural registers, testing and setting of status bits in machine specific registers, and so on. The first plurality of instructions provide key data, cryptographic parameters, and input data to the cryptography unit and direct the cryptography unit to generate key schedules (or to load key schedules that have been retrieved from memory), to load and encrypt (or decrypt) input text data, and to store output text data. An XLOAD micro instruction is provided to the cryptography unit to load control word data, to load a cryptographic key or key schedule, to load initialization vector data, to load input text data, and to load input text data and direct the cryptography unit to begin a prescribed cryptographic operation. Value **0b010** in the register field **703** of an XLOAD micro instruction directs the cryptography unit to load a control word into its internal control word register. As this micro instruction proceeds down the pipeline, an architectural control word pointer register within the register stage is accessed to obtain the address in memory where the control word is stored. Address logic translates the address into a physical address for a memory access. The load logic fetches the control word from cache and places the control word in the data field **704**, which is then passed to the cryptography unit. Likewise, register field value **0b100** directs the cryptography unit to load input text data provided in the data field **704** and, following the load, to start the prescribed cryptographic operation. Like the control word, the input data is accessed via a pointer stored in an architectural register. Value **0b101** directs that input data provided in the data field **704** be loaded into internal register 1 **IN-1**. Data loaded into **IN-1** register can be either input text data (when pipelining) or an initialization vector. Values **0b110** and **0b111** direct the cryptography unit to load lower and upper bits, respectively, of a cryptographic key or one of the keys in a user-generated key schedule. According to the present application, a user is defined as that which performs a specified function or specified operation. The user can embody an application program, an operating system, a machine, or a person. Hence, the user-generated key schedule, in one embodiment, is generated by an application program. In an alternative embodiment, the user-generated key schedule is generated by a person.

[0057] In one embodiment, register field values **0b100** and **0b101** contemplate a cryptography unit that has two

stages, whereby successive blocks of input text data can be pipelined. Hence, to pipeline two successive blocks of input data, a first XLOAD micro instruction is executed that provides a first block of input text data to **IN-1** followed by execution of a second XLOAD micro instruction that provides a second block of input text data to **IN-0** and that also directs the cryptography unit to begin performing the prescribed cryptographic operation.

[0058] If a user-generated key schedule is employed to perform the cryptographic operation, then a number of XLOAD micro instructions that correspond to the number of keys within the user-generated key schedule are routed to the cryptography unit that direct the unit to load each round key within the key schedule.

[0059] All other values of the register field **703** in an XLOAD micro instruction are reserved.

[0060] Referring to **FIG. 9**, a table **900** is presented showing values of the register field **703** for an XSTOR micro instruction according to the format **700** of **FIG. 7**. An XSTOR micro instruction is issued to the cryptography unit to direct it to provide a generated (i.e., encrypted or decrypted) output text block to store logic for storage in memory at the address provided in the address field **702**. Accordingly, translation logic according to the present invention issues an XSTOR micro instruction for a particular output text block following issuance of an XLOAD micro instruction for its corresponding input text block. Value **0b100** of the register field **703** directs the cryptography unit to provide the output text block associated with its internal output-0 **OUT-0** register to store logic for storage. Contents of **OUT-0** are associated with the input text block provided to **IN-0**. Likewise, contents of internal output-1 register, referenced by register field value **0b101**, are associated with the input text data provided to **IN-1**. Accordingly, following loading of keys and control word data, a plurality of input text blocks can be pipelined through the cryptography unit by issuing cryptographic micro instructions in the order XLOAD.**IN-1**, XLOAD.**IN-0** (XLOAD.**IN-0** directs the cryptography unit to start the cryptographic operation as well), XSTOR.**OUT-1**, XSTOR.**OUT-0**, XLOAD.**IN-1**, XLOAD.**IN-0** (starts the operation for the next two input text blocks), and so on.

[0061] Now turning to **FIG. 10**, a diagram is provided highlighting an exemplary control word format **1000** for prescribing cryptographic parameters of a cryptographic operation according to the present invention. The control word **1000** is programmed into memory by a user and its pointer is provided to an architectural register within a conforming microprocessor prior to performing cryptographic operations. Accordingly, as part of a sequence of micro instructions corresponding to a provided XCRPYT instruction, an XLOAD micro instruction is issued directing the microprocessor to read the architectural register containing the pointer, to convert the pointer into a physical memory address, to retrieve the control word **1000** from memory (cache), and to load the control word **1000** into the cryptography unit's internal control word register. The control word **1000** includes a reserved **RSVD** field **1001**, key size **KSIZE** field **1002**, an encryption/decryption **E/D** field **1003**, an intermediate result **IRSLT** field **1004**, a key generation **KGEN** field **1005**, an algorithm **ALG** field **1006**, and a round count **RCNT** field **1007**.

[0062] All values for the reserved field **1001** are reserved. Contents of the KSIZE field **1002** prescribe the size of a cryptographic key that is to be employed to accomplish encryption or decryption. In one embodiment, the KSIZE field **1002** prescribes either a 128-bit key, a 192-bit key, or a 256-bit key. The E/D field **1003** specifies whether the cryptographic operation is to be an encryption operation or a decryption operation. The KGEN field **1005** indicates if a user-generated key schedule is provided in memory or if a single cryptographic key is provided in memory. If a single cryptographic key is provided, then micro instructions are issued to the cryptography unit along with the cryptographic key directing the unit to expand the key into a key schedule according to the cryptographic algorithm that is specified by contents of the ALG field **1006**. In one embodiment, the ALG field **1006** specifies the DES algorithm, the Triple-DES algorithm, or the AES algorithm as has heretofore been discussed. Alternative embodiments contemplate other cryptographic algorithms such as the Rijndael Cipher, the Twofish Cipher, etc. Contents of the RCNT field **1007** prescribe the number of cryptographic rounds that are to be accomplished on each block of input text according to the specified algorithm. Although the standards for the above-noted algorithms prescribed a fixed number of cryptographic rounds per input text block, provision of the RCNT field **1007** allows a programmer to vary the number of rounds from that specified by the standards. In one embodiment, the programmer can specify from 0 to 15 rounds per block. Finally, contents of the IRSLT field **1004** specify whether encryption/decryption of an input text block is to be performed for the number of rounds specified in RCNT **1007** according to the standard for the cryptographic algorithm specified in ALG **1006** or whether the encryption/decryption is to be performed for the number of rounds specified in RCNT **1007** where the final round performed represents an intermediate result rather than a final result according to the algorithm specified in ALG **1006**. One skilled in the art will appreciate that many cryptographic algorithms perform the same sub-operations during each round, except for those performed in the final round. Hence, programming the IRSLT field **1004** to provide intermediate results rather than final results allows a programmer to verify intermediate steps of the implemented algorithm. For example, incremental intermediate results to verify algorithm performance can be obtained by, say, performing one round of encryption on a text block, then performing two rounds on the same text block, then three round, and so on. The capability to provide programmable rounds and intermediate results enables users to verify cryptographic performance, to trouble-shoot, and to research the utility of varying key structures and round counts.

[0063] Now referring to FIG. 11, a block diagram is presented featuring details of a cryptography unit **1100** according to the present invention. The cryptography unit **1100** includes a micro opcode register **1103** that receives cryptographic micro instructions (i.e., XLOAD and XSTOR micro instructions) via a micro instruction bus **1114**. The cryptography unit **1100** also has a control word register **1104**, an input-0 register **1105**, and input-1 register **1106**, a key-0 register **1107**, and a key-1 register **1108**. Data is provided to registers **1104-1108** via a load bus **1111** as prescribed by contents of an XLOAD micro instruction within the micro instruction register **1103**. The cryptography unit **1100** also includes block cipher logic **1101** that is

coupled to all of the registers **1103-1108** and that is also coupled to cryptographic key RAM **1102**. The block cipher logic provides a stall signal **1113** and also provides block results to an output-0 register **1109** and an output-1 register **1110**. The output registers **1109-1110** route their contents to successive stages in a conforming microprocessor via a store bus **1112**. In one embodiment, the micro instruction register **1103** is 32 bits in size and each of the remaining registers **1104-1110** are 128-bit registers.

[0064] Operationally, cryptographic micro instructions are provided sequentially to the micro instruction register **1103** along with data that is designated for the control word register **1104**, or one of the input registers **1105-1106**, or one of the key registers **1107-1108**. In the embodiment discussed with reference to FIGS. 8 and 9, a control word is first loaded via an XLOAD micro instruction to the control word register **1104**. Then the cryptographic key or key schedule is loaded via successive XLOAD micro instructions. If a 128-bit cryptographic key is to be loaded, then an XLOAD micro instruction is provided designating register KEY-**01107**. If a cryptographic key greater than 128 bits is to be loaded, then an XLOAD micro instruction is provided designating register KEY-**01107** is provided along with an XLOAD micro instruction designating register KEY-**11108**. If a user-generated key schedule is to be loaded, then successive XLOAD micro instructions designating register KEY-**01107** are provided. Each of the keys from the key schedule that are loaded are placed, in order, in the key RAM **1102** for use during their corresponding cryptographic round. Following this, input text data (if an initialization vector is not required) is loaded to IN-1 register **1106**. If an initialization vector is required, then it is loaded into IN-1 register **1106** via an XLOAD micro instruction. An XLOAD micro instruction to IN-0 register **1105** directs the cryptography unit to load input text data to IN-0 register **1105** and to begin performing cryptographic rounds on input text data in register IN-0 **1105** using the initialization vector in IN-1 or in both input registers **1105-1106** (if input data is being pipelined) according to the parameters provided via contents of the control word register **1104**. Upon receipt of an XLOAD micro instruction designating IN-0 **1105**, the block cipher logic starts performing the cryptographic operation prescribed by contents of the control word. If expansion of a single cryptographic key is required, then the block cipher logic generates each of the keys in the key schedule and stores them in the key RAM **1102**. Regardless of whether the block cipher logic **1101** generates a key schedule or whether the key schedule is loaded from memory, the key for the first round is cached within the block cipher logic **1101** so that the first block cryptographic round can proceed without having to access the key RAM **1102**. Once initiated, the block cipher logic continues executing the prescribed cryptographic operation on one or more blocks of input text until the operation is completed, successively fetching round keys from the key RAM **1102** as required by the cryptographic algorithm which is employed. The cryptography unit **1100** performs a specified block cryptographic operation on designated blocks of input text. Successive blocks of input text are encrypted or decrypted through the execution of corresponding successive XLOAD and XSTOR micro instructions. When an XSTOR micro instruction is executed, if the prescribed output data (i.e., OUT-0 or OUT-1) has not yet completed generation, then the block cipher logic asserts the stall signal **1113**. Once the output data has been generated

and placed into a corresponding output register **1109-1110**, then the contents of that register **1109-1110** are transferred to the store bus **1112**.

[0065] Now turning to **FIG. 12**, a block diagram is provided illustrating an embodiment of block cipher logic **1200** according to the present invention for performing cryptographic operations in accordance with the Advanced Encryption Standard (AES). The block cipher logic **1200** includes a round engine **1220** that is coupled to a round engine controller **1210** via buses **1211-1214** and buses **1216-1218**. The round engine controller **1210** accesses a micro instruction register **1201**, control word register **1202**, KEY-0 register **1203**, and KEY-1 register **1204** to access key data, micro instructions, and parameters of the directed cryptographic operation. Contents of input registers **1205-1206** are provided to the round engine **1220** and the round engine **1220** provides corresponding output text to output registers **1207-1208**. The output registers **1207-1208** are also coupled to the round engine controller **1210** via buses **1216-1217** to enable the round engine controller access to the results of each successive cryptographic round, which is provided to the round engine **1220** for a next cryptographic round via bus NEXTIN **1218**. Cryptographic keys from key RAM (not shown) are accessed via bus **1215**. Signal ENC/DEC **1211** directs the round engine to employ sub-operations for performing either encryption (e.g., S-Box) or decryption (e.g., Inverse S-Box). Contents of bus RNDCON **1212** direct the round engine **1220** to perform either a first AES round, an intermediate AES round, or a final AES round. Signal GENKEY **1214** is asserted to direct the round engine **1220** to generate a key schedule according to the key provided via bus **1213**. Key bus **1213** is also employed to provide each round key to the round engine **1220** when its corresponding round is executed.

[0066] The round engine **1220** includes first key XOR logic **1221** that is coupled to a first register REG-0**1222**. The first register **1222** is coupled to S-Box logic **1223**, which is coupled to Shift Row logic **1224**. The Shift Row logic **1224** is coupled to a second register REG-1**1225**. The second register **1225** is coupled to Mix Column logic **1226**, which is coupled to a third register REG-2**1227**. The first key logic **1221**, S-Box logic **1223**, Shift Row logic **1224**, and Mix Column logic **1226** are configured to perform like-named sub-operations on input text data as is specified in the AES FIPS standard discussed above. The Mix Columns logic **1226** is additionally configured to perform AES XOR functions on input data during intermediate rounds as required using round keys provided via the key bus **1213**. The first key logic **1221**, S-Box logic **1223**, Shift Row logic **1224**, and Mix Column logic **1226** are also configured to perform their corresponding inverse AES sub-operations during decryption as directed via the state of ENC/DEC **1211**. One skilled in the art will appreciate that intermediate round data is fed back to the round engine **1220** according to which particular block encryption mode is prescribed via contents of the control word register **1202**. Initialization vector data (if required) is provided to the round engine **1220** via bus NEXTIN **1218**.

[0067] In the embodiment shown in **FIG. 12**, the round engine is divided into two stages: a first stage between REG-0**1222** and REG-1**1225** and a second stage between REG-1**1225** and REG-2**1227**. Intermediate round data is pipelined between stages in synchronization with a clock

signal (not shown). When a cryptographic operation is completed on a block of input data, the associated output data is placed into a corresponding output register **1207-1208**. Execution of an XSTOR micro instruction causes contents of a designated output register **1207-1208** to be provided to a store bus (not shown).

[0068] Although the present invention and its objects, features, and advantages have been described in detail, other embodiments are encompassed by the invention as well. For example, the present invention has been discussed at length according to embodiments that are compatible with the x86 architecture. However, the discussions have been provided in such a manner because the x86 architecture is widely comprehended and thus provides a sufficient vehicle to teach the present invention. The present invention nevertheless comprehends embodiments that comport with other instruction set architectures such as PowerPC®, MIPS®, and the like, in addition to entirely new instruction set architectures.

[0069] The present invention moreover comprehends execution of cryptographic operations within elements of a computing system other than the microprocessor itself. For example, the cryptographic instruction according to the present invention could easily be applied within an embodiment of a cryptography unit that is not part of the same integrated circuit as a microprocessor that exercises as part of the computer system. It is anticipated that such embodiments of the present invention are in order for incorporation into a chipset surrounding a microprocessor (e.g., north bridge, south bridge) or as a processor dedicated for performing cryptographic operations where the cryptographic instruction is handed off to the processor from a host microprocessor. It is contemplated that the present invention applies to embedded controllers, industrial controllers, signal processors, array processors, and any like devices that are employed to process data. The present invention also comprehends an embodiment comprising only those elements essential to performing cryptographic operations as described herein. A device embodied as such would indeed provide a low-cost, low-power alternative for performing cryptographic operations only, say, as an encryption/decryption processor within a communications system. For clarity, the present inventors refer to these alternative processing elements as noted above as processors.

[0070] In addition, although the present invention has been described in terms of 128-bit blocks, it is considered that various different block sizes can be employed by merely changing the size of registers that carry input data, output data, keys, and control words.

[0071] Furthermore, although DES, Triple-DES, and AES have been prominently featured in this application, the present inventors note that the invention described herein encompasses lesser known block cryptography algorithms as well such as the MARS cipher, the Rijndael cipher, the Twofish cipher, the Blowfish Cipher, the Serpent Cipher, and the RC6 cipher. What is sufficient to comprehend is that the present invention provides dedicated block cryptography apparatus and supporting methodology within a microprocessor where atomic block cryptographic operations can be invoked via execution of a single instruction.

[0072] Also, although the present invention has been featured herein in terms of block cryptographic algorithms and associated techniques for performing block crypto-

graphic functions, it is noted that the present invention entirely comprehends other forms of cryptography other than block cryptography. It is sufficient to observe that a single instruction is provided whereby a user can direct a conforming microprocessor to perform a cryptographic operation such as encryption or decryption, where the microprocessor includes a dedicated cryptography unit that is directed towards accomplishment of cryptographic functions prescribed by the instruction.

[0073] Moreover, the discussion of a round engine herein provides for a 2-stage apparatus that can pipeline two blocks of input data, the present inventors note that additional embodiments contemplate more than two stages. It is anticipated that stage division to support pipelining of more input data blocks will evolve in concert with dividing of other stages within a computing microprocessor.

[0074] Finally, although the present invention has been specifically discussed as a single cryptography unit that supports a plurality of block cryptographic algorithms, the invention also comprehends provision of multiple cryptographic units operatively coupled in parallel with other execution units in a conforming microprocessor where each of the multiple cryptographic units is configured to perform a specific block cryptographic algorithm. For example, a first unit is configured for AES, a second for DES, and so on.

[0075] Those skilled in the art should appreciate that they can readily use the disclosed conception and specific embodiments as a basis for designing or modifying other structures for carrying out the same purposes of the present invention, and that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. An apparatus in a microprocessor, for accomplishing cryptographic operations, comprising:

translation logic, configured to receive a cryptographic instruction from a source therefrom, wherein said cryptographic instruction prescribes one of the cryptographic operations, and configured to translate said cryptographic instruction into a sequence of micro instructions specifying sub-operations required to accomplish said one of the cryptographic operations; and

execution logic, operatively coupled to said translation logic, configured to receive said sequence of micro instructions, and configured to perform said sub-operations.

2. The apparatus as recited in claim 1, wherein said one of the cryptographic operations is accomplished at the level of system privileges afforded to application programs.

3. The apparatus as recited in claim 1, wherein said one of the cryptographic operations comprises:

an encryption operation, said encryption operation comprising encryption of a plurality of plaintext blocks to generate a corresponding plurality of ciphertext blocks.

4. The apparatus as recited in claim 1, wherein said one of the cryptographic operations comprises:

a decryption operation, said decryption operation comprising decryption of a plurality of ciphertext blocks to generate a corresponding plurality of plaintext blocks.

5. The apparatus as recited in claim 1, wherein said one of the cryptographic operations is accomplished according to the Advanced Encryption Standard (AES) algorithm.

6. The apparatus as recited in claim 1, wherein said cryptographic instruction prescribes a block cipher mode to be employed in accomplishing said one of the cryptographic operations.

7. The apparatus as recited in claim 6, wherein said block cipher mode comprises electronic code book (ECB) mode.

8. The apparatus as recited in claim 6, wherein said block cipher mode comprises cipher block chaining (CBC) mode.

9. The apparatus as recited in claim 6, wherein said block cipher mode comprises cipher feedback mode (CFB) mode.

10. The apparatus as recited in claim 6, wherein said block cipher mode comprises output feedback (OFB) mode.

11. The apparatus as recited in claim 1, wherein said cryptographic instruction prescribes that said one of the cryptographic operations be accomplished on a plurality of text blocks.

12. The apparatus as recited in claim 1, wherein said cryptographic instruction is prescribed according to the x86 instruction format.

13. The apparatus as recited in claim 1, wherein said cryptographic instruction implicitly references a plurality of registers within the microprocessor.

14. The apparatus as recited in claim 13, wherein said plurality of registers comprises:

a first register, wherein contents of said first register comprise a first pointer to a first memory address, said first memory address specifying a first location in memory for access of a plurality of input text blocks upon which said one of the cryptographic operations is to be accomplished.

15. The apparatus as recited in claim 13, wherein said plurality of registers comprises:

a second register, wherein contents of said second register comprise a second pointer to a second memory address, said second memory address specifying a second location in said memory for storage of a corresponding plurality of output text blocks, said corresponding plurality of output text blocks being generated as a result of accomplishing said one of the cryptographic operations upon a plurality of input text blocks.

16. The apparatus as recited in claim 13, wherein said plurality of registers comprises:

a third register, wherein contents of said third register indicate a number of text blocks within a plurality of input text blocks.

17. The apparatus as recited in claim 13, wherein said plurality of registers comprises:

a fourth register, wherein contents of said fourth register comprise a third pointer to a third memory address, said third memory address specifying a third location in memory for access of cryptographic key data for use in accomplishing said one of the cryptographic operations.

18. The apparatus as recited in claim 17, wherein said cryptographic key data comprises a cryptographic key.

19. The apparatus as recited in claim 17, wherein said cryptographic key data comprises a cryptographic key schedule.

20. The apparatus as recited in claim 13, wherein said plurality of registers comprises:

a fifth register, wherein contents of said fifth register comprise a fourth pointer to a fourth memory address, said fourth memory address specifying a fourth location in memory for access of an initialization vector for use in accomplishing said one of the cryptographic operations.

21. The apparatus as recited in claim 13, wherein said plurality of registers comprises:

a sixth register, wherein contents of said sixth register comprise a fifth pointer to a fifth memory address, said fifth memory address specifying a fifth location in memory for access of a control word for use in accomplishing said one of the cryptographic operations, wherein said control word prescribes cryptographic parameters for said one of the cryptographic operations.

22. The apparatus as recited in claim 21, wherein said control word comprises:

an encryption/decryption field, configured to prescribe whether said one of the cryptographic operations is an encryption operation or a decryption operation.

23. The apparatus as recited in claim 1, wherein said execution logic comprises:

a cryptography unit, configured to receive a first plurality of said sequence of micro instructions, and configured to execute a plurality of cryptographic rounds on each of a plurality of input text blocks to generate a corresponding each of a plurality of output text blocks, wherein said plurality of cryptographic rounds are prescribed by a control word that is provided to said cryptography unit.

24. The apparatus as recited in claim 23, wherein said cryptography unit comprises:

block cipher logic, configured to perform said plurality of cryptographic rounds on said each of a plurality of input text blocks according to said one of the cryptographic operations to produce said corresponding each of a plurality of output text blocks; and

key RAM, operatively coupled to said block cipher logic, configured to store a key schedule, said key schedule comprising a plurality of round keys, each corresponding to each of said plurality of cryptographic rounds, and configured to provide said each of said plurality of round keys to said block cipher logic for performance of said each of said plurality of cryptographic rounds.

25. The apparatus as recited in claim 23, wherein said block cipher logic is divided into two or more stages, whereby said plurality of cryptographic rounds are simultaneously performed on two or more input text blocks.

26. The apparatus as recited in claim 23, wherein said execution logic further comprises:

an integer unit, coupled in parallel with said cryptography unit, configured to receive a second plurality of said sequence of micro instructions, and configured to

execute a plurality of integer operations that are required to accomplish said one of the cryptographic operations.

27. The apparatus as recited in claim 23, wherein said sequence of micro instructions comprises:

a first micro instruction, configured to direct said cryptography unit to load one of said each of said plurality of input text blocks and to perform said plurality of cryptographic rounds.

28. A microprocessor apparatus, for performing cryptographic operations, comprising:

a cryptographic instruction, received by a microprocessor as part of an instruction flow executing on said microprocessor, wherein said cryptographic instruction prescribes one of the cryptographic operations; and

translation logic, configured to translate said cryptographic instruction into associated micro instructions that specify sub-operations required to accomplish said one of the cryptographic operations

29. The microprocessor apparatus as recited in claim 28, wherein said one of the cryptographic operations comprises:

an encryption operation, said encryption operation comprising encryption of a plurality of plaintext blocks to generate a corresponding plurality of ciphertext blocks.

30. The microprocessor apparatus as recited in claim 28, wherein said one of the cryptographic operations comprises:

a decryption operation, said decryption operation comprising decryption of a plurality of ciphertext blocks to generate a corresponding plurality of plaintext blocks.

31. The microprocessor apparatus as recited in claim 28, wherein said one of the cryptographic operations is accomplished according to the Advanced Encryption Standard (AES) algorithm.

32. The microprocessor apparatus as recited in claim 28, wherein said cryptographic instruction prescribes a block cipher mode to be employed in accomplishing said one of the cryptographic operations.

33. The microprocessor apparatus as recited in claim 32, wherein said block cipher mode comprises electronic code book (ECB) mode.

34. The microprocessor apparatus as recited in claim 32, wherein said block cipher mode comprises cipher block chaining (CBC) mode.

35. The microprocessor apparatus as recited in claim 32, wherein said block cipher mode comprises cipher feedback mode (CFB) mode.

36. The microprocessor apparatus as recited in claim 32, wherein said block cipher mode comprises output feedback (OFB) mode.

37. The microprocessor apparatus as recited in claim 28, wherein said cryptographic instruction prescribes that said one of the cryptographic operations be accomplished on a plurality of text blocks.

38. The microprocessor apparatus as recited in claim 28, wherein said cryptographic instruction is prescribed according to the x86 instruction format.

39. The microprocessor apparatus as recited in claim 28, wherein said cryptographic instruction implicitly references a plurality of registers within said microprocessor.

40. The microprocessor apparatus as recited in claim 39, wherein said plurality of registers comprises:

a first register, wherein contents of said first register comprise a first pointer to a first memory address, said first memory address specifying a first location in memory for access of a plurality of input text blocks upon which said one of the cryptographic operations is to be accomplished.

41. The microprocessor apparatus as recited in claim 39, wherein said plurality of registers comprises:

a second register, wherein contents of said second register comprise a second pointer to a second memory address, said second memory address specifying a second location in said memory for storage of a corresponding plurality of output text blocks, said corresponding plurality of output text blocks being generated as a result of accomplishing said one of the cryptographic operations upon a plurality of input text blocks.

42. The microprocessor apparatus as recited in claim 39, wherein said plurality of registers comprises:

a third register, wherein contents of said third register indicate a number of text blocks within a plurality of input text blocks.

43. The microprocessor apparatus as recited in claim 39, wherein said plurality of registers comprises:

a fourth register, wherein contents of said fourth register comprise a third pointer to a third memory address, said third memory address specifying a third location in memory for access of cryptographic key data for use in accomplishing said one of the cryptographic operations.

44. The microprocessor apparatus as recited in claim 43, wherein said cryptographic key data comprises a cryptographic key.

45. The microprocessor apparatus as recited in claim 43, wherein said cryptographic key data comprises a cryptographic key schedule.

46. The microprocessor apparatus as recited in claim 39, wherein said plurality of registers comprises:

a fifth register, wherein contents of said fifth register comprise a fourth pointer to a fourth memory address, said fourth memory address specifying a fourth location in memory for access of an initialization vector for use in accomplishing said one of the cryptographic operations.

47. The microprocessor apparatus as recited in claim 39, wherein said plurality of registers comprises:

a sixth register, wherein contents of said sixth register comprise a fifth pointer to a fifth memory address, said fifth memory address specifying a fifth location in memory for access of a control word for use in accomplishing said one of the cryptographic operations, wherein said control word prescribes cryptographic parameters for said one of the cryptographic operations.

48. The microprocessor apparatus as recited in claim 47, wherein said control word comprises:

an encryption/decryption field, configured to prescribe whether said one of the cryptographic operations is an encryption operation or a decryption operation.

49. The microprocessor apparatus as recited in claim 28, further comprising:

execution logic, operatively coupled to said translation logic, configured to receive said associated micro instructions, and configured to perform said sub-operations.

50. The microprocessor apparatus as recited in claim 49, wherein said execution logic comprises:

a cryptography unit, configured to receive a first plurality of said associated micro instructions, and configured to execute a plurality of cryptographic rounds on each of a plurality of input text blocks to generate a corresponding each of a plurality of output text blocks, wherein said plurality of cryptographic rounds are prescribed by a control word that is provided to said cryptography unit.

51. The microprocessor apparatus as recited in claim 50, wherein said cryptography unit comprises:

block cipher logic, configured to perform said plurality of cryptographic rounds on said each of a plurality of input text blocks according to said one of the block cryptographic operations to produce said corresponding each of a plurality of output text blocks; and

key RAM, operatively coupled to said block cipher logic, configured to store a key schedule, said key schedule comprising a plurality of round keys, each corresponding to each of said plurality of cryptographic rounds, and configured to provide said each of said plurality of round keys to said block cipher logic for performance of said each of said plurality of cryptographic rounds.

52. The microprocessor apparatus as recited in claim 51, wherein said block cipher logic is divided into two or more stages, whereby said plurality of cryptographic rounds are simultaneously performed on two or more input text blocks.

53. The microprocessor apparatus as recited in claim 50, wherein said execution logic further comprises:

an integer unit, coupled in parallel with said cryptography unit, configured to receive a second plurality of said associated micro instructions, and configured to execute a plurality of integer operations that are required to accomplish said one of the cryptographic operations.

54. The microprocessor apparatus as recited in claim 50, wherein said associated micro instructions comprise:

a first micro instruction, configured to direct said cryptography unit to load one of said each of said plurality of input text blocks and to perform said plurality of cryptographic rounds.

55. The microprocessor apparatus as recited in claim 28, wherein said application program executes on said microprocessor at the level of system privileges afforded to application programs.

56. An apparatus for performing cryptographic operations, comprising:

a cryptographic instruction, received by logic within a processor, wherein said cryptographic instruction prescribes one of the cryptographic operations; and

execution logic, coupled to said logic, configured to perform said one of the cryptographic operations.

57. The apparatus as recited in claim 56, wherein said one of the cryptographic operations comprises:

an encryption operation, said encryption operation comprising encryption of a plurality of plaintext blocks to generate a corresponding plurality of ciphertext blocks.

58. The apparatus as recited in claim 56, wherein said one of the cryptographic operations comprises:

a decryption operation, said decryption operation comprising decryption of a plurality of ciphertext blocks to generate a corresponding plurality of plaintext blocks.

59. The apparatus as recited in claim 56, wherein said one of the cryptographic operations is accomplished according to the Advanced Encryption Standard (AES) algorithm.

60. The apparatus as recited in claim 56, wherein said cryptographic instruction prescribes a block cipher mode to be employed in accomplishing said one of the cryptographic operations.

61. The apparatus as recited in claim 60, wherein said block cipher mode comprises electronic code book (ECB) mode.

62. The apparatus as recited in claim 60, wherein said block cipher mode comprises cipher block chaining (CBC) mode.

63. The apparatus as recited in claim 60, wherein said block cipher mode comprises cipher feedback mode (CFB) mode.

64. The apparatus as recited in claim 60, wherein said block cipher mode comprises output feedback (OFB) mode.

65. The apparatus as recited in claim 60, wherein said cryptographic instruction prescribes that said one of the cryptographic operations be accomplished on a plurality of text blocks.

66. The apparatus as recited in claim 60, wherein said cryptographic instruction is prescribed according to the x86 instruction format.

67. The apparatus as recited in claim 56, wherein said cryptographic instruction implicitly references a plurality of registers within said processor.

68. The apparatus as recited in claim 67, wherein said plurality of registers comprises:

a first register, wherein contents of said first register comprise a first pointer to a first memory address, said first memory address specifying a first location in memory for access of a plurality of input text blocks upon which said one of the cryptographic operations is to be accomplished.

69. The apparatus as recited in claim 67, wherein said plurality of registers comprises:

a second register, wherein contents of said second register comprise a second pointer to a second memory address, said second memory address specifying a second location in said memory for storage of a corresponding plurality of output text blocks, said corresponding plurality of output text blocks being generated as a result of accomplishing said one of the cryptographic operations upon a plurality of input text blocks.

70. The apparatus as recited in claim 67, wherein said plurality of registers comprises:

a third register, wherein contents of said third register indicate a number of text blocks within a plurality of input text blocks.

71. The apparatus as recited in claim 67, wherein said plurality of registers comprises:

a fourth register, wherein contents of said fourth register comprise a third pointer to a third memory address, said third memory address specifying a third location in memory for access of cryptographic key data for use in accomplishing said one of the cryptographic operations.

72. The apparatus as recited in claim 71, wherein said cryptographic key data comprises a cryptographic key.

73. The apparatus as recited in claim 71, wherein said cryptographic key data comprises a cryptographic key schedule.

74. The apparatus as recited in claim 67, wherein said plurality of registers comprises:

a fifth register, wherein contents of said fifth register comprise a fourth pointer to a fourth memory address, said fourth memory address specifying a fourth location in memory for access of an initialization vector for use in accomplishing said one of the cryptographic operations.

75. The apparatus as recited in claim 67, wherein said plurality of registers comprises:

a sixth register, wherein contents of said sixth register comprise a fifth pointer to a fifth memory address, said fifth memory address specifying a fifth location in memory for access of a control word for use in accomplishing said one of the cryptographic operations, wherein said control word prescribes cryptographic parameters for said one of the cryptographic operations.

76. The apparatus as recited in claim 75, wherein said control word comprises:

an encryption/decryption field, configured to prescribe whether said one of the cryptographic operations is an encryption operation or a decryption operation.

77. The apparatus as recited in claim 56, further comprising:

translation logic, configured to translate said cryptographic instruction into associated micro instructions that specify sub-operations required to accomplish said one of the cryptographic operations.

78. The apparatus as recited in claim 77, wherein said execution logic comprises:

a cryptography unit, configured to receive a first plurality of said associated micro instructions, and configured to execute a plurality of cryptographic rounds on each of a plurality of input text blocks to generate a corresponding each of a plurality of output text blocks, wherein said plurality of cryptographic rounds are prescribed by a control word that is provided to said cryptography unit.

79. The apparatus as recited in claim 78, wherein said cryptography unit comprises:

block cipher logic, configured to perform said plurality of cryptographic rounds on said each of a plurality of input text blocks according to said one of the block cryptographic operations to produce said corresponding each of a plurality of output text blocks; and

key RAM, operatively coupled to said block cipher logic, configured to store a key schedule, said key schedule comprising a plurality of round keys, each corresponding to each of said plurality of cryptographic rounds,

and configured to provide said each of said plurality of round keys to said block cipher logic for performance of said each of said plurality of cryptographic rounds.

80. The apparatus as recited in claim 79, wherein said block cipher logic is divided into two or more stages, whereby said plurality of cryptographic rounds are simultaneously performed on two or more input text blocks.

81. The apparatus as recited in claim 78, wherein said execution logic further comprises:

an integer unit, coupled in parallel with said cryptography unit, configured to receive a second plurality of said associated micro instructions, and configured to execute a plurality of integer operations that are required to accomplish said one of the cryptographic operations.

82. The apparatus as recited in claim 78, wherein said associated micro instructions comprise:

a first micro instruction, configured to direct said cryptography unit to load one of said each of said plurality of input text blocks and to perform said plurality of cryptographic rounds.

83. The apparatus as recited in claim 56, wherein said one of the cryptographic operations is accomplished at the privilege level afforded to application programs.

84. A method for performing cryptographic operations in a processor, the method comprising:

receiving a cryptographic instruction, wherein the cryptographic instruction prescribes one of the cryptographic operations; and

executing the one of the cryptographic operations.

85. The method as recited in claim 84, wherein said receiving comprises:

prescribing an encryption operation as the one of the cryptographic operations, wherein the encryption operation comprises encryption of a plurality of plaintext blocks to generate a corresponding plurality of ciphertext blocks.

86. The method as recited in claim 84, wherein said receiving comprises:

prescribing a decryption operation as the one of the cryptographic operations, wherein the decryption operation comprises decryption of a plurality of ciphertext blocks to generate a corresponding plurality of plaintext blocks.

87. The method as recited in claim 84, wherein said executing comprises:

accomplishing the one of the cryptographic operations according to the Advanced Encryption Standard (AES) algorithm.

88. The method as recited in claim 84, wherein said receiving comprises:

specifying, within the cryptographic instruction, a block cipher mode to be employed in accomplishing the one of the cryptographic operations.

89. The method as recited in claim 88, wherein the block cipher mode comprises electronic code book (ECB) mode.

90. The method as recited in claim 88, wherein the block cipher mode comprises cipher block chaining (CBC) mode.

91. The method as recited in claim 88, wherein the block cipher mode comprises cipher feedback mode (CFB) mode.

92. The method as recited in claim 88, wherein the block cipher mode comprises output feedback (OFB) mode.

93. The method as recited in claim 84, wherein said receiving comprises:

specifying, within the cryptographic instruction, that the one of the cryptographic operations is to be accomplished on a plurality of text blocks.

94. The method as recited in claim 84, wherein said receiving comprises:

prescribing the block cryptographic instruction according to the x86 instruction format.

95. The method as recited in claim 84, wherein said receiving comprises:

implicitly referencing a plurality of registers within the processor.

96. The method as recited in claim 95, wherein said implicitly referencing comprises:

first referencing a first register, wherein contents of the first register comprise a first pointer to a first memory address, the first memory address specifying a first location in memory for access of a plurality of input text blocks upon which the one of the cryptographic operations is to be accomplished.

97. The method as recited in claim 95, wherein said implicitly referencing comprises:

second referencing a second register, wherein contents of the second register comprise a second pointer to a second memory address, the second memory address specifying a second location in the memory for storage of a corresponding plurality of output text blocks, the corresponding plurality of output text blocks being generated as a result of said executing the one of the cryptographic operations upon a plurality of input text blocks.

98. The method as recited in claim 95, wherein said implicitly referencing comprises:

third referencing a third register, wherein contents of the third register indicate a number of text blocks within a plurality of input text blocks.

99. The method as recited in claim 95, wherein said implicitly referencing comprises:

fourth referencing a fourth register, wherein contents of the fourth register comprise a third pointer to a third memory address, the third memory address specifying a third location in memory for access of cryptographic key data for use in said executing the one of the cryptographic operations.

100. The method as recited in claim 99, wherein the cryptographic key data comprises a cryptographic key.

101. The method as recited in claim 99, wherein the cryptographic key data comprises a cryptographic key schedule.

102. The method as recited in claim 95, wherein said implicitly referencing comprises:

fifth referencing a fifth register, wherein contents of the fifth register comprise a fourth pointer to a fourth memory address, the fourth memory address specifying a fourth location in memory for access of an initialization vector for use in said executing the one of the cryptographic operations.

103. The method as recited in claim 95, wherein said implicitly referencing comprises:

sixth referencing a sixth register, wherein contents of the sixth register comprise a fifth pointer to a fifth memory address, the fifth memory address specifying a fifth location in memory for access of a control word for use in said executing the one of the cryptographic operations, said fifth referencing comprising:

prescribing, within the control word,

cryptographic parameters for the one of the cryptographic operation.

104. The method as recited in claim 103, wherein said prescribing comprises:

indicating, via an encryption/decryption field within the control word, whether the one of the cryptographic operations is an encryption operation or a decryption operation.

105. The method as recited in claim 84, further comprising:

translating the cryptographic instruction into a sequence of micro instructions that specify sub-operations to be performed as part of said executing.

106. The method as recited in claim 84, wherein said executing comprises:

first routing a first plurality of the sequence of micro instructions to a cryptography unit; and

within the cryptography unit, first accomplishing a plurality of cryptographic rounds on each of a plurality of input text blocks to generate a corresponding each of a plurality of output text blocks, wherein the plurality of

cryptographic rounds are prescribed by a control word that is provided to the cryptography unit.

107. The method as recited in claim 106, wherein said first accomplishing comprises:

storing a key schedule within the cryptography unit, the key schedule comprising a plurality of round keys, each corresponding to each of a plurality of cryptographic rounds; and

using each of the plurality of round keys to for performance of the each of the plurality of cryptographic rounds.

108. The method as recited in claim 106, wherein said executing further comprises:

second routing a second plurality of the sequence of micro instructions to an integer unit that is coupled in parallel with the cryptography unit;

and

within the integer unit, second accomplishing a plurality of integer operations that are required for said executing the one of the cryptographic operations.

109. The method as recited in claim 105, wherein said translating comprises:

generating a first micro instruction that directs the cryptography unit to load one of the each of the plurality of input text blocks and to perform the plurality of cryptographic rounds.

110. The method as recited in claim 81, wherein said executing is accomplished at the privilege level afforded to application programs.

* * * * *