



US011606981B2

(12) **United States Patent**
Verleur et al.

(10) **Patent No.: US 11,606,981 B2**
(45) **Date of Patent: *Mar. 21, 2023**

(54) **VAPORIZER**

(58) **Field of Classification Search**

None

See application file for complete search history.

(71) Applicant: **VMR Products LLC**, San Francisco, CA (US)

(72) Inventors: **Jan Andries Verleur**, Miami, FL (US); **Dan Recio**, Miami Beach, FL (US); **Yifeng Lu**, Miami, FL (US); **Yinjun Zhang**, Miami, FL (US); **Arturo Fajardo**, Miami, FL (US); **Hans Verleur**, El Dorado, CA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,085,145 A 4/1963 Wray, Jr.

3,918,451 A 11/1975 Steil

(Continued)

(73) Assignee: **VMR Products LLC**, San Francisco, CA (US)

FOREIGN PATENT DOCUMENTS

AU 2014208287 B2 12/2016

AU 2017202891 B2 5/2019

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 18 days.

This patent is subject to a terminal disclaimer.

OTHER PUBLICATIONS

Uptoyou Fromeme, "Newest Elips CCV Pure Flat Shaped Rechargeable Double Electronic Cigarettes E-Cigarette Set," YouTube Video published on Sep. 11, 2013, <https://www.youtube.com/watch?v=ZkQe9xztu44> (year 2013).

(Continued)

(21) Appl. No.: **17/095,567**

(22) Filed: **Nov. 11, 2020**

(65) **Prior Publication Data**

US 2021/0120871 A1 Apr. 29, 2021

Related U.S. Application Data

(63) Continuation of application No. 14/201,267, filed on Mar. 7, 2014, now Pat. No. 10,980,273, which is a (Continued)

Primary Examiner — Eric Yaary

(74) *Attorney, Agent, or Firm* — Mintz Levin Cohn Ferris Glovsky and Popeo, P.C.

(51) **Int. Cl.**
A24F 47/00 (2020.01)
A24F 40/90 (2020.01)

(Continued)


(52) **U.S. Cl.**
CPC **A24F 40/90** (2020.01); **A24F 40/00** (2020.01); **A24F 40/40** (2020.01); **A24F 40/42** (2020.01);

(Continued)

(57) **ABSTRACT**

Vaporizer and/or electronic cigarette chargers useful for the recharging of rechargeable vaporizer or electronic cigarette power supplies such as batteries, compatible vaporizers and/or electronic cigarettes, their components, charging contacts, methods of their use and kits containing such chargers are disclosed.

18 Claims, 18 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 14/196,729, filed on Mar. 4, 2014, now Pat. No. 10,039,321.
- (60) Provisional application No. 61/937,851, filed on Feb. 10, 2014, provisional application No. 61/903,344, filed on Nov. 12, 2013.

(51) Int. Cl.

A61M 15/06 (2006.01)
A61M 11/04 (2006.01)
H02J 7/00 (2006.01)
A24F 40/40 (2020.01)
A24F 40/00 (2020.01)
A24F 40/44 (2020.01)
A24F 40/42 (2020.01)
A24F 40/50 (2020.01)
A61M 15/00 (2006.01)
A24F 40/10 (2020.01)
A24F 40/20 (2020.01)
A24F 40/53 (2020.01)

(52) U.S. Cl.

CPC *A24F 40/44* (2020.01); *A24F 40/50* (2020.01); *A61M 11/042* (2014.02); *A61M 15/06* (2013.01); *H02J 7/00* (2013.01); *H02J 7/0042* (2013.01); *A24F 40/10* (2020.01); *A24F 40/20* (2020.01); *A24F 40/53* (2020.01); *A61M 15/0021* (2014.02); *A61M 2205/07* (2013.01); *A61M 2205/332* (2013.01); *A61M 2205/3368* (2013.01); *A61M 2205/3633* (2013.01); *A61M 2205/3653* (2013.01); *A61M 2205/502* (2013.01); *A61M 2205/584* (2013.01); *A61M 2205/6027* (2013.01); *A61M 2205/6081* (2013.01); *A61M 2205/8206* (2013.01); *A61M 2205/8237* (2013.01); *A61M 2206/20* (2013.01); *A61M 2209/06* (2013.01); *H02J 7/0048* (2020.01)

(56) References Cited**U.S. PATENT DOCUMENTS**

3,934,117 A 1/1976 Schladitz
 4,171,000 A 10/1979 Uhle
 4,745,705 A 5/1988 Yamamoto et al.
 4,771,796 A 9/1988 Myer
 4,793,365 A 12/1988 Sensabaugh, Jr. et al.
 4,811,731 A 3/1989 Newell et al.
 4,848,374 A 7/1989 Chard et al.
 4,941,236 A 7/1990 Sherman et al.
 4,947,874 A 8/1990 Brooks et al.
 4,947,875 A 8/1990 Brooks et al.
 4,972,855 A 11/1990 Kuriyama et al.
 4,993,436 A 2/1991 Bloom, Jr.
 5,042,509 A 8/1991 Banerjee et al.
 5,117,482 A 5/1992 Hauber
 5,144,962 A 9/1992 Counts et al.
 5,261,424 A 11/1993 Sprinkel, Jr.
 5,269,327 A 12/1993 Counts et al.
 5,479,948 A 1/1996 Counts et al.
 5,666,977 A 9/1997 Higgins et al.
 5,682,050 A 10/1997 Williams
 5,865,185 A 2/1999 Collins et al.
 6,090,082 A 7/2000 King et al.
 6,155,268 A 12/2000 Takeuchi
 6,322,268 B1 11/2001 Kaufmann et al.
 6,443,146 B1 9/2002 Voges
 6,516,796 B1 2/2003 Cox et al.
 6,532,965 B1 3/2003 Abhulimen et al.
 6,708,846 B1 3/2004 Fuchs et al.
 6,772,756 B2 8/2004 Shayan

7,173,222 B2 2/2007 Cox et al.
 7,318,435 B2 1/2008 Pentafragas
 D590,990 S 4/2009 Hon
 7,726,320 B2 6/2010 Robinson et al.
 7,802,569 B2 9/2010 Yeates et al.
 7,913,688 B2 3/2011 Cross et al.
 8,205,622 B2 6/2012 Pan
 8,251,060 B2 8/2012 White et al.
 D675,777 S 2/2013 Wu
 8,365,742 B2 2/2013 Hon
 8,371,310 B2 2/2013 Brenneise
 D688,415 S 8/2013 Kim
 8,522,776 B2 9/2013 Wright et al.
 8,578,942 B2 11/2013 Schennum
 8,689,805 B2 4/2014 Hon
 8,714,161 B2 5/2014 Liu
 8,752,545 B2 6/2014 Buchberger
 8,794,231 B2 8/2014 Thorens et al.
 8,869,792 B1 10/2014 Lee
 D718,492 S 11/2014 Albanese
 8,881,737 B2 11/2014 Collett et al.
 8,893,726 B2 11/2014 Hon
 8,899,240 B2 12/2014 Mass
 8,910,639 B2 12/2014 Chang et al.
 8,948,578 B2 2/2015 Buchberger
 8,955,522 B1 2/2015 Bowen et al.
 8,978,663 B2 3/2015 Newton
 8,991,402 B2 3/2015 Bowen et al.
 9,010,335 B1 4/2015 Scatterday
 9,055,770 B2 6/2015 Liu
 9,072,321 B2 7/2015 Liu
 9,072,322 B2 7/2015 Liu
 9,078,472 B2 7/2015 Liu
 9,078,474 B2 7/2015 Thompson
 9,078,475 B2 7/2015 Li et al.
 9,089,168 B2 7/2015 Liu
 9,095,175 B2 8/2015 Terry et al.
 9,101,729 B2 8/2015 Liu
 9,113,659 B2 8/2015 Liu
 9,220,302 B2 12/2015 DePiano et al.
 9,220,303 B2 12/2015 Li et al.
 D750,320 S 2/2016 Verleur et al.
 9,247,773 B2 2/2016 Memari et al.
 9,254,007 B2 2/2016 Liu
 D750,835 S 3/2016 Wei
 D752,280 S 3/2016 Verleur et al.
 9,277,768 B2 3/2016 Xiu
 9,289,014 B2 3/2016 Tucker et al.
 9,308,336 B2 4/2016 Newton
 9,315,890 B1 4/2016 Frick et al.
 9,326,547 B2 5/2016 Tucker et al.
 9,345,541 B2 5/2016 Greeley et al.
 9,351,522 B2 5/2016 Safari
 9,364,800 B2 6/2016 Dubief
 9,380,812 B2 7/2016 Chung
 9,386,805 B2 7/2016 Liu
 9,420,829 B2 8/2016 Thorens et al.
 9,420,831 B2 8/2016 Liu
 9,423,152 B2 8/2016 Ampolini et al.
 9,439,456 B2 9/2016 Liu
 9,456,633 B2 10/2016 Liu
 9,498,588 B2 11/2016 Benassayag et al.
 9,504,279 B2 11/2016 Chen
 9,516,898 B2 12/2016 Liu
 9,526,272 B2 12/2016 Liu
 9,532,601 B2 1/2017 Liu
 9,555,203 B2 1/2017 Terry et al.
 9,578,898 B2 2/2017 Liu
 9,591,876 B2 3/2017 Alima
 9,603,390 B2 3/2017 Li et al.
 9,609,893 B2 4/2017 Novak, III et al.
 9,615,607 B2 4/2017 Liu
 9,622,511 B2 4/2017 Zhu
 9,629,391 B2 4/2017 Dube et al.
 9,629,394 B2 4/2017 Aronie et al.
 9,642,397 B2 5/2017 Dai et al.
 9,675,114 B2 6/2017 Timmermans
 9,675,117 B2 6/2017 Li et al.
 9,687,027 B2 6/2017 Poston et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,687,029 B2	6/2017	Liu	2013/0056013 A1	3/2013	Terry et al.	
9,717,275 B2	8/2017	Liu	2013/0087160 A1	4/2013	Gherghe	
9,717,276 B2	8/2017	Brammer et al.	2013/0104916 A1	5/2013	Bellinger et al.	
9,723,874 B2	8/2017	Liu	2013/0168880 A1	7/2013	Duke	
9,723,875 B2	8/2017	Liu	2013/0174842 A1	7/2013	Young et al.	
9,730,471 B2	8/2017	Li et al.	2013/0182421 A1	7/2013	Popper et al.	
9,738,622 B2	8/2017	Dull et al.	2013/0192617 A1 *	8/2013	Thompson	A24F 40/44
9,743,691 B2	8/2017	Minskoff et al.				131/329
9,781,953 B2	10/2017	Verleur et al.	2013/0192623 A1	8/2013	Tucker et al.	
9,795,168 B2	10/2017	Zhu	2013/0213420 A1	8/2013	Hon	
9,801,413 B2	10/2017	Zhu	2013/0220315 A1	8/2013	Conley et al.	
9,814,263 B2	11/2017	Cochand et al.	2013/0228191 A1	9/2013	Newton	
9,814,265 B2	11/2017	Rinker et al.	2013/0253433 A1	9/2013	Senior et al.	
9,820,508 B2	11/2017	Amel et al.	2013/0255675 A1	10/2013	Liu	
9,844,234 B2	12/2017	Thorens et al.	2013/0255702 A1	10/2013	Griffith, Jr. et al.	
9,861,135 B2	1/2018	Chen	2013/0284194 A1	10/2013	Newton	
9,918,496 B2	3/2018	Kane et al.	2013/0288081 A1	10/2013	Cheng et al.	
9,974,743 B2	5/2018	Rose et al.	2013/0298905 A1	11/2013	Levin et al.	
9,986,762 B2	6/2018	Alarcon et al.	2013/0306084 A1	11/2013	Flick	
9,999,250 B2	6/2018	Minskoff et al.	2013/0312742 A1	11/2013	Monsees et al.	
10,039,321 B2	8/2018	Verleur et al.	2013/0319431 A1	12/2013	Cyphert et al.	
10,058,122 B2	8/2018	Steingraber et al.	2013/0319435 A1	12/2013	Flick	
10,058,124 B2	8/2018	Monsees et al.	2013/0323941 A1	12/2013	Zeliff et al.	
10,085,481 B2	10/2018	Verleur et al.	2013/0333711 A1	12/2013	Liu	
10,111,467 B1	10/2018	Arnel et al.	2014/0000638 A1	1/2014	Sebastian et al.	
10,143,233 B2	12/2018	Dubief et al.	2014/0014124 A1	1/2014	Glasberg et al.	
10,195,370 B2	2/2019	Chen	2014/0034071 A1 *	2/2014	Levitz	A61M 15/06
2002/0043262 A1	4/2002	Langford et al.				131/329
2002/0078951 A1	6/2002	Nichols et al.	2014/0041655 A1	2/2014	Barron et al.	
2002/0088469 A1	7/2002	Rennecamp	2014/0053856 A1	2/2014	Liu	
2003/0226837 A1	12/2003	Blake et al.	2014/0053857 A1	2/2014	Liu	
2004/0050382 A1	3/2004	Goodchild	2014/0060552 A1	3/2014	Cohen	
2005/0016550 A1	1/2005	Katase	2014/0060556 A1	3/2014	Liu	
2005/0134215 A1	6/2005	Bozzone et al.	2014/0076310 A1	3/2014	Newton	
2007/0045288 A1	3/2007	Nelson	2014/0096781 A1	4/2014	Sears et al.	
2007/0074734 A1	4/2007	Braunshteyn et al.	2014/0096782 A1	4/2014	Ampolini et al.	
2007/0229025 A1	10/2007	Tsai et al.	2014/0123989 A1	5/2014	LaMothe	
2007/0277816 A1	12/2007	Morrison et al.	2014/0150783 A1	6/2014	Liu	
2007/0283972 A1	12/2007	Monsees et al.	2014/0150784 A1	6/2014	Liu	
2008/0023003 A1	1/2008	Rosenthal	2014/0150785 A1	6/2014	Malik et al.	
2008/0029095 A1	2/2008	Esser	2014/0158129 A1	6/2014	Pratt, Jr. et al.	
2008/0257367 A1	10/2008	Paterno et al.	2014/0166030 A1	6/2014	Li et al.	
2008/0302374 A1	12/2008	Wengert et al.	2014/0174458 A1	6/2014	Katz	
2009/0095287 A1	4/2009	Emarlou	2014/0182610 A1	7/2014	Liu	
2009/0133691 A1	5/2009	Yamada et al.	2014/0182612 A1	7/2014	Chen	
2009/0272379 A1	11/2009	Thorens et al.	2014/0190477 A1	7/2014	Qiu	
2009/0293892 A1	12/2009	Williams et al.	2014/0190496 A1	7/2014	Wensley et al.	
2009/0302019 A1	12/2009	Selenski et al.	2014/0202454 A1	7/2014	Buchberger	
2010/0031968 A1	2/2010	Sheikh et al.	2014/0209109 A1	7/2014	Larson	
2010/0194337 A1	8/2010	Opolka	2014/0216484 A1	8/2014	Liu	
2010/0200008 A1	8/2010	Taieb	2014/0224244 A1	8/2014	Liu	
2010/0207576 A1	8/2010	Elizalde Rodarte	2014/0230835 A1	8/2014	Saliman	
2010/0253279 A1	10/2010	Matthias	2014/0253144 A1	9/2014	Novak, III et al.	
2011/0036346 A1	2/2011	Cohen et al.	2014/0261487 A1	9/2014	Chapman et al.	
2011/0159705 A1	6/2011	Schmidt	2014/0261488 A1	9/2014	Tucker	
2011/0192397 A1	8/2011	Saskar et al.	2014/0261490 A1	9/2014	Kane	
2011/0226236 A1	9/2011	Buchberger	2014/0261492 A1	9/2014	Kane et al.	
2011/0226266 A1	9/2011	Tao	2014/0261493 A1	9/2014	Smith et al.	
2011/0265806 A1	11/2011	Alarcon et al.	2014/0261499 A1	9/2014	Hon	
2011/0277761 A1	11/2011	Terry et al.	2014/0270729 A1	9/2014	DePiano et al.	
2011/0278189 A1	11/2011	Terry et al.	2014/0270730 A1	9/2014	DePiano et al.	
2011/0303231 A1	12/2011	Li et al.	2014/0283823 A1	9/2014	Liu	
2012/0018529 A1	1/2012	Gammon et al.	2014/0283859 A1	9/2014	Minskoff et al.	
2012/0048266 A1	3/2012	Alelov	2014/0290677 A1	10/2014	Liu	
2012/0174914 A1	7/2012	Pirshafiey et al.	2014/0299137 A1	10/2014	Kieckbusch et al.	
2012/0199146 A1	8/2012	Marangos	2014/0299141 A1	10/2014	Flick	
2012/0199663 A1	8/2012	Qiu	2014/0311503 A1	10/2014	Liu	
2012/0223673 A1	9/2012	Chen et al.	2014/0332019 A1 *	11/2014	Liu	A24F 40/50
2012/0255546 A1	10/2012	Goetz et al.				392/404
2012/0312313 A1	12/2012	Frija	2014/0332022 A1	11/2014	Li et al.	
2012/0318882 A1	12/2012	Abehasera	2014/0334802 A1	11/2014	Dubief	
2012/0325227 A1	12/2012	Robinson et al.	2014/0334803 A1	11/2014	Li et al.	
2013/0014772 A1	1/2013	Liu	2014/0334804 A1	11/2014	Choi	
2013/0037041 A1	2/2013	Worm et al.	2014/0338685 A1	11/2014	Amir	
2013/0042865 A1	2/2013	Monsees et al.	2014/0345631 A1	11/2014	Bowen et al.	
			2014/0353856 A1	12/2014	Dubief	
			2014/0355969 A1	12/2014	Stern	
			2014/0360516 A1	12/2014	Liu	
			2014/0366896 A1	12/2014	Li et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

2014/0366898 A1	12/2014	Monsees et al.	2015/0289565 A1	10/2015	Cadieux et al.
2014/0373833 A1	12/2014	Liu	2015/0296885 A1	10/2015	Liu
2014/0376895 A1	12/2014	Han	2015/0296888 A1	10/2015	Liu
2015/0007836 A1	1/2015	Li et al.	2015/0296889 A1	10/2015	Liu
2015/0013695 A1	1/2015	McNeal et al.	2015/0305407 A1	10/2015	Li et al.
2015/0020825 A1	1/2015	Galloway et al.	2015/0305409 A1	10/2015	Verleur et al.
2015/0020831 A1	1/2015	Weigensberg et al.	2015/0313282 A1	11/2015	Ademe et al.
2015/0020832 A1 *	1/2015	Greim A24F 40/65	2015/0313283 A1	11/2015	Collett et al.
		131/329	2015/0320116 A1	11/2015	Bleloch et al.
2015/0027457 A1	1/2015	Janardhan et al.	2015/0327596 A1	11/2015	Alarcon et al.
2015/0027460 A1	1/2015	Liu	2015/0333552 A1	11/2015	Alarcon
2015/0027471 A1	1/2015	Feldman et al.	2015/0333561 A1	11/2015	Alarcon
2015/0034103 A1	2/2015	Hon	2015/0335071 A1	11/2015	Brinkley et al.
2015/0034104 A1	2/2015	Zhou	2015/0335075 A1	11/2015	Minskoff et al.
2015/0040929 A1	2/2015	Hon	2015/0342255 A1	12/2015	Wu
2015/0047658 A1	2/2015	Cyphert et al.	2015/0351454 A1	12/2015	Huang
2015/0053220 A1	2/2015	Levy et al.	2015/0351455 A1	12/2015	Liu
2015/0059783 A1	3/2015	Liu	2015/0351456 A1	12/2015	Johnson et al.
2015/0059787 A1	3/2015	Qiu	2015/0357608 A1	12/2015	Huang
2015/0083147 A1	3/2015	Schiff et al.	2016/0000147 A1	1/2016	Li et al.
2015/0090253 A1	4/2015	Farrow	2016/0007653 A1	1/2016	Tu
2015/0090256 A1	4/2015	Chung	2016/0015082 A1	1/2016	Liu
2015/0090278 A1	4/2015	Schiff et al.	2016/0021933 A1	1/2016	Thorens et al.
2015/0090281 A1	4/2015	Chen	2016/0029697 A1	2/2016	Shafer
2015/0091501 A1	4/2015	Claudepierre	2016/0029699 A1	2/2016	Li et al.
2015/0101625 A1	4/2015	Newton et al.	2016/0044962 A1	2/2016	Thorens et al.
2015/0101626 A1	4/2015	Li et al.	2016/0044965 A1	2/2016	Liu
2015/0118895 A1	4/2015	Zheng et al.	2016/0044966 A1	2/2016	Li et al.
2015/0128967 A1	5/2015	Robinson et al.	2016/0051716 A1	2/2016	Wheelock
2015/0128976 A1	5/2015	Verleur et al.	2016/0057811 A1	2/2016	Alarcon et al.
2015/0128977 A1	5/2015	Li et al.	2016/0058074 A1	3/2016	Liu
2015/0136158 A1	5/2015	Stevens et al.	2016/0073690 A1	3/2016	Liu
2015/0144145 A1	5/2015	Chang et al.	2016/0073694 A1	3/2016	Liu
2015/0144147 A1	5/2015	Li et al.	2016/0081395 A1	3/2016	Thorens et al.
2015/0150305 A1	6/2015	Shenkal	2016/0095352 A1	4/2016	Liu
2015/0150307 A1	6/2015	Liu	2016/0106936 A1	4/2016	Kimmel
2015/0157054 A1	6/2015	Liu	2016/0113326 A1	4/2016	Li et al.
2015/0157055 A1	6/2015	Lord	2016/0120226 A1	5/2016	Rado
2015/0164138 A1	6/2015	Liu	2016/0128384 A1	5/2016	Luciani et al.
2015/0164141 A1	6/2015	Newton	2016/0128388 A1	5/2016	Liu
2015/0164142 A1	6/2015	Li et al.	2016/0143365 A1	5/2016	Liu
2015/0164146 A1	6/2015	Li et al.	2016/0150824 A1	6/2016	Memari et al.
2015/0164147 A1	6/2015	Verleur et al.	2016/0157523 A1	6/2016	Liu
2015/0173422 A1	6/2015	Liu	2016/0198767 A1	7/2016	Verleur
2015/0181930 A1 *	7/2015	Liu A24F 40/40	2016/0198768 A1	7/2016	Liu
		131/329	2016/0198770 A1	7/2016	Alarcon
2015/0181940 A1	7/2015	Liu	2016/0205999 A1	7/2016	Liu
2015/0181943 A1	7/2015	Li et al.	2016/0219938 A1	8/2016	Mamoun et al.
2015/0181944 A1	7/2015	Li et al.	2016/0242463 A1	8/2016	Liu
2015/0189918 A1	7/2015	Liu	2016/0242466 A1	8/2016	Lord et al.
2015/0189919 A1	7/2015	Liu	2016/0249682 A1	9/2016	Leadley et al.
2015/0201674 A1	7/2015	Dooly et al.	2016/0270442 A1	9/2016	Liu
2015/0208728 A1	7/2015	Lord	2016/0270446 A1	9/2016	Shenkal et al.
2015/0208730 A1	7/2015	Li et al.	2016/0278435 A1	9/2016	Choukroun et al.
2015/0216237 A1	8/2015	Wensley et al.	2016/0278436 A1	9/2016	Verleur et al.
2015/0217068 A1	8/2015	Wakalopoulos	2016/0286865 A1	10/2016	King et al.
2015/0223521 A1	8/2015	Menting et al.	2016/0302471 A1	10/2016	Bowen et al.
2015/0223522 A1	8/2015	Ampolini et al.	2016/0302485 A1	10/2016	Alima
2015/0223523 A1	8/2015	McCullough	2016/0302486 A1	10/2016	Eroch
2015/0224268 A1	8/2015	Henry et al.	2016/0309779 A1	10/2016	Liu
2015/0230521 A1	8/2015	Talon	2016/0309789 A1	10/2016	Thomas, Jr.
2015/0245659 A1	9/2015	DePiano et al.	2016/0338411 A1	11/2016	Liu
2015/0245661 A1	9/2015	Milín	2016/0345628 A1	12/2016	Sabet
2015/0245669 A1	9/2015	Cadieux et al.	2016/0353804 A1	12/2016	Lord
2015/0257441 A1	9/2015	Gerkin	2016/0360784 A1	12/2016	Liu
2015/0257444 A1	9/2015	Chung	2016/0374393 A1	12/2016	Chen
2015/0257445 A1	9/2015	Henry, Jr. et al.	2017/0006916 A1	1/2017	Liu
2015/0257447 A1	9/2015	Sullivan	2017/0013875 A1	1/2017	Schennum et al.
2015/0258289 A1	9/2015	Henry, Jr. et al.	2017/0013876 A1	1/2017	Schennum et al.
2015/0272217 A1	10/2015	Chen	2017/0013882 A1	1/2017	Liu
2015/0282525 A1	10/2015	Plojoux et al.	2017/0013885 A1	1/2017	Qiu
2015/0282526 A1	10/2015	Wu	2017/0027221 A1	2/2017	Liu
2015/0282529 A1	10/2015	Li et al.	2017/0035109 A1	2/2017	Liu
2015/0282530 A1	10/2015	Johnson et al.	2017/0042229 A1	2/2017	Liu
			2017/0042242 A1	2/2017	Hon
			2017/0042248 A1	2/2017	Xiang
			2017/0049149 A1	2/2017	Carty
			2017/0049152 A1	2/2017	Liu
			2017/0071251 A1	3/2017	Goch

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0071256 A1 3/2017 Verleur et al.
 2017/0086501 A1 3/2017 Buehler et al.
 2017/0099880 A1 4/2017 Hawes
 2017/0135401 A1 5/2017 Dickens
 2017/0143038 A1 5/2017 Dickens
 2017/0143040 A1 5/2017 Liu
 2017/0157341 A1 6/2017 Pandya et al.
 2017/0164655 A1 6/2017 Chen
 2017/0188629 A1 7/2017 Dickens et al.
 2017/0197046 A1 7/2017 Buchberger
 2017/0202267 A1 7/2017 Liu
 2017/0207499 A1 7/2017 Leadley
 2017/0208865 A1 7/2017 Nettenstrom et al.
 2017/0208866 A1 7/2017 Liu
 2017/0208870 A1 7/2017 Liu
 2017/0214261 A1 7/2017 Gratton
 2017/0215476 A1 8/2017 Dickens et al.
 2017/0222468 A1 8/2017 Schennum et al.
 2017/0224014 A1 8/2017 Fraser
 2017/0231284 A1 8/2017 Newns
 2017/0238611 A1 8/2017 Buchberger
 2017/0245554 A1 8/2017 Perez et al.
 2017/0246405 A1 8/2017 Wensley et al.
 2017/0251725 A1 9/2017 Buchberger et al.
 2017/0273359 A1 9/2017 Liu
 2017/0295847 A1 10/2017 Liu
 2017/0325504 A1 11/2017 Liu
 2017/0347706 A1 12/2017 Aoun et al.

FOREIGN PATENT DOCUMENTS

CA 2641869 A1 5/2010
 CN 1196660 A 10/1998
 CN 201104488 Y 8/2008
 CN 100589726 C 2/2010
 CN 201403497 Y 2/2010
 CN 201408820 Y 2/2010
 CN 201430916 Y 3/2010
 CN 201491720 U 6/2010
 CN 101861691 A 10/2010
 CN 101869356 A 10/2010
 CN 102014677 A 4/2011
 CN 201781984 U 4/2011
 CN 202004499 U 10/2011
 CN 202566289 U 12/2012
 CN 202603608 U 12/2012
 CN 202890462 U 4/2013
 CN 202941411 U 5/2013
 CN 203040683 U 7/2013
 CN 203087525 U 7/2013
 CN 203152489 U 8/2013
 CN 203168035 U 9/2013
 CN 203182012 U 9/2013
 CN 203182014 U 9/2013
 CN 102727969 B 2/2014
 CN 203467677 U 3/2014
 CN 203538385 U 4/2014
 CN 204070533 U 1/2015
 CN 204120231 U 1/2015
 CN 204180941 U 3/2015
 CN 204217907 U 3/2015
 CN 204466899 U 7/2015
 DE 19619536 A1 10/1997
 DE 102006004484 A1 8/2007
 DE 202012004792 U1 6/2012
 DE 102012100831 B3 2/2013
 EP 0358114 A2 3/1990
 EP 0845220 B1 9/2003
 EP 2113178 A1 11/2009
 EP 2399636 A1 12/2011
 EP 2489391 A1 8/2012
 EP 2614731 A1 7/2013
 EP 2654471 A1 10/2013
 EP 2967154 A1 1/2016
 EP 3456214 A1 3/2019

EP 3469934 A1 4/2019
 GB 2264237 A 8/1993
 GB 2266466 A 11/1993
 KR 101011453 B1 1/2011
 KR 200454110 Y1 6/2011
 KR 20110006928 U 7/2011
 KR 200457340 Y1 12/2011
 KR 20120074625 A 7/2012
 KR 20120113519 A 10/2012
 KR 20120008751 U 12/2012
 KR 20130106741 A 9/2013
 KR 20130107658 A 10/2013
 TW 201315397 A 4/2013
 WO WO-2003061716 A1 7/2003
 WO WO-2003103387 A2 12/2003
 WO WO-2004080216 A1 9/2004
 WO WO-2008077271 A1 7/2008
 WO WO-2008138650 A1 11/2008
 WO WO-2009132793 A1 11/2009
 WO WO-2010118644 A1 10/2010
 WO WO-2010140841 A2 12/2010
 WO WO-2011125058 A1 10/2011
 WO WO-2011160788 A1 12/2011
 WO WO-2012043941 A1 4/2012
 WO WO-2012059726 A2 5/2012
 WO WO-2012062600 A1 5/2012
 WO WO-2012173322 A1 12/2012
 WO WO-2013020220 A1 2/2013
 WO WO-2013025921 A1 2/2013
 WO WO-2013040193 A2 3/2013
 WO WO-2013044537 A1 4/2013
 WO WO-2013068100 A1 5/2013
 WO WO-2013076750 A1 5/2013
 WO WO-2013083635 A1 6/2013
 WO WO-2013083636 A1 6/2013
 WO WO-2013089358 A1 6/2013
 WO WO-2013093695 A1 6/2013
 WO WO-2013098397 A2 7/2013
 WO WO-2013110208 A1 8/2013
 WO WO-2013110209 A1 8/2013
 WO WO-2013110210 A1 8/2013
 WO WO-2013113173 A1 8/2013
 WO WO-2013113174 A1 8/2013
 WO WO-2013116567 A1 8/2013
 WO WO-2013116983 A1 8/2013
 WO WO-2013171206 A1 11/2013
 WO WO-2013174001 A1 11/2013
 WO WO-2014008646 A1 1/2014
 WO WO-2014047948 A1 4/2014
 WO WO-2014071747 A1 5/2014
 WO WO-2014101401 A1 7/2014
 WO WO-2014101734 A1 7/2014
 WO WO-2014110750 A1 7/2014
 WO WO-2014121509 A1 8/2014
 WO WO-2014127446 A1 8/2014
 WO WO-2014139609 A2 9/2014
 WO WO-2014150979 A2 9/2014
 WO WO-2014161181 A1 10/2014
 WO WO-2014169667 A1 10/2014
 WO WO-2015024239 A1 2/2015
 WO WO-2015027383 A1 3/2015
 WO WO-2015027435 A1 3/2015
 WO WO-2015027470 A1 3/2015
 WO WO-2015032093 A1 3/2015
 WO WO-2015037925 A1 3/2015
 WO WO-2015051538 A1 4/2015
 WO WO-2015054862 A1 4/2015
 WO WO-2015066136 A1 5/2015
 WO WO-2015066927 A1 5/2015
 WO WO-2015070398 A1 5/2015
 WO WO-2015070405 A1 5/2015
 WO WO-2015071703 A1 5/2015
 WO WO-2015074187 A1 5/2015
 WO WO-2015074265 A1 5/2015
 WO WO-2015079197 A1 6/2015
 WO WO-2015082560 A1 6/2015
 WO WO-2015109476 A1 7/2015
 WO WO-2015120588 A1 8/2015
 WO WO-2015120623 A1 8/2015

(56)

References Cited

FOREIGN PATENT DOCUMENTS





WO WO-2015123831 A1 8/2015
 WO WO-2015143648 A1 10/2015
 WO WO-2015149330 A1 10/2015
 WO WO-2015149332 A1 10/2015
 WO WO-2015149406 A1 10/2015
 WO WO-2015154309 A1 10/2015
 WO WO-2015157891 A1 10/2015
 WO WO-2015157893 A1 10/2015
 WO WO-2015157900 A1 10/2015
 WO WO-2015158548 A1 10/2015
 WO WO-2015161406 A1 10/2015
 WO WO-2015161553 A1 10/2015
 WO WO-2015165081 A1 11/2015
 WO WO-2015165086 A1 11/2015
 WO WO-2015165105 A1 11/2015
 WO WO-2015168912 A1 11/2015
 WO WO-2015176230 A1 11/2015
 WO WO-2015176300 A1 11/2015
 WO WO-2015176580 A1 11/2015
 WO WO-2015180071 A1 12/2015
 WO WO-2015180088 A1 12/2015
 WO WO-2015184620 A1 12/2015
 WO WO-2015184747 A1 12/2015
 WO WO-2015190810 A1 12/2015
 WO WO-2015192326 A1 12/2015
 WO WO-2015196332 A1 12/2015
 WO WO-2016000130 A1 1/2016
 WO WO-2016000136 A1 1/2016
 WO WO-2016000206 A1 1/2016
 WO WO-2016000232 A1 1/2016
 WO WO-2016000233 A1 1/2016
 WO WO-2016015246 A1 2/2016
 WO WO-2016019353 A1 2/2016
 WO WO-2016023173 A1 2/2016
 WO WO-2016023212 A1 2/2016
 WO WO-2016026104 A1 2/2016
 WO WO-2016026105 A1 2/2016
 WO WO-2016026156 A1 2/2016
 WO WO-2016029567 A1 3/2016
 WO WO-2016033721 A1 3/2016
 WO WO-2016041114 A1 3/2016
 WO WO-2016041140 A1 3/2016
 WO WO-2016041141 A1 3/2016
 WO WO-2016041207 A1 3/2016
 WO WO-2016041209 A1 3/2016
 WO WO-2016045058 A1 3/2016
 WO WO-2016049822 A1 4/2016
 WO WO-2016049823 A1 4/2016
 WO WO-2016049855 A1 4/2016
 WO WO-2016054793 A1 4/2016
 WO WO-2016058139 A1 4/2016
 WO WO-2016059000 A1 4/2016
 WO WO-2016061730 A1 4/2016




WO WO-2016061822 A1 4/2016
 WO WO-2016062168 A1 4/2016
 WO WO-2016065521 A1 5/2016
 WO WO-2016065532 A1 5/2016
 WO WO-2016065533 A1 5/2016
 WO WO-2016065596 A1 5/2016
 WO WO-2016065598 A1 5/2016
 WO WO-2016065599 A1 5/2016
 WO WO-2016070553 A1 5/2016


OTHER PUBLICATIONS

"New Tank E-Cigarette:innokin 510T." From China Manufacturer, Manufactory, Factory and Supplier on ECVV.com, Nov. 15, 2011, www.ecvv.com/product/3118191.html.
 Chinabuy. "Innokin ITaste VV Tank Starter Kit Electronic Cigarette with Clearomizer." YouTube, YouTube, Jul. 23, 2013, www.youtube.com/watch?v=mz414d8MU20.
 Cloud pen vaporizer unboxing review by vaporizer blog // VaporizerBlog.com, <https://www.youtube.com/watch?v=ixHMkXoWKNg>.
 Glory Vapes. "Glory Vapes TV: Kanger S1 Cubica Series Starter Kit Unboxing." YouTube, YouTube, Aug. 8, 2013, www.youtube.com/watch?v=NQjvJ6YhdbA.
 Joye eGo-Tank System XXL 1000mAh Starter Kit, <https://www.myvaporstore.com/eGo-Tank-System-XXL-1000mAh-Starter-Kit-p/ego-t-xxlkit.htm>.
 Uptoyou Fromeme. "Elips Ego SOLE Electronic Cigarette Kit Patent Elipse Flat Upgrade F6 Section with Atomizer CE4." YouTube, YouTube, Sep. 12, 2013, www.youtube.com/watch?v=cnPcqDzFm0Q.
 Vaporizers Reviewed. "AtmosRX Optimus 510 Vaporizer Review." YouTube, YouTube, Oct. 10, 2013, www.youtube.com/watch?v=wsyQncG8FB8.
 Vaporizers Reviewed. "MicroG Pen Vaporizer Review." YouTube, YouTube, Nov. 6, 2013, www.youtube.com/watch?v=pLhtL8vosrs.
 U.S. Appl. No. 14/196,729, filed Mar. 4, 2014, now U.S. Pat. No. 10,039,321.
 U.S. Appl. No. 14/539,801, filed Nov. 12, 2014, now U.S. Pat. No. 10,085,481.
 U.S. Appl. No. 14/790,566, filed Jul. 2, 2015, US 2015-0305409.
 U.S. Appl. No. 14/201,267, filed Mar. 7, 2014, now U.S. Pat. No. 10,842,191.
 U.S. Appl. No. 16/119,359, filed Aug. 31, 2018, US 2018-0368481.
 U.S. Appl. No. 16/179,829, filed Nov. 2, 2018, now U.S. Pat. No. 10,653,186.
 U.S. Appl. No. 16/181,316, filed Nov. 5, 2018, now U.S. Pat. No. 10,667,561.
 U.S. Appl. No. 16/193,994, filed Nov. 16, 2018, now U.S. Pat. No. 10,736,360.
 U.S. Appl. No. 16/193,943, filed Nov. 16, 2018, US 2019-0082740.
 U.S. Appl. No. 15/036,292, filed Nov. 12, 2014, US 2016-0278436.

* cited by examiner

Fig. 1**Fig. 1A****Fig. 1B****Fig. 1C**








Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10





Fig. 11






Fig. 13





Fig. 14






Fig. 15


FIG. 16

FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21





FIG. 22



1

VAPORIZER

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 14/201,267, filed Mar. 7, 2014, which is a continuation of U.S. application Ser. No. 14/196,729 filed Mar. 4, 2014, now U.S. Pat. No. 10,039,321, which claims the benefit of U.S. Provisional Application Nos. 61/903,344 filed Nov. 12, 2013, and 61/937,851, filed Feb. 10, 2014, the disclosures of which are hereby incorporated herein by reference in their entireties.

FIELD OF THE INVENTION

This invention relates to the field of vaporizers, which may also be referred to as electronic cigarettes.

BACKGROUND

Electronic cigarettes have recently emerged as a new product for providing nicotine through a smokeless inhalation process. Typically, implementations consist of a power supply (typically a battery) and an atomizing device. In reusable electronic cigarettes the two items are separated into a battery and a cartomizer, to allow the disposal and replacement of a nicotine containing fluid cartomizer while preserving the more costly battery and associated circuitry (microcontroller, switch, indicating LED, etc.) for additional use. In disposable electronic cigarettes, the two items are combined to integrate the functions into one unit that is discarded after either the battery energy or the nicotine containing liquid is exhausted.

The electronic cigarette liquid used to vaporize ingredients such as nicotine is generally a solution of propylene glycol (PG), vegetable glycerin (VG), or polyethylene glycol 400 (PEG400), as well as their mixtures to which a flavor and/or nicotine has been added. The solution is often sold in a bottle (for refilling by the user) or in disposable cartridges or cartomizers. Many different flavors are incorporated into these liquids, including those that resemble the taste of regular tobacco, menthol, vanilla, coffee, cola and/or various fruits. Various nicotine concentrations are also available, and nicotine-free solutions are also common.

BRIEF SUMMARY

One embodiment of a vaporizer, in accordance with the disclosure, may include a shell having a battery segment and a cartomizer receiving segment, the cartomizer receiving segment may define a chamber having an insertion end distal to the battery segment of said shell and a base end proximate to the battery segment, the chamber dimensioned to receive a cartomizer inserted into the chamber at the insertion end of the chamber. The vaporizer may also include a battery housed within the battery segment. The vaporizer may further include electrical contacts provided between the base end of the chamber and the battery portion, the electrical contacts including a positive contact and a negative contact insulated from the positive contact. Electronic circuitry may be housed within the battery segment of said shell and operable to direct an electrical current between the battery and the electrical contacts. Additionally, a chamber magnet may be provided in or proximate to the chamber, the chamber magnet operable to secure a cartomizer received within the chamber, wherein the cartomizer includes either

2

a metallic surface or a cartomizer magnet having a polarity opposite to that of the chamber magnet. The electrical contacts and battery may each be in electrical connection with said electronic circuitry. The cartomizer may be securable within the chamber as a cartomizer surface and a magnetically attracted chamber surface are placed adjacent to one another.

In another embodiment of a vaporizer, in accordance with the disclosure, the vaporizer may include a shell having a battery segment and a cartomizer receiving segment, the cartomizer receiving segment defining a chamber having an insertion end distal from the battery segment and a base end proximate to the battery segment. The vaporizer may further include a cartomizer insertable into the chamber at the insertion end, and the cartomizer may include a cartomizer body dimensioned to hold a vaporizable substance, a heating element provided within or proximate to the cartomizer body operable to heat the vaporizable substance, cartomizer electrical contacts provided on the exterior of the cartomizer, cartomizer electrical circuitry operable to direct an electronic current between the cartomizer electrical contacts and the heating element, and a mouthpiece in fluid communication with the cartomizer body, the mouthpiece extending from the insertion end of the chamber when the cartomizer is inserted in the chamber. The heating element may be activated by the current and is operable to heat the vaporizable substance to a vaporization temperature. A battery may be housed within the battery segment. The vaporizer may also include battery electrical contacts provided between the base end of the chamber and the battery segment, the battery electrical contacts positioned to contact the cartomizer electrical contacts when the cartomizer is inserted in the chamber. Additionally, the vaporizer may include battery electrical circuitry housed within the battery segment and operable to direct an electrical current between the battery, the battery electrical contacts, the cartomizer electrical contacts, the heating element, and the inserted cartomizer.

BRIEF DESCRIPTION OF THE FIGURES

FIG. 1 illustrates a front view of an embodiment of an electronic cigarette of the disclosure comprising a first embodiment of a battery portion with an embodiment of a cartomizer for use with a vaporizable liquid inserted into a cartomizer chamber of the first embodiment battery portion, the outer shell of the first embodiment battery portion shown transparently so as to illustrate the inner components of the electronic cigarette.

FIG. 1A illustrates a lateral cross sectional view of the electronic cigarette of FIG. 1 illustrating an electrical connector and magnets.

FIG. 1B illustrates a lateral cross sectional view of the electronic cigarette of FIG. 1 illustrating the end of the inserted cartomizer.

FIG. 1C illustrates a lateral cross sectional view of the electronic cigarette of FIG. 1 illustrating the cartomizer chamber.

FIG. 2 illustrates a front view of an embodiment of a cartomizer in accordance with the disclosure that may be inserted into the cartomizer chamber of the battery portion of FIG. 1, the outer shell of the first embodiment battery portion shown transparently so as to illustrate the inner components of the electronic cigarette.

FIG. 2A illustrates a lateral cross sectional view of the cartomizer of FIG. 2 illustrating the end of the cartomizer at the inserted end.

3

FIG. 2B illustrates a lateral cross sectional view of the cartomizer of FIG. 2 illustrating the air hole structure.

FIG. 3 illustrates a front view of an embodiment of the battery portion of FIG. 1 with an embodiment of a charger, in accordance with the disclosure, inserted into the cartomizer chamber, with the outer shell of the first embodiment battery portion shown transparently so as to illustrate the inner components of the electronic cigarette.

FIGS. 4-7 illustrate embodiments of electronic cigarettes comprising the first battery portion of FIGS. 1-3 and the cartomizers of FIGS. 1 and 2, in accordance with the disclosure.

FIG. 8 illustrates a front view of an embodiment of an electronic cigarette, in accordance with the disclosure, comprising a second embodiment of a battery portion with the outer shell of the second embodiment battery portion shown transparently so as to illustrate the inner components of the electronic cigarette.

FIG. 9 illustrates a front view of the electronic cigarette of FIG. 8 with a charger attached, with the outer shell of the second embodiment battery portion shown transparently so as to illustrate the inner components of the electronic cigarette.

FIG. 10 illustrates a front cross sectional view of an embodiment of a cartomizer in accordance with the disclosure.

FIG. 11 illustrates a front view of an embodiment of a cartomizer in accordance with the disclosure.

FIG. 12 illustrates embodiments of electronic cigarettes comprising the second battery portion of FIGS. 8-9 and the cartomizers of FIGS. 8-10.

FIG. 13 illustrates a front view of an embodiment of an electronic cigarette in accordance with the disclosure, with the outer shell of the embodiment of the battery portion shown transparently so as to illustrate the inner components of the electronic cigarette.

FIG. 14 illustrates a front view of the electronic cigarette of FIG. 13 with a charger attached.

FIG. 15 illustrates embodiments of the electronic cigarette of FIGS. 13-14 in accordance with the disclosure.

FIG. 16 illustrates a longitudinal cross sectional view of an embodiment of charger contacts on a power cord of a vaporizer or electronic cigarette charger of the present invention.

FIG. 17 illustrates a perspective view of an embodiment of charger contacts on a power cord of a vaporizer or electronic cigarette charger of the present invention.

FIG. 18 illustrates a lateral view of an embodiment of charger contacts on a power cord of a vaporizer or electronic cigarette charger of the present invention.

FIG. 19 illustrates a longitudinal cross sectional view of an embodiment of charger contacts of a vaporizer or electronic cigarette for connecting with a vaporizer or electronic cigarette charger of the present invention.

FIG. 20 illustrates a lateral cross sectional view of an embodiment of charger contacts on a vaporizer or electronic cigarette for connecting with a vaporizer or electronic cigarette charger of the present invention.

FIG. 21 illustrates a perspective view of an embodiment of charger contacts on a power cord of a vaporizer or electronic cigarette charger of the present invention.

FIG. 22 illustrates a side view of an embodiment of a charger of the present invention in contact with charger contacts of a vaporizer or electronic cigarette for charging a vaporizer or electronic cigarette battery.

DETAILED DESCRIPTION

The following detailed description and the appended drawings describe and illustrate exemplary embodiments of

4

the invention solely for the purpose of enabling one of ordinary skill in the relevant art to make and use the invention. As such, the detailed description and illustration of these embodiments are purely exemplary in nature and are in no way intended to limit the scope of the invention, or its protection, in any manner. It should also be understood that the drawings are not to scale and in certain instances details have been omitted, which are not necessary for an understanding of the present invention, such as conventional details of fabrication and assembly.

One embodiment of a vaporizer, in accordance with the disclosure, may include a shell having a battery segment and a cartomizer receiving segment, the cartomizer receiving segment may define a chamber having an insertion end distal to the battery segment of said shell and a base end proximate to the battery segment, the chamber dimensioned to receive a cartomizer inserted into the chamber at the insertion end of the chamber. The vaporizer may also include a battery housed within the battery segment. The vaporizer may further include electrical contacts provided between the base end of the chamber and the battery portion, the electrical contacts including a positive contact and a negative contact insulated from the positive contact. Electronic circuitry may be housed within the battery segment of said shell and operable to direct an electrical current between the battery and the electrical contacts. Additionally, a chamber magnet may be provided in or proximate to the chamber, the chamber magnet operable to secure a cartomizer received within the chamber, wherein the cartomizer includes either a metallic surface or a cartomizer magnet having a polarity opposite to that of the chamber magnet. The electrical contacts and battery may each be in electrical connection with said electronic circuitry. The cartomizer may be securable within the chamber as a cartomizer surface and a magnetically attracted chamber surface are placed adjacent to one another.

In some embodiments, the chamber magnet may be provided proximate to the base end of the chamber, the chamber magnet insulated from the electrical contacts. The vaporizer may further include an additional chamber magnet provided proximate to the base end of the chamber, the additional chamber magnet insulated from the electrical contacts and the chamber magnet, the additional chamber magnet having a polarity opposite to that of the chamber magnet. The electronic circuitry may include a printed circuit board.

Additional embodiments of the vaporizer may include an activation button provided on the exterior of the shell in electrical communication with the electronic circuitry, the electrical contacts and the battery, wherein manipulation of the activation button by a user of the vaporizer operates to control the current from the battery to the electronic contacts; a printed circuit board; and an indicator ring surrounding at least a portion of the activation button, the indicator ring in electrical communication with the electronic circuitry, the electrical contacts and the battery, said indicator ring illuminable to indicate a state of the vaporizer, the indicator ring controllable by the printed circuit board, and the printed circuit board may be in electrical communication with the electrical contacts, the battery, the activation button and the indicator ring. The vaporizer may also include a display screen provided on the exterior of the shell, said display screen in electrical communication with said printed circuit board and battery, the display screen controlled by the printed circuit board and operable to display a message. At least one of the electrical contacts may be a spring-loaded pin extending into a portion of the chamber and retractable

5

when pressed by the cartomizer when inserted into the chamber. The shell may include a window provided at the cartomizer receiving segment so that a portion of the chamber is visible from outside the shell.

In another embodiment of a vaporizer, in accordance with the disclosure, the vaporizer may include a shell having a battery segment and a cartomizer receiving segment, the cartomizer receiving segment defining a chamber having an insertion end distal from the battery segment and a base end proximate to the battery segment. The vaporizer may further include a cartomizer insertable into the chamber at the insertion end, and the cartomizer may include a cartomizer body dimensioned to hold a vaporizable substance, a heating element provided within or proximate to the cartomizer body operable to heat the vaporizable substance, cartomizer electrical contacts provided on the exterior of the cartomizer, cartomizer electrical circuitry operable to direct an electronic current between the cartomizer electrical contacts and the heating element, and a mouthpiece in fluid communication with the cartomizer body, the mouthpiece extending from the insertion end of the chamber when the cartomizer is inserted in the chamber. The heating element may be activated by the current and is operable to heat the vaporizable substance to a vaporization temperature. A battery may be housed within the battery segment. The vaporizer may also include battery electrical contacts provided between the base end of the chamber and the battery segment, the battery electrical contacts positioned to contact the cartomizer electrical contacts when the cartomizer is inserted in the chamber. Additionally, the vaporizer may include battery electrical circuitry housed within the battery segment and operable to direct an electrical current between the battery, the battery electrical contacts, the cartomizer electrical contacts, the heating element, and the inserted cartomizer.

In embodiments of the disclosure, the vaporizable substance may be a fluid, the heating element may include a wicking element for absorbing the fluid, and at least a portion of the cartomizer body may be composed of a translucent material. The cartomizer may further include a container provided within the cartomizer body and dimensioned to hold the vaporizable substance, wherein the heating element is provided exterior to at least a portion of the container and is operable to heat the container thereby heating the vaporizable substance to the vaporization temperature. The heating element may include conductive material intertwined with non-conductive material, and the conductive material may be in electrical communication with the cartomizer electronic circuitry. The vaporizer may further include a printed circuit board housed in the battery segment and in electrical communication with the battery electrical circuitry, and the cartomizer may further include a sensor in electrical communication with the cartomizer electrical circuitry, and the printed circuit board is operable to process environment information received from the sensor when the cartomizer is inserted into the chamber. The mouthpiece may be detachably connected to the cartomizer body. The cartomizer may further include a basin for holding the vaporizable substance, and the heating element may be provided proximate to the basin in order to heat the basin.

With reference now to FIGS. 1 and 2, an embodiment of an electronic cigarette 10 is provided in accordance with the disclosure. Electronic cigarette 10 may include a battery portion connectable with a vaporization unit or cartomizer 200 for holding a vaporizable substance 300. The battery portion may include a battery housing segment 102 provided proximate to the first end 102A of the battery portion, and a

6

second cartomizer receiving segment 104 provided proximate a second end 104A of the battery portion. The battery portion may include an outer shell 106 for covering or protecting one or more of the components of battery portion 100 as may be internally provided as described herein. Outer shell 106 may be substantially constructed from metal, plastic, or any other known or to be developed material suitable for protecting internal components of electronic cigarette 10, including the electrical components described herein. Battery housing segment 102 and cartomizer receiving segment 104 may commonly share outer shell 106. A cartomizer chamber 108 may be provided within at least a portion of cartomizer receiving segment 104. A cartomizer 200 may be insertable into the cartomizer chamber 108 in accordance with embodiments of the disclosure. Shell 106 may cover cartomizer chamber 108 thereby protecting an inserted or received cartomizer 200.

Electrical components for operating electronic cigarette 10 may be provided within battery housing segment 102. A battery 110 may be provided in order to provide electrical power as may be required by various features of the electronic cigarette 10. In some embodiments, battery 110 may be disposable, such as an AA or AAA cell battery, while in other embodiments, battery 110 may be of a rechargeable type, for example a 13450 lithium ion battery, an 18650 2600 mAh lithium ion cell, or flat lithium ion 903180 cell rated at 2300 mAh. Multiple batteries 110 may be used in series to generate higher voltages capable of shortening times to achieve vaporization temperatures in the cartomizer 200. A printed circuit board (PCB) 112 may also be provided for controlling one or more functions of electronic cigarette 10. PCB 112 may be electrically connected to battery 110 through circuitry in order to direct current flow as required in accordance with the disclosure. PCB 112 may include one or more integrated circuit chips as well as a micro control unit. A boost chip may also be provided in order to amplify voltage with at least portion of circuitry, as may be required in order to accomplish various functions described herein. PCB 112 may include a light emitting diode (LED), a microcontroller, a plurality of capacitors, a plurality of transistors, and a plurality of resistors or any combination thereof. An accelerometer for sensing gravity shifts of electronic cigarette 10 may be further provided. The accelerometer may be operable to detect tilting or changes in orientation of battery portion 100, and PCB 112 may be accordingly operable to react to a shift in orientation detected by the accelerometer. For instance, electronic cigarette 10 including an accelerometer may be activated by shaking or inverting electronic cigarette 10. Any known or to be discovered circuitry or arrangement of the components of PCB 112 are contemplated within the disclosure in order to achieve the desired functions of electronic cigarette 10 as described herein.

A variety of indicator lights forming one or more illuminative indicators may be provided in embodiments of the disclosure. One such indicator may be a battery end indicator 114 provided as a ring extending about at least a portion of shell 106 at or proximate to first end 102A. In one such embodiment, battery end indicator 114 may be provided at or proximate to first end 102A and includes one or more LED lights having one or more colors. Each color may, for instance, indicate a status of electronic cigarette 10. The status may be associated with the power remaining of battery 110, an activation state of electronic cigarette 10, the heating level of an inserted cartomizer 200, or any other status which may be desirable to communicate to a user of electronic cigarette 10 through a light color. For instance,

when electronic cigarette **10** is activated such that a user is either actively inhaling cigarette **10**, as described in accordance with disclosure, or cigarette **10** is in a state such that the user could inhale, indicator **114** may be red or reddish. In such an embodiment, battery end indicator **114** could extend about at least a portion of the first end **102A** such that when indicator **114** emanates a red or reddish color a user may associate the red color at or proximate to first end **102A** with the red glow of a lit cigarette. In another embodiment, an indicator ring may be provided to illuminate one or more colors associated with the charge or power state of battery **110**. For instance, battery end indicator **114** may illuminate green or blue when the battery is operating with a sufficient charge, and yellow or red when the battery is operating with a low charge such that the user should consider charging battery **110**, in accordance with the disclosure. A ring indicator **116** may be provided on or proximate to an activation button **118**, which may function to activate cigarette **10** as described herein in accordance with the disclosure. While activation button **118** may be provided on the surface of outer shell **106**, and ring indicator **116** may substantially circumference button **118**. Ring indicator **116** may include one or more LED lights having one or more colors to indicate various statuses of electronic cigarette **10**. Status changes of electronic cigarette **10**, such as insertion of cartomizer **200**, activation of electronic cigarette **10** by pressing button **118**, or deactivation of electronic cigarette **10** by pressing button **118** an additional time may each result in a different associated and predetermined color. The activation of the appropriate LED light or lights may be controlled by PCB **112**. In embodiments where button **118** is coplanar or aligned with the surface of outer shell **106**, as described herein, ring indicator **116** may also be coplanar or aligned with button **118** and the surface of outer shell **106**. Another indicator light may be provided at or proximate to cartomizer end **104A**. In one embodiment, in order to transmit a lighting effect from the battery segment **102**, where battery **110** and PCB **112** may be housed, to the cartomizer end **104A**, one or more LED lights may be provided in the cartomizer receiving segment **104** at or proximate to the battery segment **102**. One or more clear tubes or optic fibers may be also be provided within or just below the surface of outer shell **106**, with the tubes or fibers terminating at or proximate to the cartomizer end **104A**. The resulting effect is an attractive, illuminative effect where the LED lights provided in the cartomizer segment are projected into and transmitted along the fibers. PCB **112** could potentially alternate or change the LED light colors projected into the fibers. The color alternation could be periodic, creating a steady change of colors, or the color alteration could be responsive to a status change of the electronic cigarette **10**.

In order to provide an electrical connection between PCB **112** and an inserted cartomizer **200**, an electrical connector **120** may be provided and may include a plurality of pogo pins **120**. Pogo pins are devices used to establish connections between two circuits, and each may take the form of a cylinder containing one or more spring-loaded pins **122**, each retractable upon compression, for instance by cartomizer **200** when it is inserted in cartomizer chamber **108**. In one such embodiment, three pogo pins **122** may be provided, one for establishing positive current connection, one for establishing a negative current connection, and one for establishing a ground current connection. Each pogo pin **122** may be connected to PCB **112**, which may control current outputted to pogo pins **122**. For instance, PCB **112** may operate to vary or intermittently activate current flow to connector **120**, the variation thereby regulating the activa-

tion of a heating element in a connected cartomizer. When cartomizer **200** is not received in cartomizer chamber **108**, a head portion of each pogo pin may extend into cartomizer chamber **108**. When cartomizer **200** is received in cartomizer chamber **108**, the pins **122** are contacted and at least partially compressed into battery portion **102**. Pins **122** may be contacted or pressed against electrical receivers provided on cartomizer **200** as described herein, thereby establishing an electrical connection between PCB **112** and cartomizer **200**. Additional pins **122** are contemplated in embodiments of the disclosure, such as a fourth pin for providing an electrical connection to another element, such as the LED lights described above or a temperature sensor **260** described herein and illustrated in FIG. 2.

An additional embodiment of connector **120** may operate to identify information from an inserted cartomizer **200** based on voltage drop over one or more pins **122**. For instance, connector **120** may include a controlling pin **122** from which connected PCB **112** may detect variations in voltage drop across the pin when connected to various types of cartomizers **200**. Circuitry provided within a first type of cartomizer **200** may effectuate a first voltage drop over a controlling pin **122**, while circuitry provided within a second type of cartomizer **200** may effectuate a second voltage drop over controlling pin **122** when cartomizer **200** is inserted in chamber **108**. If PCB **112** detects a first voltage drop, the cartomizer **200** is identified as a first type of cartomizer, whereas if PCB **112** detects a second voltage drop, the cartomizer is identified as second type of cartomizer. A first cartomizer type may hold a first type of vaporizable substance **300**, while a second cartomizer type may hold a second type of vaporizable substance **300**. In one embodiment, connector **120** includes three pins **122**: a positive pin, a ground pin, and a controlling pin. A controlling pin may also serve a dual function in that communication between a sensor **260** may also occur through a controlling pin **122**. Other known or to be developed devices or connectors are contemplated within the disclosure for establishing an electrical current between PCB **112** and cartomizer **200**.

Various features may be further provided in embodiments of electronic cigarette **10** in order to secure and align cartomizer **200** within cartomizer chamber **108**. For instance, at least one magnet **124** may be provided in or proximate to chamber **108**. A magnet **202** of opposing polarity to magnet **124** may be placed on a surface of cartomizer **200** so as to secure cartomizer **200** within chamber **108** when magnets **124**, **202** (see FIGS. 1A, 1B) contact each other. It should be understood and appreciated that, in some embodiments, battery portion magnet(s) **124** may attach to cartomizer metallic surface(s) **202** and, conversely, cartomizer magnet(s) **202** may attach to battery portion metallic surface(s) **124**, thereby establishing a magnetic connection between battery portion **100** and cartomizer **200**. Other known or to be discovered means of securing cartomizer **200** in cartomizer chamber **108** are contemplated within the disclosure, including but not limited to, snap fit connectors, friction fit, threaded insertion of cartomizer **200** into chamber **108**, a suction fit using pressurized means or any other suitable method of securing known or to be developed in the art.

One or more alignment features or mechanism may be included in order to ensure proper placement of cartomizer **200** in cartomizer chamber **108**. In one embodiment, two magnets **124** may be provided proximate to connector **120** (see FIG. 1A), each magnet **124** having an opposed polarity. In this embodiment, two cartomizer magnets **202** (see FIG. 1B) may be provided of opposing polarity at an insertion end

210 of cartomizer 200. Because of the opposing polarities of magnets 124/202, the cartomizer 200 may only be inserted and secured in one direction or orientation, thereby facilitating alignment of cartomizer 200 within chamber 108. An alignment protrusion or peg 126 (see FIG. 1C) may be provided on a portion of an interior surface of chamber 108, and an alignment slit or slot 204 may be provided on a portion of cartomizer 200. Alignment protrusion 126 may be dimensioned to fit or slid along slit 204 so that cartomizer 200 may only be inserted in a particular, proper orientation. In another embodiment, a slit, crevice, or cutout may be provided on a portion of shell 106, with a matching protrusion provided on a portion cartomizer 200. For instance, a cutout may be provided on an upper rim of shell 106 at cartomizer receiving segment 104, while a matching protrusion may be provided on a portion of cartomizer 200 proximate to insertion end 210, with battery portion cutout engageable with the cartomizer protrusion when the cartomizer is properly aligned so as to ensure proper orientation of cartomizer 200 within chamber 108. Ensuring cartomizer 200 is properly oriented within chamber 108 in turn ensures proper contacting of cartomizer 200 with connector 120, and therefore proper functioning of electronic cigarette 10.

One or more windows 130 may be provided in outer shell 106 (see FIG. 1). Windows 130 may be made of a translucent material, such as glass or substantially clear plastic, in order to view internal components of battery portion 100. Window 130 may also be a slit cut into shell 106. For instance, in one embodiment, window 130 may be provided on or proximate to cartomizer receiving segment 104 and, more particularly, cartomizer chamber 108 so as to permit a user of electronic cigarette 10 to view the cartomizer 200 when it is inserted into cartomizer chamber 108.

One embodiment of cartomizer 200 for holding vaporizable material 300 is cartomizer 200A for holding a vaporizable fluid 300A, an embodiment of which is illustrated in FIG. 1. Vaporizable fluid 300A may be, for example, any known or to be developed fluid useful to vaporize, for inhalation nicotine, flavor or other desired ingredients in an electronic cigarette, such fluids include propylene glycol (PG), vegetable glycerin (VG), or polyethylene glycol 400 (PEG400), as well as their mixtures to which a flavor and/or nicotine has been added. Cartomizer 200A may be substantially elongate and insertable into chamber 108. Chamber 108 is defined by outer shell 106 and electrical connector 120. An insertion end 210 of cartomizer 200A, defined opposite of a mouthpiece end 212, may be inserted into the chamber first and may ultimately contact or be positioned proximate to connector 120 of battery portion 100. Cartomizer 200A may include a body 208 for holding fluid 300A. At least a portion of body 208 may be composed of translucent or substantially translucent material, such as glass or plastic, so that a user may see fluid 300A held within. The portion of body 208 composed of translucent material may be alignable with window 130 and may be proximate to LED lights or fiber optics so as to illuminate cartomizer 200A as it is inserted into chamber 108. The illumination may occur automatically upon insertion, or may be programmed to illuminate upon activation or manipulation of a switch, such as button 118.

In order to vaporize fluid 300A, a heating element 214 and a wicking element 216 may be provided within cartomizer body 208. An electrical current may be transmitted to heating element 214 through circuitry in electrical communication with electrical contacts, which contact pins 122 (see FIG. 1A) when cartomizer 200A is inserted into chamber 108. Once fluid 300A is heated to an optimal vaporizing

temperature, the user may inhale the vaporized fluid 300A through a mouthpiece 220 provided on body 208 at or proximate to mouthpiece end 212. The vaporized fluid may travel through an inhalation tube 222 in fluid connection with heating element 214 and wick 216. Inhalation tube 222 may also be in fluid communication with one or more holes or ducts provided, for instance, in sides of outer shell 106 in order to permit air flow through cartomizer body 208. The electrical current transmitted to heating element 214 may be controlled by PCB 112 through connector 120 when cartomizer 200A is inserted into chamber 108. The electronic cigarette 10 may be manually controlled, as a user may press button 118 to initiate a charge to heating element 214, which in turn may heat fluid 300A to a vaporized temperature which a user may inhale through mouthpiece 220. An automatically heating version of electronic cigarette 10 is also contemplated with disclosure, where a pressure switch integrated with connector 120 may activate current flow from PCB to heating element 214 rather than by manual activation from switch 118.

So that a user may refill fluid 300A held in body 208, mouthpiece 220 may be removable from body 208. Mouthpiece 220 may include a screw thread 224 so that mouthpiece 220 may be threadably engaged with mouthpiece end 212 of body 208 or, alternatively, may be press fit onto or into mouthpiece end 212 of body 208. A bushing 226, which may be a ring formed from plastic, rubber, or any other suitable material, may be provided to help stabilize and retain cartomizer 200 tightly fit in chamber 108. Additionally, a colored ring or logo 228 may be provided about a portion of cartomizer body 208 in order to identify the type or cartomizer being used.

With reference now to FIGS. 2, 2A and 2B, an additional embodiment of cartomizer 200B is provided for holding a dry vaporizable material 300B, such as dry tobacco. A container 240 may be provided within cartomizer body 208. Container 240 may be made from a material having a high thermal conductivity, such as metal, in order to transmit heat from a heating element 214A provided about at least a portion of container 240. In that at least a portion of heating element 214A may be provided about at least a portion of container 240, the material 300B provided within container 240 may be heated from multiple sides, similar to an oven, as opposed to from a single concentrated heat source. As an electrical current is transmitted to heating element 214A, the interior of container 240 may be heated to a desired vaporizing temperature. Heating element 214A may be substantially comprised of a non-conductive material, such as a polyimide flex harness material, with a conductive material, such as copper or other metal wiring shaped into a wire or flat ribbon, dispersed throughout the non-conductive material. The conductive material may be intertwined or wound throughout the non-conductive material in order to increase the heated surface area as well as to increase the impedance of the conductive material, which may then be electrically connected to PCB 112 through connector 120 when cartomizer 200B (See FIG. 2) is inserted in cartomizer chamber 108 (See FIG. 1). The impedance value of the conductive material may be 2-3 ohms in some embodiments, and in one embodiment a maximum of 1 ohm. In some embodiments, heating element 214A may be provided around the majority of cartomizer body 208, and in some embodiments heating element 214A may be provided proximate to only a portion of cartomizer body 208. For instance, heating element 214A may be provided only proximate to insertion end 210, in order to provide a greater portion of heating through convection rather than through conduction. In some embodi-

11

ment, heating element 214A may be provided about all or the majority of body 208, and PCB 112 may be operable in order to vary the amount of heating provided through convection rather than conduction. For instance, only the portion of heating element 214A proximate to insertion end 210 may be activated in order to heat vaporizable substance 300B through convection, or all or nearly all portions of heating element 214A may be activated in order to increase the conduction heating of substance 300B. PCB 112 may operate to switch between a conduction heating and a convection heating.

An insulating material 242 may be further provided within body 208 in order to control or regulate the heat distribution. Insulating material 242 may be provided around at least a portion of the exterior of heating element 214A in order to insulate body 208 from excess heat temperature, which may transmit to outer shell 106 (See FIG. 1). Insulating material 242 may also be provided between heating element 214A and container 240 so as to regulate or control heat transmitted to container 240.

One or more screens 250 may be provided within body 208 in order to contain dry material 300B within container 240, as well as to filter circulated air. Air may be circulated by providing one or more holes 252 in the cartomizer body 208. In one embodiment, holes 252 form a "t" shape (See FIG. 2B) from which the center of the "t" is substantially aligned with a hole leading to container 240. Holes 252 may be capable of alignment with one or more holes on the outer shell 106 of battery portion 100 so that air from the environment may pass through holes 252 and into container 240 where material 300B is provided. Holes 252 may be provided proximate to the inserted end 210. Screens 250 may be provided either at or proximate to inserted end 210, mouthpiece end 212, or both. In some embodiments, container 240 is removable from the rest of cartomizer body 208. Mouthpiece 220 may be removable or detachable, for instance through a screw thread, so as to permit access to container 240. An upper screen 250 may be attached or manufactured integrally with mouthpiece 220 so as to be removed with mouthpiece 220.

A sensor 260 may be included in some embodiments of cartomizer 200. Sensor 260 may operate to sense vaporizing temperature, and may be electronically communicative with PCB 112 so as to provide sensory information to PCB 112, which may be consequently transmitted to one of the LED indicators provided in electronic cigarette 10 as described in accordance with the disclosure. For instance, indicator 118 (See FIG. 1) may illuminate a certain color when sensor 260 has detected that vaporization temperature in container 240 has been reached and the user may proceed to inhale vaporized material 300. PCB 112 may also include safety protocols for automatic shutoff in the event that sensor 260 records a temperature above a preset vaporization temperature range, which may indicate material 300 (including, for example, 300A, 300B, 300C) is actively burning or about to burn. Thus, sensor 260 may operate as a thermistor. A vaporization range for many materials 300 may be between about 190 degrees Celsius and about 240 degrees Celsius, and in some embodiments the vaporization temperature may be at about 230 degrees Celsius. In this vaporization temperature range, active ingredients of the vaporization material 300 may begin to vaporize without actively burning, which may occur at about 400 degrees Celsius or higher for some materials. PCB 112 may operate to control the vaporization temperature, for instance regulating a maximum vaporization temperature or controlling the vaporization actual temperature. In one embodiment, PCB 112 may

12

control or regulate vaporization temperature within 10 degree Celsius, and in another embodiment PCB 112 may more finely control or regulate vaporization temperature within 1 degree Celsius, based on a selected or desired vaporization temperature as inputted by a user of electronic cigarette 10. It should be understood and appreciated that communication between sensor 260 and PCB 112 may be bidirectional so that sensor 260 may operate to control at least portions of vaporizer functions or to transmit information to PCB 112 and additionally receive information from PCB 112, which operates to control electronic cigarette 10.

As shown in FIG. 3, a charger 400 may be inserted into chamber 108 (FIG. 1) in order to charge battery 110 (FIG. 1) in embodiments where battery 110 may be rechargeable. Through its insertion into chamber 108 and contact with connector 120, charger 400 may provide an electrical charge to battery 110. Charger 400 may include a plug 410 for connecting charger 400 to a power source, which in one embodiment is a wall socket. Other plugs 410 for different power sources are contemplated within the disclosure, including USB connections and other known or to be developed power sources. An indicator light 420, which may be an LED light, may be provided on charger 400 in order to indicate a charging status, for instance when charger 400 is connected with a power source. PCB 112 may operate to change other indicators, for instance LED indicators 114/116, to indicate the charging status of electronic cigarette 10. In accordance with the disclosure, and illustrated for instance in FIG. 9, charger 400 may be connectable to battery portion at or proximate to first end 102A. Furthermore, as also illustrated for instance in FIG. 9, charger magnets 404 are contemplated within the disclosure in order to securely couple charger 400 to battery portion 100. In one embodiment, a metallic surface 404 is provided and positioned so as to be adjacent to magnets 124 or magnets 162 (depending on the embodiment of the disclosure). In another embodiment, a metallic surface 124 or 162 in order to magnetically couple battery portion 100 with charger magnets 404. Additionally, charger magnets 404 may be provided having opposing polarities as battery portion magnets 124 or 162.

FIGS. 4-7 further illustrate the embodiments of electronic cigarette 10 provided in FIGS. 1-3, in accordance with the disclosure.

FIGS. 8 and 9 illustrate an additional embodiment of an electronic cigarette 10 having a battery portion 100A for receiving a cartomizer such as cartomizer 200 or cartomizer 200B. PCB 112 may operate to perform a variety of functions including, such vaporization temperature control or regulation, voltage boost, accelerometer, or various drivers for controlling LED functioning. One or more LED indicators 114 may be provided and, in one embodiment, a set of three LED lights of variable colors are provided proximate to battery end 102A of the battery portion 100A. Magnets 124/202 may be provided in order to retain cartomizer 200 within cartomizer chamber 108. A switch 118A may be provided in order to manually activate or otherwise control electronic cigarette 10.

A battery charger 400A, having charging contacts 402, may be attached or connected to charging contacts 160 provided on outer shell 106, or otherwise exposable to the environment. In one embodiment, charging contacts 160 are positioned at or proximate to battery end 102A. Charging contacts 160, 402 may include a first positive contact and a second negative contact. In order to secure charging contacts 160 against corresponding charging contacts 402 of charger 400A, one or more magnets 162 may be provided proximate

13

to charging contacts 160. Magnets 162 may then be capable of engaging with charger magnets 404 provided on portion of charger 400A such that magnets 162, 404 are adjacent to each other when contacts 160, 402 are contacting one another. In order to ensure the proper alignment of contacts 160, 402, two magnets 162 may be provided with opposed polarities, and two charger magnets 404 may be provided with opposed polarities. These opposed polarities may ensure proper orientation of charger 400A when it is connected to battery portion 100A. In some embodiments, battery portion magnet(s) 162 may operate to magnetically attract and connect a metallic charger surface 404, or charger magnets 404 may operate to magnetically attract and connect a metallic battery surface 162, each of these embodiments thereby operating to magnetically couple charger 400 with battery portion 100. An indicator light 420, which may be an LED, may be provided to indicate a charging status of battery 110. A charging extension 410 may be provided so as to connect charger 400A to a power source or, alternatively, a power source may be internally provided within charger 400A. Charging extension 410 may be an AC wall adapter to USB and USB cord to magnetic plug. Any charger 400 of the disclosure may contain OverVoltage and OverCurrent protection in order to prevent over charging of battery 110 thereby assuring long battery life and in order to reduce the likelihood of battery 110 overheating. In one embodiment, charger 400 is rated at approximately 1000 mA current, which for some embodiments will equate to approximately two hours of battery life. The battery life will vary depending on battery selection and number of batteries 110 used in a given embodiment.

Referring now to FIG. 10, an embodiment for a cartomizer 200C is provided for holding a vaporizable substance 300. Cartomizer 200C may be used as an alternative cartomizer to 200/200B cartomizers, for example. Vaporizable substance 300 in cartomizer 200C may be a wax, oil or gel 300C. In cartomizer 200C, heating element 214 may be provided at the base of a basin 214B, which may or may not be removable from cartomizer body 208. Basin 214B may be dimensioned to hold wax, oil or gel 300C while heating element 214 may elevate the temperature within basin 214B to a vaporization temperature range, as controlled by PCB 112. Once the wax, oil or gel 300C is vaporized, a user may inhale the vapor through an inhalation tube 222 and out through mouthpiece 220. In some embodiments, mouthpiece 220 is removable through a friction fit, threaded connection, or any other known or to be developed connection means. One or more O-ring seals may also be provided proximate to the mouthpiece to ensure a fluid tight connection between mouthpiece 220 and cartomizer body 208.

FIG. 11 shows an additional embodiment of a cartomizer 200D for holding a dry vaporizable substance 300B. Cartomizer 200D may be used as an alternative cartomizer to 200/200B cartomizers, for example. Dry substance 300B may be held in a removable liner or container 240. Cartomizer 200D may also include heating element 214A and insulation material 242, each of which may be similarly provided and oriented as previously described with respect to cartomizer 200B. An air flow hole or aperture 270 may be provided at the base of cartomizer 200D. This airflow hole 270 may be provided off plane or misaligned with respect to electrical contacts 218. Airflow hole 270 may align with a hole between chamber 108 and battery portion 100A, which may house a fan 190 as described below. A temperature sensor 260 may also be included.

14

FIG. 12 further illustrates the embodiments of an electronic cigarette 10 provided in FIGS. 9-11 in accordance with the disclosure.

Referring now to FIG. 13, an embodiment of an electronic cigarette 10 including a battery portion 100B is provided. PCB 112 may include a microcontroller, voltage boost integrated circuit, accelerometer, and a Fan control circuitry. A fan 190, including blades and a motor, may be provided internally in battery segment 110 of battery portion 100B. Fan 190 may operate to facilitate air flow from external battery portion 100B, such as through one or more holes 152 provided in outer shell 106, through battery segment 110 and into cartomizer thereby establishing an air flow for inhalation in accordance with the disclosure. In some embodiments, fan 190 has a reversible operation in order to "clear" the air flow path in the event debris or excess vapor is caught in the air flow path. PCB 112 may also include one or more switches that, for instance, may be provided beneath control buttons, such as that exemplified in FIG. 15). PCB 112 may also include one or more LED's for these and other similar switch lights. PCB 112 may also operate to display a status message on an LED screen, which may be provided on outer shell 106 (e.g., as shown in FIG. 15). A status message may, for example, include messages to indicate a status of the electronic cigarette 10, such as when the cigarette 10 is activated, charging, or has reached a vaporization temperature. An LED screen may also display warning or error messages, for instance a danger message when a critical temperature has been detected by a sensor. Further, as illustrated in FIG. 14. In some embodiments, PCB 112 may operate to recognize the cartomizer 200/200A/200B/200C inserted into chamber 108, and in order to identify the vaporizable substance 300 included in cartomizer 200. For instance, PCB 112 may communicate with sensor 260 in cartomizer 200 in order to identify both the type and amount of vaporizable substance 300 within cartomizer 200. This identification may be included in the status message displayable on the LED screen on outer shell 106. Charger 400A may be utilized for charging battery 110 in battery portion 100C. It should be understood and appreciated that, in some embodiments, charger 400A may be inserted into chamber 108 of battery portions 100A/100B in addition to connection of charger 400A as described herein. It should be further understood and appreciated that in embodiments where charger 400/400A is coupled with battery portion 100 at a position other than where cartomizer 200 is connected, such as embodiments where charger 400A is coupled at or proximate to first end 102A, electronic cigarette 10 may operate with a pass through function, namely the ability to operate electronic cigarette 10 while the unit is charging from charger 400A.

FIG. 15 further illustrates the embodiments of an electronic cigarette 10 provided in FIGS. 13-14 in accordance with the disclosure.

Certain charger embodiments for rechargeable vaporizers or electronic cigarettes disclosed hereinabove, for example in FIG. 3, employ electrical contacts between the charger and the cartomizer portion's electrical connector. Under these circumstances, the cartomizer portion is first removed from the chamber to expose the electrical connector and thereafter a charger with compatible electrical contacts is inserted into the chamber. The invention contemplates other types and locations of connectors on the vaporizer and charger. Accordingly, in certain embodiments, the present invention provides a charger 400 for charging a vaporizer or electronic cigarette having charging contacts attached essentially transversely to its outer shell at an end distal to the

15

cartomizer receiving portion and proximate to its battery portion. One such embodiment is shown in FIG. 14. In some of these embodiments where the cartomizer portion is not removed from the vaporizer to expose the electrical connector, the charging contacts are incorporated into the device such that the vaporizer or electronic cigarette may be operated in its typical fashion during the recharging of the battery ("pass-through" charging).

Still other embodiments for chargers and rechargeable vaporizers or electronic cigarettes are illustrated in FIGS. 16, 17, 18, 19, and 20. For example, FIG. 16 depicts aspects of the portion of the charger that connects with the vaporizer during the charging operation. In this example, the positive connection to the vaporizer's charging contacts is facilitated through the use of a spring-loaded pogo pin (see 501 and 502). The negative connection pin (503) or other negative connection is isolated from the pogo pin by an insulator 506 to isolate the positive and negative connections from each other. At the contacts insulator surface such that it is isolated from electrical connections 501 and 503 is a wiper contact that is capable of powering a LED charging indicator light. In some instances the exterior housing 504 for the charger is at least in part, translucent or transparent, so that the indicator lamp can be readily observed. To maintain readily removable connectivity with the vaporizer, a magnet 505 is provided, and is typically in proximity to the outer edges of the charger's charging contacts and optionally takes the form of a ring disposed in substantially concentric fashion about the assembly containing the electrical contacts and insulation. The charger is generally held in the correct position for charging by magnetic attraction to the vaporizer's charging contacts. The magnetic attraction strength is such that the charger can be easily detached by just pulling on the charger. This level of attractive force may also allow the charger to break away if it is pulled too far away from the battery portion of the vaporizer so that no significant damage will occur to the vaporizer or the charger. Other aspects of the charger include one or more of support pieces and/or fixing screws, for example. The materials employed in the construction of the charger would be readily understood by the ordinarily skilled artisan once equipped with the teachings of the present invention. Any material that conducts electricity will generally be acceptable where transfer of electricity to charge the battery is required. Similarly, where insulation is a necessary property for normal operation, electrically non-conductive materials are typically acceptable. FIG. 17 illustrating a perspective drawing of a charger that employs a USB terminus connection 507 as a source of power for the charging operation. At the end distal to the USB terminus are the charger's charging contacts for the vaporizer or electronic cigarette, including a pogo pin-type positive connection 501, an insulator 506, a negative connection 503, a magnet 505 and a housing 504.

FIG. 18 shows an alternate end on view of a charger's electrical contacts region, depicting a housing 504, magnet 505, negative connection 503, wiper contact 508 for an optional LED-type charging indicator light disposed on the housing, pogo pin-type positive connection 501, and insulator 506.

FIG. 19 illustrates a partial longitudinal cross section view of an embodiment of the vaporizer's electrical connector attached essentially transversely to its outer shell 512 at an end distal to the cartomizer receiving portion and proximate to its battery portion, which may be contacted with the chargers contacts illustrated in FIG. 18. FIG. 19 shows an arrangement of components for an embodiment of

16

present invention's electrical connector including a positive contact 509, negative contact 510, and insulation 511.

An alternative vaporizer electrical connector compatible with the charger shown in FIG. 18 is shown in FIG. 20 in an end on view. In this view, the positive contact 509 forms an innermost circle, surrounded by concentric circles of independently varying dimensions including an insulator 511, a negative contact 510, a magnet 513 and outer shell 512. In certain embodiments 513 may be a magnet or a magnetic material. In embodiments where 513 is a magnetic material, it is preferably magnetic metal, more preferably a ferromagnetic metal. The magnetic attraction between 513 and the magnet in the charger contacts is strong enough to hold the charger contacts and vaporizer charging contacts sufficiently so that the battery may be recharged. In certain preferred embodiments, the attraction is sufficiently strong to maintain the charger/vaporizer connection, but weak enough to be disconnected without substantial damage to the charger or the vaporizer.

FIG. 21 shows a perspective side on view of the FIG. 18 charger's electrical contacts region depicting a housing (504), magnet (505), negative connection (503), wiper contact (508), pogo pin-type positive connection (501), and insulator (506).

FIG. 22 shows the charger of FIG. 18 connected for recharging to the electrical connector of the vaporizer compatible with the charger shown in FIG. 20.

Vaporizer or electronic cigarette charger kits useful in, for example, the recharging of batteries used to power the vaporization process in such devices, are also within the ambit of the present invention. These kits typically include one or more chargers of the present invention, or alternatively a charger with multiple interchangeable power connectors (e.g., wall plug and USB connector). Such kits may further include, if desired, one or more of various compatible vaporizers or electronic cigarettes, their components, such as for example, one or more interchangeable cartomizers, cartomizer refills, etc., as will be readily apparent to those skilled in the art. Instructions, either as inserts or as labels, indicating quantities of the components contained in the kit, guidelines for operation or use, and/or guidelines for connecting any of the components and/or refilling the cartomizers, may also be included in the kit.

In accordance with certain embodiments of the present invention, there are provided methods which comprise contacting a charger of the present invention with a compatible vaporizer or electronic cigarette for a time and under conditions effective to recharge a rechargeable battery contained within said vaporizer or electronic cigarette sufficient to repower vaporizer or electronic cigarette for its continued use.

As will be understood by the ordinarily skilled artisan equipped with the disclosure herein, electrical contacts compatible with the charger must be provided for on or within the vaporizer or electronic cigarette.

The descriptions set forth above are meant to be illustrative and not limiting, and persons of skill in the art will recognize that various common and known deviations from the above described structures are considered to be within the scope of the disclosed concepts described herein.

The invention illustratively disclosed herein suitably may be practiced in the absence of any element which is not specifically disclosed herein. The invention illustratively disclosed herein suitably may also be practiced in the absence of any element which is not specifically disclosed herein and that does not materially affect the basic and novel characteristics of the claimed invention.

LIST OF REFERENCES

10 Electronic Cigarette
 100 Battery Portion
 100A Battery Portion
 100B Battery Portion
 102 Battery Housing Segment
 102A First end of Battery Portion
 104 Cartomizer Receiving Segment
 104A Second end of Battery Portion
 106 Shell
 108 Cartomizer Chamber
 110 Battery
 112 PCB
 112A PCB
 114 Indicator
 116 Ring Indicator
 118 Button
 118A Switch
 120 Electrical Connector
 122 Pin
 124 Magnet
 126 Protrusion
 130 Window
 152 Hole
 160 Charging Contact
 162 Magnet
 190 Fan
 200 Cartomizer
 200A Cartomizer
 200B Cartomizer
 200C Cartomizer
 202 Magnet
 204 Groove
 208 Body
 210 Insertion End
 212 Mouthpiece End
 214 Heating Element
 214A Heating Element
 214B Basin
 216 Wick
 218 Electrical Contact
 220 Mouthpiece
 222 Inhalation Tube
 224 Threading
 226 Bushing
 228 Colored Ring
 240 Container
 242 Insulating Material
 250 Screen
 252 Hole
 260 Sensor
 300 Vaporizable Substance
 300A Vaporizable Fluid
 300B Vaporizable Dry Substance
 300C Vaporizable Wax
 400 Charger
 400A Charger
 402 Electrical Contact
 404 Magnet
 410 Plug
 420 Light
 501 pogo pin
 502 spring
 503 negative connection pin
 504 exterior housing
 505 magnet

506 insulator
 507 USB terminus connection
 508 wiper contact
 509 positive contact
 510 negative contact
 511 insulation
 512 outer shell
 513 magnet or magnetic metal
 What is claimed:
 1. A vaporizer device comprising:
 a battery portion having an outer shell and a chamber defined by the outer shell; and
 a cartomizer having a mouthpiece end and an insertion end disposed opposite the mouthpiece end, the cartomizer comprising:
 a cartomizer body having a volume defined therein, the volume configured to hold a fluid vaporizable substance, wherein at least a portion of the cartomizer body comprises a translucent material configured to allow viewing of the fluid vaporizable substance, wherein the cartomizer body is configured for insertion into the chamber such that at least part of the volume is positioned in the chamber when the cartomizer body is inserted into the chamber;
 a heating element and a wicking element within the cartomizer body;
 an inhalation tube in fluid communication with the heating element and the wicking element;
 a mouthpiece at or proximate to the mouthpiece end, the mouthpiece in fluid communication with the inhalation tube; and
 a plurality of cartomizer electrical contacts on an exterior of the insertion end, wherein the plurality of cartomizer electrical contacts is positioned to contact a plurality of battery electrical contacts at a base end of the chamber when the cartomizer body is inserted into the chamber.
 2. The cartomizer of claim 1, wherein the translucent material comprises glass or plastic.
 3. The cartomizer of claim 1, wherein the portion of the cartomizer body composed of the translucent material is proximate to LED lights or fiber optics so as to illuminate the cartomizer body as the cartomizer body is inserted into the chamber.
 4. The cartomizer of claim 1, wherein the cartomizer further comprises a structure that secures the cartomizer in the chamber, and wherein the structure comprises a snap fit connector.
 5. The cartomizer of claim 1, wherein the cartomizer further comprises a structure that secures the cartomizer in the chamber, and wherein the structure comprises a cartomizer metallic surface configured to be attracted to at least one magnet in or proximate to the chamber.
 6. The cartomizer of claim 1, wherein the cartomizer further comprises a structure that secures the cartomizer in the chamber, and wherein the structure comprises a friction fit or a suction fit using a pressurized structure.
 7. The cartomizer of claim 1, wherein the inhalation tube is in fluid communication with one or more holes or ducts provided inside of the outer shell when the cartomizer body is inserted into the chamber.
 8. The cartomizer of claim 1, wherein the plurality of cartomizer electrical contacts is further configured to at least partially compress the plurality of battery electrical contacts when the cartomizer body is inserted into the chamber.
 9. A vaporizer device comprising:
 a cartomizer comprising,

19

a cartomizer body configured to hold a fluid vaporizable substance, wherein at least a portion of the cartomizer body comprises a translucent material configured to allow viewing of the fluid vaporizable substance;

a heating element and a wicking element within the cartomizer body; and

a plurality of cartomizer electrical contacts on an exterior of the insertion end; and

a battery portion, the battery portion having a first end and a second end and comprising:

a battery housing segment proximate the first end of the battery portion; and

a cartomizer receiving segment proximate the second end of the battery portion, the cartomizer receiving segment comprising a chamber defined by an outer shell of the battery portion, wherein a window is provided in the outer shell, and wherein the translucent portion of the cartomizer body aligns with the window when the cartomizer body is inserted into the chamber.

10. The vaporizer device of claim 9, wherein outer shell is commonly shared by the battery housing segment and the cartomizer receiving segment.

11. The vaporizer device of claim 9, further comprising a rechargeable battery in the battery housing segment.

12. The vaporizer device of claim 9, wherein the window comprises a slit cut into the outer shell.

13. A vaporizer device comprising:

a battery portion having an outer shell and a chamber defined by the outer shell; and

a cartomizer having a mouthpiece end and an insertion end disposed opposite the mouthpiece end, the cartomizer comprising:

a cartomizer body having a volume defined therein, the volume configured to hold a vaporizable substance, wherein the vaporizable substance is in a fluid state, wherein the cartomizer body is configured for insertion into the chamber such that at least part of the volume is positioned in the chamber when the cartomizer body is inserted into the chamber;

a heating element within the cartomizer body;

cartomizer electrical contacts operable to direct current to the heating element, wherein the cartomizer electrical contacts are on an exterior of the cartomizer body; and

a wicking element inside the cartomizer body, the wicking element configured to absorb the vaporizable substance;

an inhalation tube in fluid communication with the heating element and the wicking element; and

a mouthpiece at or proximate to the mouthpiece end, the mouthpiece in fluid communication with the inhalation tube.

14. The cartomizer of claim 13, wherein at least a portion of the cartomizer body comprises a translucent material configured to allow viewing of the fluid vaporizable substance.

20

15. The cartomizer of claim 13, wherein the vaporizable substance comprises a liquid comprising nicotine.

16. The cartomizer of claim 13, wherein cartomizer electrical contacts are positioned to contact a plurality of battery electrical contacts at a base end of the chamber when the cartomizer body is inserted into the chamber.

17. A vaporizer device comprising:

a cartomizer comprising:

a cartomizer body configured to hold a vaporizable substance, wherein the vaporizable substance is in a fluid state, wherein the cartomizer body is configured for insertion into a chamber defined by an outer shell of a battery portion of a vaporizer device,

a heating element within the cartomizer body,

cartomizer electrical contacts operable to direct current to the heating element, and

a mouthpiece at or proximate to the mouthpiece end, the mouthpiece in fluid communication with the inhalation tube; and

a battery portion, the battery portion having a first end and a second end, the battery portion comprising:

a chamber of a cartomizer receiving segment, the chamber configured for receiving the cartomizer body, the cartomizer electrical contacts, and the heating element through an opening at a distal insertion end of the battery portion,

a battery segment disposed between the cartomizer receiving segment and a battery end of the battery portion opposite from the distal insertion end of the battery portion, the battery segment comprising a battery,

battery electrical contacts for completing a circuit with the cartomizer electrical contacts when the cartomizer electrical contacts are received into the chamber, the battery electrical contacts being coplanar, and

an outer shell forming at least part of the chamber, wherein a window is formed in the outer shell to permit viewing of the cartomizer body when the cartomizer body is received into the chamber.

18. The vaporizer device of claim 9, wherein the cartomizer has a mouthpiece end and an insertion end disposed opposite the mouthpiece end, the cartomizer further comprises,

an inhalation tube in fluid communication with the heating element and the wicking element; and

a mouthpiece at or proximate to the mouthpiece end, the mouthpiece in fluid communication with the inhalation tube;

wherein the plurality of cartomizer electrical contacts is positioned to contact a plurality of battery electrical contacts at a base end of the chamber when the cartomizer body is inserted into the chamber.

* * * * *