



US010722159B2

(12) **United States Patent**
Al-Ali

(10) **Patent No.:** **US 10,722,159 B2**
(45) **Date of Patent:** ***Jul. 28, 2020**

(54) **PHYSIOLOGICAL MONITORING DEVICES, SYSTEMS, AND METHODS**

(71) Applicant: **MASIMO CORPORATION**, Irvine, CA (US)

(72) Inventor: **Ammar Al-Ali**, San Juan Capistrano, CA (US)

(73) Assignee: **Masimo Corporation**, Irvine, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/791,963**

(22) Filed: **Feb. 14, 2020**

(65) **Prior Publication Data**

US 2020/0178867 A1 Jun. 11, 2020

Related U.S. Application Data

(63) Continuation of application No. 16/532,065, filed on Aug. 5, 2019, which is a continuation of application (Continued)

(51) **Int. Cl.**
A61B 5/1455 (2006.01)
A61B 5/024 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 5/14552** (2013.01); **A61B 5/0002** (2013.01); **A61B 5/02416** (2013.01);
(Continued)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,960,128 A 10/1990 Gordon et al.
4,964,408 A 10/1990 Hink et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101484065 B 7/2009
CN 101564290 B 10/2009
(Continued)

OTHER PUBLICATIONS

US 8,845,543 B2, 09/2014, Diab et al. (withdrawn)
(Continued)

Primary Examiner — Eric F Winakur


Assistant Examiner — Marjan Fardanesh

(74) *Attorney, Agent, or Firm* — Knobbe, Martens, Olson & Bear, LLP

(57) **ABSTRACT**

A non-invasive, optical-based physiological monitoring system is disclosed. One embodiment includes an emitter configured to emit light. A diffuser is configured to receive and spread the emitted light, and to emit the spread light at a tissue measurement site. The system further includes a concentrator configured to receive the spread light after it has been attenuated by or reflected from the tissue measurement site. The concentrator is also configured to collect and concentrate the received light and to emit the concentrated light to a detector. The detector is configured to detect the concentrated light and to transmit a signal representative of the detected light. A processor is configured to receive the transmitted signal and to determine a physiological parameter, such as, for example, arterial oxygen saturation, in the tissue measurement site.

25 Claims, 7 Drawing Sheets



Related U.S. Application Data

- No. 16/226,249, filed on Dec. 19, 2018, now Pat. No. 10,470,695, which is a continuation of application No. 15/195,199, filed on Jun. 28, 2016, now Pat. No. 10,448,871.
- (60) Provisional application No. 62/188,430, filed on Jul. 2, 2015.
- (51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/145 (2006.01)
- (52) **U.S. Cl.**
 CPC *A61B 5/14532* (2013.01); *A61B 5/14546* (2013.01); *A61B 5/4875* (2013.01); *A61B 5/6826* (2013.01); *A61B 5/7278* (2013.01); *A61B 5/742* (2013.01); *A61B 2562/04* (2013.01)

References Cited

U.S. PATENT DOCUMENTS

5,041,187 A	8/1991	Hink et al.	5,800,349 A	9/1998	Isaacson et al.
5,069,213 A	12/1991	Polczynski	5,810,734 A	9/1998	Caro et al.
5,099,842 A	3/1992	Mannheimer et al.	5,823,950 A	10/1998	Diab et al.
5,158,091 A	10/1992	Butterfield et al.	5,830,131 A	11/1998	Caro et al.
5,163,438 A	11/1992	Gordon et al.	5,830,137 A	11/1998	Scharf
5,203,329 A	4/1993	Takatani et al.	5,833,618 A	11/1998	Caro et al.
5,228,449 A	7/1993	Christ et al.	5,860,919 A	1/1999	Kiani-Azarbayjany et al.
5,319,355 A	6/1994	Russek	5,890,929 A	4/1999	Mills et al.
5,337,744 A	8/1994	Branigan	5,904,654 A	5/1999	Wohltmann et al.
5,341,805 A	8/1994	Stavridi et al.	5,919,134 A	7/1999	Diab
D353,195 S	12/1994	Savage et al.	5,934,925 A	8/1999	Tobler et al.
D353,196 S	12/1994	Savage et al.	5,940,182 A	8/1999	Lepper, Jr. et al.
5,377,676 A	1/1995	Vari et al.	5,987,343 A	11/1999	Kinast
D359,546 S	6/1995	Savage et al.	5,995,855 A	11/1999	Kiani et al.
5,431,170 A	7/1995	Mathews	5,997,343 A	12/1999	Mills et al.
D361,840 S	8/1995	Savage et al.	6,002,952 A	12/1999	Diab et al.
D362,063 S	9/1995	Savage et al.	6,011,986 A	1/2000	Diab et al.
5,452,717 A	9/1995	Branigan et al.	6,027,452 A	2/2000	Flaherty et al.
D363,120 S	10/1995	Savage et al.	6,036,642 A	3/2000	Diab et al.
5,456,252 A	10/1995	Vari et al.	6,045,509 A	4/2000	Caro et al.
5,462,051 A	10/1995	Oka et al.	6,067,462 A	5/2000	Diab et al.
5,479,934 A	1/1996	Imran	6,081,735 A	6/2000	Diab et al.
5,482,036 A	1/1996	Diab et al.	6,088,607 A	7/2000	Diab et al.
5,490,505 A	2/1996	Diab et al.	6,102,856 A	8/2000	Groff et al.
5,494,043 A	2/1996	O'Sullivan et al.	6,110,522 A	8/2000	Lepper, Jr. et al.
5,497,771 A	3/1996	Rosenheimer	6,124,597 A	9/2000	Shehada
5,533,511 A	7/1996	Kaspari et al.	6,128,521 A	10/2000	Marro et al.
5,534,851 A	7/1996	Russek	6,129,675 A	10/2000	Jay
5,561,275 A	10/1996	Savage et al.	6,144,868 A	11/2000	Parker
5,562,002 A	10/1996	Lalin	6,151,516 A	11/2000	Kiani-Azarbayjany et al.
5,564,429 A	10/1996	Bornn et al.	6,152,754 A	11/2000	Gerhardt et al.
5,584,296 A	12/1996	Cui et al.	6,157,850 A	12/2000	Diab et al.
5,590,649 A	1/1997	Caro et al.	6,165,005 A	12/2000	Mills et al.
5,601,079 A	2/1997	Wong et al.	6,184,521 B1	2/2001	Coffin, IV et al.
5,602,924 A	2/1997	Durand et al.	6,206,830 B1	3/2001	Diab et al.
5,623,925 A	4/1997	Swenson et al.	6,223,063 B1	4/2001	Chaiken et al.
5,632,272 A	5/1997	Diab et al.	6,229,856 B1	5/2001	Diab et al.
5,638,816 A	6/1997	Kiani-Azarbayjany et al.	6,232,609 B1	5/2001	Snyder et al.
5,638,818 A	6/1997	Diab et al.	6,236,872 B1	5/2001	Diab et al.
5,645,440 A	7/1997	Tobler et al.	6,241,680 B1	6/2001	Miwa
5,685,299 A	11/1997	Diab et al.	6,241,683 B1	6/2001	Macklem et al.
5,699,808 A	12/1997	John	6,253,097 B1	6/2001	Aronow et al.
5,729,203 A	3/1998	Oka et al.	6,256,523 B1	7/2001	Diab et al.
D393,830 S	4/1998	Tobler et al.	6,263,222 B1	7/2001	Diab et al.
5,743,262 A	4/1998	Lepper, Jr. et al.	6,278,522 B1	8/2001	Lepper, Jr. et al.
5,758,644 A	6/1998	Diab et al.	6,280,213 B1	8/2001	Tobler et al.
5,760,910 A	6/1998	Lepper, Jr. et al.	6,285,896 B1	9/2001	Tobler et al.
5,769,785 A	6/1998	Diab et al.	6,301,493 B1	10/2001	Marro et al.
5,782,757 A	7/1998	Diab et al.	6,308,089 B1	10/2001	von der Ruhr et al.
5,785,659 A	7/1998	Caro et al.	6,317,627 B1	11/2001	Ennen et al.
5,791,347 A	8/1998	Flaherty et al.	6,321,100 B1	11/2001	Parker
5,792,052 A	8/1998	Isaacson et al.	6,325,761 B1	12/2001	Jay
			6,334,065 B1	12/2001	Al-Ali et al.
			6,343,223 B1	1/2002	Chin et al.
			6,343,224 B1	1/2002	Parker
			6,349,228 B1	2/2002	Kiani et al.
			6,356,203 B1	3/2002	Halleck et al.
			6,360,114 B1	3/2002	Diab et al.
			6,368,283 B1	4/2002	Xu et al.
			6,371,921 B1	4/2002	Caro et al.
			6,377,829 B1	4/2002	Al-Ali
			6,388,240 B2	5/2002	Schulz et al.
			6,397,091 B2	5/2002	Diab et al.
			6,430,437 B1	8/2002	Marro
			6,430,525 B1	8/2002	Weber et al.
			6,463,311 B1	10/2002	Diab
			6,470,199 B1	10/2002	Kopotic et al.
			6,501,975 B2	12/2002	Diab et al.
			6,505,059 B1	1/2003	Kollias et al.
			6,515,273 B2	2/2003	Al-Ali
			6,519,487 B1	2/2003	Parker
			6,525,386 B1	2/2003	Mills et al.
			6,526,300 B1	2/2003	Kiani et al.
			6,541,756 B2	4/2003	Schulz et al.
			6,542,764 B1	4/2003	Al-Ali et al.
			6,580,086 B1	6/2003	Schulz et al.
			6,584,336 B1	6/2003	Ali et al.
			6,595,316 B2	7/2003	Cybulski et al.
			6,597,932 B2	7/2003	Tian et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,597,933 B2	7/2003	Kiani et al.	7,186,966 B2	3/2007	Al-Ali
6,606,511 B1	8/2003	Ali et al.	7,190,261 B2	3/2007	Al-Ali
6,632,181 B2	10/2003	Flaherty et al.	7,215,984 B2	5/2007	Diab
6,639,668 B1	10/2003	Trepagnier	7,215,986 B2	5/2007	Diab
6,640,116 B2	10/2003	Diab	7,221,971 B2	5/2007	Diab
6,643,530 B2	11/2003	Diab et al.	7,225,006 B2	5/2007	Al-Ali et al.
6,650,917 B2	11/2003	Diab et al.	7,225,007 B2	5/2007	Al-Ali
6,654,624 B2	11/2003	Diab et al.	RE39,672 E	6/2007	Shehada et al.
6,658,276 B2	12/2003	Kiani et al.	7,227,156 B2	6/2007	Colvin, Jr. et al.
6,661,161 B1	12/2003	Lanzo et al.	7,239,905 B2	7/2007	Kiani-Azarbayjany et al.
6,671,526 B1	12/2003	Aoyagi et al.	7,245,953 B1	7/2007	Parker
6,671,531 B2	12/2003	Al-Ali et al.	7,254,429 B2	8/2007	Schurman et al.
6,678,543 B2	1/2004	Diab et al.	7,254,431 B2	8/2007	Al-Ali
6,684,090 B2	1/2004	Ali et al.	7,254,433 B2	8/2007	Diab et al.
6,684,091 B2	1/2004	Parker	7,254,434 B2	8/2007	Schulz et al.
6,697,656 B1	2/2004	Al-Ali	7,272,425 B2	9/2007	Al-Ali
6,697,657 B1	2/2004	Shehada et al.	7,274,955 B2	9/2007	Kiani et al.
6,697,658 B2	2/2004	Al-Ali	D554,263 S	10/2007	Al-Ali
RE38,476 E	3/2004	Diab et al.	7,280,858 B2	10/2007	Al-Ali et al.
6,699,194 B1	3/2004	Diab et al.	7,289,835 B2	10/2007	Mansfield et al.
6,714,804 B2	3/2004	Al-Ali et al.	7,292,883 B2	11/2007	De Felice et al.
RE38,492 E	4/2004	Diab et al.	7,295,866 B2	11/2007	Al-Ali
6,721,582 B2	4/2004	Trepagnier et al.	7,328,053 B1	2/2008	Diab et al.
6,721,585 B1	4/2004	Parker	7,332,784 B2	2/2008	Mills et al.
6,725,075 B2	4/2004	Al-Ali	7,340,287 B2	3/2008	Mason et al.
6,728,560 B2	4/2004	Kollias et al.	7,341,559 B2	3/2008	Schulz et al.
6,735,459 B2	5/2004	Parker	7,343,186 B2	3/2008	Lamego et al.
6,745,060 B2	6/2004	Diab et al.	D566,282 S	4/2008	Al-Ali et al.
6,760,607 B2	7/2004	Al-Ali	7,355,512 B1	4/2008	Al-Ali
6,770,028 B1	8/2004	Ali et al.	7,356,365 B2	4/2008	Schurman
6,771,994 B2	8/2004	Kiani et al.	7,371,981 B2	5/2008	Abdul-Hafiz
6,785,568 B2	8/2004	Chance	7,373,193 B2	5/2008	Al-Ali et al.
6,792,300 B1	9/2004	Diab et al.	7,373,194 B2	5/2008	Weber et al.
6,801,799 B2	10/2004	Mendelson	7,376,453 B1	5/2008	Diab et al.
6,813,511 B2	11/2004	Diab et al.	7,377,794 B2	5/2008	Al Ali et al.
6,816,741 B2	11/2004	Diab	7,377,899 B2	5/2008	Weber et al.
6,822,564 B2	11/2004	Al-Ali	7,383,070 B2	6/2008	Diab et al.
6,826,419 B2	11/2004	Diab et al.	7,415,297 B2	8/2008	Al-Ali et al.
6,830,711 B2	12/2004	Mills et al.	7,428,432 B2	9/2008	Ali et al.
6,831,266 B2	12/2004	Paritsky et al.	7,438,683 B2	10/2008	Al-Ali et al.
6,850,787 B2	2/2005	Weber et al.	7,440,787 B2	10/2008	Diab
6,850,788 B2	2/2005	Al-Ali	7,454,240 B2	11/2008	Diab et al.
6,852,083 B2	2/2005	Caro et al.	7,467,002 B2	12/2008	Weber et al.
6,861,639 B2	3/2005	Al-Ali	7,469,157 B2	12/2008	Diab et al.
6,898,452 B2	5/2005	Al-Ali et al.	7,471,969 B2	12/2008	Diab et al.
6,920,345 B2	7/2005	Al-Ali et al.	7,471,971 B2	12/2008	Diab et al.
6,931,268 B1	8/2005	Kiani-Azarbayjany et al.	7,483,729 B2	1/2009	Al-Ali et al.
6,934,570 B2	8/2005	Kiani et al.	7,483,730 B2	1/2009	Diab et al.
6,939,305 B2	9/2005	Flaherty et al.	7,489,958 B2	2/2009	Diab et al.
6,943,348 B1	9/2005	Coffin, IV	7,496,391 B2	2/2009	Diab et al.
6,950,687 B2	9/2005	Al-Ali	7,496,393 B2	2/2009	Diab et al.
6,961,598 B2	11/2005	Diab	D587,657 S	3/2009	Al-Ali et al.
6,970,792 B1	11/2005	Diab	7,499,741 B2	3/2009	Diab et al.
6,979,812 B2	12/2005	Al-Ali	7,499,835 B2	3/2009	Weber et al.
6,985,764 B2	1/2006	Mason et al.	7,500,950 B2	3/2009	Al-Ali et al.
6,993,371 B2	1/2006	Kiani et al.	7,509,154 B2	3/2009	Diab et al.
6,996,427 B2	2/2006	Ali et al.	7,509,494 B2	3/2009	Al-Ali
6,999,904 B2	2/2006	Weber et al.	7,510,849 B2	3/2009	Schurman et al.
7,003,338 B2	2/2006	Weber et al.	7,519,327 B2	4/2009	White
7,003,339 B2	2/2006	Diab et al.	7,526,328 B2	4/2009	Diab et al.
7,015,451 B2	3/2006	Dalke et al.	7,530,942 B1	5/2009	Diab
7,024,233 B2	4/2006	Ali et al.	7,530,949 B2	5/2009	Al Ali et al.
7,027,849 B2	4/2006	Al-Ali	7,530,955 B2	5/2009	Diab et al.
7,030,749 B2	4/2006	Al-Ali	7,563,110 B2	7/2009	Al-Ali et al.
7,039,449 B2	5/2006	Al-Ali	7,596,398 B2	9/2009	Al-Ali et al.
7,041,060 B2	5/2006	Flaherty et al.	7,601,123 B2	10/2009	Tweed et al.
7,044,918 B2	5/2006	Diab	7,613,490 B2	11/2009	Sarussi et al.
7,048,687 B1	5/2006	Reuss et al.	7,618,375 B2	11/2009	Flaherty
7,060,963 B2	6/2006	Maegawa et al.	D606,659 S	12/2009	Kiani et al.
7,067,893 B2	6/2006	Mills et al.	7,647,083 B2	1/2010	Al-Ali et al.
7,096,052 B2	8/2006	Mason et al.	D609,193 S	2/2010	Al-Ali et al.
7,096,054 B2	8/2006	Abdul-Hafiz et al.	D614,305 S	4/2010	Al-Ali et al.
7,132,641 B2	11/2006	Schulz et al.	RE41,317 E	5/2010	Parker
7,142,901 B2	11/2006	Kiani et al.	7,726,209 B2	6/2010	Ruotoistenmäki
7,149,561 B2	12/2006	Diab	7,729,733 B2	6/2010	Al-Ali et al.
			7,734,320 B2	6/2010	Al-Ali
			7,740,588 B1	6/2010	Sciarra
			7,740,589 B2	6/2010	Maschke et al.
			7,761,127 B2	7/2010	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,761,128 B2	7/2010	Al-Ali et al.	8,255,028 B2	8/2012	Al-Ali et al.
7,764,982 B2	7/2010	Dalke et al.	8,260,577 B2	9/2012	Weber et al.
D621,516 S	8/2010	Kiani et al.	8,265,723 B1	9/2012	McHale et al.
7,791,155 B2	9/2010	Diab	8,274,360 B2	9/2012	Sampath et al.
7,801,581 B2	9/2010	Diab	8,280,469 B2	10/2012	Baker, Jr. et al.
7,822,452 B2	10/2010	Schurman et al.	8,280,473 B2	10/2012	Al-Ali
RE41,912 E	11/2010	Parker	8,289,130 B2	10/2012	Nakajima et al.
7,844,313 B2	11/2010	Kiani et al.	8,301,217 B2	10/2012	Al-Ali et al.
7,844,314 B2	11/2010	Al-Ali	8,306,596 B2	11/2012	Schurman et al.
7,844,315 B2	11/2010	Al-Ali	8,310,336 B2	11/2012	Muhsin et al.
7,862,523 B2	1/2011	Ruotoistenmaki	8,315,683 B2	11/2012	Al-Ali et al.
7,865,222 B2	1/2011	Weber et al.	RE43,860 E	12/2012	Parker
7,869,849 B2	1/2011	Ollerdissen et al.	8,337,403 B2	12/2012	Al-Ali et al.
7,873,497 B2	1/2011	Weber et al.	8,346,330 B2	1/2013	Lamego
7,880,606 B2	2/2011	Al-Ali	8,353,842 B2	1/2013	Al-Ali et al.
7,880,626 B2	2/2011	Al-Ali et al.	8,355,766 B2	1/2013	MacNeish, III et al.
7,891,355 B2	2/2011	Al-Ali et al.	8,359,080 B2	1/2013	Diab et al.
7,894,868 B2	2/2011	Al-Ali et al.	8,364,223 B2	1/2013	Al-Ali et al.
7,899,507 B2	3/2011	Al-Ali et al.	8,364,226 B2	1/2013	Diab et al.
7,899,510 B2	3/2011	Hoarau	8,364,389 B2	1/2013	Dorogusker et al.
7,899,518 B2	3/2011	Trepagnier et al.	8,374,665 B2	2/2013	Lamego
7,904,132 B2	3/2011	Weber et al.	8,385,995 B2	2/2013	Al-Ali et al.
7,909,772 B2	3/2011	Popov et al.	8,385,996 B2	2/2013	Smith et al.
7,910,875 B2	3/2011	Al-Ali	8,388,353 B2	3/2013	Kiani et al.
7,919,713 B2	4/2011	Al-Ali et al.	8,399,822 B2	3/2013	Al-Ali
7,937,128 B2	5/2011	Al-Ali	8,401,602 B2	3/2013	Kiani
7,937,129 B2	5/2011	Mason et al.	8,405,608 B2	3/2013	Al-Ali et al.
7,937,130 B2	5/2011	Diab et al.	8,414,499 B2	4/2013	Al-Ali et al.
7,941,199 B2	5/2011	Kiani	8,418,524 B2	4/2013	Al-Ali
7,951,086 B2	5/2011	Flaherty et al.	8,423,106 B2	4/2013	Lamego et al.
7,957,780 B2	6/2011	Lamego et al.	8,428,967 B2	4/2013	Olsen et al.
7,962,188 B2	6/2011	Kiani et al.	8,430,817 B1	4/2013	Al-Ali et al.
7,962,190 B1	6/2011	Diab et al.	8,437,825 B2	5/2013	Dalvi et al.
7,976,472 B2	7/2011	Kiani	8,452,364 B2	5/2013	Hannula et al.
7,988,637 B2	8/2011	Diab	8,455,290 B2	6/2013	Siskavich
7,990,382 B2	8/2011	Kiani	8,457,703 B2	6/2013	Al-Ali
7,991,446 B2	8/2011	Al-Ali et al.	8,457,707 B2	6/2013	Kiani
8,000,761 B2	8/2011	Al-Ali	8,463,349 B2	6/2013	Diab et al.
8,008,088 B2	8/2011	Bellott et al.	8,466,286 B2	6/2013	Bellot et al.
RE42,753 E	9/2011	Kiani-Azarbayjany et al.	8,471,713 B2	6/2013	Poeze et al.
8,019,400 B2	9/2011	Diab et al.	8,473,020 B2	6/2013	Kiani et al.
8,028,701 B2	10/2011	Al-Ali et al.	8,483,787 B2	7/2013	Al-Ali et al.
8,029,765 B2	10/2011	Bellott et al.	8,489,364 B2	7/2013	Weber et al.
8,036,727 B2	10/2011	Schurman et al.	8,496,595 B2	7/2013	Jornod
8,036,728 B2	10/2011	Diab et al.	8,498,684 B2	7/2013	Weber et al.
8,046,040 B2	10/2011	Ali et al.	8,504,128 B2	8/2013	Blank et al.
8,046,041 B2	10/2011	Diab et al.	8,509,867 B2	8/2013	Workman et al.
8,046,042 B2	10/2011	Diab et al.	8,515,509 B2	8/2013	Bruinsma et al.
8,048,040 B2	11/2011	Kiani	8,515,515 B2	8/2013	McKenna et al.
8,050,728 B2	11/2011	Al-Ali et al.	8,523,781 B2	9/2013	Al-Ali
8,071,935 B2	12/2011	Besko et al.	8,529,301 B2	9/2013	Al-Ali et al.
RE43,169 E	2/2012	Parker	8,532,727 B2	9/2013	Ali et al.
8,118,620 B2	2/2012	Al-Ali et al.	8,532,728 B2	9/2013	Diab et al.
8,126,528 B2	2/2012	Diab et al.	D692,145 S	10/2013	Al-Ali et al.
8,128,572 B2	3/2012	Diab et al.	8,547,209 B2	10/2013	Kiani et al.
8,130,105 B2	3/2012	Al-Ali et al.	8,548,548 B2	10/2013	Al-Ali
8,145,287 B2	3/2012	Diab et al.	8,548,549 B2	10/2013	Schurman et al.
8,150,487 B2	4/2012	Diab et al.	8,548,550 B2	10/2013	Al-Ali et al.
8,175,672 B2	5/2012	Parker	8,560,032 B2	10/2013	Al-Ali et al.
8,180,420 B2	5/2012	Diab et al.	8,560,034 B1	10/2013	Diab et al.
8,182,443 B1	5/2012	Kiani	8,570,167 B2	10/2013	Al-Ali
8,185,180 B2	5/2012	Diab et al.	8,570,503 B2	10/2013	Vo et al.
8,190,223 B2	5/2012	Al-Ali et al.	8,571,617 B2	10/2013	Reichgott et al.
8,190,227 B2	5/2012	Diab et al.	8,571,618 B1	10/2013	Lamego et al.
8,203,438 B2	6/2012	Kiani et al.	8,571,619 B2	10/2013	Al-Ali et al.
8,203,704 B2	6/2012	Merritt et al.	8,577,431 B2	11/2013	Lamego et al.
8,204,566 B2	6/2012	Schurman et al.	8,581,732 B2	11/2013	Al-Ali et al.
8,219,172 B2	7/2012	Schurman et al.	8,584,345 B2	11/2013	Al-Ali et al.
8,224,411 B2	7/2012	Al-Ali et al.	8,588,880 B2	11/2013	Abdul-Hafiz et al.
8,228,181 B2	7/2012	Al-Ali	8,591,426 B2	11/2013	Onoe et al.
8,229,533 B2	7/2012	Diab et al.	8,600,467 B2	12/2013	Al-Ali et al.
8,233,955 B2	7/2012	Al-Ali et al.	8,606,342 B2	12/2013	Diab
8,244,325 B2	8/2012	Al-Ali et al.	8,615,290 B2	12/2013	Lin et al.
8,255,026 B1	8/2012	Al-Ali	8,626,255 B2	1/2014	Al-Ali et al.
8,255,027 B2	8/2012	Al-Ali et al.	8,630,691 B2	1/2014	Lamego et al.
			8,634,889 B2	1/2014	Al-Ali et al.
			8,641,631 B2	2/2014	Sierra et al.
			8,652,060 B2	2/2014	Al-Ali
			8,655,004 B2	2/2014	Prest et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

8,663,107 B2	3/2014	Kiani	9,028,429 B2	5/2015	Telfort et al.
8,666,468 B1	3/2014	Al-Ali	9,037,207 B2	5/2015	Al-Ali et al.
8,667,967 B2	3/2014	Al-Ali et al.	9,060,721 B2	6/2015	Reichgott et al.
8,670,811 B2	3/2014	O'Reilly	9,066,666 B2	6/2015	Kiani
8,670,814 B2	3/2014	Diab et al.	9,066,680 B1	6/2015	Al-Ali et al.
8,676,286 B2	3/2014	Weber et al.	9,072,437 B2	7/2015	Paalasmaa
8,682,407 B2	3/2014	Al-Ali	9,072,474 B2	7/2015	Al-Ali et al.
RE44,823 E	4/2014	Parker	9,078,560 B2	7/2015	Schurman et al.
RE44,875 E	4/2014	Kiani et al.	9,081,889 B2	7/2015	Ingrassia, Jr. et al.
8,690,799 B2	4/2014	Telfort et al.	9,084,569 B2	7/2015	Weber et al.
8,700,111 B2	4/2014	LeBoeuf et al.	9,095,316 B2	8/2015	Welch et al.
8,700,112 B2	4/2014	Kiani	9,106,038 B2	8/2015	Telfort et al.
8,702,627 B2	4/2014	Telfort et al.	9,107,625 B2	8/2015	Telfort et al.
8,706,179 B2	4/2014	Parker	9,107,626 B2	8/2015	Al-Ali et al.
8,712,494 B1	4/2014	MacNeish, III et al.	9,113,831 B2	8/2015	Al-Ali
8,715,206 B2	5/2014	Telfort et al.	9,113,832 B2	8/2015	Al-Ali
8,718,735 B2	5/2014	Lamego et al.	9,119,595 B2	9/2015	Lamego
8,718,737 B2	5/2014	Diab et al.	9,131,881 B2	9/2015	Diab et al.
8,718,738 B2	5/2014	Blank et al.	9,131,882 B2	9/2015	Al-Ali et al.
8,720,249 B2	5/2014	Al-Ali	9,131,883 B2	9/2015	Al-Ali
8,721,541 B2	5/2014	Al-Ali et al.	9,131,917 B2	9/2015	Telfort et al.
8,721,542 B2	5/2014	Al-Ali et al.	9,138,180 B1	9/2015	Coverston et al.
8,723,677 B1	5/2014	Kiani	9,138,182 B2	9/2015	Al-Ali et al.
8,740,792 B1	6/2014	Kiani et al.	9,138,192 B2	9/2015	Weber et al.
8,754,776 B2	6/2014	Poeze et al.	9,142,117 B2	9/2015	Muhsin et al.
8,755,535 B2	6/2014	Telfort et al.	9,153,112 B1	10/2015	Kiani et al.
8,755,856 B2	6/2014	Diab et al.	9,153,121 B2	10/2015	Kiani et al.
8,755,872 B1	6/2014	Marinow	9,161,696 B2	10/2015	Al-Ali et al.
8,760,517 B2	6/2014	Sarwar et al.	9,161,713 B2	10/2015	Al-Ali et al.
8,761,850 B2	6/2014	Lamego	9,167,995 B2	10/2015	Lamego et al.
8,764,671 B2	7/2014	Kiani	9,176,141 B2	11/2015	Al-Ali et al.
8,768,423 B2	7/2014	Shakespeare et al.	9,186,102 B2	11/2015	Bruinsma et al.
8,768,426 B2	7/2014	Haisley et al.	9,192,312 B2	11/2015	Al-Ali
8,771,204 B2	7/2014	Telfort et al.	9,192,329 B2	11/2015	Al-Ali
8,777,634 B2	7/2014	Kiani et al.	9,192,351 B1	11/2015	Telfort et al.
8,781,543 B2	7/2014	Diab et al.	9,195,385 B2	11/2015	Al-Ali et al.
8,781,544 B2	7/2014	Al-Ali et al.	9,210,566 B2	12/2015	Ziemianska et al.
8,781,549 B2	7/2014	Al-Ali et al.	9,211,072 B2	12/2015	Kiani
8,788,003 B2	7/2014	Schurman et al.	9,211,095 B1	12/2015	Al-Ali
8,790,268 B2	7/2014	Al-Ali	9,218,454 B2	12/2015	Kiani et al.
8,801,613 B2	8/2014	Al-Ali et al.	9,226,696 B2	1/2016	Kiani
8,821,397 B2	9/2014	Al-Ali et al.	9,241,662 B2	1/2016	Al-Ali et al.
8,821,415 B2	9/2014	Al-Ali et al.	9,245,668 B1	1/2016	Vo et al.
8,830,449 B1	9/2014	Lamego et al.	9,259,185 B2	2/2016	Abdul-Hafiz et al.
8,831,700 B2	9/2014	Schurman et al.	9,267,572 B2	2/2016	Barker et al.
8,838,210 B2	9/2014	Wood et al.	9,277,880 B2	3/2016	Poeze et al.
8,840,549 B2	9/2014	Al-Ali et al.	9,289,167 B2	3/2016	Diab et al.
8,847,740 B2	9/2014	Kiani et al.	9,295,421 B2	3/2016	Kiani et al.
8,849,365 B2	9/2014	Smith et al.	9,307,928 B1	4/2016	Al-Ali et al.
8,852,094 B2	10/2014	Al-Ali et al.	9,311,382 B2	4/2016	Varoglu et al.
8,852,994 B2	10/2014	Wojtczuk et al.	9,323,894 B2	4/2016	Kiani
8,868,147 B2	10/2014	Stippick et al.	D755,392 S	5/2016	Hwang et al.
8,868,150 B2	10/2014	Al-Ali et al.	9,326,712 B1	5/2016	Kiani
8,870,792 B2	10/2014	Al-Ali et al.	9,333,316 B2	5/2016	Kiani
8,886,271 B2	11/2014	Kiani et al.	9,339,220 B2	5/2016	Lamego et al.
8,888,539 B2	11/2014	Al-Ali et al.	9,339,236 B2	5/2016	Frix et al.
8,888,708 B2	11/2014	Diab et al.	9,341,565 B2	5/2016	Lamego et al.
8,892,180 B2	11/2014	Weber et al.	9,351,673 B2	5/2016	Diab et al.
8,897,847 B2	11/2014	Al-Ali	9,351,675 B2	5/2016	Al-Ali et al.
8,909,310 B2	12/2014	Lamego et al.	9,357,665 B2	5/2016	Myers et al.
8,911,377 B2	12/2014	Al-Ali	9,364,181 B2	6/2016	Kiani et al.
8,912,909 B2	12/2014	Al-Ali et al.	9,368,671 B2	6/2016	Wojtczuk et al.
8,920,317 B2	12/2014	Al-Ali et al.	9,370,325 B2	6/2016	Al-Ali et al.
8,920,332 B2	12/2014	Hong et al.	9,370,326 B2	6/2016	McHale et al.
8,921,699 B2	12/2014	Al-Ali et al.	9,370,335 B2	6/2016	Al-Ali et al.
8,922,382 B2	12/2014	Al-Ali et al.	9,375,185 B2	6/2016	Ali et al.
8,929,964 B2	1/2015	Al-Ali et al.	9,386,953 B2	7/2016	Al-Ali
8,942,777 B2	1/2015	Diab et al.	9,386,961 B2	7/2016	Al-Ali et al.
8,948,834 B2	2/2015	Diab et al.	9,392,945 B2	7/2016	Al-Ali et al.
8,948,835 B2	2/2015	Diab	9,397,448 B2	7/2016	Al-Ali et al.
8,965,471 B2	2/2015	Lamego	9,408,542 B1	8/2016	Kinast et al.
8,983,564 B2	3/2015	Al-Ali	9,436,645 B2	9/2016	Al-Ali et al.
8,989,831 B2	3/2015	Al-Ali et al.	9,445,759 B1	9/2016	Lamego et al.
8,996,085 B2	3/2015	Kiani et al.	9,466,919 B2	10/2016	Kiani et al.
8,998,809 B2	4/2015	Kiani	9,474,474 B2	10/2016	Lamego et al.
			9,480,422 B2	11/2016	Al-Ali
			9,480,435 B2	11/2016	Olsen
			9,489,081 B2	11/2016	Anzures et al.
			9,492,110 B2	11/2016	Al-Ali et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,497,534 B2	11/2016	Prest et al.	9,847,002 B2	12/2017	Kiani et al.
9,510,779 B2	12/2016	Poeze et al.	9,847,749 B2	12/2017	Kiani et al.
9,517,024 B2	12/2016	Kiani et al.	9,848,800 B1	12/2017	Lee et al.
9,526,430 B2	12/2016	Srinivas et al.	9,848,806 B2	12/2017	Al-Ali et al.
9,532,722 B2	1/2017	Lamego et al.	9,848,807 B2	12/2017	Lamego
9,538,949 B2	1/2017	Al-Ali et al.	9,848,823 B2	12/2017	Raghuram et al.
9,538,980 B2	1/2017	Telfort et al.	9,861,298 B2	1/2018	Eckerbom et al.
9,549,696 B2	1/2017	Lamego et al.	9,861,304 B2	1/2018	Al-Ali et al.
9,553,625 B2	1/2017	Hatanaka et al.	9,861,305 B1	1/2018	Weber et al.
9,554,737 B2	1/2017	Schurman et al.	9,866,671 B1	1/2018	Thompson et al.
9,560,996 B2	2/2017	Kiani	9,867,575 B2	1/2018	Maani et al.
9,560,998 B2	2/2017	Al-Ali et al.	9,867,578 B2	1/2018	Al-Ali et al.
9,566,019 B2	2/2017	Al-Ali et al.	9,872,623 B2	1/2018	Al-Ali
9,579,039 B2	2/2017	Jansen et al.	9,876,320 B2	1/2018	Coverston et al.
9,591,975 B2	3/2017	Dalvi et al.	9,877,650 B2	1/2018	Muhsin et al.
9,593,969 B2	3/2017	King	9,877,686 B2	1/2018	Al-Ali et al.
9,622,692 B2	4/2017	Lamego et al.	9,891,079 B2	2/2018	Dalvi
9,622,693 B2	4/2017	Diab	9,891,590 B2	2/2018	Shim et al.
D788,312 S	5/2017	Al-Ali et al.	9,895,107 B2	2/2018	Al-Ali et al.
9,636,055 B2	5/2017	Al-Ali et al.	9,898,049 B2	2/2018	Myers et al.
9,636,056 B2	5/2017	Al-Ali	9,913,617 B2	3/2018	Al-Ali et al.
9,649,054 B2	5/2017	Lamego et al.	9,918,646 B2	3/2018	Singh Alvarado et al.
9,651,405 B1	5/2017	Gowreesunker et al.	9,924,893 B2	3/2018	Schurman et al.
9,662,052 B2	5/2017	Al-Ali et al.	9,924,897 B1	3/2018	Abdul-Hafiz
9,668,676 B2	6/2017	Culbert	9,936,917 B2	4/2018	Poeze et al.
9,668,679 B2	6/2017	Schurman et al.	9,943,269 B2	4/2018	Muhsin et al.
9,668,680 B2	6/2017	Bruinsma et al.	9,949,676 B2	4/2018	Al-Ali
9,668,703 B2	6/2017	Al-Ali	9,952,095 B1	4/2018	Hotelling et al.
9,675,286 B2	6/2017	Diab	9,955,937 B2	5/2018	Telfort
9,681,812 B2	6/2017	Presura	9,965,946 B2	5/2018	Al-Ali
9,684,900 B2	6/2017	Motoki et al.	9,980,667 B2	5/2018	Kiani et al.
9,687,160 B2	6/2017	Kiani	D820,865 S	6/2018	Muhsin et al.
9,693,719 B2	7/2017	Al-Ali et al.	9,986,919 B2	6/2018	Lamego et al.
9,693,737 B2	7/2017	Al-Ali	9,986,952 B2	6/2018	Dalvi et al.
9,697,928 B2	7/2017	Al-Ali et al.	9,989,560 B2	6/2018	Poeze et al.
9,699,546 B2	7/2017	Qian et al.	9,993,207 B2	6/2018	Al-Ali et al.
9,716,937 B2	7/2017	Qian et al.	10,007,758 B2	6/2018	Al-Ali et al.
9,717,425 B2	8/2017	Kiani et al.	D822,215 S	7/2018	Al-Ali et al.
9,717,448 B2	8/2017	Frix et al.	D822,216 S	7/2018	Barker et al.
9,717,458 B2	8/2017	Lamego et al.	10,010,276 B2	7/2018	Al-Ali et al.
9,723,997 B1	8/2017	Lamego	10,032,002 B2	7/2018	Kiani et al.
9,724,016 B1	8/2017	Al-Ali et al.	10,039,080 B2	7/2018	Miller et al.
9,724,024 B2	8/2017	Al-Ali	10,039,482 B2	8/2018	Al-Ali et al.
9,724,025 B1	8/2017	Kiani et al.	10,039,491 B2	8/2018	Thompson et al.
9,730,640 B2	8/2017	Diab et al.	10,052,037 B2	8/2018	Kinast et al.
9,743,887 B2	8/2017	Al-Ali et al.	10,055,121 B2	8/2018	Chaudhri et al.
9,749,232 B2	8/2017	Sampath et al.	10,058,275 B2	8/2018	Al-Ali et al.
9,750,442 B2	9/2017	Olsen	10,064,562 B2	9/2018	Al-Ali
9,750,443 B2	9/2017	Smith et al.	10,066,970 B2	9/2018	Gowreesunker et al.
9,750,461 B1	9/2017	Telfort	10,076,257 B2	9/2018	Lin et al.
9,752,925 B2	9/2017	Chu et al.	10,078,052 B2	9/2018	Ness et al.
9,775,545 B2	10/2017	Al-Ali et al.	10,086,138 B1	10/2018	Novak, Jr.
9,775,546 B2	10/2017	Diab et al.	10,092,200 B2	10/2018	Al-Ali et al.
9,775,570 B2	10/2017	Al-Ali	10,092,244 B2	10/2018	Chuang et al.
9,778,079 B1	10/2017	Al-Ali et al.	10,092,249 B2	10/2018	Kiani et al.
9,781,984 B2	10/2017	Baranski et al.	10,098,550 B2	10/2018	Al-Ali et al.
9,782,077 B2	10/2017	Lamego et al.	10,098,591 B2	10/2018	Al-Ali et al.
9,782,110 B2	10/2017	Kiani	10,098,610 B2	10/2018	Al-Ali et al.
9,787,568 B2	10/2017	Lamego et al.	D833,624 S	11/2018	DeJong et al.
9,788,735 B2	10/2017	Al-Ali	10,117,587 B2	11/2018	Han
9,788,768 B2	10/2017	Al-Ali et al.	10,123,726 B2	11/2018	Al-Ali et al.
9,795,300 B2	10/2017	Al-Ali	10,130,289 B2	11/2018	Al-Ali et al.
9,795,310 B2	10/2017	Al-Ali	10,130,291 B2	11/2018	Schurman et al.
9,795,358 B2	10/2017	Telfort et al.	D835,282 S	12/2018	Barker et al.
9,795,739 B2	10/2017	Al-Ali et al.	D835,283 S	12/2018	Barker et al.
9,801,556 B2	10/2017	Kiani	D835,284 S	12/2018	Barker et al.
9,801,588 B2	10/2017	Weber et al.	D835,285 S	12/2018	Barker et al.
9,808,188 B1	11/2017	Perea et al.	10,149,616 B2	12/2018	Al-Ali et al.
9,814,418 B2	11/2017	Weber et al.	10,154,815 B2	12/2018	Al-Ali et al.
9,820,691 B2	11/2017	Kiani	10,159,412 B2	12/2018	Lamego et al.
9,833,152 B2	12/2017	Kiani et al.	10,165,954 B2	1/2019	Lee
9,833,180 B2	12/2017	Shakespeare et al.	10,188,296 B2	1/2019	Al-Ali et al.
9,838,775 B2	12/2017	Qian et al.	10,188,331 B1	1/2019	Al-Ali et al.
9,839,379 B2	12/2017	Al-Ali et al.	10,188,348 B2	1/2019	Kiani et al.
9,839,381 B1	12/2017	Weber et al.	RE47,218 E	2/2019	Al-Ali
			RE47,244 E	2/2019	Kiani et al.
			RE47,249 E	2/2019	Kiani et al.
			10,194,847 B2	2/2019	Al-Ali
			10,194,848 B1	2/2019	Kiani et al.

(56)	References Cited				2012/0165629	A1	6/2012	Merritt et al.
	U.S. PATENT DOCUMENTS				2012/0179006	A1	7/2012	Jansen et al.
					2012/0197093	A1	8/2012	LeBoeuf et al.
					2012/0197137	A1	8/2012	Jeanne et al.
10,201,286	B2	2/2019	Waydo		2012/0209082	A1	8/2012	Al-Ali
10,201,298	B2	2/2019	Al-Ali et al.		2012/0209084	A1	8/2012	Olsen et al.
10,205,272	B2	2/2019	Kiani et al.		2012/0283524	A1	11/2012	Kiani et al.
10,205,291	B2	2/2019	Scruggs et al.		2012/0296178	A1	11/2012	Lamego et al.
10,213,108	B2	2/2019	Al-Ali		2012/0319816	A1	12/2012	Al-Ali
10,215,698	B2	2/2019	Han et al.		2012/0330112	A1	12/2012	Lamego et al.
10,219,706	B2	3/2019	Al-Ali		2013/0006076	A1	1/2013	McHale
10,219,746	B2	3/2019	McHale et al.		2013/0018233	A1	1/2013	Cinbis et al.
10,219,754	B1	3/2019	Lamego		2013/0023775	A1	1/2013	Lamego et al.
10,226,187	B2	3/2019	Al-Ali et al.		2013/0041591	A1	2/2013	Lamego
10,226,576	B2	3/2019	Kiani		2013/0046204	A1	2/2013	Lamego et al.
10,231,657	B2	3/2019	Al-Ali et al.		2013/0060147	A1	3/2013	Welch et al.
10,231,670	B2	3/2019	Blank et al.		2013/0085346	A1	4/2013	Lin et al.
10,231,676	B2	3/2019	Al-Ali et al.		2013/0096405	A1	4/2013	Garfio
RE47,353	E	4/2019	Kiani et al.		2013/0096936	A1	4/2013	Sampath et al.
10,247,670	B2	4/2019	Ness et al.		2013/0131474	A1	5/2013	Gu et al.
10,251,585	B2	4/2019	Al-Ali et al.		2013/0190581	A1	7/2013	Al-Ali et al.
10,251,586	B2	4/2019	Lamego		2013/0204112	A1	8/2013	White et al.
10,255,994	B2	4/2019	Sampath et al.		2013/0211214	A1	8/2013	Olsen
10,258,265	B1	4/2019	Poeze et al.		2013/0243021	A1	9/2013	Siskavich
10,258,266	B1	4/2019	Poeze et al.		2013/0253334	A1	9/2013	Al-Ali et al.
10,265,024	B2	4/2019	Lee et al.		2013/0262730	A1	10/2013	Al-Ali et al.
10,271,748	B2	4/2019	Al-Ali		2013/0267804	A1	10/2013	Al-Ali
10,278,626	B2	5/2019	Schurman et al.		2013/0274572	A1	10/2013	Al-Ali et al.
10,278,648	B2	5/2019	Al-Ali et al.		2013/0296672	A1	11/2013	O'Neil et al.
10,279,247	B2	5/2019	Kiani		2013/0296713	A1	11/2013	Al-Ali et al.
10,285,626	B1	5/2019	Kestelli et al.		2013/0317370	A1	11/2013	Dalvi et al.
10,292,628	B1	5/2019	Poeze et al.		2013/0324808	A1	12/2013	Al-Ali et al.
10,292,657	B2	5/2019	Abdul-Hafiz et al.		2013/0331660	A1	12/2013	Al-Ali et al.
10,292,664	B2	5/2019	Al-Ali		2013/0331670	A1	12/2013	Kiani
10,299,708	B1	5/2019	Poeze et al.		2014/0012100	A1	1/2014	Al-Ali et al.
10,299,709	B2	5/2019	Perea et al.		2014/0034353	A1	2/2014	Al-Ali et al.
10,305,775	B2	5/2019	Lamego et al.		2014/0051953	A1	2/2014	Lamego et al.
10,307,111	B2	6/2019	Muhsin et al.		2014/0051955	A1	2/2014	Tiao et al.
10,325,681	B2	6/2019	Sampath et al.		2014/0066783	A1	3/2014	Kiani et al.
10,327,337	B2	6/2019	Triman et al.		2014/0073887	A1	3/2014	Petersen et al.
10,390,716	B2	8/2019	Shimuta		2014/0073960	A1	3/2014	Rodriguez-Llorente et al.
10,398,383	B2	9/2019	van Dinther et al.		2014/0077956	A1	3/2014	Sampath et al.
10,406,445	B2	9/2019	Vock et al.		2014/0081100	A1	3/2014	Muhsin et al.
10,416,079	B2	9/2019	Magnussen et al.		2014/0081175	A1	3/2014	Telfort
2002/0042558	A1	4/2002	Mendelson		2014/0094667	A1	4/2014	Schurman et al.
2003/0036690	A1	2/2003	Geddes et al.		2014/0100434	A1	4/2014	Diab et al.
2004/0054290	A1	3/2004	Chance		2014/0107493	A1	4/2014	Yuen et al.
2004/0114783	A1	6/2004	Spycher et al.		2014/0114199	A1	4/2014	Lamego et al.
2005/0277819	A1	12/2005	Kiani et al.		2014/0120564	A1	5/2014	Workman et al.
2006/0009607	A1	1/2006	Lutz et al.		2014/0121482	A1	5/2014	Merritt et al.
2006/0161054	A1	7/2006	Reuss et al.		2014/0121483	A1	5/2014	Kiani
2006/0182659	A1	8/2006	Unlu et al.		2014/0127137	A1	5/2014	Bellott et al.
2007/0282478	A1	12/2007	Al-Ali et al.		2014/0129702	A1	5/2014	Lamego et al.
2008/0030468	A1	2/2008	Al-Ali et al.		2014/0135588	A1	5/2014	Al-Ali et al.
2009/0177097	A1	7/2009	Ma et al.		2014/0142401	A1	5/2014	Al-Ali et al.
2009/0247984	A1	10/2009	Lamego et al.		2014/0163344	A1	6/2014	Al-Ali
2009/0275813	A1	11/2009	Davis		2014/0163402	A1	6/2014	Lamego et al.
2009/0275844	A1	11/2009	Al-Ali		2014/0166076	A1	6/2014	Kiani et al.
2010/0004518	A1	1/2010	Vo et al.		2014/0171146	A1	6/2014	Ma et al.
2010/0030040	A1	2/2010	Poeze et al.		2014/0171763	A1	6/2014	Diab
2010/0030043	A1	2/2010	Kuhn		2014/0180038	A1	6/2014	Kiani
2010/0113948	A1	5/2010	Yang et al.		2014/0180154	A1	6/2014	Sierra et al.
2011/0004106	A1	1/2011	Iwamiya et al.		2014/0180160	A1	6/2014	Brown et al.
2011/0082711	A1	4/2011	Poeze et al.		2014/0187973	A1	7/2014	Brown et al.
2011/0085721	A1	4/2011	Guyon et al.		2014/0192177	A1	7/2014	Bartula et al.
2011/0105854	A1	5/2011	Kiani et al.		2014/0194766	A1	7/2014	Al-Ali et al.
2011/0125060	A1	5/2011	Telfort et al.		2014/0206954	A1	7/2014	Yuen et al.
2011/0208015	A1	8/2011	Welch et al.		2014/0206963	A1	7/2014	Al-Ali
2011/0213212	A1	9/2011	Al-Ali		2014/0213864	A1	7/2014	Abdul-Hafiz et al.
2011/0230733	A1	9/2011	Al-Ali		2014/0221854	A1	8/2014	Wai
2011/0237969	A1	9/2011	Eckerbom et al.		2014/0266790	A1	9/2014	Al-Ali et al.
2011/0245697	A1	10/2011	Miettinen		2014/0275808	A1	9/2014	Poeze et al.
2011/0288383	A1	11/2011	Diab		2014/0275835	A1	9/2014	Lamego et al.
2011/0301444	A1	12/2011	Al-Ali		2014/0275871	A1	9/2014	Lamego et al.
2012/0041316	A1	2/2012	Al-Ali et al.		2014/0275872	A1	9/2014	Merritt et al.
2012/0046557	A1	2/2012	Kiani		2014/0275881	A1	9/2014	Lamego et al.
2012/0059267	A1	3/2012	Lamego et al.		2014/0276013	A1	9/2014	Muehlemann et al.
2012/0088984	A1	4/2012	Al-Ali et al.		2014/0276115	A1	9/2014	Dalvi et al.
2012/0150052	A1	6/2012	Buchheim et al.		2014/0276116	A1	9/2014	Takahashi et al.

(56)	References Cited			2016/0029933	A1	2/2016	Al-Ali et al.
	U.S. PATENT DOCUMENTS			2016/0038045	A1	2/2016	Shapiro
				2016/0041531	A1	2/2016	Mackie et al.
				2016/0045118	A1	2/2016	Kiani
2014/0288400	A1	9/2014	Diab et al.	2016/0051157	A1	2/2016	Waydo
2014/0303520	A1	10/2014	Telfort et al.	2016/0051158	A1	2/2016	Silva
2014/0316217	A1	10/2014	Purdon et al.	2016/0051205	A1	2/2016	Al-Ali et al.
2014/0316218	A1	10/2014	Purdon et al.	2016/0058302	A1	3/2016	Raghuram et al.
2014/0316228	A1	10/2014	Blank et al.	2016/0058309	A1	3/2016	Han
2014/0323825	A1	10/2014	Al-Ali et al.	2016/0058310	A1	3/2016	Lijima
2014/0323897	A1	10/2014	Brown et al.	2016/0058312	A1	3/2016	Han et al.
2014/0323898	A1	10/2014	Purdon et al.	2016/0058338	A1	3/2016	Schurman et al.
2014/0330092	A1	11/2014	Al-Ali et al.	2016/0058347	A1	3/2016	Reichgott et al.
2014/0330098	A1	11/2014	Merritt et al.	2016/0058356	A1	3/2016	Raghuram et al.
2014/0330099	A1	11/2014	Al-Ali et al.	2016/0058370	A1	3/2016	Raghuram et al.
2014/0336481	A1	11/2014	Shakespeare et al.	2016/0066823	A1	3/2016	Kind et al.
2014/0357966	A1	12/2014	Al-Ali et al.	2016/0066824	A1	3/2016	Al-Ali et al.
2014/0361147	A1	12/2014	Fei	2016/0066879	A1	3/2016	Telfort et al.
2014/0371548	A1	12/2014	Al-Ali et al.	2016/0071392	A1	3/2016	Hankey et al.
2014/0371632	A1	12/2014	Al-Ali et al.	2016/0072429	A1	3/2016	Kiani et al.
2014/0378784	A1	12/2014	Kiani et al.	2016/0073967	A1	3/2016	Lamego et al.
2014/0378844	A1	12/2014	Fei	2016/0081552	A1	3/2016	Wojtczuk et al.
2015/0005600	A1	1/2015	Blank et al.	2016/0095543	A1	4/2016	Telfort et al.
2015/0011907	A1	1/2015	Purdon et al.	2016/0095548	A1	4/2016	Al-Ali et al.
2015/0012231	A1	1/2015	Poeze et al.	2016/0103598	A1	4/2016	Al-Ali et al.
2015/0018650	A1	1/2015	Al-Ali et al.	2016/0106367	A1	4/2016	Jorov et al.
2015/0025406	A1	1/2015	Al-Ali	2016/0113527	A1	4/2016	Al-Ali et al.
2015/0032029	A1	1/2015	Al-Ali et al.	2016/0143548	A1	5/2016	Al-Ali
2015/0038859	A1	2/2015	Dalvi et al.	2016/0154950	A1	6/2016	Nakajima et al.
2015/0045637	A1	2/2015	Dalvi	2016/0157780	A1	6/2016	Rimminen et al.
2015/0045685	A1	2/2015	Al-Ali et al.	2016/0166182	A1	6/2016	Al-Ali et al.
2015/0051462	A1	2/2015	Olsen	2016/0166183	A1	6/2016	Poeze et al.
2015/0065889	A1	3/2015	Gandelman et al.	2016/0196388	A1	7/2016	Lamego
2015/0080754	A1	3/2015	Purdon et al.	2016/0197436	A1	7/2016	Barker et al.
2015/0087936	A1	3/2015	Al-Ali et al.	2016/0213281	A1	7/2016	Eckerbom et al.
2015/0094546	A1	4/2015	Al-Ali	2016/0213309	A1	7/2016	Sannholm et al.
2015/0097701	A1	4/2015	Al-Ali et al.	2016/0228043	A1	8/2016	O'Neil et al.
2015/0099324	A1	4/2015	Wojtczuk et al.	2016/0233632	A1	8/2016	Scruggs et al.
2015/0099950	A1	4/2015	Al-Ali et al.	2016/0234944	A1	8/2016	Schmidt et al.
2015/0099951	A1	4/2015	Al-Ali et al.	2016/0256058	A1	9/2016	Pham et al.
2015/0099955	A1	4/2015	Al-Ali et al.	2016/0256082	A1	9/2016	Ely et al.
2015/0101844	A1	4/2015	Al-Ali et al.	2016/0267238	A1	9/2016	Nag
2015/0106121	A1	4/2015	Muhsin et al.	2016/0270735	A1	9/2016	Diab et al.
2015/0112151	A1	4/2015	Muhsin et al.	2016/0283665	A1	9/2016	Sampath et al.
2015/0116076	A1	4/2015	Al-Ali et al.	2016/0287090	A1	10/2016	Al-Ali et al.
2015/0119725	A1	4/2015	Martin et al.	2016/0287107	A1	10/2016	Szabados et al.
2015/0126830	A1	5/2015	Schurman et al.	2016/0287181	A1	10/2016	Han et al.
2015/0133755	A1	5/2015	Smith et al.	2016/0287786	A1	10/2016	Kiani
2015/0140863	A1	5/2015	Al-Ali et al.	2016/0296169	A1	10/2016	McHale et al.
2015/0141781	A1	5/2015	Weber et al.	2016/0296173	A1	10/2016	Culbert
2015/0165312	A1	6/2015	Kiani	2016/0296174	A1	10/2016	Isikman et al.
2015/0173671	A1	6/2015	Paalasmaa et al.	2016/0310027	A1	10/2016	Han
2015/0196237	A1	7/2015	Lamego	2016/0310052	A1	10/2016	Al-Ali et al.
2015/0201874	A1	7/2015	Diab	2016/0314260	A1	10/2016	Kiani
2015/0208966	A1	7/2015	Al-Ali	2016/0324488	A1	11/2016	Olsen
2015/0216459	A1	8/2015	Al-Ali et al.	2016/0327984	A1	11/2016	Al-Ali et al.
2015/0230755	A1	8/2015	Al-Ali et al.	2016/0331332	A1	11/2016	Al-Ali
2015/0238722	A1	8/2015	Al-Ali	2016/0367173	A1	12/2016	Dalvi et al.
2015/0245773	A1	9/2015	Lamego et al.	2016/0378069	A1	12/2016	Rothkopf
2015/0245793	A1	9/2015	Al-Ali et al.	2016/0378071	A1	12/2016	Rothkopf
2015/0245794	A1	9/2015	Al-Ali	2017/0000394	A1	1/2017	Al-Ali et al.
2015/0255001	A1	9/2015	Haughav et al.	2017/0007134	A1	1/2017	Al-Ali et al.
2015/0257689	A1	9/2015	Al-Ali et al.	2017/0007183	A1	1/2017	Dusan et al.
2015/0272514	A1	10/2015	Kiani et al.	2017/0007198	A1	1/2017	Al-Ali et al.
2015/0281424	A1	10/2015	Vock et al.	2017/0010858	A1	1/2017	Prest et al.
2015/0318100	A1	11/2015	Rothkopf et al.	2017/0014083	A1	1/2017	Diab et al.
2015/0351697	A1	12/2015	Weber et al.	2017/0014084	A1	1/2017	Al-Ali et al.
2015/0351704	A1	12/2015	Kiani et al.	2017/0024748	A1	1/2017	Haider
2015/0359429	A1	12/2015	Al-Ali et al.	2017/0042488	A1	2/2017	Muhsin
2015/0366472	A1	12/2015	Kiani	2017/0055851	A1	3/2017	Al-Ali
2015/0366507	A1	12/2015	Blank	2017/0055882	A1	3/2017	Al-Ali et al.
2015/0374298	A1	12/2015	Al-Ali et al.	2017/0055887	A1	3/2017	Al-Ali
2015/0380875	A1	12/2015	Coverston et al.	2017/0055896	A1	3/2017	Al-Ali et al.
2016/0000362	A1	1/2016	Diab et al.	2017/0074897	A1	3/2017	Mermel et al.
2016/0007930	A1	1/2016	Weber et al.	2017/0079594	A1	3/2017	Telfort et al.
2016/0019360	A1	1/2016	Pahwa et al.	2017/0084133	A1	3/2017	Cardinali et al.
2016/0022160	A1	1/2016	Pi et al.	2017/0086689	A1	3/2017	Shui et al.
2016/0023245	A1	1/2016	Zadesky et al.	2017/0086723	A1	3/2017	Al-Ali et al.
2016/0029932	A1	2/2016	Al-Ali	2017/0086742	A1	3/2017	Harrison-Noonan et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2017/0086743	A1	3/2017	Bushnell et al.	2018/0130325	A1	5/2018	Kiani et al.
2017/0094450	A1	3/2017	Tu et al.	2018/0132769	A1	5/2018	Weber et al.
2017/0143281	A1	5/2017	Olsen	2018/0132770	A1	5/2018	Lamego
2017/0147774	A1	5/2017	Kiani	2018/0146901	A1	5/2018	Al-Ali et al.
2017/0156620	A1	6/2017	Al-Ali et al.	2018/0146902	A1	5/2018	Kiani et al.
2017/0164884	A1	6/2017	Culbert et al.	2018/0153418	A1	6/2018	Sullivan et al.
2017/0172435	A1	6/2017	Presura	2018/0153442	A1	6/2018	Eckerbom et al.
2017/0172476	A1	6/2017	Schilthuizen	2018/0153446	A1	6/2018	Kiani
2017/0173632	A1	6/2017	Al-Ali	2018/0153447	A1	6/2018	Al-Ali et al.
2017/0187146	A1	6/2017	Kiani et al.	2018/0153448	A1	6/2018	Weber et al.
2017/0188919	A1	7/2017	Al-Ali et al.	2018/0161499	A1	6/2018	Al-Ali et al.
2017/0196464	A1	7/2017	Jansen et al.	2018/0164853	A1	6/2018	Myers et al.
2017/0196470	A1	7/2017	Lamego et al.	2018/0168491	A1	6/2018	Al-Ali et al.
2017/0202505	A1	7/2017	Kirenko et al.	2018/0174679	A1	6/2018	Sampath et al.
2017/0209095	A1	7/2017	Wagner et al.	2018/0174680	A1	6/2018	Sampath et al.
2017/0224262	A1	8/2017	Al-Ali	2018/0182484	A1	6/2018	Sampath et al.
2017/0228516	A1	8/2017	Sampath et al.	2018/0184917	A1	7/2018	Kiani
2017/0245790	A1	8/2017	Al-Ali et al.	2018/0192924	A1	7/2018	Al-Ali
2017/0248446	A1	8/2017	Gowreesunker et al.	2018/0192953	A1	7/2018	Shreim et al.
2017/0251974	A1	9/2017	Shreim et al.	2018/0192955	A1	7/2018	Al-Ali et al.
2017/0251975	A1	9/2017	Shreim et al.	2018/0196514	A1	7/2018	Allec et al.
2017/0258403	A1	9/2017	Abdul-Hafiz et al.	2018/0199871	A1	7/2018	Pauley et al.
2017/0273619	A1	9/2017	Alvarado et al.	2018/0206795	A1	7/2018	Al-Ali
2017/0281024	A1	10/2017	Narasimhan et al.	2018/0206815	A1	7/2018	Telfort
2017/0293727	A1	10/2017	Klaassen et al.	2018/0213583	A1	7/2018	Al-Ali
2017/0311851	A1	11/2017	Schurman et al.	2018/0214031	A1	8/2018	Kiani et al.
2017/0311891	A1	11/2017	Kiani et al.	2018/0214090	A1	8/2018	Al-Ali et al.
2017/0325698	A1	11/2017	Allec et al.	2018/0218792	A1	8/2018	Muhsin et al.
2017/0325728	A1	11/2017	Al-Ali et al.	2018/0225960	A1	8/2018	Al-Ali et al.
2017/0325744	A1	11/2017	Allec et al.	2018/0228414	A1	8/2018	Shao et al.
2017/0332976	A1	11/2017	Al-Ali et al.	2018/0238718	A1	8/2018	Dalvi
2017/0340209	A1	11/2017	Klaassen et al.	2018/0238734	A1	8/2018	Hotelling et al.
2017/0340219	A1	11/2017	Sullivan et al.	2018/0242853	A1	8/2018	Al-Ali
2017/0340293	A1	11/2017	Al-Ali et al.	2018/0242921	A1	8/2018	Muhsin et al.
2017/0347885	A1	12/2017	Tan et al.	2018/0242923	A1	8/2018	Al-Ali et al.
2017/0354332	A1	12/2017	Lamego	2018/0242924	A1	8/2018	Barker et al.
2017/0354795	A1	12/2017	Blahnik et al.	2018/0242926	A1	8/2018	Muhsin et al.
2017/0358239	A1	12/2017	Arney et al.	2018/0242926	A1	8/2018	Muhsin et al.
2017/0358240	A1	12/2017	Blahnik et al.	2018/0247353	A1	8/2018	Al-Ali et al.
2017/0358242	A1	12/2017	Thompson et al.	2018/0247712	A1	8/2018	Muhsin et al.
2017/0360306	A1	12/2017	Narasimhan et al.	2018/0249933	A1	9/2018	Schurman et al.
2017/0360310	A1	12/2017	Kiani et al.	2018/0253947	A1	9/2018	Muhsin et al.
2017/0366657	A1	12/2017	Thompson et al.	2018/0256087	A1	9/2018	Al-Ali et al.
2017/0367632	A1	12/2017	Al-Ali et al.	2018/0256113	A1	9/2018	Weber et al.
2018/0008146	A1	1/2018	Al-Ali et al.	2018/0279956	A1	10/2018	Waydo et al.
2018/0013562	A1	1/2018	Haider et al.	2018/0285094	A1	10/2018	Housel et al.
2018/0014752	A1	1/2018	Al-Ali et al.	2018/0289325	A1	10/2018	Poeze et al.
2018/0014781	A1	1/2018	Clavelle et al.	2018/0289337	A1	10/2018	Al-Ali et al.
2018/0025287	A1	1/2018	Mathew et al.	2018/0296161	A1	10/2018	Shreim et al.
2018/0056129	A1	1/2018	Narasimha Rao et al.	2018/0300919	A1	10/2018	Muhsin et al.
2018/0028124	A1	2/2018	Al-Ali et al.	2018/0310822	A1	11/2018	Indorf et al.
2018/0042556	A1	2/2018	Shahparnia et al.	2018/0310823	A1	11/2018	Al-Ali et al.
2018/0049694	A1	2/2018	Singh Alvarado et al.	2018/0317826	A1	11/2018	Muhsin
2018/0050235	A1	2/2018	Tan et al.	2018/0317841	A1	11/2018	Novak, Jr.
2018/0055375	A1	3/2018	Martinez et al.	2018/0333055	A1	11/2018	Lamego et al.
2018/0055385	A1	3/2018	Al-Ali	2018/0333087	A1	11/2018	Al-Ali
2018/0055390	A1	3/2018	Kiani et al.	2019/0000317	A1	1/2019	Muhsin et al.
2018/0055430	A1	3/2018	Diab et al.	2019/0000362	A1	1/2019	Kiani et al.
2018/0055439	A1	3/2018	Pham et al.	2019/0015023	A1	1/2019	Monfre
2018/0064381	A1	3/2018	Shakespeare et al.	2019/0021638	A1	1/2019	Al-Ali et al.
2018/0069776	A1	3/2018	Lamego et al.	2019/0029574	A1	1/2019	Schurman et al.
2018/0070867	A1	3/2018	Smith et al.	2019/0029578	A1	1/2019	Al-Ali et al.
2018/0078151	A1	3/2018	Allec et al.	2019/0038143	A1	2/2019	Al-Ali
2018/0078182	A1	3/2018	Chen et al.	2019/0058280	A1	2/2019	Al-Ali et al.
2018/0082767	A1	3/2018	Al-Ali et al.	2019/0058281	A1	2/2019	Al-Ali et al.
2018/0085068	A1	3/2018	Telfort	2019/0069813	A1	3/2019	Al-Ali
2018/0087937	A1	3/2018	Al-Ali et al.	2019/0069814	A1	3/2019	Al-Ali
2018/0103874	A1	4/2018	Lee et al.	2019/0076028	A1	3/2019	Al-Ali et al.
2018/0103905	A1	4/2018	Kiani	2019/0082979	A1	3/2019	Al-Ali et al.
2018/0110469	A1	4/2018	Maani et al.	2019/0090748	A1	3/2019	Al-Ali
2018/0110478	A1	4/2018	Al-Ali	2019/0090760	A1	3/2019	Kinast et al.
2018/0116575	A1	5/2018	Perea et al.	2019/0090764	A1	3/2019	Al-Ali
2018/0125368	A1	5/2018	Lamego et al.	2019/0104973	A1	4/2019	Poeze et al.
2018/0125430	A1	5/2018	Al-Ali et al.	2019/0110719	A1	4/2019	Poeze et al.
2018/0125445	A1	5/2018	Telfort et al.	2019/0117070	A1	4/2019	Muhsin et al.
				2019/0117139	A1	4/2019	Al-Ali et al.
				2019/0117140	A1	4/2019	Al-Ali et al.
				2019/0117141	A1	4/2019	Al-Ali
				2019/0117930	A1	4/2019	Al-Ali
				2019/0122763	A1	4/2019	Sampath et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2019/0133525	A1	5/2019	Al-Ali et al.
2019/0142283	A1	5/2019	Lamego et al.
2019/0142344	A1	5/2019	Telfort et al.
2019/0150800	A1	5/2019	Poeze et al.
2019/0150856	A1	5/2019	Kiani et al.
2019/0167161	A1	6/2019	Al-Ali et al.
2019/0175019	A1	6/2019	Al-Ali et al.
2019/0192076	A1	6/2019	McHale et al.

FOREIGN PATENT DOCUMENTS

CN	103906468	A	7/2014
EP	0630208	A1	12/1994
EP	0770349	A1	5/1997
EP	0781527	A1	7/1997
EP	0880936	A2	12/1998
EP	0985373	A1	3/2000
EP	1124609	B1	8/2001
EP	2277440	A1	1/2011
GB	2243691	A	11/1991
JP	H09257508	A	10/1997
JP	H10314133	A	12/1998
JP	H1170086	A	3/1999
JP	2919326	B2	7/1999
KR	2010/0091592	A	8/2010
KR	20100091592	A	8/2010
WO	WO 1994/23643	A1	10/1994
WO	WO 1995/000070	A1	1/1995
WO	WO 1995000070	A1	1/1995
WO	WO 1996/027325	A1	9/1996
WO	WO 1997/00923	A1	1/1997
WO	WO 1997009923	A1	3/1997
WO	WO 1996/063883	A1	12/1999
WO	WO 1999063883	A1	12/1999
WO	WO 2000/028892	A1	5/2000
WO	WO 2000028892	A1	5/2000
WO	WO 02/028274	A	4/2002
WO	WO 2006/113070	A1	10/2006
WO	WO 2008/107238	A1	9/2008
WO	WO 2009/001988	A1	12/2008
WO	WO 2009/137524	A1	11/2009
WO	WO 2011/069122	A1	6/2011
WO	WO 2013/030744	A1	3/2013
WO	WO 2013030744	A1	3/2013
WO	WO 2013/106607	A1	7/2013
WO	WO 2013/181368	A1	12/2013
WO	WO 2014/18447	A1	1/2014
WO	WO 2014/115075	A1	7/2014
WO	WO 2014/153200	A1	9/2014
WO	WO 2014/178793	A1	11/2014
WO	WO 2014184447	A1	11/2014
WO	WO 2015/187732	A1	12/2015
WO	WO 2016/066312	A1	5/2016

OTHER PUBLICATIONS

"Heart Rate Measurement Technology" EPSON, 2019.
 "Introducing Easy Pulse: A DIY Photoplethysmographic Sensor for Measuring Heart Rate", Embedded Lab, 2012.
 "PerformTek Precision Biometrics", ValenCell, 2013.
 "Galaxy S5 Explained: The Heart Rate Sensor and S Health 3.0." Samsung Global Newsroom, 2014.
 "Withings Pulse: Activity Tracker—Sleep Analyzer Hear Rate Analyzer; Installation and Operating Instructions", Withings, 2015.
 Jan. 9, 2020 Complaint for (1) Patent Infringement (2) Trade Secret Misappropriation and (3) Ownership of Patents and Demand for Jury Trial, *Masimo Corporation and Cercacor Laboratories, Inc. v. Apple Inc.*, Case No. 8:20-cv-00048, 64 pages.
 Anliker et al., "AMON: a wearable multiparameter medical monitoring and alert system," in *IEEE Transactions on Information Technology in Biomedicine*, vol. 8, No. 4, Dec. 2004.

Asada, et al. "Mobile Monitoring with Wearable Photoplethysmographic Biosensors", *IEEE Engineering in Medicine and Biology Magazine*, 2003.
 Bagha, et al. "A Real Time Analysis of PPG Signal for Measurement of SpO₂ and Pulse Rate", *International Journal of Computer Applications* (0975-8887), vol. 36—No. 11, 2011.
 Branche, et al. "Measurement Reproducibility and Sensor Placement Considerations in Designing a Wearable Pulse Oximeter for Military Applications", *IEEE*, 2004.
 Branche, et al. "Signal Quality and Power Consumption of a New Prototype Reflectance Pulse Oximeter Sensor", *IEEE*, 2005.
 Celka, et al. "Motion resistant earphone located infrared based heart rate measurement device", *Research Gate*, 2004.
 Comtois, et al. "A Comparative Evaluation of Adaptive Noise Cancellation Algorithms for Minimizing Motion Artifacts in a Forehead-Mounted Wearable Pulse Oximeter", *IEEE*, 2007.
 Comtois, et al. "A Noise Reference Input to an Adaptive Filter Algorithm for Signal Processing in a Wearable Pulse Oximeter", *IEEE*, 2007.
 Conway, et al. "Wearable computer as a multi-parametric monitor for physiological signals," *Proceedings IEEE International Symposium on Bio-Informatics and Biomedical Engineering*, pp. 236-242, 2000.
 Crilly, et al. "An Integrated Pulse Oximeter System for Telemedicine Applications", *IEEE Instrumentation and Measurement Technology Conference*, 1997.
 Dassel, et al. "Reflective Pulse Oximetry at the Forehead Improves by Pressure on the Probe", *J. Clin. Monit.*, 11:237-244, 1995.
 Dresher, et al. "A New Reflectance Pulse Oximeter Housing to Reduce Contact Pressure Effects", *IEEE*, 2006.
 Dresher, et al. "Reflectance Forehead Pulse Oximetry: Effects of Contact Pressure During Walking", *IEEE*, 2006.
 Faulkner, "Apple Watch Heart Rate Sensor: Everything You Need to Know." *TechRadar India*, TechRadar, 2015.
 Gibbs, et al. "Active motion artifact cancellation for wearable health monitoring sensors using collocated MEMS accelerometers", *SPIE*, vol. 5765, 2005.
 Hayes, "How the Sensors inside Fitness Tracker Work." *Digital Trends*, 2014.
 Heerlein, et al. "LED-Based Sensor for Wearable Fitness Tracking Products", *EDN*, 2014.
 Johnston, et al. "Extracting Breathing Rate Information from a Wearable Reflectance Pulse Oximeter Sensor", *IEEE*, 2004.
 Johnston, et al. "Extracting Heart Rate Variability From a Wearable Reflectance Pulse Oximeter", *IEEE*, 2005.
 Keikhosravi, et al. "Effect of deep breath on the correlation between the wrist and finger photoplethysmograms", pp. 135-138, 2012.
 Kilbane, et al. "Design Considerations for Wrist-Wearable Heart Rate Monitors," *Arrow Intelligent Systems*, 2015.
 König, V. et al., "Reflectance Pulse Oximetry—Principles and Obstetric Application in the Zurich System," *J Clin Monit* 1998; 14: 403-412.
 Konstantas, et al. "Mobile Patient Monitoring: The MobiHealth System", *Research Gate*, 2004.
 Kuboyama, "Motion Artifact Cancellation for Wearable Photoplethysmographic Sensor", *Massachusetts Institute of Technology*, pp. 1-66, 2010.
 Kviesis-Kipge, et al., "Miniature Wireless Photoplethysmography Devices: Integration in Garments and Test Measurements", *SPIE* vol. 8427 84273H-6, 2012.
 Lee, et al. "Development of a Wristwatch-Type PPG Array Sensor Module", *IEEE*, 2011.
 Lin, et al. "RTWPMS: A Real-Time Wireless Physiological Monitoring System", *IEEE Transactions on Information Technology in Biomedicine*, vol. 10, No. 4, 2006.
 Lingaiah, et al. "Measurement of Pulse rate and SpO₂ using Pulse Oximeter developed using LabVIEW", *IOSR Journal of Electrical and Electronics Engineering (IOSR-JEEE)*, e-ISSN: 2278-1676, p-ISSN: 2320-3331, vol. 8, Issue 1, pp. 22-26, 2013.
 Lukowicz, et al. "AMON: a wearable medical computer for high risk patients," *Proceedings. Sixth International Symposium on Wearable Computers*, 2002.
 Lukowicz, et al. "The Weararm Modular, Low-Power Computing Core", *IEEE Micro*, 2001.

(56)

References Cited**OTHER PUBLICATIONS**

- Mapar "Wearable Sensor for Continuously Cigilant Blood Perfusion and Oxygenation", UCLA, 2012.
- Mendelson et al., "Noninvasive Pulse Oximetry Utilizing Skin Reflectance Photoplethysmography", IEEE Biomedical Engineering, vol. 35 No. 10, 1988.
- Mendelson et al., "A Mobile PDA-Based Wireless Pulse Oximeter," Proceedings of the IASTED International Conference Telehealth, Jul. 19-21, 2005, pp. 1-6.
- Mendelson et al., "A Wearable Reflectance Pulse Oximeter for Remote Physiological Monitoring," Proceedings of the 28th IEEE EMBS Annual International Conference, Aug. 30-Sep. 3, 2006, pp. 912-915.
- Mendelson et al., "Accelerometry-Based Adaptive Noise Cancellation for Remote Physiological Monitoring by a Wearable Pulse Oximeter," Proceedings of the 3rd IASTED International Conference TELEHEALTH, May 31-Jun. 1, 2007, pp. 28-33.
- Mendelson et al., "Measurement Site and Photodetector Size Considerations in Optimizing Power Consumption of a Wearable Reflectance Pulse Oximeter," Proceedings of the 25th Annual International Conference of the IEEE EMBS, Sep. 17-21, 2003, pp. 3016-3019.
- Mendelson et al., "Minimization of LED Power Consumption in the Design of a Wearable Pulse Oximeter," Proceedings of the IASTED International Conference Biomedical Engineering, Jun. 25-27, 2003, 6 pages.
- Oliver et al., "HealthGear: A Real-time Wearable System for Monitoring and Analyzing Physiological Signals," Proceedings of the International Workshop on Wearable and Implantable Body Sensor Networks, IEEE Computer Society, 2006, pp. 1-4.
- Pandian et al., "Smart Vest: Wearable Multi-Parameter Remote Physiological Monitoring System," Medical Engineering & Physics 30, 2008, pp. 466-477.
- Phattrapayoon, et al., "Accuracy of Pulse Oximeter Readings From Probe Placement on Newborn Wrist and Ankle", Journal of Perinatology, vol. 32, pp. 276-280, 2012.
- Poh et al., "Motion-Tolerant Magnetic Earring Sensor and Wireless Earpiece for Wearable Photoplethysmography", IEEE Transactions on Information Technology in Biomedicine, vol. 14, No. 3, 2010.
- Pujary, "Investigation of Photodetector Optimization in Reducing Power Consumption by a Noninvasive Pulse Oximeter Sensor", Worcester Polytechnic Institute, pp. 1-133, 2004.
- Purjary et al., "Photodetector Size Considerations in the Design of a Noninvasive Reflectance Pulse Oximeter for Telemedicine Applications", IEEE, 2003.
- Renevey et al., "Wrist-Located Pulse Detection Using IR Signals, Activity and Nonlinear Artifact Cancellation," Proceedings of the 23rd Annual EMBS International Conference, Oct. 25-28, 2001, pp. 3030-3033.
- Rhee et al., "Artifact-Resistant Power-Efficient Design of Finger-Ring Plethysmographic Sensors," IEEE Transactions on Biomedical Engineering, vol. 48, No. 7, Jul. 2001, pp. 795-805.
- Rhee et al., "Artifact-Resistant, Power Efficient Design of Finger-Ring Plethysmographic Sensors, Part I: Design and Analysis," 22nd Annual International Conference IEEE Engineering in Medicine and Biology Society, Jul. 23-28, 2000, pp. 2792-2795.
- Rhee et al., "Design of a Artifact-Free Wearable Plethysmographic Sensor," 21st Annual International Conference IEEE Engineering in Medicine and Biology Society, Oct. 13-16, 1999, p. 786.
- Rhee et al., "The Ring Sensor: a New Ambulatory Wearable Sensor for Twenty-Four Hour Patient Monitoring," Proceedings of the 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society, Oct. 29-Nov. 1, 1998, 4 pages.
- Savage et al., "Optimizing Power Consumption in the Design of a Wearable Wireless Telesensor: Comparison of Pulse Oximeter Modes," Proceedings of IEEE 29th Annual Nonheust Bioengineering Conference, 2003, pp. 150-151.
- Scully, et al., "Physiological Parameter Monitoring from Optical Recordings with a Mobile Phone", IEEE Trans Biomed Eng. ; 59(2): 303-306, 2012.
- Shaltis et al., "Novel Design for a Wearable, Rapidly Depolyable, Wireless Noninvasive Triage Sensor," Proceedings of the 2005 IEEE, Engineering in Medicine and Biology 27th Annual Conference, Sep. 1-4, 2005, pp. 3567-3570.
- Shin et al., "A Novel Headset with a Transmissive PPG Sensor for Heart Rate Measurement", ICBME 2008, Proceedings 23, pp. 519-522, 2009.
- Shyamkumar, et al. "Wearable Wireless Cardiovascular Monitoring Using Textile-Based Nanosensor and Nanomaterial Systems", Electronics 3, pp. 504-520, 2014.
- Stojanovic, et al. "Design of an Oximeter Based on LED-LED Configuration and FPGA Technology", Sensors, 13, 574-586, 2013.
- Stuban, et al. "Optimal filter bandwidth for pulse oximetry", Rev. Sci. Instrum. 83, 104708, 2012.
- Tamannagari, "Power Efficient Design of Finger-Ring Sensor for Patient Monitoring," Master of Science in Electrical Engineering, The University of Texas at San Antonio, College of Engineering, Department of Electrical Engineering, Dec. 2008, 74 pages.
- Tamura et al. "Wearable Photoplethysmographic Sensors—Past and Present", Electronics, 3, 282-302, 2014.
- Tofs, et al. "Body-Heat Powered Autonomous Pulse Oximeter", IEEE Sensors, 2006.
- Townsend, et al. "Pulse Oximetry", Medical Electronics, 2001.
- Tura, et al., "A Medical Wearable Device with Wireless Bluetooth-based Data Transmission", Measurement Science Review, vol. 3, Section 2, 2003.
- Vogel, et al. "In-Ear Vital Signs Monitoring Using a Novel Microoptic Reflective Sensor", IEEE Transactions on Information Technology in Biomedicine, vol. 13, No. 6, 2009.
- Warren, et al. "Designing Smart Health Care Technology into the Home of the Future", United States: N. p., 1999.
- Written Opinion received in International Application No. PCT/US2016/040190, dated Jan. 2, 2018.
- Yamashita et al., "Development of a Ring-Type Vital Sign Telemeter," Biotelemetry XIII, Mar. 26-31, 1995, pp. 145-150.
- Yan, et al. "An Efficient Motion-Resistant Method for Wearable Pulse Oximeter", IEEE Transactions on Information Technology in Biomedicine, vol. 12, No. 3, 2008.
- Yang, et al. "A Twenty-Four Hour Tele-Nursing System Using a Ring Sensor", Proc. of 1998 Int. Conf. on Robotics and Automation, 1998.
- Yang, et al. "Development of the Ring Sensor for Healthcare Automation", Robotics and Autonomous Systems, 30, pp. 273-281, 2000.
- Yang, et al. "SpO2 and Heart Rate Measurement with Wearable Watch Based on PPG", IEEE, 2015.
- Zhai, et al. "A Wireless Sensor Network for Hospital Patient Monitoring", University of Calgary, 2007.




FIG. 1
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6
(PRIOR ART)




FIG. 7A




FIG. 7B




FIG. 8

1

PHYSIOLOGICAL MONITORING DEVICES, SYSTEMS, AND METHODS

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 16/532,065 filed Aug. 5, 2019, which is a continuation of U.S. patent application Ser. No. 16/226,249 filed Dec. 19, 2018, which is a continuation of U.S. patent application Ser. No. 15/195,199 filed Jun. 28, 2016, which claims priority benefit under 35 U.S.C. § 119(e) from U.S. Provisional Application No. 62/188,430, filed Jul. 2, 2015, which is incorporated by reference herein. Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57.

FIELD OF THE DISCLOSURE

The present disclosure relates to the field of non-invasive optical-based physiological monitoring sensors, and more particularly to systems, devices and methods for improving the non-invasive measurement accuracy of oxygen saturation, among other physiological parameters.

BACKGROUND

Spectroscopy is a common technique for measuring the concentration of organic and some inorganic constituents of a solution. The theoretical basis of this technique is the Beer-Lambert law, which states that the concentration C , of an absorbent in solution can be determined by the intensity of light transmitted through the solution, knowing the path-length d_{λ} , the intensity of the incident light $I_{0,\lambda}$, and the extinction coefficient $\epsilon_{1,\lambda}$ at a particular wavelength λ .

In generalized form, the Beer-Lambert law is expressed as:

$$I_{\lambda} = I_{0,\lambda} e^{-d_{\lambda} \mu_{a,\lambda}} \quad (1)$$

$$\mu_{a,\lambda} = \sum_{i=1}^n \epsilon_{i,\lambda} \cdot C_i \quad (2)$$

where $\mu_{a,\lambda}$ is the bulk absorption coefficient and represents the probability of absorption per unit length. The minimum number of discrete wavelengths that are required to solve equations 1 and 2 is the number of significant absorbers that are present in the solution.

A practical application of this technique is pulse oximetry, which utilizes a noninvasive sensor to measure oxygen saturation and pulse rate, among other physiological parameters. Pulse oximetry relies on a sensor attached externally to the patient to output signals indicative of various physiological parameters, such as a patient's blood constituents and/or analytes, including for example a percent value for arterial oxygen saturation, among other physiological parameters. The sensor has an emitter that transmits optical radiation of one or more wavelengths into a tissue site and a detector that responds to the intensity of the optical radiation after absorption by pulsatile arterial blood flowing within the tissue site. Based upon this response, a processor determines the relative concentrations of oxygenated hemoglobin (HbO₂) and deoxygenated hemoglobin (Hb) in the

2

blood so as to derive oxygen saturation, which can provide early detection of potentially hazardous decreases in a patient's oxygen supply.

A pulse oximetry system generally includes a patient monitor, a communications medium such as a cable, and/or a physiological sensor having one or more light emitters and a detector, such as one or more light-emitting diodes (LEDs) and a photodetector. The sensor is attached to a tissue site, such as a finger, toe, earlobe, nose, hand, foot, or other site having pulsatile blood flow which can be penetrated by light from the one or more emitters. The detector is responsive to the emitted light after attenuation or reflection by pulsatile blood flowing in the tissue site. The detector outputs a detector signal to the monitor over the communication medium. The monitor processes the signal to provide a numerical readout of physiological parameters such as oxygen saturation (SpO₂) and/or pulse rate. A pulse oximetry sensor is described in U.S. Pat. No. 6,088,607 entitled Low Noise Optical Probe; pulse oximetry signal processing is described in U.S. Pat. Nos. 6,650,917 and 6,699,194 entitled Signal Processing Apparatus and Signal Processing Apparatus and Method, respectively; a pulse oximeter monitor is described in U.S. Pat. No. 6,584,336 entitled Universal/Upgrading Pulse Oximeter; all of which are assigned to Masimo Corporation, Irvine, Calif., and each is incorporated by reference herein in its entirety.

There are many sources of measurement error introduced to pulse oximetry systems. Some such sources of error include the pulse oximetry system's electronic components, including emitters and detectors, as well as chemical and structural physiological differences between patients. Another source of measurement error is the effect of multiple scattering of photons as the photons pass through the patient's tissue (arterial blood) and arrive at the sensor's light detector.

SUMMARY

This disclosure describes embodiments of non-invasive methods, devices, and systems for measuring blood constituents, analytes, and/or substances such as, by way of non-limiting example, oxygen, carboxyhemoglobin, methemoglobin, total hemoglobin, glucose, proteins, lipids, a percentage thereof (e.g., saturation), pulse rate, perfusion index, oxygen content, total hemoglobin, Oxygen Reserve Index™ (ORI™) or for measuring many other physiologically relevant patient characteristics. These characteristics can relate to, for example, pulse rate, hydration, trending information and analysis, and the like.

In an embodiment, an optical physiological measurement system includes an emitter configured to emit light of one or more wavelengths. The system also includes a diffuser configured to receive the emitted light, to spread the received light, and to emit the spread light over a larger tissue area than would otherwise be penetrated by the emitter directly emitting light at a tissue measurement site. The tissue measurement site can include, such as, for example, a finger, a wrist, or the like. The system further includes a concentrator configured to receive the spread light after it has been attenuated by or reflected from the tissue measurement site. The concentrator is also configured to collect and concentrate the received light and to emit the concentrated light to a detector. The detector is configured to detect the concentrated light and to transmit a signal indicative of the detected light. The system also includes a processor configured to receive the transmitted signal indicative of the detected light and to determine, based on an

3

amount of absorption, an analyte of interest, such as, for example, arterial oxygen saturation or other parameter, in the tissue measurement site.

In certain embodiments of the present disclosure, the diffuser comprises glass, ground glass, glass beads, opal glass, or a microlens-based, band-limited, engineered diffuser that can deliver efficient and uniform illumination. In some embodiments the diffuser is further configured to define a surface area shape by which the emitted spread light is distributed onto a surface of the tissue measurement site. The defined surface area shape can include, by way of non-limiting example, a shape that is substantially rectangular, square, circular, oval, or annular, among others.

According to some embodiments, the optical physiological measurement system includes an optical filter having a light-absorbing surface that faces the tissue measurement site. The optical filter also has an opening that is configured to allow the spread light, after being attenuated by the tissue measurement site, to be received by the concentrator. In an embodiment, the opening has dimensions, wherein the dimensions of the opening are similar to the defined surface area shape by which the emitted spread light is distributed onto the surface of the tissue measurement site. In an embodiment, the opening has dimensions that are larger than the defined surface area shape by which the emitted spread light is distributed onto the surface of the tissue measurement site. In other embodiments, the dimensions of the opening in the optical filter are not the same as the diffuser opening, but the dimensions are larger than the detector package.

In other embodiments of the present disclosure, the concentrator comprises glass, ground glass, glass beads, opal glass, or a compound parabolic concentrator. In some embodiments the concentrator comprises a cylindrical structure having a truncated circular conical structure on top. The truncated section is adjacent the detector. The light concentrator is structured to receive the emitted optical radiation, after reflection by the tissue measurement site, and to direct the reflected light to the detector.

In accordance with certain embodiments of the present disclosure, the processor is configured to determine an average level of the light detected by the detector. The average level of light is used to determine a physiological parameter in the tissue measurement site.

According to another embodiment, a method to determine a constituent or analyte in a patient's blood is disclosed. The method includes emitting, from an emitter, light of at least one wavelength; spreading, with a diffuser, the emitted light and emitting the spread light from the diffuser to a tissue measurement site; receiving, by a concentrator, the spread light after the spread light has been attenuated by the tissue measurement site; concentrating, by the concentrator, the received light and emitting the concentrated light from the concentrator to a detector; detecting, with the detector, the emitted concentrated light; transmitting, from the detector, a signal responsive to the detected light; receiving, by a processor, the transmitted signal responsive to the detected light; and processing, by the processor, the received signal responsive to the detected light to determine a physiological parameter.

In some embodiments, the method to determine a constituent or analyte in a patient's blood includes filtering, with a light-absorbing detector filter, scattered portions of the emitted spread light. According to an embodiment, the light-absorbing detector filter is substantially rectangular in shape and has outer dimensions in the range of approximately 1-5 cm in width and approximately 2-8 cm in length,

4

and has an opening through which emitted light may pass, the opening having dimensions in the range of approximately 0.25-3 cm in width and approximately 1-7 cm in length. In another embodiment, the light-absorbing detector filter is substantially square in shape and has outer dimensions in the range of approximately 0.25-10 cm², and has an opening through which emitted light may pass, the opening having dimensions in the range of approximately 0.1-8 cm². In yet another embodiment, the light-absorbing detector filter is substantially rectangular in shape and has outer dimensions of approximately 3 cm in width and approximately 6 cm in length, and has an opening through which emitted light may pass, the opening having dimensions of approximately 1.5 cm in width and approximately 4 cm in length.

In still other embodiments of the method to determine a constituent or analyte in a patient's blood, spreading, with a diffuser, the emitted light and emitting the spread light from the diffuser to a tissue measurement site is performed by at least one of a glass diffuser, a ground glass diffuser, a glass bead diffuser, an opal glass diffuser, and an engineered diffuser. In some embodiments the emitted spread light is emitted with a substantially uniform intensity profile. And in some embodiments, emitting the spread light from the diffuser to the tissue measurement site includes spreading the emitted light so as to define a surface area shape by which the emitted spread light is distributed onto a surface of the tissue measurement site.

According to yet another embodiment, a pulse oximeter is disclosed. The pulse oximeter includes an emitter configured to emit light at one or more wavelengths. The pulse oximeter also includes a diffuser configured to receive the emitted light, to spread the received light, and to emit the spread light directed at a tissue measurement site. The pulse oximeter also includes a detector configured to detect the emitted spread light after being attenuated by or reflected from the tissue measurement site and to transmit a signal indicative of the detected light. The pulse oximeter also includes a processor configured to receive the transmitted signal and to process the received signal to determine an average absorbance of a blood constituent or analyte in the tissue measurement site over a larger measurement site area than can be performed with a point light source or point detector. In some embodiments, the diffuser is further configured to define a surface area shape by which the emitted spread light is distributed onto a surface of the tissue measurement site, and the detector is further configured to have a detection area corresponding to the defined surface area shape by which the emitted spread light is distributed onto the surface of the tissue measurement site. According to some embodiments, the detector comprises an array of detectors configured to cover the detection area. In still other embodiments, the processor is further configured to determine an average of the detected light.

For purposes of summarizing, certain aspects, advantages and novel features of the disclosure have been described herein. It is to be understood that not necessarily all such advantages can be achieved in accordance with any particular embodiment of the systems, devices and/or methods disclosed herein. Thus, the subject matter of the disclosure herein can be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as can be taught or suggested herein.

BRIEF DESCRIPTION OF THE DRAWINGS

Throughout the drawings, reference numbers can be used to indicate correspondence between referenced ele-

5

ments. The drawings are provided to illustrate embodiments of the disclosure described herein and not to limit the scope thereof.

FIG. 1 illustrates a conventional approach to two-dimensional pulse oximetry in which the emitter is configured to emit optical radiation as a point optical source.

FIG. 2 illustrates the disclosed three-dimensional approach to pulse oximetry in which the emitted light irradiates a substantially larger volume of tissue as compared to the point source approach described with respect to FIG. 1.

FIG. 3 illustrates schematically a side view of a three-dimensional pulse oximetry sensor according to an embodiment of the present disclosure.

FIG. 4A is a top view of a portion of a three-dimensional pulse oximetry sensor according to an embodiment of the present disclosure.

FIG. 4B illustrates the top view of a portion of the three-dimensional pulse oximetry sensor shown in FIG. 4A, with the addition of a tissue measurement site in operational position.

FIG. 5 illustrates a top view of a three-dimensional pulse oximetry sensor according to an embodiment of the present disclosure.

FIG. 6 illustrates a conventional two-dimensional approach to reflective pulse oximetry in which the emitter is configured to emit optical radiation as a point optical source.

FIG. 7A is a simplified schematic side view illustration of a reflective three-dimensional pulse oximetry sensor according to an embodiment of the present disclosure.

FIG. 7B is a simplified schematic top view illustration of the three-dimensional reflective pulse oximetry sensor of FIG. 7A.

FIG. 8 illustrates a block diagram of an example pulse oximetry system capable of noninvasively measuring one or more blood analytes in a monitored patient, according to an embodiment of the disclosure.

DETAILED DESCRIPTION

FIG. 1 illustrates schematically a conventional pulse oximetry sensor having a two-dimensional (2D) approach to pulse oximetry. As illustrated, the emitter 104 is configured to emit optical radiation as a point optical source, i.e., an optical radiation source that has negligible dimensions such that it may be considered as a point. This approach is referred to herein as “two-dimensional” pulse oximetry because it applies a two-dimensional analytical model to the three-dimensional space of the tissue measurement site 102 of the patient. Point optical sources feature a defined, freely selectable, and homogeneous light beam area. Light beams emitted from LED point sources often exhibit a strong focus which can produce a usually sharply-defined and evenly-lit illuminated spot often with high intensity dynamics. Illustratively, when looking at the surface of the tissue measurement site 102 (or “sample tissue”), which in this example is a finger, a small point-like surface area of tissue 204 is irradiated by a point optical source. In some embodiments, the irradiated circular area of the point optical source is in the range between 8 and 150 microns. Illustratively, the emitted point optical source of light enters the tissue measurement site 102 as a point of light. As the light penetrates the depth of the tissue 102, it does so as a line or vector, representing a two-dimensional construct within a three-dimensional structure, namely the patient's tissue 102.

Use of a point optical source is believed to reduce variability in light pathlength which would lead to more

6

accurate oximetry measurements. However, in practice, photons do not travel in straight paths. Instead, the light particles scatter, bouncing around between various irregular objects (such as, for example, red blood cells) in the patient's blood. Accordingly, photon pathlengths vary depending on, among other things, their particular journeys through and around the tissue at the measurement site 102. This phenomenon is referred to as “multiple scattering.” In a study, the effects of multiple scattering were examined by comparing the results of photon diffusion analysis with those obtained using an analysis based on the Beer-Lambert law, which neglects multiple scattering in the determination of light pathlength. The study found that the difference between the average lengths of the paths traveled by red and infrared photons makes the oximeter's calibration curve (based on measurements obtained from normal subjects) sensitive to the total attenuation coefficients of the tissue in the two wavelength bands used for pulse oximetry, as well as to absorption by the pulsating arterial blood.

FIG. 2 illustrates schematically the disclosed systems, devices, and methods to implement three-dimensional (3D) pulse oximetry in which the emitted light irradiates a larger volume of tissue at the measurement site 102 as compared to the 2D point optical source approach described with respect to FIG. 1. In an embodiment, again looking at the surface of the tissue measurement site 102, the irradiated surface area 206 of the measurement site 102 is substantially rectangular in shape with dimensions in the range of approximately 0.25-3 cm in width and approximately 1-6 cm in length. In another embodiment, the irradiated surface area 206 of the measurement site 102 is substantially rectangular in shape and has dimensions of approximately 1.5 cm in width and approximately 2 cm in length. In another embodiment, the irradiated surface area 206 of the measurement site 102 is substantially rectangular in shape and has dimensions of approximately 0.5 cm in width and approximately 1 cm in length. In another embodiment, the irradiated surface area 206 of the measurement site 102 is substantially rectangular in shape has dimensions of approximately 1 cm in width and approximately 1.5 cm in length. In yet another embodiment, the irradiated surface area 206 of the measurement site 102 is substantially square in shape and has dimensions in a range of approximately 0.25-9 cm². In certain embodiments, the irradiated surface area 206 of the measurement site 102 is within a range of approximately 0.5-2 cm in width, and approximately 1-4 cm in length. Of course a skilled artisan will appreciate that many other shapes and dimensions of irradiated surface area 206 can be used. Advantageously, by irradiating the tissue measurement site 102 with a surface area 206, the presently disclosed systems, devices, and methods apply a three-dimensional analytical model to the three-dimensional structure being measured, namely, the patient's sample tissue 102.

According to the Beer-Lambert law, the amount of light absorbed by a substance is proportional to the concentration of the light-absorbing substance in the irradiated solution (i.e., arterial blood). Advantageously, by irradiating a larger volume of tissue 102, a larger sample size of light attenuated (or reflected) by the tissue 102 is measured. The larger, 3D sample provides a data set that is more representative of the complete interaction of the emitted light as it passes through the patient's blood as compared to the 2D point source approach described above with respect to FIG. 1. By taking an average of the detected light, as detected over a surface area substantially larger than a single point, the disclosed pulse oximetry systems, devices, and methods will yield a

more accurate measurement of the emitted light absorbed by the tissue, which will lead to a more accurate oxygen saturation measurement.

FIG. 3 illustrates schematically a side view of a pulse oximetry 3D sensor 300 according to an embodiment of the present disclosure. In the illustrated embodiment, the 3D sensor 300 irradiates the tissue measurement site 102 and detects the emitted light, after being attenuated by the tissue measurement site 102. In other embodiments, for example, as describe below with respect to FIGS. 7A and 7B, the 3D sensor 300 can be arranged to detect light that is reflected by the tissue measurement site 102. The 3D sensor 300 includes an emitter 302, a light diffuser 304, a light-absorbing detector filter 306, a light concentrator 308, and a detector 310. In some optional embodiments, the 3D sensor 300 further includes a reflector 305. The reflector 305 can be a metallic reflector or other type of reflector. Reflector 305 can be a coating, film, layer or other type of reflector. The reflector 305 can serve as a reflector to prevent emitted light from emitting out of a top portion of the light diffuser 304 such that light from the emitter 302 is directed in the tissue rather than escaping out of a side or top of the light diffuser 304. Additionally, the reflector 305 can prevent ambient light from entering the diffuser 304 which might ultimately cause errors within the detected light. The reflector 305 also prevent light piping that might occur if light from the detector 302 is able to escape from the light diffuser 304 and be piped around a sensor securement mechanism to detector 310 without passing through the patient's tissue 102.

The emitter 302 can serve as the source of optical radiation transmitted towards the tissue measurement site 102. The emitter 302 can include one or more sources of optical radiation, such as LEDs, laser diodes, incandescent bulbs with appropriate frequency-selective filters, combinations of the same, or the like. In an embodiment, the emitter 302 includes sets of optical sources that are capable of emitting visible and near-infrared optical radiation. In some embodiments, the emitter 302 transmits optical radiation of red and infrared wavelengths, at approximately 650 nm and approximately 940 nm, respectively. In some embodiments, the emitter 302 includes a single source optical radiation.

The light diffuser 304 receives the optical radiation emitted from the emitter 302 and spreads the optical radiation over an area, such as the area 206 depicted in FIG. 2. In some embodiments, the light diffuser 304 is a beam shaper that can homogenize the input light beam from the emitter 302, shape the output intensity profile of the received light, and define the way (e.g., the shape or pattern) the emitted light is distributed to the tissue measurement site 102. Examples of materials that can be used to realize the light diffuser 304 include, without limitation, a white surface, glass, ground glass, glass beads, polytetrafluoroethylene (also known as Teflon®), opal glass, and greyed glass, to name a few. Additionally, engineered diffusers can be used to realize the diffuser 304 by providing customized light shaping with respect to intensity and distribution. Such diffusers can, for example, deliver substantially uniform illumination over a specified target area (such as, for example, irradiated surface area 206) in an energy-efficient manner. Examples of engineered diffusers can include molded plastics with specific shapes, patterns or textures designed to diffuse the emitter light across the entirety of the patient's tissue surface.

Advantageously, the diffuser 304 can receive emitted light in the form of a point optical source and spread the light to fit a desired surface area on a plane defined by the surface of the tissue measurement site 102. In an embodiment, the diffuser 304 is made of ground glass which spreads the

emitted light with a Gaussian intensity profile. In another embodiment the diffuser 304 includes glass beads. In some embodiments, the diffuser 304 is constructed so as to diffuse the emitted light in a Lambertian pattern. A Lambertian pattern is one in which the radiation intensity is substantially constant throughout the area of dispersion. One such diffuser 304 is made from opal glass. Opal glass is similar to ground glass, but has one surface coated with a milky white coating to diffuse light evenly. In an embodiment, the diffuser 304 is capable of distributing the emitted light on the surface of a plane (e.g., the surface of the tissue measurement site 102) in a predefined geometry (e.g., a rectangle, square, or circle), and with a substantially uniform intensity profile and energy distribution. In some embodiments, the efficiency, or the amount of light transmitted by the diffuser 304, is greater than 70% of the light emitted by the emitter 302. In some embodiments, the efficiency is greater than 90% of the emitted light. Other optical elements known in the art may be used for the diffuser 304.

In an embodiment, the diffuser 304 has a substantially rectangular shape having dimensions within a range of approximately 0.5-2 cm in width and approximately 1-4 centimeters in length. In another embodiment, the substantially rectangular shape of the diffuser 304 has dimensions of approximately 0.5 cm in width and approximately 1 cm in length. In another embodiment, the diffuser's 304 substantially rectangular shape has dimensions of approximately 1 cm in width and approximately 1.5 cm in length. In yet another embodiment, the diffuser 304 has a substantially square shape with dimensions in the range of approximately 0.25-10 cm².

The light-absorbing detector filter 306, which is also depicted in FIG. 4A in a top view, is a planar surface having an opening 402 through which the emitted light may pass after being attenuated by the tissue measurement site 102. In the depicted embodiment, the opening 402 is rectangular-shaped, with dimensions substantially similar to the irradiated surface area 206. According to an embodiment, the light-absorbing detector filter is substantially rectangular in shape and has outer dimensions of 4 cm in width and 8 cm in length, and has an opening through which emitted light may pass, the opening having dimensions of 2 cm in width and 5 cm in length. In another embodiment, the light-absorbing detector filter is substantially rectangular in shape and has outer dimensions in the range of 1-3 cm in width and 2-8 cm in length, and has an opening through which emitted light may pass, the opening having dimensions in the range of 0.25-2 cm in width and 1-4 cm in length. In yet another embodiment, the light-absorbing detector filter is substantially rectangular in shape and has outer dimensions of 3 cm in width and 6 cm in length, and has an opening through which emitted light may pass, the opening having dimensions of 1.5 cm in width and 4 cm in length.

The top surface of the light-absorbing filter 306 (facing the tissue measurement site 102 and the emitter 302) is coated with a material that absorbs light, such as, for example, black pigment. Many other types of light-absorbing materials are well known in the art and can be used with the detector filter 306. During operation, light emitted from the emitter 302 can reflect off of the tissue measurement site 102 (or other structures within the 3D sensor 300) to neighboring portions of the 3D sensor 300. If those neighboring portions of the 3D sensor 300 possess reflective surfaces, then the light can reflect back to the tissue measurement site 102, progress through the tissue and arrive at the detector 310. Such multiple scattering can result in detecting photons whose pathlengths are considerably lon-

ger than most of the light that is detected, thereby introducing variations in pathlength which will affect the accuracy of the measurements of the pulse oximetry 3D sensor 300. Advantageously, the light-absorbing filter 306 reduces or eliminates the amount of emitted light that is reflected in this manner because it absorbs such reflected light, thereby stopping the chain of scattering events. In certain embodiments, the sensor-facing surfaces of other portions of the 3D sensor 300 are covered in light-absorbing material to further decrease the effect of reflective multiple scattering.

The light concentrator 308 is a structure to receive the emitted optical radiation, after attenuation by the tissue measurement site 102, to collect and concentrate the dispersed optical radiation, and to direct the collected and concentrated optical radiation to the detector 310. In an embodiment, the light concentrator 308 is made of ground glass or glass beads. In some embodiments, the light concentrator 308 includes a compound parabolic concentrator.

As described above with respect to FIG. 1, the detector 310 captures and measures light from the tissue measurement site 102. For example, the detector 310 can capture and measure light transmitted from the emitter 302 that has been attenuated by the tissue in the measurement site 102. The detector 310 can output a detector signal responsive to the light captured or measured. The detector 310 can be implemented using one or more photodiodes, phototransistors, or the like. In addition, a plurality of detectors 310 can be arranged in an array with a spatial configuration corresponding to the irradiated surface area 206 to capture the attenuated or reflected light from the tissue measurement site.

Referring to FIG. 4A, a top view of a portion of the 3D sensor 300 is provided. The light-absorbing detector filter 306 is illustrated having a top surface coated with a light-absorbing material. The light-absorbing material can be a black opaque material or coating or any other dark color or coating configured to absorb light. Additionally, a rectangular opening 402 is positioned relative to the light concentrator 308 (shown in phantom) and the detector 310 such that light may pass through the rectangular opening 402, into the light concentrator 308, and to the detector 310. FIG. 4B illustrates the top view of a portion of the 3D sensor 300 as in FIG. 4A, with the addition of the tissue measurement site 102 in operational position. Accordingly, the rectangular opening 402, the light concentrator 308 and the detector 310 are shown in phantom as being under the tissue measurement site 102. In FIGS. 4A and 4B, the light concentrator 308 is shown to have dimensions significantly larger than the dimensions of the rectangular opening 402. In other embodiments, the dimensions of the light concentrator 308, the rectangular opening 402, and the irradiated surface area 206 are substantially similar.

FIG. 5 illustrates a top view of a 3D pulse oximetry sensor 500 according to an embodiment of the present disclosure. The 3D sensor 500 is configured to be worn on a patient's finger 102. The 3D sensor 500 includes an adhesive substrate 502 having front flaps 504 and rear flaps 506 extending outward from a center portion 508 of the 3D sensor 500. The center portion 508 includes components of the 3D pulse oximetry sensor 300 described with respect to FIGS. 3, 4A and 4B. On the front side of the adhesive substrate 502 the emitter 302 and the light diffuser 304 are positioned. On the rear side of the adhesive substrate 502 the light-absorbent detector filter 306, the light concentrator 308 and the detector 310 are positioned. In use, the patient's finger serving as the tissue measurement site 102 is positioned over the rectangular opening 402 such that when the front portion of the adhesive substrate is folded over on top of the patient's

finger 102, the emitter 302 and the light diffuser 304 are aligned with the measurement site 102, the filter 306, the light concentrator 308 and the detector 310. Once alignment is established, the front and rear flaps 504, 506 can be wrapped around the finger measurement site 102 such that the adhesive substrate 502 provides a secure contact between the patient's skin and the 3D sensor 500. FIG. 5 also illustrates an example of a sensor connector cable 510 which is used to connect the 3D sensor 500 to a monitor 809, as described with respect to FIG. 8.

FIG. 6 is a simplified schematic illustration of a conventional, 2D approach to reflective pulse oximetry in which the emitter is configured to emit optical radiation as a point optical source. Reflective pulse oximetry is a method by which the emitter and detector are located on the same side of the tissue measurement site 102. Light is emitted into a tissue measurement site 102 and attenuated. The emitted light passes into the tissue 102 and is then reflected back to the same side of the tissue measurement site 102 as the emitter. As illustrated in FIG. 6, a depicted reflective 2D pulse oximetry sensor 600 includes an emitter 602, a light block 606, and a detector 610. The light block 606 is necessary because the emitter 602 and the detector 610 are located on the same side of the tissue measurement site 102. Accordingly, the light block 606 prevents incident emitter light, which did not enter the tissue measurement site 102, from arriving at the detector 610. The depicted 2D pulse oximetry sensor 600 is configured to emit light as a point source. As depicted in FIG. 6, a simplified illustration of the light path 620 of the emitted light from the emitter 602, through the tissue measurement site 102, and to the detector 610 is provided. Notably, a point source of light is emitted, and a point source of light is detected. As discussed above with respect to FIG. 1, use of a point optical source can result in substantial measurement error due to pathlength variability resulting from the multiple scatter phenomenon. The sample space provided by a 2D point optical emitter source is not large enough to account for pathlength variability, which will skew measurement results.

FIGS. 7A and 7B are simplified schematic side and top views, respectively, of a 3D reflective pulse oximetry sensor 700 according to an embodiment of the present disclosure. In the illustrated embodiment, the 3D sensor 700 irradiates the tissue measurement site 102 and detects the emitted light that is reflected by the tissue measurement site 102. The 3D sensor 700 can be placed on a portion of the patient's body that has relatively flat surface, such as, for example a wrist, because the emitter 702 and detector 710 are on located the same side of the tissue measurement site 102. The 3D sensor 700 includes an emitter 702, a light diffuser 704, a light block 706, a light concentrator 708, and a detector 710.

As previously described, the emitter 702 can serve as the source of optical radiation transmitted towards the tissue measurement site 102. The emitter 702 can include one or more sources of optical radiation. Such sources of optical radiation can include LEDs, laser diodes, incandescent bulbs with appropriate frequency-selective filters, combinations of the same, or the like. In an embodiment, the emitter 702 includes sets of optical sources that are capable of emitting visible and near-infrared optical radiation. In some embodiments, the emitter 702 transmits optical radiation of red and infrared wavelengths, at approximately 650 nm and approximately 940 nm, respectively. In some embodiments, the emitter 702 includes a single source of optical radiation.

The light diffuser 704 receives the optical radiation emitted from the emitter 702 and homogenously spreads the optical radiation over a wide, donut-shaped area, such as the

11

area outlined by the light diffuser **704** as depicted in FIG. 7B. Advantageously, the diffuser **704** can receive emitted light in the form of a 2D point optical source (or any other form) and spread the light to fit the desired surface area on a plane defined by the surface of the tissue measurement site **102**. In an embodiment, the diffuser **704** is made of ground glass or glass beads. A skilled artisan will understand that many other materials can be used to make the light diffuser **704**.

The light blocker **706** includes an annular ring having a cover portion **707** sized and shaped to form a light isolation chamber for the light concentrator **708** and the detector **710**. (For purposes of illustration, the light block cover **707** is not illustrated in FIG. 7B.) The light blocker **706** and the cover **707** can be made of any material that optically isolates the light concentrator **708** and the detector **710**. The light isolation chamber formed by the light blocker **706** and cover **707** ensures that the only light detected by the detector **710** is light that is reflected from the tissue measurement site.

The light concentrator **708** is a cylindrical structure with a truncated circular conical structure on top, the truncated section of which is adjacent the detector **710**. The light concentrator **708** is structured to receive the emitted optical radiation, after reflection by the tissue measurement site **102**, and to direct the reflected light to the detector **710**. In an embodiment, the light concentrator **708** is made of ground glass or glass beads. In some embodiments, the light concentrator **708** includes a compound parabolic concentrator.

As previously described, the detector **710** captures and measures light from the tissue measurement site **102**. For example, the detector **710** can capture and measure light transmitted from the emitter **702** that has been reflected from the tissue in the measurement site **102**. The detector **710** can output a detector signal responsive to the light captured or measured. The detector **710** can be implemented using one or more photodiodes, phototransistors, or the like. In addition, a plurality of detectors **710** can be arranged in an array with a spatial configuration corresponding to the irradiated surface area depicted in FIG. 7B by the light concentrator **708** to capture the reflected light from the tissue measurement site.

Advantageously, the light path **720** illustrated in FIG. 7A depicts a substantial sample of reflected light that enter the light isolation chamber formed by the light blocker **706** and cover **707**. As previously discussed, the large sample of reflected light (as compared to the reflected light collected using the 2D point optical source approach) provides the opportunity to take an average of the detected light, to derive a more accurate measurement of the emitted light absorbed by the tissue, which will lead to a more accurate oxygen saturation measurement.

Referring now to FIG. 7B, a top view of the 3D sensor **700** is illustrated with both the emitter **702** and the light blocker cover **707** removed for ease of illustration. The outer ring illustrates the footprint of the light diffuser **704**. As light is emitted from the emitter **702** (not shown in FIG. 7B), it is diffused homogenously and directed to the tissue measurement site **102**. The light blocker **706** forms the circular wall of a light isolation chamber to keep incident light from being sensed by the detector **710**. The light blocker cover **707** blocks incidental light from entering the light isolation chamber from above. The light concentrator **710708** collects the reflected light from the tissue measurement site **102** and funnels it upward toward the detector **710** at the center of the 3D sensor **700**.

12

FIG. 8 illustrates an example of an optical physiological measurement system **800**, which may also be referred to herein as a pulse oximetry system **800**. In certain embodiments, the pulse oximetry system **800** noninvasively measures a blood analyte, such as oxygen, carboxyhemoglobin, methemoglobin, total hemoglobin, glucose, proteins, lipids, a percentage thereof (e.g., saturation), pulse rate, perfusion index, oxygen content, total hemoglobin, Oxygen Reserve Index™ (ORI™) or many other physiologically relevant patient characteristics. These characteristics can relate to, for example, pulse rate, hydration, trending information and analysis, and the like. The system **800** can also measure additional blood analytes and/or other physiological parameters useful in determining a state or trend of wellness of a patient.

The pulse oximetry system **800** can measure analyte concentrations at least in part by detecting optical radiation attenuated by tissue at a measurement site **102**. The measurement site **102** can be any location on a patient's body, such as a finger, foot, earlobe, wrist, forehead, or the like.

The pulse oximetry system **800** can include a sensor **801** (or multiple sensors) that is coupled to a processing device or physiological monitor **809**. In an embodiment, the sensor **801** and the monitor **809** are integrated together into a single unit. In another embodiment, the sensor **801** and the monitor **809** are separate from each other and communicate with one another in any suitable manner, such as via a wired or wireless connection. The sensor **801** and monitor **809** can be attachable and detachable from each other for the convenience of the user or caregiver, for ease of storage, sterility issues, or the like.

In the depicted embodiment shown in FIG. 8, the sensor **801** includes an emitter **804**, a detector **806**, and a front-end interface **808**. The emitter **804** can serve as the source of optical radiation transmitted towards measurement site **102**. The emitter **804** can include one or more sources of optical radiation, such as light emitting diodes (LEDs), laser diodes, incandescent bulbs with appropriate frequency-selective filters, combinations of the same, or the like. In an embodiment, the emitter **804** includes sets of optical sources that are capable of emitting visible and near-infrared optical radiation.

The pulse oximetry system **800** also includes a driver **811** that drives the emitter **804**. The driver **811** can be a circuit or the like that is controlled by the monitor **809**. For example, the driver **811** can provide pulses of current to the emitter **804**. In an embodiment, the driver **811** drives the emitter **804** in a progressive fashion, such as in an alternating manner. The driver **811** can drive the emitter **804** with a series of pulses for some wavelengths that can penetrate tissue relatively well and for other wavelengths that tend to be significantly absorbed in tissue. A wide variety of other driving powers and driving methodologies can be used in various embodiments. The driver **811** can be synchronized with other parts of the sensor **801** to minimize or reduce jitter in the timing of pulses of optical radiation emitted from the emitter **804**. In some embodiments, the driver **811** is capable of driving the emitter **804** to emit optical radiation in a pattern that varies by less than about 10 parts-per-million.

The detector **806** captures and measures light from the tissue measurement site **102**. For example, the detector **806** can capture and measure light transmitted from the emitter **804** that has been attenuated or reflected from the tissue at the measurement site **102**. The detector **806** can output a detector signal **107** responsive to the light captured and measured. The detector **806** can be implemented using one

13

or more photodiodes, phototransistors, or the like. In some embodiments, a detector **806** is implemented in detector package to capture and measure light from the tissue measurement site **102** of the patient. The detector package can include a photodiode chip mounted to leads and enclosed in an encapsulant. In some embodiments, the dimensions of the detector package are approximately 2 square centimeters. In other embodiments, the dimensions of the detector package are approximately 1.5 centimeters in width and approximately 2 centimeters in length.

The front-end interface **808** provides an interface that adapts the output of the detectors **806**, which is responsive to desired physiological parameters. For example, the front-end interface **808** can adapt the signal **807** received from the detector **806** into a form that can be processed by the monitor **809**, for example, by a signal processor **810** in the monitor **809**. The front-end interface **808** can have its components assembled in the sensor **801**, in the monitor **809**, in a connecting cabling (if used), in combinations of the same, or the like. The location of the front-end interface **808** can be chosen based on various factors including space desired for components, desired noise reductions or limits, desired heat reductions or limits, and the like.

The front-end interface **808** can be coupled to the detector **806** and to the signal processor **810** using a bus, wire, electrical or optical cable, flex circuit, or some other form of signal connection. The front-end interface **808** can also be at least partially integrated with various components, such as the detectors **806**. For example, the front-end interface **808** can include one or more integrated circuits that are on the same circuit board as the detector **806**. Other configurations can also be used.

As shown in FIG. 8, the monitor **909** can include the signal processor **810** and a user interface, such as a display **812**. The monitor **809** can also include optional outputs alone or in combination with the display **812**, such as a storage device **814** and a network interface **816**. In an embodiment, the signal processor **810** includes processing logic that determines measurements for desired analytes based on the signals received from the detector **806**. The signal processor **810** can be implemented using one or more microprocessors or sub-processors (e.g., cores), digital signal processors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), combinations of the same, and the like.

The signal processor **810** can provide various signals that control the operation of the sensor **801**. For example, the signal processor **810** can provide an emitter control signal to the driver **811**. This control signal can be useful in order to synchronize, minimize, or reduce jitter in the timing of pulses emitted from the emitter **804**. Accordingly, this control signal can be useful in order to cause optical radiation pulses emitted from the emitter **804** to follow a precise timing and consistent pattern. For example, when a transimpedance-based front-end interface **808** is used, the control signal from the signal processor **810** can provide synchronization with an analog-to-digital converter (ADC) in order to avoid aliasing, cross-talk, and the like. As also shown, an optional memory **813** can be included in the front-end interface **808** and/or in the signal processor **810**. This memory **813** can serve as a buffer or storage location for the front-end interface **808** and/or the signal processor **810**, among other uses.

The user interface **812** can provide an output, e.g., on a display, for presentation to a user of the pulse oximetry system **800**. The user interface **812** can be implemented as a touch-screen display, a liquid crystal display (LCD), an

14

organic LED display, or the like. In alternative embodiments, the pulse oximetry system **800** can be provided without a user interface **812** and can simply provide an output signal to a separate display or system.

The storage device **814** and a network interface **816** represent other optional output connections that can be included in the monitor **809**. The storage device **814** can include any computer-readable medium, such as a memory device, hard disk storage, EEPROM, flash drive, or the like. The various software and/or firmware applications can be stored in the storage device **814**, which can be executed by the signal processor **810** or another processor of the monitor **809**. The network interface **816** can be a serial bus port (RS-232/RS-485), a Universal Serial Bus (USB) port, an Ethernet port, a wireless interface (e.g., WiFi such as any 802.1x interface, including an internal wireless card), or other suitable communication device(s) that allows the monitor **809** to communicate and share data with other devices. The monitor **809** can also include various other components not shown, such as a microprocessor, graphics processor, or controller to output the user interface **812**, to control data communications, to compute data trending, or to perform other operations.

Although not shown in the depicted embodiment, the pulse oximetry system **800** can include various other components or can be configured in different ways. For example, the sensor **801** can have both the emitter **804** and detector **806** on the same side of the tissue measurement site **102** and use reflectance to measure analytes.

Although the foregoing disclosure has been described in terms of certain preferred embodiments, many other variations than those described herein will be apparent to those of ordinary skill in the art.

Conditional language used herein, such as, among others, “can,” “might,” “may,” “e.g.,” and the like, unless specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or states. Thus, such conditional language is not generally intended to imply that features, elements and/or states are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without author input or prompting, whether these features, elements and/or states are included or are to be performed in any particular embodiment. The terms “comprising,” “including,” “having,” and the like are synonymous and are used inclusively, in an open-ended fashion, and do not exclude additional elements, features, acts, operations, and so forth. Also, the term “or” is used in its inclusive sense (and not in its exclusive sense) so that when used, for example, to connect a list of elements, the term “or” means one, some, or all of the elements in the list. Further, the term “each,” as used herein, in addition to having its ordinary meaning, can mean any subset of a set of elements to which the term “each” is applied.

While the above detailed description has shown, described, and pointed out novel features as applied to various embodiments, it will be understood that various omissions, substitutions, and changes in the form and details of the systems, devices or algorithms illustrated can be made without departing from the spirit of the disclosure. As will be recognized, certain embodiments of the disclosure described herein can be embodied within a form that does not provide all of the features and benefits set forth herein, as some features can be used or practiced separately from others.

15

The term “and/or” herein has its broadest, least limiting meaning which is the disclosure includes A alone, B alone, both A and B together, or A or B alternatively, but does not require both A and B or require one of A or one of B. As used herein, the phrase “at least one of” A, B, “and” C should be construed to mean a logical A or B or C, using a non-exclusive logical or.

The apparatuses and methods described herein may be implemented by one or more computer programs executed by one or more processors. The computer programs include processor-executable instructions that are stored on a non-transitory tangible computer readable medium. The computer programs may also include stored data. Non-limiting examples of the non-transitory tangible computer readable medium are nonvolatile memory, magnetic storage, and optical storage. Although the foregoing disclosure has been described in terms of certain preferred embodiments, other embodiments will be apparent to those of ordinary skill in the art from the disclosure herein. Additionally, other combinations, omissions, substitutions and modifications will be apparent to the skilled artisan in view of the disclosure herein. Accordingly, the present invention is not intended to be limited by the description of the preferred embodiments, but is to be defined by reference to claims.

Additionally, all publications, patents, and patent applications mentioned in this specification are herein incorporated by reference to the same extent as if each individual publication, patent, or patent application were specifically and individually indicated to be incorporated by reference.

What is claimed is:

1. A physiological monitoring device comprising:
 - a plurality of emitters configured to emit light in a first shape;
 - a material positioned between the plurality of emitters and a tissue measurement site on a wrist of a user when the physiological monitoring device is in use, the material configured to change the first shape into a second shape by which the light emitted from one or more of the plurality of emitters is projected towards a surface of the tissue measurement site;
 - a plurality of detectors configured to detect at least a portion of the light after passing through tissue, the plurality of detectors further configured to output at least one signal responsive to the detected light;
 - a surface comprising a dark-colored coating, the surface positioned between the plurality of detectors and the tissue when the physiological monitoring device is in use, wherein an opening defined in the dark-colored coating is configured to allow at least a portion of light reflected from the tissue to pass through the surface;
 - a light block configured to prevent at least a portion of the light emitted from the plurality of emitters from reaching the plurality of detectors without first reaching the tissue; and
 - a processor configured to receive and process one or more signals responsive to the at least one outputted signal and determine a physiological parameter of the user responsive to the one or more signals.
2. The physiological monitoring device of claim 1, further comprising a display configured to present visual feedback responsive to the determined physiological parameter.
3. The physiological monitoring device of claim 2, wherein the display is a touch-screen display.
4. The physiological monitoring device of claim 1, wherein the plurality of emitters and the plurality of detectors are arranged in a reflectance measurement configuration.

16

5. The physiological monitoring device of claim 1, wherein the plurality of detectors are arranged in an array having a spatial configuration corresponding to a shape of a portion of the tissue measurement site bounded by the light block.

6. The physiological monitoring device of claim 1, wherein the light block comprises an at least partially circular shape, and wherein the plurality of emitters are positioned outside the light block and the plurality of detectors are positioned inside the light block.

7. The physiological monitoring device of claim 1, wherein the physiological parameter comprises pulse rate.

8. The physiological monitoring device of claim 1, wherein the physiological parameter comprises oxygen saturation.

9. The physiological monitoring device of claim 1, wherein the material comprises plastic.

10. The physiological monitoring device of claim 1, wherein the material comprises glass.

11. The physiological monitoring device of claim 1, wherein the second shape comprises a circular geometry.

12. The physiological monitoring device of claim 1, wherein the opening defined in the dark-colored coating comprises a width and a length, and wherein the width is larger than the length.

13. The physiological monitoring device of claim 1, wherein the dark-colored coating comprises black.

14. A physiological monitoring device comprising:
- a plurality of optical sources configured to emit light proximate a wrist of a user;
 - a diffuser configured to be positioned between the plurality of optical sources and a tissue measurement site on the wrist of the user when the physiological monitoring device is in use;
 - a light block having a circular shape;
 - a plurality of detectors configured to detect at least a portion of the light after the light passes through a portion of the tissue measurement site bounded by the light block, wherein the plurality of detectors are arranged in an array having a spatial configuration corresponding to a shape of the portion of the tissue measurement site bounded by the circular shaped light block, wherein the plurality of detectors are further configured to output at least one signal responsive to the detected light, and wherein the plurality of optical sources and the plurality of detectors are arranged in a reflectance measurement configuration;
 - wherein the light block is configured to prevent at least a portion of light emitted from the plurality of optical sources from reaching the plurality of detectors without first reaching tissue;
 - a processor configured to receive and process one or more signals responsive to the at least one outputted signal and determine a physiological parameter of the user responsive to the one or more signals; and
 - wherein the physiological monitoring device is configured to transmit physiological parameter data to a separate processor.

15. The physiological monitoring device of claim 14, wherein the plurality of optical sources are positioned outside the light block and the plurality of detectors are positioned inside the light block.

16. The physiological monitoring device of claim 14, wherein the physiological parameter comprises pulse rate.

17. The physiological monitoring device of claim 14, wherein the physiological parameter comprises oxygen saturation.

17

18. The physiological monitoring device of claim 14, wherein the plurality of optical sources are configured to emit light in a first shape, and wherein the diffuser comprises a material configured to change the first shape into a second shape by which the light emitted from one or more of the plurality of optical sources is projected towards the tissue measurement site.

19. A system configured to measure one or more physiological parameters of a user, the system comprising:

a physiological monitoring device comprising:

a plurality of emitters configured to emit light in a first shape;

a material positioned between the plurality of emitters and a tissue measurement site when the physiological monitoring device is in use, the material configured to change the first shape into a second shape by which the light emitted from one or more of the plurality of emitters is projected towards the tissue measurement site;

a plurality of detectors configured to detect at least a portion of the light passing through tissue, the plurality of detectors further configured to output at least one signal responsive to the detected light;

a surface comprising a dark-colored coating, the surface positioned between the plurality of detectors and the tissue when the physiological monitoring device is in use, wherein an opening defined in the dark-colored coating is configured to allow at least a portion of light reflected from the tissue to pass through the surface;

a light block configured to prevent at least a portion of light from the plurality of emitters from reaching the plurality of detectors without first reaching the tissue; and

18

a processor configured to receive and process one or more signals responsive to the outputted at least one signal and determine a physiological parameter of the user responsive to the one or more signals; and

a processing device configured to wirelessly receive physiological parameter data from the physiological monitoring device, wherein the processing device comprises a user interface, a storage device, and a network interface configured to wirelessly communicate with the physiological monitoring device, and wherein the user interface includes a touch-screen display configured to present visual feedback responsive to the physiological parameter data.

20. The system of claim 19, wherein the system is configured to determine a state of wellness of the user based on the determined physiological parameter.

21. The system of claim 19, wherein the system is configured to determine a trend of wellness of the user based on the determined physiological parameter.

22. The system of claim 19, wherein the visual feedback presented by the touch-screen display is responsive to at least one of a pulse rate and an oxygen saturation of the user.

23. The system of claim 19, wherein the material comprises at least one of glass and plastic.

24. The system of claim 19, wherein the second shape comprises a width and a length, and wherein the width is different from the length.

25. The system of claim 19, wherein the plurality of detectors are arranged in an array having a spatial configuration corresponding to a shape of a portion of the tissue measurement site bounded by the light block.

* * * * *