

DECLARATION OF DOMENIC RIZZOLO

1. I, Domenic Rizzolo, submit this Declaration on behalf of the Patent Owner, Provisur Technologies, Inc. (“Provisur”). I am a citizen of the United States, over 18 years of age, and competent to testify to the matters contained in this Declaration. If called as a witness, I could and would competently testify to these same facts.

BACKGROUND & QUALIFICATIONS

2. I am currently employed as a Manager in Aon’s Stroz Friedberg Digital Forensic and Incident Response team (“Stroz Friedberg”). I have been employed at Stroz Friedberg since September 2015. My CV attached as Exhibit A.

3. At Stroz Friedberg, I frequently conduct forensic examinations on a variety of computers and other digital media, advising in civil litigation and incident response cases. Specifically, my consultations have included the retrieval, preservation, and analysis of a variety of electronic evidence in order to present facts and opinions.

4. I attended the University of Michigan where I received a Bachelor’s Degree in Mathematics. I have multiple certifications in computer forensics and other information security fields.

RETENTION AND ASSIGNMENT

5. Stroz Friedberg was retained by Provisur, under the direction of Willkie Farr & Gallagher LLP, to preserve a webpage and a document linked on that webpage.

6. I preserved the webpage and linked document on December 4, 2023. A true and accurate copy of the original evidence was captured.

PRESERVATION

7. I preserved the webpage residing at the following URL:

<https://web.archive.org/web/20150418111911/http://www.omega.com/pptst/PXM409.html> (“the webpage”).

8. I preserved the webpage by accessing its URL via version 119.0.6045.200 of the Google Chrome web browser on December 4, 2023. Upon accessing the webpage, I used multiple built-in functionalities of the Google Chrome web browser to capture the content of the webpage. I used all three settings of the “Save Page As...” feature within Google Chrome to capture the data that comprised the webpage. The resulting downloaded iterations of the webpage were preserved as it would appear to a Google Chrome user.

9. I used the “Webpage, HTML Only (*.html; *.htm)” setting of the “Save Page As...” feature to preserve the webpage on December 4, 2023, at 21:14:31 UTC¹. This preservation captured the contents of the webpage in a single “.html” file of size 223,785 bytes.

10. I used the “Webpage, Single File (*.mhtml)” setting of the “Save Page As...” feature to preserve the webpage on December 4, 2023, at 21:14:45 UTC. This preservation captured the contents of the webpage in a single “.mhtml” file of size 740,545 bytes. A true and correct copy of this preserved webpage, converted to a PDF, is attached here as Exhibit B.

11. I used the “Webpage, Complete (*.html; *.htm)” setting of the “Save Page As...” feature to preserve the webpage on December 4, 2023, at 21:16:25 UTC. This preservation captured the contents of the webpage and its associated elements in 79 separate files that sum to a total size of 2,225,936 bytes.

12. The Internet Archive, also known as the Wayback Machine, is a website residing at the following URL: “<https://web.archive.org/>”. The Internet Archive is a 501(c)(3) non-profit

¹ All dates in this declaration are recorded in Universal Coordinate Time (“UTC”) unless otherwise noted. Some timestamps have been converted to UTC from their original time zones.

focused on building a digital library of Internet sites and other cultural artifacts in digital form. The site provides free access to researchers, historians, scholars, the print disabled, and the general public. The archive has been preserving stateful copies of billions of webpages for over 25 years².

13. Since the Wayback Machine can snapshot the same webpage across multiple days and years, the naming convention of a given URL from the Wayback Machine includes a date code embedded in the archived URL which indicates when a particular version of the webpage was archived by the Wayback Machine's web crawler. These date codes include a date and timestamp in the UTC time zone.

14. Based on the disclosed formatting style of the Wayback Machine's date codes, I discerned that the embedded date code associated with the webpage, "20150418111911", correlated with a preservation timestamp of March 18, 2015, at 11:19:11 UTC.

15. Additionally, the webpage contained a link labelled "Specs" to a PDF file, named "PXM409.pdf". Due to the iterative nature of the Wayback Machine's webpage crawler, a copy of this file was snapshotted and is accessible via the URL "https://web.archive.org/web/20150418111911/http://www.omega.com/Pressure/pdf/PXM409.pdf" which redirects to a second Wayback Machine URL of "https://web.archive.org/web/20151017134840/http://www.omega.com/pressure/pdf/PXM409.pdf" ("the PDF webpage"). I preserved the underlying PDF file by accessing the PDF webpage via version 119.0.6045.200 of the Google Chrome web browser on December 4, 2023.

² See <https://archive.org/about/> for further information about the Internet Archive.

16. The resulting, preserved PDF was a file named “PXM409.pdf” of size 809,363 bytes (“the PDF file”). The PDF file has a SHA1 cryptographic hash value of 7aaa340fdcf5288b91eed4fe177c46781e291a88³.
17. A true and correct copy of this PDF file is attached here as Exhibit C.
18. The date code of the PDF webpage’s Wayback Machine URL was “20151017134840”, which was different than that associated with the webpage. Based on the disclosed formatting style of the Wayback Machine’s date codes, I discerned that the embedded date code associated with the PDF webpage correlated with a preservation timestamp of October 17, 2015, at 13:48:40 UTC.
19. “Metadata” refers to “data about data,” as distinguished from the visual or interactive content of the document being analyzed. This may include information such as the original creation date of a document, or names of the original creators. Internal metadata refers to the specific set of metadata stored within a file’s contents, rather than externally such as metadata stored in a computer’s filesystem or operating system. In this case the internal metadata was metadata specific to the “.PDF” file format.
20. I extracted internal metadata using the publicly available metadata extraction tool “exiftool” against the PDF file. The PDF file’s “Create Date” attribute was set to January 16, 2015, at 20:48, while both its “Metadata Date” and “Modify Date” attributes were set to January 20, 2015, at 16:10:10.
21. The version history of the PDF file embedded within the file’s metadata recorded 51 version history events for the PDF file, ranging from a “Creation” event on May 25, 2012, at

³ The SHA1 algorithm is one of many publicly-established mathematical functions commonly used to establish file integrity and uniqueness via cryptographic hashing resulting in a hexadecimally-formatted numerical output.

17:26:33 UTC to the most recent "Saved" event on January 15, 2015, at 19:42:57 UTC. These events track the history of the document preceding its most recent version.


22. Under penalties of perjury, I declare that the foregoing Declaration and the facts stated in it are true and correct.

By: Domeniz Rizzolo

Name: Domeniz Rizzolo

Title: Manager, Stroz Friedberg

Date: 2023-12-06



Christina
Christina Goedar
Commission # 881221

Domenic Rizzolo

Manager



+1 312 646 7352



domenic.rizzolo2@aon.com



200 East Randolph Street, Floor 10, Chicago IL, 60601

PROFESSIONAL EXPERIENCE

Stroz Friedberg, an Aon Company

Manager, April 2020 to present
Chicago, IL

Manage Chicago, formerly Minneapolis, forensic lab and directly supervise forensic and incident response examiners. Conduct digital forensic acquisitions and examinations of laptops, desktops, and other digital storage media in civil litigations, criminal matters, and internal investigations. Conduct significant breach investigations. Utilize various open-source and proprietary analysis tools to identify attacker presence and impact. Identify data exfiltration through forensic host analysis, memory analysis, and active SIEM and IDS monitoring. Preserved and analyzed data from laptops, desktop computers, servers, and mobile devices. Identify clients' risk related to internal IT infrastructure, publicly available IT assets, and other relevant attack surfaces.

Senior Consultant, April 2018 to May 2020

Consultant, June 2016 to April 2018

Cyber Associate, September 2015 to May 2016

Duo Security

Security Researcher, Labs Division & Office of the CTO, April 2014 to April 2015
Ann Arbor, MI

Contributed to special projects, assessments, and creation of strategic surprise in daily collaboration with CTO and Duo Labs research team. Created and refined content drawing 5,000+ unique viewers to the company website. Assisted in vulnerability research, cataloging, and disclosure; developed code in collaboration with Engineering, Product, and Marketing; published internal threat assessments.

Levy Restaurants: Park View at Ravinia Festival

Lead Server and Caterer, Summer 2012 to Summer 2013
Highland Park, IL

University of Michigan

Research Assistant on "The Cyberwar History Project", September 2012 to May 2013
Ann Arbor, MI

Researched and analyzed scholarly articles, tracked findings in database, interpreted and analyzed metadata, extrapolated trends. Other projects included presenting findings at annual University Research Symposium

Vector Marketing

Personal Sales Associate, Summer 2011
Northbrook, IL

About: Aon's Cyber Solutions offers holistic cyber risk management, unsurpassed investigative skills, and proprietary technologies to help clients uncover and quantify cyber risks, protect critical assets, and recover from cyber incident.

Cyber security services offered by Stroz Friedberg Inc. and its affiliates. Insurance products and services offered by Aon Risk Insurance Services West, Inc., Aon Risk Services Central, Inc., Aon Risk Services Northeast, Inc., Aon Risk Services Southwest, Inc., and Aon Risk Services, Inc. of Florida and their licensed affiliates.

www.aon.com/cyber-solutions | © Aon plc 2023. All rights reserved.

EDUCATION

University of Michigan, Ann Arbor, Michigan
Bachelors of Science, Mathematics - Discrete and Algorithmic Methods, May 2015

Certifications

GIAC Defending Advanced Threats (GDAT) 2020. Global Information Assurance Certification
GIAC Certified Forensic Analyst (GCFA), 2019-2023. Global Information Assurance Certification
GIAC Network Forensic Analyst (GNFA), 2018. Global Information Assurance Certification
GIAC Certified Forensic Examiner (GCFE), 2015-2023. Global Information Assurance Certification

Training

Stroz Friedberg Internal Cyber Training Program: Participate in regular in-house training presentations on current digital forensics, cybercrime response, computer security, desktop, and network forensic tools in conjunction with relevant legal and industry matters. Lead advanced training for annual associate classes.

SANS DFIR, Forensics 509: Enterprise Cloud Forensics and Incident Response. Attended week-long training with focus on cloud hosting infrastructure, digital forensic processes in cloud computing environments, and responding to threats against enterprise cloud environments.

SANS DFIR, Security 599: Defeating Advanced Adversaries - Purple Team Tactics & Kill Chain Defenses. Attended week-long training with focus on advanced attack techniques and corresponding system defenses.

SANS DFIR, Forensics 508: Advanced Incident Response, Threat Hunting, and Digital Forensics. Attended week-long training on enterprise incident response and forensics.

SANS DFIR, Forensics 572: Advanced Network Forensics. Attended week-long training focused on evidence collection and analysis of computer networks.

SANS DFIR, Security 504: Hacker Tools, Exploits, and Incident Handling. Attended week-long training focused on incident response and network intrusion techniques.

SANS DFIR, Forensics 408: Windows Forensic Analysis, September 2015 Attended week-long training on in-depth forensic analysis of Windows operation systems.

Lectures and Presentations

Winter Semester 2016, 2017, 2018, 2020, 2021, 2022, 2023: Guest Lecture presentation "Introduction to Forensics", at Loyola University Chicago class on Electronic Discovery Law & Problem Solving

August 2014: Presented on "Hacker Community and Culture", at BSides InfoSec Conference, Las Vegas, NV

May 2017: Guest Lecture presentation "Digital Forensics & Incident Response", at DePaul University

February 2018: Guest Lecture presentation "Simplified Kill Chain: Actor Sophistication" at Northwestern University class "COMP_SCI 355: Digital Forensics and Incident Response"

May 2018: Presented on "Family-Style Incident Response" at BSides Chicago Conference

September 2018: Presenter on "What Keeps You Up at Night" roundtable at Washington University in St. Louis

Awards and Recognition

SANS Institute "DFIR Netwars" Individual Event Winner, December 2020

SANS Institute "DFIR Netwars" Team Event Winner, December 2017 & 2018

Michigan Traditions Scholarship for Notable Academic Achievement, University of Michigan, 2012 - 2015

Paul Taylor Award for Most Valuable Member, University of Michigan Men's Glee Club,

Llangollen Award for Tradition, Camaraderie, and Musical Excellence, University of Michigan Men's Glee Club,

Youth Leadership Award, Archdiocese of Chicago Vicariate II,



Your One-Stop Source for Process Measurement & Control!

1-888-TC-OMEGA (1-888-826-6342) US and Canada
1-203-359-1660 INTERNATIONAL

☐ Part Number ☒ All OMEGA



[Home](#) [Quick Order](#) [Products](#) [Search Tools](#) [Support](#) [About OMEGA](#) [My Account](#) [Select Region](#)

Product Groups

- Temperature >
- Pressure, Strain, Force >
- Flow & Level >
- pH & Conductivity >
- Electric Heaters >
- Data Acquisition >
- Automation >
- What's New

Application/Industry

- Wireless
- Sanitary
- Test & Measurement >
- Process Control >
- Power Monitoring >
- Environmental >
- Lab Equipment >

Support

- Manuals
- Technical Reference
- Currently Offline
[Leave a Message](#)
- FTP Site

[Home](#) >> [Pressure Strain and...](#) >> [Pressure Transducers](#) >> [Pressure Transducer...](#) >> PXM409

High (0.08%) Accuracy Metric Pressure Transducers

PXM409

High Accuracy Metric Pressure Transducers



\$475.00 PXM409-350HGV

[PLACE ORDER](#)



- 5-Point Agency Traceable Calibration Included
- Metric Pressure Ranges
- G 1/4 Thread Standard
- 0 to 100 mV, 0 to 10 Vdc, or 4 to 20 mA Outputs
- Gauge, Compound Gauge, Absolute, Vacuum and Barometric Pressure Ranges Available
- Welded Stainless Steel Construction
- 316 Stainless Steel Wetted Parts
- Premium Temperature Performance
- Broad Compensated Temperature Range
- Ruggedized with Secondary Containment

[View related products - Pressure Transducers](#)



Related Products



Printer Friendly

Omega's high accuracy piezoresistive pressure transducers have a proven record in high performance commercial and aerospace applications for over 25 years. The piezoresistive process uses strain gages molecularly embedded into a highly stable silicon wafer. The silicon wafer is diced into individual die which each contain a full strain gage bridge. The die is mounted in a sealed chamber protected from the environment by glass to metal seals and a stainless steel diaphragm.

A small volume of silicone oil transfers the pressure from the diaphragm to the strain bridge. The construction provides a very rugged transducer with exceptional accuracy, stability and thermal effects. A unique design ruggedizes the transducers by providing secondary fluid containment in the event of a diaphragm rupture.

At our state-of-the-art facilities, automated test equipment performs pressure and temperature cycling on 100% of the PX409 transducers. The transducers are then calibrated using extremely high accuracy equipment and a 5-point NIST traceable calibration certificate is included with each transducer. The inherent stability of the piezoresistive core provides excellent long term stability, repeatability and very low thermal effects at the price of much lower performance transducers. Standard features of the PX409 Series also include protective features built into the electronics and the pressure element. Reverse polarity, EMC, and power supply fluctuation protection are standard on all models. For Intrinsically Safe and CSA ratings see model PXM509.

The most popular ranges and configurations are stocked for immediate delivery. All others typically have very short lead-time.



PRESSURE TRANSDUCER CONFIGURATOR

Still can't find the right model? Specify the perfect transducer for your application with this easy, step-by-step configurator.

The PXM409 is also available in standard/imperial configurations, with NPT ports, and models from 0-10 inH2O to 0-5,000 psi pressure ranges. Please see the [PX409](#) for complete details, or contact our Pressure department for more information..

SPECIFICATIONS

Accuracy: Standard $\pm 0.08\%$ FS, BSL, Linearity, Hysteresis and Repeatability Combined

(compound ranges calibrated only in positive direction)

Operating Temperature:

mV/V Output: -45 to 121°C (-49 to 250°F)

Amplified Output: -45 to 115°C (-49 to 239°F)

Compensated Temperature Range:

25 to 350 mB: -18 to 85°C (0 to 185°F)

1 to 350 bar: -29 to 85°C (-20 to 185°F)

Thermal Accuracy: % span shift over compensated temperature range

25 to 350 mB:

Zero: ±1.0% max

Span: ±1.0% max

1 to 350 bar:

Zero: ±0.50% max

Span: ±0.50% max

ROHS Compliant

Minimum Isolation Between Case and Terminations: 100 MΩ @ 50 Vdc

Pressure Cycles: 1 million, minimum

Long Term Stability (1-Year): ±0.1% FS typical

Shock: 50 g, 11 ms half sine shock, Vertical and Horizontal

Vibration: 5-2000-5 Hz 30 minute cycle, Curve L, Mil Spec 810 figure 514-2-2, Vertical and Horizontal

Bandwidth: DC to 1 kHz typical

Response Time: <1 ms

CE Compliant: Industrial Level

Emissions: IEC550022 Class B

Electrostatic Discharge Immunity: IEC1000-4-2

EM Field Immunity: IEC61000-4-3

EFT Immunity: IEC61000-4-4

Surge Immunity: IEC61000-4-5

Conducted RF: IEC610000-4-6

Rate Power Frequency Magnetic Field: IEC61000-4-8

Environmental Protection:

PXM409: IP67

PXM419: IP65 gauge, IP67 Abs

PXM459: IP65 gauge, IP67 Abs

Proof Pressure Gauge/Vac/Compound:

25 mB: 10 times span

70 mB: 6 times span

170 mB to 100 bar: 4 times span

175 to 350 bar to 500 bar max

Proof Pressure Absolute:

350 mB to 100 bar: 4 times span

175 to 350 bar: to 500 bar max

Secondary Containment;

Gauge/Vac/Compound:

25 to 350 mB: to 70 bar

1 to 70 bar: to 200 bar

100 to 350 bar: to 700 bar

Absolute/Barometric:

350 mB: to 70 bar

1 to 70 bar (includes barometric ranges): to 200 bar

100 to 350 bar: to 700 bar

Wetted Parts: 316L SS

Electrical Terminations

PXM409: 2 m (6.6') cable

PXM419: mini DIN with mating connector

PXM459: M12 4-pin

Pressure Port: G1/4

Weight: 115 to 200 gm depending upon configuration

Electrical Outputs:

mV/V Output:

Output: 10 mV/V ratiometric

Supply Voltage: 5 to 10 Vdc (5 mA @ 10 Vdc)

Zero Balance:

Ranges > 170 mB: ±0.5% typ. (1% max)

Ranges ≤ 170 mB: ±1% typ. (2% max)

Span Setting:

Ranges > 170 mB: ±0.5% typ. (1% max)

Ranges ≤ 170 mB: ±1% typ. (2% max)

Input/Output Resistance: 5000 Ω ±20%

Voltage Output:

Output: 0 to 10 Vdc

Supply Voltage: 15 to 30 Vdc @ 10 mA (±10 Vdc or compound)

Zero Balance:

Ranges > 170 mB: ±0.5% typ. (1% max)

Ranges ≤ 170 mB: ±1% typ. (2% max)

Span Setting:

Ranges > 170 mB: ±0.5% typ. (1% max)

Ranges ≤ 170 mB: ±1% typ. (2% max)

Current Output:

Output: 4 to 20 mA (zero pressure = 12 mA on compound ranges)

Supply Voltage: 9 to 30 Vdc (9 to 20 Vdc above 105°C) max loop resistance = (Vs-9) x 50 Ω

Zero Balance:

Ranges > 170 mB: ±0.5% typ. (1% max)

Ranges ≤ 170 mB: ±1% typ. (2% max)
Span Setting:
Ranges > 170 mB: ±0.5% typ. (1% max)
Ranges ≤ 170 mB: ±1% typ. (2% max)

The table below features models with 10 mV/V ratiometric outputs.
To order 4-20 mA output change the suffix "V" to an "I"
To order 0-10 Vdc output change the suffix "V" to an "10V"
Or see the Part Number Builder below the table to order all models.

To Order (Specify Model Number)					ADD TO CART +
What Other People Bought: When you see this icon, click on it to expand a list of products that other people have bought when they purchased this model.					
Part Number	Availability	Price	Description	Qty.	
Gauge Pressure Models					
PXM409-001BGV	1 Week	\$475.00	1 bar gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-010BGV	1 Week	\$475.00	10 bar gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-350BGV	In Stock	\$475.00	350 bar gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-100BGV	1 Week	\$475.00	100 bar gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-350HGV	1 Week	\$475.00	350 mbar gauge pressure high accuracy transducer, mV/V output, cable connection	0	
Absolute Pressure Models					
PXM409-350HAV	In Stock	\$495.00	350 mbar absolute pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-002BAV	1 Week	\$495.00	2 bar absolute pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-010BAV	1 Week	\$495.00	10 bar absolute pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-245BAV	1 Week	\$495.00	245 bar absolute pressure high accuracy transducer, mV/V output, cable connection	0	
Vacuum (Negative Gauge) Pressure Models					
PXM409-025HVV	1 Week	\$600.00	25 mbar vacuum (negative gauge) pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-070HVV	1 Week	\$600.00	70 mbar vacuum (negative gauge) pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-170HVV	1 Week	\$600.00	170 mbar vacuum (negative gauge) pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-350HVV	1 Week	\$550.00	350 mbar vacuum (negative gauge) pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-001BVV	1 Week	\$550.00	1 bar vacuum (negative gauge) pressure high accuracy transducer, mV/V output, cable connection	0	
Compound Gauge Pressure Models					
PXM409-025HCGV	1 Week	\$665.00	±25 mbar compound gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-070HCGV	In Stock	\$665.00	±70 mbar compound gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-170HCGV	1 Week	\$665.00	±170 mbar compound gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-350HCGV	1 Week	\$665.00	±350 mbar compound gauge pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-001BCGV	1 Week	\$615.00	±1 bar compound gauge pressure high accuracy transducer, mV/V output, cable connection	0	
Barometric Pressure Models					
PXM409-1100HBV	In Stock	\$625.00	0 to 1100 mbar barometric pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-550HBV	1 Week	\$625.00	550 to 1100 mbar barometric pressure high accuracy transducer, mV/V output, cable connection	0	
PXM409-880HBV	1 Week	\$625.00	880 to 1100 mbar barometric pressure high accuracy transducer, mV/V output, cable connection	0	
Accessories					
CX5302	In Stock	\$15.00	Replacement micro mini DIN connector for PXM419, 4 contacts on 9.4 mm (0.37") spacing with PG7 gland	0	
CX5303	In Stock	\$25.00	Micro mini DIN connector, 4 contacts on 9.4 mm (0.37") spacing with 1/2" conduit fitting	0	

	M12C-PVC-4-S-F-5	In Stock	\$15.50	PVC cable, straight 4-pin M12 female connector one end, flying leads one end, 5 m (16') long	0
	M12C-PVC-4-S-F-107	Weeks	\$18.50	PVC cable, straight 4-pin M12 female connector one end, flying leads one end, 10 m (32') long	0
Compatible Panel Meters					
	DP25B-S	In Stock	\$250.00	4-digit strain meter for mV/V transducers	0
	DP25B-E	In Stock	\$250.00	4-digit process meter for 10V or 4 to 20 mA transducers	0
	DP41-B	In Stock	\$525.00	6-digit process meter for 10V or 4 to 20 mA transducers	0
					ADD TO CART +

† All dollar amounts on this site are shown in US currency.

Note: All models come with a NIST traceable calibraton certificate.

Ordering Example: (1) **PXM409-007BGV** 0.08% accuracy, G 1/4 Th'd, 7 bar range, 10 mV/V output, cable termination, **\$475.00**

Part Number Builder

(1)

(2)

(3)

(4)

PXM4

0

9-

025H

G

V

Qty: 1

Option Descriptions

(1)Electrical Termination

Select

- 0 for 2m cable
- 1 for mini DIN
- 5 for M12 4-pin male connector

(2)bar Range - Not all ranges are available for every pressure type

Select

- 025H for 25 mbar
- 070H for 70 mbar
- 170H for 170 mbar
- 350H for 350 mbar
- 1100H for 0 to 1100 mbar (barometric models only)
- 550H for 550 to 1100 mbar (barometric models only)
- 880H for 880 to 1100 mbar (barometric models only)
- 001B for 1 bar
- 002B for 2 bar
- 3.5B for 3.5 bar
- 007B for 7 bar
- 010B for 10 bar
- 17.5B for 17.5 bar
- 035B for 35 bar
- 050B for 50 bar
- 070B for 70 bar
- 100B for 100 bar
- 175B for 175 bar
- 245B for 245 bar
- 350B for 350 bar

(3)Pressure Type

Select

- G for Gauge
- A for Absolute
- V for Vacuum
- CG for Compound Gauge
- B for Barometric

(4)Output

Select

- V for 10 mV/V
- 10V for 0 to 10 Vdc
- I for 4 to 20 mA

NOTE: All combinations may not be valid, check spec sheet for valid part numbers.

Related Links - Related Products

Related Products



[PX409 Gage and Absolute Pressure:](#)
PX409 Series High Accuracy Pressure Transducers
Now with 0.05% Accuracy and 0.03% Linearity Options



DP41-S:

High Performance Strain Gage Meter, High Resolution 6-Digit Display

Keywords:High Accuracy Metric Pressure Transducers Metric Pressure Transducer Metric Pressure Ranges PXM409, electrical panel meters limit switch circuit negative temperature coefficient thermistor pressure level measurement

[Back to top](#)

[Anemometer](#) | [Automation](#) | [Accelerometers](#) | [Calibrators](#) | [Cartridge Heaters](#) | [Chart Recorders](#) | [Cryogenics](#) | [Custom Pressure Transducers](#) | [Data Loggers](#) | [Data Acquisition](#) | [Dial Thermometers](#) | [Fiber Optics](#) | [Flexible Heaters](#) | [Flowmeters](#) | [Glass Bulb Thermometers](#) | [Grippers](#) | [Heaters](#) | [Humidity Measurement](#) | [Integrated Circuit Sensors](#) | [Immersion Heaters](#) | [Infrared Thermometers](#) | [Level Measurement](#) | [Load Cells](#) | [M12 Temperature Connectors](#) | [Magnetic Flow Meters](#) | [Panel Meters](#) | [PID Controllers](#) | [pH meter](#) | [Pressure Gauges](#) | [Pressure Transducers](#) | [Pressure Transmitters](#) | [Rotameters](#) | [RTD](#) | [Remote Process Monitoring](#) | [Sanitary Sensors](#) | [Signal Conditioners](#) | [Stepper Motors](#) | [Strain Gages](#) | [Strip Heaters](#) | [Temperature Controllers](#) | [Temperature Labels](#) | [Temperature Measurement](#) | [Temperature Sensor Manufacturing](#) | [Temperature Sensors](#) | [Temperature Transmitters](#) | [Thermal Imagers](#) | [Thermistors](#) | [Thermocouple](#) | [Thermocouple Wire](#) | [Thermowell](#) | [Ultrasonic Flow Meters](#) | [Wireless Sensors](#)

© Copyright 2003-2015 OMEGA Engineering inc. | [OMEGA privacy statement](#) | [Terms and Conditions](#) | [Export Control Policy](#)



PRECISION MICRO-MACHINED SILICON TRANSDUCERS AND TRANSMITTERS

**Gauge Pressure, Absolute, Vacuum,
Compound and Barometric Ranges**
±25 mbar to 0-350 bar Ranges
10 mV/V, 0 to 10 Vdc or 4-20 mA Outputs

PXM409 Series



- ✓ 5-Point Agency Traceable Calibration Included
- ✓ Gauge, Compound Gauge, Absolute, Vacuum and Barometric Pressure Ranges Available
- ✓ Welded Stainless Steel Construction
- ✓ 316 SS Wetted Parts
- ✓ Premium Temperature Performance
- ✓ Broad Compensated Temperature Range
- ✓ Ruggedized with Secondary Containment

The PXM409 Series use a micro-machined piezoresistive silicon element for high accuracy and all stainless steel wetted parts for durability and superior chemical compatibility. Their high accuracy combined with very high thermal compensation (0.7% Typ.) over the compensated range make the PXM409 series ideal for scientific or industrial applications requiring a rugged, high accuracy transducer with very low thermal drift. They can be used in test benches, laboratory testing, engine testing, ground test stations and other industrial applications requiring

durable, precision transducers. Their standard accuracy is a high industrial grade accuracy of 0.08%. The modular construction allows for fast delivery of most models (typically 2-week maximum). Models are available with gauge (relative), compound gauge, absolute, vacuum (negative gauge) and barometric pressure ranges.

SPECIFICATIONS

Accuracy: Standard $\pm 0.08\%$ FS, BSL, linearity, hysteresis and repeatability combined (compound ranges calibrated only in positive direction)

Operating Temperature:

mV/V Output: -45 to 121°C
(-49 to 250°F)

Amplified Output: -45 to 115°C
(-49 to 239°F)

Compensated Temperature Range:

25 to 350 mB: -18 to 85°C
(0 to 185°F)

1 to 350 bar: -29 to 85°C
(-20 to 185°F)

**0.08% Accuracy
Standard**

Cable style.



PXM409-001BGV,
shown smaller
than actual size.

mini DIN
style.




PXM419-007BGI,
shown smaller
than actual size.

M12
connector
style.



PXM459-002BAV,
shown smaller
than actual size.

PXM409: 2 m (6.6')
cable IP67 rating



PXM459: M12 connector
IP67 rating, absolute
IP65 rating, gauge



PXM419: mini DIN
IP67 rating, absolute
IP65 rating, gauge



Thermal Accuracy: % span shift over compensated temperature range

25 to 350 mB:

Zero: $\pm 1.0\%$ max

Span: $\pm 1.0\%$ max

1 to 350 bar:

Zero: $\pm 0.50\%$ max

Span: $\pm 0.50\%$ max

ROHS Compliant

Minimum Isolation Between Case and Terminations: 100 M Ω @ 50 Vdc

Pressure Cycles: 1 million, minimum

Long Term Stability (1-Year):

$\pm 0.1\%$ FS typical

Shock: 50 g, 11 ms half sine shock, vertical and horizontal

Vibration: 5-2000-5 Hz 30 minute cycle, Curve L, Mil Spec 810 figure 514-2-2, vertical and horizontal

Bandwidth: DC to 1 kHz typical

Response Time: <1 ms

CE Compliant: Industrial Level

Emissions: IEC550022 Class B

Electrostatic Discharge Immunity: IEC1000-4-2

EM Field Immunity: IEC61000-4-3

EFT Immunity: IEC61000-4-4

Surge Immunity: IEC61000-4-5

Conducted RF: IEC61000-4-6

Rate Power Frequency Magnetic Field: IEC61000-4-8

Environmental Protection:

PXM409: IP67

PXM419: IP65 gauge, IP67 Abs

PXM459: IP65 gauge, IP67 Abs

Proof Pressure Gauge/Vac/Compound:

25 mB: 10 times span

70 mB: 6 times span

170 mB to 100 bar: 4 times span

175 to 350 bar: to 500 bar max

Proof Pressure Absolute:

350 mB to 100 bar: 4 times span

175 to 350 bar: to 500 bar max

Secondary Containment; Gauge/Vac/Compound:

25 to 350 mB: to 70 bar

1 to 70 bar: to 200 bar

100 to 350 bar: to 700 bar

Absolute/Barometric:

350 mB: to 70 bar

1 to 70 bar (Includes Barometric Ranges): to 200 bar

100 to 350 bar: to 700 bar

Wetted Parts: 316L SS

Electrical Terminations

PXM409: 2 m (6.6') cable

PXM419: mini DIN with mating connector

PXM459: M12 4-pin

Pressure Port: G $\frac{1}{4}$ standard

Weight: 115 to 200 gm depending upon configuration

Electrical Outputs

mV/V Output:

Output: 10 mV/V ratiometric

Supply Voltage: 5 to 10 Vdc

(5 mA @ 10 Vdc)

Zero Balance:

Ranges > 170 mB: $\pm 0.5\%$ typ (1% max)

Ranges $\leq$ 170 mB: $\pm 1\%$ typ (2% max)

Span Setting:

Ranges > 170 mB: $\pm 0.5\%$ typ (1% max)

Ranges $\leq$ 170 mB: $\pm 1\%$ typ (2% max)

Input/Output Resistance: 5000 Ω $\pm 20\%$

Voltage Output:

Output: 0 to 10 Vdc

Supply Voltage: 15 to 30 Vdc @ 10 mA (± 10 Vdc or compound)

Zero Balance:

Ranges > 170 mB: $\pm 0.5\%$ typ (1% max)

Ranges $\leq$ 170 mB: $\pm 1\%$ typ (2% max)

Span Setting:

Ranges > 170 mB: $\pm 0.5\%$ typ (1% max)

Ranges $\leq$ 170 mB: $\pm 1\%$ typ (2% max)

Current Output:

Output: 4 to 20 mA (zero pressure = 12 mA on compound ranges)

Supply Voltage: 9 to 30 Vdc (9 to 20 Vdc above 105°C) max loop resistance = (Vs-9) x 50 Ω

Zero Balance:

Ranges > 170 mB: $\pm 0.5\%$ typ (1% max)


Ranges $\leq$ 170 mB: $\pm 1\%$ typ (2% max)

Span Setting:

Ranges > 170 mB: $\pm 0.5\%$ typ (1% max)


Ranges $\leq$ 170 mB: $\pm 1\%$ typ (2% max)

Integral cable back end PXM409




Dimensions: mm (inch)
 $\varnothing$ = diameter

mini DIN back end PXM419



PXM409 CABLE CONNECTION			
Color	mV	5/10V	mA
Black	- EXC	Common	- Supply
White	+ SIG	+ Output	NC
Green	- SIG	NC	NC
Red	+ EXC	+ EXC	+ Supply




PXM419/PXM459 PINOUT			
PIN	mV	5/10V	mA
1	+ EXC	+ EXC	+ Supply
2	- EXC	Common	- Supply
3	+ SIG	+ Output	NC
4	- SIG	NC	NC

Product Label

Hex 22 (0.87) AF


G $\frac{1}{4}$ Pressure Fitting



PXM409 Series pressure ranges >1 bar to 70 bar for pressure ranges above 70 bar consult factory.

Hex 25 (1.0) AF

G $\frac{1}{4}$ Pressure Fitting




PXM409 Series pressure ranges 1 bar and below.


Gauge and Absolute Pressure Models

Thermal Effects -29 to 85°C (-20 to 185°F)

Span Error: 100 psig



USB Models Available



High 0.08% Accuracy Models

To Order

RANGE	MODEL NO. 0.08% ACCURACY	DESCRIPTION
GAUGE (RELATIVE) PRESSURE		
25 mbar (hPa)	PXM4[*]9-025HG[**]	25 mbar gauge pressure
70 mbar (hPa)	PXM4[*]9-070HG[**]	70 mbar gauge pressure
170 mbar (hPa)	PXM4[*]9-170HG[**]	170 mbar gauge pressure
350 mbar (hPa)	PXM4[*]9-350HG[**]	350 mbar gauge pressure
1 bar	PXM4[*]9-001BG[**]	1 bar gauge pressure
2 bar	PXM4[*]9-002BG[**]	2 bar gauge pressure
3.5 bar	PXM4[*]9-3.5BG[**]	3.5 bar gauge pressure
7 bar	PXM4[*]9-007BG[**]	7 bar gauge pressure
10 bar	PXM4[*]9-010BG[**]	10 bar gauge pressure
17.5 bar	PXM4[*]9-17.5BG[**]	17.5 bar gauge pressure
35 bar	PXM4[*]9-035BG[**]	35 bar gauge pressure
50 bar	PXM4[*]9-050BG[**]	50 bar gauge pressure
70 bar	PXM4[*]9-070BG[**]	70 bar gauge pressure
100 bar	PXM4[*]9-100BG[**]	100 bar gauge pressure
175 bar	PXM4[*]9-175BG[**]	175 bar gauge pressure
245 bar	PXM4[*]9-245BG[**]	245 bar gauge pressure
350 bar	PXM4[*]9-350BG[**]	350 bar gauge pressure
ABSOLUTE PRESSURE		
350 mbar (hPa)	PXM4[*]9-350HA[**]	350 mbar absolute pressure
1 bar	PXM4[*]9-001BA[**]	1 bar absolute pressure
2 bar	PXM4[*]9-002BA[**]	2 bar absolute pressure
3.5 bar	PXM4[*]9-3.5BA[**]	3.5 bar absolute pressure
7 bar	PXM4[*]9-007BA[**]	7 bar absolute pressure
10 bar	PXM4[*]9-010BA[**]	10 bar absolute pressure
17.5 bar	PXM4[*]9-17.5BA[**]	17.5 bar absolute pressure
35 bar	PXM4[*]9-035BA[**]	35 bar absolute pressure
50 bar	PXM4[*]9-050BA[**]	50 bar absolute pressure
70 bar	PXM4[*]9-070BA[**]	70 bar absolute pressure
100 bar	PXM4[*]9-100BA[**]	100 bar absolute pressure
175 bar	PXM4[*]9-175BA[**]	175 bar absolute pressure
245 bar	PXM4[*]9-245BA[**]	245 bar absolute pressure
350 bar	PXM4[*]9-350BA[**]	350 bar absolute pressure


[*] [**] See next page for selection.

Vacuum, Compound and Barometric Pressure Models



PXM409 SERIES SILICON WAFER TECHNOLOGY

PXM409 Series uses a highly stable silicon wafer which is micro-machined to precision tolerances and then has strain gauges molecularly embedded into it.



Strain gauges shown larger than actual size.

High 0.08% Accuracy Models

To Order

RANGE	MODEL NO. 0.08% ACCURACY	DESCRIPTION
VACUUM (NEGATIVE GAUGE) RANGES (ZERO OUTPUT = AMBIENT)		
25 mbar (hPa)	PXM4[*]9-025HV[**]	25 mbar vacuum (negative gauge)
70 mbar (hPa)	PXM4[*]9-070HV[**]	70 mbar vacuum (negative gauge)
170 mbar (hPa)	PXM4[*]9-170HV[**]	170 mbar vacuum (negative gauge)
350 mbar (hPa)	PXM4[*]9-350HV[**]	350 mbar vacuum (negative gauge)
1 bar	PXM4[*]9-001BV[**]	1 bar vacuum (negative gauge)
COMPOUND GAUGE RANGES† (BI-DIRECTIONAL OUTPUT)		
±25 mbar (hPa)	PXM4[*]9-025HCG[**]	±25 mbar compound gauge
±70 mbar (hPa)	PXM4[*]9-070HCG[**]	±70 mbar compound gauge
±170 mbar (hPa)	PXM4[*]9-170HCG[**]	±170 mbar compound gauge
±350 mbar (hPa)	PXM4[*]9-350HCG[**]	±350 mbar compound gauge
±1 bar	PXM4[*]9-001BCG[**]	±1 bar compound gauge
BAROMETRIC (ABSOLUTE) PRESSURE RANGES		
0 to 1100 hPa	PXM4[*]9-1100HB[**]	0 to 1100 mbar barometric
550 to 1100 hPa	PXM4[*]9-550HB[**]	550 to 1100 mbar barometric
880 to 1100 hPa	PXM4[*]9-880HB[**]	880 to 1100 mbar barometric

ACCESSORIES

MODEL NO.	DESCRIPTION
CX5302	Replacement micro mini DIN connector for PXM419, 4 contacts on 9.4 mm (0.37") spacing with PG7 gland
CX5303	Micro mini DIN connector, 4 contacts on 9.4 mm (0.37") spacing with ½" conduit fitting
M12C-PVC-4-S-F-5	PVC cable, straight 4-pin M12 female connector one end, flying leads one end, 5 m (16') long
M12C-PVC-4-S-F-10	PVC cable, straight 4-pin M12 female connector one end, flying leads one end, 10 m (32') long
COMPATIBLE PANEL METERS	
DP25B-S	4-digit strain meter for mV/V transducers
DP25B-E	4-digit process meter for 10V or 4 to 20 mA transducers
DP41-B	6-digit process meter for 10V or 4 to 20 mA transducers

[*] Select Electrical Termination: **0** = 2 m (6') cable, **1** = mini DIN, **5** = M12, 4-pin male connector.

[**] Select Output: **V** = 10 mV/V, **10V** = 0 to 10 Vdc, **I** = 4 to 20 mA.

† Compound range models are calibrated in the positive direction only.

Ordering Examples: PXM409-007BGV, 0.08% accuracy, 7 bar range, 10 mV/V output, cable termination.

PXM419-001BAI, 0.08% accuracy, 1 bar absolute range, 4 to 20 mA output, mini DIN termination.

PXM459-350HV10V, 0.08% accuracy, 350 mbar Vacuum (ambient to -350 mB) range, 0 to 10 Vdc output, M12 termination.