




US 20130067303A1

(19) **United States**(12) **Patent Application Publication**  
**Kantor et al.**(10) **Pub. No.: US 2013/0067303 A1**(43) **Pub. Date: Mar. 14, 2013**(54) **DISTINCT LINKS FOR PUBLISH TARGETS**(52) **U.S. CL.**

USPC ..... 715/205

(75) Inventors: **Arcadiy G. Kantor**, Seattle, WA (US);  
**Jonathan A. Bockelman**, Kirkland, WA  
(US); **Jeffrey E. Steinbok**, Redmond,  
WA (US)(73) Assignee: **Microsoft Corporation**, Redmond, WA  
(US)(21) Appl. No.: **13/229,121**(22) Filed: **Sep. 9, 2011****Publication Classification**(51) **Int. Cl.**  
**G06F 17/00** (2006.01)(57) **ABSTRACT**

Techniques for sharing of items from online storage (e.g., cloud storage) are described herein. In one approach, distinct sharing links to an item can be generated for multiple different publish targets through a single publishing user interface exposed to a user. Through the publishing user interface, a user may submit a request having a selection of different social networks and/or other sites/targets to receive a sharing link for an item. In response to the request, a distinct sharing link is generated for each selected recipient and the generated sharing links are published to appropriate targets. Thus, a user is able to easily send links for a shared item to multiple targets through a single request and can separately manage permissions associated with each distinct sharing link.






Fig. 1

200 




*Fig. 2*





Fig. 3

400

*Fig. 4*




Fig. 5

600





Fig. 6

*Fig. 7*




Fig. 8

900





Fig. 9

Docket Number: 333783.01 Page: 10 of 15

Inventors: Kantor et al.

Title: Distinct Links for Publish Targets

1000

*Fig. 10*






Fig. 11

*Fig. 12*

1300

*Fig. 13*





Fig. 14

1500 *Fig. 15*

## DISTINCT LINKS FOR PUBLISH TARGETS

### BACKGROUND

[0001] The availability and popularity of web-based content and services is ever increasing. For example, users are increasingly using online storage services that provide storage “in the cloud” for content items (e.g., documents, application files, photos, mobile uploads, audio/video files, etc.). Storage in the cloud makes it convenient for users to access their files over a network from anywhere using various different kinds of devices (e.g., computer, mobile phone, tablet, etc.). Due in part to this convenience, users may also seek ways in which to share content items from their online storage with others.

[0002] Traditionally, though, online storage services provide limited tools for sharing items particularly in the case of sharing items to multiple sites, groups, and/or individuals. For instance, a user may have to individually configure an email or message for each intended recipient of a shared item and/or may have to manually provide a shared item as an attachment. In some cases, a user may even have to download a stored item locally before they can share the item through email or another messaging system. Thus, traditional techniques for sharing items from online storage may be quite inconvenient.

### SUMMARY

[0003] Techniques for sharing of items from online storage (e.g., cloud storage) are described herein. Sharing links for items maintained in online storage available from a service provider can be generated and distributed in various ways. The sharing links may provide recipients with access to shared items online from storage associated with the sender. The sender is able to manage permissions associated with different sharing links sent to different recipients on an individual basis.

[0004] In one or more implementations, distinct sharing links to an item can be generated for multiple different publish targets through a single publishing user interface exposed to a user. A request having a selection of publish targets by a user as recipients for a shared item can be received through the user interface and the request can be parsed to identify the publish targets. A distinct sharing link is then generated for each of the identified targets. The generated sharing links are published to the publish targets, which can include for example different social networks and/or websites. The distinct sharing links associated with an item may then be presented through an online service to enable individual management of the distinct sharing links.

[0005] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The detailed description is described with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different instances in the description and the figures may indicate similar or identical items.

[0007] FIG. 1 is an illustration of an environment in which sharing links for online storage may be employed in accordance with one or more embodiments.

[0008] FIG. 2 is an illustration of an example sharing link in accordance with one or more embodiments.

[0009] FIG. 3 depicts an example user interface for interaction with online storage in accordance with one or more embodiments.

[0010] FIG. 4 is a flow diagram depicting an example procedure in which distinct sharing links are generated for different publish targets.

[0011] FIG. 5 depicts an example user interface for publishing a sharing link in accordance with one or more embodiments.

[0012] FIG. 6 depicts an example user interface for management of distinct sharing links in accordance with one or more embodiments.

[0013] FIG. 7 is a flow diagram depicting an example procedure in which group opt-in links are employed to expose an option to join a group for a shared item.

[0014] FIG. 8 depicts an example user interface for getting a sharing link to implement a group opt-in option in accordance with one or more embodiments.

[0015] FIG. 9 depicts an example user interface for management of recipients that opt-in to a group in accordance with one or more embodiments.

[0016] FIG. 10 is a flow diagram depicting an example procedure in which one-time sharing links are employed to expose an option to select an account for a shared item.

[0017] FIG. 11 is a flow diagram depicting an example procedure for an authentication sequence that may be initiated by selection of a one-time sharing link.

[0018] FIG. 12 depicts an example user interface for sending a sharing link to implement an option to select an account for use to access a shared item in accordance with one or more embodiments.

[0019] FIG. 13 depicts an example user interface for prompting a user to select an account for use to access a shared item in accordance with one or more embodiments.

[0020] FIG. 14 depicts an example multiple device environment for online resources in accordance with one or more embodiments.

[0021] FIG. 15 depicts an example computing system in accordance with one or more embodiments.

### DETAILED DESCRIPTION

#### Overview

[0022] Traditionally, online storage services provide limited tools for sharing items particularly in the case of sharing items to multiple sites, groups, and/or individuals. For instance, a user may have to manually attach items to messages and/or publish an item to multiple different services/sites that the user wants to receive the item. Thus, traditional techniques for sharing items from online storage may be inconvenient.

[0023] Techniques for sharing of items from online storage (e.g., cloud storage) are described herein. In one approach, distinct sharing links to an item can be generated for multiple different publish targets through a single publishing user interface exposed to a user. Through the publishing user interface, a user may submit a request having a selection of different social networks and/or other sites/targets to receive a sharing link for an item. In response to the request, a distinct

sharing link is generated for each selected recipient and the generated sharing links are published to appropriate targets. Thus, a user is able to easily send links for a shared item to multiple targets through a single request and can separately manage permissions associated with each distinct sharing link.

**[0024]** In another approach, sharing links can be configured as group opt-in links designed to provide recipients with an option to join a group having permissions on a corresponding shared item. An owner of an item may distribute a group opt-in link publicly and does not have to predetermine the group size or individual members. Recipients of the link can choose whether to join the group or not. The group opt-in link may provide limited access to join the group and then members who join the group may gain enhanced permissions to the shared item. The owner of the item is able to see individuals who have opted-in and manage corresponding permissions on an individual basis.

**[0025]** In another approach, sharing links can be configured as one-time sharing links that provide recipients with limited, one-time access to a shared item for the purpose of selecting or registering an account to use for subsequent access to the item. The owner/sharer of the item may use any available contact information to send one-time sharing links. A recipient is then able to use the link to select an account the recipient would like to use to access the shared item. The owner/sharer does not need to send the link to the selected account or even have contact information for the account. Once the one-time sharing link is redeemed to select an account, the link may be invalidated for subsequently gaining enhanced permission to the item.

**[0026]** In the following discussion, an example operating environment is first described that may employ the techniques described herein. The discussion of the example operating environment includes a discussion of an example user interface to facilitate interaction with online storage. Next, example details and techniques are described which may be implemented in the example environment as well as other environments. Consequently, performance of the techniques is not limited to the example environment and the example environment is not limited to performance of the example techniques. Lastly, example systems and devices are described that may be employed to implement one or more embodiments.

#### **[0027]** Example Operating Environment

**[0028]** FIG. 1 is an illustration of an environment 100 in an example implementation that is operable to employ techniques described herein. The illustrated environment 100 includes a client device 102, another client device 104, a service provider 106, and a social network service 108 that are communicatively coupled via a network 110. The client device 102, other client device 104, service provider 106, and social network service 108 may be implemented by one or more computing devices and also may be representative of one or more entities. The social network service 108 is representative of various external web services/sites (e.g., partner sites) that may operate in conjunction with the service provider 106 to provide additional/enhanced experiences and services to users. In at least some embodiments, this occurs through linking or otherwise associating user accounts with the service provider 106 to corresponding accounts with the external web services/sites.

**[0029]** A computing device may be configured in a variety of ways. For example, a computing device may be configured as a computer that is capable of communicating over the network 110, such as a desktop computer, a mobile station, an entertainment appliance, a set-top box communicatively coupled to a display device, a wireless phone, a game console, and so forth. Thus, the computing device may range from full resource devices with substantial memory and processor resources (e.g., personal computers, game consoles) to a low-resource device with limited memory and/or processing resources (e.g., traditional set-top boxes, hand-held game consoles). Additionally, although a single computing device is shown in some instances, the computing device may be representative of a plurality of different devices, such as multiple servers utilized by a business to perform operations such as by the service provider 106 and/or social network service 108, and so on.

**[0030]** Although the network 110 is illustrated as the Internet, the network may assume a wide variety of configurations. For example, the network 110 may include a wide area network (WAN), a local area network (LAN), a wireless network, a public telephone network, an intranet, and so on. Further, although a single network 110 is shown, the network 110 may be configured to include multiple networks.

**[0031]** The client device 102 is further illustrated as including an operating system 112. The operating system 112 is configured to abstract underlying functionality of the underlying device to applications 114 that are executable on the client device 102. For example, the operating system 112 may abstract processing, memory, network, and/or display functionality such that the applications 114 may be written without knowing “how” this underlying functionality is implemented. The application 114, for instance, may provide data to the operating system 112 to be rendered and displayed by a display device as illustrated without understanding how this rendering will be performed.

**[0032]** The client device 102 is also illustrated as including a communication module 116. The communication module 116 represents functionality to enable various communications over the network 110. For example, the communication module 116 may be implemented as a browser or other suitable application to obtain and output webpages and/or other user interfaces from the service provider 106 over the network 110. The communication module 116 may also represent a component of another application used to obtain one or more resources from the service provider 102.

**[0033]** The service provider 106 is depicted as storing a resource manager 118 that represents functionality operable by the service provider 106 to manage various resources 120 that may be made available over the network 108. For example, various resources 120 may be provided via webpages or other user interfaces 122 that are communicated over the network for output by one or more clients via a communication module 116 or other client application. The resource manager 118 may manage access to the resources 120, performance of the resources, and configuration of user interfaces 122 to provide the resources 120, and so on. The service provider 106 may represent one or more server devices used to provide the various resources 120.

**[0034]** Generally, resources 120 made accessible by a service provider 106 may include any suitable combination of services and/or content typically made available over a network by one or more providers. Some examples of services include, but are not limited to, a search service, an email

service, an instant messaging service, an online productivity suite, and an authentication service to control access of clients to the resources **120**. Content may include various combinations of text, multi-media streams, documents, application files, photos, audio/video files animations, images, web pages, web applications, device applications, content for display by a browser or other client application, and the like.

**[0035]** One particular example of a resource **120** that may be provided by a service provider **106** is a collaboration service **124** as depicted in FIG. 1. The collaboration service **124** is representative of functionality operable to provide and manage online storage **126** that may be allocated to user accounts associated with the service provider **106**. The online storage **126** provides users with storage “in the cloud” for content items such as documents, application files, photos, mobile uploads, and audio/video files so user may access their content items from anywhere over the network **110**, and share content to collaborate with others. The collaboration service **124** enables users to share files with other individuals and/or groups through sharing links **128** that can be created and distributed for particular content items in various ways. The sharing links **128** are configured to implement permissions that may be set to control who is able to view, edit, or otherwise interact with corresponding content items, as discussed in greater detail in relation to FIG. 2.

**[0036]** Clients may access the collaboration service **124** and other resources **120** provided by a service provider **106** through user accounts represented by client account data **130** of FIG. 1. The client account data **130** may include account identifiers, credentials, access permissions, profile data and other data typically associated with user accounts. The resource manager **118** may implement or otherwise make use of an authentication service operable to authenticate clients to access various resources **120** including the collaboration service **124**. The authentication service may be provided as a component of the service provider **106**, as a standalone service, by a third party provider, or otherwise. To access resources **120**, a client device **104** may provide a username and password that is authenticated by the authentication service. When the authentication is successful (e.g., the client “is who they say they are”), the authentication service may pass a token to enable access to corresponding resources. A single authentication may correspond to one or more resources, such that authentication to a single account by a “single sign-on” may provide access to individual resources, resources from multiple service providers **106**, and/or to an entire suite of resources available from a service provider **106**.

**[0037]** FIG. 2 is a diagram showing an example implementation of a sharing link **128** in accordance with one or more embodiments, generally at **200**. In this example, the sharing link **128** is constructed to include a navigation path **202** that is associated with a sharing key **204**. The navigation path **202** provides a path that can be used to navigate to a corresponding content item. For example, the navigation path **202** may be configured as a uniform resource identifier (URI) that when selected causes an application such as a browser to navigate to a location where the resource is available. The sharing key **204** is configured as key, token, or other shared secret that can be used to make different distinct sharing links **128** to the same resource. Thus, the sharing key **204** uniquely identifies a particular, corresponding sharing link **128** and can be used to distinguish between sharing links.

**[0038]** Additionally, the sharing link **128** can encode data that defines or references permissions for a corresponding item. The permissions designate access levels and corresponding actions for content items. For instance, different access levels may be established to control who is able to perform actions such as read-only, print, publish, view, edit, one-time access, move, and/or copy, to name a few examples. In one approach, the service provider **106** maintains a table or other database that can be used to match a sharing key **204** to corresponding permissions on content items. Such permission data may be maintained as part of the file structure for online storage **126** along with individual files. This may include maintaining access control lists (ACLs) that may be referenced by or otherwise mapped to sharing keys **204**. Additionally or alternatively, permissions can be encoded directly within a sharing link using an access parameter or other suitable field that is indicative of a corresponding permission level. The collaboration service **124** may be configured to reference and interpret the access parameter in a sharing link **128** and enforce corresponding permissions when the sharing link **128** is used to gain access to an item.

**[0039]** FIG. 3 depicts a diagram **300** showing an example user interface **122** that includes one or more portions to enable interaction with online storage in accordance with one or more embodiments. The user interface **122** in this instance is illustrated as incorporated within a user interface **302** that may be provided by the communication module **116**. For example, the communication module **116** may be configured as a browser operable to expose the user interface **302** to enable interaction with one or more service providers **106** and corresponding resources **120**. The user interface **122** for example may be configured and provided by way of the collaboration service **124** as previously described.

**[0040]** To provide the interaction with online storage, the user interface **122** may expose a file management portion **304** to enable navigation, viewing, and management of content items stored “in the cloud” in association with a user/account. A file management portion **304** can be configured in any suitable way to enable the interaction with online storage, such as representing content items in a list, showing different icons or tiles for stored items, using a preview pane, and so forth. In the depicted example, the file management portion **304** is shown as a “My Files” list for a logged in user “Robyn.” The list of content items represents files available to Robyn from her online storage **126** through the collaboration service **124** including documents, folders, photos, and other types of content mentioned previously. The list of content items shows names for individual files and folders as well as basic information associated with each item, such as the example date and sharing columns depicted in FIG. 3.

**[0041]** An item details portion **306** is also shown that may be configured to provide more detailed information regarding a selected item, which in this example presents details for a “Reunion” folder selected from the list of content items. In addition, the user interface **122** includes a sharing portion **308** that represents functionality to review and manage sharing options for content items. In this example, the sharing portion **308** is incorporated as part of the item detail portion **306**. Alternatively, a sharing portion **308** may be provided as a separate portion or even a separate page that is accessible via a link, menu item, or other navigation instrumentality exposed in the user interface **122**. The sharing portion **308** is configured to provide various options for sharing of selected items. This may include creating sharing links **128**, viewing

and setting permissions for items, publishing links to a social network service **108** or other external web service/site, distributing links using various messaging systems, and so forth.

**[0042]** Thus, a user interface **122** such as the example just described may be employed to facilitate various interactions to access online storage **126** and/or share items. In accordance with sharing link techniques described herein, distinct links to a content item may be generated for different publish targets. In addition, links may be shared to an arbitrary group through a corresponding sharing link **128**. In this case, sharing link **128** is configured to expose an option for recipients to opt into the group having permissions on the item. Thus, recipients explicitly opt into the group before gaining full permission to the item. In another example, a recipient of a link may be able to choose a particular account to use for access a shared item. This may occur through a one-time link that may be redeemed once to access the item and associate a selected account for subsequent access to the shared item. Further details regarding each of these examples are discussed in turn below in different sections titled “Distinct Links for Publish Targets,” “Group Opt-In Links,” and “Shared Item Account Selection,” respectively.

**[0043]** Thus, having considered the foregoing discussion of an example operating environment and an example user interface for interaction with online storage, consider now details regarding techniques to employ sharing links in accordance with one or more embodiments.

**[0044]** Distinct Links for Publish Targets

**[0045]** This section describes techniques for publishing of sharing links **128** to different selected publish targets. In portions of the following discussion, reference will be made to the example environment **100** of FIG. **1** and example user interface of FIG. **3**. Generally speaking, a user may access associated online storage **126** through a collaboration service **124**. The user may be able to select an item to share as well as target recipients to receive a link to the item. The user action to share the item causes the collaboration service **124** to generate one or more sharing links **128** to the item. In one approach, the collaboration service **124** may generate distinct links to the same item for multiple different publish targets selected by the user. Accordingly, different permissions may be associated with the distinct links and the distinct links may be separately presented and managed. Just below, an example procedure is discussed followed by some example user interfaces illustrating further details regarding distinct links.

**[0046]** FIG. **4** depicts a procedure **400** in an example implementation in which distinct links are generated for different publish targets. Aspects of each of the procedures described herein may be implemented in hardware, firmware, or software, or a combination thereof. The procedures are shown as a set of blocks that specify operations performed by one or more devices and are not necessarily limited to the orders shown for performing the operations by the respective blocks.

**[0047]** A request is obtained to create distinct links for selected publish targets to share an item from online storage associated with a user account (block **402**). The request, for instance, may be formed via a user interface **122** output at a client device **102** for interaction with online storage **126** associated with a user. Thorough the user interface **122**, an item to share as well as different targets may be selected. This may occur through a publish control or page link provided as part of the user interface **122**. At least some of the targets may be social network services or other partner sites to which the user wishes to publish a link for the selected item.

**[0048]** The request may be formatted in any suitable way to encode information describing the selected item and targets. For example, the request may be configured as a hyper-text transfer protocol (HTTP) request using JavaScript, XML, HTML and/or other scripting languages. The request may include variables, parameters, and/or other suitable identifiers used to submit the item and targets for handling by a service provider **106**. Thus, the request may be formatted to encode the user selections in some manner and then submitted, which causes the client device **102** to communicate the request to a service provider **106**. In one example, a collaboration service **124** implemented by the service provider **106** is configured to obtain the request and process the request to generate corresponding sharing links **128**. In at least some embodiments, the collaboration service **124** may expose an application programming interface (API) that can be called with the request via script within a webpage or other user interface **122** to initiate creation of sharing links **128**. In addition or alternatively, any client-server architecture and/or communication protocols suitable for passing requests/responses between a client device **102** and service provider **106** may be employed to implement the techniques related to sharing links described herein.

**[0049]** In particular, the request is parsed to identify the selected publish targets (block **404**). For instance, the collaboration service **124** is able to interpret the request and extract information contained therein to identify selected publish targets. The collaboration service **124** also obtains from the request an identifier of the particular item to be shared with the publish targets. This information enables the collaboration service **124** to construct sharing links **128** as described previously.

**[0050]** For instance, a distinct sharing link is generated for each publish target identified (block **406**) and the generated sharing links are added to permissions on the item (block **408**). Here, the collaboration service **124** constructs a different link for each identified target. Each link may include a navigation path **202** to the item and a sharing key **204** as discussed above. The navigation path **202** to the item may be the same for each link. The sharing key **204**, though, may be generated as a unique identifier that is different for each link and corresponding target. In one example, the sharing key **204** is configured as a token that is different for each link.

**[0051]** Permissions to a shared item can also be encoded within the generated sharing links. As mentioned, the token or other sharing key **204** may be mapped to permissions on the item using ACLs that define the permissions. Thus, to encode permissions the collaboration service **124** may update the ACLs to reflect respective permissions designated for each of the generated sharing links. Using this technique, the system can store a mapping of permission for a sharing link that may or may not be apparent to the recipient(s) of the sharing link. In another approach, the sharing key **204** itself can be used to designate the permissions that the corresponding link grants to recipients/users of the link. In this case, the collaboration service **124** may be configured to interpret the sharing key **204** when a link is used to determine and enforce corresponding permissions.

**[0052]** The sharing links are published to the publish targets (block **410**). For example, the collaboration service **124**, in addition to creating the links, may be configured to publish links to various partner sites. Such partner sites may expose network accessible application programming interface (APIs) that can be invoked to publish information to user

accounts. For instance, a post link or post picture API may be provided to post content to a social network service **108**. The collaboration service **124** may be configured to form calls in appropriate formats designated by different supported partner sites via such APIs or otherwise. This enables a user of the collaboration service **124** to interact once to select an item and publish target, submit a single request, and then turn over handling to the collaboration service **124** to create the appropriate links and post the links to corresponding publish targets. Accordingly, the user is able to avoid individual creation and manually post links to different targets.

**[0053]** Representations of the distinct sharing links are presented in association with the item in a user interface for viewing and managing the online storage (block **412**) and individual management of the distinct sharing links associated with each publish target is enabled (block **414**). Since distinct sharing links are created for different targets, the links may be used and managed separately from one another. Thus, the collaboration service **124** may separately represent the distinct sharing links for an item within a user interface presented to review and manage stored items. For example, different sharing links may be listed via a sharing portion **308** of a user interface **122** as discussed in relation to FIG. **3**. In this way, a user is able to review each of the links generated for a particular item and see associated permissions. Additionally, the collaboration service **124** is configured to provide various options to separately manage distinct links for an item. This includes, but is not limited to, actions such as associating and changing permissions individually for different links, removing one or more links (e.g., un-publishing links) and/or invalidating a link without affecting other links on an item. Additional details regarding creating, using, and managing distinct links are provided in relation to example user interfaces of FIGS. **5** and **6**.

**[0054]** FIG. **5** depicts a diagram **500** showing an example user interface **122** that can be employed to publish a link to selected targets as just described. The user interface **122** in this instance is illustrated as incorporated within a user interface **502** that may be provided by the communication module **116**. For example, the communication module **116** may be configured as a browser operable to expose the user interface **502** to enable interaction with one or more service providers **106** and corresponding resources **120**. The interface **502** may alternatively be provided using a separate tab, a pop-up dialog box, an expandable portion of a page, or otherwise.

**[0055]** In at least some embodiments, the interface **502** may be accessible by selection of a link, menu item, or other navigation control provided in the example user interface of FIG. **3**. For instance, the example interface depicted in FIG. **5** may be presented responsive to selection of the “Publish a Link” object appearing within the sharing portion **308** in FIG. **3**. Thus, the different interfaces in the examples of FIGS. **3** and **5** may represent different pages available via the collaboration service **124**.

**[0056]** Here, the example user interface **122** is operable to create distinct sharing links **128** for the “Reunion” folder of FIG. **3**. A target selection portion **504** may be provided to enable input of a selection of publish targets by a user in any suitable way. In the depicted example, a list of available targets is presented along with check boxes to select/deselect different targets. The list may represent targets that have been pre-associated with a user’s account. Other selection controls such as a drop down box, search tool, list box, and/or other selection tools may also be implemented to enable input of the

selection. In addition, an add control **506** may be provided to enable a user to explicitly search for and/or add another network/site as a publish target. It should be noted, that publish targets to which distinct links are provided may also include individual people or contacts. Once added, a site/network/individual may automatically appear as a pre-associated option in subsequent publish operations.

**[0057]** The example user interface **122** of FIG. **5** further includes a message input portion **508**, a permissions portion **510**, and a publish control **512**. The message input portion **508** enables input of an optional description or message to accompany a published link. The permissions portion **510** enables selection of permissions to associate with the created links. For instance, the permissions portion **510** may allow a user to select whether created links may be used to view, edit, move, and/or grant admin rights to a corresponding item. In the illustrated example, the permissions portion **510** is configured to apply globally to each of the selected publish targets. In another approach, individual permissions portions **510** may be associated with each target to enable selection of different permissions for the different links. Again, various selection controls may be employed to implement permissions portions **510** including for example, check boxes, list boxes, drop down boxes, search tools, and other typical selection tools. The publish control **512** when selected causes a request having the selection made via the example interface to be submitted for handling by the service provider **106** and/or collaboration service as previously described.

**[0058]** FIG. **6** depicts a diagram **600** showing a sharing portion for review and management of distinct links. In particular, the item detail portion **306** of FIG. **3** is shown after distinct links are created for the “Reunion Folder” and the page is refreshed. Now, the sharing portion **308** has been reconfigured to include a list **602** of the distinct links created in accordance with procedure **400** of FIG. **4**. A representation of each distinct link published for the particular item is provided along with a corresponding permission control **604**. The permission controls **604** enable a user to individually view and manage permissions associated with the distinct links. For example, the permission controls **604** are illustrated as list boxes operable to select an access level (e.g., view, edit, move, copy, print, admin, etc.) for individual links. Further, the permission controls **604** may enable invalidation/removal of links on an individual basis. In addition to or in lieu of providing permission controls **604**, a edit permissions control **606** may be included. The edit permissions control **606** may be selectable to navigate to a permissions page that exposes various tools and options for review and management of permissions for particular items.

**[0059]** Group Opt-In Links

**[0060]** This section describes techniques for sharing links **128** configured to provide an option to opt-in to a group having permissions on an item. In portions of the following discussion, reference will again be made to the example environment **100** of FIG. **1** and example user interface of FIG. **3**. Generally speaking, a user may access associated online storage **126** through a collaboration service **124**. The user may be able to select a get a link option that causes a collaboration service **124** to provide a link for sharing an item. The user may then take action to copy and/or distribute in various ways. In one approach, the collaboration service **124** configures the link such that selection of the link causes an option to be exposed to join a group having permissions on a corresponding item. The group is not necessarily predetermined and

recipients of the link may be granted limited or no access to the item until the recipients explicitly opt into the corresponding group. Group membership is determined by those that exercise the group opt-in option. Recipients that do opt-in are granted permissions on the item that are established for the group. Subsequently, the owner of the item may view a list of recipients who have opted-in as members of the group, modify the group permissions, and/or modify permissions for members of the group on an individual basis. Just below, an example procedure is discussed followed by some example user interfaces illustrating details of techniques for group opt-in links.

**[0061]** FIG. 7 depicts a procedure 700 in an example implementation in which links configured for explicit opt-in to a group for a shared item are generated. A sharing link to share an item from online storage is generated in response to a request (block 702). As before, the request to get a link may be formed via a user interface 122 output at a client device 102 for interaction with online storage 126 associated with a user. A “get a link” request may also be formatted using various scripting languages, protocols, and/or communication techniques as discussed previously.

**[0062]** In one approach, the collaboration service 124 creates a link in response to the request that includes a navigation path 202 and a sharing key 204 as previously discussed. After generating the link, the collaboration service 124 communicates the link back to the client device 102 for presentation to the user. For instance, the collaboration service 124 may configure a webpage or other suitable user interface 122 including the link and return the webpage for output at the client in response to the request.

**[0063]** The collaboration service 124 may also configure the link to cause a group opt-in option to be exposed when the link is selected (e.g., clicked or navigated to) by recipients. This may occur in a variety of ways. For example, the sharing key 204 may be used as an identifier that prompts the collaboration service 124 to present an appropriate option to join a group when a link is used to gain access to the item. ACLs maintained by the collaboration service 124 may be used to designate that a particular sharing key is configured to cause the group opt-in option. The collaboration service 124 may use the sharing key 204 (or an identifier contained therein) to look-up permissions and properties of the corresponding link in the ACLs. Based on this matching of the sharing key 204 to ACLs, the collaboration service 124 is able to determine whether the link is configured for the group opt-in option.

**[0064]** In addition or alternatively, the collaboration service 124 may examine the sharing key 204 or another field contained within the link and determine directly from the examination that the link is configured for the group opt-in option. For example, a particular string or value associated with sharing key 204 may be used as a toggle to selectively indicate whether the group opt-in option is activated. Thus, the collaboration service 124 may set the toggle to activate the group opt-in option when generating a sharing link, which then prompts the collaboration service 124 to present the appropriate option when the link is used by a recipient.

**[0065]** The sharing link is distributed to one or more recipients (block 704). The sharing link may be communicated to a user and/or distributed to recipients in various ways. For example, the sharing link 128 generated per block 702 may be presented in a user interface 122 that enables a user to view and/or copy the link. The user may then distribute the link to selected recipients in any suitable way. For example, the user

may copy the link into a message and send the link to selected recipients as an email, instant message, text message, and so forth. Further, the user may take action to post the link to web services/sites, such as adding the link to a user profile page with a social network service 108. The link may also be distributed using other techniques such as by word of mouth, in ads, in written communications (electronic and/or physical), and so forth. In addition to providing a link that can be copied, a user interface 122 may also be configured to facilitate distribution of the link using one or more techniques as discussed further in relation to FIG. 8 below.

**[0066]** Note that distinct links as discussed above can also be created to activate the group opt-in option. If the user so chooses, the sharing link 128 generated per block 702 may be distributed to multiple publish targets using techniques discussed in relation to FIGS. 4-6. For example, the user may select a publish option that exposes an interface for selection of publish targets comparable to the example of FIG. 5. In this case, the distinct links created when the user publishes the link may also be configured to activate the group opt-in options. This may occur by modifying or otherwise employing the sharing link 128 generated per block 702 to produce multiple distinct links for the selected targets. Each of the distinct links is configured to include a sharing key or other suitable identifier to indicate that the group opt-in option is active.

**[0067]** Responsive to selection of the sharing link by recipients, an option is exposed for the recipients to opt into a group having permissions on the item (block 706). As mentioned above, the collaboration service 124 may examine a selected link to detect a sharing key 204 or other identifier that is indicative of the group opt-in option. A determination that the group opt-in option is active prompts the service to present the appropriate option when the link is used by a recipient. In some cases, a comparison is made to ACLs that encode whether the group opt-in option is active or inactive for corresponding links. The collaboration service 124 may also identify that the group opt-in option is active based on a particular value, string, or toggle field incorporated within a sharing link 128 when the link is created.

**[0068]** When the group opt-in option is appropriate, the collaboration service 124 operates to present the option to the recipient. This may occur in a variety of ways. For example, an opt-in interface or dialog may be output for display by a client device 102. The opt-in interface or dialog presents recipients with the option to join the group and enables a recipient to explicitly opt-in to the group having permissions on the item. Additionally, a recipient may be asked to select an account to associate with the item/group in accordance with techniques discussed below in relation to FIGS. 10-13.

**[0069]** More generally, note that the different techniques related to sharing links described in different sections herein may be combined in various ways. Thus, techniques described for distinct links, group opt-in links, and one-time sharing links may be implemented individually and/or may be combined in some scenarios to create sharing links configured for multiple purposes.

**[0070]** Recipients that exercise the option are added to the group having permissions on the items (block 708). In particular, permissions defined in an ACL or otherwise for an item are updated to reflect addition of recipients that opted in as members. This may involve associating account identifiers

and/or credentials for the recipients that opt-in with the group, permissions, and/or corresponding item to make the recipients members of the group.

**[0071]** As noted group membership is determined by those that exercise the group opt-in option and therefore the group is not necessarily predetermined in membership or size. The owner of the item/group does not have to manually select each member to create the group and does not need to have contact information for individual people. Rather, the owner simply gets a link per block **702** and can post the link to a public site or otherwise distribute the link. In this case, the link is effectively public and anyone who possesses the link may use the link to gain access to at least the group opt-in option for the item.

**[0072]** The group opt-in option may implement a tiered access level approach in which permissions on the item change from a first level of access before opting-in to a second level of access after opting-in. Initially, a link may be associated with initial, basic permissions on the item. The initial permissions may be set by default and/or may be designated by the user. In general, the initial permissions available through the sharing link grant limited or no access to the item. For instance, the initial permissions may be set to limit access to viewing of the item or viewing just a preview of the item. Alternatively, access may be limited to obtaining and acting on the group opt-in option for the item. Opting in causes permissions to change from the initial, basic permissions to enhanced permissions on the item that are established for the group. For example, the enhanced permissions available through the group may be set to enable editing in addition to viewing the item. Thus, various different access levels may be associated with an item prior to opting-in through the sharing link and after opting-in through the group.

**[0073]** Representations of recipients that have opted-in are presented in association with the item in a user interface for viewing and managing the online storage (block **710**) and management of the recipients individually and separate from management of the sharing link is enabled (block **712**).

**[0074]** As with the distinct sharing links for different targets discussed previously, links configured for group opt-in and members within the group may be managed separately from one another. Thus, the collaboration service **124** may separately represent a group link and group members for an item within a user interface presented to review and manage stored items. For example, representations of different group members and/or a group opt-in link may be listed via a sharing portion **308** of a user interface **122** as discussed in relation to FIG. 3. In this way, a user is able to review each of the links and members for a particular item, see associated permissions, and/or separately manage permissions for the group and/or individual members of the group. This includes but is not limited to actions such as changing permissions individually, removing one or more members, and/or invalidating a link without affecting the access permissions of members who have already opted-in, and so forth. Additional details regarding managing group links and members are provided in relation to example user interfaces of FIGS. 8 and 9.

**[0075]** FIG. 8 depicts a diagram **800** showing an example user interface **122** that can be employed to get a link for distribution to an arbitrary group. The user interface **122** in this instance is illustrated as incorporated within a user interface **802** that may be provided by a communication module **116** as with the preceding example user interfaces. In at least some embodiments, the example interface depicted in FIG. 8 may be presented responsive to selection of the “Get a Link” object appearing within the sharing portion **308** in FIG. 3.

**[0076]** Here the example user interface **122** is again operable to provide a sharing link **128** for the “Reunion” folder of FIG. 3. In this case, the interface provides the actual link (as opposed to publication of the distinct links in the previous section) that a user may copy and distribute in various ways. In particular, a link portion **804** is depicted that may return a link generated by a collaboration service **124** as previously described. As mentioned, the link may be configured to cause a group opt-in option to be presented when the link is selected by a recipient. In one approach, the sharing key **204** associated with the link is set to cause the option to be exposed when the collaboration service **124** interprets the link.

**[0077]** The example user interface **122** of FIG. 8 further includes a permissions portion **806**, a distribute portion **808**, and a done control **810**. As with preceding examples, the permissions portion **806** enables selection of permissions to associate with the created links. For instance, the permissions portion **510** may allow a user to select whether the returned linked may be used to view, edit, move, and/or grant admin rights to a corresponding item. The user may be able to set both initial permissions before opting-in and enhanced permissions after opting-in in accordance with the tiered access level approach discussed in relation to FIG. 7.

**[0078]** The distribute portion **808** may be included to provide various options to share the link. For example, the example distribute portion **808** provides options to distribute by email or instant messaging. Selection of these options may be used to automatically create an appropriate message that includes the link through the service provider **106**, a default messaging program, a third party messaging service, and so forth. In addition, a post option is provided that may enable publication of the link to different sites. In at least some cases, the post option may link to an interface similar to the example of FIG. 5 that may enable selection of different publish targets and/or creation of distinct links for the different publish targets. In this case, the distinct links may be generated to correspond to the particular link returned in the link portion **804** and may also cause the opt-in option to be exposed when selected. As before, a different sharing key **204** may be associated with different distinct links.

**[0079]** The done control **810**, when selected, may cause the interface to be closed out and navigation back to a home page or start page for the collaboration service **124**, such as returning to the example interface shown in FIG. 3.

**[0080]** FIG. 9 depicts a diagram **900** showing a sharing portion for review and management of recipients who exercise the option to join a group. In particular, the item detail portion **306** of FIG. 3 is shown after a link is distributed for the “Reunion” folder and one or more recipients opt into a corresponding group. This example is similar to the example of FIG. 6 except in this case the sharing portion **308** is reconfigured to include a list **902** of individuals who opt-in. A representation of each individual is provided along with a corresponding permission control **904**. The permission controls **904** enable a user to individually view and manage permissions associated with the different individual links. For example, the permission controls **904** are illustrated as list boxes operable to select an access level (e.g., view, edit, move, copy, print, admin, etc.) for individual links.

**[0081]** In addition, a deactivate control **906** is provided that is operable to deactivate a distributed link. When deactivated the link is no longer usable to opt-in to the group. In at least some embodiments, deactivating the link or changing permissions associated with the link does not affect users that have

already been added to the group. Thus, the individual users may be managed individually and separately from the sharing link itself. In another approach, invalidating the link or changing permissions will populate the changes to any members of the group.

**[0082]** Shared Item Account Selection

**[0083]** This section describes techniques for sharing links **128** configured to enable a recipient to select a particular account the recipient would like to use to access a corresponding shared item. In portions of the following discussion, reference will again be made to the example environment **100** of FIG. **1** and example user interface of FIG. **3**. Generally speaking, a user may access associated online storage **126** through a collaboration service **124**. The user may be able to select a send a link option that causes a collaboration service **124** to provide a link for sharing an item. The user may then take action to send the link to selected individuals. The user may have limited contact information for some individuals and therefore may not address the link to addresses or accounts that some recipients would prefer to use for access to the shared item. As discussed below, the collaboration service **124** may configure sharing links **128** generated in response to the send operation as one-time sharing links. In general, the one-time sharing links enable recipients to get limited, one-time access to a shared item for the purpose of selecting or registering an account to use for subsequent access to the item. Once the one-time sharing link is redeemed, the one-time sharing link may be invalidated for subsequent access to gain enhanced permissions to the item. The one-time sharing link may or may not continue remain valid for limited access, such as read-only access. In this manner, recipients are able to select accounts they find most convenient for accessing a shared item without the owner/sharer of the item necessarily having contact information for those accounts or sending a link to the accounts. Just below, example procedures are discussed followed by some example user interfaces illustrating details of techniques for one-time sharing links.

**[0084]** FIG. **10** depicts a procedure **1000** in an example implementation in which one-time sharing links are employed for selection of accounts to access a shared item.

**[0085]** Selected recipients are determined for a sharing link to an item maintained in online storage (block **1002**). One way this may occur is through a user interface provided to enable sending of a link to one or more recipients. For example, the collaboration service **124** may output a user interface **122** accessible by a client device **102** over a network **110**. The user interface **122** may be output in response to a selection of a send a link control to share a particular content item. The user interface **122** enables a user to select one or more recipients, input known contact info, and/or submit a request to send a link to the one or more recipients. The collaboration service **124** may receive and process the request to identify intended recipients. This may involve parsing the request to extract contact info for the one or more recipients.

**[0086]** Different one-time sharing links are generated for each of the selected recipients (block **1004**). Here, the collaboration service **124** may create a different one-time link for each individual recipient. This may occur substantially in the same manner as creating distinct links for different publish targets as discussed in relation to FIGS. **4-6**. For instance, links may be formatted to have a navigation path **202** and a sharing key **204** as with other links described herein. The one-time sharing links though contain information sufficient to designate the link as a one-time sharing link and/or enable

the collaboration service **124** to identify and handle the links as one-time sharing links. In one approach, the sharing key **204** can be mapped to an ACL that designates the link as a one-time sharing links. Additionally the sharing key **204** or another suitable identifier contained within a link can be used to flag the link as a one-time sharing link. In any case, the collaboration service **124** is able to examine a link, determine in some manner whether the link is a one-time sharing link, and handle the link accordingly.

**[0087]** Once appropriate one-time sharing links are generated, the collaboration service **124** may then send notifications having a unique one-time sharing link to each designated recipients. The collaboration service **124** may send notifications through different messaging service including for example email, instant messaging, text messaging, and so forth. In some cases, the collaboration service **124** may send notifications through associated partner sites such as social networks, in which case recipient is notified through messaging functionality provided by the partner sites.

**[0088]** As mentioned, links designated in some manner as one-time sharing links enable recipients to get limited, one-time access to a shared item for the purpose of selecting or registering an account to use for subsequent access to the item. In this manner, recipients are able to select accounts they find most convenient for accessing a shared item without the owner/sharer of the item necessarily having contact information for those accounts or sending a link to the accounts.

**[0089]** To do so, an option for a recipient to select an account to use for access to the item is exposed responsive to a selection of the sharing link by the recipient (block **1006**). An option to select an account may be provided in various ways and at different times. For example, an account selection user interface or dialog may be presented that enables selection of a particular account at an appropriate time during an authentication sequence. Through the dialog, a user may be prompted to select a current account, choose a different account, and/or create a new account to use for accessing the shared item. An example dialog is discussed below in relation to FIG. **13**.

**[0090]** The timing for presenting the account selection option may be dependent upon access permissions associated with the one-time sharing link. For example, a link may be configured to require sign-in before any access to the item is provided. If this is the case, an authentication sequence that incorporates the option to select an account may be initiated right away when a link is used. On the other hand, if some level of access, such as view only access, is granted by a link, then selection of the link does not cause initiation of the authentication sequence right away. Instead, appropriate access to the item is granted and the recipient of the link may view the item. When the recipient attempts an action that requires sign-in and/or different access privileges, the authentication sequence incorporating the option to select an account may be initiated at that time. One example authentication sequence that can be employed to control access to items and account selection is discussed below in relation to FIG. **11**.

**[0091]** Permissions on the item are associated with the selected account (block **1008**) and the link is invalidated for subsequent use to gain permissions on the object (block **1010**). Thus, when an option to select an account is exercised using a one-time sharing link, the selected account is granted permissions on the item. This can occur by associating the account with the item through an ACL or otherwise.

[0092] Similar to the tiered access level approach discussed above in relation to the group opt-in option, different access levels may be used in conjunction with one-time sharing links. Here, a first level of access may be associated with a one-time sharing link before the link is redeemed. For instance, an unredeemed link may be associated with initial, basic permissions for unauthenticated users that allow a user simply to view the item. Again, the initial permissions may be set by default and/or may be designated by the user. In general, the initial permissions grant limited or no access to the item. Redeeming the link by selection of an account causes permissions to change from the initial, basic permissions to enhanced permissions established for authenticated users when the link is created. For example, the enhanced permissions may be set to enable editing in addition to viewing the item. Thus, various different access levels may be associated with an item using the one-time sharing link and granted to a user of the link after redeeming the link.

[0093] Once a one-time sharing link is redeemed, the collaboration service 124 invalidates the link for subsequent access to the item. For instance, an ACL may be updated to reflect that the one-time sharing link has been redeemed. This may occur by revoking the sharing key 204 associated with the link or in another suitable manner that revokes privileges for the one-time sharing link. The one-time sharing link will no longer be valid to access the item or gain permissions to the item. Instead, permissions are now associated with the selected account, which can be used for subsequent access to the item.

[0094] Consider now FIG. 11 that depicts a procedure 1100 for an authentication sequence in which one-time sharing links are employed for selection of an account in accordance with one or more embodiments. Selection of a one-time sharing link for a shared item is detected (block 1102). A determination is made regarding whether the link involves a sign-in to gain access to the shared item (block 1104). The determination may be based on tiered access levels assigned to a link as discussed earlier in this document. For example, sign-in may optionally be required by a user when a one-time sharing link for a shared item is created. Effectively, the one-time sharing link will then provide limited access for the purpose of selecting an account to use to access the corresponding shared item.

[0095] If the link does not involve a sign-in, access to the item is enabled with unauthenticated permissions (block 1106). The unauthenticated permissions represent initial, basic permissions set by default or by user selections when the one-time sharing link is created. Thereafter, the system may monitor to detect action that does involve the sign-in (block 1108). It should be noted that unauthenticated access can be disabled by forcing link redemption. In this case, the owner may designate at the time of link creation that a sharing link be redeemed before permissions are granted. Effectively, the link is configured without unauthenticated permissions and a recipient may be unable to even view an item before redeeming the associated link.

[0096] Both when the link requires sign-in per block 1104 and when action requiring sign-in is detected per block 1108, a determination is made as to whether the user is already signed-in (block 1110). If the user is not already signed-in, the user is redirected to login (block 1112) and the user is authenticated to a selected account (block 1114). This may occur through the collaboration service 124 and/or an authentication service accessible via the service provider 102 using any

suitable authentication techniques. In general, the user provides credentials (e.g., username and password) to access and account which are verified to ensure that the user is who they claim to be. In at least some embodiments the user may be prompted to log-in to an account the user would like to use for access to the item at this point. In addition or alternatively, an account selection prompt may also occur later within the authentication sequence as described below.

[0097] After authenticating the user per block 1114 and also when user is already signed-in per block 1110, a determination is made as regarding whether the user already has authenticated access to the shared item (block 1116). If so, the one-time sharing link is redeemed (block 1118) and access to the shared item is provided with authenticated permissions (block 1120). In this case, an assumption may be made that the user prefers to use the current account that already has permissions on the shared item. As such, access is granted without prompting to select a different account. In an alternate approach, a switch account option may be provided to enable the user to switch accounts even if the user already has authenticated access per block 1116. However, in the depicted example access is granted through the current account already having access and if not already the case, the link is redeemed and invalidated for subsequent use.

[0098] Otherwise, if the user does not have authenticated access per block 1116, a determination of the validity of the one-time sharing link is made (block 1122). Here a check is made to ensure that the link has not been previously redeemed. If the one-time sharing link is not valid, access is denied (block 1124) and an error message may be presented indicating that the one-time sharing link is not valid to gain access to the shared item.

[0099] On the other hand, when the one-time sharing link is determined to be valid, a check is made regarding whether an optional auto-redeem option is set (block 1126). The auto-redeem option can be selectively set as a design parameter to control whether one-time sharing links are redeemed automatically or through an account selection dialog. In addition or alternatively, a configurable parameter for the auto-redeem option may be associated with items and/or user accounts. In this example, the configurable parameter may be set by an item owner and/or individually for accounts of link recipients. If the auto-redeem option is set, the flow proceeds back to blocks 1118 and 1120 where the one-time sharing link is automatically redeemed and access to the shared item is provided with authenticated permissions. This may occur without outputting a prompt to the user.

[0100] If the auto-redeem option is not set, though, an account selection dialog (e.g. redeem dialog) prompting the user to select an account is output (block 1128). Based on input obtained via the account selection dialog, a determination is made regarding whether to use the current account or select another account (block 1130). If the current account is selected, the flow again proceeds back to blocks 1118 and 1120 where the one-time sharing link is redeemed and access to the shared item is provided with authenticated permissions. Otherwise, the flow proceeds back to block 1112 where the user is redirected to login and authentication to a different account may occur. Blocks 1112-1130 may therefore be repeated for the different account until the current account is selected at block 1130.

[0101] FIG. 12 depicts a diagram 1200 showing an example user interface 122 that can be employed to send a link to selected contacts. Once again, the user interface 122 is illus-

trated as incorporated within a user interface **1202** that may be provided by a communication module **116** as with the preceding examples. In at least some embodiments, the example interface depicted in FIG. **12** may be presented responsive to selection of the “Send a Link” object appearing within the sharing portion **308** in FIG. **3**.

[0102] Here the example user interface **122** is again operable to provide a sharing link **128** for the “Reunion” folder of FIG. **3**. In this case, the interface can be used to submit a request that causes the collaboration service **124** to create and distribute one-time sharing links for selected recipients that may be formatted, distributed, and employed as discussed previously. In particular, an address portion **1204** is depicted that may be used to input email addresses or other contact information for selected recipients. As mentioned, the sender does not necessarily have to send the link to accounts the recipients ultimately choose to access the shared item. A message portion **1206** enables the sender to optionally include a personal message along with the sharing link. Additionally, a require sign-in control **1208** is operable to selectively set whether a sign-in is involved to access the item by the recipients. When require sign-in is set, the one-time sharing links are configured to provide limited access to a shared item for the purpose of selecting an account. Otherwise a default or selected access level established for unauthenticated users may be associated with one-time sharing links created through the dialog. Although not shown in this particular example, the sender may also be able to access a permissions control or menu to designate access levels for both initial permissions before sign-in (e.g., unauthenticated permissions) and enhanced permissions after sign-in (e.g., authenticated permissions) in accordance with techniques discussed in relation to FIG. **10-11**.

[0103] The example user interface **122** of FIG. **12** further includes a send control **1210**. The send control **1210** is selectable to submit a request that causes the collaboration service **124** to create and distribute appropriate one-time sharing links based on the recipients selected through the user interface **122**.

[0104] FIG. **13** depicts a diagram **1300** showing an example account selection dialog **1302** in accordance with one or more embodiments. The account selection dialog **1302** may be exposed at various times within an authentication sequence as previously described to enable a user to select a particular account to use for access to a shared item when appropriate. For example, the account selection dialog **1302** may be exposed at block **1128** within the example authentication sequence described in relation to FIG. **11**.

[0105] Here, the account selection dialog **1302** includes a current account indication **1304** that indicates an account to which the user is currently authenticated. The user may select a continue control **1306** provided by the dialog to use the current account for access to the corresponding shared item. If the user so chooses, the user may select a switch accounts control **1308** also provided by the dialog to select a different account. Selection of the switch accounts control **1308** causes a redirection to a log-in process to select the different account and/or provide corresponding credentials to authenticate to the account.

[0106] Having considered some example details regarding various techniques to create and use sharing links, consider now a discussion of example systems and device that may be employed to implement the various techniques in one or more embodiments.

#### [0107] Example System and Device

[0108] FIG. **14** illustrates an example multiple device environment **1400** that includes the computing device **102** as described with reference to FIG. **1**. The example multiple device environment **1400** enables ubiquitous environments for a seamless user experience when running applications on a personal computer (PC), a television device, and/or a mobile device. Services and applications run substantially similar in all three environments for a common user experience when transitioning from one device to the next while utilizing an application, playing a video game, watching a video, and so on.

[0109] In the example multiple device environment **1400**, multiple devices are interconnected through a central computing device. The central computing device may be local to the multiple devices or may be located remotely from the multiple devices. In one embodiment, the central computing device may be a cloud of one or more server computers that are connected to the multiple devices through a network, the Internet, or other data communication link. In one embodiment, this interconnection architecture enables functionality to be delivered across multiple devices to provide a common and seamless experience to a user of the multiple devices. Each of the multiple devices may have different physical requirements and capabilities, and the central computing device uses a platform to enable the delivery of an experience to the device that is both tailored to the device and yet common to all devices. In one embodiment, a class of target devices is created and experiences are tailored to the generic class of devices. A class of devices may be defined by physical features, types of usage, or other common characteristics of the devices.

[0110] In various implementations, the computing device **102** may assume a variety of different configurations, such as for computer **1402**, mobile **1404**, and television **1406** uses. Each of these configurations includes devices that may have generally different constructs and capabilities, and thus the computing device **102** may be configured according to one or more of the different device classes. For instance, the computing device **102** may be implemented as the computer **1402** class of a device that includes a personal computer, desktop computer, a multi-screen computer, laptop computer, netbook, and so on.

[0111] The computing device **102** may also be implemented as the mobile **1404** class of device that includes mobile devices, such as a mobile phone, portable music player, portable gaming device, a tablet computer, a multi-screen computer, and so on. The computing device **102** may also be implemented as the television **1406** class of device that includes devices having or connected to generally larger screens in casual viewing environments. These devices include televisions, set-top boxes, gaming consoles, and so on. The techniques described herein may be supported by these various configurations of the computing device **102** and are not limited to the specific examples the techniques described herein. This is illustrated through inclusion of the communication module **116** on the client device **102**. For instance different devices may include different communication modules **116** (e.g., browsers) adapted for the particular device and through which various resources **120** of the platform **1410** can be accessed, including the collaboration service **124** and online storage **126** described herein.

[0112] The cloud 1408 includes and/or is representative of a platform 1410 for resources 120. The platform 1410 abstracts underlying functionality of hardware (e.g., servers) and software resources of the cloud 1408. The resources 120 may include applications and/or data that can be utilized while computer processing is executed on servers that are remote from the computing device 102. Resources 120 can be provided as a service over the Internet and/or through a subscriber network, such as a cellular or Wi-Fi network.

[0113] The platform 1410 may abstract resources and functions to connect the computing device 102 with other computing devices. The platform 1410 may also serve to abstract scaling of resources to provide a corresponding level of scale to encountered demand for the resources 120 that are implemented via the platform 1410. Accordingly, in an interconnected device embodiment, implementation of functionality of the functionality described herein may be distributed throughout the multiple device environment 1400. For example, the functionality may be implemented in part on the computing device 102 as well as via the platform 1410 that abstracts the functionality of the cloud 1408.

[0114] FIG. 15 illustrates an example system generally at 1500 that includes an example computing device 1502 that is representative of one or more such computing systems and/or devices that may implement the various embodiments described above. The computing device 1502 may be, for example, a server of a service provider 106, a client device 102, a system on-chip, and/or any other suitable computing device or computing system.

[0115] The example computing device 1502 includes one or more processors 1504 or processing units, one or more computer-readable media 1506 which may include one or more memory and/or storage components 1508, one or more input/output (I/O) interfaces 1510 for input/output (I/O) devices, and a bus 1512 that allows the various components and devices to communicate one to another. Computer-readable media 1506 and/or one or more I/O devices may be included as part of, or alternatively may be coupled to, the computing device 1502. The bus 1512 represents one or more of several types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. The bus 1512 may include wired and/or wireless buses.

[0116] The one or more processors 1504 are not limited by the materials from which they are formed or the processing mechanisms employed therein. For example, processors may be comprised of semiconductor(s) and/or transistors (e.g., electronic integrated circuits (ICs)). In such a context, processor-executable instructions may be electronically-executable instructions. The memory/storage component 1508 represents memory/storage capacity associated with one or more computer-readable media. The memory/storage component 1508 may include volatile media (such as random access memory (RAM)) and/or nonvolatile media (such as read only memory (ROM), Flash memory, optical disks, magnetic disks, and so forth). The memory/storage component 1508 may include fixed media (e.g., RAM, ROM, a fixed hard drive, etc.) as well as removable media (e.g., a Flash memory drive, a removable hard drive, an optical disk, and so forth).

[0117] Input/output interface(s) 1510 allow a user to enter commands and information to computing device 1502, and also allow information to be presented to the user and/or other components or devices using various input/output devices. Examples of input devices include a keyboard, a touchscreen display, a cursor control device (e.g., a mouse), a microphone,

a scanner, and so forth. Examples of output devices include a display device (e.g., a monitor or projector), speakers, a printer, a network card, and so forth.

[0118] Various techniques may be described herein in the general context of software, hardware (fixed logic circuitry), or program modules. Generally, such modules include routines, programs, objects, elements, components, data structures, and so forth that perform particular tasks or implement particular abstract data types. An implementation of these modules and techniques may be stored on or transmitted across some form of computer-readable media. The computer-readable media may include a variety of available medium or media that may be accessed by a computing device. By way of example, and not limitation, computer-readable media may include “computer-readable storage media” and “communication media.”

[0119] “Computer-readable storage media” may refer to media and/or devices that enable persistent and/or non-transitory storage of information in contrast to mere signal transmission, carrier waves, or signals per se. Thus, computer-readable storage media refers to non-signal bearing media. Computer-readable storage media also includes hardware elements having instructions, modules, and/or fixed device logic implemented in a hardware form that may be employed in some embodiments to implement aspects of the described techniques.

[0120] The computer-readable storage media includes volatile and non-volatile, removable and non-removable media and/or storage devices implemented in a method or technology suitable for storage of information such as computer readable instructions, data structures, program modules, logic elements/circuits, or other data. Examples of computer-readable storage media may include, but are not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, hard disks, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, hardware elements (e.g., fixed logic) of an integrated circuit or chip, or other storage device, tangible media, or article of manufacture suitable to store the desired information and which may be accessed by a computer.

[0121] “Communication media” may refer to a signal bearing medium that is configured to transmit instructions to the hardware of the computing device, such as via a network. Communication media typically may embody computer readable instructions, data structures, program modules, or other data in a modulated data signal, such as carrier waves, data signals, or other transport mechanism. Communication media also include any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media include wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared, and other wireless media.

[0122] Combinations of any of the above are also included within the scope of computer-readable media. Accordingly, software, hardware, or program modules, including the resources 120, collaboration service 124, applications 114, communication module 116, and other program modules, may be implemented as one or more instructions and/or logic embodied on some form of computer-readable media.

[0123] Accordingly, particular modules, functionality, components, and techniques described herein may be implemented in software, hardware, firmware and/or combinations thereof. The computing device **1502** may be configured to implement particular instructions and/or functions corresponding to the software and/or hardware modules implemented on computer-readable media. The instructions and/or functions may be executable/operable by one or more articles of manufacture (for example, one or more computing devices **1502** and/or processors **1504**) to implement techniques related to sharing links, as well as other techniques. Such techniques include, but are not limited to, the example procedures described herein. Thus, computer-readable media may be configured to store or otherwise provide instructions that, when executed by one or more devices described herein, cause various techniques related to sharing links.

### CONCLUSION

[0124] Although the invention has been described in language specific to structural features and/or methodological acts, it is to be understood that the invention defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as example forms of implementing the claimed invention.

What is claimed is:

1. A method implemented by a computing device, the method comprising:

generating distinct sharing links to share an item from online storage associated with a user account for each of multiple publish targets responsive to a request to create the distinct sharing links;

publishing the distinct sharing links to the sharing targets; and

enabling individual management of the distinct sharing links associated with the multiple publish targets.

2. A method as described in claim 1, wherein multiple distinct sharing links are generated in response to a single request.

3. A method as described in claim 1, wherein the generating the distinct sharing links comprises constructing each of the sharing links to include a navigation path to the item and a sharing key that uniquely identifies the particular sharing link.

4. A method as described in claim 1, wherein the generating the distinct sharing links comprises encoding respective permissions to the item within the distinct sharing links.

5. A method as described in claim 1, wherein the publishing the distinct sharing links comprises configuring a call to at least one network accessible application programming interface (APIs) exposed by a partner site in a designated format and invoking the network accessible API with the call to post a corresponding sharing link to the partner site.

6. A method as described in claim 1, wherein at least one of the publish targets is a social network service.

7. A method as described in claim 1, further comprising mapping the distinct sharing links to permissions on the item defined by an access control list.

8. A method as described in claim 1, further comprising:  
exposing a user interface to enable formation of the request having a selection of the multiple publish targets to cause creation of the distinct sharing links;  
obtaining the request formed via the user interface; and  
parsing the request to identify the multiple publish targets.

9. A method as described in claim 1, further comprising presenting representations of the distinct sharing links in association with the item in a user interface for viewing and managing the online storage.

10. A method as described in claim 1, wherein enabling individual management of the distinct sharing links comprises at least providing options to associate different permissions on the item with different distinct sharing links.

11. One or more computer-readable storage media storing instructions that, when executed by one or more components of a computing device, implement a collaboration service configured to perform operations including:

providing online storage that is allocated to user accounts with a service provider; and

enabling users to share items from the online storage with others through sharing links including publishing of distinct sharing links for a shared item stored in online storage associated with a particular user account to multiple publish targets responsive to obtaining a single request having a selection of the multiple publish targets.

12. One or more computer-readable storage media as recited in claim 11, wherein the collaboration service is provided in conjunction with a plurality of resources available to clients over a network from the service provider.

13. One or more computer-readable storage media as recited in claim 11, wherein the collaboration service is further configured to perform operations including:

parsing the request to identify the multiple publish targets; and

generating the distinct sharing links by constructing a different link for each of the multiple publish targets that is identified.

14. One or more computer-readable storage media as recited in claim 11, wherein the collaboration service is further configured to perform operations including:

exposing an application programming interface (API) callable by script contained in a webpage output to a client to enable input of the selection of the multiple publish targets to initiate creation of the distinct sharing links, and

receiving the single request having the selection of the multiple publish targets as a call to the API formed via the webpage.

15. One or more computer-readable storage media as recited in claim 11, wherein each individual distinct sharing link is configured to include a sharing key used to uniquely identify the individual distinct sharing link and associate permissions on the item with the individual distinct sharing link.

16. One or more computer-readable storage media as recited in claim 11 wherein one or more of the publish targets is a social network service.

17. One or more computer-readable storage media as recited in claim 11, wherein the collaboration service is further configured to perform operations including:

presenting representations of the distinct sharing links in association with the shared item in a user interface for viewing and managing the online storage;

providing options to enable individual management of the distinct sharing links including individually associating permissions with different links, changing permissions associated with different links on an individual basis,

and invalidating a particular one of the distinct sharing links without affecting other distinct sharing links.

**18.** A computing system comprising:

one or more processing components;

one or more computer-readable storage media storing instructions that, when executed by the one or more processing components, perform operations to publish sharing links for an item to multiple publish targets including:

obtaining a single request to create distinct sharing links for the multiple publish targets to share the item from online storage allocated to a user account with a service provider;

parsing the single request to identify the multiple publish targets;

generating distinct sharing links such that each of the distinct sharing links corresponds to one of the identified publish targets and is constructed to include a

navigation path to the item and a sharing key that uniquely identifies the distinct sharing link; and

encoding permissions to the item within the distinct sharing links by associating the permissions with the sharing key of each distinct sharing link on an individual basis thereby enabling individual management of the distinct sharing links through the permissions.

**19.** A computing system as described in claim **18**, wherein encoding the permissions comprises mapping the sharing key of each distinct sharing link to corresponding permissions in an access control list managed by the service provider.

**20.** A computing system as described in claim **18**, wherein encoding the permissions comprises configuring the sharing key of each distinct sharing link to include an access parameter indicative of a corresponding permission level granted by the distinct sharing link.

\* \* \* \* \*