

(12) **United States Patent**
Carlton et al.

(10) **Patent No.:** **US 9,173,054 B2**
(45) **Date of Patent:** ***Oct. 27, 2015**

(54) **DATA TRANSFER BETWEEN WIRELESS DEVICES**

(71) Applicant: **InterDigital Patent Holdings, Inc.**,
Wilmington, DE (US)

(72) Inventors: **Alan G. Carlton**, Mineola, NY (US);
Alexander Reznik, Titusville, NJ (US)

(73) Assignee: **InterDigital Patent Holdings, Inc.**,
Wilmington, DE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/251,383**

(22) Filed: **Apr. 11, 2014**

(65) **Prior Publication Data**

US 2014/0220900 A1 Aug. 7, 2014

Related U.S. Application Data

(63) Continuation of application No. 13/930,743, filed on Jun. 28, 2013, now Pat. No. 8,737,933, which is a continuation of application No. 13/493,650, filed on Jun. 11, 2012, now Pat. No. 8,478,207, which is a continuation of application No. 12/644,948, filed on Dec. 22, 2009, now Pat. No. 8,200,265.

(60) Provisional application No. 61/140,126, filed on Dec. 23, 2008.

(51) **Int. Cl.**
H04W 4/00 (2009.01)
H04W 4/02 (2009.01)
H04L 29/08 (2006.01)
G06F 3/0482 (2013.01)
G06F 3/0488 (2013.01)

(52) **U.S. Cl.**
CPC **H04W 4/008** (2013.01); **G06F 3/0482** (2013.01); **G06F 3/0488** (2013.01); **H04L 67/16** (2013.01); **H04L 67/18** (2013.01); **H04W 4/02** (2013.01)

(58) **Field of Classification Search**
CPC combination set(s) only.
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,544,321 A	8/1996	Theimer et al.	
7,813,697 B2	10/2010	McKillop	
7,877,494 B2	1/2011	Carlton et al.	
8,200,265 B2 *	6/2012	Carlton et al.	455/509
8,478,207 B2 *	7/2013	Carlton et al.	455/73
8,611,317 B2	12/2013	Banerjee et al.	
8,737,933 B2 *	5/2014	Carlton et al.	455/73

(Continued)

FOREIGN PATENT DOCUMENTS

EP	1 513 262	3/2005
WO	03/081373	10/2003

OTHER PUBLICATIONS

Hazas et al., "A Relative Positioning System for Co-located Mobile Devices," International Conference on Mobile Systems, Proceedings of the 3rd International Conference on Mobile Systems, Applications and Services, Seattle, Washington, 2005, pp. 177-190.


Primary Examiner — Diane Mizrahi

(74) *Attorney, Agent, or Firm* — Volpe and Koenig, P.C.

(57) **ABSTRACT**

A wireless transmit/receive unit (WTRU) may detect another WTRU over bluetooth. The WTRU may send to the another WTRU a message to transfer selected media. The WTRU may transfer the selected media to the another WTRU over WiFi.

50 Claims, 9 Drawing Sheets



MICROSOFT CORP.
EXHIBIT 1201

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0234762 A1 10/2006 Ozluturk
 2006/0293063 A1 12/2006 Corrion
 2007/0146347 A1 6/2007 Rosenberg
 2007/0177729 A1 8/2007 Reznik et al.

2007/0271379 A1 11/2007 Carlton et al.
 2011/0119702 A1 5/2011 Jang et al.
 2011/0119710 A1 5/2011 Jang et al.
 2011/0126237 A1 5/2011 Lee et al.
 2011/0138334 A1 6/2011 Jung

* cited by examiner




FIG. 1




FIG. 2







FIG. 3

**FIG. 4**





60




FIG. 7A






FIG. 7B






FIG. 8




FIG. 9

1

DATA TRANSFER BETWEEN WIRELESS DEVICES

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/930,743, filed Jun. 28, 2013, which is a continuation of U.S. patent application Ser. No. 13/493,650, filed Jun. 11, 2012, which issued as U.S. Pat. No. 8,478,207 on Jul. 2, 2013, which is a continuation of U.S. patent application Ser. No. 12/644,948, filed Dec. 22, 2009, which issued as U.S. Pat. No. 8,200,265 on Jun. 12, 2012, which claims the benefit of U.S. Provisional Application Ser. No. 61/140,126, filed Dec. 23, 2008. The contents of the above-referenced applications are hereby incorporated by reference herein.

FIELD OF INVENTION

This application is related to wireless communications.

BACKGROUND

In current communications, functionality that allows the transfer of data (such as files or digital media) between devices in both fixed and wireless environments is commonplace. Currently, data transfers may be performed using applications such as electronic mail, or multimedia message services (MMS) with the data being transmitted from one device to another through suitable technologies, for example, General Packet Radio Service (GPRS) or Wireless Local Area Network (WLAN). As the sophistication of user interfaces supporting data transfers has developed (for example, the emergence of touch screen and multi-touch technology), the user experience has been simplified considerably. These advances in user interface technology may be seen in devices such as the Apple® iPhone® and iPod Touch®.

Despite these advances, however, file transfers may still be a cumbersome, multi-step task requiring adaptation between multiple implementations. For example, many technologies involve a fragmented approach to access and manipulation of files such as attachments. These hurdles inhibit the more regular use of file transfer schemes in spontaneous situations. A simplified and more intuitive approach to data transfer between devices is therefore required.

SUMMARY

A method for controlling communication of data in wireless communications, implemented in a wireless transmit/receive unit (WTRU) detects environment information relating to at least one candidate WTRU operating in a local area associated with the WTRU. A user input is received via a user interface, wherein the user input relates to a selection of data for transfer between the WTRU and at least one of the candidate WTRUs and to an identified target WTRU. The user input is processed as well as the information relating to the at least one candidate WTRU. At least one target WTRU is identified from the at least one candidate WTRU based in part on the user input. Information relating to candidate WTRUs is solicited through a lower layer. Environment information is used to identify the target WTRU and transmission instructions are generated to enable transmission of data to the target WTRU.

BRIEF DESCRIPTION OF THE DRAWING(S)

A more detailed understanding may be had from the following description, given by way of example in conjunction with the accompanying drawings wherein:

2

FIG. 1 shows a sending and receiving wireless transmit/receive unit (WTRU) that may be used for data transfer between devices;

FIG. 2 shows a wireless communication environment for data communication between devices;

FIG. 3 shows a target discrimination algorithm for identifying a target WTRU;

FIG. 4 is a block diagram of a method of communicating data between wireless devices;

FIG. 5 is a block diagram of physical layer security for data communication between devices;

FIG. 6 shows a user input for transferring a data file between devices;

FIGS. 7A and 7B show a user experience during a data communication between devices at a sending device and a receiving device;

FIG. 8 shows a user input for transferring a data file to a target device, where the user input includes a directional indication of the location of the target device; and

FIG. 9 shows a user input for transferring a data file from a sending device to multiple receiving devices.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

When referred to hereafter, the terminology “wireless transmit/receive unit (WTRU)” includes but is not limited to a user equipment (UE), a communications device, a mobile station, a fixed or mobile subscriber unit, a pager, a cellular telephone, a personal digital assistant (PDA), a computer, or any other type of device capable of operating in a wireless environment. When referred to hereafter, the terminology “base station” includes but is not limited to a Node-B, a site controller, an access point (AP), or any other type of interfacing device capable of operating in a wireless environment.

FIG. 1 is an illustration of a sending WTRU 101 and a receiving WTRU 103 whereby data is transferred between the WTRUs. The sending WTRU 101 and the receiving WTRU 103 are similarly equipped. The sending WTRU 101 and receiving WTRU 103 are separated by a communications environment 115 that may include other similarly equipped WTRUs which are not shown for simplicity. In general, WTRU 101, and WTRU 103 are each minimally comprised of an application processor 105, a communication peripheral 107, and a touchscreen/display peripheral 109. The communication peripheral 107 may be implemented as a wireless personal area network (WPAN) device, for example Bluetooth®, Wireless Universal Serial Bus (W-USB) or WiFi® in ad-hoc mode. The application processor 105 may be equipped with software such as an operating system (O/S)/kernel 117 (for example, Linux® or Windows®), middleware 119, and applications 113. The O/S may include necessary drivers to provide support for the touchscreen 109 and the communication peripheral 107 in addition to a file system 121 for storing media. An application 123 (hereinafter referred to as “TapAPP”) may include application software configured to implement a method of data transfer between WTRU 101 and WTRU 103. TapAPP 123 may run on the application processor 105 running a high-end O/S such as Linux® or Windows®, for example. The communication peripherals 107 may include technologies such as a third generation partnership (3GPP) second or third generation standards (2G/3G) modem, Bluetooth® or WiFi®. Any combination or all of these communication technologies may be implemented in a single component design. Other peripherals such as a touchscreen/display 109, may also be supported. Peripherals 107, 109 may be operationally coupled to the application proces-

3

sor **105** through a physical interface **125** which, by way of example, may be a serial peripheral interface (SPI) or shared memory. The application processor **105** may provide support for the peripherals **107**, **109** through drivers or general application software.

TapAPP **123** may run on either or both of the sending **101** and receiving **103** WTRUs. TapAPP **123** may run on any communications device, and may be run in a send or receive mode. TapAPP **123** runs on the embedded O/S **117** and may be implemented as a native application, a Java® application or any other suitable type of application on the WTRUs **101**, **103**. TapAPP **123** may be a stand alone application **113** or may be tightly bound to middleware **119** thereby providing a background process, giving the user an “always on” usage experience. Additionally or alternatively, TapAPP **123** may be implemented as a plug-in application that may be launched by a user as needed in a manner known in the art. TapAPP **123** may provide display features to indicate a current state of the application (i.e. send or receive mode). For example, while in send mode, TapAPP **123** may allow the user to access and display a media file, such as a digital photograph for transfer, on the touchscreen/display **109**. In one representation of receive mode, TapAPP **123** may provide a touch point on the screen **109** or illuminate a touch point upon the user touching the touchscreen **109**, thereby enabling the user to access the underlying functionality of TapAPP **123** and receive the data transfer from the sending WTRU **101**. The underlying mechanics and technologies of touchscreens and displays are beyond the scope of this disclosure and are therefore omitted for the sake of clarity.

Referring to FIG. 2, a WTRU **101** configured for communicating data to target WTRU **101_{c,t}** is shown. The WTRU **101** comprises a user interface (UI) **109**, a processor **105**, a communication peripheral **107**, and an antenna **209**. Other components located within the WTRU **101**, for example, are a transmitter and receiver, but are not shown to avoid obfuscating the data communication illustration of FIG. 2. The communication peripheral **107** operates in the lower layers, for example, the physical (PHY) communication layer. The communication peripheral **107** receives and processes information relating to the electromagnetic environment in which the WTRU **101** is operating. The electromagnetic environment (hereafter referred to as local areas **211**, **213**) contains information being provided by the energy emanating from other WTRUs **101_c** operating within the local areas **211**, **213** of the WTRU **101**.

The local area in which WTRU **101** is operating may be configured to be a smaller radius of communication as identified by **213**, or the local area may be configured to be a larger radius as identified by **211**. The radius that defines the local areas **211**, **213** may be configured at the WTRU **101** by a user-defined variable that defines a search radius with respect to the WTRU **101**. Additionally, the local area in which the WTRU **101** is operating may be defined by any other appropriate manner. The communication peripheral **107** receives and maintains the environment information relating to the WTRUs **101_c** operating within the local areas **211**, **213**.

WTRUs **101_c** operating within the local areas **211**, **213** of WTRU **101** are referred to as candidate WTRUs **101_c** because they are potential recipients of data to be communicated by WTRU **101**. As shown in FIG. 2, there may be more than one candidate WTRU **101_c** as indicated by the WTRUs denoted with a “c”. Candidate WTRUs **101_c** may be WTRUs similarly equipped like WTRU **101**. From the candidate WTRUs **101_c**, at least one target WTRU **101_{c,t}** will be selected. FIG. 2 shows only one target WTRU **101_{c,t}**, but there may be more than one target WTRU **101_{c,t}** selected from the candidate

4

WTRUs **101_c**. For example, one WTRU **101** configured to communicate data to another WTRU, may communicate data to one or a multitude of other WTRUs selected from a set of candidate WTRUs **101_c**.

WTRU **101** comprises a UI **109** which may allow a user to provide user input to the WTRU **101**. Through the UI **109**, the user may provide user preferences relating to the communication of data from the WTRU **101**. The UI **109**, may be implemented, for example, in a touchscreen/display. Using a touchscreen display, the user may provide gestural actions to indicate user preferences. The user’s gestures may be directed to some visual depiction displayed on the touchscreen/display. The user may manipulate the visual depiction through a pre-defined gesture that is indicative of the user’s preferences regarding the data communication. For example, the visual depiction may identify a selected media element stored in the WTRU **101**. The user may manipulate the visual depiction of the media element to indicate the movement of the media element through the local areas **211**, **213**, in which the WTRU **101** is operating. Such movement, for example, may include distance denoted by the speed at which the visual depiction is moved across the UI **109**, or alternatively by the pressure exerted on the surface of the UI **109** by the user. Other gestural inputs may be defined to indicate user preferences. Direction of a data communication within the local areas **211**, **213** where the WTRU **101** is operating may be indicated by a movement of the visual depiction in the direction to indicate the direction of the data communication. Thus, for example, if the user wishes a data communication to occur between the user’s WTRU **101** and another WTRU operating in local areas **211**, **213** (i.e. the user has identified a desired target WTRU **101_{c,t}**), the user may provide a gesture via the UI **109** that is representative of the distance and direction of the selected target WTRU **101_{c,t}** with respect to the sending WTRU **101**.

WTRU **101** includes a processor **105** that is configurable to process information from the UI **109** and the communication peripheral **107**. Electromechanical signals from the UI **109** are provided as inputs to the processor **105**. Processor **105** may be configurable to execute machine readable instructions stored in any type of memory. Processor **105** is also configured to receive environment information stored by the communication peripheral **107**. The environment information and the user input are then used as inputs to the processor **105** and are processed to identify a target WTRU **101_{c,t}**. The electromechanical inputs from the UI **109**, which may include for example, an indication of direction and distance, are then correlated to the environment information stored at the lower layers by the communication peripheral **107**. Based on the correlation, a identification of at least one target WTRU **101_{c,t}** is determined and a data communication from the WTRU **101** may be transmitted to the identified target WTRU **101_{c,t}**.

The lower level information is provided to the application processor **105** according to the communication technology being used. For example, the information available to the application processor **205** may vary based on an implementation using a Third Generation Partnership Project (3GPP) technology, an Institute of Electronic and Electrical Engineers (IEEE) standard such as WiFi, or some other communication technology. For example IEEE 802.21 standard may be used where the TapAPP may register with an 802.21 client or other proprietary client to access and process lower layer information. Specific information relevant to the TapAPP’s identification of a target WTRU **101_{c,t}** may be provided from the communications peripheral **107**.

FIG. 3 shows inputs that may be used to drive a target discrimination algorithm **313** that uniquely identifies a target

5

WTRU for transfer of data. Possible inputs include environment information 301, receiver information 303, touchscreen information 305 and other information 307, such as WTRU 101 orientation for example where the WTRU 101 includes an accelerometer and supporting drivers. After processing the available inputs 301, 303, 305, and 307 by the application processor 105 through a target discrimination algorithm 313, configuration information 309 and transmission instructions 311 are generated as outputs.

The environment information 301 may, for example, be generated as follows. The application processor 105 may process instructions to periodically solicit information from the communication peripheral 107 relating to candidate WTRUs 101c operating in the local areas 211, 213 of a communicating WTRU 101. A configuration variable may be provided that allows the end user to define a search radius (e.g. 2-3 m) in which to solicit information. Devices outside the configured search radius will be excluded from received environment information. Throughout the timeframe that the application processor 105 is running a data communication application, the solicited information will be regenerated or updated. Upon receiving a user input indicating a data communication is desired, the solicited environment information 301 may be refreshed. The information collected regarding the candidate WTRUs 101c is included in the environment information 301 and may be used as an input to the target discrimination algorithm 313. In an embodiment, environment information 301 may be solicited by a localization method. For example, in a mesh network or a sensor network, the solicitation may include both the neighboring devices as well as independent device elements that enable the location and identity of each candidate WTRU to be determined accurately. Such a network may be comprised of independent sensors that respond to the communication peripheral 107 of the communicating WTRU 101, or may include the candidate WTRUs 101c, operating in the local areas 211, 213 of the communicating WTRU 101.

The environment information 301 may be gathered via a service discovery protocol (SDP) such as currently available in protocols such as Bluetooth®, for example. This protocol allows the WTRU 101 to discover the services (e.g. TapAPP as described herein) that are supported by other WTRUs operating in the local environment. An application such as TapAPP described above may invoke SDP functionality to discover all of the TapAPP enabled WTRUs operating in a particular location. For example, a Bluetooth® connection may be used to implement a SDP for this purpose. A radio dialog between the WTRU 101 and one or more candidate WTRUs 101c is established according to the defined SDP. Information received in the radio dialog may be analyzed and filtered (e.g. power level, or quality of a received signal) to determine the individual candidate WTRUs 101c or set of candidate WTRUs 101c in a local proximity. When a set of candidate WTRUs 101c is determined, a second level of search radius granularity may be applied by further defined radio dialogs between the WTRU 101 and a subset of candidate WTRUs 101c. In addition to the SDP information directly discoverable by the WTRU 101, each candidate WTRU 101c may exchange additional locally gathered information (e.g. GPS, or other location information gathered via a localization scheme) with other candidate WTRUs 101c. On a condition that a sufficient number of candidate WTRUs 101c are identified by the SDP, triangulation mechanisms may be implemented to establish a view of relative locations between a set of identified candidate WTRUs 101c. The entire environment discovery procedure may be implemented continuously and in real-time while the TapAPP is running on all

6

the candidate WTRUs 101c with the TapAPP capabilities to update and maintain a real-time local map that is preserved in each instance of the TapAPP.

The receiver information 303, may be generated according to the following example. During data communication, send and receive operations are initiated between a sending WTRU 101 and a target WTRU 101c,t. The user of the sending WTRU 101 initiates, through a user input, a send operation for a selected media element. On the receiving side, the target WTRU 101c,t user may touch and hold the touchscreen of the target WTRU 101c,t for all or part of the transfer process. The user input of the target WTRU 101c,t may result in the target WTRU 101c,t transmitting a radio signal to the sending WTRU 101, for example, an acknowledgement signal, the radio signal may be reported to the application processor 105. This receiver information 303 may serve as an input to the target discrimination algorithm 313.

A user input received from the UI 109, for example a touchscreen/display, may be translated into application signals by the touchscreen/display 109 or processor 105. This touchscreen information 305 is input to the target discrimination algorithm 313 to identify a target WTRU 101c,t. Touchscreen information 305 may include a file reference, speed, pressure, acceleration, timing information, direction, etc. File reference information may be used to identify a selected media element stored in the file system of the sending WTRU 101 that is the object of the data communication.

Directional inputs provided by the user via the touchscreen/display 109 may be synthesized to establish relative orientation to the real-time local map and select a target WTRU 101c,t from the identified group of candidate WTRUs 101c to establish a one-to-one communication between the transmitting WTRU 101 and the target WTRU 101c,t or a selected one-to-many communication to a plurality of target WTRUs 101c,t. In an example of a user input, an accelerometer associated with the WTRU 101 may provide input regarding the orientation of the WTRU 101 with respect to the real-time local map. For example, if the WTRU 101 was held upside-down, the real-time local map would be referenced and applied upside-down as dictated by the orientation of the sending WTRU 101.

Other information 307 may be used as an input to the target discrimination algorithm 313. For example, if the sending WTRU 101 device is equipped with an accelerometer and supporting drivers, the orientation of the sending WTRU 101 may be used as input information 307. Any type of other information 307 germane to the selection of a target WTRU 101c,t may be used as an input to the target discrimination algorithm 313.

Configuration information 309 may include settings for attributes such as power level, antenna orientation, security parameters and the like. Transmission instructions 311 may include information regarding the data to be communicated and the identity of the target WTRU 101c,t as well as instructions for implementing the transfer through specific components in the communication peripheral. The configuration information 309 and transmission instructions 311 may be delivered to the communication peripheral 107. The configuration information 309 and transmission instructions 311 may impact the configuration of the Layer 2/3 baseband components, (e.g., the power settings), and/or the analog and radio frequency components, (e.g., antenna orientation of the communication peripheral 107). The application processor 105 in the sending WTRU 101 may control the manner in which the data is transferred to the target WTRU 101c,t, for example, by breaking the data into blocks corresponding to the manner in which the visual depiction of the data should appear at the

7

target WTRU 101*c,t*. This control may involve the appending of some segmentation/display guidance information to the file blocks that may be used at the target WTRU 101*c,t* receiver to help render the visual depiction in a synergistic manner which is described in more detail hereinafter with respect to FIG. 7.

FIG. 4 shows a method of identifying a target WTRU 101*c,t* for a data communication with multiple WTRUs. Environment information 301 is solicited and information related to at least one candidate WTRU 101*c* operating in the local area of the sending WTRU 101 is detected 401. A user input is received 403, for example, through a touchscreen/display UI 109, wherein the user input is related to the communication of data from the sending WTRU 101 to at least one candidate WTRU 101*c*. The user input and the environment information relating to the candidate WTRUs 101*c* is processed simultaneously 405. For example, in a target discrimination algorithm 313 as described in FIG. 3. At least one target WTRU 101*c,t* is identified from the set of candidate WTRUs 407. The target WTRU 101*c,t* is identified at least in part on the user input received and the environment information 301 detected.

Physical layer security mechanisms may be applied to establish the environment information 301 as well as securing the data for short range data communication between WTRUs 101. The data may be transferred only as far as is necessary to reach a minimal set of users in the local environment of the sending WTRU 101. The target discrimination algorithm 313 may be configured to secure the file from beyond a local group (i.e. the local environment of the sending WTRU 101) and excluding others. One example of achieving this is a secure data transfer based on the reciprocity of the wireless channels between the sending WTRU 101 and the target WTRU 101*c,t*. The uniqueness and reciprocity of the wireless channel may be utilized to accomplish this in two steps. First, the location information for a particular WTRU 101 is associated with a channel impulse response (CIR) from that WTRU 101, which is unique, albeit variable. The CIR may be used to generate a secret key stream for that location. A more detailed description of such a secret key encryption may be found in U.S. patent application Ser. No. 11/339,958 which is herein incorporated by reference. A common cipher source, for example, Advanced Encryption Standard (AES), may be seeded with the key, and the information for the target WTRU 101*c,t* is encrypted with it. Alternatively or in addition, the CIR based information may be used to authenticate the message. The result is that only the selected target WTRU 101*c,t* may receive the data, because only the target WTRU 101*c,t* has the required channel-based key.

FIG. 5 shows an implementation of physical layer security for data communication between multiple WTRUs 101. The static (or slowly changing) physical location 501 of WTRUs 101 operating in the local areas 211, 213 and their respective radio channels 503 are input to a locations and channels association unit 505 that associates the locations 501 and the channels 503 of each WTRU 101 operating in the local areas 211, 213. Dynamic receiver information 507 relating to the CIR of each communicating WTRU 101 is used by channel-based key distillation unit 509, which continuously generates channel-based encryption keys for each WTRU 101 in the local environment. When required by a user, as indicated by touchscreen information 513, a target WTRU 101*c,t* may be identified from an available listing of candidate WTRUs 101*c* by the dynamic target matching algorithm 515. The dynamic target matching algorithm 515, receives input from the locations and channels association unit 505, the channel-based encryption keys 509, and the touchscreen information 513,

8

and the directional information 511 of the sending WTRU as inputs to identify one or more target WTRUs 101*c,t* as the recipient(s) of the data communication. Transmission instructions 517 are generated to facilitate the data transfer to the target WTRUs 101*c,t*.

Referring now to FIG. 6, a user input action for sending a file to another device is shown. The data transfer may take place from a sending WTRU 101 as shown in FIG. 1. The sending WTRU 101 may use an application such as TapAPP 123 to facilitate the data transfer. The sending WTRU 101 may have a touchscreen/display device 109 through which an end user may provide input information to the sending WTRU 101. The transfer application (TapAPP 123) may be running on the sending WTRU 101. As an example, TapAPP 123 may be configured to receive a simple three step hand (or finger) motion to enable the data transfer. The three steps include a tap 6A, a push action 6B, and a release action 6C. Referring to 6A, the user taps 605 the touchscreen 109 at a location on the touchscreen 109 where a visual depiction 603 of a media element to be transferred is displayed. Without lifting the finger used to tap 605 the visual depiction 603, the user then pushes the visual depiction 603 of the media element across the touchscreen 109 as shown by the directional arrow 607 in FIG. 6B. In an embodiment, the direction in which the user pushes the visual depiction 603 may simulate the direction of a target receiving WTRU 101*c,t* which is the intended recipient of the media element to be transferred. The media element may be any type of data file capable of being stored on the WTRU 101, for example, the media element may be a digital photograph, a video file, a word processing document or the like. When the user has pushed the visual depiction 603 of the media element in the direction the user would like the media element to be transferred, the user then releases 609 contact with the visual depiction 603 to initiate the data transfer. The three user actions 6A, 6B, and 6C, provide inputs to the touchscreen 109, which may be converted to electromechanical signals through mechanisms known in the art. The electromechanical signals may serve as input to the TapAPP 123 application, which may generate environmental information and transmission instructions relating to a target WTRU 101*c,t* selected by TapAPP in a manner explained above with respect to FIG. 3. The environmental information 301 and transmission instructions 311 are then processed by the WTRU 101 and the media element is transmitted 611.

FIGS. 7A and 7B are an illustration of a data transfer depicted from the perspective of both a sending WTRU 101 and a receiving WTRU 103. The data transfer is a process between two or more WTRUs. For example, the data transfer may originate from one sending WTRU 101 and be directed toward one or more receiving WTRUs 103. As seen in FIG. 7A, the media element being transferred in this example is a digital photograph. A visual depiction 603 may be displayed on the touchscreen/display 109. The sender may touch the touchscreen 109 and push 707 the visual depiction 603 of the digital photograph in the direction of the intended receiving WTRU 103. A receiving WTRU 103 may run TapAPP 123 to enable the receiving WTRU 103 to receive the transferred data. The receiving WTRU 103, for example, may be running TapAPP 123 in a receive mode. The TapAPP 123 provides an indication 603*b* or a prompt that a data transfer is ready for receiving. To receive a file, the user may touch 701 the touchscreen 109 to initiate reception of the data transfer. The user may touch 701 the touchscreen 109 for the entire time the data transfer is taking place, or the user may touch 701 the touchscreen 109 for some portion of the time the data transfer is occurring.

9

During the transfer, the visual depiction **603** may be configured to display the progress of the data transfer to the user at one or both of the sending WTRU **101** and the receiving WTRU **103**. As shown in FIG. 7A on the sending WTRU **101** as visual depiction **603a**, the portion of the data transfer remaining to be sent may be displayed on the touchscreen/display **109** of the sending WTRU **101** as a partial visual depiction **603a** of the digital photograph. As the data transfer progresses, the visual depiction **603a** is updated to indicate the remaining amount of data to be transferred. Similarly, at the receiving WTRU **103**, a visual depiction **603b** may be displayed on the touchscreen/display **109** of the receiving WTRU **103** to indicate to a user the amount of the data transfer that has been transmitted to the receiving WTRU **103**. As shown in FIG. 7B, when the data transfer is complete, the visual depiction **603** is displayed in its entirety at the receiving WTRU **103**. Upon receipt of the file, the user of the receiving WTRU **103** may release the touchscreen **109** and the receiving WTRU **103** may send an application level acknowledgment to the sending WTRU **101**. Thus, as shown in FIGS. 7A and 7B, the user may observe the visual depiction **603a** disappearing from the sending WTRU **101** while the visual depiction **603b** is emerging on the receiving WTRU **103** in such manner that the overall visual depiction **603** is preserved for the duration of the data transfer. The underlying data transfer mechanism may prioritize the transfer of data file elements to enable this user experience. In an alternate embodiment, this user experience may be provided at the application level. The file may be transferred as a whole, but the rendering aspect of the application on both the send and receive sides of the data transfer creates the appearance of a progressive and contiguous data transfer.

FIG. 8 is an illustration of the user experience while sending a data transfer in a direction of a targeted recipient. The same three step process described in FIG. 6 is utilized where the sender taps **605** a visual depiction **603** of the selected media element. As shown in FIG. 8B, the sender then pushes the visual depiction **603** of the media element to the right **801** which may simulate the physical direction with relation to the sending WTRU **101** where an intended receiving WTRU **103** (not shown) is operating. Based on the input information of the user, including the direction **801** in which the sender pushed the visual depiction **603** of the media element, the sending WTRU **101** may be configured to transmit the data transfer in a direction **803** matching the direction of the user action direction **801**. The visual depiction **603** may be configured to indicate the progress of the data transfer and may accomplish this by causing the visual depiction **603** to disappear from the touchscreen/display **109** in the same direction as the user action direction **801**. Antenna orientation may be utilized to control the transmission direction **803**.

FIG. 9 shows an illustration of a UI **109** being used to perform a data communication to multiple receiving WTRUs. The user may tap on a visual depiction **903** of a media element selected for communication to a receiving WTRU as shown in FIG. 9A. As shown, the user may tap on the visual depiction **903** multiple times **905**. While in the example of FIG. 9A, the user taps the visual depiction **903** twice, the user may tap the visual depiction **903** any number of times corresponding to the intended number of receiving WTRUs. Upon performing a multiple tap **905**, the master visual depiction **903** will be split into a number of secondary visual depictions **907**, **909** equal to the number of taps **905** of the user. This action by the user will lock the master visual depiction **903** while allowing the secondary visual depictions **907**, **909** to be manipulated by the user via the UI **109**. For example, with respect to FIG. 9B, a user may use a two-hand, two finger motion to move

10

secondary visual depiction **907** in the direction of a first target WTRU, while simultaneously moving secondary visual depiction **909** in the direction of a second target WTRU. The user may also use a single-hand, single finger motion to move each secondary visual depiction **907**, **909** sequentially. Upon release of the secondary visual depiction **907**, **909**, the data is communicated to a target WTRU identified by the process described herein regarding FIG. 2. The secondary visual depictions **907**, **909** may be smaller than the master visual depiction **903**, or the secondary depictions may be the same size as the master depiction. Alternatively, the secondary depictions **907**, **909** may have a visually distinguishing feature that distinguishes them from the master depiction **903** to the user.

Although features and elements are described above in particular combinations, each feature or element can be used alone without the other features and elements or in various combinations with or without other features and elements. The methods or flow charts provided herein may be implemented in a computer program, software, or firmware incorporated in a computer-readable storage medium for execution by a general purpose computer or a processor. Examples of computer-readable storage mediums include a read only memory (ROM), a random access memory (RAM), a register, cache memory, semiconductor memory devices, magnetic media such as internal hard disks and removable disks, magneto-optical media, and optical media such as CD-ROM disks, and digital versatile disks (DVDs).

Suitable processors include, by way of example, a general purpose processor, a special purpose processor, a conventional processor, a digital signal processor (DSP), a plurality of microprocessors, one or more microprocessors in association with a DSP core, a controller, a microcontroller, Application Specific Integrated Circuits (ASICs), Field Programmable Gate Arrays (FPGAs) circuits, any other type of integrated circuit (IC), and/or a state machine.

A processor in association with software may be used to implement a radio frequency transceiver for use in a wireless transmit receive unit (WTRU), user equipment (UE), terminal, base station, radio network controller (RNC), or any host computer. The WTRU may be used in conjunction with modules, implemented in hardware and/or software, such as a camera, a video camera module, a videophone, a speakerphone, a vibration device, a speaker, a microphone, a television transceiver, a hands free headset, a keyboard, a Bluetooth® module, a frequency modulated (FM) radio unit, a liquid crystal display (LCD) display unit, an organic light-emitting diode (OLED) display unit, a digital music player, a media player, a video game player module, an Internet browser, and/or any wireless local area network (WLAN) or Ultra Wide Band (UWB) module.

What is claimed is:

1. A method performed by a wireless transmit/receive unit (WTRU), the method comprising:
 - processing, by the WTRU from a touch display, an input to select media in an application;
 - detecting, by the WTRU over bluetooth, another WTRU;
 - processing, by the WTRU, another input from the touch display to select the another WTRU;
 - sending, by the WTRU to the selected another WTRU, a message to transfer the selected media;
 - receiving, by the WTRU, an acceptance to transfer the selected media; and
 - transferring, by the WTRU to the selected another WTRU over WiFi, the selected media.
2. The method of claim 1, wherein the input or the another input is a multi-touch input.

11

3. The method of claim 1 further comprising:
displaying, by the WTRU, a progress of the transfer to the selected another WTRU.
4. The method of claim 1, wherein the media is any one of a photograph, video, or a document.
5. The method of claim 1, wherein the input or the another input is a tap.
6. The method of claim 1, wherein the message to transfer is a request.
7. The method of claim 1, wherein the transferring by the WTRU over WiFi uses a WiFi link.
8. The method of claim 1, wherein the transferring by the WTRU is provided by a communication peripheral.
9. The method of claim 1 further comprising using blue-
tooth to detect one of a plurality of WTRUs in proximity to the WTRU.
10. The method of claim 9, wherein the detection of the plurality of WTRUs utilizes a service discovery protocol.
11. The method of claim 1 further comprising:
processing, by the WTRU, release of a touch contact to initiate transfer of the selected media to the selected another WTRU.
12. The method of claim 1 further comprising:
determining, by the WTRU, that the selected another WTRU is compatible to receive the selected media.
13. The method of claim 1, wherein a real time map is maintained of a plurality of WTRUs in proximity to the WTRU.
14. The method of claim 1 further comprising:
determining, by the WTRU, environment information that lists a plurality of WTRUs in proximity to the WTRU.
15. The method of claim 1, wherein the WTRU processes the input or the another input based on information from the touch display.
16. The method of claim 1 further comprising:
initiating, by the WTRU, transfer of media based on a gesture on a visual representation, displayed on the touch display, of the media; and
wherein the gesture is in a direction of an intended receiving WTRU.
17. The method of claim 1, wherein the input or the another input is a gesture input.
18. The method of claim 1, wherein the input or the another input is a multi-finger input.
19. The method of claim 1, wherein the input or the another input is a multi-finger gesture.
20. The method of claim 1 further comprising:
transferring, by the WTRU to the selected another WTRU, additional display information; and
wherein the additional display information is displayed before the selected media is completely transferred.
21. The method of claim 1 further comprising:
receiving, by the WTRU from a different WTRU, a request to transfer other media;
receiving, in response to accepting the request by the WTRU, the other media; and
displaying, by the WTRU, the other media substantially completely to a user of the WTRU.
22. The method of claim 1, wherein the input or the another input is a gesture input.
23. A wireless transmit/receive unit (WTRU) comprising:
circuitry configured to process, from a touch display, an input to select media in an application;
circuitry configured to detect, by the WTRU over blue-
tooth, another WTRU;
the circuitry further configured to process another input from the touch display to select the another WTRU;

12

- circuitry configured to send, by the WTRU to the selected another WTRU, a message to transfer the selected media;
- circuitry configured to receive, by the WTRU, an acceptance to transfer the selected media; and
- circuitry configured to transfer, by the WTRU to the selected another WTRU over WiFi, the selected media.
24. The WTRU of claim 23, wherein the input or the another input is a multi-touch input.
25. The WTRU of claim 23 further comprising:
circuitry configured to display, by the WTRU, a progress of the transfer to the selected another WTRU.
26. The WTRU of claim 23, wherein the media is any one of a photograph, video, or a document.
27. The WTRU of claim 23, wherein the first input or the another input is a tap.
28. The WTRU of claim 23, wherein the message to transfer is a request.
29. The WTRU of claim 23, wherein the circuitry configured to transfer over WiFi uses a WiFi link.
30. The WTRU of claim 23, wherein the circuitry configured to transfer is provided by a communication peripheral.
31. The WTRU of claim 23 further comprising using blue-
tooth to detect one of a plurality of WTRUs in proximity to the WTRU.
32. The WTRU of claim 31, wherein the detection of the plurality of WTRUs utilizes a service discovery protocol.
33. The WTRU of claim 23 further comprising:
the circuitry further configured to process, by the WTRU, release of a touch contact to initiate transfer of the selected media to the selected another WTRU.
34. The WTRU of claim 23 further comprising:
circuitry configured to determine, by the WTRU, that the selected another WTRU is compatible to receive the selected media.
35. The WTRU of claim 23, wherein a real time map is maintained of a plurality of WTRUs in proximity to the WTRU.
36. The WTRU of claim 23 further comprising:
circuitry configured to determine, by the WTRU, environment information that lists a plurality of WTRUs in proximity to the WTRU.
37. The WTRU of claim 23, wherein the WTRU processes the input or the another input based on information from the touch display.
38. The WTRU of claim 23 further comprising:
circuitry configured to initiate, by the WTRU, transfer of media based on a gesture on a visual representation, displayed on the touch display, of the media; and
wherein the gesture is in a direction of an intended receiving WTRU.
39. The WTRU of claim 23, wherein the input or the another input is a gesture input.
40. The WTRU of claim 23, wherein the input or the another input is a multi-finger input.
41. The WTRU of claim 23, wherein the input or the another input is a multi-finger gesture.
42. The WTRU of claim 23 further comprising:
the circuitry further configured to transfer, by the WTRU to the selected another WTRU, additional display information; and
wherein the additional display information is displayed before the selected media is completely transferred.
43. The WTRU of claim 23 further comprising:
the circuitry further configured to receive, by the WTRU from a different WTRU, a request to transfer other media;

13

the circuitry further configured to receive, in response to accepting the request by the WTRU, the other media; and

circuitry configured to display, by the WTRU, the other media substantially completely to a user of the WTRU. 5

44. The WTRU of claim 23, wherein the input or the another input is a gesture input.

45. The method of claim 7, wherein the WiFi link operates using 802.21.

46. The method of claim 7, wherein the WiFi link utilizes 10 peer-to-peer communication.

47. The method of claim 46, wherein the peer-to-peer communication operates in WiFi ad-hoc mode.

48. The WTRU of claim 29, wherein the WiFi link operates using 802.21. 15

49. The WTRU of claim 29, wherein the WiFi link utilizes peer-to-peer communication.

50. The WTRU of claim 49, wherein the peer-to-peer communication operates in WiFi ad-hoc mode.

* * * * *

20

14

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 9,173,054 B2
APPLICATION NO. : 14/251383
DATED : October 27, 2015
INVENTOR(S) : Carlton et al.


Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

IN THE CLAIMS

In claim 27, at column 12, line 15, after “wherein the”, delete “first”.

Signed and Sealed this
Eighth Day of November, 2016

A handwritten signature in black ink, reading "Michelle K. Lee". The signature is written in a cursive style with a large, stylized "M" and "L".

Michelle K. Lee
Director of the United States Patent and Trademark Office