US 20080168384A1

(19) United States

(12) Patent Application Publication

Platzer et al.

(10) Pub. No.: US 2008/0168384 A1

(43) Pub. Date: Jul. 10, 2008

(54) APPLICATION PROGRAMMING INTERFACES FOR SCROLLING OPERATIONS

(76) Inventors: **Andrew Platzer**, Santa Clara, CA (US); **Scott Herz**, Santa Clara, CA (US)

Correspondence Address:
APPLE COMPUTER, INC./BLAKELY
1279 OAKMEAD PARKWAY
SUNNYVALE, CA 94085-4040

(21) Appl. No.: 11/620,717

(22) Filed: Jan. 7, 2007

Publication Classification

(51) Int. Cl.
G06F 3/048 (2006.01)
G06F 9/54 (2006.01)

(52) U.S. Cl. 715/784; 719/328

(57) ABSTRACT

At least certain embodiments of the present disclosure include an environment with user interface software interacting with a software application. A method for operating through an application programming interface (API) in this environment includes transferring a set bounce call. The method further includes setting at least one of maximum and minimum bounce values. The set bounce call causes a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.



MICROSOFT CORP.
EXHIBIT 1245


100
RECEIVE A USER INPUT
102
CREATE AN EVENT OBJECT IN RESPONSE TO THE USER INPUT
104
DETERMINE WHETHER THE EVENT OBJECT INVOKES A SCROLL OR GESTURE OPERATION
106
ISSUE AT LEAST ONE SCROLL OR GESTURE CALL BASED ON INVOKING THE SCROLL OR GESTURE OPERATION
108
RESPOND TO AT LEAST ONE SCROLL CALL, IF ISSUED, SCROLL A WINDOW HAVING A VIEW ASSOCIATED WITH THE EVENT OBJECT BASED ON AN AMOUNT OF A SCROLL WITH THE SCROLL STOPPED AT A PREDETERMINED POSITION IN RELATION TO THE USER INPUT
110
RESPOND TO AT LEAST ONE GESTURE CALL, IF ISSUED, CHANGE A VIEW ASSOCIATED WITH THE EVENT OBJECT BASED ON RECEIVING A PLURALITY OF INPUT POINTS IN THE FORM OF THE USER INPUT
112

FIG. 1


200
TRANSFER A SET BOUNCE CELL
202
SET AT LEAST ONE OF MAXIMUM AND MINIMUM BOUNCE VALUES
204
CAUSE A SLIGHT BOUNCE OF A SCROLLED REGION IN AN OPPOSITE DIRECTION OF A SCROLL BASED ON A REGION PAST AN EDGE OF A CONTENT BEING VISIBLE IN A DISPLAY REGION AT THE END OF THE SCROLL
206

FIG. 2


300
TRANSFER A RUBBERBAND CALL TO CAUSE RUBBERBANDING A SCROLLED REGION DISPLAYED WITHIN A DISPLAY REGION
302
TRANSFER AN EDGE RUBBERBAND CALL TO SET DISPLACEMENT VALUES FOR AT LEAST ONE EDGE OF THE DISPLAY REGION
304

FIG. 3


GUI
DISPLAY
408
400
INFORMATION
412-1
INFORMATION
412-2
INFORMATION
412-3
INFORMATION
412-4
MOVEMENT
414
416
WINDOW
410
MENU

FIG. 4


GUI
DISPLAY
408
400
INFORMATION
412-1
VELOCITY
510-1
DISTANCE
512-1
TERMINUS
514
WINDOW
410
MENU

FIG. 5A


GUI
DISPLAY
408
400
INFORMATION
412-1
TERMINUS
514
WINDOW
410
MENU

FIG. 5B


GUI
DISPLAY
408
400
VELOCITY
510-2
INFORMATION
412-1
DISTANCE
512-1
TERMINUS
514
WINDOW
410
MENU

FIG. 5C


PORTABLE MULTIFUNCTION DEVICE
100
206
SPEAKER
111
OPTICAL
SENSOR 164
PROXIMITY
SENSOR 166
3500A
208
208
402
Current Time
404
406
Mailboxes
3502
Inbox
6
3504
3512-1
Bruce Walker
3506-2
January 30, 2006
3510-2
Lunch meeting today
3508-2
Kim Brook
3506-3
January 30, 2006
3510-3
Draft agreement
3508-3
Bob Adams
January 29, 2006
Project Orion
3514
3512-2
Darin Adler
January 29, 2006
fantasy football
Aaron Jones
January 29, 2006
Fwd: status report
Kim Brook
January 28, 2006
Re: proposal
3532
3518
3520
3522
3524
3526
3510
MICROPHONE
113
HOME
204

FIG. 6A


PORTABLE MULTIFUNCTION DEVICE
100
206
SPEAKER
111
OPTICAL
SENSOR 164
PROXIMITY
SENSOR 166
3500A
208
208
402
Current Time
404
406
Mailboxes
3502
Inbox
6
3504
Aaron Jones
3506-1
January 30, 2006
3510-1
Re: Project Orion
3508-1
3534
3512-1
Bruce Walker
3506-2
January 30, 2006
3510-2
Lunch meeting today
3508-2
3530
Kim Brook
3506-3
January 30, 2006
3510-3
Draft agreement
3508-3
3514
Bob Adams
January 29, 2006
Project Orion
3512-2
Darin Adler
January 29, 2006
fantasy football
Aaron Jones
January 29, 2006
Fwd: status report
3518
3520
3522
3524
3526
3510
MICROPHONE
113
HOME
204

FIG. 6B


PORTABLE MULTIFUNCTION DEVICE
100
206
SPEAKER
111
OPTICAL
SENSOR 164
PROXIMITY
SENSOR 166
3500A
208
402
Current Time
404
406
208
Mailboxes
3502
Inbox
6
3504
3536
Aaron Jones
3506-1
January 30, 2006
3510-1
Re: Project Orion
3508-1
3512-1
Bruce Walker
3506-2
January 30, 2006
3510-2
Lunch meeting today
3508-2
3530
Kim Brook
3506-3
January 30, 2006
3510-3
Draft agreement
3508-3
3514
Bob Adams
January 29, 2006
Project Orion
3512-2
Darin Adler
January 29, 2006
fantasy football
3518
3520
3522
3524
3526
3510
MICROPHONE
113
HOME
204

FIG. 6C


PORTABLE MULTIFUNCTION DEVICE
100
206
SPEAKER
111
OPTICAL
SENSOR 164
PROXIMITY
SENSOR 166
3500A
208
208
402
Current Time
404
406
Mailboxes
3502
Inbox
6
3504
Aaron Jones
3506-1
January 30, 2006
3510-1
Re: Project Orion
3508-1
3534
3512-1
Bruce Walker
3506-2
January 30, 2006
3510-2
Lunch meeting today
3508-2
3530
Kim Brook
3506-3
January 30, 2006
3510-3
Draft agreement
3508-3
Bob Adams
January 29, 2006
Project Orion
3512-2
Darin Adler
January 29, 2006
fantasy football
Aaron Jones
January 29, 2006
Fwd: status report
3518
3520
3522
3524
3526
3510
MICROPHONE
113
HOME
204

FIG. 6D


700
TRANSFER A DIRECTIONAL SCROLL CALL TO DETERMINE IF DIRECTIONAL SCROLLING IS ENABLED
702
TRANSFER A DIRECTIONAL SCROLL ANGLE CALL TO SET A SCROLL ANGLE FOR LOCKING THE SCROLLING IN AT LEAST ONE OF A VERTICAL OR A HORIZONTAL DIRECTION
704
LOCK THE SCROLLING IN THE HORIZONTAL DIRECTION IF A USER INPUT FORMS AN ANGLE WITH A HORIZONTAL DIRECTION THAT IS LESS THAN OR EQUAL TO A FIRST SCROLL ANGLE
706
LOCK THE SCROLLING IN THE VERTICAL DIRECTION IF A USER INPUT FORMS AN ANGLE WITH A VERTICAL DIRECTION THAT IS LESS THAN OR EQUAL TO A SECOND SCROLL ANGLE
708

FIG. 7



FIG. 8


900
TRANSFER A DECELERATION SCROLL CALL TO SET A DECELERATION FACTOR FOR A DRAG USER INPUT THAT INVOKES A SCROLL
902
SLOW THE SCROLL TO A STOP BASED ON THE SPEED OF THE DRAG USER INPUT
904

FIG. 9


1000
TRANSFER A SCROLL HYSTERESIS CALL TO DETERMINE WHETHER THE USER INPUT INVOKES A SCROLL
1002
SET THE HYSTERESIS VALUE FOR DETERMINING WHETHER A USER INPUT INVOKES A SCROLL
1004

FIG. 10


1100
TRANSFER A SCROLL INDICATOR CALL TO DETERMINE WHETHER AT LEAST ONE SCROLL INDICATOR ATTACHES TO A SCROLL REGION OR A WINDOW EDGE
1102
OPTIONALLY ATTACH SCROLL INDICATORS TO A SCROLL REGION BASED ON THE SCROLL INDICATOR CALL
1104
OPTIONALLY ATTACH SCROLL INDICATORS TO A WINDOW EDGE BASED ON THE SCROLL INDICATOR CALL
1106

FIG. 11


1200
TRANSFER AN INADVERTENT USER INPUT CALL TO DETERMINE WHETHER THE USER INPUT WAS INADVERTENT
1202
IGNORE THE INADVERTENT USER INPUT BASED ON THE INADVERTENT USER INPUT CALL
1204

FIG. 12


1300
TRANSFER A HANDLE GESTURE EVENT CALL
1302
TRANSFER A GESTURE CHANGE CALL IN RESPONSE TO THE HANDLE GESTURE EVENT CALL
1304

FIG. 13


1400
TRANSFER A SCALING TRANSFORM CALL TO DETERMINE A SCALING TRANSFORM FOR A VIEW ASSOCIATED WITH A USER INPUT HAVING A PLURALITY OF INPUT POINTS
1402
TRANSFER A SCALING GESTURE START CALL
1404
TRANSFER A SCALING GESTURE PROGRESS CALL
1406
TRANSFER A SCALING GESTURE END CALL
1408

FIG. 14



FIG. 15



FIG. 16B



FIG. 16A



FIG. 16C


1700
TRANSFER A ROTATION TRANSFORM CALL TO DETERMINE A ROTATION TRANSFORM FOR A VIEW ASSOCIATED WITH A USER INPUT HAVING A PLURALITY OF INPUT POINTS
1702
TRANSFER A START ROTATION GESTURE CALL
1704
TRANSFER ROTATION GESTURE PROCESS CALL
1706
TRANSFER A ROTATION GESTURE END CALL
1708

FIG. 17


1800
ANY ANIMATION? 1802
NO
YES
PROGRESS? 1804
YES
CALCULATE NEXT STATE 1806
NO
DELEGATE? 1808
NO
YES
NOTIFY DELEGATE 1810

FIG. 18


1900
START AT LEAST TWO ANIMATIONS
1902
DETERMINE THE PROGRESS OF EACH ANIMATION
1904
UPDATE EACH OF AT LEAST TWO ANIMATIONS BASED ON A SINGLE TIMER
1906

FIG. 19


2000
PROVIDE A SINGLE ANIMATION TIMER
2002
ANIMATE A PLURALITY OF ANIMATIONS
WITH THE SINGLE ANIMATION TIMER
2004

FIG. 20


2100
SET ATTRIBUTES OF VIEWS INDEPENDENTLY WITH EACH VIEW BEING ASSOCIATED WITH PROCESS
2102
TRANSFER A SYNCHRONIZATION CALL TO SYNCHRONIZE ANIMATIONS FOR THE MULTIPLE VIEWS OF THE DISPLAY
2104
TRANSFER A SYNCHRONIZATION CONFIRMATION MESSAGE WHEN A SYNCHRONIZATION FLAG IS ENABLED BASED ON THE LIST OF THE PROCESS BEING SYNCHRONIZED
2106
UPDATE THE ATTRIBUTES OF THE VIEWS INDEPENDENTLY
2108
TRANSFER A START ANIMATION CALL TO DRAW THE REQUESTED ANIMATIONS
2110

FIG. 21



FIG. 22A



FIG. 22B


2300
CONSTRUCT A DATA STRUCTURE HAVING A HIERARCHY OF LAYERS WITH A LAYER BEING ASSOCIATED WITH A VIEW AND OWNING THE VIEW
2302
REMOVE THE LAYER FROM THE DATA STRUCTURE
2304
SWITCH OWNERSHIP OF THE VIEW FROM THE LAYER TO THE VIEW
2306

FIG. 23


2400
CONSTRUCT A DATA STRUCTURE HAVING A HIERARCHY OF LAYERS WITH A LAYER BEING ASSOCIATED WITH A VIEW
2402
STORE THE DATA STRUCTURE IN MEMORY
2404
MAINTAIN A RETAINED COUNT OF THE NUMBER OF REFERENCES TO THE VIEW FROM OTHER OBJECTS
2406
DEALLOCATE THE VIEW FROM MEMORY IF THE RETAINED COUNT IS ZERO
2408

FIG. 24



FIG. 25A



FIG. 25B


2600
CONSTRUCT A DATA STRUCTURE HAVING A HIERARCHY OF LAYERS ASSOCIATED WITH THE USER INTERFACE OF THE DEVICE
2402
DETERMINE WHETHER EACH LAYER OF THE DATA STRUCTURE IS ASSOCIATED WITH MEDIA OR NON-MEDIA CONTENT
2604
DETACH MEDIA CONTENT FROM THE DATA STRUCTURE
2606
STORE MEDIA CONTENT IN A FIRST MEMORY LOCATION
2608
STORE NON-MEDIA CONTENT IN A SECOND MEMORY LOCATION
2610
COMPOSITE THE MEDIA AND NON-MEDIA CONTENT FOR DISPLAY ON THE DEVICE
2612

FIG. 26



FIG. 27



FIG. 28



FIG. 29



FIG. 30A



FIG. 30B


3100
STORAGE DEVICE 3104
AUDIO TRANSDUCER 3108
BATTERY 3107
MICROPHONE
105A
DISPLAY DEVICE 3106
BACKLIGHT 3106A
DIGITAL PROCESSING SYSTEM 3103
MEDIA PROCESSING SYSTEM 3109
INPUT DEVICE(S) 3105
DIGITAL AND/OR ANALOG RF TRANSCEIVER 3102
SENSOR(S) 3110
ANTENNA SYSTEM 3101

FIG. 31


3200
CACHE (OPTIONAL)
3208
3202
3204
MICROPROCESSOR
MEMORY
3206
BUS
3210
3212
DISPLAY CONTROLLER AND DISPLAY DEVICE (OPTIONAL)
I/O CONTROLLER(S)
3216
SENSOR(S) FOR USER ACTIVITY
3214
I/O DEVICE(S) (E.G., KEYBOARD, CURSOR CONTROL DEVICE, NETWORK INTERFACE)

FIG. 32



FIG. 33A



FIG. 33B



FIG. 33C


3400
CONSTRUCT A HIERARCHY OF VIEWS OPERATING ON TOP OF A HIERARCHY OF LAYERS
3402
PROVIDE ACCESS TO THE HIERARCHY OF VIEWS WITHOUT PROVIDING ACCESS TO THE HIERARCHY OF LAYERS
3404

FIG. 34

APPLICATION PROGRAMMING INTERFACES FOR SCROLLING OPERATIONS

FIELD OF THE DISCLOSURE

[0001] This disclosure relates to application programming interfaces that provide scrolling operations.

COMPUTER PROGRAM LISTING

[0002] A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent & Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

[0003] Applicant has submitted herewith Computer Program Listings which are included as Appendix A, attached.

BACKGROUND OF THE DISCLOSURE

[0004] An API is a source code interface that a computer system or program library provides in order to support requests for services from a software application. An API is specified in terms of a programming language that can be interpretative or compiled when an application is built, rather than an explicit low level description of how data is laid out in memory. The software that provides the functionality described by an API is said to be an implementation of the API.

[0005] Various devices such as electronic devices, computing systems, portable devices, and handheld devices have software applications. The API interfaces between the software applications and user interface software to provide a user of the device with certain features and operations. A user may desire certain operations such as scrolling, selecting, gesturing, and animating operations for a display of the device.

[0006] Scrolling is the act of sliding a directional (e.g., horizontal or vertical) presentation of content, such as text, drawings, or images, across a screen or display window. In a typical graphical user interface, scrolling is done with the help of a scrollbar or using keyboard shortcuts often the arrow keys. Gesturing is a type of user input with two or more input points. Animating operations include changing content within a given time period.

[0007] The various types of devices may have a limited display size, user interface, software, API interface and/or processing capability which limits the ease of use of the devices. User interfaces of devices implement APIs in order to provide requested functionality and features. These user interfaces can have difficulty interpreting the various types of user inputs and providing the intended functionality associated with the user inputs.

SUMMARY OF THE DESCRIPTION

[0008] At least certain embodiments of the present disclosure include one or more application programming interfaces in an environment with user interface software interacting with a software application. Various function calls or messages are transferred via the application programming interfaces between the user interface software and software applications. Example application programming interfaces transfer function calls to implement scrolling, gesturing, and animating operations for a device.

[0009] At least certain embodiments of the present disclosure include an environment with user interface software interacting with a software application. A method for operating through an application programming interface (API) in this environment includes transferring a set bounce call. The method further includes setting at least one of maximum and minimum bounce values. The set bounce call causes a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.

[0010] At least certain embodiments of the present disclosure include an environment with user interface software interacting with a software application. A method for operating through an application programming interface (API) in this environment includes transferring a rubberband call. Rubberbanding a scrolled region within a display region occurs by a predetermined maximum displacement when the scrolled region exceeds a display edge. The method further includes transferring an edge rubberband call to set displacement values for at least one edge of the display (e.g., top and bottom edges, left and right edges).

[0011] At least certain embodiments of the present disclosure include gesture operations for a display of a device. The gesture operations include performing a scaling transform such as a zoom in or zoom out in response to a user input having two or more input points. The gesture operations also include performing a rotation transform to rotate an image or view in response to a user input having two or more input points.

[0012] At least certain embodiments of the present disclosure include a method for performing animations for a display of a device. The method includes starting at least one animation. The method further includes determining the progress of each animation. The method further includes completing each animation based on a single timer. The single timer can be based on a redraw interval of the display hardware.

[0013] Various devices which perform one or more of the foregoing methods and machine readable media which, when executed by a processing system, cause the processing system to perform these methods, are also described.

[0014] Other methods, devices and machine readable media are also described.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The disclosure is described by way of example with reference to the accompanying drawings, wherein:

[0016] FIG. **1** is flow chart of a method for responding to a user input of a data processing device;

[0017] FIG. **2** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0018] FIG. **3** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0019] FIG. **4** is a schematic diagram illustrating an embodiment of user interface of a portable electronic device **400** having a touch-sensitive display **408**;

[0020] FIG. **5**A-**5**C illustrate at least some embodiments of user interface of a portable electronic device **400** having a touch-sensitive display;

[0021] FIG. **6**A-**6**D illustrate the scrolling of a list of items to a terminus of the list, at which point an area beyond the

terminus is displayed and the list is then scrolled in an opposite direction until the area beyond the terminus is no longer displayed, in accordance with some embodiments;

[0022] FIG. **7** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0023] FIG. **8** illustrates first and second scroll angles for locking a scroll of a display of a device in a horizontal or vertical direction according to certain teachings of the present disclosure;

[0024] FIG. **9** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0025] FIG. **10** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0026] FIG. **11** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0027] FIG. **12** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0028] FIG. **13** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0029] FIG. **14** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0030] FIG. **15** illustrates a display of a device having a scaling transform of a view:

[0031] FIGS. **16**A and **16**B illustrate a display of a device with a view having a first and a second scaling factor;

[0032] FIG. **17** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0033] FIG. **18** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0034] FIG. **19** is flow chart of a method for animating views displayed on a display of a device;

[0035] FIG. **20** is flow chart of a method for animating views displayed on a display of a device;

[0036] FIG. **21** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure;

[0037] FIGS. **22**A and **22**B illustrate synchronizing the resizing of windows of a display of a device;

[0038] FIG. **23** illustrates a method for switching ownership of a view of an application displayed on a display of a data processing device;

[0039] FIG. **24** illustrates a method for memory management of a view of an application displayed on a display of a device;

[0040] FIGS. **25**A and **258** illustrate a data structure having a hierarchy of layers with a layer being associated with a view;

[0041] FIG. **26** illustrates a method for compositing media and non-media content of user interface for display on a device;

[0042] FIG. **27** illustrates a data structure or layer tree having a hierarchy of layers;

[0043] FIG. **28** is a perspective view of a device in accordance with one embodiment of the present disclosure;

[0044] FIG. **29** is a perspective view of a device in accordance with one embodiment of the present disclosure;

[0045] FIG. **30** is a perspective view of a wireless device in accordance with one embodiment of the present disclosure;

[0046] FIG. **31** is a block diagram of a system in which embodiments of the present disclosure can be implemented;

[0047] FIG. **32** shows another example of a device in accordance with one embodiment of the present disclosure;

[0048] FIG. **33**A is a perspective view of a device in a first configuration (e.g. in a laptop configuration) in accordance with one embodiment of the present disclosure;

[0049] FIG. **33**B is a perspective view of the device of FIG. **33**A in a second configuration (e.g. a transition configuration) in accordance with one embodiment of the present disclosure;

[0050] FIG. **33**C is a perspective view of the device of FIG. **33**A in a third configuration (e.g., a tablet configuration) in accordance with one embodiment of the present disclosure; and

[0051] FIG. **34** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure.

DETAILED DESCRIPTION

[0052] Various embodiments and aspects of the disclosure will be described with reference to details discussed below, and the accompanying drawings will illustrate the various embodiments. The following description and drawings are illustrative of the disclosure and are not to be construed as limiting the disclosure. Numerous specific details are described to provide a through understanding of various embodiments of the present disclosure. However, in certain instances, well-known or conventional details are not described in order to provide a concise discussion of embodiments of the present disclosure.

[0053] Some portions of the detailed descriptions which follow are presented in terms of algorithms which include operations on data stored within a computer memory. An algorithm is generally a self-consistent sequence of operations leading to a desired result. The operations typically require or involve physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

[0054] It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as "processing" or "computing" or "calculating" or "determining" or "displaying" or the like, can refer to the action and processes of a data processing system, or similar electronic device, that manipulates and transforms data represented as physical (electronic) quantities within the system's registers and memories into other data similarly represented as physical quantities within the system's memories or registers or other such information storage, transmission or display devices.

[0055] The present disclosure can relate to an apparatus for performing one or more of the operations described herein.

This apparatus may be specially constructed for the required purposes, or it may comprise a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a machine (e.g. computer) readable storage medium, such as, but is not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), erasable programmable ROMs (EPROMs), electrically erasable programmable ROMs (EEPROMs), flash memory, magnetic or optical cards, or any type of media suitable for storing electronic instructions, and each coupled to a bus.

[0056] A machine-readable medium includes any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computer). For example, a machine-readable medium includes read only memory ("ROM"); random access memory ("RAM"); magnetic disk storage media; optical storage media; flash memory devices; electrical, optical, acoustical or other form of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.); etc.

[0057] At least certain embodiments of the present disclosure include one or application programming interfaces in an environment with user interface software interacting with a software application. Various function calls or messages are transferred via the application programming interfaces between the user interface software and software applications. Transferring the function calls or messages may include issuing, initiating, invoking or receiving the function calls or messages. Example application programming interfaces transfer function calls to implement scrolling, gesturing, and animating operations for a device having a display region. An API may also implement functions having parameters, variables, or pointers. An API may receive parameters as disclosed or other combinations of parameters. In addition to the APIs disclosed, other APIs individually or in combination can perform similar functionality as the disclosed APIs.

[0058] The display region is a form of a window. A window is a display region which may not have a border and may be the entire display region or area of a display. In some embodiments, a display region may have at least one window and/or at least one view (e.g., web, text, or image content). A window may have at least one view. The methods, systems, and apparatuses disclosed can be implemented with display regions, windows, and/or views.

[0059] At least certain embodiments of the present disclosure include scrolling operations for scrolling a display of a device. The scrolling operations include bouncing a scrolled region in an opposite direction of a scroll when a scroll completes, rubberbanding a scrolled region by a predetermined maximum displacement when the scrolled region exceeds a display edge, and setting a scrolling angle that locks the scroll in a horizontal or vertical direction.

[0060] At least certain embodiments of the present disclosure include gesture operations for a display of a device. The gesture operations include performing a scaling transform such as a zoom in or zoom out in response to a user input having two or more input points. The gesture operations also include performing a rotation transform to rotate an image or view in response to a user input having two or more input points.

[0061] At least certain embodiments of the present disclosure include a method for performing animations for a display of a device. The method includes starting at least one animation. The method further includes determining the progress of each animation. The method further includes completing each animation based on a single timer. The single timer can be based on a redraw interval of the display hardware.

[0062] At least certain embodiments of the disclosure may be part of a digital media player, such as a portable music and/or video media player, which may include a media processing system to present the media, a storage device to store the media and may further include a radio frequency (RF) transceiver (e.g., an RF transceiver for a cellular telephone) coupled with an antenna system and the media processing system. In certain embodiments, media stored on a remote storage device may be transmitted to the media player through the RF transceiver. The media may be, for example, one or more of music or other audio, still pictures, or motion pictures.

[0063] The portable media player may include a media selection device, such as a click wheel input device on an iPod® or iPod Nano® media player from Apple Computer, Inc. of Cupertino, Calif., a touch screen input device, push-button device, movable pointing input device or other input device. The media selection device may be used to select the media stored on the storage device and/or the remote storage device. The portable media player may, in at least certain embodiments, include a display device which is coupled to the media processing system to display titles or other indicators of media being selected through the input device and being presented, either through a speaker or earphone(s), or on the display device, or on both display device and a speaker or earphone(s). In some embodiments, the display device and input device are integrated while in other embodiments the display device and input device are separate devices. Examples of a portable media player are described in published U.S. patent application Nos. 2003/0095096 and 2004/0224638, both of which are incorporated by reference.

[0064] Embodiments of the disclosure described herein may be part of other types of data processing systems, such as, for example, entertainment systems or personal digital assistants (PDAs), or general purpose computer systems, or special purpose computer systems, or an embedded device within another device, or cellular telephones which do not include media players, or multi touch tablet devices, or other multi touch devices, or devices which combine aspects or functions of these devices (e.g., a media player, such as an iPod®, combined with a PDA, an entertainment system, and a cellular telephone in one device). In this disclosure, electronic devices and consumer devices are types of devices.

[0065] FIG. **1** is flow chart of a method for responding to a user input of a device. The method **100** includes receiving a user input at block **102**. The user input may be in the form of an input key, button, wheel, touch, or other means for interacting with the device. The method **100** further includes creating an event object in response to the user input at block **104**. The method **100** further includes determining whether the event object invokes a scroll or gesture operation at block **106**. For example, a single touch that drags a distance across a display of the device may be interpreted as a scroll operation. In one embodiment, a two or more finger touch of the display may be interpreted as a gesture operation. In certain embodiments, determining whether the event object invokes a scroll or gesture operation is based on receiving a drag user input for a certain time period. The method **100** further includes issuing at least one scroll or gesture call based on invoking the scroll or gesture operation at block **108**. The

method **100** further includes responding to at least one scroll call, if issued, by scrolling a window having a view (e.g., web, text, or image content) associated with the event object based on an amount of a scroll with the scroll stopped at a predetermined position in relation to the user input at block **110**. For example, an input may end at a certain position on a display of the device. The scrolling may continue until reaching a predetermined position in relation to the last input received from the user. The method **100** further includes responding to at least one gesture call, if issued, by changing a view associated with the event object based on receiving a plurality of input points in the form of the user input at block **112**.

[0066] In certain embodiments of the present disclosure scroll operations include attaching scroll indicators to a content edge of a display. Alternatively, the scroll indicators can be attached to the display edge. In some embodiments, user input in the form of a mouse/finger down causes the scroll indicators to be displayed on the display edge, content edge, or window edge of the scrolled region. If a mouse/finger up is then detected, the scroll indicators are faded out from the display region, content edge, or window edge of the scrolled region.

[0067] In certain embodiments of the present disclosure, gesture operations include responding to at least one gesture call, if issued, by rotating a view associated with the event object based on receiving a plurality of input points in the form of the user input. Gesture operations may also include scaling a view associated with the event object by zooming in or zooming out based on receiving the user input.

[0068] In some embodiments, a device includes a display region having multiple views or windows. Each window may have a multiple views including superviews and subviews. It is necessary to determine which window, view, superview, or subview is contacted by a user input in the form of a mouse up, mouse down, or drag, etc. An API can set various modes for making this determination. In one embodiment, a pass mode sends mouse down, mouse up, and drag inputs to the nearest subview. In another embodiment, an intercept on drag mode sends a drag input to the superview while mouse up and down inputs are sent to the subview. In another embodiment, an intercept mode sends all drag, mouse up and down inputs to the superview. The superview may be scroller software operating as a subclass of a view software. The subview may be view software operating as a subclass of the user interface software.

[0069] FIG. **2** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a bounce operation. The method **200** for providing a bounce operation includes transferring a set bounce call at block **202**. The method **200** further includes setting at least one of maximum and minimum bounce values at block **204**. The minimum and maximum bounce values may be associated with at least one edge of a window that has received a user input. The method **200** further includes causing a bounce of a scrolled region in an opposite direction of a scroll based on a region past the scrolled region being visible in a display region at the end of the scroll at block **206**. The scrolled region may be a content region.

[0070] In certain embodiments of the present disclosure, transferring the set bounce call is either one of issuing, initiating, invoking or receiving the set bounce call.

[0071] FIG. **3** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a rubberband operation. The method **300** for providing a rubberband operation includes transferring a rubberband call to cause rubberbanding a scrolled region displayed within a display at block **302**. The method **300** further includes transferring an edge rubberband call to set displacement values for at least one edge of the display at block **304**. In some embodiments, the displacement values are set for top and bottom edges, left and right edges, or all edges.

[0072] Rubberbanding a scrolled region according to the method **300** occurs by a predetermined maximum displacement value when the scrolled region exceeds a display edge of a display of a device based on the scroll. If a user scrolls content of the display making a region past the edge of the content visible in the display, then the displacement value limits the maximum amount for the region outside the content. At the end of the scroll, the content slides back making the region outside of the content no longer visible on the display.

[0073] In certain embodiments of the present disclosure, transferring the rubberband call is either one of issuing, initiating, invoking or receiving the rubberband call.

[0074] FIG. **4** is a schematic diagram illustrating an embodiment of user interface of a portable electronic device **400** having a touch-sensitive display **408**. The display **408** may include a window **410**. The window **410** may include one or more displayed objects, such as information objects **412-1** to **412-4**. In an exemplary embodiment, the information objects **412** may correspond to contact information for one or more individuals in a list of items. The displayed objects may be moved in response to detecting or determining movement **414** of a point of contact with the display, such as that associated with one or more digits **416** of a user (which are not drawn to Scale in FIG. **4**). In some embodiments, movement of the displayed objects may be accelerated in response to detecting or determining accelerated movement of the point of contact. While embodiment **400** includes one window **410**, in other embodiments there may be two or more display windows. In addition, while embodiment **400** illustrates movement **414** in a particular direction, in other embodiments movement of the displayed objects may be in response to movement **414** in one or more other directions, or in response to a scalar (i.e., a determined or detected movement independent of the direction).

[0075] FIGS. **5A-5C** illustrate the scrolling of a list of items on a device to a terminus of the list, at which point one or more displayed items at the end of the list smoothly bounce off the end of the display, reverse direction, and then optionally come to a stop. FIG. **5A** is a schematic diagram illustrating an embodiment of user interface of a portable electronic device **400** having a touch-sensitive display. One or more displayed objects, such as information object **412-1** may be a distance **512-1** from a terminus **514** of the list of items which is an edge of a scrolled region and may be moving with a velocity **510-1** while the list is being scrolled. Note that the terminus **514** is a virtual boundary associated with the displayed objects, as opposed to a physical boundary associated with the window

410 and/or the display 408. As illustrated in FIG. 5B, when the one or more displayed objects, such as the information object 412-1, reach or intersect with the terminus 514, the movement corresponding to the scrolling may stop, i.e., the scrolling velocity may be zero at an instant in time. As illustrated in FIG. 5C, the one or more displayed objects, such as the information 412-1, may subsequently reverse direction. At a time after the intersection with the terminus 514, the information object 412-1 may have velocity 510-2 and may be a distance 512-2 from the terminus 514. In some embodiments, the magnitude of velocity 510-2 may be less than the magnitude of velocity 510-1 when the distance 512-2 equals the distance 512-1, i.e., the motion of the one or more displayed objects is damped after the scrolling list reaches and "bounces" at its terminus.

[0076] In at least some embodiments of the present disclosure, the method 200 performs the bounce operations described in FIGS. 5A-5C. The bounce call transferred at block 202 determines whether a bounce operation is enabled. The maximum and minimum bounces values determine the amount of bouncing of the scrolled region in an opposite direction of the scroll.

[0077] FIGS. 6A-6D illustrate the scrolling of a list of items to a terminus of the list, at which point an area beyond the terminus is displayed and the list is then scrolled in an opposite direction until the area beyond the terminus is no longer displayed, in accordance with some embodiments. The rubberband operation of method 300 is illustrated in the example of FIGS. 6A-6D with the listed items being email messages. FIGS. 6A-6D illustrate an exemplary user interface 3500A for managing an inbox in accordance with some embodiments. An analogous user interface may be used to display and manage other mailboxes (e.g., drafts, sent, trash, personal, etc.). In addition, other types of lists are possible, including but not limited to lists of instant message conversations, favorite phone numbers, contact information, labels, email folders, email addresses, physical addresses, ringtones, or album names.

[0078] If the list of emails fills more than the allotted screen area, the user may scroll through the emails using vertically upward and/or vertically downward swipe gestures on the touch screen. In the example of FIG. 6A, a portion of a list of emails is displayed in the screen area, including a top displayed email 3530 from Bruce Walker and a bottom displayed email 3532 from Kim Brook. A user performs a vertically downward swipe gesture 3514 to scroll toward the top of the list. The vertically downward gesture 3514 need not be exactly vertical; a substantially vertical gesture is sufficient. In some embodiments, a gesture within a predetermined angle of being perfectly vertical results in vertical scrolling.

[0079] As a result of detecting the vertically downward gesture 3514, in FIG. 6B the displayed emails have shifted down, such that the previous bottom displayed email 3532 from Kim Brook is no longer displayed, the previous top displayed email 3530 from Bruce Walker is now second from the top, and the email 3534 from Aaron Jones, which was not displayed in FIG. 6A, is now displayed at the top of the list.

[0080] In this example, the email 3534 from Aaron Jones is the first email in the list and thus is the terminus of the list. Upon reaching this email 3534, in response to continued detection of the vertically downward gesture 3514, an area 3536 (FIG. 6C) above the first email 3534 (i.e., beyond the terminus of the list) is displayed. In some embodiments, the area displayed beyond the terminus of the list is visually indistinct from the background of the list. In FIG. 6C, both the area 3536 and the background of the emails (e.g., emails 3534 and 3530) are white and thus are visually indistinct.

[0081] Once vertically downward gesture 3514 is complete, such that a corresponding object is no longer detected on or near the touch screen display, the list is scrolled in an opposite direction until the area 3536 is no longer displayed. FIG. 6D illustrates the result of this scrolling in the opposite direction, the email 3534 from Aaron Jones is now displayed at the top of the screen area allotted to the list and the area 3536 is not displayed.

[0082] In the example of FIGS. 6A-6D, a vertically downward gesture resulted in display of an area beyond the first item in the list. As described in FIG. 3, the values for the predetermined maximum displacement (e.g., display of an area beyond the first item in the list) are set at block 304 for top and bottom edges or at block 306 for all edges of the window.

[0083] Similarly, a vertically upward gesture may result in display of an area beyond the last item of the list, if the vertically upward gesture continues once the list has been scrolled to the last item. The last item may be considered a terminus of the list, similar to the first item. As discussed above, the gesture need not be exactly vertical to result in vertical scrolling; a gesture within a predefined range of angles from perfectly vertical is sufficient.

[0084] FIG. 7 illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a directional scrolling operation. The method 700 for operating through an application programming interface (API) includes transferring a directional scroll angle call to determine if directional scrolling is enabled at block 702. The method 700 further includes transferring a directional scroll angle call to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction at block 704. The method 700 further includes locking the scrolling in the horizontal direction if a user input forms an angle with a horizontal direction that is less than or equal to a first scroll angle at block 706. The method 700 further includes locking the scrolling in the vertical direction if a user input forms an angle with the vertical direction that is less than or equal to a second scroll angle at block 708.

[0085] In certain embodiments, a user input in the form of a drag forms an angle with the horizontal direction that is less than the first scroll angle. In this case, the user presumably intends to scroll in the horizontal direction. The scrolling will be locked in the horizontal direction until the user input exceeds the first scroll angle. A second scroll angle may be used for locking the user input in the vertical direction. The second scroll angle may be set equal to the first scroll angle.

[0086] FIG. 8 illustrates first and second scroll angles for locking a scroll of a display of a device in a horizontal or vertical direction. The horizontal direction 802 and vertical direction 804 are in reference to a window or a display of a device. As discussed in the method 700, a user input such as a drag movement forming an angle with the horizontal direction 802 less than or equal to the first scrolling angle 806 or 808 will lock the user input in the horizontal direction. In a similar manner, a user input forming an angle with the vertical direction 810 less than or equal to the second scrolling angle 810 or 812 will lock the user input in the vertical direction.

The first and second scrolling angles may be set at the same angle or at different angles as well. For example, the first and second scrolling angles may be set at 25 degrees. A user input less than or equal to 25 degrees with respect to the horizontal or vertical direction will lock the scrolling in the appropriate direction.

[0087] In some embodiments, the horizontal and vertical locking angles can be determined in part by the aspect of the content. For example, content in the form of a tall page may receive a larger vertical locking angle compared to the horizontal locking angle.

[0088] FIG. **9** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a deceleration scroll operation. The method **900** for providing the deceleration scroll operation includes transferring a deceleration scroll call to set a deceleration factor for a drag user input at block **902**. The method **900** further includes slowing the scroll to a stop based on the speed of the drag user input and the deceleration factor at block **904**.

[0089] In certain embodiments, a user input in the form of a drag invokes a scroll operation for a certain time period. The user input has a certain speed. The scroll of the scrolled region of a window or a display region of a display of a device will be stopped after the user input stops by applying a deceleration factor to the speed of the user input during the drag movement.

[0090] FIG. **10** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a scroll hysteresis operation. The method **1000** for providing the scroll hysteresis operation includes transferring a scroll hysteresis call to determine whether a user input invokes a scroll at block **1002**. The method **1000** further includes setting a hysteresis value for determining whether a user input invokes a scroll at block **1004**.

[0091] In certain embodiments, a user input in the form of a drag over a certain distance across a display or window within a display of a device invokes a scroll operation. The hysteresis value determines the certain distance which the user input must drag across the display or window prior to invoking a scroll operation. A user input that does not drag the certain predetermined distance will not invoke a scroll operation and may be considered a mouse up or down input or other type of input.

[0092] FIG. **11** illustrates details of all application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to attach a scroll indicator to a scroll region edge or a window edge of a device. In some embodiments, the scroll region edge is associated with a content edge. The window or display edge may be associated with the edge of a display region. The method **1100** for providing the scroll indicator includes transferring a scroll indicator call to determine whether at least one scroll indicator attaches to an edge of a scroll region or a window edge at block **1102**. A scroll indicator may be displayed on any display edge, window edge or scroll region edge. The method **1100** further includes optionally attaching at least one scroll indicator to the edge of the scroll region based on the scroll indicator call at block **1104**. Alternatively, the method **1100** further includes optionally attaching at least one scroll indicator to the window edge of the view based on the scroll indicator call at block **1106**.

[0093] In some embodiments, the operations of method **1100** can be altered, modified, combined, or deleted. For example, block **1104** can be deleted. Likewise, block **1106** can be deleted from the method **1100**. Alternatively, the order of block **1104** and block **1106** can be switched. Other methods having various operations that have been disclosed within the present disclosure can also be altered, modified, rearranged, collapsed, combined, or deleted.

[0094] In certain embodiments of the present disclosure, transferring the scroll indicator call is either one of issuing, initiating, invoking or receiving the scroll indicator call. For example, the user interface software (e.g., software kit or library) may receive the scroll indicator call from the software application.

[0095] FIG. **12** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to determine if an inadvertent user input contacts a view of a display of a device. The method **1200** includes transferring an inadvertent user input call to determine whether the user input was inadvertent at block **1202**. The method **1200** further includes ignoring the inadvertent user input based on the determination of the inadvertent user input call at block **1204**. In one embodiment, the inadvertent user input call comprises a thumb detection call to determine whether the user input was an inadvertent thumb.

[0096] In certain embodiments of the present disclosure, transferring the inadvertent user input call is either one of issuing, initiating, invoking or receiving the inadvertent user input call.

[0097] A gesture API provides an interface between an application and user software in order to handle gesturing. Gesturing may include scaling, rotating, or other changes to a view, window, or display. A mask may merely permit certain changes while limiting or not permitting other changes. Events of all kinds come into the application via a graphics framework. They are enqueued, collaleced if necessary and dispatched. If the events are system level events (e.g., application should suspend, device orientation has chanted, etc) they are routed to the application having an instance of a class of the user interface software. If the events are hand events based on a user input, the events are routed to the window they occurred over. The window then routes these events to the appropriate control by calling the instance's mouse and gesture methods. The control that receives a mouse down or mouse entered function will continue to get all future calls until the hand is lifted. If a second finger is detected, the gesture methods or functions are invoked. These functions may include start, change, and end gesture calls. The control that receives start gesture call will be sent all future change gesture calls until the gesture ends.

[0098] FIG. **13** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a gesture operation. The method **1300** for providing

the gesture operation includes transferring a handle gesture event call at block **1302**. The method **1300** further includes transferring a gesture change call in response to the handle gesture event call at block **1304**.

[0099] In certain embodiments, a user input in the form of two or more points is received by a display of a device. A multi-touch driver of the device receives the user input and packages the event into an event object. A window server receives the event object and determines whether the event object is a gesture event object. If the window server determines that a gesture event object has been received, then user interface software issues or transfers the handle gesture call at block **1302** to a software application associated with the view. The software application confirms that a gesture event has been received and passes the handle gesture call to a library of the user interface software. The window server also associates the gesture event object with the view that received the user input. The library responds by transferring a gesture change call in response to the handle gesture event call at block **1304**.

[0100] In one embodiment, a window or view associated with the user input receives the change call in order to perform the gesture event. The user software that provides the view receives a gesture start event call, a gesture changed event call, a zoom to scale setting for the view, and a gesture end call. The gesture calls receive an input of a gesture event which may be base event having a type such as a hand event, keyboard event, system event, etc. A delegate associated with the application receives a start gesture call, gesture did change call, and gesture did finish call. The user software is dynamically linking into the application during the run time of the gesture process.

[0101] In some embodiments, the gesture changed function call contains the following information about the gesture:
the number of fingers currently down;
the number of fingers initially down;
the rotation of the hand;
the scale of the hand;
the translation of the hand;
the position of the inner and outermost fingers; and
the pressure of the first finger.
In other embodiments, more information about each finger down may be included as follows.
the stage of the finger Oust touch down, fully pressed, lifting off, etc);
the position of the finger;
the proximity of the finger (how hard you're touching);
the orientation of the finger (what angle the ovoid is at);
the length of the major and minor axis,
the velocity of the finger; and
the eccentricity of the finger's ovoid.

[0102] A gesture event object may be a chord event object having a chord count (e.g., number of fingers contacted the view or display), a chord start event, a chord change event, and a chord end event. A chord change event may include a scaling or rotation transform.

[0103] FIG. **14** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a scaling transform of a display region, window, or view of a display of a device. The method **1400** for providing the scaling transform includes transferring a scaling transform call to determine a scaling transform for a view associated with a user input having a plurality of input points at block **1402**. The method **1400** further includes transferring a scaling gesture start call at block **1404**. The method **1400** further includes transferring a scaling gesture progress call at block **1406**. The method **1200** further includes transferring a scaling gesture end call at block **1408**.

[0104] In certain embodiments, a user input in the form of two or more input points (e.g., fingers) moves together or apart to invoke a gesture event that performs a scaling transform on the view associated with the user input. A scale transform includes a minimum and maximum scale factor. FIG. **15** illustrates a display **1502** of a device having a scaling transform of a view. The view **1504** (e.g., web, text, or image content) has a first scale factor. A user input (e.g., two fingers moving apart) associated with the view **1504** is interpreted as a gesture event to zoom out from view **1504** to view **1508** having a second scale factor that exceeds the maximum scale factor of the view **1516**. A snapback flag determines whether the zoom out can proceed past the maximum scale factor to view **1508** prior to snapping back to the maximum scale factor associated with view **1516**.

[0105] FIG. **16**A illustrates a display **1604** of a device having a first scaling factor of a view **1616**. A user input (e.g., two fingers **1608** and **1610** moving together) associated with the view **1614** is interpreted as a gesture event to zoom in from view **1614** to view **1664** having a second scale factor as illustrated in FIG. **16**B. The dashed regions **1602** and **1650** represent the total area of the content with the only content being displayed in the display area **1604** and **1652**. In performing the scaling transform from FIG. **16**A to FIG. **16**B, the center of the gesture event, center **1612** for FIG. **16**A and center **1660** for FIG. **16**B, remains in the same position with respect to the display **1604**. The scroll indicator **1606** shrinks to become scroll indicator **1654** during the transform to indicate that a smaller portion of the total content **1650** is being displayed on display **1604** as a result of the zoom in operation. The dashed region **1650** is larger than the dashed region **1602** to represent that a larger portion of content is not being displayed on display **1652** in FIG. **16**B as a result of the zoom in operation.

[0106] In at least some embodiments of the present disclosure, a user desires to change a view **1670** from a scale factor of 2× to a scale factor of 1× as illustrated in FIG. **16**C. A first set of user inputs **1672** and **1674** that move to the second set of user inputs **1676** and **1678** will decrease the scale factor from 2× to 1×. It may be desirable for the user to scale from 2× to 1× without having to move the user inputs a large distance across the view **1670**. In an environment with user interface software interacting with a software application, a gesture scaling transform flag may be set in order to determine a scaling transform for a view associated with a user input having a plurality of input points. The scaling transform flag scales either from a current scale factor to a minimum scale factor or from the current scale factor to a maximum scale factor. For example, a flag may be set at the position associated with a 1.5× scale factor and a third set of user inputs **1680** and **1682**. A user desiring to change the scale factor from 2× to 1× would only have to move his fingers, the user inputs, from the first set **1672** and **1674** to the third set **1680** and **1682** if the gesture scaling transform flag has been set at a scale factor of 1.5×.

[0107] FIG. **17** illustrates details of an application programming interface in flow chart form according to certain

teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to provide a rotation transform of a view, window, or display region of a display of a device. The method **1700** for providing the rotation transform includes transferring a rotation transform call to determine a rotation transform for a view associated with a user input having a plurality of input points at block **1702**. The method **1700** further includes transferring a rotation gesture start call at block **1704**. The method **1700** further includes transferring a scaling gesture progress call at block **1706**. The method **1700** further includes transferring a scaling gesture end call at block **1708**.

[0108] In certain embodiments, a user input in the form of two or more input points rotates to invoke a gesture event that performs a rotation transform on the view associated with the user input. The rotation transform includes a minimum and maximum degree of rotation for associated minimum and maximum rotation views. The user input may temporarily rotate a view past a maximum degree of rotation prior to the view snapping back to the maximum degree of rotation.

[0109] FIG. **18** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application in order to notify a delegate of at least one animation associated with a display region, window, or view of a display of a device. A delay in the animation may be specified by the API. Also, multiple animations may be assigned priority by the API. The method **1800** for notifying the delegate includes determining whether any animation occurs at block **1802**. The method **1800** further includes checking the progress of an animation at block **1804**. If progress has occurred, then the next state (e.g., position, opacity, or transform) of the animation can be calculated at block **1806**. If progress has completed at block **1806**, then at block **1808** it is determined whether the view associated with the completed animation is associated with a delegate. If so, a delegate call is transferred to notify the delegate of the animation for the view at block **1810**. The delegate operating under the control of the software application can change other views in response to the view being modified by the animation.

[0110] In certain embodiments, software invokes an animation that performs a scaling transform on the view associated with the user input. A display may include numerous views. The view being increased in size by the scaling transform may obstruct other views in which case the other views may need to be reduced in size. Alternatively, the view being decreased in size by the scaling transform may create additional area for other views to increase in size.

[0111] FIG. **19** is flow chart of a method for animating a display region, windows, or views displayed on a display of a device. The method **1900** includes starting at least two animations at block **1902**. The method **1900** further includes determining the progress of each animation at block **1904**. The method **1900** further includes completing each animation based on a single timer at block **1906**.

[0112] In certain embodiments of the present disclosure, the single timer includes a timer based on a redraw interval which is a time period between the display of a current frame and a next frame of the display of the device. In this case, changes in animation are updated to the display during the redraw interval in order to display the chances during the next frame of the display. The progress of each animation may be calculated periodically or based upon a progress call.

[0113] The method **1900** may further include determining whether each animation is associated with a delegate. The delegate is then notified of the animation. Other views not associated with an animation may be changed depending on the software application controlling the delegate.

[0114] FIG. **20** is flow chart of a method for animating a display region, windows, or views displayed on a display of a device. The method **2000** includes providing a single animation timer at block **2002**. The method **2000** further includes animating a plurality of animations with the single animation timer at block **2004**. For example, a single timer may control all animations which occur simultaneously. The animations may include a transform, a frame, and an opacity animation. A animation transform may include a scaling or rotation transform. A frame animation may include resizing of a frame. An opacity animation changes the opacity from opaque to transparent or vice versa.

[0115] FIG. **21** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with multiple software applications or processes in order to synchronize animations associated with multiple views or windows of a display of a device. The method **2100** for synchronizing the animations includes setting attributes of views independently with each view being associated with a process at block **2102**. For example, an attribute or property of a view may include a position, size, opacity, etc. An animation alters one or more attributes from a first state to a second state. The method **2100** further includes transferring a synchronization call to synchronize animations for the multiple views of the display at block **2104**. The synchronization call may include input parameters or arguments such as an identification of the synchronization of the processes and a list of the processes that are requesting animation of the multiple views. In one embodiment, the synchronization call includes the identification and the number of processes that are requesting animation. In one embodiment, each application or process sends a synchronization call at different times. The method **2100** further includes transferring a synchronization confirmation message when a synchronization flag is enabled at block **2106**. The synchronization flag can be enabled when the processes to be synchronized have each sent messages to a window server operating the user interface software. The method **2100** further includes updating the attributes of the views from a first state to a second state independently at block **2108**. In one embodiment, the window server receives the updated attributes from each process at different times. The method **2100** further includes transferring a start animation call to draw the requested animations when both processes have updated attributes associated with the second state at block **2110**.

[0116] In some embodiments, a first data structure or layer tree represents a hierarchy of layers that correspond to the views or windows of the processes. A second data structure or render tree represents a similar copy of the layer tree. However, the render tree is not updated until the independent processes have completed their separate animations. At this time, the render tree updates and redraws the screen with the new animations.

[0117] FIGS. **22**A and **22**B illustrate synchronizing the resizing of views or windows of a display of a device. For example, a window **2210** associated with a first process with a size attribute may increase in size by changing from a first state, window **2210** in FIG. **22**A, to a second state window **2210** in FIG. **22**B. At approximately the same time, a second window **2220** may decrease in size in proportion to the increase in size of the first window **2210**. The method **2100** provides synchronization of the resizing of the windows **2210** and **2220** illustrated in FIGS. **22**A and **22**B. The animations in changing from the first state to the second state may occur incrementally and occur with the synchronization of method **2100**.

[0118] FIG. **23** illustrates a method for switching ownership of a view of an application displayed on a display of a data processing device. The method **2300** includes constructing a data structure having a hierarchy of layers with a layer being associated with a view and owning the view at block **2302**. The layers may be content, windows, video, images, text, media, or any other type of object for user interface of the application. The method **2300** further includes removing the layer from the data structure at block **2304**. The method **2300** further includes switching ownership of the view from the layer to the view at block **2306**.

[0119] In some embodiments, each layer from the data structure is associated with a view. The layer associated with the view sends a delegate function call to the view in order to generate content provided by the view. A first pointer reference points from the layer to the view. A second pointer reference points from the view to the layer. The number of references pointing to an object such as the view is defined as the retained count of the object. The view may receive notification that the layer will be removed from the data structure. Removing the layer from the data structure may occur based on the view associated with the layer being removed from the display of the device. When the layer is removed from the data structure or layer tree the pointer from the layer to the view will be removed. The view will have a retained count of zero and be deallocated or removed from memory if the ownership of the view is not reversed. The view will have a retained count of at least one if ownership is reversed.

[0120] FIG. **24** illustrates a method for memory management of a view of an application displayed on a display of a device. The method **2400** includes constructing a data structure having a hierarchy of layers with at least one layer being associated with the view at block **2402**. The method **2400** further includes storing the data structure in memory at block **2404**. The method **2400** further includes maintaining a retained count of the number of references to the view from other objects at block **2406**. The method **2400** further includes deallocating the view from memory if the retained count is zero at block **2408**. As discussed above, the retained count of the view will be decremented if the layer is removed from the data structure. Removing the layer from the data structure may occur based on the view associated with the layer being removed from the display of the device.

[0121] FIGS. **25**A and **25**B illustrate a data structure having a hierarchy of layers with a layer being associated with a view. The data structure includes layers **2502**, **2504**, and **2506**. Layer **2506** is associated with the view **2510**. The layer **2506** associated with the **2510** view sends a delegate call to the view in order to generate content provided by the view. A first pointer reference **2508** points from the layer **2506** to the view **2510**. A second pointer reference **2512** points from the view **2510** to the layer **2506**. A third pointer reference **2532** may point from user interface (UI) controller **2530** to the view **2510**. The UI controller **2530** may control operations associated with the view **2510** such as scrolling the view **2510** in response to a user input. The view **2510** in FIG. **25**A has a retained count of two based on the pointer references **2508** and **2532**.

[0122] If the layer **2506** is removed from the data structure as illustrated in FIG. **25**B, then the pointer **2508** is removed. View **2510** will have a lower retained count as illustrated in FIG. **25**B. If view **2510** has a retained count of zero, then the memory storing the view **2510** will be deallocated.

[0123] FIG. **26** illustrates a method for compositing media and non-media content of user interface for display on a device. The method **2600** includes constructing a data structure having a hierarchy of layers associated with the user interface of the device at block **2602**. The method **2600** further includes determining whether each layer of the data structure is associated with media or non-media content at block **2604**. The data structure or layer tree is traversed in order to determine whether each of the layers of the data structure is associated with media or non-media content. The method **2600** further includes detaching a layer associated with media content from the data structure at block **2606**. The method **2600** further includes storing media content in a first memory location at block **2606**. The method **2600** further includes storing non-media content in a second memory location at block **2608**. The method **2600** further includes compositing the media and non-media content for display on the device at block **2610**.

[0124] In some embodiments, compositing the media and non-media content includes retrieving the media content from the first memory location, retrieving the non-media content from the second memory location, and scanning the media and non-media content directly to the display. The memory location can be any type of memory located in cache, main memory, a graphics processing unit, or other location within a device. The media content may include video, video plug-in, audio, image, or other time varying media. The media content may be in the form of a YUV model with the Y representing a luminance component (the brightness) and U and V representing chrominance (color) components. The media content may be scanned to the display at a rate of substantially twenty to forty frames per second. The media content may be scaled prior to being scanned to the display of the device.

[0125] The non-media content may include content, views, and images that do not require frequent updating. The non-media content may be in the form of a RGB model which is an additive model in which red, green, and blue (often used in additive light models) are combined in various ways to reproduce other colors. The non-media content may be scanned to the display at a slower rate compared to the media content.

[0126] FIG. **27** illustrates a data structure or layer tree having a hierarchy of layers. The layers can be associated with media and non-media content. For example, layer **2704** is associated with media content **2706** such as a video. Layer **2710** is associated with non-media content **2712** which may be user interface view for the video. Layers **2720**, **2730**, and **2740** are associated with non-media content **2722**, **2732**, and **2742**, respectively, that forms the components of the non-media content **2712**. The method **2600** will determine whether each layer of the data structure is associated with media or non-content. Any layers associated with media con-

tent such as layer **2704** will be removed from the data structure and processed in a separate memory location.

[0127] In some embodiments, the methods, systems, and apparatuses of the present disclosure can be implemented in various devices including electronic devices, consumer devices, data processing devices, desktop computers, portable computers, wireless devices, cellular devices, tablet devices, handheld devices, multi touch devices, multi touch data processing devices, any combination of these devices, or other like devices. FIGS. **4-6** and **28-33** illustrate examples of a few of these devices.

[0128] FIG. **28** illustrates a device **2800** according to one embodiment of the disclosure. FIG. **28** shows a wireless device in a telephone configuration having a "candy-bar" style. In FIG. **28**, the wireless device **2800** may include a housing **2832**, a display device **2834**, an input device **2836** which may be an alphanumeric keypad, a speaker **2838**, a microphone **2840** and an antenna **2842**. The wireless device **2800** also may include a proximity sensor **2844** and an accelerometer **2846**. It will be appreciated that the embodiment of FIG. **28** may use more or fewer sensors and may have a different form factor from the form factor shown in FIG. **28**.

[0129] The display device **2834** is shown positioned at an upper portion of the housing **2832**, and the input device **2836** is shown positioned at a lower portion of the housing **2832**. The antenna **2842** is shown extending from the housing **2832** at an upper portion of the housing **2832**. The speaker **2838** is also shown at an upper portion of the housing **2832** above the display device **2834**. The microphone **2840** is shown at a lower portion of the housing **2832**, below the input device **3286**. It will be appreciated that the speaker **2838** and microphone **2840** can be positioned at any location on the housing, but are typically positioned in accordance with a user's ear and mouth, respectively.

[0130] The display device **2834** may be, for example, a liquid crystal display (LCD) which does not include the ability to accept inputs or a touch input screen which also includes an LCD. The input device **2836** may include, for example, buttons, switches, dials, sliders, keys or keypad, navigation pad, touch pad, touch screen, and the like. Any well-known speaker, microphone and antenna can be used for speaker **2838**, microphone **2840** and antenna **2842**, respectively.

[0131] The data acquired from the proximity sensor **2844** and the accelerometer **2846** can be combined together, or used alone, to gather information about the user's activities. The data from the proximity sensor **2844**, the accelerometer **2846** or both can be used, for example, to activate/deactivate a display backlight, initiate commands, make selections, control scrolling, gesturing, animating or other movement in a display, control input device settings, or to make other changes to one or more settings of the device. In certain embodiments of the present disclosure, the device **2800** can be used to implement at least some of the methods discussed in the present disclosure.

[0132] FIG. **29** shows a device **2950** in accordance with one embodiment of the disclosure. The device **2950** may include a housing **2952**, a display/input device **2954**, a speaker **2956**, a microphone **2958** and an optional antenna **2960** (which may be visible on the exterior of the housing or may be concealed within the housing). The device **2950** also may include a proximity sensor **2962** and an accelerometer **2964**. The device **2950** may be a cellular telephone or a device which is an integrated PDA and a cellular telephone or a device which is an integrated media player and a cellular telephone or a device which is both an entertainment system (e.g. for playing games) and a cellular telephone, or the device **2950** may be other types of devices described herein. In one particular embodiment, the device **2950** may include a cellular telephone and a media player and a PDA, all contained within the housing **2952**. The device **2950** may have a form factor which is small enough that it fits within the hand of a normal adult and is light enough that it can be carried in one hand by an adult. It will be appreciated that the term "portable" means the device can be easily held in an adult user's hands (one or both); for example, a laptop computer and an iPod are portable devices.

[0133] In one embodiment, the display/input device **2954** may include a multi-point touch input screen in addition to being a display, such as an LCD. In one embodiment, the multi-point touch screen is a capacitive sensing medium configured to detect multiple touches (e.g., blobs on the display from a user's face or multiple fingers concurrently touching or nearly touching the display) or near touches (e.g., blobs on the display) that occur at the same time and at distinct locations in the plane of the touch panel and to produce distinct signals representative of the location of the touches on the plane of the touch panel for each of the multiple touches.

[0134] In certain embodiments of the present disclosure, the device **2800** can be used to implement at least some of the methods discussed in the present disclosure.

[0135] FIGS. **30**A and **30**B illustrate a device **3070** according to one embodiment of the disclosure. The device **3070** may be a cellular telephone which includes a hinge **3087** that couples a display housing **3089** to a keypad housing **3091**. The hinge **3087** allows a user to open and close the cellular telephone so that it can be placed in at least one of two different configurations shown in FIGS. **30**A and **30**B. In one particular embodiment, the hinge **3087** may rotatably couple the display housing to the keypad housing. In particular, a user can open the cellular telephone to place it in the open configuration shown in FIG. **30**A and can close the cellular telephone to place it in the closed configuration shown in FIG. **30**B. The keypad housing **3091** may include a keypad **3095** which receives inputs (e.g. telephone number inputs or other alphanumeric inputs) from a user and a microphone **3097** which receives voice input from the user. The display housing **3089** may include, on its interior surface, a display **3093** (e.g. an LCD) and a speaker **3098** and a proximity sensor **3084**; on its exterior surface, the display housing **3089** may include a speaker **3096**, a temperature sensor **3094**, a display **3088** (e.g. another LCD), an ambient light sensor **3092**, and a proximity sensor **3084**A. Hence, in this embodiment, the display housing **3089** may include a first proximity sensor on its interior surface and a second proximity sensor on its exterior surface.

[0136] In at least certain embodiments, the device **3070** may contain components which provide one or more of the functions of a wireless communication device such as a cellular telephone, a media player, an entertainment system, a PDA, or other types of devices described herein. In one implementation of an embodiment, the device **3070** may be a cellular telephone integrated with a media player which plays MP3 files, such as MP3 music files.

[0137] Each of the devices shown in FIGS. **4**, **5**A, **5**B, **5**C, **6**A, **6**B, **6**C, **6**D, **28**, **29**, **30**A and **30**B may be a wireless communication device, such as a cellular telephone, and may include a plurality of components which provide a capability for wireless communication. FIG. **31** shows an embodiment of a wireless device **3070** which includes the capability for

wireless communication. The wireless device **3070** may be included in any one of the devices shown in FIGS. **4**, **5**A, **5**B, **5**C, **6**A, **6**B, **6**C, **6**D, **28**, **29**, **30**A and **30**B, although alternative embodiments of those devices of FIGS. **4**, **5**A, **5**B, **5**C, **6**A, **6**B, **6**C, **6**D, **28**, **29**, **30**A and **308** may include more or fewer components than the Wireless device **3070**. Wireless device **3070** may include an antenna system **3101**. Wireless device **3070** may also include a digital and/or analog radio frequency (RF) transceiver **3102**, coupled to the antenna system **3101**, to transmit and/or receive voice, digital data and/or media signals through antenna system **3101**.

[0138] Wireless device **3070** may also include a digital processing system **3103** to control the digital RF transceiver and to manage the voice, digital data and/or media signals. Digital processing system **3103** may be a general purpose processing device, such as a microprocessor or controller for example. Digital processing system **3103** may also be a special purpose processing device, such as an ASIC (application specific integrated circuit), FPGA (field-programmable gate array) or DSP (digital signal processor). Digital processing system **3103** may also include other devices, as are known in the art, to interface with other components of wireless device **3070**. For example, digital processing system **3103** may include analog-to-digital and digital-to-analog converters to interface with other components of wireless device **3070**. Digital processing system **3103** may include a media processing system **3109**, which may also include a general purpose or special purpose processing device to manage media, such as files of audio data.

[0139] Wireless device **3070** may also include a storage device **3104**, coupled to the digital processing system, to store data and/or operating programs for the Wireless device **3070**. Storage device **3104** may be, for example, any type of solid-state or magnetic memory device.

[0140] Wireless device **3070** may also include one or more input devices **3105**, coupled to the digital processing system **3103**, to accept user inputs (e.g., telephone numbers, names, addresses, media selections, etc.) Input device **3105** may be, for example, one or more of a keypad, a touchpad, a touch screen, a pointing device in combination with a display device or similar input device.

[0141] Wireless device **3070** may also include at least one display device **33106**, coupled to the digital processing system **3103**, to display information such as messages, telephone call information, contact information, pictures, movies and/or titles or other indicators of media being selected via the input device **3105**. Display device **3106** may be, for example, an LCD display device. In one embodiment, display device **3106** and input device **3105** may be integrated together in the same device (e.g., a touch screen LCD such as a multi-touch input panel which is integrated with a display device, such as an LCD display device). The display device **3106** may include a backlight **3106**A to illuminate the display device **3106** under certain circumstances. It will be appreciated that the Wireless device **3070** may include multiple displays.

[0142] Wireless device **3070** may also include a battery **3107** to supply operating power to components of the system including digital RF transceiver **3102**, digital processing system **3103**, storage device **3104**, input device **3105**, microphone **310**A, audio transducer **3108**, media processing system **3109**, sensor(s) **3110**, and display device **3106**. Battery **3107** may be, for example, a rechargeable or non-rechargeable lithium or nickel metal hydride battery. Wireless device **3070** may also include audio transducers **3108**, which may include one or more speakers, and at least one microphone **3105**A. In certain embodiments of the present disclosure, the wireless device **3070** can be used to implement at least some of the methods discussed in the present disclosure.

[0143] FIG. **32** shows another example of a device according to an embodiment of the disclosure. This device **3200** may include a processor, such as microprocessor **3202**, and a memory **3204**, which are coupled to each other through a bus **3206**. The device **3200** may optionally include a cache **3208** which is coupled to the microprocessor **3202**. This device may also optionally include a display controller and display device **3210** which is coupled to the other components through the bus **3206**. One or more input/output controllers **3212** are also coupled to the bus **3206** to provide an interface for input/output devices **3214** and to provide an interface for one or more sensors **3216** which are for sensing user activity. The bus **3206** may include one or more buses connected to each other through various bridges, controllers, and/or adapters as is well known in the art. The input/output devices **3214** may include a keypad or keyboard or a cursor control device such as a touch input panel. Furthermore, the input/output devices **3214** may include a network interface which is either for a wired network or a wireless network (e.g. an RF transceiver). The sensors **3216** may be any one of the sensors described herein including, for example, a proximity sensor or an ambient light sensor. In at least certain implementations of the device **3200**, the microprocessor **3202** may receive data from one or more sensors **3216** and may perform the analysis of that data in the manner described herein. For example, the data may be analyzed through an artificial intelligence process or in the other ways described herein. As a result of that analysis, the microprocessor **3202** may then automatically cause an adjustment in one or more settings of the device.

[0144] In certain embodiments of the present disclosure, the device **3200** can be used to implement at least some of the methods discussed in the present disclosure.

[0145] FIGS. **33**A-C show another example of a device according to at least certain embodiments of the disclosure. FIG. **33**A illustrates a laptop device **3300** with a keyboard **3302**, a body **3304**, a display frame **3306**, and a display **3308**. The laptop device **3300** can be converted into a tablet device as illustrated in FIG. **33**B and FIG. **33**C. FIG. **33**B illustrates the conversion of the laptop device into a tablet device. An edge of a display frame **3356** containing a display **3358** is slide within the body **3354** across the top of a keyboard **3352** until forming a tablet device as illustrated in FIG. **33**C. The tablet device with a display **2362** and a display frame **3366** rests on top of a body **3360**.

[0146] In certain embodiments of the present disclosure, the laptop device **3300** can be used to implement at least some of the methods discussed in the present disclosure.

[0147] FIG. **34** illustrates details of an application programming interface in flow chart form according to certain teachings of the present disclosure. The application programming interface operates in an environment with user interface software interacting with a software application. In some embodiments, a hierarchy of views operates on top of a hierarchy of layers within the user interface software. The API operates as illustrated in method **3400** that includes constructing a hierarchy of views operating on top of a hierarchy of layers at block **3402**. The method **3400** further includes providing access to the hierarchy of views without providing access to the hierarchy of layers at block **3404**. An application

may interact with the hierarchy of views via the API without accessing the hierarchy of layers operating below the hierarchy of views.

[0148] In some embodiments, a platform provides various scrolling, gesturing, and animating operations. The platform includes hardware components and an operating system. The hardware components may include a processing unit coupled to an input panel and a memory coupled to the processor. The operating system includes one or more programs that are stored in the memory and configured to be executed by the processing unit. One or more programs include various instructions for transferring function calls or messages through an application programming interface in order to perform various scrolling, gesturing, and animating operations.

[0149] In an embodiment, the one or more programs include instructions for transferring a bounce call through an API to cause a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll. In an embodiment, the one or more programs include instructions for transferring a rubberband call through an API to cause a rubberband effect on a scrolled region by a predetermined maximum displacement when the scrolled region exceeds a display edge based on a scroll. In an embodiment, the one or more programs include instructions for transferring a directional scroll call through an API to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

[0150] In an embodiment, the one or more programs include instructions for transferring a scroll hysteresis call through an API to determine whether a user input invokes a scroll. In an embodiment, the one or more programs include instructions for transferring a deceleration scroll call through an API to set a deceleration factor for a user input based on the user input invoking a scroll. In an embodiment, the one or more programs include instructions for transferring a scroll indicator call through an API to determine whether at least one scroll indicator attaches to a content edge or a display edge of a display region.

[0151] In some embodiments, the platform includes a framework containing a library of software code. The framework interacts with the programs of the platform to provide application programming interfaces for performing various scrolling, gesturing, and animating operations. The framework also includes associated resources (e.g., images, text, etc.) that are stored in a single directory.

[0152] In an embodiment, the library of the framework provides an API for specifying a bounce operation to cause a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll. In an embodiment, the library of the framework provides an API for specifying a rubberband operation that has a rubberband effect on a scrolled region by a predetermined maximum displacement when the scrolled region exceeds a display edge based on a scroll. In an embodiment, the library of the framework provides an API for specifying a directional scroll operation to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

[0153] In an embodiment, the library of the framework provides an API for specifying a scroll hysteresis operation to determine whether a user input invokes a scroll. In an embodiment, the library of the framework provides an API for specifying a deceleration scroll operation to set a deceleration factor for a user input based on the user input invoking a scroll. In an embodiment, the library of the framework provides an API for specifying a scroll indicator operation to determine whether at least one scroll indicator attaches to a content edge or a display edge of a display region.

[0154] In the foregoing specification, the disclosure has been described with reference to specific exemplary embodiments thereof. It will be evident that various modifications may be made thereto without departing from the broader spirit and scope of the disclosure as set forth in the following claims. The specification and drawings are, accordingly, to be regarded in an illustrative sense rather than a restrictive sense.

What is claimed is:

1. A machine implemented method for scrolling on a display of a device comprising:

receiving a user input;

creating an event object in response to the user input;

determining whether the event object invokes a scroll or gesture operation;

issuing at least one scroll or gesture call based on invoking the scroll or gesture operation;

responding to at least one scroll call, if issued, by scrolling a window having a view associated with the event object based on an amount of a scroll with the scroll stopped at a predetermined position in relation to the user input; and

responding to at least one gesture call, if issued, by scaling the view associated with the event object based on receiving a plurality of input points in the form of the user input.

2. The method as in claim **1**, further comprising:

rubberbanding a scrolling region displayed within the window by a predetermined maximum displacement when the scrolling region exceeds a window edge based on the scroll.

3. The method as in claim **1**, further comprising:

attaching scroll indicators to a content edge of the window.

4. The method as in claim **1**, further comprising:

attaching scroll indicators to the window edge.

5. The method as in claim **1**, wherein determining whether the event object invokes a scroll or gesture operation is based on receiving a drag user input for a certain time period.

6. The method as in claim **1**, further comprising:

responding to at least one gesture call, if issued, by rotating a view associated with the event object based on receiving a plurality of input points in the form of the user input.

7. The method as in claim **1**, wherein the device is one of a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

8. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

receiving a user input;

creating an event object in response to the user input;

determining whether the event object invokes a scroll or gesture operation;

issuing at least one scroll or gesture call based on invoking the scroll or gesture operation;

responding to at least one scroll call, if issued, by scrolling a window having a view associated with the event object

based on an amount of a scroll with the scroll stopped at a predetermined position in relation to the user input; and

responding to at least one gesture call, if issued, by scaling the view associated with the event object based on receiving a plurality of input points in the form of the user input.

9. The medium as in claim **8**, further comprising:

rubberbanding a scrolling region displayed within the window by a predetermined maximum displacement when the scrolled region exceeds a window edge based on the scroll.

10. The medium as in claim **8**, further comprising:

attaching scroll indicators to a content edge of the view.

11. The medium as in claim **8**, further comprising:

attaching scroll indicators to a window edge of the view.

12. The medium as in claim **8**, wherein determining whether the event object invokes a scroll or gesture operation is based on receiving a drag user input for a certain time period.

13. The medium as in claim **8**, further comprising:

responding to at least one gesture call, if issued, by rotating a view associated with the event object based on receiving a plurality of input points in the form of the user input.

14. The medium as in claim **8**, wherein the data processing system is one of: a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

15. In an environment with user interface software interacting with a software application, a method for operating through an application programming interface (API), comprising:

transferring a set bounce call.

16. The method as in claim **15**, further comprises:

setting at least one of maximum and minimum bounce values.

17. The method as in claim **15**, wherein transferring the set bounce call causes a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region of a device at the end of the scroll.

18. The method as in claim **15**, wherein transferring the set bounce call is either one of issuing, initiating, invoking or receiving the set bounce call.

19. The method as in claim **15**, wherein the device is one of: a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

20. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

transferring a set bounce call.

21. The medium as in claim **20**, further comprises:

setting at least one of maximum and minimum bounce values.

22. The medium as in claim **20**, wherein transferring the set bounce call causes a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region of a device at the end of the scroll.

23. The medium as in claim **20**, wherein transferring the set bounce call is either one of issuing, initiating, invoking or receiving the set bounce call.

24. The medium as in claim **20**, wherein the device is one of: a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

25. In an environment with user interface software interacting with a software application, an apparatus, comprising:

means for transferring a set bounce call.

26. In an environment with user interface software interacting with a software application, a method for operating through an application programming interface (API), comprising:

receiving a set bounce call.

27. The method as in claim **26**, further comprises:

setting at least one of maximum and minimum bounce values.

28. The method as in claim **26**, wherein receiving the set bounce call causes a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.

29. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

receiving a set bounce call.

30. The medium as in claim **29**, further comprises:

setting at least one of maximum and minimum bounce values.

31. The medium as in claim **29**, wherein receiving a set bounce call causes a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.

32. In an environment with user interface software interacting with a software application, an apparatus, comprising:

means for receiving a set bounce call.

33. In an environment with user interface kit interacting with a software application, a method for operating through an application programming interface (API), comprising:

transferring a rubberband call to cause rubberbanding a scrolled region displayed within a display region of a device.

34. The method as in claim **33**, wherein rubberbanding a scrolled region occurs by a predetermined maximum displacement when the scrolled region exceeds a display edge based on the scroll.

35. The method as in claim **33**, further comprising:

transferring an edge rubberband call to set displacement values for at least one display edge.

36. The method as in claim **33**, wherein at the end of the scroll, the scrolled region associated with content returns within the display region.

37. The method as in claim **33**, wherein transferring the rubberband call is either one of issuing, initiating, invoking or receiving the rubberband call.

38. The method as in claim **33**, wherein the device is one of a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

39. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

transferring a rubberband call to cause rubberbanding a scrolled region displayed within a display region of a device.

40. The medium as in claim **39**, wherein rubberbanding a scrolled region occurs by a predetermined maximum displacement when the scrolled region exceeds a window edge of the view based on the scroll.

41. The medium as in claim **39**, further comprising:

transferring an edge rubberband call to set displacement values for at least one display edge.

42. The medium as in claim **39**, wherein transferring the rubberband call is either one of issuing, initiating, invoking or receiving the rubberband call.

43. The method as in claim **39**, wherein the device is one of: a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

44. In an environment with user interface software interacting with a software application, an apparatus, comprising:

means for transferring a rubberband call to cause rubberbanding a scrolled region displayed within a view.

45. In an environment with user interface kit interacting with a software application, a method for operating through an application programming interface (API), comprising:

receiving a rubberband call to cause rubberbanding a scrolled region displayed within a view.

46. The method as in claim **45**, wherein rubberbanding a scrolled region occurs by a predetermined maximum displacement when the scrolled region exceeds a window edge of the view based on the scroll.

47. The method as in claim **45**, further comprising:

receiving an edge rubberband call to set displacement values for at least one display edge.

48. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

receiving a rubberband call to cause rubberbanding a scrolled region displayed within a view.

49. The medium as in claim **48**, wherein rubberbanding a scrolled region occurs by a predetermined maximum displacement when the scrolled region exceeds a window edge of the view based on the scroll.

50. The medium as in claim **48**, further comprising:

receiving an edge rubberband call to set displacement values for at least one display edge.

51. In an environment with user interface software interacting with a software application, an apparatus, comprising:

means for receiving a rubberband call to cause rubberbanding a scrolled region displayed within a view.

52. In an environment with user interface software interacting with a software application and a user input contacting a view of a display of a device, a method for operating through an application programming interface (API), comprising:

transferring a directional scroll call to determine if directional scrolling is enabled.

53. The method as in claim **52**, further comprising:

transferring a directional scroll angle call to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

54. The method of claim **52**, wherein a drag user input forming an angle with a horizontal direction that is less than or equal to a first scroll angle locks the scrolling in the horizontal direction.

55. The method of claim **52**, wherein a drag user input forming an angle with a vertical direction that is less than or equal to a second scroll angle locks the scrolling in the vertical direction.

56. The method as in claim **52**, wherein transferring the directional scroll angle call is either one of issuing, initiating, invoking or receiving the directional scroll angle call.

57. The method as in claim **52**, wherein the device is one of: a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

58. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

transferring a directional scroll call to determine if directional scrolling is enabled.

59. The medium as in claim **58**, further comprising:

transferring a directional scroll angle call to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

60. The medium of claim **58**, wherein a drag user input forming an angle with a horizontal direction that is less than or equal to a first scroll angle locks the scrolling in the horizontal direction.

61. The medium of claim **58**, wherein a drag user input forming an angle with a vertical direction that is less than or equal to a second scroll angle locks the scrolling in the vertical direction.

62. The medium as in claim **58**, wherein transferring the directional scroll angle call is either one of issuing, initiating, invoking or receiving the directional scroll angle call.

63. The method as in claim **58**, wherein the data processing system is one of: a data processing device, a portable device, a portable data processing device, a multi touch device, a multi touch portable device, a wireless device, and a cell phone.

64. In an environment with user interface software interacting with a software application an apparatus, comprising:

means for transferring a directional scroll call to determine if directional scrolling is enabled.

65. In an environment with user interface software interacting with a software application and a user input contacting a view of a display of a device, a method for operating through an application programming interface (API), comprising:

receiving a directional scroll call to determine if directional scrolling is enabled.

66. The method as in claim **65**, further comprising:

receiving a directional scroll angle call to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

67. The method of claim **65**, wherein a drag user input forming an angle with a horizontal direction that is less than or equal to a first scroll angle locks the scrolling in the horizontal direction.

68. The method of claim **65**, wherein a drag user input forming an angle with a vertical direction that is less than or equal to a second scroll angle locks the scrolling in the vertical direction.

69. A machine readable medium storing executable program instructions which when executed cause a data processing system to perform a method comprising:

receiving a directional scroll call to determine if directional scrolling is enabled.

70. The medium as in claim **69**, further comprising:

receiving a directional scroll angle call to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

71. The medium of claim **69**, wherein a drag user input forming an angle with a horizontal direction that is less than or equal to a first scroll angle locks the scrolling in the horizontal direction.

72. The medium of claim **69**, wherein a drag user input forming an angle with a vertical direction that is less than or equal to a second scroll angle locks the scrolling in the vertical direction.

73. In an environment with user interface software interacting with a software application, an apparatus, comprising:

means for receiving a directional scroll call to determine if directional scrolling is enabled.

74. A computer read medium containing executable instructions, comprising:

program code configured, when executed, to transfer a bounce call through an application programming interface to cause a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.

75. The medium as in claim **74**, wherein transferring the bounce call is either one of issuing, initiating, invoking or receiving the bounce call.

76. A computer read medium containing executable instructions, comprising:

program code configured, when executed, to transfer a rubberband call through an application programming interface to cause a rubberband effect on a scrolled region by a predetermined maximum displacement when the scrolled region exceeds a display edge based on a scroll.

77. The medium as in claim **76**, wherein transferring the rubberband call is either one of issuing, initiating, invoking or receiving the rubberband call.

78. A computer read medium containing executable instructions, comprising:

program code configured, when executed, to transfer a directional scroll call through an application programming interface to set a scroll angle for locking the scrolling in at least one of a vertical or horizontal direction.

79. The medium as in claim **78**, wherein transferring the directional scroll call is either one of issuing, initiating, invoking or receiving the directional scroll call.

80. A platform for performing scrolling operations, comprising:

a processing unit coupled to an input panel,

a memory coupled to the processor; and

one or more programs, wherein the one or more programs are stored in the memory and configured to be executed by the processing unit, the programs including:

instructions for transferring a bounce call through an application programming interface to cause a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.

81. The platform of claim **80**, wherein the one or more programs further comprise instructions for transferring a rubberband call through an application programming interface that has a rubberband effect on a scrolled region by a predetermined maximum displacement when the scrolled region exceeds a display edge based on a scroll.

82. The platform of claim **80**, wherein the one or more programs further comprise instructions for transferring a directional scroll call through an application programming interface to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

83. The platform as in claim **80**, wherein transferring the bounce call is either one of issuing, initiating, invoking or receiving the bounce call.

84. The platform as in claim **81**, wherein transferring the rubberband call is either one of issuing, initiating, invoking or receiving the rubberband call.

85. The platform as in claim **82**, wherein transferring the directional scroll call is either one of issuing, initiating, invoking or receiving the directional scroll call.

86. A framework for performing scrolling operations, comprising:

a directory for storing one or more programs and associated resources, wherein the programs contain instructions that when executed provide an application programming interface to specify a bounce operation to cause a bounce of a scrolled region in an opposite direction of a scroll based on a region past an edge of the scrolled region being visible in a display region at the end of the scroll.

87. The framework of claim **86**, wherein the one or more programs further comprise instructions that when executed provide an application programming interface to specify a rubberband operation that has a rubberband effect on a scrolled region by a predetermined maximum displacement when the scrolled region exceeds a display edge based on a scroll.

88. The framework of claim **86**, wherein the one or more programs further comprise instructions that when executed provide an application programming interface to specify a directional scroll operation to set a scroll angle for locking the scrolling in at least one of a vertical or a horizontal direction.

* * * * *