US008447598B2

(12) **United States Patent**
Chutorash et al.

(10) **Patent No.: US 8,447,598 B2**
(45) **Date of Patent: May 21, 2013**

(54) **VEHICLE USER INTERFACE SYSTEMS AND METHODS**

(75) Inventors: **Richard J. Chutorash**, Rochester Hills, MI (US); **Elisabet Anderson**, Holland, MI (US); **Rodger W. Eich**, Holland, MI (US); **Jeffrey Golden**, Holland, MI (US); **Philip J. Vanderwall**, Marne, MI (US); **Michael J. Sims**, Zeeland, MI (US)

(73) Assignee: **Johnson Controls Technology Company**, Holland, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/007,447**

(22) Filed: **Jan. 14, 2011**

(65) **Prior Publication Data**

US 2011/0257973 A1 Oct. 20, 2011

Related U.S. Application Data

(63) Continuation of application No. 12/794,490, filed on Jun. 4, 2010, now abandoned, which is a continuation of application No. PCT/US2008/085570, filed on Dec. 4, 2008.

(60) Provisional application No. 61/005,419, filed on Dec. 5, 2007.

(51) **Int. Cl.**
G10L 15/00 (2006.01)
H04B 1/38 (2006.01)

(52) **U.S. Cl.**
USPC **704/231**; 455/563

(58) **Field of Classification Search**
USPC 704/231–257; 455/563
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,390,877 A 6/1983 Curran
4,760,394 A 7/1988 Takeuchi et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 660 542 A1 6/1995
EP 1 052 609 B1 11/2000

(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/US2007/088171, dated Jun. 27, 2008, 9 pages.

(Continued)

Primary Examiner — Samuel G Neway
(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(57) **ABSTRACT**

A control system for mounting in a vehicle and for providing information to a portable electronic device for processing by the portable electronic device is shown and described. The control system includes a first interface for communicating with the portable electronic device and a memory device. The control system also includes a processing circuit communicably coupled to the first interface and the memory device, the processing circuit configured to extract information from the memory device and to provide the information to the first interface so that the first interface communicates the information to the portable electronic device. The processing circuit is further configured to determine the capabilities of the portable electronic device based on data received from the portable electronic device via the first interface and to determine whether or not to communicate the information to the portable electronic device based on the determined capabilities.

3 Claims, 19 Drawing Sheets



U.S. PATENT DOCUMENTS

4,792,796	A	12/1988	Bradshaw et al.	
4,825,200	A	4/1989	Evans et al.	
4,827,520	A	5/1989	Zeinstra	
5,113,182	A	5/1992	Suman et al.	
5,278,547	A	1/1994	Suman et al.	
5,475,366	A	12/1995	Van Lente et al.	
5,479,155	A	12/1995	Zeinstra et al.	
5,479,157	A	12/1995	Suman et al.	
5,583,485	A	12/1996	Van Lente et al.	
5,614,885	A	3/1997	Van Lente et al.	
5,614,891	A	3/1997	Zeinstra et al.	
5,619,190	A	4/1997	Duckworth et al.	
5,627,529	A	5/1997	Duckworth et al.	
5,646,701	A	7/1997	Duckworth et al.	
5,661,455	A	8/1997	Van Lente et al.	
5,691,848	A	11/1997	Van Lente et al.	
5,699,044	A	12/1997	Van Lente et al.	
5,708,415	A	1/1998	Van Lente et al.	
5,717,387	A	2/1998	Suman et al.	
5,854,593	A	12/1998	Dykema et al.	
5,903,226	A	5/1999	Suman et al.	
5,926,087	A	7/1999	Busch et al.	
6,010,403	A	1/2000	Adam et al.	
6,020,654	A	2/2000	Chutorash	
6,028,537	A	2/2000	Suman et al.	
6,067,681	A	5/2000	Zeinstra et al.	
6,144,114	A	11/2000	Chutorash	
6,154,148	A	11/2000	Fluharty et al.	
6,181,255	B1	1/2001	Crimmins et al.	
6,188,889	B1	2/2001	Tsai	
6,212,474	B1	4/2001	Fowler et al.	
6,282,152	B1	8/2001	Kurple	
6,282,407	B1	8/2001	Vega et al.	
6,336,031	B1	1/2002	Schyndel	
6,374,182	B2	4/2002	Bechtolsheim et al.	
6,430,164	B1	8/2002	Jones et al.	
6,472,771	B1	10/2002	Frese et al.	
6,539,358	B1 *	3/2003	Coon et al.	704/275
6,556,813	B2	4/2003	Tsui	
6,603,405	B2	8/2003	Smith	
6,615,023	B1	9/2003	Ehrensvard	
6,771,749	B1 *	8/2004	Bansal et al.	379/88.17
6,825,751	B1	11/2004	Kita et al.	
6,978,126	B1	12/2005	Blaker et al.	
7,050,593	B1	5/2006	Emerling et al.	
7,050,834	B2 *	5/2006	Harwood et al.	455/563
7,116,229	B1	10/2006	Miramontes	
7,228,211	B1	6/2007	Lowrey et al.	
7,257,426	B1	8/2007	Witkowski et al.	
7,346,374	B2	3/2008	Witkowski et al.	
7,349,722	B2	3/2008	Witkowski et al.	
7,516,072	B2	4/2009	Campbell et al.	
7,564,377	B2	7/2009	Kimchi et al.	
7,689,253	B2 *	3/2010	Basir	455/563
7,787,907	B2 *	8/2010	Zeinstra et al.	455/563
8,103,445	B2	1/2012	Smith et al.	
2001/0033225	A1 *	10/2001	Razavi et al.	340/425.5
2002/0032510	A1	3/2002	Turnbull et al.	
2002/0040271	A1	4/2002	Park et al.	
2002/0054159	A1	5/2002	Obradovich	
2002/0169584	A1	11/2002	Fu et al.	
2003/0096593	A1	5/2003	Naboulsi	
2003/0114202	A1 *	6/2003	Suh et al.	455/569
2003/0210796	A1	11/2003	McCarty et al.	
2003/0236818	A1	12/2003	Bruner et al.	
2004/0054468	A1	3/2004	Yamada et al.	
2004/0104842	A1	6/2004	Drury et al.	
2005/0005298	A1	1/2005	Tranchina et al.	
2005/0015197	A1	1/2005	Ohtsuji et al.	
2005/0024264	A1	2/2005	Harrison	
2005/0053008	A1	3/2005	Griesing et al.	
2005/0197747	A1	9/2005	Rappaport et al.	
2005/0208968	A1	9/2005	Codeville	
2005/0239434	A1	10/2005	Marlowe	
2005/0242970	A1	11/2005	Blaker et al.	
2005/0245272	A1	11/2005	Spaur et al.	
2006/0158344	A1	7/2006	Bambini et al.	
2006/0214813	A1	9/2006	Witkowski et al.	
2006/0232376	A1	10/2006	Blaker	
2006/0232377	A1	10/2006	Witkowski	
2007/0057810	A1	3/2007	Bos et al.	
2007/0123191	A1 *	5/2007	Simpson	455/345
2007/0143798	A1	6/2007	Jira et al.	
2007/0152798	A1	7/2007	Witkowski	
2007/0197172	A1	8/2007	Witkowski et al.	
2007/0213092	A1 *	9/2007	Geelen	455/556.1
2008/0027643	A1 *	1/2008	Basir et al.	701/213
2008/0068205	A1	3/2008	Witkowski	
2008/0192659	A1	8/2008	Santavicca	
2008/0221742	A1	9/2008	DiCroce	
2008/0244050	A1 *	10/2008	Wong et al.	709/223
2009/0085728	A1	4/2009	Catten et al.	
2010/0100310	A1	4/2010	Eich et al.	

FOREIGN PATENT DOCUMENTS

EP	1 267 111	A1	12/2002
EP	1 304 695	A2	4/2003
EP	1 338 866	A2	8/2003
EP	1 357 358	A1	10/2003
EP	1 058 220	B1	2/2004
EP	1 387 145	A1	2/2004
EP	1 568 834	A1	8/2005
EP	1 655 677	A2	5/2006
EP	1 698 518	A2	9/2006
EP	1 493 994	B1	8/2007
EP	1 959 410	A1	8/2008
EP	1 560 200	B1	11/2008
GB	2 375 397	B	5/2004
JP	01-290032		11/1989
JP	2001-297527	A	10/2001
JP	2001-304875	A	10/2001
JP	2002-087183	A	3/2002
JP	2002-169584	A	6/2002
JP	2002-171217	A	6/2002
JP	2003-244343	A	8/2003
JP	2003-304339	A	10/2003
JP	2004-153660	A	5/2004
JP	2005-236560	A	9/2005
JP	2005-284886	A	10/2005
JP	2006-033377		2/2006
JP	2006-321470	A	11/2006
JP	2007-256137		10/2007
WO	WO-00/75905	A1	12/2000
WO	WO-01/67413		9/2001
WO	WO-2004/043750	A2	5/2004
WO	WO-2004/077729	A2	9/2004
WO	WO-2005/002080	A1	1/2005
WO	WO 2006/063602	A1	6/2006
WO	WO 2007/123798	A1	11/2007
WO	WO-2008/079811	A1	7/2008
WO	WO 2008/079889	A2	7/2008
WO	WO 2008/079891	A2	7/2008
WO	WO 2008/091727	A1	7/2008
WO	WO 2009/073806	A2	6/2009

OTHER PUBLICATIONS

International Search Report and Written Opinion for Application No. PCT/US2007/088175, dated Sep. 19, 2008, 9 pages.

International Search Report and Written Opinion for Application No. PCT/US2008/085570, dated Oct. 22, 2009, 12 pages.

International Search Report and Written Opinion for Application. No. PCT/US2008/050436, dated Jun. 18, 2008, 9 pages.

MP3CAR.COM, MP3Car.com Wiki, http://www.mp3car.com, believed to be available by at least Jan. 12, 2007, 11 pages.

Office Action for European Patent Application No. 07869543.4, dated Dec. 22, 2010, 6 pages.

Office Action for European Patent Application No. 08705741, dated Jan. 13, 2010, 3 pages.

Office Action for European Patent Application No. 07869543.4, dated Oct. 14, 2009, 3 pages.

Invitation to Pay Additional Fees and Communication Relating to the Results of the Partial International Search dated Jun. 12, 2009 as received in PCT/US2008/085570, 6 pages.

Office Action for European Patent Application No. 07 869 539.2, dated Jun. 25, 2010, 5 pages.

Dahn, et al., "Combinatorial Study of Sn1-xCox (0 < x < 0.6) and [Sn0.55Co0.45]1-yCy (0 < y < 0.5) Alloy Negative Electrode Materials for Li-Ion Batteries," Journal of Electrochemical Society, (2006), 153:A361-365.
http://en.wikipedia.org/wiki/Near_Field_Communication, Oct. 17, 2007, 6 pages.
International Search Report and Written Opinion for International Patent Application No. PCT/US2009/065855, dated Jun. 11, 2010.
Japan Office Action dated May 15, 2012 as received in corresponding Japan Application No. 2009-543188 and its English Translation, 7 pages.
Japan Office Action dated May 15, 2012 as received in corresponding Japan Application No. 2009-547339 and its English Translation.
Office Action for European Application No. 04751431.0, mail date Dec. 14, 2009, 5 pages.
Office Action for U.S. Appl. No. 10/558121, dated Jan. 20, 2010, 9 pages.
Office Action for U.S. Appl. No. 10/558,121, dated Jul. 9, 2010, 11 pages.
Office Action in JP 2010-537078 dated Oct. 2, 2012.
Office Action in JP Appln No. 2009-543188 dated Nov. 6, 2012.
Office Action in U.S. Appl. No. 13/428,857 dated Oct. 16, 2012.
Office Action in U.S. Appl. No. 12/328,663 dated Apr. 26, 2012.
Office Action in U.S. Appl. No. 12/519,735 dated Jun. 13, 2012.
Office Action received for U.S. Appl. No. 12/328,663, dated Nov. 23, 2011, 13 pages.
Office Action U.S. Appl. No. 10/558,121 dated Apr. 11, 2012.
PCT Invitation to Pay Additional Fees and Partial International Search Report as received in PCT/US2009/065855, dated Mar. 19, 2010.
Written Opinion for International Patent Application No. PCT/US2004/017058, mailed Oct. 15, 2004.

* cited by examiner



FIG. 1


106
108
114
112
MEDIA PLAYBACK
HANDS-FREE PHONE
HVAC CONTROL
CONTACT MANAGEMENT
CALENDAR
VEHICLE LOGS
112
112
SELECT
112
110

FIG. 2



FIG. 3


Portable Electronic Device
116
Remote Source
117
118
118
Communication Device
120
Portable Electronic Device w/Wired Port
116
Remote Source w/ Wired Port
117
118
118
Wired Interface
170
Wired Interface
172
Vehicle Control System
106
Data Processing System
122
Display Driver
124
Memory Device
132
Audio System Interface
174
Audio System
104
Audio Input Interface
182
Electronics Interface
180
Audio Output Device Interface
178
Display Interface
176
Output Display
108
Audio Input Device
128
User Interface
126
Audio Output Device
130

FIG. 4


Remote Server
154
Internet
Mobile Device
160
161
144
118
Personal Digital Assistant
146
Media Player
148
Personal Navigation Device
150
Pager
152
Communication Device
120
Vehicle Control System
106
Memory Device
132
Volatile Memory
140
Non-Volatile Memory
142
Display Driver
122
Data Processing System
122
Text-to-Grammar Device
134
Speech Recognition Device
136
Text-to-Speech Device
138
Remote Source w/ Wired Port
116
Audio System
104
Output Display
108
Audio Input Device
128
User Interface
126
Audio Output Device
130

FIG. 5


602
Portable Device Display
600
604
First Display Portion
610
Vehicle Display
606
Second Display Portion
Second Display Portion
(Reproduced from Portable Device)
612

FIG. 6


116
106
Portable Device
Vehicle Control System
602
Display
702
World Clock
704
Nav / Maps
706
HMI Elements
708
Voice Recognition Engine
710
Media Decoding Elements
712
Connectivity Applications
714
Calendar
716
E-Mail
718
Text Messaging
720
Voice Mail
722
Web Services
724
Videos
726
Memory
728
Games
730
Home Status
732
Stocks
740
Vehicle Tactile Controls
742
Vehicle Touch Screen
108
Vehicle Display
104
Vehicle Audio System
744
Vehicle Microphone
752
GPS Receiver
754
Processing System
756
Voice Recognition System
758
HMI Configuration Engine

FIG. 7


116
Portable Device
810
Memory Device
802
Wireless Transceiver
Vehicle Mode Information
804
812
Processing System
Normal Mode Information
806
Mode Switching Module
808
Wired Interface
814

FIG. 8


900
Establish Communication Link with Portable Device
902
Send Command to Enter Vehicle Mode to Portable Device
904
Receive Confirmation from Portable Device that the Portable Device is Operating in Vehicle Mode
906
Receive Images (e.g., simplified, based on Vehicle Mode) from Portable Device
908
Display Images Received from Portable Device
910
Determine Feature Set of Portable Device Capable of Suppression
912
Send Command to Portable Device to Suppress a Feature of Portable Device
914
Send Command to Portable Device to Lift a Feature Restriction (Based on Vehicle Parking or UI Command)
916

FIG. 9


126
User Interface
108
Display
104
Audio System
106
Control System
116
Portable Device
1002
Vehicle Data Bus
Vehicle Subsystems
1004
1006
Vehicle Subsystems

FIG. 10


1100
1102
Receive Signal from Vehicle Subsystem
1104
Make Situational Determination Based on Received Signal
1106
Is Vehicle Parked?
No
Yes
1108
Retrieve Operational Parameters Associated with Parking
1110
Allow User Interface Activities Based on Retrieved Operational Parameters
1112
Retrieve Operational Parameters Associated with Driving
1114
Restrict Available User Interface Activities Based on Retrieved Operational Parameters
1116
Change Default User Interface Control to Hands-Free

FIG. 11


1200
1202
Receive Signal Indicating Portable Device is Connected
1204
Send Request to Portable Device to Check for Compatibility
1206
Receive Response from Portable Device
1208
Make Compatibility Determination
1210
Request Feature Set Information from Portable Device
1212
Receive and Interpret Feature Set Information from Portable Device
1214
Map Portable Device Feature to Vehicle UI Element

FIG. 12


1300
1302
Receive Signal from Mapped UI Element
1304
Retrieve or Determine Command for Sending to Portable Device
1306
Send Command to Portable Device
1308
Receive Confirmation from Portable Device

FIG. 13


1400
Request Feature Set Information from Portable Device
1402
Receive and Interpret Feature Set Information from Portable Device
1404
Target UI Feature Available on Portable Device via Single Command?
1406
Yes
Map UI Feature to Command
1408
No
Target UI Feature Available on Portable Device via Multiple Commands?
1410
No
Indicate Failure to Set Target UI Feature to User
1412
Yes
Build (or Retrieve) Macro Based on Feature Set Information from Portable Device
1414
Map UI Feature to Macro
1416

FIG. 14


1500
Receive Signal from UI Feature Mapped to Macro
1502
Send Multiple Commands to Portable Device
1504
Receive Response from Portable Device
1506
Reproduce Portable Device Display
1508
Display or Feedback Information via Audio System or Display System
1510

FIG. 15


1600
Receive Command to Begin Voice Typing
1602
Receive Utterance
1604
Detect Character from Received Utterance
1606
Display Character
1608
Enlarge the Detected Character
(e.g., Relative to Other Displayed Characters)
1610
Store the Detected Character
1612
Delay for Some Period of Time
1614
Display the Detected Character at a Reduced Size
1616
Move the Character on the Screen or Move a Cursor for
Displaying the Next Character Received
1618
Enlarge an Entire Word if a Word is Detected or Indicated to
Be Complete
1620

FIG. 16



FIG. 17



FIG. 18



FIG. 19


2000
Establish First Communication Connection
2002
Conduct Communication Task
2004
Measure Speed and/or Interference of First Communication Connection
2006
Measure Other Channels and/or Strength of Signals from Alternative Remote Sources
2008
Estimate Best Communications Connection
2010
Is Present Connection Estimated to the the Best?
2012
Yes
No
Is Alternative Connection Significantly Better than Present Connection?
2014
No
Yes
Establish Second Communication Connection
2106
Wait for Idle or Low Communication Bandwidth on First Communication Connection
2108
Switch to Second Communication Connection for Data and/or Voice Communications
2020
Terminate First Communication Connection
2022
Define Second Communication Connection as First Communication Connection
2024

FIG. 20


2100
Detect Device Connection
2102
Query Device for a Communication Capability or a Feature
2104
Receive Response from Device
2106
2108
Does Portable Device Include Capability or Feature?
Yes
Use Capability or Feature
2110
No
2112
Permission to Push Update to Device?
Yes
No
2114
Send Text Message (e.g., SMS Message) to Device, Commanding Software Update
2116
Wait for Response from Device
2118
Send Software Update to Device

FIG. 21


2200
Receive Text Message from Vehicle
2202
Parse Text Message
2204
Respond to Text Message Based on Parsed Information
2206
Wait to Receive Software Update
2208
Receive Software Update
2210
Install Software Update
2212
Send Confirmation Message to Vehicle
2214

FIG. 22


2314
Remote Processing
2316
Wireless Services / Remote Source
2300
2312
Control System
Communication Device
2302
Processing System
Voice Typing Engine
Dictation Engine
First Phoneme Extractor
Second Phoneme Extractor
2304
2306
2308
2310

FIG. 23


2400
Receive Signal Representing Vocal Utterance
2402
Attempt to Extract Unit of Speech from Next Signal Part
2404
2406
Difficulty with Extraction?
No
Yes
2408
Send Signal Part to Remote Source for Extraction
2410
Receive Unit of Speech from Remote Source
No
Signal Fully Extracted?
2412
Yes
2416
2414
Extraction Recognized Command?
No
Prompt User for Repeat
Yes
2418
Send Extracted Signal to Remote Source for Recognition
2420
Confirm Vocal Utterance

FIG. 24


2500
2502
2504
2510
PHONE
2512
2518
2514
2508
2506
2516
CONTACTS
MENU

FIG. 25


2620
Wireless Service / Remote Source
100
2614
Active, Passive, or Hybrid Antenna Interface Module
Vehicle
2602
2612
Vehicle Dash
2604
Isolation Bin
106
Control System
PSU
2606
2610
Wired Interface
Wireless Interface
2616
Jamming Device
2608
2618
116
Unauthorized Mobile Device

FIG. 26


100
Vehicle
106
Control System
2704
Charging Module
2706
Command and Control Module
2708
Data Transfer Module
2712
Handset to Vehicle Class
Class Database
2710
.....
Custom Drivers
2718
2716
Handset to Vehicle Driver
Class Drivers
2714
.....
2720
Vehicle Class Communication Protocol Stack
2722
USB System Software
Root Hub
2726
USB Host Controller
2724
2728
USB Interface
Wireless USB Host
Wireless USB Transceiver
2730
2732
2734
Wireless USB Device
2750
2744
1706
2742
Compass System
Access Controller (e.g., HomeLink)
USB Interface
Media Player
2752
GPS Receiver
Navigation Device
752
2740
2746
2748

FIG. 27


Vehicle
106
Control System
2728
2802
USB Interface
Vehicle USB Class Identifier
2804
USB Interface
Portable Device
2808
Vehicle Class Device Driver
Host Controller
2806
116

FIG. 28


Vehicle
106
Control System
2902
2904
Browser Module
Modem Application Software
2728
Modem Device Driver
Communication Stack Compatible with Modem
USB Interface
2906
2908
2910
USB Interface
Modem Device
2912
Communications Module
2900

FIG. 29


Vehicle
106
Control System
3004
Connection Manager
3012
Comm. Device Switching Module
3006
GPS System
3014
Connection Point Database
3008
Browser Module
3016
Network Detection Application
3010
User Interface Module for Configuration of Wireless Comm. Device
3018
Security Module for Configuration of Wireless Comm. Device Security Features
Comm. Stack Compatible with Wireless Comm. Device
3020
2728
USB Interface
3022
Device Driver for Wireless Comm. Device
Comm. Device
120
3030
USB Interface
3032
Wireless Communication Device
3034
Communications Module

FIG. 30

VEHICLE USER INTERFACE SYSTEMS AND METHODS

CROSS REFERENCE TO RELATED APPLICATIONS

The present application is a Continuation of U.S. application Ser. No. 12/794,490 filed Jun. 4, 2010, which is a Continuation of International Application No. PCT/US2008/085570, filed Dec. 4, 2008, which claims priority to U.S. Provisional Application No. 61/005,419, filed Dec. 5, 2007. The foregoing applications are incorporated by reference herein in their entirety.

BACKGROUND

The present disclosure relates generally to the fields of communication, navigation, and/or user control in a motor vehicle.

Vehicles typically include a number of electronics systems and subsystems such as an audio system, a mobile telephone system, a navigation system, an in-vehicle entertainment system, an HVAC system, an engine management system, and the like that may be controlled by an in-vehicle user interface and an in-vehicle control system.

Conventional vehicle control systems typically do not interface well with remote sources and portable devices such as cellular phones. Even when vehicle control systems are configured to interface with remote sources and portable devices, the human-machine interfaces and processing electronics are typically separate, look very different, and are difficult to use together. Applications provided on a portable device are typically not configured to interact with a vehicle and vice versa. There is a need for improved user interface features and/or connectivity features relating to vehicle control systems, remote sources, and/or portable devices. There is a need for effective display reproduction and/or user interface reproduction from a remote source to an in-vehicle display or other in-vehicle interface.

It would be desirable to provide a system and/or method that satisfies one or more of these needs or provides other advantageous features. Other features and advantages will be made apparent from the present specification. The teachings disclosed extend to those embodiments that fall within the scope of the disclosure, regardless of whether they accomplish one or more of the aforementioned needs.

SUMMARY

One embodiment relates to a control system for mounting in a vehicle and for providing information to a portable electronic device for processing by the portable electronic device. The control system includes a first interface for communicating with the portable electronic device and a memory device. The control system also includes a processing circuit communicably coupled to the first interface and the memory device, the processing circuit configured to extract information from the memory device and to provide the information to the first interface so that the first interface communicates the information to the portable electronic device. The processing circuit is further configured to determine the capabilities of the portable electronic device based on data received from the portable electronic device via the first interface and to determine whether or not to communicate the information to the portable electronic device based on the determined capabilities. The first interface may be or include a transceiver configured to form a wireless communication with a portable electronic device or circuitry and/or connection hardware for forming a wired connection to the portable electronic device.

Another embodiment relates to using a vehicle control system for voice typing purposes. The vehicle control system includes an interface for coupling to an audio input device mounted to the vehicle interior and for receiving voice information from a user. The interface may be circuitry and/or connection hardware for forming a functional connection to an audio input device such as a microphone. A processing circuit of the vehicle control system includes a speech recognition module configured to convert the voice information received at the second interface into text characters. The text characters from the speech recognition module are transmitted to the portable electronic device from the processing circuit and/or a transmitter associated therewith. The vehicle control system can also include an interface for providing display information to an electronic display device mounted to the vehicle interior and the processing circuit may be configured to enter a voice-typing mode of operation. During the voice-typing mode of operation, the processing circuit can be configured to cause the electronic display device to display the text characters from the speech recognition module. The processing circuit may be further configured to magnify a recently converted text character relative to previously converted text characters on the electronic display device. The processing circuit may also be configured to communicate the text characters to the portable electronic device in a format that causes the text characters to be entered into a text field displayed on the portable electronic device. The processing circuit can also be configured to communicate the text characters to the portable electronic device in a format that causes the portable electronic device to provide the text characters to an application running on the portable electronic device (e.g., a text-messaging application, a calendaring application, a mobile commerce application, a web-browsing application, a gaming application, a navigation application, an e-mail application, a media application, and a notes application, etc.).

Another embodiment relates to using a vehicle control system configured to transmit information to a portable electronic device; the information being formatted for further processing by a software application of the portable electronic device. The format may be a WAP format, a WXML format, an HTML format, an XHTML format, an XML format and/or any other suitable format for transferring over a radio frequency wireless communications link from a vehicle control system to a nearby portable electronic device. The vehicle control system may further include an interface configured to receive position information from at least one of a global positioning system receiver and a compass. The information communicated to the portable electronic device may include the position information. The position information may be formatted to be transmitted to a remote source from the portable electronic device and/or transmitted to the portable electronic device with data for transmitting the position information to the remote source from the portable electronic device.

Another embodiment relates to using a vehicle control system having a processing circuit configured to receive information regarding a vehicle operational mode (e.g., from a vehicle subsystem), and to provide information to a portable electronic device including a command to disable a feature of the portable electronic device. The operational mode may be a driving mode and the information provided to the portable electronic device may include a command to disable at least one of a local display of the portable electronic device, a text messaging capability of the portable electronic device, and an

e-mail capability of the portable electronic device. The processing circuit may be configured to send the command to the phone based on a speed of the vehicle.

Another embodiment relates to a vehicle control system having a processing circuit configured to utilize the vehicle subsystem information and position information received from a global position system receiver to calculate a precise vehicle location relative to the position information. The precise vehicle location information may be transmitted to the portable electronic device for processing, display, storage, or otherwise. The processing circuit may be further configured to utilize locationing information received and/or determined by the portable electronic device in the calculation of the precise vehicle location.

Another embodiment relates to a vehicle control system having a processing circuit configured to send information to a portable electronic device; the information may include software update information formatted for installation on the portable electronic device once received by the portable electronic device and/or a command for the portable electronic device to obtain a software update from a remote source. The processing circuit is configured to determine whether or not the portable electronic device is in need of the update based on capabilities of the portable electronic device determined by the processing circuit based on data received from the portable electronic device. The processing circuit may also or alternatively be configured to use data received from the portable electronic device to determine whether an update is available for the processing circuit and/or for another vehicle subsystem. The processing circuit may be configured to request the update from a remote source via the portable electronic device, receive the update via the first interface from the portable electronic device and the remote source, and/or to process the update.

Alternative exemplary embodiments relate to other features and combinations of features as may be generally recited in the claims.

BRIEF DESCRIPTION OF THE FIGURES

The disclosure will become more fully understood from the following detailed description, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements, in which:

FIG. **1** is a perspective view of a vehicle that includes a number of vehicle systems, including a vehicle control system, according to an exemplary embodiment;

FIG. **2** is a front elevation view of the vehicle control system of FIG. **1**, according to an exemplary embodiment;

FIG. **3** is a cutaway perspective view of a portable electronic device communicably coupled to the vehicle control system of FIG. **1**, according to an exemplary embodiment;

FIG. **4** is a block diagram of the vehicle control system of FIG. **1**, according to an exemplary embodiment;

FIG. **5** is a more detailed embodiment of the vehicle control system and remote source of FIG. **4**, according to an exemplary embodiment;

FIG. **6** is a block diagram of a display reproduction system, according to an exemplary embodiment;

FIG. **7** is a block diagram of a portable electronic device interfacing with a vehicle control system using wired or wireless communications, according to an exemplary embodiment;

FIG. **8** is a detailed block diagram of a portable electronic device, according to an exemplary embodiment;

FIG. **9** is a flow chart of a vehicle control system process for interacting with a portable electronic device, according to an exemplary embodiment;

FIG. **10** is a block diagram of a vehicle control system coupled to a variety of components in a vehicle and a portable electronic device, according to an exemplary embodiment;

FIG. **11** is a flow chart of a process for providing situational awareness in a vehicle, according to an exemplary embodiment;

FIG. **12** is a flow chart of a process for a vehicle control system inheriting a feature of a portable device, according to an exemplary embodiment;

FIG. **13** is a flow chart of a process for a vehicle control system activity based on the programmed or "feature mapped" user interface element determined in the process of FIG. **12**, according to an exemplary embodiment;

FIG. **14** is a flow chart of a process for configuring a vehicle control system to inherit a multiple-command feature from a portable electronic device, according to an exemplary embodiment;

FIG. **15** is a flow chart of a process for a vehicle using the multiple-command feature of FIG. **14**, according to an exemplary embodiment;

FIG. **16** is a flow chart of a process for providing a voice typing function to a vehicle control system and/or to a portable electronic device communicably coupled to a vehicle control system, according to an exemplary embodiment;

FIG. **17** is a block diagram of a vehicle including navigational features, according to an exemplary embodiment;

FIG. **18** is a flow chart of a process for a vehicle control system providing improved navigation activity, according to an exemplary embodiment;

FIG. **19** is a flow chart of a process for a portable electronic device used in conjunction with the process of FIG. **18**, according to an exemplary embodiment;

FIG. **20** is a flow chart of a process for utilizing two communication connections to provide for voice and/or data communications, according to an exemplary embodiment;

FIG. **21** is a flow chart of a process for generating a text message to trigger an update, according to an exemplary embodiment;

FIG. **22** is a flow chart of a process for a portable device receiving the text message generated by the process of FIG. **21**, according to an exemplary embodiment;

FIG. **23** is a block diagram of a system for providing in-vehicle voice processing assisted by a remote processing system, according to an exemplary embodiment;

FIG. **24** is a flow chart of a process for providing in-vehicle voice processing assisted by a remote processing system, according to an exemplary embodiment;

FIG. **25** is a diagram of a control for mounting to a vehicle interior element or for integrating with a vehicle interior element, according to an exemplary embodiment;

FIG. **26** is a block diagram of a vehicle including an isolation bin for a portable electronic device, according to an exemplary embodiment;

FIG. **27** is a block diagram of a vehicle control system including components for universal serial bus (USB) connectivity with a portable electronic device brought into the vehicle, according to an exemplary embodiment;

FIG. **28** is a block diagram of another vehicle control system including USB connectivity features, according to an exemplary embodiment;

FIG. **29** is a block diagram of a vehicle control system configured to connect to and utilize a USB modem device, according to an exemplary embodiment; and

FIG. **30** is a block diagram of a vehicle control system for communicating with a wireless service or a remote source via a USB-connected wireless communication device (e.g., a USB WiFi transceiver), according to an exemplary embodiment.

DETAILED DESCRIPTION

Before turning to the figures, which illustrate the exemplary embodiments in detail, it should be understood that the application is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology is for the purpose of description only and should not be regarded as limiting.

The vehicle control systems described in FIGS. **1-5** are examples of a vehicle systems that may be used in conjunction with the systems and methods of the present disclosure. Control circuits and processing components of the vehicle control systems shown in FIGS. **1-5** can be configured to complete and/or facilitate the features described herein. For example, executable computer code for conducting one or more of the processes described herein may be stored in a memory device communicably coupled to a processing circuit or component configured to execute the stored computer code.

Referring to FIG. **1**, a perspective view of vehicle **100** is illustrated. Vehicle **100** includes a number of subsystems for user convenience and entertainment. For example, vehicle **100** may include a heating, ventilation, and air-conditioning (HVAC) system, a sound system, and a vehicle control system **106** (e.g., media system, navigational system, entertainment system, display system, communications systems, etc.). The HVAC system, sound system, and other systems may be coupled to vehicle control system **106**, which is capable of controlling and monitoring a variety of systems, automatically or by a manual user command. It is noted that in various exemplary embodiments, vehicle **100**, the HVAC system, the sound system, and other vehicle systems may be of any past, present, or future design capable of being physically coupled to, communicably coupled to, and interacting with vehicle control system **106**.

Referring to FIG. **2**, one exemplary embodiment of vehicle control system **106** is shown. Vehicle control system **106** generally includes an output display **108**, one or more knobs **110**, one or more pushbuttons **112**, and one or more tactile user inputs or pushbuttons **114**, which facilitate controlling various vehicle functions. Output display **108** may be configured to display data related to the control of the vehicle functions. In one exemplary embodiment, output display **108** may be a touch-screen display, while in other exemplary embodiments, may be anon-touch sensitive display. In still other exemplary embodiments, output display **108** may be of any technology (e.g., LCD, DLP, plasma, CRT), configuration (e.g., portrait or landscape), or shape (e.g., polygonal, curved, curvilinear). Output display **108** may be a manufacturer installed output display, an aftermarket output display, or an output display provided by or installed by any other source. Output display **108** may be an embedded display (e.g., a display embedded in the control system or other vehicle systems, parts, or structures), a standalone display (e.g., a portable display, a display mounted on a movable arm), or a display having any other configuration. User interface elements (e.g., output knobs **110** and pushbuttons **112** and **114**) may be configured to control functions of the HVAC system such as fan speed, cabin temperature, or routing of air flow, to control playback of media files over the sound system, to control retrieval of phonebook entries, to control a function of a connected remote source, or to control any other desired vehicle function.

User interface elements such as pushbuttons **114** typically allow for the selection and display of various functions of vehicle control system **106** including sound system control, media system control, display system control, communications system control, hands-free phone use, HVAC system control, contact or address/phone book management, calendar viewing and modification, and vehicle data logging. The operation of pushbutton **114** for media playback may display a media playback menu screen or execute commands that allow the user to view, select, sort, search for, and/or play audio or video files by tactile or oral command. The operation of pushbutton **114** for hands-free phone operation may display a menu screen or execute commands that allow the user to connect vehicle control system **106** to a mobile phone so that speaking into the vehicle console of vehicle control system **106** operates the mobile phone. The operation of pushbutton **114** for HVAC control may display a menu screen or execute commands that allow the user to control cabin temperature and air flow by tactile or oral command. The operation of pushbutton **114** for contact management may display a menu screen or execute commands that allow the user to view, list, select, sort, search for, edit, and/or dial one or more entries containing personal contact information, by use of a tactile or oral command. The operation of pushbutton **114** for calendar management may display a menu screen or execute commands that allow the user to view, list, select, sort, search for, edit, and/or create one or more entries containing personal schedule information by tactile or oral command. The operation of pushbutton **114** for vehicle log management may display a menu screen or execute commands that allow the user to input, view, select and/or reset information related to the vehicle operation (e.g., fuel economy, engine temperature, distance to empty, etc.) by tactile or oral command.

Pushbuttons **114** (and/or any other user interface element (s)) of vehicle control system **106** may be used to control other vehicle subsystems such as, but not limited to, vehicle door locking systems, vehicle cruise control systems, seat control systems, window control systems, hands-free communication systems, vehicle lighting systems, vehicle radio systems, wireless control systems, media control systems, and/or any other control system that may accept user input. According to an exemplary embodiment, user interface elements, display elements, audio input and output elements and the like mounted in the vehicle and communicably coupled to vehicle control system **106** may be used to provide input and/or output features to a connected (e.g., wired, wirelessly) portable electronic device brought into the vehicle.

Referring now to FIG. **3**, a portable electronic device **116** is shown near and in communication with vehicle control system **106**. According to various exemplary embodiments, portable electronic device **116** may communicably couple to vehicle control system **106** via a wired or wireless connection. In the embodiment shown in FIG. **3**, portable electronic device **116** may attach to or physically rest in a holder **302** configured to hold portable electronic device **116** and provide a physical connection (e.g., a power charging connection, a communication link connection, etc.) to vehicle control system **106**. According to one exemplary embodiment, the connection may allow for information to be transmitted between portable electronic device **116** and vehicle control system **106** (e.g., the display **301** of portable electronic device **116** is shown duplicated on display **108** of vehicle control system **106**, and display **301** may be altered using pushbuttons **112**, **114**). As shown, vehicle control system **106**, and more par-

ticularly display **108** is replicating display information shown on portable electronic device **116**'s display **301**. According to various alternative embodiments, user interface features of vehicle control system **106** can be shared with connected portable electronic device **106**, portable device **106** can replicate display information shown on display **108**, vehicle control system **106** can provide information to portable electronic device **116** for additional processing, and/or portable electronic device **116** can provide information to vehicle control system **106** for processing.

Referring now to FIG. **4**, vehicle control system **106** is capable of accessing data (e.g., pieces of information, commands, streaming information, data files, etc.) from a portable electronic device **116** or another remote source **117** over a communication link **118**. For example, vehicle control system **106** may access media files, phonebook data files, display information, voice information, applications, application programming interfaces (APIs), calendar data, or any other accessible data for use by vehicle control system **106**. Vehicle control system **106** may be capable of accessing data files from multiple remote sources over a single communication link or multiple communication links. Vehicle control system **106** may also send and receive requests, signals, files, commands, messages (e.g., text messages, voice messages, etc.), voice information, audio information, display information, meta information, stream data or information, and any other type of data to and/or from portable electronic device **116** and/or another remote source **117** over communication link **118**.

Vehicle control system **106** is shown to include a communication device **120**, a data processing system **122**, a display driver **124**, a user interface **126**, an audio input device **128**, an audio output device **130**, an output display **108**, and a memory device **132**.

Communication device **120** is generally configured to establish communication link **118** with portable electronic device **116** or another remote source **116**. In one exemplary embodiment, vehicle control system **106** may establish a wireless communication link such as with a Bluetooth communications protocol, an IEEE 802.11 protocol, an IEEE 802.15 protocol, an IEEE 802.16 protocol, a cellular phone protocol, another mobile phone protocol, a shared wireless access protocol-cord access (SWAP-CA) protocol, a wireless universal serial bus (USB) protocol, or any other suitable wireless technology. In another exemplary embodiment, vehicle control system **106** may establish a wired communication link such as with USB technology, IEEE 1394 technology, Firewire technology, optical technology, other serial or parallel port technology, or any other suitable wired link. According to various other exemplary embodiments, vehicle control system **106** and/or communication device **120** may form wireless and/or wired connections with a plurality of device and source **116***s* and **117***s*. Communication links may be formed such that communication device **120** may be simultaneously connected to multiple device and source **116***s* and **117***s*. Communication device **120** may send and receive one or more data streams, data strings, data files and/or other types of information (e.g., non-file based data, file based data, etc.) from connected devices and remote sources. In various exemplary embodiments, the communicated information may be, represent, or include text, numeric data, audio, video, program data, command data, information data, coordinate data, image data, streaming media, or any combination thereof.

Data processing system **122** (e.g., processing electronics, processing circuit, processing system, etc.) is coupled to communications device **120** and is generally configured to control and/or facilitate each function of vehicle control system **106**. Data processing system **122** may facilitate speech recognition capabilities of vehicle control system **106** for the convenience of the user. Data processing system **122** may include digital or analog processing components and/or be of any past, present, or future design that facilitates control or provides processing features to vehicle control system **106**. Data processing system **122** may be a single data processing device or multiple data processing devices. Data processing system **122** may be a data processing device having data processing sub-devices or components. Data processing system **122** may include any combination of program software and hardware capable of providing control, display, communications, input and output features to the vehicle. Data processing system **122** may coordinate, control, and/or facilitate the various devices, components and features of vehicle control system **106** (e.g., communications device **120**, output display **108**, display driver **24**, memory device **132**, audio system **104**, user interface **126**, audio input device **128**, audio output device **130**, etc).

According to an exemplary embodiment, data processing system **122** is communicably coupled to memory device **132** and is configured to extract information from memory device **132** and to provide information to a first interface such as communication device **120** or wired interface **170** so that the first interface communicates the information to the portable electronic device **116** connected via a wired or wireless connection. Data processing system **122** may further be configured to determine the capabilities of the connected portable electronic device based on data received from the portable electronic device via the first interface and to determine whether or not to communicate the information (e.g., certain types of information, specific information, update information, navigation information, information for processing by the portable electronic device, etc.) to the portable electronic device based on the determined capabilities.

Display driver **124** is coupled to output display **108** and is typically configured to provide an electronic signal to output display **108**. In one exemplary embodiment, the electronic signal may include the text and/or numeric data of the data files, while in other exemplary embodiments, any other desired data may be included with the text and/or numeric data or by itself in the electronic signal to output display **108**. In another exemplary embodiment, display driver **124** may be configured to control output display **108** with touch-screen capabilities, while in other exemplary embodiments, display driver **124** may be configured to control output display **108** without making use of touch-screen capabilities. Display driver **124** may include any number of functions, software or hardware, to facilitate the control and display of images on output display **108**. In still other exemplary embodiments, display driver **124** may be of any past, present, or future design that allows for the control of output display **108**.

User interface **126** is typically configured to facilitate tactile user interaction with vehicle control system **106**. In various exemplary embodiments, user interface **126** may include pushbuttons or rotatable knobs as in the exemplary embodiment of FIG. **2** in any similar or dissimilar configuration or may include other tactile user contact points.

Audio input device **128**, for example a microphone, is configured to receive the utterance of a user for transmission to data processing system **122** for speech recognition so that the functions of vehicle control system **106** may be operated by voice command. Audio output device **130**, for example a built-in speaker, is configured to provide the user with an audio prompt of various functions, such as user selection confirmation.

Memory device **132** is configured to store information and data for accessing by vehicle control system **106**. For example, memory device **132** may store data input by remote source **116**, data created by data processing system **122** that may be used later, intermediate data of use in current calculation or process, computer code for execution by data processing system **122** (e.g., the computer code for completing the various processes described herein), any other information or data of use by vehicle control system **106**, and/or information that may be communicated to a connected portable electronic device or remote source.

Referring still to FIG. **4**, vehicle control system **106** is shown to includes interfaces **170-182**. Interfaces **170-182** can include any hardware and/or electronics for communicably coupling to each interface's respective connected device. The interfaces can include electronics local to the vehicle control system which may connect directly or indirectly to the portable electronic device. In some embodiments, one or more cords, connectors, or other electronics may be included with or between the vehicle control system interfaces and the portable electronic devices.

Audio input interface **182** can be configured to physically couple a audio input device **128** (e.g., via a corded connection) to vehicle control system **106**. Signals from audio input device **128** can be received at audio input interface **182**, filtered, interpreted, or otherwise processed, and routed or provided to electronics of vehicle control system **106** (e.g., to data processing system **122** or another processing circuit of the vehicle control system). Electronics interface **180** may be configured to communicably couple to wiring, a harness, or another connection scheme associated with user interface electronics **126**. For example, buttons, switches, LEDs or other user interface elements located throughout the vehicle interior may provide signals to and/or receive signals from electronics interface **180**. Electronics interface **180** may be configured to control the activity of the connected user interface elements, interpret received signals, and/or to route received signals to appropriate processing circuitry such as data processing system **122**. Audio output device interface **178** may be configured to receive audio signals from data processing system **122** or other processing circuitry of vehicle control system **106** and to provide the received audio signals to audio output device **130**. Audio output interface **178** may convert digital signals to analog, amplify the signals, normalize the signals, or otherwise before providing the signals (or a transformed version of the audio signals) to audio output device **130**. Display interface **176** may be configured to receive control signals from data processing system **122** or other processing circuitry of vehicle control system **106**, convert the control signals into analog or digital signals for the particular output display connected to display interface **176**, or otherwise configured to provide display information from vehicle control system to output display **108**. Audio system interface **174** may be configured to receive signals from data processing system **122** or other processing circuitry of vehicle control system **106** and to route the signals to audio system **104**. Audio interface **174** may conduct any number of processing tasks (e.g., A/D conversion, D/A conversion, decoding, normalizing, filtering, etc.) on audio signals prior to providing the audio signals (or a transformed version of the audio signals) to audio system **104**. Wired interface **172** may include any number of jacks, terminals, solder points, cords, or other hardware for physically coupling a cord or other hardware linkage system formed between wired interface **172** and remote source **117** that may include a wired port. Wired interface **170** may be configured similarly or differently from wired interface **170** and may be configured to physically couple (directly or indirectly) personal electronic device **116** to vehicle control system **106** and/or to vehicle control system **106**'s processing electronics (e.g., data processing system **122**). Wired interfaces **172**, **170** may be, for example, a USB terminal and associated hardware as described below or otherwise. According to other exemplary embodiments, wired interfaces **172**, **170** may be proprietary interfaces (e.g., an Apple iPod interface, etc.). Wired interfaces **172**, **170** may merely include connectors or terminals for connecting vehicle control system **106** and another device or can be or include the connectors or terminals in addition to electronics (e.g., filters, converters, security circuitry, power charging circuitry) that facilitates the communicative/functional connection between vehicle control system **106** (e.g., and its various processing circuitry) and the connected devices. According to various exemplary embodiments, communication device **120** may be considered an interface for wirelessly connecting vehicle control system **106** and remote or portable devices such as portable device **116** and remote source **117**.

Referring to FIG. **5**, vehicle control system **106** is shown in greater detail and as communicating with a number of different systems/devices via wired or wireless communications. Data processing system **122** is shown to include a text-to-grammar device **134**, a speech recognition device **136**, and a text-to-speech device **138**. Data processing system **122** may include any number of additional hardware modules, software modules, or processing devices (e.g., additional graphics processors, communications processors, etc.).

Text-to-grammar device **134** is preferably coupled to communication device **120** and is generally configured to generate a phonemic representation of text and/or numeric data provided to the text-to-grammar device. The text and/or numeric data can be provided to text-to-grammar device **134** by data processing device **122**, memory device **132**, and/or communication device **120**. The vehicle control system may receive the text and/or numeric data from any number of the wired or wirelessly connected remote sources. The phonetic representation of the text and/or numeric data may be configured to facilitate speech recognition of the text or numeric data. After conversion of a set of text (e.g., a command, a word, etc.) to a phonemic representation, an associated data file, command, or device may be accessed or requested via an oral input received by speech recognition device **136** and by audio input device **128**.

Speech recognition device **136** is typically configured to receive an oral input command from a user via audio input device **128**. Speech recognition device **136** compares the received oral input command to a set of predetermined input commands, which may have been generated or configured by text-to-grammar device **134**. In various exemplary embodiments, the input commands may be related to the playback of a media file, the dialing or input of a phone book entry, the entry or listing of calendar or contact data, the control of the HVAC system, a vehicle navigation system command, a portable electronic device feature, or any other desired function to be performed on data. Speech recognition device **136** may determine an appropriate response to the oral input command received from the user, for example, whether the oral input command is a valid or invalid instruction, what command to execute, whether the command should be provided on to a connected portable electronic device or other remote source, or any other appropriate response. According to an exemplary embodiment, speech recognition device **136** may be able to trigger or activate processing activities and features of a connected portable electronic device. For example, speech recognition device **136** may be able to pass commands to mobile

device **144** to facilitate interactive control of mobile device **144** via communication link **118**.

Text-to-speech device **138** is generally configured to convert the text and/or numeric information of a data file, data stream, or other data received from mobile device **144**, recalled from memory device **132**, or otherwise received, into an audible speech representation (e.g., an audio file for playback, audio data for playback by a vehicle audio system, etc.). This functionality may allow vehicle control system **106** to audibly provide feedback or other data to the user via audio output device **130** or audio system **104**. For example, vehicle control system **106** may repeat a user selected function back to the user, provide navigational information, announce directions, announce menu options, announce media file information, provide phonebook or contact information, or other information related to data stored in memory **132**, remote source **116**, remote server **154**, etc.

According to various other exemplary embodiments, text-to-grammar functionality, speech recognition functionality, and text-to-speech functionality are implemented primarily in software (e.g., executable modules stored in memory, computer code stored in memory, etc.) and executed by data processing system **122**, which may be a general purpose data processing system. According to yet other exemplary embodiments, text-to-grammar functionality, speech recognition functionality, and text-to-speech functionality are implemented partially in software and partially in hardware.

Memory device **132** is shown to include both a volatile memory **140** and a non-volatile memory **142**. Volatile memory **140** may be configured so that the contents stored therein may be erased during each power cycle of vehicle control system **106** or vehicle **100**. Non-volatile memory **142** may be configured so that the contents stored therein may be retained across power cycles, such that upon vehicle control system **106** and/or vehicle **100** power-up, data from previous system use remains available for the user. According to an exemplary embodiment non-volatile memory **142** may store one or more user profiles, executable computer code files, navigation information, display information, logic modules, display profiles, communications profiles, navigation profiles, and/or any other type of user or system setting file.

According to an exemplary embodiment, vehicle control system **106** may be configured to communicate (e.g., wired, wirelessly) with any suitable remote source (e.g., that includes a transceiver) that is able to interface with vehicle control system **106**. In various exemplary embodiments, a connected remote source or portable electronic device may be one or more of a mobile phone **144**, a personal digital assistant (PDA) **146**, a media player **148**, a personal navigation device (PND) **150**, a pager, **152**, a remote server **154** that may be coupled to the Internet, a handheld personal computer, or various other remote data sources. Connected portable electronic devices may include a storage device, one or more processing devices, and one or more communications devices. According to various exemplary embodiments, connected portable electronic devices such as mobile device **144** may connect to the Internet or any other remote source with first communication device **160** while communicating with vehicle control system **106** using second communication device **161**.

Display Reproduction System

Referring now to FIG. **6**, a block diagram of a display reproduction system **600** is shown, according to an exemplary embodiment. Display reproduction system may generally include a portable device display **602** of a portable electronic device and a vehicle display **610** (e.g., a display such as output display **108** of vehicle control system **106**). Portable device display **602** is shown to include a first display portion **604** and a second display portion **606**. The portable device of portable device display **602** may generally be configured to send an image of one or more portable display portions **604**, **606** to vehicle control system **106** for reproduction on vehicle display **610**. According to the embodiment shown in FIG. **6**, only second display portion **606** of portable device display **602** is sent to vehicle display **610** for reproduction. Even when only a single display portion is reproduced on vehicle display **610**, an image representing the entire display shown on the portable device may be transmitted to a vehicle system. A check bit, command, or other code sent with the image to the vehicle system may indicate which portion of the image to reproduce. According to other exemplary embodiments, only the portion for reproduction on the vehicle display is sent from portable device display **602** to vehicle display **610**. A vehicle system may send the portable device an indication of vehicle display size, resolution, vehicle display size dedicated to display reproduction or other information for describing attributes of the vehicle display.

According to an embodiment where a navigation graphical user interface (GUI) of the portable device is reproduced on vehicle display **610**, the navigation software of the portable device may operate with (or may be) software specifically configured for display reproduction on vehicle display **610**. This software may have the "brand" or otherwise similar look and feel of the vehicle interfaces. The software may include a definition of the display portion that should be transmitted to vehicle display **610**. The software may be configured to only send the most important portion of the navigational image or GUI shown on portable device display **602**. Advantageously, this software can be resident and replaceable on portable device display **602**, thereby allowing accommodation to new software on portable device display **602** without requiring changes to the software associated with the vehicle. According to other exemplary embodiments, the vehicle or the portable device may be configured to make a determination that the images shown on portable device display **602** would not fit or otherwise be totally represented on vehicle display **610** and to request and/or send a partial image based on the determination.

Vehicle display **610** may be mounted, integrated or otherwise provided to the vehicle interior. According to an exemplary embodiment, the display portion **612** for reproduction is provided to a car head medium display or a head-up display. According to an exemplary embodiment, a vehicle control system of vehicle display **610** includes user interfaces and logic for allowing the user to toggle and/or adjust display reproduction settings. The vehicle control system may be configured to allow a user to set conditions for display reproduction and/or frequency of reproduction. For example, in the situation in which the reproduced image is shown on a car medium display or head-up display, the user may choose to display the reproduced image or images prior to making changes in direction, merges, turns, or otherwise. By way of further example, the vehicle control system may reproduce images when the portable device issues acoustic directions. The reproduced image(s) may be displayed for some period of time (seconds, minutes, etc.) after the acoustic instructions have completed.

According to various exemplary embodiments, the vehicle control system and/or vehicle display system **610** are configured to magnify, invert, sharpen, process, stretch, crop, overlay, process, or otherwise enhance any image portion received from the portable device. The enhancement activity may be user selectable and multiple enhancement activities may be provided at any one time or to any one image. For example,

the vehicle control system might be configured to receive a second display portion **606** to invert the colors on the image for easier readability, to adjust the contrast of the image, to adjust the brightness of the image, to outline certain elements of the image, to magnify the image, to resize the image, and/or to soften the edges or provide anti-aliasing processing to the image.

Feature and Data Sharing Between a Portable Electronic Device and a Connected Vehicle Control System

Referring now to FIG. **7**, a block diagram of portable device **116** and vehicle control system **106** for inheriting functions of portable device **116** and/or for providing functions to portable device **116** is shown, according to an exemplary embodiment. The functionality of portable device **116** and/or vehicle control system **106** can be varied. Some functionalities of portable device **116** may be complex to operate when driving. Other functionalities of portable device **116** may generate and/or display quickly changing or detailed images that would not be appropriate to operate while the vehicle is in motion. Further, some features of portable device **116** may not normally be available on vehicle control system **106** and vise versa. Portable device **116** and/or vehicle control system **106** may be configured to utilize features and data of the other device. Portable device **116** may include display **602** as described with reference to FIG. **6**. In FIG. **7**, portable device **116** is also shown to include various modules (e.g., hardware and/or software modules)/components **702-732**.

World clock information **702** may be sent from portable device **116** to vehicle control system **106** for display, use in an emergency system, updating of vehicle clocks, or otherwise.

Navigational features, navigational databases, and/or map information **704** may be provided from portable device **116** to vehicle control system **106** for display and/or processing. Navigational features, navigational databases, and/or map information from vehicle control system **106** may also be provided to portable device **116** for display and/or further processing.

Human machine interface (HMI) elements **706** of portable device **116** may be used by HMI configuration engine **758** of vehicle control system **106** for display reproduction, voice recognition, and/or for transferring data between portable device **116** and vehicle control system **106**.

A voice recognition engine **708** of portable device **116** may be used by voice recognition system **756** of vehicle control system **106** to provide additional features and extra processing capability to vehicle control system **106** and/or to the user's in-vehicle command and control experience.

Media decoding elements **710** provided on portable device **116** may be used to decode audio files stored on portable device **116** and/or vehicle control system **106**. The decoded audio and/or a transformed data stream or file may be provided from portable device **116** to vehicle control system **106** for storage, further processing, and/or output via vehicle audio system **746**.

Connectivity applications **712** of portable device **116** may be utilized by vehicle control system **106**. For example, a TCP/IP stack, communications protocol modules, security software, decryption algorithms, browser software, or other communications or connectivity software may be utilized by vehicle control system **106** to complete vehicle control system communications tasks and/or to retrieve information (e.g., from another remote source or a remote server) for forwarding to vehicle control system **106**.

A calendar application **714** of portable device **116** may be utilized by vehicle control system **106** to receive calendar data from portable electronic device memory and/or a remote source, to receive alerts, reminders, schedule information, calendar display information, a mechanism for accepting or rejecting meeting requests, or otherwise. According to various alternative embodiments, vehicle control system **106** may include a calendar feature and may be configured to synchronize data with calendar application **714**, a database of portable device **116**, and/or an remote calendaring data source (e.g., an enterprise server accessible via the Internet).

An E-Mail feature **716** of portable device **116** may be utilized by vehicle control system **106** to receive E-Mail text, to synchronize stored e-mail information, to reproduce an inbox view, to play back voice mails residing in an E-Mail inbox, to draft and send an E-Mail (e.g., using a voice typing and/or voice recognition feature of the vehicle), or otherwise.

A text messaging feature **718** of portable device **116** may be utilized by vehicle control system **106** to receive text messages, to send text messages, to reproduce an inbox view, to draft and send a text message (e.g., using the voice recognition feature of the vehicle), to synchronize text messages with text messages stored in vehicle memory or otherwise. According to an exemplary embodiment, text messages received by the portable electronic device are provided to a connected vehicle control system for display and/or audio output by the vehicle control system (e.g., and connected displays, audio systems, etc.).

A voice mail feature **720** of portable device **116** may be utilized by vehicle control system **106** to display or audibly provide an indication that a new message has arrived, the number of new messages, the number of undeleted messages, the number of saved messages, the contents of the voice mail (via audio and/or text via a speech to text module provided in the vehicle, etc.), or otherwise.

Web services **722** of portable device **116** may be utilized by vehicle control system **106** to provide web-based transmissions and/or receptions of information, to parse information, to display information, to provide access to Internet-based information, to provide access to applications on portable device **116**, to provide access to hardware of portable device **116**, or for other purposes.

Video services **724** of the portable device **116** may be utilized by vehicle control system **106** to provide video decoding and/or playback features to the vehicle. For example, while vehicle control system **106** may include provisions for playing a standard MPEG file, and video services **724** of portable electronic device **116** may include an updated codec and/or application for decoding a media file stored on portable device **116** or vehicle control system **106**. Vehicle control system **106** may provide data (e.g., data files, streaming data) to portable device **116** for processing. Video services **724** and/or portable electronic device **116** may be configured to provide the results of such processing back to vehicle control system **106** for storage and/or output (e.g., display output, audio output).

A flash memory element **726** (or other memory element) of portable device **116** may be utilized by vehicle control system **106** and/or portable electronic device **116** to store media files, configuration files, and/or any other type of files or information. According to an exemplary embodiment, memory element **726** may be used to provide updates (e.g., application updates, firmware updates, etc.) to portable electronic device **116** and/or for vehicle control system **106**.

Games **728** provided on portable device **116** may be provided to vehicle control system **106** and/or to a vehicle display **744** or vehicle audio system **746** thereof. Vehicle control system **106** may be configured to forward game information to a rear seat entertainment system, wireless headphones via a vehicle-mounted transmitter, or otherwise.

Home status information **730** available at portable device **116** may be forwarded to vehicle control system **106** for processing, display, and/or user alerts. For example, portable device **116** may be configured to receive an alert from a home security system. The alert may be forwarded from portable device **116** to vehicle control system **106** for display, processing, and/or audible indication. Further, commands generated at a vehicle user interface may be provided to portable device **116** for processing, execution, and/or forwarding commands or requests to the home security system.

Stock market information **732** or applications available on portable device **116** may be forwarded, retrieved, or otherwise communicated from portable device **116** to vehicle control system **106**. According to an exemplary embodiment, requests for stock information may be generated by a vehicle user interface and/or vehicle control system and provided to the portable electronic device for processing and/or for retrieval by the portable electronic device (e.g., from a remote source). According to an exemplary embodiment, for example, a request for updated stock ticker information may be formed at the vehicle control system (e.g., by prompting for and receiving one or more ticker symbols). The vehicle control system can interface with an application on the portable electronic device for requesting and retrieving updated ticker information (e.g., price) from a remote source (e.g., an Internet source). The results can be processed by the portable electronic device (e.g., to generate a chart, percentage change, etc.) and provided to the vehicle control system from the portable electronic device for storage and/or display.

Referring still to FIG. **7**, vehicle control system **106** is shown as communicably coupled to various vehicle components. For example, vehicle tactile controls **740** associated with vehicle control system **106** may be used to control portable device **116** activities and/or to make selections of display elements reproduced on vehicle display **744**. A vehicle touch screen **742** may be used to provide touch screen features to portable device **116** or to send other control signals to the portable device **116**. A vehicle microphone **744** may be used for detection and interpretation of vocal utterances. The utterances or information representing the utterances may then sent from vehicle control system **106** to portable device **116** for processing. In some exemplary embodiments, the utterances may be processed by the vehicle control system to generate requests or commands for providing to the portable electronic device for processing (e.g., by an application of the portable electronic device, for forwarding to a remote system from the portable electronic device, etc.). Vehicle display **108** and vehicle audio system **104** are also coupled to vehicle control system **106** (as described in FIGS. **4-5** or otherwise).

A GPS receiver **752** of vehicle control system **106** may be configured to send location and/or heading information to portable device **116** for use in one or more applications or for transmission to another remote source. According to an exemplary embodiment, a processing system **754** of vehicle control system **106** can be configured to receive subsystem information and to provide dead-reckoning processing to the location information received by GPS receiver **752** using the subsystem information.

A processing system **754** of vehicle control system **106** may be used to process information, files, or streams provided by portable device **116**. Similarly, a processing system of portable device **116** may be configured to process information, files, streams, or signals provided from vehicle control system **106** to portable device **116**. According to an exemplary embodiment, the processor (the processor of the vehicle control system or the portable electronic device) more suitable and/or available for processing certain elements or tasks may be used to process those elements or tasks. Processing system **754** may be similar to data processing system **122** of vehicle control system **106** as described in FIGS. **4-5**.

A voice recognition system **756** (e.g., a system including various text and speech devices **134-138** as described in FIGS. **4-5**) and/or human machine interface (HMI) configuration engine **758** provided with vehicle control system **106** may be used to provide control to portable device **116**. HMI configuration engine **758** may be used to customize the graphical user interfaces or other interfaces (e.g., voice recognition interfaces, button functions, touch screen configuration, etc.).

Operational Mode Features

In situations where a "normal" display mode and/or menu mode of portable electronic device **116** is not desirable for display reproduction or otherwise, portable electronic device **116** may be configured to switch from a normal mode of operation to a "vehicle" mode of operation.

Referring to FIG. **8**, a portable electronic device **116** is shown in detail, according to an exemplary embodiment. Portable electronic device **116** is shown to include a memory device **802**, a wireless transceiver **810**, a processing system **812**, and a wired interface **814**. Memory device **802** is shown to include "vehicle mode" information **804** (e.g., information relating to a vehicle mode of operation), normal mode information **806**, and a mode switching module **808**. Processing system **812** may be a general processing system configured to execute computer code, a specialized processing system, and/or a collection of circuitry for completing the activities described herein. Vehicle mode information **804** may include, relative to the normal mode of operation, parameters for anew GUI theme, a new GUI color scheme, new display driver settings, software elements configured to generate displays suitable for display reproduction, or otherwise. Vehicle mode information **804** may also include feature suppression commands or settings such that portable device **116** suppresses unsafe and/or complicated features or screens from use during a vehicle mode. Mode switching module **808** may be provided and may include computer code, scripts, or macros for switching from a normal mode of operation to a vehicle mode of operation. According to an exemplary embodiment, mode switching module **808** is a web service, application programming interface, or other server or service configured to receive a command, request, or other information from a vehicle control system; the receipt of which is processed and causes the portable electronic device to controllably switch from mode to mode or to enable/disable certain features. Portable device **116** may use wireless transceiver **810** and wired interface **814** for connecting wirelessly or via a wired connection, respectively, with a vehicle control system.

Referring also to FIG. **9**, a vehicle control system process **900** for interacting with a portable device having vehicle mode features is shown, according to an exemplary embodiment. Process **900** includes establishing a communication link (wired or wireless) with a portable device (step **902**). Process **900** further includes sending a command to enter a "vehicle mode" to the portable device (step **904**). Any number of handshaking steps and/or querying steps may additionally take place. For example, the vehicle control system may query the portable device to determine if the portable device includes a "vehicle mode" feature or if a "vehicle mode" has been defined for the portable device that is connected. In response to the command, the portable device may enter a vehicle mode and send a confirmation message to the vehicle control system. The vehicle control system may be configured to receive a confirmation from the portable device that the portable device is operating in vehicle mode (step **906**).

The receipt of confirmation information may trigger any number of activities, including, for example, display reproduction activities. According to an embodiment wherein the vehicle control system and the portable device utilize the vehicle mode for display reproduction activities, the vehicle control system may begin receiving simplified images (relative to those shown on the portable device during a normal mode) from the portable device (step **908**). The received images may be displayed on one or more vehicle displays (step **910**). During (or prior to entering) vehicle mode, the vehicle control system may be configured to determine a feature set of a portable device capable of suppression (step **912**). For example, a portable device may include a gaming feature or a text messaging feature. These features may be suppressed during vehicle mode for any number of reasons. The portable device may have knowledge that these features may be suppressed (e.g., via a stored table or database) and may transmit relevant data to the vehicle control system upon request. Based on the suppressible feature information, the vehicle control system may send a command to the portable device to suppress a feature of the portable device (step **914**). According to various exemplary embodiments, a command to enter "vehicle mode" or a specific vehicle operational mode (e.g., "driving at highway speeds," "driving in unsafe conditions," "driving in slippery conditions," "driving in the dark," "parked," or another driving mode of operation) may cause a portable device to suppress one or more number of features (e.g., voice feature restrictions may be selectively (or automatically via vehicle control system determination) lifted (step **916**). According to an exemplary embodiment, the command provided to the portable electronic device from the vehicle control system includes a command to disable one or more of a local display of the portable electronic device, a text messaging capability of the portable electronic device, an e-mail capability of the portable electronic device, a web-browsing capability, and a media application (e.g., a photo application, a music application, a video application, a gaming application, etc.).

According to yet other exemplary embodiments, a processing circuit of the vehicle control system may further be configured to cause a vehicle audio system or a vehicle display system to prompt the user for whether a feature corresponding to the disabled portable electronic device feature should be enabled or replicated by the control system. The vehicle control system processing circuit may be configured to enable or replicate the feature based on received user input. Any vehicle control system component or subsystem may be used to enable or replicate the feature by the vehicle control system. For example, a vehicle display may be used to replicate a disabled portable electronic device display or a vehicle media player may be used to replicate a portable electronic device media player (in some embodiments, using media from the portable electronic device for playback via the vehicle audio system). If a text messaging capability is disabled on the portable electronic device based on a command received from the vehicle control system, the vehicle control system can prompt the user for whether the vehicle control system should enable a text-messaging application of the vehicle control system (e.g., using voice typing, steering wheel controls, or other vehicle user interface elements to enter the messages), and in some embodiments using the portable electronic device to transmit the text-messages to a remote source or to receive text messages for display on a vehicle display or for playback via a vehicle audio system. According to an exemplary embodiment, the vehicle control system and/or a processing circuit thereof may be configured to send a feature disabling command to the portable electronic device based on information such as a speed of the vehicle, accelerometer information, compass information, global positioning system information, and/or vehicle error codes from an engine control unit.

During "vehicle mode," "normal mode," or other switching activities, a vehicle control system may be configured with situational awareness logic for switching modes (or for conducting another portable device/vehicle control system activity) without direct user input. Referring to FIG. **10**, vehicle control system **106** is shown. Vehicle control system **106** could use any number of logic processes to determine that the vehicle is in motion, in drive, or if another vehicular operational and/or situational states (e.g., traveling at a certain speed, encountering an emergency situation, whether the airbags were released, etc.). Through a connection to vehicle control system **106**, portable device **116** could receive an indication that the vehicle is in a park mode, drive mode, or otherwise. Portable device **116** could then, after receiving the situational signal, change modes and/or change operational parameters. Vehicle control system **106** could also communicate information to the portable electronic device that causes the portable electronic device to dial 911 or another emergency number, send a text message reporting the emergency, send detailed data to a remote server regarding the emergency (e.g., vehicle location from a GPS system, the condition of the vehicle, dead reckoning information, etc.). A situational state or signal may be effected by any one or more of a user interface **126**, a vehicle subsystem **1004** (e.g., an accelerometer, etc.) directly coupled to vehicle control system **106**, a vehicle subsystem **1006** coupled to control system **106** via a vehicle data bus **1002**, or otherwise. An indication of situation may be provided to vehicle display **108**, vehicle audio system **104**, and/or via a portable device display. Vehicle subsystems **1004**, **1006** may include an engine controller, a wheel speed sensor, a transmission, a GPS receiver, a compass, a light sensor, a rain sensor, a seating sensor, an occupancy sensor, an oxygen sensor, an impact sensor, a speed sensor, an emergency system, an air bag system, a gyroscope, a breathalyzer, an accelerometer, an airbag sensor, an anti-lock brake sensor, a temperature sensor, a navigational system, or other suitable vehicle systems that may indicate a vehicle state (e.g., whether in drive, the speed of the vehicle, whether the vehicle has crashed, whether the vehicle has experienced an emergency condition, whether the vehicle is driving on a highway, whether the vehicle has cruise control engaged, etc.). The information (e.g., vehicle status information) communicated to the vehicle from vehicle subsystems can be received at an interface communicably coupling the subsystem to the vehicle control system and the vehicle control system (e.g., a processing circuit and a communications interface coupled thereto) may be configured to communicate the vehicle status information to a portable electronic device brought into the vehicle and/or to a remote source (e.g., via the portable electronic device or otherwise). According to some exemplary embodiments, vehicle status information may be formatted to be transmitted to a remote source from the portable electronic device, or may be transmitted to the portable electronic device with data for transmitting (e.g., a URL, an IP address, or another remote source identifier, etc.) the vehicle status information to the remote source from the portable electronic device.

Referring to FIG. **11**, a flow chart of a process **1100** for providing situational awareness-based activities in a vehicle is shown, according to an exemplary embodiment. Process **1100** is shown to include receiving a signal from a vehicle subsystem (step **1102**). The process may include receiving one or more signals from multiple vehicle subsystems. Based

on the signals and/or other indicators or logic, the system may be configured to make a situational determination (step **1104**) (e.g., whether an emergency has occurred, whether the vehicle is traveling too fast for texting to occur, etc.). According to an exemplary embodiment, the vehicle control system determines whether the vehicle is parked or not (step **1106**). If the vehicle is parked, the control system and/or the portable device may retrieve operational parameters associated with parking (step **1108**). The retrieved operational parameters may include a command or setting to effect the allowance of user interface activities not available when the vehicle is moving (step **1110**). If the vehicle is not parked, the vehicle control system and/or the portable device may retrieve operational parameters associated with driving (step **1112**). If the vehicle is not parked, the vehicle control system and/or the portable device may effect the restriction of user interface activities based on retrieved operational parameters or otherwise (step **1114**). A "not parked" determination may cause the portable to switch to one or more "vehicle" operational modes from a normal mode of operation. A determination that the vehicle is not parked may further change a default user interface control set to a control set configured to facilitate hands-free control and/or operation of the vehicle control system and/or the portable device (step **1116**).

Inheriting Portable Device Features

Referring now to FIG. **12**, a flow chart of a process **1200** for inheriting a feature (e.g., processing feature) of a portable device is shown, according to an exemplary embodiment. Process **1200** may include receiving a signal indicating the portable device is connected (wirelessly or wired) or otherwise ready for functional communication (step **1202**). A vehicle control system may send a request to the connected portable device to check for compatibility with a feature inheriting activity (step **1204**). After the vehicle control system receives a response from the portable device (step **1206**), the control system may be configured to make a compatibility determination (step **1208**). The compatibility determination may affect which features the vehicle attempts to inherit from the portable device. The vehicle control system may then request feature set information from the portable device (step **1210**). The feature set information may include one or more feature tables, text files listing available features, device type or class identifiers, or otherwise. The vehicle control system may be configured to receive and interpret the feature set information (step **1212**) and to map a portable device feature to a vehicle user interface element (step **1214**). For example, if the portable device includes a one-touch dialing feature, a return call button, a list N calls list, a dead reckoning feature, an emergency calling feature, or another desirable feature, the vehicle control system may map a routine or command for sending to the portable device to receiving a signal from a programmable button (e.g., on the steering wheel) or a programmable touch screen element.

Referring now to FIG. **13**, a flow chart of a process **1300** of a vehicle control system activity based on the programmed/mapped user interface element of step **1214** of process **1200** of FIG. **12** is shown, according to an exemplary embodiment. Process **1300** includes receiving a signal from a mapped user interface element (e.g., receiving a signal that a programmable button on the steering wheel has been pressed) (step **1302**). In response to the signal, the vehicle control system may retrieve or otherwise determine the appropriate command or control signal (step **1304**) for sending to the portable device (step **1306**). The command or control signal may be configured to trigger or request the execution of the desired portable device function/feature. The vehicle control system may receive a confirmation signal from the portable device in response to the command (step **1308**).

Referring now to FIG. **14**, a flow chart of a process **1400** for configuring a vehicle control system to inherit a multiple-command feature from a portable device is shown, according to an exemplary embodiment. A multiple-command feature may be a target user interface feature that is desired by the user. For example, a vehicle occupant may desire to display a recently called list on the vehicle display, but the display of the recently called list may require two commands at the portable device (e.g., a phone menu must be accessed followed by the selection of an item on the phone menu). The vehicle control system may request feature set information from the portable device (step **1402**) and receive and interpret the information (step **1404**). The feature set information received may indicate that the target user interface feature is available or not available on the portable device via multiple activities or a single command (step **1406**). If so, the user interface feature may be mapped to a command (step **1408**). The vehicle control system may parse or otherwise interpret the feature information. If the target user interface feature is only available on the device via multiple commands (step **1410**), the in-vehicle control system may be configured to build (or retrieve from memory) a macro (e.g., script, table to be parsed, text file to be parsed, etc.) based on any number of processes and/or the feature set information from the portable device (step **1414**). A vehicle user interface feature may then be mapped to the macro (step **1416**). If the target user interface feature is not available via a single command or multiple commands, a failure to set a target user interface may be indicated to a user (step **1412**).

Referring now to FIG. **15**, a flow chart of a process **1500** for a vehicle control system using the multiple-command feature of process **1400** of FIG. **14** is shown, according to an exemplary embodiment. Process **1500** includes receiving a signal from a UI feature mapped to a macro (step **1502**), parsing or executing the macro, and sending multiple commands to a portable device based on the macro (step **1504**). The vehicle control system may wait some period of time for a response from the portable device (e.g., prior to trying again or timing out) (step **1506**). According to an exemplary embodiment, the vehicle control system will wait a period of time that it expects the portable device to respond within and then begin reproducing the display of the portable device (step **1508**). This activity may help to provide a seamless transition from vehicle button press to the display of information relating to the button press. If information is sent to the vehicle control system based on the macro, the vehicle control system may send an audio signal to the vehicle audio system and/or a display signal to the vehicle display system (step **1510**).

Voice Typing to the Portable Electronic Device Using a Vehicle Control System

Referring now to FIG. **16**, a flow chart of a process **1600** for providing a voice typing function in a vehicle is shown, according to an exemplary embodiment. Voice information could be spoken and understood by the vehicle control system and communicated to the portable electronic device via a wired or wireless communication connection. The vehicle control system may include an interface coupled to an audio input device mounted to the vehicle interior for receiving the voice information, according to an exemplary embodiment. Voice information may be single words, single phrases, sequences of spoken words, sequences of utterances and/or single letters, numbers, symbols (e.g., pound, star, dot, etc.), etc. According to an exemplary embodiment, the voice information may relate to a voice command. Process **1600** may be

executed by a speech recognition module (e.g., speech recognition device **136**) of the vehicle control system, according to an exemplary embodiment.

A dictation engine could be provided in or coupled to the vehicle control system. Results from the dictation engine may be sent to the portable electronic device whenever text may be entered and/or is expected by the portable electronic device. For example, if the portable electronic device is configured for web browsing and the user seeks to enter text into a text field on a browser screen, the dictation engine may be used to recognize spoken words to generate text that should be entered in the text field. Once a complete unit of text is recognized, the text may be forwarded to the portable electronic device for entry into the text field.

The text provided to the portable electronic device may be formatted by the processing circuit of the vehicle control system, according to an exemplary embodiment. The text may be formatted such that the text characters may be entered into a text field displayed on the portable electronic device or such that the portable electronic device provides the text characters to a text-messaging application running on the device. According to various exemplary embodiments, the format may be at least one of a WAP format, a WXML format, an HTML format, an XHTML format, and an XML format.

Process **1600** includes receiving a command to begin voice typing (step **1602**). Process **1600** further include receiving a vocal utterance (or other voice information) at an interface (e.g., a microphone or other interface coupled to an audio input device) of the control system (step **1604**). One or more characters (or other units of speech) may be detected by the control system from the received utterance (or a signal representing the utterance) (step **1606**). The control system may be configured to display the recognized character or unit of speech on a display of the vehicle (step **1608**). If the control system is receiving a string of text or other units of speech, the control system may be configured to enlarge a character (or other unit of speech) as the character is detected (step **1610**). Enlarging a character may include magnifying the character and/or increasing the size of the character for display relative to adjacent characters. After recognition, a detected character may be stored in a memory device (step **1612**). The control system may delay for some period of time (step **1614**) before reducing the size of the character or otherwise displaying the detected character at a reduced size (step **1616**). The control system may then move the character on the screen or move a cursor for displaying the next character received (step **1618**). While character-by-character enlargement or magnification may be provided, an entire word or phrase may be enlarged or highlighted (e.g., bolded, underlined, etc.) if complete (step **1620**). Process **1600** may further include displaying a keyboard image on a vehicle display and highlighting images on the keyboard image. Process **1600** may further include communicating the text characters to the portable electronic device in a format that causes the portable electronic device to provide the text characters to an application running on the portable electronic device (e.g., a text-messaging application, a calendaring application, a mobile commerce application, a web-browsing application, a gaming application, a navigation application, an e-mail application, a notes application, a to-do list application, and a media application such a music, movies, or photo application, etc.).

Referring more specifically to step **1616** of process **1600**, according to an exemplary embodiment, the vehicle control system may include an interface for providing display information to an electronic display device (e.g., output display **108**) mounted to the vehicle interior. The processing circuit of the vehicle control system is configured to enter a voice-typing mode operation in process **1600** and is configured to display text characters as shown in step **1616**. According to an exemplary embodiment, during step **1616**, a recently converted text may be magnified (i.e., a recently converted text character may be magnified or larger compared to other previous converted text characters already displayed in the electronic display device.

Navigation Using a Portable Electronic Device and Vehicle Control System

Referring now to FIGS. **17-19**, systems and processes for providing improved navigational features in a vehicle using a portable electronic device are shown, according to various exemplary embodiments. Some functionalities of a portable device **1708** may utilize location coordinates or other location information. Some portable devices may include location coordinate electronics. Vehicle GPS receiver **752** and/or vehicle subsystem data (e.g., sensor data, compass data) received at the vehicle control system from subsystems **1012** (e.g., via data bus **1010**) may be used to calculate a more precise location than the location processed by portable device **116**. Processing system **754** of vehicle **100** may be configured to use transceiver **1702** to communicate location data to portable device **116** via a wired or wireless connection. Furthermore, commands or information pertaining to the vehicle's operational and/or situational modes could be communicated to portable device **116**.

Processing system **754** may be used to receive the information from receiver **752**, compass system **1706**, and other vehicle subsystems **1012** via an input such as data bus **1010**. Processing system **754** may use the information (e.g., subsystem information, position information) to calculate a precise vehicle location relative to the previously calculated or received position information. Processing system **754** may further utilize locationing information received from portable device **116** in the calculations.

Referring now to FIG. **18**, flow chart a process **1800** for a vehicle control system providing improved navigation activity is shown, according to an exemplary embodiment. Process **1800** includes receiving location information via the vehicle GPS receiver **752** (step **1802**). Location information may also be received via portable electronic device **116** and/or a GPS receiver operatively coupled (e.g., via USB) to the vehicle control system. The vehicle control system may receive vehicle sensor data directly from a vehicle sensor **1704** (step **1804**), via a vehicle compass system **1706** (step **1806**), via a vehicle data bus **1010** (step **1808**), or otherwise. Other vehicle subsystems (e.g., cruise control system, engine ECU, transmission, etc.) may send data to the vehicle control system. An improved location determination may also be based on receiving and/or processing vehicle operational and/or situational modes (step **1810**). For example, improved location determination logic may use the fact that a cruise control mode is set at a highway speed to help estimate the precise location of the vehicle in the near future. Process **1800** further includes any number of logical steps and/or considerations to provide improved/updated location information (e.g., dead reckoning) (step **1812**). The updated location information may be sent to portable device **116** and used for display, sent to a vehicle display system for display, sent to a vehicle navigation system for further processing and/or display, or otherwise (step **1814**).

Referring also to FIG. **19**, a flow chart of a process **1900** for portable device **116** is shown, according to an exemplary embodiment. Process **1900** for portable device **116** may operate in conjunction with process **1800** for a vehicle control system or otherwise. Process **1900** includes utilizing portable device navigation elements (step **1902**). Step **1902** may

include receiving updated location information from vehicle **100** and supplementing the portable device **116**'s navigational activity based on the updated location information. Portable device **116** may at some point detect a disconnect with the vehicle control system, a separation from the location information provided by the vehicle control system, and/or otherwise detect an "on foot" mode of operation (e.g., detect that portable device **116** has left the vehicle) (step **1904**). Once this detection has been made, portable device **116** may discontinue use and/or reliance on location information from the vehicle. Portable device **116** may switch from receiving location information from vehicle **100** to using location information received via the portable device **116**'s GPS receiver (step **1906**).

According to an exemplary embodiment, portable electronic device **116** may be configured to transmit the position information to another remote source (e.g., an emergency response service, a concierge service) depending on the situational mode information of the vehicle control system (e.g., whether an emergency has occurred). According to another exemplary embodiment, the vehicle control system may be configured to provide portable device **116** with the position information including data for transmitting the position information to another remote device.

A Vehicle Control System Utilizing Two Possible Communications Devices

Referring now to FIG. **20**, a flow chart of a process **2000** for utilizing two communication connections to provide for voice and/or data communications is shown, according to an exemplary embodiment. Process **2000** includes establishing a first communication connection (step **2002**) and conducting a first communication task (step **2004**). Process **2000** may include measuring the speed and/or interference of a first communication connection (step **2006**). Process **2000** may further include measuring other channels and/or the strength of signals from alternative remote sources (step **2008**). Process **2000** may further include estimating a best communications connection based on the measured information or other metric relating to the first communication connection or a potential communication connection (step **2010**). Process **2000** further includes a determination or query regarding whether the present connection is estimated to be the best (step **2012**). Process **2000** yet further includes determining whether an alternative connection is significantly better than the present connection (step **2014**). If the present connection is estimated to be the best or if the alternative connection is not significantly better than the present connection, the communication system may continue operating via the first communication connection and conducting communication tasks and return to step **2004**. If an alternative connection is significantly better than the present connection, the control system may establish a second communication connection (step **2016**). The system may then wait for idle or low communication bandwidth on the first communication connection (step **2018**) prior to switching to a second communication connection for data and/or voice communications (step **2020**). The system may then terminate the first communication connection (step **2022**). A process of the system may then define the second communication connection as the first communication connection and proceed with conducting communication tasks (step **2024**).

Generating Text Messages for Updates Between Portable Device and Vehicle Control System

Referring now to FIG. **21**, a flow chart of a process **2100** for generating a text message to trigger an update is shown, according to an exemplary embodiment. Process **2100** includes detecting a device connection (step **2102**). Once a connection is detected, the system may query a portable device for a communication capability or feature (e.g., display reproduction capabilities, voice recognition capabilities, navigation capabilities, hands-free communication capabilities, text-messaging capabilities, e-mailing capabilities, Internet capabilities, mobile-commerce capabilities, media capabilities, macro capabilities, feature replication capabilities, dead reckoning capabilities, emergency capabilities, processing capabilities, etc.) (step **2104**). The system may then receive a response from the device (step **2106**) and the system may determine whether the portable device includes the capability or feature (step **2108**). If the portable electronic device includes the capability or feature, the control system may use the capability or feature (step **2110**). The vehicle control system may also check for permission to push an update (or a new software element) to the device (step **2112**). If permission is available, the control system may push or otherwise send (e.g., via a request followed by a transmission) a software update to the portable device (step **2118**). If permission is not available (or if further confirmation is desirable), the vehicle control system may send a text message (e.g., SMS message) to the portable device, the text message representing or otherwise configured to request a software update (step **2114**). The control system may then wait for a response from the device (indicating permission or otherwise) (step **2116**) prior to sending or pushing the software update to the device (step **2118**). The software sent or pushed to the portable device may include application software, navigation software, codec software, device drivers, operating system updates, communication system updates, add-on modules, or otherwise. According to an exemplary embodiment, the vehicle control system and/or the portable electronic device can trigger updates using other than text messaging information (e.g., via a formatted request to an update application running on the portable electronic device). Further, in step **2108**, the decision step as to whether the portable device includes the capability or feature may include a check to determine whether the portable electronic device includes the latest version of the software for conducting or supporting the capability or feature. If the portable electronic device does not include the latest version of the software for conducting or supporting the capability or feature, the vehicle control system can determine that it should update the portable electronic device with the latest version of the software. According to various exemplary embodiments, in addition to (or instead of) updating the portable electronic device, processing circuitry of the vehicle control system may be configured to determine whether an update is available for the processing circuitry and/or for another vehicle subsystem. The vehicle control system processing circuitry may be configured to request the update from a remote source via the portable electronic device, to receive the update via an interface communicably coupling the portable electronic device and the vehicle control system (e.g., a wired interface, a wireless interface), and to process or install the update.

Referring now to FIG. **22**, a flow chart of a portable electronic device process **2200** for receiving a text message (e.g., the text message generated by process **2100** of FIG. **21**) to trigger an update of the portable electronic device is shown, according to an exemplary embodiment. Process **2200** includes receiving a text message from the vehicle (step **2202**). Process **2200** further includes parsing the text message (step **2204**). The parsed information may include, for example, a name, number, and message field. The fields may be used to instruct the portable device which number to dial or where to send confirmation (e.g, e-mail address, Bluetooth identifier, IP address, network address, etc.). The process

further includes responding to the text message based on the parsed information (step **2206**). The response may include a request to send an update, identifying information, and/or a confirmation to send. The portable device may then wait to receive the software update (step **2208**), receive the software update (step **2210**), install the software update (step **2212**), and/or send an additional confirmation message to the vehicle (step **2214**).

Voice Processing Using a Portable Electronic Device and a Vehicle Control System

Referring now to FIG. **23**, a block diagram of a system for providing remote voice processing is shown, according to an exemplary embodiment. Vehicle control system **106** is shown to include communication device **120** and processing system **754** as described in the disclosure. Processing system **754** includes a voice typing engine **2302**, a dictation engine **2304**, a first phoneme extractor **2306**, and a second phoneme extractor **2308**. According to various exemplary embodiments, different parts of speech may be extracted by the extractors of vehicle control system **106**. Vehicle control system **106** may generally be configured to utilize voice typing engine **2302**, dictation engine **2304**, and/or phoneme extractors **2306**, **2308** until vehicle control system **106** determines that a remote processing system **2314** should assist or handle the extraction. First phoneme extractor **2306** may be a fast phoneme extractor, configured for reduced complexity but relatively high speed. Second phoneme extractor **2308** may be a slow phoneme extractor configured for increased accuracy and extraction capability but reduced speed.

Referring also to FIG. **24**, a flow chart of a process **2400** for off-board part of speech extraction and/or voice recognition is shown, according to an exemplary embodiment. Process **2400** is shown to include the step of receiving a signal representing a vocal utterance (e.g., voice information) (step **2402**). Process **2400** is further shown to include attempting to extract a unit of speech from the next (or first) signal part (e.g., a microphone signal, a microphone signal part) (step **2404**). If vehicle control system **106** experiences difficulty with the extraction (step **2406**), the signal part may be sent to a wireless service/remote source **2316** for extraction (step **2408**). After wireless service/remote source **2316** has completed the extraction, an extracted unit of speech may be received from wireless service/remote source **2316** (step **2410**). If vehicle control system **106** determines that the signal has been fully extracted (step **2412**), system **106** may then determine whether the extraction is a recognized command (step **2414**). If the extraction is not a recognized command, the system may prompt the user for a repeat (step **2416**). If the extraction is a recognized command, system **106** may send the extracted signal to wireless service/remote source **2316** for further recognition or processing (step **2418**). System **106** may confirm a vocal utterance once a word, phrase, signal part, sentence, or otherwise has been extracted (step **2420**). Alternatively (or additionally), system **106** may confirm a vocal utterance based on brief processing or no processing, allowing the user to hear how system **106** detected the user's utterance. Remote processing may be completed via the portable device in the car, a remote processing station attached to the wireless service via the portable device, or otherwise. Further, even if a control system is not experiencing difficulty with extraction, some voice typing, dictation, or extraction tasks may be sent to a portable device or other remote processing station.

Various Exemplary Vehicle Control System Embodiments and Processes

Referring to FIGS. **25-30**, various vehicle and vehicle control system embodiments are illustrated that may be used with various of the systems and methods of the present disclosure.

Referring to FIG. **25**, an exemplary control for mounting to a vehicle interior element or for integrating with a vehicle interior element (e.g., a steering wheel) is shown, according to an exemplary embodiment. In the embodiment of FIG. **25**, he control is shown to be a directional pad **2500**, allowing the user to press an up **2510**, left **2512**, right **2514**, and down **2516** portion of the pad. The control may also be configured for pressing in on the center **2518** of the pad. At the corners of directional pad **2500** might be provided one or more programmable buttons **2502-2508**. Buttons **2502-2508** may have default settings. For example, the left arrow in the upper left corner **2502** may correspond to a "back" command, a "phone" button **2504** may correspond to a phone or hands-free feature or menu, a "menu" button **2506** may correspond to a home or root menu activity, and a "contacts" button **2508** may trigger a contacts menu or the display of contacts. It should be noted that button elements **2502-2508** may be programmed to features or macros of a connected portable device. If a new portable electronic device is brought into the vehicle and connected, the vehicle control system may be configured to automatically map one or more elements of control pad **2500** to portable device commands, features, or macros. Profile information stored in a memory device of the vehicle control system may be accessed for each connected portable electronic device, the profile information used by the vehicle control system to program one or more control elements.

Referring now to FIG. **26**, a block diagram of a vehicle communications system is shown, according to an exemplary embodiment. Government laws have been enacted to restrict use of handsets in vehicles. One method to assist adherence to these rules would be to install systems/components within the vehicle that interfere with and/or otherwise degrade the performance of certain handset functions to an extent that effectively renders them unstable. Some vehicles make handset use and communications difficult from within the interior of the vehicle. This may be due to degradation of the wireless signals to and from the handset resulting from vehicle structural materials and/or materials embedded in the vehicle glass that interfere with and/or otherwise negatively impact the signal characteristics. One or more isolation bins **2604** where a portable device **116** may be placed within vehicle **100** could be designed with equipment to avoid signal paths subject to this type of signal degradation. These bins **2604** could have the additional feature to restrict wireless signals that would otherwise contribute to signal degradation from reaching the handset (e.g., bin **2604** could be shielded). Bin **2604** may be located at a vehicle dash **2602** location or otherwise. Bin **2604** may totally enclose portable device **116** (e.g., may be closed) or bin **2604** may be permanently open on one or more sides. Isolation bin **2604** may further include be located adjacent a power supply unit (PSU) **2606**, a wired interface **2608**, and/or a wireless interface **2610**. PSU **2606** may provide a power source for isolation bin **2604** and interfaces **2608**, **2610** may be configured to connect to portable electronic device **116**. Isolation bin **2604** may further include an interface **2612** for coupling to an active, passive, or hybrid antenna module **2614** mounted to the vehicle. Isolation bin **2604** may be coupled to vehicle control system **106** and portable device **116** may communicate with vehicle control system **106** via the operative coupling between bin **2604** and vehicle control system **106**. Vehicle **100** having bin **2604** may also include a jamming device **2616** configured to jam the signal of one or more unauthorized mobile devices **2618**. Antenna module **2614** may facilitate improved communications between portable device **116** and a wireless service/remote source **2620**.

Referring to FIGS. **27-30**, various embodiments for a vehicle control system connecting via a USB interface to various remote sources are shown.

Referring now to FIG. **27**, a detailed block diagram of vehicle control system **106** is shown, according to an exemplary embodiment. Generally, a USB connector or interface **2728**, **2744** is provided within vehicle **100**. The USB interface may be embedded in vehicle control system **106** (interface **2728**) or may be coupled to vehicle control system **106** (interface **2744**). Any past, present, or future USB protocol, specification, and/or hardware standard may be utilized (e.g., USB 2.0, USB micro connectors, USB mini connectors, etc.). USB interface **2728**, **2744** may facilitate operative connection of a mobile phone **2734**, a compass system **1706**, a GPS receiver **752**, another navigation device **2740**, an access controller **2742** (e.g., a HomeLink® product sold by Johnson Controls, Inc.), a PDA **2746**, a media player **2752**, a satellite radio, a USB microphone, a wireless USB device **2750**, or another portable device that may be brought into vehicle **100** and configured to communicate via USB connection (either via USB interfaces **2728**, **2744**, or via a wireless USB transceiver **2732** embedded in vehicle control system **106**). Vehicle control system **106** may use the USB interface **2728** and/or features for charging, command and control, and/or data transfer. The USB specification includes standards for device classes. Vehicle control system **106** could be configured to support all USB specification device classes. Vehicle control system **106** could be classified as an embedded host, a host, a client, or otherwise. A handset-to-vehicle class might be provided and utilized by vehicle control system **106**. Also, a vehicle class might be provided and utilized by a portable device. A vehicle or handset-to-vehicle class might include a number of attributes for facilitating vehicle control system **106** to portable device communications. For example a button configuration attribute may be defined with possible values including characteristics of the button configuration available on vehicle **100** and/or the portable device (e.g., the number of buttons, the type (d-pad), type+ button number, etc.). A display reproduction attribute may be defined with possible values including an indication as to whether vehicle **100** or the portable device is compatible with display reproduction activities (e.g., full display, partial display, not capable, etc.). Similarly, a display reproduction resolution attribute and a display reproduction area attribute could be defined in vehicle **100** or handset-to-vehicle USB device classes so that communicating devices are may be aware of the capabilities and parameters of the connected system via some standard mechanism. A vehicle voice recognition capability attribute may also be defined. The voice recognition (VR) capability attribute may include possible values such as "Full VR Capable," "Partial VR Capable," "Phoneme Extraction Capable," "Number Recognition Capable," etc. It should be noted that one or more binary, hexadecimal, or otherwise formatted code may represent one or more of the possible values for any of the aforementioned attributes.

Referring further to FIG. **27**, a class database **2710** and/or class driver **2714** set included on control system **106** may include information and/or drivers relating to the handset-to-vehicle class **2712** and/or handset to vehicle driver **2716**. Custom drivers **2718** may alternatively (or additionally) be provided for a connected USB device. A vehicle class communication protocol stack **2720** may be provided on the vehicle. Stack **2720** may include activities that facilitate car-system specific communications and/or display reproduction communications. Control system **106** may further include a charging module **2704**, a command and control module **2706**, and a data transfer module **2708**. Modules **2704-2708** may include hardware and/or software elements configured to facilitate charging, command and control, and/or data transfer features relating to USB devices. A wireless USB host **2730** and wireless USB transceiver **2732** may be provided with or instead of a wired USB interface **2728**. Control system **106** may include a USB host controller **2724**, a root hub **2726** element, USB system software **2722**, and/or any other processing element, memory, drivers, hardware circuitry, and/or software circuitry configured to facilitate operative vehicle to portable device communications via a USB connection.

Referring now to FIG. **28**, vehicle control system **106** having USB interface **2728** is shown, according to an exemplary embodiment. USB interface **2728** is shown coupled to a USB interface **2804** of portable device **116**. Vehicle control system **106** may include a vehicle USB class identifier **2802** for communicating to portable device **116**. Portable device **116** is shown to include a "vehicle class" device driver **2806** and a host controller **2808**. Advantageously, this may allow vehicle control system **106** and/or portable device **116** to communicate according to known attributes, common device drivers, common communication protocols, and the like. For example, a "vehicle class" device may include a number of attributes and methods specific to vehicle data or vehicle features.

Referring now to FIG. **29**, a block diagram of vehicle control system **106** is shown, according to an exemplary embodiment. Vehicle control system **106** is shown coupled to a modem device **2900** via a USB connection (e.g., via USB interfaces **2728**, **2910**). Vehicle control system **106** may be configured to communicate with a wireless service and/or a remote source via communications module **2912** of USB modem **2900**. Vehicle control system **106** is shown to include a browser module **2902**, modem application software **2904**, a modem device driver **2906**, and a communication stack **2908** compatible with modem **2900**. Vehicle control system **106** may use USB modem **2900** and browser module **2902** for web browsing activities or other communications activities. Advantageously, USB modem **2900** may be provided for different and/or upgraded communications without changing mobile phones or changing an embedded phone of the vehicle. USB modem **2900** may be any USB modem of the past, present, or future including, for example a GSM modem, a CDMA modem, a 3G modem, a GPRS modem, a UMTS modem, an HSDPA modem, etc.

Referring now to FIG. **30**, vehicle control system **106** for communicating with a wireless service or a remote source via a USB-connected wireless communication device **3030** is shown, according to an exemplary embodiment. According to an exemplary embodiment, wireless communication device **3030** is a WiFi device or a WiMax device. Control system **106** is shown to include a connection point (e.g., WiFi "hot spot") database **3014**. Connection point database **3014** may be used to store information regarding the location of areas within which or near which wireless communication device **3030** is estimated to be able to operatively connect to a network. GPS system **3006** may use database **3014** to display potential areas for connectivity to a user. GPS system **3006** may be used to calculate a route to the potential area for connectivity based on connection point database **3014**. A network detection application **3016** may alternatively or additionally be provided to control system **106**. Network detection application **3016** may be configured to use wireless communication device **3030** to detect available networks regardless of whether wireless communication device **3030** is already connected to another network.

Referring still to FIG. **30**, control system **106** includes a connection manager **3004**, according to an exemplary embodiment. Connection manager **3004** may be a logic module (e.g., hardware circuitry configured to execute computer code) configured to provide an operative communication connection whenever possible from a vehicle to a wireless service and/or remote source. Connection manager **3004** may be configured to switch between communicating using wireless communication device **3030** and communicating using on a second communication device embedded (or otherwise coupled to) control system **106**. A communication device switching module **3012** may be used to switch from a first communication device to a second communication device during voice and/or data communications without revealing the switch to the user. Alternatively, the switch may be revealed to the user but occurs automatically so that the user need not manually command control system **106** to connect or reconnect via the one or more devices. A user interface module **3010** for the configuration of wireless communication device **3030** may be provided in control system **106**. User interface module **3010** may present the user with fields, options, or available networks for configuring wireless communication device **3030**. Control system **106** further includes a security module **3018** for configuration of wireless communication device **3030** security features. Security module **3018** may be configured to negotiate encryption features, to conduct encryption tasks, decryption tasks, authentication tasks, password tasks, or otherwise. Device driver **3022** may be configured to allow higher level software to interact with the hardware with the hardware of, for example, communication device **120**, USB interface **2728**, and/or wireless communications device **3030**. Browser module **3008** may be configured to provide a user of the vehicle control with web-browser functionality for viewing Internet sites, Intranet sites, locally stored HTTP pages, or otherwise.

While the exemplary embodiments illustrated in the figures and described herein are presently preferred, it should be understood that the embodiments are offered by way of example only. Accordingly, the present application is not limited to a particular embodiment, but extends to various modifications that nevertheless fall within the scope of the appended claims.

The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system.

The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a machine, the machine properly views the connection as a machine-readable medium. Thus, any such connection is properly termed a machine-readable medium. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

Although the figures may show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

What is claimed is:

1. A control system for mounting in a vehicle and for providing information to a portable electronic device for processing by the portable electronic device, the control system comprising:

a first interface for communicating with the portable electronic device;

a second interface for coupling to an audio input device mounted to the vehicle interior and for receiving voice information from a user;

a third interface for providing display information to an electronic display device mounted to the vehicle interior;

a memory device;

a processing circuit communicably coupled to the first interface and the memory device, wherein the processing circuit comprises a speech recognition module configured to convert the voice information received at the second interface into text characters, wherein the processing circuit configured to:

determine the capabilities of the portable electronic device based on data received from the portable electronic device via the first interface;

determine whether to communicate the information to the portable electronic device based on the determined capabilities;

extract information from the memory device and to provide the information to the first interface so that the first interface communicates the information to the portable electronic device, wherein the information

communicated to the portable electronic device comprises the text characters from the speech recognition module;

enter a voice-typing mode of operation, wherein, during the voice-typing mode of operation, the processing circuit is configured to cause the electronic display device to display the text characters from the speech recognition module; and

magnify a recently converted text character relative to previously converted text characters on the electronic display device.

2. The control system of claim **1**, wherein the processing circuit is further configured to communicate the text characters to the portable electronic device in a format that causes the text characters to be entered into a text field displayed on the portable electronic device.

3. The control system of claim **1**, wherein the processing circuit is further configured to communicate the text characters to the portable electronic device in a format that causes the portable electronic device to provide the text characters to an application running on the portable electronic device, wherein the application is at least one of: a text-messaging application, a calendaring application, a mobile commerce application, a web-browsing application, a gaming application, a navigation application, an e-mail application, a media application, and a notes application.

* * * * *