



US008970513B2

(12) **United States Patent**
Kwon et al.

(10) **Patent No.:** **US 8,970,513 B2**
(45) **Date of Patent:** **Mar. 3, 2015**

(54) **TOUCH PANEL HAVING DEFORMABLE ELECTROACTIVE POLYMER ACTUATOR**

(75) Inventors: **Jong-oh Kwon**, Suwon-si (KR);
Seung-Tae Choi, Hwaseong-si (KR);
Seong-Taek Lim, Suwon-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 331 days.

5,055,840 A	10/1991	Bartlett
5,222,895 A	6/1993	Fricke
5,856,822 A	1/1999	Du et al.
5,977,867 A	11/1999	Blouin
6,118,435 A	9/2000	Fujita et al.
6,278,439 B1	8/2001	Rosenberg et al.
6,317,116 B1	11/2001	Rosenberg et al.
6,429,846 B2	8/2002	Rosenberg et al.
6,809,462 B2	10/2004	Pelrine et al.
7,051,292 B2	5/2006	Nagase
7,067,756 B2	6/2006	Cok
7,131,073 B2	10/2006	Rosenberg et al.
7,196,688 B2	3/2007	Schena
7,202,837 B2	4/2007	Ihara

(Continued)

(21) Appl. No.: **13/050,550**

(22) Filed: **Mar. 17, 2011**

(65) **Prior Publication Data**

US 2012/0086651 A1 Apr. 12, 2012

(30) **Foreign Application Priority Data**

Oct. 11, 2010 (KR) 10-2010-0098961

(51) **Int. Cl.**

G06F 3/041 (2006.01)

G06F 3/01 (2006.01)

G06F 3/045 (2006.01)

(52) **U.S. Cl.**

CPC **G06F 3/016** (2013.01); **G06F 3/041**
(2013.01); **G06F 3/045** (2013.01)

USPC **345/173**

(58) **Field of Classification Search**

USPC 345/173

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,923,057 A 5/1990 Carlson et al.
4,963,417 A 10/1990 Taniguchi et al.

FOREIGN PATENT DOCUMENTS

CN 1678978 A 10/2005
CN 1829951 A 9/2006

(Continued)

OTHER PUBLICATIONS

Extended European search report dated Oct. 7, 2010 issued by the European Patent Office in counterpart European Application No. 10166013.2.

(Continued)

Primary Examiner — Long D Pham



(74) *Attorney, Agent, or Firm* — Sughrue Mion, PLLC

(57)

ABSTRACT

A touch panel is provided. The touch panel includes an electroactive polymer (EAP) actuator which is deformable when protruded or depressed locally at a part to which a driving voltage is applied; and a flexible touch sensor which is disposed on the EAP actuator. The flexible touch sensor is deformable locally in correspondence with a deformation of the EAP actuator, and senses an input according to a contact or pressing operation.

15 Claims, 16 Drawing Sheets



Valve Exhibit 1012
Valve v. Immersion

(56)

References Cited

U.S. PATENT DOCUMENTS

7,268,770	B1	9/2007	Takahata et al.	
7,339,572	B2	3/2008	Schena	
7,342,573	B2	3/2008	Ryynaenen et al.	
7,436,396	B2	10/2008	Akieda et al.	
7,477,242	B2	1/2009	Cross et al.	
7,511,706	B2	3/2009	Schena	
7,589,714	B2	9/2009	Funaki	
7,598,949	B2	10/2009	Han	
7,608,976	B1	10/2009	Cheng et al.	
7,679,611	B2	3/2010	Schena	
7,688,080	B2	3/2010	Golovchenko et al.	
7,719,167	B2	5/2010	Kwon et al.	
8,164,573	B2	4/2012	DaCosta et al.	
8,345,013	B2	1/2013	Heubel et al.	
8,493,131	B2	7/2013	Mo et al.	
8,581,866	B2	11/2013	Park et al.	
2001/0026636	A1*	10/2001	Mainguet	382/124
2001/0035854	A1	11/2001	Rosenberg et al.	
2002/0033795	A1	3/2002	Shahoian et al.	
2002/0039620	A1	4/2002	Shahinpoor et al.	
2002/0101410	A1	8/2002	Sakata et al.	
2003/0016849	A1	1/2003	Andrade	
2004/0090426	A1	5/2004	Bourdelaïs et al.	
2005/0057528	A1*	3/2005	Kleen	345/173
2005/0076824	A1*	4/2005	Cross et al.	116/205
2005/0130604	A1	6/2005	Chipchase et al.	
2005/0200286	A1	9/2005	Stoschek et al.	
2005/0285846	A1	12/2005	Funaki	
2006/0097991	A1	5/2006	Hotelling et al.	
2006/0099808	A1	5/2006	Kondo	
2006/0103634	A1	5/2006	Kim et al.	
2006/0119589	A1	6/2006	Rosenberg et al.	
2007/0080951	A1	4/2007	Maruyama et al.	
2007/0152974	A1	7/2007	Kim et al.	
2007/0152982	A1	7/2007	Kim et al.	
2007/0182718	A1	8/2007	Schoener et al.	
2007/0211032	A1	9/2007	Ahn et al.	
2007/0229464	A1	10/2007	Hotelling et al.	
2008/0007815	A1	1/2008	Liang et al.	
2008/0024459	A1	1/2008	Poupyrev et al.	
2008/0024461	A1*	1/2008	Richter et al.	345/173
2008/0036746	A1	2/2008	Klinghult	
2008/0100590	A1	5/2008	Hur et al.	
2008/0111788	A1	5/2008	Rosenberg et al.	
2008/0143689	A1	6/2008	Foo et al.	
2008/0158169	A1	7/2008	O'Connor et al.	
2008/0165134	A1	7/2008	Krah	
2008/0165158	A1	7/2008	Hotelling et al.	
2008/0284277	A1*	11/2008	Kwon et al.	310/309
2009/0002199	A1*	1/2009	Lainonen et al.	341/20
2009/0002328	A1	1/2009	Ullrich et al.	
2009/0046065	A1	2/2009	Liu et al.	
2009/0046068	A1	2/2009	Griffin	
2009/0075694	A1	3/2009	Kim et al.	
2009/0085878	A1	4/2009	Heubel et al.	
2009/0182501	A1	7/2009	Fyke et al.	
2009/0231305	A1	9/2009	Hotelling et al.	
2009/0250267	A1*	10/2009	Heubel et al.	178/18.03
2009/0308737	A1	12/2009	Kudoh	
2010/0024573	A1	2/2010	Daverman et al.	
2010/0026654	A1	2/2010	Suddreth	
2010/0026655	A1	2/2010	Harley	
2010/0059295	A1	3/2010	Hotelling et al.	
2010/0060610	A1	3/2010	Wu	
2010/0149108	A1	6/2010	Hotelling et al.	
2010/0156829	A1	6/2010	Shimodaira	
2010/0177050	A1	7/2010	Heubel et al.	
2010/0214232	A1	8/2010	Chan et al.	
2010/0244858	A1	9/2010	Cormier, Jr.	
2010/0259485	A1	10/2010	Chuang	
2010/0321330	A1	12/2010	Lim et al.	
2010/0321335	A1	12/2010	Lim et al.	
2011/0057899	A1	3/2011	Sleeman et al.	
2011/0163978	A1	7/2011	Park et al.	
2011/0181530	A1	7/2011	Park et al.	

2011/0227862	A1	9/2011	Lim
2011/0279374	A1	11/2011	Park et al.
2012/0019467	A1	1/2012	Hotelling et al.
2012/0038563	A1	2/2012	Park et al.
2012/0086651	A1	4/2012	Kwon et al.
2012/0127122	A1	5/2012	Lim
2012/0262410	A1	10/2012	Lim

FOREIGN PATENT DOCUMENTS

CN	101046720	A	10/2007
CN	101510008	A	8/2009
CN	101840296	A	9/2010
EP	1 544 720	A1	6/2005
EP	2 026 178	A1	2/2009
EP	2 141 569	A2	1/2010
EP	2 079 052	B1	3/2011
JP	6-34940	A	2/1994
JP	09-319509	A	12/1997
JP	11-203025	A	7/1999
JP	11-273501	A	10/1999
JP	2000-066782	A	3/2000
JP	2001-282433	A	10/2001
JP	2002-157087	A	5/2002
JP	2002-236550	A	8/2002
JP	2002-342035	A	11/2002
JP	2004-71765	A	3/2004
JP	2004-362428	A	12/2004
JP	2005-107804	A	4/2005
JP	2005-135876	A	5/2005
JP	2005-275632	A	10/2005
JP	2006-011646	A	1/2006
JP	2006-146611	A	6/2006
JP	2007-513392	A	5/2007
JP	2008-33739	A	2/2008
JP	2008-257748	A	10/2008
JP	2010-016969	A	1/2010
JP	2010-079882	A	4/2010
JP	2010-108505	A	5/2010
JP	2011-3177	A	1/2011
JP	2012-500089	A	1/2012
KR	91-14838	A	8/1991
KR	10-2001-0054523	A	7/2001
KR	10-2004-0058731	A	7/2004
KR	10-2005-0029285	A	3/2005
KR	10-2006-0053769	A	5/2006
KR	10-2006-0075135	A	7/2006
KR	10-2006-0118640	A	11/2006
KR	10-2006-0125544	A	12/2006
KR	10-2007-0011524	A	1/2007
KR	10-2007-0070897	A	7/2007
KR	10-2007-0093251	A	9/2007
KR	10-2008-0061047	A	7/2008
KR	10-2008-0100757	A	11/2008
KR	10-0877067	B1	1/2009
KR	10-2009-0011367	A	2/2009
KR	10-2009-0029520	A	3/2009
KR	10-0901381	B1	6/2009
KR	10-2009-0087351	A	8/2009
KR	10-2009-0101292	A	9/2009
KR	10-2009-0126760	A	12/2009
KR	10-2010-0011368	A	2/2010
KR	10-2010-0020065	A	2/2010
KR	10-2010-0136759	A	12/2010
WO	02/089038	A2	11/2002
WO	03/050754	A1	6/2003
WO	2004/014115	A1	2/2004
WO	2004/053909	A1	6/2004
WO	2004/106099	A1	12/2004
WO	2005/010735	A1	2/2005
WO	2005/091257	A1	9/2005
WO	2008/037275	A1	4/2008
WO	2009/002605	A1	12/2008
WO	2010105705	A1	9/2010

OTHER PUBLICATIONS

US Advisory Action, dated Apr. 26, 2013, issued in U.S. Appl. No. 12/849,310.

(56)

References Cited

OTHER PUBLICATIONS

Final US Office Action, dated Dec. 20, 2012, issued in U.S. Appl. No. 12/849,310.
Non-Final US Office Action, dated Aug. 28, 2012, issued in U.S. Appl. No. 12/849,310.
Final US Office Action, dated Mar. 27, 2013, issued in U.S. Appl. No. 12/948,479.
Non-Final US Office Action, dated Oct. 15, 2012, issued in U.S. Appl. No. 12/948,479.
Non-Final US Office Action, dated Feb. 1, 2013, issued in U.S. Appl. No. 13/103,221.
Non-Final US Election Requirement, dated Apr. 10, 2013, issued in U.S. Appl. No. 13/097,937.
European Communication, dated Mar. 19, 2013, issued in European Application No. 11150285.2.
Non-Final US Office Action, dated May 7, 2013, issued in U.S. Appl. No. 12/719,281.
Non-Final US Office Action, dated Mar. 15, 2013, issued in U.S. Appl. No. 12/889,800.
Communication, dated Mar. 4, 2014, issued by the Japanese Patent Office in counterpart Japanese Patent Application No. 2010-133879.
Notice of Allowance, dated Mar. 28, 2014, issued in related U.S. Appl. No. 12/849,310.
Final US Office Action, dated Apr. 3, 2014, issued in related U.S. Appl. No. 12/889,800.
Final US Office Action, dated Mar. 7, 2014, issued in related U.S. Appl. No. 13/097,937.
Non-Final US Office Action, dated Mar. 7, 2014, issued in related U.S. Appl. No. 13/224,422.
Final US Office Action dated Nov. 22, 2013 issued in U.S. Appl. No. 12/849,310.

Non-Final US Office Action dated Jun. 20, 2013, issued in U.S. Appl. No. 12/780,996.
Non-Final US Office Action dated Jul. 8, 2013, issued in U.S. Appl. No. 12/849,310.
Non-Final US Office Action dated Aug. 16, 2013, issued in U.S. Appl. No. 12/889,800.
Non-Final US Office Action dated Jul. 17, 2013, issued in U.S. Appl. No. 13/097,937.
Non-Final US Office Action dated Dec. 6, 2013, issued in U.S. Appl. No. 13/190,120.
Non-Final US Office Action dated Aug. 12, 2013, issued in U.S. Appl. No. 13/224,422.
US Notice of Allowance dated Sep. 19, 2013, issued in U.S. Appl. No. 12/719,281.
US Notice of Allowance dated Oct. 25, 2013, issued in U.S. Appl. No. 12/780,996.
Chinese Office Action dated Oct. 10, 2013, issued in a corresponding Chinese Patent Application No. 201010200349.1.
Non-Final US Office Action dated Feb. 10, 2014, issued in U.S. Appl. No. 12/719,281.
US Notice of Allowance dated Jan. 22, 2014, issued in U.S. Appl. No. 12/780,996.
Communication issued Oct. 16, 2014, by the European Patent Office in related Application No. 11186005.2.
Communication issued Oct. 29, 2014, by the State Intellectual Property Office of P.R. China in related Application No. 201010280797.7.
Communication issued Sep. 30, 2014, by the Japanese Patent Office in related Application No. 2010-265704.
Communication issued Oct. 8, 2014, by the State Intellectual Property Office of P.R. China in related Application No. 201010609836.3.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7A




FIG. 7B




FIG. 8




FIG. 9A





FIG. 9B



1

TOUCH PANEL HAVING DEFORMABLE ELECTROACTIVE POLYMER ACTUATOR

CROSS-REFERENCE TO RELATED APPLICATION

This application claims priority from Korean Patent Application No. 10-2010-0098961, filed Oct. 11, 2010, the entire disclosure of which is incorporated herein by reference for all purposes.

BACKGROUND

1. Field

The following description relates to a user interface, and more particularly, to a touch panel.

2. Description of the Related Art

A touch panel is one example of a kind of user input device used to determine whether a user generates an input and the position of the user's input by sensing the user's contact thereon. A user may input data or signals to a touch panel by contacting or pressing a surface of the touch panel with a finger, a stylus pen or the like. The touch panel may be used as a touch pad functioning as a substitute for a mouse in a laptop computer or a netbook, etc., or used in place of an input switch of an electronic device. Also, the touch panel may be used in association with a display. A touch panel which is mounted on the screen of a display device, such as a liquid crystal display (LCD), a plasma display panel (PDP), a cathode ray tube (CRT) and the like, is generally called a "touch screen". A touch panel may be integrated with a display device to configure the screen of the display or may be attached additionally on the screen of the display.

In certain situations, a touch panel may be substituted for a user input device such as a keyboard, a trackball, or a mouse, and also may allow for simple manipulations. Moreover, the touch panel can provide users with various types of buttons according to the types of applications to be executed or stages of the executed application. Accordingly, a touch panel, and more specifically, a touch screen, has been used as an input device for electronic equipment, such as a mobile phone, a personal digital assistant (PDA), a portable multimedia player (PMP), a digital camera, a portable game, a Moving Picture Experts Group Layer-3 (MP3) player, etc., as well as an automated teller machine (ATM), an information trader, a ticket vending machine, etc.

A touch panel can be classified into a resistive type, a capacitive type, a saw type, an infrared type, etc., according to methods of sensing user's inputs. A capacitive type touch panel determines whether a user generates an input and the position of the user's input by measuring variations in capacitance due to contact or pressure. However, the capacitive type touch panel fails to offer users a sense of input, that is, a feeling of recognition that a user gets upon inputting. In order to overcome this disadvantage, a method of installing a vibration motor under a touch panel has been proposed. The method offers users a sense of input by vibrating the whole touch panel using the vibration motor when a user's contact is sensed. Recently, a method of offering various senses of inputs by adjusting the magnitude or frequency of vibration has been developed.

SUMMARY

One or more embodiments relate to a touch panel that can output various signals which a user can recognize through tactile sense according to the kinds or stages of applications and/or the user's selection.

2

One or more embodiments also relate to a touch panel which allows a user to recognize an input button through tactile sense.

According to an aspect of an embodiment, there is provided a touch panel including an electroactive polymer (EAP) actuator which is deformable when protruded or depressed locally at a part to which a driving voltage is applied; and a flexible touch sensor which is disposed on the EAP actuator, is deformable locally in correspondence with a deformation of the EAP actuator, and senses an input according to a contact or pressing operating.

According to an aspect of another embodiment, there is provided a touch panel including a multi-layered electroactive polymer (EAP) actuator body including a plurality of polymer thin films that are formed with EAP and have a stacked structure, and a plurality of driving electrodes disposed between each of the polymer thin films; a flexible touch sensor which is disposed on the multi-layered EAP actuator body, and which includes a piezoelectric layer formed from a piezoelectric polymer, and a plurality of sensing electrodes formed on the piezoelectric layer, wherein current generated when the piezoelectric layer is pressed flows through the sensing electrodes; a driving unit electrically connected to the driving electrodes and applying a driving voltage to the driving electrodes to form an electric field locally in the polymer thin films; and a sensing unit electrically connected to the sensing electrodes and sensing current flowing through the sensing electrodes to detect an input location at which the piezoelectric layer is pressed.

Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and/or other aspects will be more apparent from the following detailed description taken with reference to the accompanying drawings, in which:

FIG. 1 is a diagram illustrating an example of a touch panel according to an embodiment;

FIG. 2 illustrates a touch panel body of the touch panel illustrated in FIG. 1;

FIGS. 3A and 3B are perspective views illustrating two types of unit layers included in an electro-active polymer (EAP) actuator body of FIG. 2;

FIG. 4 is a plan view illustrating an example of a shape that is displayed using driving electrodes arranged in a matrix form;

FIG. 5 is a cross-sectional view cut along a X-Y line of FIG. 4;

FIGS. 6A through 6E are views for explaining an example of a method of sequentially outputting signals to display the shape illustrated in FIG. 4 using an EAP actuator body including a structure in which a pair of unit layers illustrated in FIGS. 3A and 3B are stacked;

FIGS. 7A and 7B are a perspective view and a cross-sectional view showing a bumpy member of FIG. 2;

FIG. 8 is a cross-sectional view for explaining a driving state of a touch panel including the bumpy member of FIG. 7B; and

FIGS. 9A and 9B illustrate examples of touch panels according to other embodiments.

DETAILED DESCRIPTION

The following description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. Accordingly,

3

various changes, modifications, and equivalents of the methods, apparatuses, and/or systems described herein will be suggested to those of ordinary skill in the art. Also, descriptions of well-known functions and constructions may be omitted for increased clarity and conciseness. The meanings of terms used in the following examples follow given definitions, and terms not explicitly defined in the specification should be interpreted using meanings that are known to those skilled in the art. For example, the meaning that a first material layer is formed on a second material layer includes the case in which a third material layer is inserted between the first and second material layers, if no description excluding the case is given, as well as the case where the first material layer is formed directly on the second material layer.

Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference numerals will be understood to refer to the same elements, features, and structures. The relative size and depiction of these elements may be exaggerated for clarity, illustration, and convenience.

In this description, a touch panel is one example of a user input device, and may be included in various kinds of electronic devices. For example, the touch panel may be used as a user input device for various kinds of home and office appliances, as well as a touch pad for a notebook, a netbook, etc. Also, the touch panel may be mounted on the display of an electronic device and used as a touch screen. For example, a touch panel, specifically, a touch screen has been widely used as an input device for electronic equipment, such as a mobile phone, a PDA, a PMP, an E-book terminal, etc., as well as an ATM, an information trader, a ticket vending machine, etc.

Also, a touch panel may be mounted on the surface of an electronic device and used as an input/output device. For example, a touch panel may be used as input buttons (for example, navigation keys) of a mobile phone or a mobile multimedia player, or may provide various output signals (for example, letters, figures, simple symbols such as arrows) which a user can recognize through tactile sense. The input buttons or output signals may depend on a user's selection and/or the kinds or stages of applications. For this, a touch panel may include an actuator allowing local deformation, and a flexible sensor that may be deformable in correspondence to deformation of the actuator. The actuator and flexible sensor will be described in detail later.

FIG. 1 is a diagram illustrating an example of a touch panel A according to an embodiment.

Referring to FIG. 1, the touch panel A includes a touch panel body 10, a sensing unit 20, and a driving unit 30. The touch panel body 10 indicates a physical structure of the touch panel A. The sensing unit 20 and the driving unit 30 may be electrical circuits and/or hardware/software which senses an input onto the touch panel body 10, drives the touch panel body 10, and controls the operation of the touch panel body 10. The term "touch panel" used in the following description may be used to indicate only the touch panel body 10 in a narrow sense, or may be used in a broad sense to indicate the whole touch panel A including the sensing unit 20 and driving unit 30.

In FIG. 1, the sensing unit 20 and the driving unit 30 are shown as separate units depending on logical classification according to their functions. However, alternatively, they may be integrated into a single unit. Also, the logical function classification of the sensing unit 20 and the driving unit 30 is also for convenience of description, and any other integrated component may perform all functions that can be performed by the sensing unit 20 and the driving unit 30, or some functions that are performed by any one of the sensing unit 20

4

and the driving unit 30 may be performed by the other one. Also, the touch panel A may further include a controller (not shown) which controls the operation of the sensing unit 20 and the driving unit 30. Moreover, the functionality of the sensing unit 20 and the driving unit 30 may be performed by at least one central processing unit (CPU) of a computer. Hereinafter, the structure and operation of the touch panel body 10 will be described.

FIG. 2 is a perspective view illustrating a schematic structure of the touch panel body 10. In FIG. 2, the touch panel body 10 is shown to have a square shape. However, this is only exemplary. That is, the shape of the touch panel body 10 may be variously shaped, and the shape may depend on the kind or installation position of an electronic device on which the touch panel A (see FIG. 1) is mounted, and/or the purpose of the touch panel A. Referring to FIG. 2, the touch panel body 10 may include an actuator body 110, a sensor body 120, and a bumpy member 130.

The actuator body 110 indicates the physical structure of an actuator which is deformed when protruded or depressed locally at areas to which driving voltages have been applied. For example, the actuator may be made of electro-active polymer (EAP) or piezoelectric ceramic that is a high molecule material deformable by electrical stimuli, and may be deformed locally at areas where driving voltages are applied to form an electric field. Since an EAP actuator, whose deformation rate is maximally 5%, has a higher deformation rate than other actuators (for example, a piezoelectric ceramic actuator has a deformation rate of maximally 0.2%), the EAP actuator may cause a relatively great displacement even when the EAP actuator is fabricated with a small size.

The EAP actuator generally causes a displacement of several % under an electric field of about 20 to about 150 V/ μ m. Accordingly, in order to obtain a great displacement (for example, a displacement of about 3 to about 7%) from an EAP actuator made of polymer having the thickness of about 10 μ m, a driving voltage from about 200 to about 1500 V is needed. Such a high driving voltage makes application of an existing EAP actuator to an electronic device such as a mobile device which tends to require a relatively low driving voltage (for example, below 24V) difficult. Korean Patent Application No. 2008-0100757 entitled "Electroactive Actuator and Fabrication Method thereof", filed and laid-open by the same applicant, proposes a multi-layered EAP actuator as a method for reducing a driving voltage of an EAP actuator.

A multi-layered EAP actuator is formed by stacking a plurality of thin polymer films and arranging driving electrodes between the polymer films, wherein opposite voltages are applied to both sides of each polymer film. The actuator body 110 may be a multi-layered EAP actuator body that is formed by stacking a plurality of unit layers each layer including an EAP thin film made of electroactive polymer and driving electrodes formed on the EAP thin film. Specifically, the multi-layered EAP actuator body 110 may have a structure where two types of unit layers are alternately stacked, the two types of unit layers constructing a pair of unit layers, in order to alternately apply different voltages to the driving voltages of the respective unit layers.

FIGS. 3A and 3B are perspective views illustrating the two types of unit layers included in the EAP actuator body 110. For example, when it is assumed that the multi-layered EAP actuator body 110 has a structure where ten unit layers are stacked, the odd-numbered layers (that is, the first, third, fifth, seventh, and ninth layers) of the ten unit layers may each have a structure 112 (hereinafter referred to as a "first unit layer") illustrated in FIG. 3A, and the even-numbered layers (that is, the second, fourth, sixth, eighth, and tenth layers) may each

have a structure **114** (hereinafter referred to as a “second unit layer”) illustrated in FIG. 3B. Alternatively, it is also possible that the odd-numbered layers (that is, the first, third, fifth, seventh, and ninth layers) of the ten unit layers each is the second unit layer **114**, and the even-numbered layers (that is, the second, fourth, sixth, eighth, and tenth layers) each is the first unit layer **112**.

Referring to FIGS. 3A and 3B, the first unit layer **112** includes a first polymer thin film **1120** and a plurality of first driving electrodes **1122** formed on a surface of the first polymer thin film **1120**, and the second unit layer **114** includes a second polymer thin film **1140** and a plurality of second driving electrodes **1142** formed on a surface of the second polymer thin film **1140**. Also, the first and second driving electrodes **1122** and **1142** include a plurality of electrode lines **1122a** through **1122h**, and **1142a** through **1142h**, respectively, as shown in FIGS. 3A and 3B. The electrode lines **1142a** through **1142h** (hereinafter, referred to as second electrode lines) of the second driving electrodes **1142** extend perpendicular to the electrode lines **1122a** through **1122h** (hereinafter, referred to as first electrode lines) of the first driving electrodes **1122**.

The first and second polymer thin films **1120** and **1140** may be made of a dielectric polymer material which is deformable by electrical stimuli. For example, the first and second polymer thin films **1120** and **1140** may be formed with silicon (or polyurethane) dielectric elastomers, ferro-electric polymer such as Poly Vinylidene Fluoride (PVDF) polymer or Poly (Vinylidene Fluoride-TriFluoroEthylene) (P(VDF-TrFE)) polymer, or relaxor ferro-electric polymer such as Poly (Vinylidene Fluoride-TriFluoroEthylene-CloroTriFluoroEthylene (P(VDF-TrFE-CFE) polymer or Poly (Vinylidene Fluoride-TriFluoroEthylene-CloroTriFluoroEthylene (P(VDF-TrFE-CFTE) polymer. The first and second polymer thin films **1120** and **1140** made of such dielectric polymer may have a thin thickness of about 2 μm or less.

The P(VDF-TrFE-CFTE) polymer and P(VDF-TrFE-CFE) polymer among the above-mentioned dielectric polymers have a property that the polymer contracts in the direction in which a voltage is applied but stretches in the direction perpendicular to the direction in which the voltage is applied. Also, the P(VDF-TrFE-CFTE) polymer and P(VDF-TrFE-CFE) polymer show a greatest displacement (maximally about 4%) with respect to a low driving voltage (for example, about 100V or less) among the above-mentioned dielectric polymers. Furthermore, the P(VDF-TrFE-CFTE) polymer and P(VDF-TrFE-CFE) polymer improve, after they are crosslinked, a thermal resistance (about 200° C. or more), increase a driving displacement, and also show high visible light transmission of about 90% or more. Accordingly, the first and second polymer thin films **1120** and **1140** formed with crosslinked P(VDF-TrFE-CFTE) or P(VDF-TrFE-CFE) polymer can be applied to a wider variety of applications.

The first and second driving electrodes **1122** and **1142** may be formed with a flexible, conductive material which is deformable in correspondence to local deformation of the polymer thin films **1120** and **1140**. For example, the first and second driving electrodes **1122** and **1142** may be formed with transparent, conductive polymer, such as polyaniline, polypyrrole, PEDOT [Poly(3,4-EthyleneDiOxyThiophene)]:PSS [Poly(4-StyreneSulfonic acid)], polythiophen, etc.

Since the EAP actuator body **110** is formed by stacking a plurality of unit layer pairs each pair including a first unit layer **112** and a second unit layer **114** placed on the first unit layer **112**, driving electrodes are defined in a matrix form at intersections of the first and second electrode lines **1122a** through **1122h** and **1142a** through **1142h** that are arranged

perpendicular to each other, as illustrated in FIGS. 3A and 3B. That is, the EAP actuator body **110** includes driving electrodes arranged in a matrix form. When the driving electrodes arranged in a matrix form are electrically connected to be individually driven, the EAP actuator body **110** may be deformed to display a shape, such as a letter, a figure, a simple symbol, etc.

FIG. 4 is a plan view illustrating an example of a shape that is displayed using the driving electrodes arranged in a matrix form, and FIG. 5 is a cross-sectional view cut along a X-Y line of FIG. 4. FIG. 4 corresponds to the case where driving voltages are applied only to 15 driving electrodes among total of 64 driving electrodes to display a right directional arrow. Also, FIG. 5 shows the case where a driving area is protruded upward. Alternatively, it is also possible that a driving area is depressed downward. Referring to FIGS. 4 and 5, areas to which driving voltages are applied, that is, polymer thin films **1120** and **1140** corresponding to driving areas, are deformed to be protruded upward, whereas areas to which no driving voltage is applied, that is, polymer thin films **1120** and **1140** corresponding to non-driven areas, are not deformed. Accordingly, by appropriately combining driving areas through application of driving voltages, the EAP actuator body **110** may be deformed to display a shape, such as a letter, a figure, a simple symbol, etc.

As such, in order for the EAP actuator body **110** to be locally deformed, the first or second driving electrodes **1122** and **1142** may be formed in a pattern on the first and second polymer thin films **1120** and **1140**, respectively. For example, as illustrated in FIGS. 3A and 3B, when the first and second driving electrodes **1122** and **1142** are defined by the first and second electrode lines **1122a** through **1122h** and **1142a** through **1142h**, respectively, that extend perpendicular to each other, the EAP actuator body **110** is deformable.

In more detail, when driving voltages are applied to a part of the first and second driving electrodes **1122** and **1142** arranged in a matrix form, that is, when opposite voltages are respectively applied to a part of the first electrode lines **1122a** through **1122h** and the corresponding part of the second electrode lines **114a** through **1142h**, an electric field is formed at intersections of the first electrode lines **1122a** through **1122h** and the second electrode lines **1142a** through **1142h** to which the voltages have been applied. As a result, only polymer thin films **1120** and **1140** corresponding to driving areas where the electric field is formed are deformed to be protruded or depressed, and polymer thin films **1120** and **1140** corresponding to non-driven areas where no electric field is formed are not deformed, so that the EAP actuator body **110** is locally deformed.

However, in this case, since on/off is selected in units of an electrode line, not in units of a driving electrode at each intersection, there are difficulties in deforming the EAP actuator body **110** to various shapes. For example, the deformed area of the EAP actuator body **110**, when it is simultaneously driven, cannot have the right directional arrow shape illustrated in FIG. 4.

The patterns of the first and second driving electrodes **1122** and **1142** as illustrated in FIGS. 3A and 3B are only exemplary. For example, in the case where the EAP actuator body **110** has driving electrodes arranged in a matrix form, the first and second driving electrodes **1122** and **1142** may be respectively formed with different patterns on the polymer thin films **1120** and **1140**. For example, a plurality of square electrode pads each having a unit cell size may be formed in a matrix form on each of the polymer thin films **1120** and **1140**. In this case, a driving voltage is applied to each electrode pad to locally deform the EAP actuator body **110**. That is, by appro-

7

privately combining and selecting electrode pads to which the driving voltage will be applied, the EAP actuator body 110 may be deformed to display a shape, such as a letter, a figure, a symbol (for example, the arrow shape illustrated in FIG. 4), etc.

In order to apply driving voltages to the individual electrode pads, electrode pads on each unit layer are provided with terminals. For example, when the electrode pads are arranged in the form of an 8x8 matrix, at least 128 terminals are used. However, it is difficult to dispose a large number of terminals in the small-sized actuator body 110, and also, rearrangement of terminals to connect the individual terminals to a controller becomes increasingly challenging as the number of electrode pads increases, which results in complicated wirings and makes a fabrication process more difficult.

Meanwhile, defining driving electrodes at intersections of the first electrode lines 1122a through 1122h and the second electrode lines 1142a through 1142h, as illustrated in FIGS. 3A and 3B, may significantly reduce the number of terminals. In more detail, when eight first electrode lines 1122a through 1122h and eight second electrode lines 1142a through 1142h are arranged, only sixteen terminals are used to apply driving voltages to all the first electrode lines 1122a through 1122h and the second electrode lines 1142a through 1142h. However, in this case, as described above, the EAP actuator body 110 may be deformed to show only several limited shapes.

A method of deforming the EAP actuator body 100 which has a structure where a pair of unit layer are stacked, that permits more various shapes is to sequentially apply driving voltages to all or a part selected from among the first electrode lines 1122a through 1122h and all or a part selected from among the second electrode lines 1142a through 1142h for a predetermined time period. At this time, a pattern of driving voltages that are sequentially applied for the predetermined time period may be periodically repeated. The predetermined time period may be decided based on a time interval for which a user can sense deformation through tactile sense to recognize an output signal. For example, a predetermined pattern of driving voltages may be applied repeatedly with a cycle of about $1/100$ to about 1 second. In this case, the predetermined pattern of applied driving voltages will be repeated once every 100 times per second.

FIGS. 6A through 6E are views for explaining an example of a method of sequentially outputting signals to display the shape illustrated in FIG. 4 using the EAP actuator body including the structure to which a pair of unit layers illustrated in FIGS. 3A and 3B is stacked. Referring to FIG. 6A, at a first timing, driving voltages are applied to three first electrode lines 1122c, 1122d and 1122e and one second electrode line 1142b. As a result, the driving voltages are applied to an area corresponding to the most left vertical line 1142b of the arrow illustrated in FIG. 4 and the corresponding area is deformed. Then, referring to FIG. 6B, at a second timing, the driving voltages are applied to three first electrode lines 1122c, 1122d, and 1122e and one second electrode line 1142c. As a result, the driving voltages are applied to an area corresponding to the second left vertical line 1142c of the arrow illustrated in FIG. 4 and the corresponding area is deformed. Then, referring to FIG. 6C, at a third timing, the driving voltages are applied to five first electrode lines 1122b, 1122c, 1122d, 1122e and 1122f and one second electrode line 1142d. As a result, the driving voltages are applied to an area corresponding to the third left vertical line 1142d of the arrow illustrated in FIG. 4 and the corresponding area is deformed. Next, referring to FIG. 6D, at a fourth timing, the driving voltages are applied to three first electrode lines 1122c, 1122d, and 1122e and one second electrode line 1142e. As a result, the

8

driving voltages are applied to an area corresponding to the fourth left vertical line 1142e of the arrow illustrated in FIG. 4 and the corresponding area is deformed. Finally, referring to FIG. 6E, at a fifth timing, the driving voltages are applied to one first electrode line 1122d and one second electrode line 1142f. As a result, the driving voltages are applied to an area corresponding to the fifth left vertical line 1142f of the arrow illustrated in FIG. 4 and the corresponding area is deformed. The method of applying the driving voltages, as shown in FIGS. 6A through 6E, may be repeated once per a predetermined time period, for example, every $1/100$ to 1 second.

When the driving voltages are applied as shown in FIGS. 6A through 6E, the user may recognize the shape (that is, the arrow shape) of the protruded area for a predetermined time period through tactile sense. Particularly, a signal such as an arrow may be output by sequentially applying driving voltages whose output timings are adjusted in the same direction which the arrow indicates. Also, when application of the driving voltages is periodically repeated, the user can exactly recognize what output signal is output through tactile sense.

Referring again to FIG. 2, the touch panel body 10 includes a sensor body 120 disposed on the EAP actuator body 110. An insulative layer (not shown) for electrical isolation may be inserted between the EAP actuator body 110 and the sensor body 120. The insulative layer may be made of a material such as silicon oxide or silicon nitride having an excellent insulation property and capable of being manufactured as a thin film.

The sensor body 120 generates an input signal when a contact or pressing operation occurs. The sensor body 120 may be a capacitive type touch panel, a resistive type touch panel, a piezoelectric type touch panel, etc. The sensor body 120 includes a flexible touch sensor made of a material that is locally deformable in correspondence to local deformation of the EAP actuator body 110. The touch sensor is flexible to allow for the sensor body 120 to be deformed in correspondence to deformation of the EAP actuator body 110 so that a user can sense deformation of the touch panel body 10 through tactile sense.

For example, the sensor body 120 may include a piezoelectric layer which generates current when a surface of the sensor body 120 is pressed and is formed with piezoelectric polymer having flexibility, and a plurality of sensing electrodes through which the current generated by the piezoelectric layer can flow. The piezoelectric polymer may be Poly(Vinylidene Fluoride-TriFluoroEthylene) P(VDF-TrFE) polymer. The P(VDF-TrFE) polymer is a high molecular material having a piezoelectric property and can convert mechanical energy into electrical energy. The P(VDF-TrFE) polymer may be used to manufacture a sensor which senses a pressure or contact.

The sensing electrodes also may be made of a conductive, flexible material which is deformable in correspondence to local deformation of the piezoelectric layer. For example, the sensing electrodes may be, like the driving electrodes described above, formed with transparent, conductive polymer, such as polyaniline, polypyrrole, PEDOT [Poly(3,4-EthyleneDiOxyThiophene)]:PSS [Poly(4-StyreneSulfonic acid)], polythiophen, etc. The shape of the sensing electrodes is matrix-shaped arrangement of square pads, or a plurality of electrode lines arranged on the upper and lower surfaces of the piezoelectric layer in such a manner as to cross perpendicular to each other, like the pattern of the driving electrodes described above.

The bumpy member 130 may be disposed on the sensor body 120. The bumpy member 130 has a structure whose surface is in a concavo-convex pattern to improve a tactile

9

sense with respect to the surface. Since the EAP actuator body **110** can cause a greater displacement rather than other actuator bodies but has a small size of about several micrometers, the user can more sensitively and accurately sense deformation of the EAP actuator body **110** and sensor body **120** from the concave-convex surface of the bumpy member **130** than from a flat surface.

The concavo-convex shape or size of the bumpy member **130** is not limited. For example, the bumpy member **130** may include a plurality of unit bumpy members each having a pyramid shape as illustrated in FIGS. 7A and 7B. In this case, each pyramid structure is disposed in correspondence to a cell, that is, a driving electrode, or a plurality of pyramid structures are arranged in the form of a matrix (for example, a 2x2 matrix in the example of FIGS. 7A and 7B). Alternatively, the concavo-convex structure formed in the bumpy member **130** may be a structure where a plurality of concave, fine lines and a plurality of convex, fine lines (for example, lying trigonal prisms) are arranged or a structure where one or more pillars (for example, cylinders or hexagon pillars) are protruded in correspondence to each cell.

Thus, in other words, the bumpy member **130** may be locally deformable in correspondence to deformation of the sensor body **120**, that is, in correspondence to deformation of the EAP actuator body **110**. This local deformability allows a user to recognize deformation of the EAP actuator body **110** through tactile sense, like the sensor body **120** which is formed with a flexible material.

For this, the bumpy member **130** may be made of a flexible material such as polymer. In this case, however, since the bumpy member **130** has low rigidity, the bumpy member **130** is easy to be damaged when it is repeatedly used, and particularly, the concavo-convex structure for improving a tactile sense is easy to be damaged.

It may be advantageous for the bumpy member **130** to perform a function of protecting the EAP actuator body **110** and the sensor body **120** that are positioned below the bumpy member **130**. As described above, since the EAP actuator body **110** and the sensor body **120** are made of a material (for example, polymer) having a flexible property, repeatedly contacting the surface of the EAP actuator body **110** or sensor body **120** with a finger, or a stylus pen, etc. may damage the EAP actuator body **110** or sensor body **120**. Thus, the bumpy member **130** may act as a protective member for preventing the surfaces of the EAP actuator body **110** and the sensor body **120**, particularly, the surface of the sensor body **120** from being damaged.

In order to perform a protective function, the bumpy member **130** may be formed with a material (for example, plastic or metal, etc.) having sufficient rigidity for preventing a surface of the bumpy member **130** from being damaged. However, in the case where the bumpy member **130** is formed with sheet-shaped plastic or metal having the same size as the sensor body **120** disposed below the bumpy member **130**, it becomes more difficult to deform the bumpy member **130** in correspondence to the deformation of the sensor body **120**.

Thus, the current embodiment allows local deformation of the bumpy member **130** by forming the bumpy member **130** having a structure where a plurality of unit bumpy members whose upper surfaces have a concave-convex shape are separated and arranged in a matrix form, as shown, for example, in FIG. 7A. The size of each unit bumpy member may be equal to or smaller than the size of each driving electrode cell. Accordingly, it is also possible that a plurality of unit bumpy members are disposed in correspondence to a driving electrode cell.

10

FIG. 8 is a cross-sectional view for explaining a driving state of a touch panel including the bumpy member **130**. Referring to FIG. 8, the bumpy member **130** includes a plurality of unit bumpy members that are separated and arranged in a matrix form on the sensor body **120** such that the unit bumpy members can move individually. Unit bumpy members positioned in correspondence to driving areas are protruded upward according to deformation of the EAP actuator body **110** and the sensor body **120**, and unit bumpy members positioned in correspondence to non-driven areas do not move upon deformation of the EAP actuator body **110** and the sensor body **120**.

Referring again to FIGS. 1 and 2, the sensing unit **20** determines whether a user input onto the touch panel A, in more detail, onto the touch panel body **10** occurs, and detects the location of the user input when the user input occurs. For detecting a user input location, the sensing unit **20** may electrically connect to sensing electrodes of the touch panel body **10**. If the touch panel body **10** is a piezoelectric type, the sensing unit **20** determines whether current flows through the sensing electrodes to determine whether a user input occurs. Then, information about occurrence of user input and the user input location, determined by the sensing unit **20**, may be transferred to the driving unit **30**.

The driving unit **30** applies a driving voltage to the touch panel A, specifically, to the EAP actuator body **110** to locally deform the EAP actuator body **110**. That is, the driving unit **30** selects the number and/or locations of driving electrodes to which a driving voltage will be applied to apply the driving voltage only to the selected driving electrodes. For this, the driving unit **30** may electrically connect to the driving electrodes of the EAP actuator body **110**. The driving unit **30** may apply various patterns of driving voltages according to a selection from a user and/or the stage of an application of an electronic device in which the touch panel A is installed. For example, an application pattern of driving voltages includes a method of driving the EAP actuator body **110** as described above with reference to FIGS. 6A through 6E. Also, the driving unit **30** may apply, when receiving an input signal including an input location from the sensing unit **20**, a predetermined pattern of driving voltages based on the input location.

FIGS. 9A and 9B illustrate examples of touch panels. The touch panels illustrated in FIGS. 9A and 9B may have the same structure as the touch panel illustrated in FIGS. 1 and 2, and accordingly detailed descriptions therefor will be omitted. Shaded areas in FIGS. 9A and 9B represent areas deformed by application of driving voltages. For example, in each of the touch panels, driving voltages may be applied only to shaded areas, and for this, the touch panel, in more detail, the EAP actuator body, may be disposed only in parts corresponding to the shaded areas. That is, instead of a structure where square electrode pads or line-type electrode lines are arranged on the surface of a polymer thin film, electrode pads having the shapes of the shaded areas may be arranged on a polymer thin film. Accordingly, the touch panels illustrated in FIGS. 9A and 9B will be deformed to the patterns of electrode pads corresponding to the shaded areas when driving voltages are applied. The touch panels may use the shaded areas as various input buttons. For example, input buttons having the shapes illustrated in FIGS. 9A and 9B may be used as navigation keys for a mobile phone or a mobile multimedia player, etc.

A number of examples have been described above. Nevertheless, it will be understood that various modifications may be made. For example, suitable results may be achieved if the described techniques are performed in a different order and/or

11

if components in a described system, architecture, device, or circuit are combined in a different manner and/or replaced or supplemented by other components or their equivalents. Accordingly, other implementations are within the scope of the following claims.

What is claimed is:

1. A touch panel comprising:
 - an electroactive polymer (EAP) actuator which is deformable when protruded or depressed locally at a part to which a driving voltage is applied;
 - a flexible touch sensor which is disposed on the EAP actuator, is deformable locally in correspondence with a deformation of the EAP actuator, and senses an input according to a contact or pressing operation; and
 - a bumpy member disposed on the flexible touch sensor and formed of plastic or metal, the bumpy member being deformable locally in correspondence with a deformation of the flexible touch sensor,
 wherein the bumpy member comprises a plurality of unit bumpy members that are separated and arranged in a matrix form,
 wherein the EAP actuator comprises a plurality of layers which are stacked together to form a multi-layered EAP actuator, each layer of the plurality of layers comprising:
 - a polymer thin film formed from an electro-active polymer (EPA); and
 - a plurality of driving electrodes which are formed on a surface of the polymer thin film, and are configured to apply driving voltages to the polymer thin film, and
 wherein the EAP actuator is deformed in the same direction as the plurality of layers are stacked in layers.
2. The touch panel of claim 1, wherein the polymer thin film comprises a crosslinked Poly(Vinylidene Fluoride-TriFluoroEthylene-ChloroTriFluoroEthylene) (P(VDF-TrFE-CTFE)) polymer or a crosslinked Poly(Vinylidene Fluoride-TriFluoroEthylene-ChloroFluoroEthylene) (P(VDF-TrFE-CFE)) polymer.
3. The touch panel of claim 1, wherein the driving electrodes are comprise polypyrrole, polyaniline, or polythiophen.
4. The touch panel of claim 1, wherein the flexible touch sensor comprises:
 - a piezoelectric layer comprising a piezoelectric polymer; and
 - a plurality of sensing electrodes which are formed on the piezoelectric layer, and through which current generated when a surface of the piezoelectric layer is deformed flows.
5. The touch panel of claim 4, wherein the piezoelectric layer comprises a Poly(Vinylidene Fluoride-TriFluoroEthylene) (P(VDF-TrFE)) polymer.
6. The touch panel of claim 4, wherein the sensing electrodes comprises polypyrrole, polyaniline, or polythiophen.
7. The touch panel of claim 1, wherein the plurality of unit bumpy members have upper surfaces with a concavo-convex structure.
8. A touch panel comprising:
 - a multi-layered electroactive polymer (EAP) actuator body comprising a plurality of polymer thin films that are formed with EAP and have a stacked structure, and a plurality of driving electrodes disposed between each of the polymer thin films;
 - a flexible touch sensor which is disposed on the multi-layered EAP actuator body, and comprises a piezoelectric layer formed from a piezoelectric polymer, and a plurality of sensing electrodes formed on the piezoelec-

12

- tric layer, wherein current generated when the piezoelectric layer is pressed flows through the sensing electrodes;
 - a bumpy member disposed on the flexible touch sensor and formed of plastic or metal, the bumpy member being deformable locally in correspondence with a deformation of the flexible touch sensor;
 - a driving unit which is electrically connected to the driving electrodes and applies a driving voltage to the driving electrodes to form an electric field locally in the polymer thin films; and
 - a sensing unit which is electrically connected to the sensing electrodes and senses current flowing through the sensing electrodes to detect an input location at which the piezoelectric layer is pressed,
- wherein the bumpy member comprises a plurality of unit bumpy members that are separated and arranged in a matrix form,
- wherein the multi-layered EAP actuator body comprises a plurality of unit layers having a stacked structure, and each of the unit layers comprises:
- a first polymer thin film formed from an EAP;
 - a first driving electrode including a plurality of first electrode lines which are formed on the first polymer thin film and extend in a first direction;
 - a second polymer thin film which is formed from an EAP and is formed on the first polymer thin film on which the first driving electrode is formed; and
 - a second driving electrode comprising a plurality of second electrode lines which are formed on the second polymer thin film and extend in a second direction perpendicular to the first direction,
- wherein the driving unit applies different driving voltages to the first driving electrode and the second driving electrode, respectively, so that the first and second driving electrodes have opposite voltages, and
- wherein the EAP actuator is deformed in the same direction as the plurality of layers are stacked in layers.
9. The touch panel of claim 8, wherein the plurality of driving electrodes are arranged in a matrix form on each of the polymer thin films, and the driving unit applies the driving voltage to a part of the driving electrodes arranged in the matrix form.
 10. The touch panel of claim 8, wherein the driving unit applies the driving voltage to all of the plurality of first electrode lines or to a part of the first electrode lines selected from among the plurality of first electrode lines, and to all of the plurality of second electrode lines or to a part of the second electrode lines selected from among the plurality of second electrode lines.
 11. The touch panel of claim 10, wherein the driving unit sequentially applies the driving voltage to all or the selected part of the first electrode lines, and to all or the selected part of the second electrode lines, for a predetermined time period.
 12. The touch panel of claim 11, wherein the predetermined time period is within a range of about $\frac{1}{100}$ to about 1 second.
 13. The touch panel of claim 8, wherein the plurality of unit bumpy members have upper surfaces with a concavo-convex structure.
 14. The touch panel of claim 8, wherein the plurality of driving electrodes are arranged in a predetermined pattern on each of the polymer thin films.
 15. The touch panel of claim 14, wherein when the driving unit applies the driving voltage to the driving electrodes, the

13

flexible touch sensor functions as an input button at an area
corresponding to the predetermined pattern.

* * * * *

14