



US 20190233275A1

(19) **United States**

(12) **Patent Application Publication**
CARR et al.

(10) **Pub. No.: US 2019/0233275 A1**

(43) **Pub. Date: Aug. 1, 2019**

(54) **METHOD AND APPARATUS FOR
METERING FLOW DURING CENTRALIZED
WELL TREATMENT**

B67D 7/36 (2006.01)

B67D 7/62 (2006.01)

(52) **U.S. Cl.**

CPC **B67D 7/02** (2013.01); **B67D 7/70**
(2013.01); **E21B 43/26** (2013.01); **B67D 7/62**
(2013.01); **B67D 7/0288** (2013.01); **B67D**
7/36 (2013.01)

(71) Applicant: **HALLIBURTON ENERGY
SERVICES, INC.**, Houston, TX (US)

(72) Inventors: **Jared Michael CARR**, Williston, ND
(US); **Beauden Richard SCHNEIDER**,
Williston, ND (US); **Patrick Barrett**
SIEVERT, Sidney, MT (US); **Russell**
Ray LOCKMAN, Commerce City, CO
(US)

(21) Appl. No.: **15/885,198**

(22) Filed: **Jan. 31, 2018**

Publication Classification

(51) **Int. Cl.**


B67D 7/02 (2006.01)

B67D 7/70 (2006.01)

(57)

ABSTRACT

A system for providing a well stimulation fluid can include a manifold, a first flow meter and a second flow meter. The manifold can be an integrated manifold defining a first isolated manifold path and a second isolated manifold path. The first isolated manifold path can be configured to be in fluid communication with a first wellhead and the second isolated manifold path is configured to be in fluid communication with a second wellhead. The first flow meter can be in fluid communication with the first isolated manifold path. The second flow meter can be in fluid communication with the second isolated manifold path.






FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5






FIG. 7

METHOD AND APPARATUS FOR METERING FLOW DURING CENTRALIZED WELL TREATMENT

TECHNICAL FIELD

[0001] The present description relates in general to well operations, and more particularly, for example and without limitation, to methods and apparatuses for simultaneously treating multiple wells from a centralized location.

BACKGROUND OF THE DISCLOSURE

[0002] In the production of oil and gas in the field, it is often required to stimulate and treat several well locations within a designated amount of time. Stimulation and treatment processes often involve mobile equipment that is set up at a pad location and is then moved by truck from pad to pad within short time periods.

[0003] The movement of equipment and personnel can involve complex logistics. The servicing and stimulation of wells can require a series of coordinated operations that begin with the delivery of equipment, supplies, fuel, and chemicals to the wellhead. The equipment is then set up and made ready with proppant and chemicals. After completion of the well services, equipment must be broken down and made ready for transport to the next pad for service. Often, the next pad will be less than 500 feet away from the previously treated pad. In addition, due to the limited storage capacity of the moving equipment for chemicals and equipment, additional trucks are often required to resupply and reequip an existing operation. This movement of equipment and supplies has environmental impacts, and the exposure of mobile equipment to adverse weather conditions can jeopardize well treatment operations and worker safety.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] In one or more implementations, not all of the depicted components in each figure may be required, and one or more implementations may include additional components not shown in a figure. Variations in the arrangement and type of the components may be made without departing from the scope of the subject disclosure. Additional components, different components, or fewer components may be utilized within the scope of the subject disclosure.

[0005] FIG. 1 is a flow diagram of a centralized well treatment facility that can employ the principles of the present disclosure.

[0006] FIG. 2 is a diagram of a manifold for use with the centralized well treatment facility of FIG. 1, according to some embodiments of the present disclosure.

[0007] FIG. 3 is a diagram of a manifold for use with the centralized well treatment facility of FIG. 1, according to some embodiments of the present disclosure.

[0008] FIG. 4 is a flow diagram of a centralized well treatment facility, according to some embodiments of the present disclosure.

[0009] FIG. 5 is a flow diagram of a centralized well treatment facility, according to some embodiments of the present disclosure.

[0010] FIG. 6 is a flow diagram of a centralized well treatment facility, according to some embodiments of the present disclosure.

[0011] FIG. 7 is a diagram of a manifold for use with the centralized well treatment facility of FIG. 6, according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0012] This section provides various example implementations of the subject matter disclosed, which are not exhaustive. As those skilled in the art would realize, the described implementations may be modified without departing from the scope of the present disclosure. Accordingly, the drawings and description are to be regarded as illustrative in nature and not restrictive.

[0013] The present description relates in general to well operations, and more particularly, for example and without limitation, to methods and apparatuses for simultaneously treating multiple wells from a centralized location.

[0014] Simultaneous well stimulation and treatment processes from a centralized location can simplify logistics and reduce operation time and costs. In some applications, a single fracturing crew or fleet can increase their productivity by fracturing multiple wells from a centralized location without the need for additional blending equipment or personnel. However, as multiple wells are simultaneously stimulated or treated from a central location, an operator may not be able to monitor fluid flow to each well treated from the centralized location.

[0015] An aspect of at least some embodiments disclosed herein is that by monitoring fluid flow from a centralized location to multiple wells, operators can have enhanced control over the multiple wells while operating from a centralized location.

[0016] FIG. 1 is a flow diagram of a centralized well treatment facility that can employ the principles of the present disclosure. Multiple wells, such as the first well 140 and the second well 142 can be treated or stimulated simultaneously using the centralized well treatment facility 100. The well treatment facility 100 can be set upon a pad from which at least the first well 140 and the second well 142 can be serviced. In some embodiments, the well treatment operations facility 100 can be connected to at least the first well 140 and the second well 142 via a central manifold 120. Connections within the well treatment facility 100 may be a standard piping or tubing known to one of ordinary skill in the art. The well treatment facility 100 can include a centralized location 105 that includes at least some of the components of the well treatment facility 100 and may be open, or may be at least partially enclosed with various combinations of structures including a supported fabric structure, a collapsible structure, a prefabricated structure, a retractable structure, a composite structure, a temporary building, a prefabricated wall and roof unit, a deployable structure, a modular structure, a preformed structure, or a mobile accommodation unit.

[0017] Advantageously, the well treatment facility 100 allows for fluids for treatment, stimulation, fracturing, or other well operations to be manufactured, formed and/or mixed at a centralized location 105 prior to being transferred to the first well 140 and the second well 142. In some embodiments, well fluids can be created by optionally mixing constituents in a hydration blender 102 before mixing the fluid in a mixing blender 108. In some embodiments, water from a water supply 104 and dry powder can be introduced into the hydration blender 102. Dry powder, such as guar can be metered into the hydration blender 102 from

a storage tank via a screw conveyor. In some embodiments, various chemical additives and modifiers can be introduced into the hydration blender **102** from a chemical storage system **106**.

[0018] In some embodiments, the chemical storage system **106** is connected to the hydration blender **102** and can include tanks for breakers, gel additives, crosslinkers, and liquid gel concentrate. The tanks can have level control systems such as a wireless hydrostatic pressure system and may be insulated and heated. Pressurized tanks may be used to provide positive pressure displacement to move chemicals, and some tanks may be agitated and circulated. The chemical storage system **106** can continuously meter chemicals with additive pumps, which are able to meter chemical solutions to the hydration blender **102** at specified rates as determined by the required final concentrations and the pump rates of the main treatment fluid from the hydration blender **102**. In some embodiments, chemical storage tanks of the chemical storage system **106** are pressurized to drive fluid flow. The quantities and rates of chemicals added to the main fluid stream may be controlled by valve-metering control systems. In addition, chemical additives can be added to the main treatment fluid in the hydration blender **102** via aspiration (Venturi Effect). The rates that the chemical additives are aspirated into the main fluid stream can be controlled via adjustable, calibrated apertures located between the chemical storage system **106** and the hydration blender **102**. In some embodiments, the components of the chemical storage system **106** are modularized allowing pumps, tanks, or blenders to be added or removed independently.

[0019] After pre-mixing in the hydration blender **102**, the treatment or fracturing fluid can be further mixed in the mixing blender **108**. In some embodiments, mixing can occur solely in the mixing blender **108** without any pre-mixing in the hydration blender **102**. In some embodiments, the mixing blender **108** can be utilized to introduce, mix and blend proppant and chemical additives into a base fluid. Mixing can be accomplished at downhole pump rates. In some embodiments, the mixing blender **108** is configured to blend proppant and chemical additives into the base fluid without destroying the base fluid properties while still providing ample energy for the blending of proppant into a near fully hydrated fracturing fluid. In some embodiments, the mixing blender **108** is a modified Halliburton Growler mixer.

[0020] Proppant can be introduced into the mixing blender **108** from a proppant storage system **110**. In some embodiments, the proppant storage system **110** can include automatic valves and a set of tanks that contain proppant. Each tank can be monitored for level, material weight, and the rate at which proppant is being consumed. This information can be transmitted to a controller or control area. Each tank is capable of being filled pneumatically and can be emptied through a calibrated gravity discharge. Tanks may be added to or removed from the proppant storage system **110** as needed. Empty storage tanks can be replenished as full or partially full tanks are being used, allowing for continuous operation. The tanks can be arranged around a calibrated v-belt conveyor. In addition, a resin-coated proppant may be used by the addition of a mechanical proppant coating system. In some embodiments, the coating system may be a Muller System.

[0021] In some embodiments, the mixed or manufactured fluid from the mixing blender **108** can be pumped simultaneously to the first well **140** and the second well **142** via a manifold **120**. In some embodiments, the manifold **120** can be isolated into a first isolated manifold path **122** directed to the first well **140** and a second isolated manifold path **124** directed to the second well **142**. The first isolated manifold path **122** and the second isolated manifold path **124** can be integrated in a single manifold **120**, which may be referred to as a “missile.” The use of the manifold **120** can allow multiple wells to be fractured or treated simultaneously.

[0022] Treatment or fracturing fluid can be transferred, transported, and/or pressurized within the first isolated manifold path **122** and the second isolated manifold path **124** via an array of pumps **130**. The array of pumps **130** can be fluidly connected to the first isolated manifold path **122** via suction lines **132** and discharge lines **134**. A separate array of pumps **130** can be fluidly connected to the second isolated manifold path **124** via suction lines **132** and discharge lines **134**. The pumps **130** within the arrays can be electric, gas, diesel, or natural gas powered. In some embodiments, the pumps **130** can be modularized for ease of configuration. In some embodiments, the output and pressure of the pumps **130** can be adjusted in response to sensor data, such as data received from the first flow meter **150** and the second flow meter **152**.

[0023] As treatment or fracturing fluid flows from a centralized location **105** to the first well **140** and the second well **142** via the manifold **120**, a first flow meter **150** in fluid communication with the first isolated manifold path **122** and a second flow meter **152** in fluid communication with the second isolated manifold path **124** can provide an operator and/or a control system **112** with flow rate and total flow information. Advantageously, the first flow meter **150** and the second flow meter **152** can provide flow information about each flow to the first well **140** and the second well **142** for precise measurement and regulation. Flow measurements for the first well **140** and the second well **142** can allow for enhanced control of treatment or fracturing of both the first well **140** and the second well **142** while allowing for the benefits of a centralized well treatment facility **100** as described herein. The first flow meter **150** and the second flow meter **152** can be disposed along any suitable portion of the first isolated manifold path **122** and the second isolated manifold path **124**, respectively.

[0024] The first flow meter **150** and the second flow meter **152** can be any suitable type of flow meter, including, but not limited to an orifice plate, Pitot tube, averaging Pitot tube, flume, weir, turbine, target, positive displacement, rotameter, vortex, Coriolis, ultrasonic, magnetic, wedge, v-cone, flow nozzle, and/or Venturi type flow meters. The flow meters can be utilized to measure mass and/or volumetric flow rates of the fluid. Information from the first flow meter **150** and the second flow meter **152** can be transmitted to a display and/or a control system **112**.

[0025] In some embodiments, information from the first flow meter **150** and/or the second flow meter **152** can be utilized to control the production of fluid and the output of fluid to the first well **140** and the second well **142**. In some embodiments, the operations of the chemical storage system **106**, hydration blender **102**, proppant storage system **110**, mixing blender **108**, manifold **120**, and/or pumps **130** are controlled, coordinated, and monitored by a central control system **112**. The central control system **112** may utilize

sensor data including information from the first flow meter **150** and the second flow meter **152** as well as operating parameters from the chemical storage system **106**, hydration blender **102**, proppant storage system **110**, mixing blender **108**, manifold **120**, and pumps **130** to identify operation of the well treatment facility **100**. In some embodiments, the control system **112** can be utilized to adjust the output of the pumps **130** by utilizing flow data from the first flow meter **150** and the second flow meter **152** in light of fluid flow targets for the first well **140** and/or the second well **142**. In some embodiments, fluid flow to the first well **140** and/or the second well **142** can be exclusively controlled by adjusting the output of the pumps **130**. Further, information from the first flow meter **150** and the second flow meter **152** can be utilized to control desired fluid properties such as density, rate, viscosity, etc. Flow information can also be utilized to identify dynamic or steady state bottlenecks within the well treatment facility **100**. The central control system **112** can also be used to monitor equipment health and status.

[0026] FIG. **2** is a diagram of a manifold for use with the centralized well treatment facility of FIG. **1**, according to some embodiments of the present disclosure. In some embodiments, the manifold **120** is an integrated manifold that defines a first isolated manifold path **122** and a second isolated manifold path **124** within an integrated body.

[0027] In some embodiments, an inlet **160** of the first isolated manifold path **122** can receive a fluid flow from the mixing blender **108**. As fluid flow is directed into the first isolated manifold path **122**, the first flow meter **150** can measure flow rate therethrough. The first isolated manifold path **122** can direct the flow of fluid from the inlet **160** to the outlet **162** while allowing the fluid flow therethrough to be pressurized via the array of pumps **130**. The outlet **162** can direct the pressurized fluid flow to the first well **140**.

[0028] In the depicted example, the suction ports **166** and the discharge ports **168** can be in fluid communication with the first isolated manifold path **122** at junctions or nodes **164a-164n**.

[0029] In some embodiments, the suction ports **166** of the first isolated manifold path **122** allow pumps **130** to receive a fluid flow from the first isolated manifold path **122**. The discharge ports **168** provide the pumped fluid from the pumps **130** back to the first isolated manifold path **122**.

[0030] As shown in FIG. **2**, the second isolated manifold path **124** can have a similar configuration as the first isolated manifold path **122**. The second isolated manifold path **124** can similarly receive fluid flow from the mixing blender **108** via an inlet **160**. The second flow meter **152** can measure fluid flow through the second isolated manifold path **124**. The second isolated manifold path **124** can direct the flow of fluid from the inlet **160** to the outlet **162** while allowing the fluid flow therethrough to be pressurized via the array of pumps **130**. The outlet **162** can direct the pressurized fluid flow to the second well **142**.

[0031] FIG. **3** is a diagram of a manifold for use with the centralized well treatment facility of FIG. **1**, according to some embodiments of the present disclosure. Referring to FIG. **3**, in some embodiments, manifold **220** can include a first flow meter **150** and/or a second flow meter **150** within the manifold **220** along the first isolated manifold path **222** and/or the second isolated manifold path **224**. In some embodiments, the manifold **220** can include various valves and sensors along the first isolated manifold path **222** and/or the second isolated manifold path **224**.

[0032] FIG. **4** is a flow diagram of a centralized well treatment facility that can employ the principles of the present disclosure. In some embodiments, the well treatment facility **300** can include an additional flow meter **354** disposed downstream of the mixing blender **108** to measure the flow from the mixing blender **108** before the flow is separated and directed into the first isolated manifold path **122** and the second isolated manifold path **124** of the manifold **120**. The flow meter **354** can provide total flow and/or flow rates out of the mixing blender **108**.

[0033] FIG. **5** is a flow diagram of a centralized well treatment facility that can employ the principles of the present disclosure. In some embodiments, the well treatment facility **400** can optionally include a first valve **470** disposed along the first isolated manifold path **122** and/or a second valve **472** disposed along the second isolated manifold path **124**. The first valve **470** can be utilized to control the flow from the mixing blender **108** to the first well **140** and the second valve **472** can be utilized to control the flow from the mixing blender **108** to the second well **142**. The first valve **470** and the second valve **472** can be disposed outside of the manifold **120** or disposed within the manifold **120**. The first valve **470** and the second valve **472** can allow for the first well **140** and the second well **142** to each be stimulated individually by opening the respective first valve **470** or the second valve **472** and closing the other valve. Further, in some embodiments, the first valve **470** and the second valve **472** can be used to control the flow rate to the first well **140**, the second well **142**, or to both the first well **140** and the second well **142** simultaneously.

[0034] In some embodiments, the well treatment facility **400** can optionally include a proportioning valve **474** in place of, or in addition to, the first valve **470** and the second valve **472**. The proportioning valve **474** can control and direct the flow from the mixing blender **108** to the first isolated manifold path **122** and the second isolated manifold path **124**. The proportioning valve **474** can separate or direct flow completely to the first isolated manifold path **122**, to the second isolated manifold path **124**, or to a combination of the first isolated manifold path **122** and the second isolated manifold path **124** at a desired proportion. The proportioning valve **474** can be used in conjunction with, or separate from, the first valve **470** and the second valve **472**.

[0035] In some embodiments, the control system **112** can be utilized to control the position of the first valve **470**, second valve **472**, and/or the proportioning valve **474** by utilizing flow data from the first flow meter **150** and the second flow meter **152** in light of fluid flow targets for the first well **140** and/or the second well **142**.

[0036] FIG. **6** is a flow diagram of a centralized well treatment facility that can employ the principles of the present disclosure. In some embodiments, the well treatment facility **500** can utilize multiple manifolds **520** instead of a single integrated manifold. Each manifold **520** can receive a flow from the mixing blender **108** and direct the flow to either the first well **140** or the second well **142**. In some embodiments, the separate manifolds **520** can be manifold trailers or other modular manifold assemblies.

[0037] FIG. **7** is a diagram of a manifold for use with the centralized well treatment facility of FIG. **6**, according to some embodiments of the present disclosure. In some embodiments, the manifold **520** provides a single flow path **521** within the manifold **520**.

[0038] In some embodiments, an inlet **560** of the manifold **520** can receive a fluid flow from the mixing blender **108**. As fluid flow is directed into the manifold **520**, the first flow meter **150** or the second flow meter **152** can measure flow rate therethrough. The flow path **521** can direct the flow of fluid from the inlet **560** to the outlet **562** while allowing the fluid flow therethrough to be pressurized via the array of pumps **130**. The outlet **562** can direct the pressurized fluid flow to the first well **140** or the second well **142**.

[0039] In the depicted example, the suction ports **566** and the discharge ports **568** can be in fluid communication with the flow path **521** at junctions or nodes **164a-164n**.

[0040] In some embodiments, the suction ports **566** allow pumps **130** to receive a fluid flow from the flow path **521**. The discharge ports **568** provide the pumped fluid from the pumps **130** back to the flow path **521**.

[0041] In some embodiments, the well treatment facility can be used for both onshore and offshore operations using existing or specialized equipment or a combination of both. Such equipment can be modularized to expedite installation or replacement.

[0042] Various examples of aspects of the disclosure are described below as clauses for convenience. These are provided as examples, and do not limit the subject technology.

[0043] Clause 1. A method, comprising: providing a well stimulation fluid flow comprising a well stimulation fluid; separating the well stimulation fluid flow to a first fluid flow via a first isolated manifold path and a second fluid flow via a second isolated manifold path; measuring a first fluid flow rate corresponding to the first fluid flow via a first flow meter; measuring a second fluid flow rate corresponding to the second fluid flow via a second flow meter; directing the first fluid flow to a first wellhead via the first isolated manifold path; and directing the second fluid flow to a second wellhead via the second isolated manifold path.

[0044] Clause 2. The method of Clause 1, further comprising manufacturing the well stimulation fluid.

[0045] Clause 3. The method of Clause 2, wherein the manufacturing comprises mixing the well stimulation fluid.

[0046] Clause 4. The method of Clause 2, wherein the manufacturing comprises introducing a proppant to the well stimulation fluid.

[0047] Clause 5. The method of Clause 2, wherein the manufacturing comprises introducing water to the well stimulation fluid.

[0048] Clause 6. The method of Clause 2, wherein the manufacturing comprises introducing chemicals to the well stimulation fluid.

[0049] Clause 7. The method of any preceding Clause, wherein the first isolated manifold path and the second isolated manifold path are defined by an integrated manifold.

[0050] Clause 8. The method of any preceding Clause, wherein the first isolated manifold path is defined by a first manifold and the second isolated manifold path is defined by a second manifold.

[0051] Clause 9. The method of any preceding Clause, further comprising increasing a pressure of the first fluid flow via a first plurality of pumps in fluid communication with the first isolated manifold path.

[0052] Clause 10. The method of Clause 9, further comprising adjusting the first plurality of pumps in response to the first flow rate.

[0053] Clause 11. The method of any preceding Clause, further comprising increasing a pressure of the second fluid flow via a second plurality of pumps in fluid communication with the second isolated manifold path.

[0054] Clause 12. The method of Clause 11, further comprising adjusting the second plurality of pumps in response to the second flow rate.

[0055] Clause 13. The method of any preceding Clause, further comprising separating the well stimulation fluid flow via a proportioning valve in fluid communication with the first isolated manifold path and the second isolated manifold path.

[0056] Clause 14. The method of Clause 13, further comprising adjusting the proportioning valve in response to the first flow rate or the second flow rate.

[0057] Clause 15. The method of any preceding Clause, further comprising controlling the first fluid flow via a first valve disposed within the first isolated manifold path.

[0058] Clause 16. The method of Clause 15, further comprising adjusting the first valve in response to the first flow rate.

[0059] Clause 17. The method of any preceding Clause, further comprising controlling the second fluid flow via a second valve disposed within the second isolated manifold path.

[0060] Clause 18. The method of Clause 17, further comprising adjusting the second valve in response to the second flow rate.

[0061] Clause 19. The method of any preceding Clause, further comprising measuring a total fluid flow rate corresponding to the well stimulation fluid flow.

[0062] Clause 20. The method of any preceding Clause, wherein directing the first fluid flow to the first wellhead and directing the second fluid flow to the second wellhead is simultaneous.

[0063] Clause 21. A system comprising: an integrated manifold defining a first isolated manifold path and a second isolated manifold path, wherein the first isolated manifold path is configured to be in fluid communication with a first wellhead and the second isolated manifold path is configured to be in fluid communication with a second wellhead; a first flow meter in fluid communication with the first isolated manifold path; and a second flow meter in fluid communication with the second isolated manifold path.

[0064] Clause 22. The system of Clause 21, further comprising a well stimulation fluid source in fluid communication with the first isolated manifold path and the second isolated manifold path.

[0065] Clause 23. The system of Clause 22, wherein the well stimulation fluid source comprises a mixer.

[0066] Clause 24. The system of Clause 22, wherein the well stimulation fluid source comprises a hydration blender.

[0067] Clause 25. The system of Clause 22, further comprising a third flow meter in fluid communication with the well stimulation fluid source, the first isolated manifold path and the second isolated manifold path.

[0068] Clause 26. The system of Clause 22, further comprising a proportioning valve in fluid communication with the well stimulation fluid source, the first isolated manifold path and the second isolated manifold path to direct flow from the well stimulation fluid source to the first isolated manifold path and the second isolated manifold path.

[0069] Clause 27. The system of Clauses 21-26, further comprising a first valve disposed within the first isolated manifold path to control flow through the first isolated manifold path.

[0070] Clause 28. The system of Clauses 21-27, further comprising a second valve disposed within the second isolated manifold path to control flow through the second isolated manifold path.

[0071] Clause 29. The system of Clauses 21-28, further comprising a first plurality of pumps in fluid communication with the first isolated manifold path.

[0072] Clause 30. The system of Clauses 21-29, further comprising a second plurality of pumps in fluid communication with the second isolated manifold path.

[0073] Clause 31. A system comprising: a first manifold defining a first isolated manifold path configured to be in fluid communication with a first wellhead; a second manifold defining a second isolated manifold path configured to be in fluid communication with a second wellhead; a first flow meter in fluid communication with the first isolated manifold path; and a second flow meter in fluid communication with the second isolated manifold path.

[0074] Clause 32. The system of Clause 31, further comprising a well stimulation fluid source in fluid communication with the first isolated manifold path and the second isolated manifold path.

[0075] Clause 33. The system of Clause 32, wherein the well stimulation fluid source comprises a mixer.

[0076] Clause 34. The system of Clause 32, wherein the well stimulation fluid source comprises a hydration blender.

[0077] Clause 35. The system of Clause 32, further comprising a third flow meter in fluid communication with the well stimulation fluid source, the first isolated manifold path and the second isolated manifold path.

[0078] Clause 36. The system of Clause 32, further comprising a proportioning valve in fluid communication with the well stimulation fluid source, the first isolated manifold path and the second isolated manifold path to direct flow from the well stimulation fluid source to the first isolated manifold path and the second isolated manifold path.

[0079] Clause 37. The system of Clauses 31-36, further comprising a first valve disposed within the first isolated manifold path to control flow through the first isolated manifold path.

[0080] Clause 38. The system of Clauses 31-37, further comprising a second valve disposed within the second isolated manifold path to control flow through the second isolated manifold path.

[0081] Clause 39. The system of Clauses 31-38, further comprising a first plurality of pumps in fluid communication with the first isolated manifold path.

[0082] Clause 40. The system of Clauses 31-39, further comprising a second plurality of pumps in fluid communication with the second isolated manifold path.

What is claimed is:

1. A method, comprising:

providing a well stimulation fluid flow comprising a well stimulation fluid;

separating the well stimulation fluid flow to a first fluid flow via a first isolated manifold path and a second fluid flow via a second isolated manifold path;

measuring a first fluid flow rate corresponding to the first fluid flow via a first flow meter;

measuring a second fluid flow rate corresponding to the second fluid flow via a second flow meter;

directing the first fluid flow to a first wellhead via the first isolated manifold path; and

directing the second fluid flow to a second wellhead via the second isolated manifold path.

2. The method of claim 1, further comprising manufacturing the well stimulation fluid.

3. The method of claim 1, wherein the first isolated manifold path and the second isolated manifold path are defined by an integrated manifold.

4. The method of claim 1, wherein the first isolated manifold path is defined by a first manifold and the second isolated manifold path is defined by a second manifold.

5. The method of claim 1, further comprising increasing a pressure of the first fluid flow via a first plurality of pumps in fluid communication with the first isolated manifold path.

6. The method of claim 5, further comprising adjusting the first plurality of pumps in response to the first flow rate.

7. The method of claim 1, further comprising increasing a pressure of the second fluid flow via a second plurality of pumps in fluid communication with the second isolated manifold path.

8. The method of claim 7, further comprising adjusting the second plurality of pumps in response to the second flow rate.

9. A system comprising:

an integrated manifold defining a first isolated manifold path and a second isolated manifold path, wherein the first isolated manifold path is configured to be in fluid communication with a first wellhead and the second isolated manifold path is configured to be in fluid communication with a second wellhead;

a first flow meter in fluid communication with the first isolated manifold path; and

a second flow meter in fluid communication with the second isolated manifold path.

10. The system of claim 9, further comprising a well stimulation fluid source in fluid communication with the first isolated manifold path and the second isolated manifold path.

11. The system of claim 10, wherein the well stimulation fluid source comprises a mixer.

12. The system of claim 10, wherein the well stimulation fluid source comprises a hydration blender.

13. The system of claim 10, further comprising a third flow meter in fluid communication with the well stimulation fluid source, the first isolated manifold path and the second isolated manifold path.

14. The system of claim 9, further comprising a first plurality of pumps in fluid communication with the first isolated manifold path.

15. The system of claim 9, further comprising a second plurality of pumps in fluid communication with the second isolated manifold path.

16. A system comprising:

a first manifold defining a first isolated manifold path configured to be in fluid communication with a first wellhead;

a second manifold defining a second isolated manifold path configured to be in fluid communication with a second wellhead;

a first flow meter in fluid communication with the first isolated manifold path; and

a second flow meter in fluid communication with the second isolated manifold path.

17. The system of claim **16**, further comprising a well stimulation fluid source in fluid communication with the first isolated manifold path and the second isolated manifold path.

18. The system of claim **17**, further comprising a third flow meter in fluid communication with the well stimulation fluid source, the first isolated manifold path and the second isolated manifold path.

19. The system of claim **16**, further comprising a first plurality of pumps in fluid communication with the first isolated manifold path.

20. The system of claim **16**, further comprising a second plurality of pumps in fluid communication with the second isolated manifold path.

* * * * *