



US007467874B2

(12) **United States Patent**
Gautschi et al.

(10) **Patent No.:** **US 7,467,874 B2**
(45) **Date of Patent:** **Dec. 23, 2008**

(54) **SANITARY FITTING WITH A LIGHTGUIDE
OUTFLOW PIPE**

(75) Inventors: **Christian Gautschi**, Reinach (CH);
Stefan Brunner, Moosleerau (CH)

(73) Assignee: **KWC AG**, Unterkulm (CH)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 89 days.

(21) Appl. No.: **11/372,207**

(22) Filed: **Mar. 10, 2006**

(65) **Prior Publication Data**

US 2006/0203470 A1 Sep. 14, 2006

(30) **Foreign Application Priority Data**

Mar. 11, 2005 (EP) 05005389

(51) **Int. Cl.**
F21V 33/00 (2006.01)

(52) **U.S. Cl.** **362/96**; 239/18

(58) **Field of Classification Search** 362/96,
362/101, 149, 154, 156, 276, 800; 239/16-18,
239/548; 4/615; 137/801
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,827,538 A * 5/1989 Heimann et al. 4/677
5,123,437 A 6/1992 Egli et al.

5,171,429 A 12/1992 Yasuo
5,491,617 A * 2/1996 Currie 362/96
5,937,892 A 8/1999 Meisner et al.
6,126,290 A 10/2000 Veigel
6,439,472 B1 8/2002 Lin et al.
6,805,458 B2 * 10/2004 Schindler et al. 362/96
2003/0168100 A1 9/2003 Ericsson

FOREIGN PATENT DOCUMENTS

DE 31 35 861 A1 3/1983
DE 3841 026 A1 6/1990
DE 41 11 928 A1 10/1991
DE 40 31 764 A1 2/1992
DE 43 13 439 A 1 10/1994
DE 201 02 857 U 1 7/2001
EP 0 446 365 A1 9/1991
JP 54159075 A * 12/1979
WO WO 94/24379 10/1994
WO WO 2004/092626 A1 10/2004

* cited by examiner


Primary Examiner—Hargobind S Sawhney

(74) *Attorney, Agent, or Firm*—Oliff & Berridge, PLC

(57) **ABSTRACT**

A sanitary fitting includes a light-permeable water-carrying outflow pipe that has (i) an exposed end face and (ii) an input face located upstream of the exposed end face. A light source, preferably including light emitting diodes (LED), inputs light into the outflow pipe through the input face. The light emerges from the outflow pipe at the end face, and may also emerge at an exposed outer peripheral surface area of the outflow pipe.

13 Claims, 6 Drawing Sheets



Delta 2009
Kohler v. Delta
IPR2024-00700





Fig. 1








Fig. 3






Fig. 6




Fig. 7

1

SANITARY FITTING WITH A LIGHTGUIDE OUTFLOW PIPE

BACKGROUND

The present invention relates to a sanitary fitting that includes a lightguide.

Sanitary fittings of this general type are known from EP-A-0 446 365 and DE-U-201 02 857.

EP-A-0 446 365 discloses a sanitary fitting with an outflow pipe manufactured from metal. The outflow pipe has an exposed end face at an end located downstream. Through the wall of the outflow pipe runs a lightguide element which has an output face lying in the end face. Light from a light source arranged in the sanitary fitting is output through the lightguide element at the output face in such a way that a water jet is illuminated from outside by the lightguide element.

In a further sanitary fitting, likewise disclosed in EP-A-0 446 365, which has an outflow pipe manufactured from metal, light from a light source is input into the water running out of the sanitary fitting. For this purpose, the sanitary fitting has a lightguide which is arranged in a wall of the outflow pipe and which terminates above the end face in the flow direction. An end division of the lightguide which faces away from the light source is oriented in the direction of the flow duct and is adjacent to the flow duct. The light is input into the outflowing water from the lightguide.

DE-U-201 02 857 discloses a water jet illuminator with a jet former which is fixedly connected to a conventional domestic water tap. The water flowing out of the domestic water tap is illuminated by a light emitting diode and a lightguide. One end of the lightguide bears against the light emitting diode and the other end of the lightguide is arranged within the outflowing water.

SUMMARY

An object of exemplary embodiments of the present invention is to provide a generic sanitary fitting which makes it possible to have a substantially simpler design.

This object may be achieved by a sanitary fitting that includes a light-permeable water-carrying outflow pipe and a light source. The outflow pipe has (i) an exposed end face and (ii) an input face located upstream of the exposed end face. Light from the light source is input into the outflow pipe at the input face, and emerges at the end face.

According to exemplary embodiments of the invention, the water-carrying outflow pipe is manufactured from a light-permeable—transparent or translucent—material, and light is input into the outflow pipe at an input face lying upstream. The outflow pipe has an exposed end face which is located downstream and at which the light is output from the outflow pipe.

Visual effects can be achieved by the partial exposure of the outer surface area of the outflow pipe.

According to a preferred embodiment, the sanitary fitting according to the invention has an extendable hose capable of being extended out of a guide pipe and having a water outflow head attached to the end of the extendable hose and having an outflow pipe. It is thereby possible to bring the water outflow head and therefore also the light source into an advantageous position for cleaning an article.

A sanitary fitting according to exemplary embodiments of the invention has the further advantage that the surroundings of the outflowing water and/or even the outflowing water itself can be illuminated, depending on the form of the end face. By the surroundings of the outflowing water being illu-

2

minated, it is possible to ensure that an article to be cleaned is illuminated optimally even when the surrounding lighting is poor.

Further particular advantages and types of action may be gathered from the detailed description of the drawing.

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary embodiments of the invention are explained in detail below with reference to the drawings in which, purely diagrammatically:

FIG. 1 shows a partially sectional view of a first exemplary embodiment of a sanitary fitting according to the invention with a water outflow head arranged in a widened end region of a guide pipe and having a lightguide outflow pipe;

FIG. 2 shows, enlarged in relation to FIG. 1, a section through the water outflow head arranged in the widened end region and having an extendable hose;

FIG. 3 shows a view of a further embodiment of a water outflow head for a sanitary fitting according to the invention, according to the first exemplary embodiment;

FIG. 4 shows a view, in the direction of the arrow II depicted in FIG. 1, of the widened end region with an inserted water outflow head according to FIGS. 1 and 2;

FIG. 5 shows a view of a second exemplary embodiment of a sanitary fitting according to the invention with an exposed outflow pipe projecting from the housing of the sanitary fitting;

FIG. 6 shows, enlarged in relation to FIG. 5, a longitudinal section through part of the fitting housing with the lightguide outflow pipe inserted into the fitting housing; and

FIG. 7 shows a longitudinal section through part of a further embodiment of a lightguide outflow pipe.

DETAILED DESCRIPTION OF EMBODIMENTS

A first exemplary embodiment of a sanitary fitting 10 according to the invention is shown in FIGS. 1, 2 and 4.

As shown in FIG. 1, the sanitary fitting 10 has a fitting housing 12, from which a mounting connection piece 14 projects downward. The latter is intended for fastening the sanitary fitting 10 to a mounting surface, not shown, of a washing table by a nut 14'. The fitting housing 12 has a recess with a mixer cartridge 15 inserted in a known way and having an actuation element 16 for controlling the water flow. A guide pipe 18, which may be pivotable about a vertical axis, projects from the fitting housing 12 in the vertical direction. The guide pipe 18 may narrow from the fitting housing 12 in the manner of a bell to a diameter D, and may run initially rectilinearly and then virtually in a semicircular arc. A free end region 20 of the guide pipe 18 may widen continuously in the manner of the bell. The interior of the free end region 20 may form a receptacle 22 for a water outflow head 24 that can be pulled out and reinserted.

The water outflow head 24 may be fixedly connected to an extendable hose 26 running through the interior of the guide pipe 18, the interior of fitting housing 12 and the interior of the mounting connection piece 14. The extendable hose 26, as is generally known, runs back to the fitting housing 12 in a loop. The extendable hose 26 may have (see FIG. 2) an external casing hose 86 and a water hose 28 arranged inside the casing hose 86. Between the casing hose 86 and the water hose 28 is arranged an electrical line 84, preferably a multiwire cord. The water hose 28 is intended for carrying mixed water from the mixer cartridge 15 to the water outflow head 24. Moreover, the mixer cartridge 15 is connected in a known way to a cold and hot water feed line, not shown.

3

As shown in FIGS. 1, 2 and 4, a housing 36 of the water outflow head 24 has a bell-like shape which is adapted to the shape of the receptacle 22. In order to allow simple handling, the housing 36 has a tenon-like pull-out aid 38 which projects in a radial direction. For this purpose, the free end region 20 of the guide pipe 18 has (see FIG. 4) a guide slot 40 which is open at the end of the guide pipe 18 and through which the pull-out aid 38 is guided when the water outflow head 24 is being moved in and moved out. The housing 36 has, further, a bead 42 which, if the water outflow head 24 is inserted into the receptacle 22, engages into the guide slot 40. Apart from in the region of the bead 42 and in an end region 44 located upstream, the housing 36 has a thin-walled design with substantially constant wall thickness. At the end located downstream, apart from in the region of the bead 42, the housing 36 has a peripheral housing end face 46. The bead 42 may project beyond the housing end face 46 in the flow direction.

The water outflow head 24 has a water-carrying, preferably rotationally symmetric, light-permeable lightguide outflow pipe 50 connected to the water hose 28. The outflow pipe 50 is manufactured, for example, from acrylic glass or from another transparent or translucent material. The outflow pipe 50 has a hollow-cylindrical light transmission region 52 in a portion located downstream. This light transmission region 52 is delimited, on the one hand, upstream, by an input face 56 and, on the other hand, downstream, by an exposed end face 58. The end face 58 lies opposite the input face 56 in the outflow direction, and both the end face 58 and the input face 56 may lie at right angles to the longitudinal axis of the outflow pipe 50.

The outflow pipe 50 may have, spaced apart from the end face 58, a radially outer shoulder 60 which is oriented upstream and which, with the outflow pipe 50 inserted into the housing 36, bears against the housing end face 46. Between the shoulder 60 and the end face 58, the outflow pipe 50 may have an exposed outer surface area 72, the exposed outer surface area 72 merging continuously into an outer surface of the housing 36. The exposed outer surface area 72 may be exposed even with the water outflow head 24 inserted into the receptacle 22.

Adjacently to the light transmission region 52, the outflow pipe 50 has a connecting region 64 in the manner of a connection piece. The outflow pipe 50 may narrow in a steplike manner in the transitional region from the light transmission region 52 to the connecting region 64.

An inside diameter of the outflow pipe narrows in, for example, two steps from the larger inside diameter of the light transmission region 52 to the smaller inside diameter of the connecting region 64. The inside diameter is selected such that a jet controller 110, described further below, can be inserted into the outflow pipe 50.

A light source 70 is arranged, preferably so as to bear directly against the input face 56 of the outflow pipe 50. The light from the light source 70 which is input at the input face 56 is transmitted by the light transmission region 52 to the end face 58, and is at least partially output from the outflow pipe 50 at the end face 58. Moreover, light may also be output from the outflow pipe 50 in the region of the exposed outer surface area 72 between the shoulder 60 and the end face 58, apart from in the region of the bead 42.

One or more, and preferably a plurality of, light emitting diodes (LED) 74 (nine in this example) are used as light source 70. The diodes 74 are preferably arranged at regular intervals in the circumferential direction, with a light cone axis of each diode 74 running at least approximately at right angles through the input face 56 and parallel to the axis of rotation of the outflow pipe 50. What is achieved by such an

4

orientation of the light cone axes is that as large a fraction as possible of the light emitted by the diodes 74 emerges through the end face 58 and through the outer surface area 72. In addition to or instead of white light, the light source 70 may also emit colored light.

The diodes 74 may be arranged on an annular circuit board 76 which surrounds the outflow pipe 50 in the connecting region 64. On a further circuit board 78 connected electrically to the annular circuit board 76, a control circuit for the light source 70, with a switching element 80, is arranged. The further circuit board 78 is fastened to the connecting region 64 of the outflow pipe 50 and above the annular circuit board 76 in the flow direction. The switching element 80 may be a key 80' with a key head 82. The key head 82 may pierce the bead 42 of the housing 36 in a leaktight manner below the pull-out aid 38 in the flow direction. By the key 80', depending on the configuration of the switch electronics on the further circuit board 78, the light source 70 can be activated. It is conceivable that the key 80' switches on the light source 70 in the event of a first actuation and switches it off again in the event of a further actuation, in which case the switch-off may take place with a time delay. A further possibility is that the light source 70 is switched off after a certain period of time by a timer.

The supply of electrical energy to the electrical circuit and the light source 70 is ensured via the electrical line 84 which is connected electrically to a power supply. The power supply is preferably mounted in a specific box below the washing table and is designed to be used in a wet area. A power pack is used as energy source for the power supply, although batteries or accumulators may also be used instead of the power pack.

In order to make a leaktight and at the same time fixed connection of the extendable hose 26 with water hose 28 and the water outflow head 24 with outflow pipe 50, the internal water hose 28 may project beyond the external casing hose 86. An end region of the extendable hose 26 may be surrounded completely by a sleeve 90. A clamping tenon 92 may be introduced into the water hose 28 from the free end, so that the water hose 18 is clamped firmly and sealingly between the clamping tenon 92 and the sleeve 90. The clamping tenon 92 has a flow duct, the diameter of which corresponds substantially to the diameter of the unstretched water hose 28. A length of the clamping tenon 92 is preferably selected such that the clamping tenon 92 can be introduced only into that region of the water hose 28 which projects beyond the casing hose 86, so that the clamping tenon 92 is spaced apart from the casing hose 86 in the flow direction. It is thereby possible to guide the electrical line 84, arranged between the casing hose 86 and the water hose 28, through a passage orifice 94 of the sleeve 90 to the further circuit board 78, without the electrical line 84 being clamped between the casing hose 86 and the clamping tenon 92.

The sleeve 90 may have an external thread and be screwed into the connection region 64 of the outflow pipe 50. In order to make a leaktight connection between the clamping tenon 92 and the outflow pipe 50, the clamping tenon 92 preferably has an annular face lying at right angles to the outflow direction, and the connecting region 64 preferably has a likewise annular contact face lying opposite the annular face of the tenon 92. A sealing ring 96 is preferably clamped between the annular face and the contact face. Adjacently to the contact face, the connecting region 64 is water-carrying and has an inside diameter which is substantially equal to the inside diameter of the clamping-tenon 92.

The housing 36, in a region in which the extendable hose 26 enters the water outflow head 24 and in a region in which the housing 36 bears against the light transmission region 52 of

the outflow pipe **50**, may be adhesively bonded in a leaktight manner to the extendable hose **26** and to the outflow pipe **50** respectively, with the result that a connection of the housing **26** to the outflow pipe **50** and to the casing hose **86** respectively is made, and neither dirt nor moisture can penetrate into the interior of the water outflow head **24**.

A jet controller **110** having an external thread **98** may be screwed into the outflow pipe **50** from the end lying downstream. The jet controller **110** preferably is of cylindrical design, has a form fitting into the outflow pipe, and is countersunk completely into the outflow pipe **50** in the flow direction. A crownlike plug-in region **112** lying downstream is formed by depressions **114** and elevations **114'** spaced in the circumferential direction and oriented in the flow direction. An O-ring **116** for sealing off the jet controller **110** with respect to the outflow pipe **50** is arranged on the jet controller **110** between the external thread **98** and the plug-in region **112** in the flow direction. The jet controller **110** used may be a perlator of the company Neoperl.

The crownlike plug-in region **112** makes it possible for the jet controller **110** to be exchanged in a simple way for a new jet controller of the same type. To exchange the jet controller **110**, the crownlike plug-in region of the new jet controller may be plugged onto, i.e., engaged with, the plug-in region **112** of the jet controller **110** installed in the outflow pipe **50**. By the new jet controller, the jet controller **110** screwed into the outflow pipe **50** can be screwed out. The new jet controller is screwed in in a similar way. On account of the crownlike plug-in region **112**, a special tool is not needed for exchanging the jet controller **110**.

The housing **36** may be manufactured from a plastic or a metal. The key head **82** of the key **80'** may, as shown in FIG. 2, be guided sealingly through the housing **36** or be spanned by a diaphragm. The diaphragm may, for example, be injection-molded, by means of a generally known two-component injection molding method, onto the housing manufactured from plastic.

A further embodiment of a water outflow head is shown in FIG. 3, only differences from the water outflow head described above being dealt with below. The same reference symbols are used for corresponding elements.

In this embodiment, the switching element **80** is integrated into the pull-out aid **38**. For this purpose, the pull-out aid **38** has an outwardly open recess which runs in an axial direction of the pull-out aid and into which the switching element **80** is inserted. A line duct **120** leads from a bottom of the recess into the interior of the water outflow head **24**. The switching element **80**, in the form of a key **80'**, may have a key head **82** which projects from the recess and which is completely surrounded in its circumferential direction by a protective cap **122**. The protective cap **122** may be screwed onto the pull-out aid **38** and is preferably elastomeric. A sealing ring **124** bearing against the inner surface area of the recess may be arranged between the protective cap **122** and the switching element **80**.

The electrical line **84** led through the extendable hose **24** is connected electrically to the circuit board **76** carrying the light source **70**. The circuit board **76**, which preferably is firmly clamped in a generally known way, also carries switch electronics. The switching element **80** may be connected to the circuit board **76** via an electrical switch line **126** led through the line duct **120**.

The housing **36** of the water outflow head **24** is preferably of thin-walled design, apart from in the region of the bead **42**. The bead engaging into the guide slot **40** may terminate in the longitudinal direction of the housing **36** at the same height as the housing **36**, so that the bead **42** does not project beyond the

housing end face **46**. The outflow pipe **50** has a peripheral exposed outer surface area **72**.

In the end region **44** located upstream, the housing **36** has a plurality of radial passages **128** arranged, preferably uniformly, in the circumferential direction. A cavity located in the radial direction between the outflow pipe **50** or the sleeve **90** and the housing **36** and in the longitudinal direction between the passages **128** and the input face **56** is filled with a filling compound, for example a two-component casting resin, which is introduced into the cavity through the passages.

In a modification of any of the above-described or below-described structures, the actuation element **16** of the mixer cartridge **15** may be operatively connected to a switching element arranged in the fitting housing **12**, so that the light source is switched on when water flows out.

In another modification of any of the above-described or below-described structures, instead of the mixer cartridge with an actuation element for the manual regulation of the water throughflow through the sanitary fitting **10**, an electronically controlled valve may be used. The valve may be connected to the electrical circuit in the water outflow head **24** via a control line of the multiwire electrical line **84**. As a result of the actuation of the switching element **80**, on the one hand, the light source **70** in the water outflow head **24** and, on the other hand, the electrically controlled valve, are activated.

In another modification of any of the above-described or below-described structures, the end face **58** does not lie at right angles to the outflow direction. The end face may lie at an angle to the outflow direction, may be a curved face or may have virtually any desired form, with the result that an incidence of light from the outflow pipe **50** can be influenced virtually as desired. The exposed outer surface area may likewise be varied in its optical properties, for example by the surface being roughened, with the result that the emerging light is scattered to a greater extent, or by the outer surface area being colored.

In another modification of any of the above-described or below-described structures, the circuit board **76** has a larger outside diameter, so that the circuit board **76** bears against the housing **36**.

A second exemplary embodiment is described with reference to FIGS. 5 and 6.

As FIG. 5 shows, a hollow-cylindrical fitting housing **140** of circular cross section of a sanitary fitting **10** according to this embodiment of the invention is oriented vertically. The sanitary fitting **10** is intended to be fastened in a known way on a mounting surface of a washing table by a fastening spindle **154** projecting downward. Inside the fitting housing **140** is arranged a housing inner body **156** (see FIG. 6) which bears against the fitting housing **140** in a radial direction. Two connecting lines **142**, **142'** project downward from the housing inner body **156** and are intended for supplying hot and cold water to the sanitary fitting **10**. A mixer cartridge **144** with an actuation element **16** arranged above the fitting housing **140** is inserted in a known way from above into the fitting housing **140**.

A circular-cylindrical outflow pipe **50** is inserted into the fitting housing **140**, so that the cylinder axis of the fitting housing **140** forms an angle of 55 degrees with the cylinder axis of the outflow pipe **50** and the outflow pipe **50** projects, inclined downward, from the fitting housing. The outside diameter of the outflow pipe **50** is preferably smaller than the outside diameter of the fitting housing **140**.

The outflow pipe **50** is preferably manufactured from a light-permeable material, the material having transparent and/or translucent properties. For example, the outflow pipe

50 may be manufactured from glass or acrylic glass. The surface of the pipe is designed to be smooth, but may also be rough or roughened, with the result that optical properties of the outflow pipe **50** can be influenced.

As shown in FIGS. **5** and **6**, the outflow pipe **50** has an end face **58** at an end located downstream and an input face **56**, lying opposite the end face **58**, at an end located upstream. An inside diameter **I** of the outflow pipe **50** is preferably constant, apart from in a mounting region which is adjacent to the input face **56** and which lies within the fitting housing **140**. The mounting region preferably has a larger inside diameter than the inside diameter **I**. In the mounting region, a threaded sleeve **146** having an internal thread may be inserted, preferably glued, into the outflow pipe **50**. Below the mounting region in the flow direction, the outflow pipe **50** is water-carrying. The threaded sleeve **146** preferably has screwed into it a threaded bush **150** which projects out of the outflow pipe **50** at the input face **56**. The threaded bush **150** may be surrounded by a holding ring **152** which is in the form of a U-profile and the orifice of which is oriented in the direction of the input face **56** and in which an annular circuit board **76** is arranged. The annular circuit board **76** carries a light source **70**, which may include a plurality of light emitting diodes (LED) **74**, preferably manufactured as surface-mountable components (SMD). The diodes **74** preferably bear against the input face **56** of the outflow pipe **50** in such a way that the light cone axis of each diode **74** runs at right angles through the input face **56** and the end face **58** and parallel to the cylinder axis of the outflow pipe **50**. The diodes **74** are preferably attached to the circuit board **76** at regular intervals in a circumferential direction. Instead of or in addition to the diodes **74**, of course, light sources **70** of another design may be used.

Light introduced by the diodes **74** into the outflow pipe **50** is guided from the latter to the end face **58** and to a radially outer surface area **72**, lying outside the fitting housing **140**, of the outflow pipe **50** and is output from the latter at the end face **58** and also at the exposed surface area **72**.

The threaded sleeve preferably has an external thread above the holding ring **152** in the flow direction.

The fitting housing **140** has a recess, through which the outflow pipe **50** is led. The housing inner body **156** may have a circular-cylindrical stepped blind hole for receiving the outflow pipe **50**, the blind hole having, adjacently to the fitting housing **12**, a larger inside diameter corresponding to the outside diameter of the outflow pipe **50** and, spaced apart from the fitting housing **12**, a smaller inside diameter. The region of the blind hole having the larger inside diameter is designed in such a way that the outflow pipe **50** and the holding ring **152** can be inserted into this region. The blind hole may have, in the region of the smaller diameter, an internal thread into which the threaded bush **150** is screwed.

A mixed water duct **158** coming from the mixer cartridge **144** issues into a bottom region **160** of the blind hole and carries mixed water from the mixer cartridge **144** to the outflow pipe **50**.

The threaded bush **150** is preferably screwed into the housing inner body **156** into abutment against the bottom region **160**. The threaded bush **150** has, radially on the inside, an abutment face which faces the bottom region **160** and against which a jet controller **110** bears. Between the jet controller **110** and the bottom region **160** may be clamped a sealing ring **162**. The sealing ring **162** forms a leaktight transition from the mixing water duct **158** to the threaded bush **150** having the jet controller **110** inserted in it, so that outflowing water cannot reach a radially outer side of the threaded bush **150** and of the outflow pipe **50**.

In order to lead a multiwire electrical line **84** through the housing inner body **156** to the circuit board **76** having the light source **70** arranged on it, the housing inner body **156** has a line duct **164** which issues into the blind hole, into a region in which the holding ring **152** is arranged. The holding ring **152** has, adjacently to the line duct **164**, a passage orifice **166** oriented in a radial direction, so that the electrical line **84** can be led through the line duct **164** and through the passage orifice **166**. The electrical line **84** is connected electrically, on the one hand, to the circuit board **76** arranged in the holding ring **152** and, on the other hand, to the switch electronics which are controlled by a switching element **80**.

As shown in FIG. **5**, the switching element **80** is a generally known switching element for room lighting. By the switching element **80**, a power supply to the switch electronics is switched on and switched off. As a result of the fairly slender type of construction, the switch electronics are preferably mounted in a box **170** below the washing table. The box **170** may have arranged in it, for example, a transformer, the power supply of which can be switched on or switched off by this switching element **80** and which supplies power to the switch electronics.

Many diverse possibilities are conceivable for switching on and switching off the light source **70**, in any of the above-described or below-described structures. For example, both switch-on and switch-off may take place via a dimmer switch, so that the light intensity increases or decreases continuously.

Further, the light intensity can be adapted to the current light conditions in the room by a sensor.

In another embodiment, the switching element may be designed as a flow monitor which detects a water flow through at least one of the connecting lines **142**, **142'**. In the event of a water flow through the connecting lines **142**, **142'** and therefore through the sanitary fitting **10**, the flow monitor activates the switch electronics in such a way that the light source is supplied with power when water flows out of the sanitary fitting **10**.

Moreover, the light source may be switched off with a time delay, and/or the valve of the mixer cartridge **144** may be closed with a time delay.

In another embodiment, the switching element may be designed as an infrared detector, by which an electromagnetic valve of the sanitary fitting is activated in a known way. Moreover, the switching element designed as an infrared detector may be used for controlling the switch electronics, so that the light source **70** is supplied with power when water flows out.

Another exemplary embodiment is shown in FIG. **7**. Only differences from the preceding exemplary embodiment are dealt with below, the same reference symbols being used for corresponding elements.

The outflow pipe **50** has, adjacently to the input face **56**, a mounting region which lies partially outside the fitting housing **140**. The inside diameter of the outflow pipe **50** widens conically from the inside diameter **I** outside the mounting region to an inside diameter at the input face **56**. The threaded bush **150** has, at its end region inserted into the outflow pipe **50**, an outer face fitting with an inner surface area of the mounting region of the outflow pipe **50** and is preferably glued into the outflow pipe **50**.

The threaded bush **150** is screwed into the housing inner body **156** into abutment against the holding ring **152**, so that the threaded bush **150** does not bear against the bottom region **160** of the blind hole.

9

In another embodiment, the switching element operatively connected to the actuation element **16** in such a way that the light source **70** is switched on when water flows out through the outflow pipe **50**.

In another embodiment, the line duct **164** is filled with a filler, for example a two-component casting resin.

While the invention has been described in conjunction with specific embodiments, these embodiments should be viewed as illustrative and not limiting. Various changes, substitutes, improvements or the like are possible within the spirit and scope of the invention.

What is claimed is:

1. A sanitary fitting comprising:
 - a light-permeable water-carrying outflow pipe that has (i) an exposed end face and (ii) an input face located upstream of the exposed end face; and
 - a light source disposed against the input face, wherein light from the light source is input into a wall of the outflow pipe at the input face, is guided in the wall, and emerges at the end face, and the input face lies opposite the end face.
2. The sanitary fitting as claimed in claim 1, wherein light is output from an outer peripheral surface area of the outflow pipe.
3. The sanitary fitting as claimed in claim 1, wherein the light source has one or more light emitting diodes (LED) which are designed as a surface-mountable component.
4. The sanitary fitting as claimed in claim 1, wherein the outflow pipe and the light source are built into a water outflow head.
5. The sanitary fitting as claimed in claim 4, wherein the sanitary fitting has (i) a fitting housing and (ii) a guide pipe

10

which projects from the fitting housing and which has, in a free end region, a receptacle for the water outflow head.

6. The sanitary fitting as claimed in claim 5, wherein an extendable hose connected to the water outflow head runs in the guide pipe, the extendable hose having a water hose and an electrical line in order to supply water and power to the water outflow head.

7. The sanitary fitting as claimed in claim 6, wherein the water outflow head, together with the extendable hose, can be pulled out of the receptacle and can be inserted into the receptacle again.

8. The sanitary fitting as claimed in claim 1, wherein the sanitary fitting has a fitting housing which is intended to be fastened to a holding face, an end region of the outflow pipe lying opposite the end face is inserted into the fitting housing, and the outflow pipe projects out of the fitting housing.

9. The sanitary fitting as claimed in claim 8, wherein a surface area, lying outside the fitting housing, of the outflow pipe is exposed.

10. The sanitary fitting as claimed in claim 1, wherein the sanitary fitting has a switching element for controlling the light source.

11. The sanitary fitting as claimed in claim 10, wherein the switching element controls, on the one hand, the light source and, on the other hand, a valve for controlling the water flow.

12. The sanitary fitting as claimed in claim 10, wherein an actuation element for actuating a mixer cartridge for controlling the water flow is operatively connected to the switching element for the actuation of the switching element.

13. The sanitary fitting as claimed in claim 10, wherein the switching element is arranged on a water outflow head.

* * * * *