US008743790B2

(12) **United States Patent**
Taylor et al.

(10) **Patent No.: US 8,743,790 B2**
(45) **Date of Patent: Jun. 3, 2014**

(54) **RESIDENTIAL GATEWAY**

(75) Inventors: **Darrell Taylor**, Lithonia, GA (US); **Alfonso Jones**, Suwanee, GA (US); **Steven McDonald**, Locust Grove, GA (US)

(73) Assignee: **AT&T Intellectual Property I, L.P.**, Atlanta, GA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/593,704**

(22) Filed: **Aug. 24, 2012**

(65) **Prior Publication Data**

US 2012/0320761 A1 Dec. 20, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/545,940, filed on Aug. 24, 2009, now Pat. No. 8,279,805.

(51) **Int. Cl.**
H04W 4/00 (2009.01)

(52) **U.S. Cl.**
USPC **370/328**; 370/401; 709/223; 725/110

(58) **Field of Classification Search**
CPC H04N 21/43615; H04N 5/4403; H04L 29/06462; H04L 29/06503; H04L 29/08657
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,740,176	A	4/1998	Gupta et al.	
5,808,767	A	9/1998	Williams et al.	
6,018,452	A	1/2000	Meyerhoefer et al.	
6,112,232	A	8/2000	Shahar et al.	
6,252,952	B1	6/2001	Kung et al.	
6,272,151	B1	8/2001	Gupta et al.	
6,526,581	B1	2/2003	Edson	
6,684,030	B1	1/2004	Taylor et al.	
6,847,718	B1	1/2005	Hiraoka	
6,931,659	B1	8/2005	Kinemura	
7,020,249	B1	3/2006	Haines et al.	
7,149,474	B1	12/2006	Mikhak	
7,180,988	B2	2/2007	Phillips et al.	
7,239,628	B1	7/2007	Pendleton et al.	
7,558,251	B1 *	7/2009	Huang et al.	370/352
8,006,275	B1	8/2011	Poole et al.	
8,085,798	B2	12/2011	Cha	
8,279,805	B2	10/2012	Taylor et al.	
2002/0009099	A1	1/2002	D'Onofrio	
2002/0105955	A1	8/2002	Roberts, III et al.	

(Continued)

OTHER PUBLICATIONS

2WIRE.Com: iNID, Extend Your Network Into Subscribers' Homes With the 2WIRE Homeportal iNID (Intelligent Network Interface Device), The Industry's First Outdoor Residential Gateway, search dated Jun. 9, 2009, 2 pages.

(Continued)

Primary Examiner — Jung Park
(74) *Attorney, Agent, or Firm* — Toler Law Group, PC

(57) **ABSTRACT**

A particular residential gateway includes a network interface, a connector interface to receive a signal via one or more communication lines, and a power coupling device to receive power from at least one of the one or more communication lines. The residential gateway includes a first module to receive first data via the signal and to route the first data to a first device coupled to the network interface. The first module is powered using the power received from the at least one communication line by the power coupling device.

20 Claims, 6 Drawing Sheets



(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0199203	A1	12/2002	Duffy et al.	
2003/0035540	A1	2/2003	Freeman et al.	
2003/0161333	A1	8/2003	Schain et al.	
2003/0233667	A1	12/2003	Umipig et al.	
2004/0074656	A1	4/2004	Bloodworth et al.	
2004/0172657	A1	9/2004	Phillips et al.	
2004/0179541	A1	9/2004	Godwin	
2004/0228336	A1	11/2004	Kung et al.	
2004/0233860	A1	11/2004	Campbell et al.	
2005/0086694	A1	4/2005	Hicks et al.	
2005/0235307	A1	10/2005	Relan et al.	
2005/0265240	A1*	12/2005	Jain et al.	370/241
2006/0187071	A1	8/2006	Kortum et al.	
2006/0209857	A1*	9/2006	Hicks, III	370/401
2006/0251094	A1	11/2006	Van Vleck et al.	
2006/0291493	A1	12/2006	Schley-May et al.	
2007/0217436	A1*	9/2007	Markley et al.	370/401
2007/0272440	A1	11/2007	Grunwald et al.	
2007/0276771	A1	11/2007	Saeger	
2007/0277205	A1*	11/2007	Grannan	725/80
2008/0205285	A1	8/2008	Scherer	
2009/0100492	A1	4/2009	Hicks, III et al.	
2010/0020821	A1	1/2010	Droms et al.	
2010/0023994	A1	1/2010	Taylor et al.	
2010/0071009	A1	3/2010	Xiu et al.	
2010/0083337	A1	4/2010	Williams et al.	
2010/0107186	A1	4/2010	Varriale et al.	
2011/0044347	A1	2/2011	Taylor et al.	

OTHER PUBLICATIONS

Non-Final Office Action for U.S. Appl. No. 12/545,940 received from the United States Patent and Trademark Office (USPTO) mailed Jul. 18, 2011, 20 pages.

Final Office Action for U.S. Appl. No. 12/545,940 received from the United States Patent and Trademark Office (USPTO) mailed Jan. 18, 2012, 14 pages.

Notice of Allowance for U.S. Appl. No. 12/545,940 received from the United States Patent and Trademark Office (USPTO) mailed Aug. 24, 2012, 10 pages.

"Adtran Quad FXS+ Voice Interface Card (1202300L1)," retrieved from <<http://www.mysimon.com/9015-11587_8-20180039.html>>, Jul. 18, 2008, Adtran, Inc. Huntsville, Alabama, 2 pages.

"Plug-and-play," retrieved from <<http://en.wikipedia.org/wiki/Plug-and-play>>, Jul. 18, 2008, Wikipedia, the free encyclopedia, San Francisco, California, 2 pages.

* cited by examiner


VoIP Device
132
Computing Device
134
138
STB
136
IPv4 / IPv6 / TCP Signal
VoIP Signal
HPNA Signal
IPTV Device
Network
(e.g., LAN)
120
Network Interface
102
103
Voice Module
104
Video Module
107
Testing
Module
100
108
Network
Module
Power
Coupling
Device
Data
Communication
Interface
105
106
109
Connector Interface
101
Communication Line(s)
(Composite Signal)
110

FIG. 1


200
Removable plug-in module(s)
250
Connection manager
252
Video unit
254
Output driver
256
Amp
258
Test unit
260
Controller
262
Memory
264
Power coupling device
266
Removable plug-in module
270
Data router
272
231
233
232
Lightning protection unit
Network interface
Modular interface connector(s)
242
Modular interface connector(s)
244
Housing
240
236
238
Network interface
230
202
203
Field unit
Video line unit
DSLAM
Maintenance unit
204
280
282
284
Communication Network
206
234
290
Provisioning Record(s)
292
210
212
Splitter
220
Splitter
222
STB
230
STB
228
STB
226
Amp
224
214
216
218

FIG. 2


Remote communication network
305
300
306
304
Housing
Lightning protection unit
310
NID
Remote network interface
308
Interface connector(s)
Removable plug-in module(s)
302
320
322
Power coupling device
VRU
Gateway
Controller
330
332
334
336
338
340
342
344
Diagnostic unit
Line conditioning unit
Connection manager
Memory
312
Local network interface
RJ45
RJ11
F
314
316
318

FIG. 3


400
Couple a network interface device (NID) to a coaxial wiring system at a customer premise
402
Couple the NID to a telephone wiring system at the customer premise
404
Connect the NID to at least one set of communication lines to couple the NID to a remote communication network
406
Connect a plug-in module to a modular interface connector of the NID, where the plug-in module receives power via the at least one set of communication lines
408
Detect reception of the plug-in module
412
Automatically enable access to voice, video and data services
414
Automatically initialize video data processing
410
Store a provisioning record at a database, where the provisioning record associates the plug-in module with a subscriber account associated with the customer premise
416
Receive communication data from the remote communication network
418
Route the communication data to one or more devices coupled to the NID
420
Store performance data associated with one or more components of the NID
422
Operational criteria
426
Analyze the performance data
Compare the performance data to one or more operational criteria to identify one or more operational concerns before the one or more operational concerns are perceptible by a user
424
423
Communicate results of the performance data analysis to a network unit of the remote communication network
428
Disable access to voice, video or data services in response to removal of the plug-in module from the interface connector
430

FIG. 4


500
Insert a residential gateway into an outdoor network interface device (NID) coupled to one or more communication lines
502
Couple the NID to a communication network that transmits a composite signal including voice data, video data, and network data via the one or more communication lines, where the residential gateway has an input to receive the composite signal from the NID and includes at least one module that is powered by power received via at least one of the one or more communication lines
504
Enable/disable access to one or more of voice services, video services, and data services provided by the communication network by sending a connection/ disconnection message to the residential gateway
506

FIG. 5


600
602
Processor
Instructions
624
604
Main Memory
Instructions
624
606
Static Memory
Instructions
624
620
Network Interface Device
630
Residential Gateway
Network
626
608
610
Video Display
612
Alpha-Numeric Input Device
614
Cursor Control Device
616
Drive Unit
622
Computer Readable Medium
624
Instructions
618
Signal Generation Device

FIG. 6

RESIDENTIAL GATEWAY

CLAIM OF PRIORITY

This application is a Continuation Patent Application of, and claims priority from, U.S. Pat. No. 8,279,805, file as Ser. No. 12/545,940 filed on Aug. 24, 2009, and entitled "RESIDENTIAL GATEWAY," which is hereby incorporated by reference in its entirety.

BACKGROUND

Improvements in technology have led to an increase in service providers offering so-called "triple play" services. Triple play services provide voice, video and data service to a subscriber from a single provider. Offering triple play services that meet customer expectations in an efficient manner can be challenging. For example, providing new services to a customer or terminating existing services for a customer may require dispatching one or more service technicians to customer premises. Technicians may also need to be dispatched to customer premises when a customer complains about a service outage. Occasionally, the first dispatched technician diagnoses the problem and determines a that a second technician must be dispatched in order to solve the problem, lengthening service outage response time and further aggravating the customer.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a block diagram of a particular embodiment of a system including a residential gateway;

FIG. **2** is a block diagram of a first embodiment of a system including a network interface device into which the residential gateway of FIG. **1** may be inserted;

FIG. **3** is a block diagram of a second embodiment of a system including a network interface device into which the residential gateway of FIG. **1** may be inserted;

FIG. **4** is a flow chart of an embodiment of a method of using a network interface device;

FIG. **5** is a flow chart of an embodiment of a method of using a residential gateway and a network interface device; and

FIG. **6** is a block diagram of an embodiment of a general computer system.

DETAILED DESCRIPTION

Residential gateways and methods are disclosed. In a particular embodiment, a residential gateway includes a connector interface to receive a composite signal including voice data, video data, and network data via one or more communication lines. The residential gateway also includes a network interface and a power coupling device to receive power via at least one of the one or more communication lines. The residential gateway further includes a voice module to route the voice data to a voice-enabled device coupled to the network interface, a video module to route the video data to a video-enabled device coupled to the network interface, and a network module to route the network data to a computing device coupled to the network interface. The residential gateway includes a testing module to communicate test results to an external device via a data communication interface. At least one of the voice module, the video module, the network module, and the testing module is powered using the power received by the power coupling device.

In another particular embodiment, a method includes inserting a residential gateway into an outdoor network interface device (NID) coupled to one or more communication lines. The method also includes coupling the NID to a communication network that transmits a composite signal including voice data, video data, and network data via the one or more communication lines. The residential gateway has an input to receive the composite signal from the NID and includes at least one module that is powered by power received via at least one of the one or more communication lines.

In another particular embodiment, an apparatus includes an outdoor housing, a network interface device (NID) within the outdoor housing, and a residential gateway connected to the NID. The residential gateway includes a connector interface to receive a very high speed digital subscriber line 2 (VDSL2) signal including voice data, video data, and network data from the NID via one or more communication lines. The residential gateway also includes a power coupling device to receive power via at least one of the one or more communication lines. The residential gateway further includes a voice module to route the voice data to a voice-enabled device, a video module to route the video data to a video-enabled device, and a network module to route the network data to a computing device. The residential gateway includes a testing module to detect errors in at least one of the voice module, the video module, and the network module. The testing module can also control one or more status indicators to indicate an operational status of the residential gateway and communicates test results to an external device. At least one of the voice module, the video module, the network module, and the testing module is powered by the power coupling device.

FIG. **1** depicts a particular embodiment of a system including a residential gateway **100**. The residential gateway **100** receives a composite signal **110** via one or more communication lines. In a particular embodiment, the composite signal **110** is received from a provider of triple play services. The residential gateway **100** is also coupled to a network **120**. In a particular embodiment the network **120** is a local area network (LAN) located at a customer premises, such as a residence or business.

The composite signal **110** carried by the one or more communication lines may include voice data, video data, and network data. For example, the composite signal **110** may be a very high speed digital subscriber line 2 (VDSL2) signal, an asymmetric DSL2 plus (ADSL2+) signal, a fiber optic communication signal, or an optical carrier (OC) signal. In a particular embodiment, a connector interface **101** that receives the composite signal **110** is a coaxial interface.

The residential gateway **100** includes a network interface **102** coupled to the network **120** and configured to communicate with one or more devices that are also coupled to the network **120**. For example, the network interface **102** may enable communication with voice-enabled devices, video-enabled devices, and computing devices. Voice-enabled devices include, but are not limited to, Voice over Internet Protocol (VoIP) devices such as a VoIP device **132**. Computing devices include, but are not limited to, laptop computers and desktop computers (e.g., a computing device **134**). Video-enabled devices include, but are not limited to, Internet Protocol Television (IPTV) devices such as a set-top box (STB) **136** connected to a television **138**.

The residential gateway **100** includes a voice module **103**, a video module **104**, and a network module **105**. The voice module **103** may route voice data included in the composite signal **110** to voice-enabled devices, such as the VoIP device

132. For example, the voice module **103** may extract voice data from the composite signal **110**, convert the extracted voice data into a VoIP signal, and route the VoIP signal to the VoIP device **132**. The video module **104** may route video data included in the composite signal **110** to video-enabled devices, such as the set-top box **136**. For example, the video module **104** may extract video data from the composite signal **110**, convert the extracted video data into a Home Phone line Networking Alliance (HPNA) protocol signal, and transmit the HPNA signal to the set-top box **136**. The network module **105** may route network data included in the composite signal **110** to computing devices, such as the computing device **134**. For example, the network module **105** may extract network data from the composite signal **110**, convert the extracted network data into one or more of an Internet Protocol version 4 (IPv4) format, an Internet Protocol version 6 (IPv6) format, and Transmission Control Protocol (TCP) format, and route the IPv4/IPv6/TCP signal to the computing device **134**. In a particular embodiment, one or more of the extraction and conversion operations performed by the modules **103-105** include a demodulation operation.

The residential gateway **100** also includes a testing module **107**. The testing module **107** may conduct tests on one or more of the composite signal **110**, the modules **103-105**, the interfaces **101**, **102**, the network **120**, the devices **132**, **134**, **136**, and itself. For example, the testing module **107** may be configured to monitor and detect errors in the composite signal **110** (e.g., a drop in signal strength of the composite signal **110**). It will thus be appreciated that the testing module **107** may monitor and detect problems both upstream (e.g., off customer premises) as well as downstream (e.g., at the customer premises) of the residential gateway **100**.

The residential gateway **100** includes a data communication interface **108**. In a particular embodiment, the data communication interface **108** is operable by the testing module **107** to communicate monitoring and test results to a device connected to the data communication interface **108**. For example, the data communication interface **108** may be a Universal Serial Bus (USB) interface, an Ethernet interface, a serial interface, or any combination thereof. In a particular embodiment, the testing module **107** is configured to conduct tests on the data communication interface **108**.

In a particular embodiment, the testing module **107** is configured to transmit test results to a provider (e.g., a triple play services vendor) of the composite signal **110** via the data communication interface **108**. For example, the testing module **107** may periodically transmit monitoring and testing data to a technical support center of the triple play services vendor.

The residential gateway **100** further includes a power coupling device **106**. The power coupling device **106** receives power via one or more of the communication lines carrying the composite signal **110**. One or more of the modules **103**, **104**, **105**, **107** may be powered by the power coupling module **106**.

In a particular embodiment, the residential gateway **100** may include one or more status indicators **109** to indicate an operational status of the residential gateway **100**. For example, the status indicators **109** may include three light emitting diodes (LEDs)—a red LED to indicate an "inoperational" status, a yellow LED to indicate a "possible error status," and a green LED to indicate a "normal" status. In a particular embodiment, the testing module **107** is configured to control the status indicators **109** based on test results produced by the testing module **107**. In a particular embodiment, the status indicators **109** include audible status indicators (e.g., alarms) as well as visual status indicators.

In operation, the connector interface **101** of the residential gateway **100** may receive the composite signal **110**, where the composite signal **110** includes voice data, video data, and network data. The modules **103-105** may receive power from the power coupling device **106** and may route the voice data, video data, and network data to the devices **132**, **134**, and **136** via the network **120**. During operation, the testing module **107** may monitor and conduct tests on or more of the components of the system of FIG. **1**, control the status indicators **109** based on the test results, and transmit the test results to a provider of the composite signal **110** and to devices connected to the data communication interface **108**.

It will be appreciated that a technician or other service personnel may download monitoring and testing data for the system of FIG. **1** by connecting a device to the data communication interface **108**. Further, by monitoring and detecting errors both upstream and downstream of the residential gateway **100**, and by transmitting test data to providers, the residential gateway **100** may reduce the time taken to fix problems that customers may experience in their voice, video, or network services. For example, a provider deploying the residential gateway **100** may know whether to send a technician specializing in solving off-premises problems (e.g., when the problem detected is upstream of the residential gateway **100**) or a technician specializing in solving on-premises problems (e.g., when the problem detected is downstream of the residential gateway **100**). It will also be appreciated that the power coupling device **106** may enable the residential gateway **100** to be operable without requiring a customer to provide (and pay for) electricity to the residential gateway **100**.

FIG. **2** depicts a first particular embodiment of a system including a network interface device. The system is designated generally **200**. The system **200** includes a network interface device **202** coupled to a field unit **204** of a communication network **206**. For example, the communication network **206** may be associated with a provider of triple play services. In a particular embodiment, the network interface device **202** may be attached to an exterior of a customer premise, such as a residence or business, to terminate communication lines from the communication network **206** and to terminate communication lines from the customer premise.

The network interface device **202** may receive data from the communication network **206** and distribute the data to devices at a customer residence. For example, the devices to which the data is distributed may include one or more telephones **210**, one or more computers **212**, one or more display devices **214-218**, one or more set-top box devices **226-230**, or any combination thereof. The data may include one or more of voice data, video data, and network data. The network interface device **202** may send the data to the devices via one or more intermediate devices. For example, video data may be provided to the one or more display devices **214-218** via one or more splitters **220** and **222**, one or more amplifiers **224**, the one or more set-top box devices **226-230**, or any combination thereof.

The network interface device **202** may include a housing **230** adapted to provide climate protection to components housed therein. In a particular embodiment, the housing **230** may also be adapted to restrict access to one or more portions of the network interface device **202**. For example, the network interface device **202** may include a customer accessible portion and a service provider accessible portion. The network interface device **202** may also include a lightning protection unit **232**. The lightning protection unit **232** may include lightening protection coils adapted to protect electronic equipment within the network interface device **202** (at the customer's residence) from harmful effects of a lightning strike at the

communication network **206**, the field unit **204**, the network interface device **202**, or any connection point or communication line there between.

In a particular embodiment, the network interface device **202** includes a first network interface **233** including one or more connectors to terminate one or more communication lines **203** from the communication network **206**. The communication lines **203** may include one or more twisted pair lines (e.g., telephone lines), one or more non-twisted lines (e.g., a T-1 line, an E-1 line or a coaxial cable line), or any combination thereof. The network interface device **202** also includes a second network interface **234** including one or more connectors **236-240** to terminate communication lines of the customer premise. The connectors **236-240** may include one or more connectors for a twisted pair line, a non-twisted pair line, and a coaxial cable line. For example, the connectors may include a standard telephone jack (e.g., an RJ11 jack), an Ethernet jack (e.g., an RJ45 jack), a coaxial line connection (e.g., an F connector), or any other local network connector to connect a wiring system at the customer premise to the network interface device **202**.

In a particular embodiment, the network interface device **202** includes one or more modular interface connectors **242**, **244**. The modular interface connectors **242**, **244** may be adapted to receive one or more removable plug-in modules that provide particular functionality to the network interface device **202**. In an illustrative embodiment, the one or more removable plug-in modules include the residential gateway **100** of FIG. **1**. In an illustrative embodiment, when no removable plug-in modules are provided, the network interface device may provide access only to voice service (e.g., telephone service) at the customer residence. Video service (e.g., television), network service (e.g., computer data communications), or both may be conveniently added to the network interface device **202** via the one or more removable plug-in modules. In other embodiments, other services or combinations of services available via the communication network **206** can be provided by the network interface device **202** alone or by the network interface device **202** in combination with one or more removable plug-in modules. For example, the network interface device **202** alone (i.e., without any removable plug-in modules) may not provide access to any of the services of the communication network **206**. In another example, one removable plug-in module may provide access to voice, video, and network services.

In the particular example illustrated in FIG. **2**, a first modular interface connector **242** is adapted to receive a first removable plug-in module **250**. The first removable plug-in module **250** may include a video unit **254** to access video services available via the communication network **206**. For example, the video unit **254** may include the video module **104** of FIG. **1**. When the first removable plug-in module **250** is coupled to the first modular interface connector **242**, the video unit **254** may be enabled to receive video data from the field unit **204** via the one or more communication lines **203** and to process the video data for communication via at least one coaxial line or at least one twisted pair line to the one or more display devices **214-218**. In a particular embodiment, the video unit **254** may include an output driver **256** adapted to communicate the processed video data via wiring at the customer premise (e.g., one or more coaxial lines or one or more twisted pair lines) to at least one of the set-top box devices **226-230** for display at one or more of the display devices **214-218**.

In an illustrative embodiment, the video data may include Internet Protocol Television (IPTV) data. The video data may be communicated from a video line unit **280** of the field unit **204**. The video line unit **280** may modulate the video data and communicate the modulated video data via the one or more communication lines **203** to the network interface device **202**. At the network interface device **202**, the video unit **254** may demodulate the video data to communicate the data via the second network interface **234** to one or more devices at the customer premise. In a particular embodiment, the video line unit **280** modulates the video data in accordance with a very high speed digital subscriber line (VDSL) protocol and the video unit **254** demodulates the modulated video data to generate a Home Phoneline Networking Alliance (HPNA) protocol signal for communication via the second network interface **234** to devices at the customer premise.

In a particular embodiment, the output driver **256** may include a signal amplifier **258**. The signal amplifier **258** may be adapted to amplify the processed video signal for communication to the one or more user devices coupled to the second network interface **234**. In an illustrative embodiment, the network interface device **202** and the display devices **214-218** at the customer premise are coupled to a pre-existing coaxial cable network (i.e., a coaxial cable network that was installed at the customer premise before the network interface device **202** was installed at the customer premise). In this embodiment, the coaxial cable network may include one or more communication paths that are not direct paths between the network interface device **202** and the display devices **214-218** or the set top box devices **226-230**. For example, the coaxial cable network may include the splitters **220** or **222**, the amplifier **224**, or other devices (not shown). The signal amplifier **258** may be adapted to amplify the signal sufficiently to communicate the amplified signal to the set-top box devices **226-230** or the display devices **214-218** for display.

In a particular embodiment, the first removable plug-in module **250** may also include a test unit **260**. In an illustrative embodiment, the test unit **260** may implement one or more of the functionalities described herein with reference to the testing module **107** of FIG. **1**. The test unit **260** may be adapted to loop signals received from the field unit **204** back to the field unit **204** in response to a signal received from the communication network **206**. For example, the test unit **260** may loopback the signals in response to a loopback test signal received from a maintenance unit **284** of the field unit **204** or from the communication network **206**. Loopback testing may enable the maintenance unit **284** to identify communication problems between the field unit **204** and the first plug-in module **250**, or between the communication network **206** and the first plug-in module **250**.

In a particular embodiment, the first removable plug-in module **250** may also include a connection manager **252**. In an illustrative embodiment, the connection manager **252** may implement one or more of the functionalities described herein with reference to the testing module **107** of FIG. **1**. The connection manager **252** may be operable to manage a connection to the communication network **206** via the one or more communication lines **203**. For example, the connection manager **252** may be operable to communicate with the video line unit **280**, a digital subscriber line modem (DSLAM) **282** or another component of the field unit **204** to condition the one or more communication lines **203** for data communication.

In a particular embodiment, the connection manager **252** or the test unit **260** may be operable to execute function testing of other components of the first removable plug-in module **250**, another removable plug-in module (e.g., a second removable plug-in module **270**), another component of the network interface device **202**, a device at the customer premise (such as one of the set-top box devices **226-230**), or any combination thereof. In an illustrative embodiment, the

connection manager **252** or the test unit **260** may communicate results of the testing to the maintenance unit **284** for analysis and follow-up (e.g., to dispatch an appropriate technician to repair a detected problem). In another illustrative embodiment, the connection manager **252** or the test unit **260** may store performance data associated with the tested components at a memory **264**. The connection manager **252** or the test unit **260** may analyze the performance data and communicate results of the performance data analysis to the maintenance unit **284**. For example, analyzing the performance data may include comparing the performance data to one or more operational criteria associated with a particular component to identify one or more operational concerns before the operational concern becomes perceptible by a user at the customer premise. The connection manager **252** or the test unit **260** may also be adapted to provide a status display indicating whether one or more communication problems or other operational concerns have been identified. For example, the network interface device **202** may include a visual status display **231**, such as red, yellow and green lights that indicate whether the network interface device **202** or one or more components of the network interface device **202** are functioning properly and able to communicate with the communication network **206**, as described herein with reference to the status indicators **109** of FIG. **1**.

In a particular embodiment, the first removable plug-in module **250** includes a controller **262**. The controller **262** may be adapted to detect connection of the first removable plug-in module **250** to the first modular interface connector **242**. In response to detecting connection of the first removable plug-in module **250** to the first modular interface connector **242**, the controller **262** may automatically initialize video data processing at the video unit **254**. Thus, when the first removable plug-in module **250** is connected to the first modular interface connector **242**, the first removable plug-in module **250** may be automatically initiated and may automatically initiate communication with the communication network **206** to allow functionality of the first removable plug-in module **250** to be accessible to the user.

In a particular embodiment, the network interface device **202** and the one or more removable plug-in modules **250** and **270** may be line powered. For example, the first removable plug-in module **250** may include a power coupling device **266**, similar to the power coupling device **106** of FIG. **1**. The power coupling device **266** may be adapted to receive power via the one or more communication lines **203** from the communication network **206**. The power coupling device **266** may provide operating power to the network interface device **202** and to one or more of the components of the network interface device **202** (e.g., the first removable plug-in module **250**, the second removable plug-in module **270**, the visual display **231**, other removable plug-in modules or other components, or any combination thereof). By providing line power via one or more of the removable plug-in modules **250** and **270**, no additional power interface may be required for the network interface device **202**. For example, no other connection to a power source outside the network interface device **202** may be required. Additionally, by providing line power via one or more of the removable plug-in modules **250** and **270**, the network interface device **202** may remain unpowered until the one or more removable plug-in modules **250** and **270** are connected to modular interface connectors **242** and **244**. In a particular illustrative embodiment, each removable plug-in module **250** and **270** may include a power coupling device to provide line power for itself and/or one or more other components of the network interface device **202**.

In a particular embodiment, the network interface device **202** includes the second modular interface connector **244**. The second modular interface connector **244** may be adapted to receive a second removable plug-in module **270**. The second removable plug-in module **270** may enable other functionality at the network interface device **202**. For example, where the first removable plug-in module **250** enables access to video services, the second removable plug-in module **270** may enable access to voice services or computer data communications. In another example, other functionality may be enabled via the second removable plug-in module **270**, for example administrative functions, such as line conditioning, testing, performance monitoring, power coupling, or other functions of the connection manager **252**, the test unit **260**, the controller **262**, the memory **264**, the power coupling device **266**, or any combination thereof may be provided via the second removable plug-in module **270**.

In a particular embodiment, the second removable plug-in module includes a data router **272**. In an illustrative embodiment, the data router **272** is configured to implement one or more of the functionalities as described herein with respect to the voice module **103**, the video module **104**, and the network module **105** of FIG. **1**. The data router **272** may be adapted to receive communication data via the one or more communication lines **203** from the communication network **206** and to route the communication data to one or more devices connected to the second network interface **234**. For example, the data router **272** may receive voice data (e.g., plain old telephone service (POTS) data or VoIP data) from the communication network **206** and communicate the voice data to the telephone **210**. In another example, the data router **272** may receive network data (e.g., IP data) from the communication network **206** and route the computer communication data to the computer **212**. In still another example, the data router **272** may receive video data (e.g., IPTV data) from the communication network **206** and route the video data to the one or more display devices **214-218** or the one or more set-top box devices **226-230**. In a particular illustrative embodiment, the data router **272** may be included on the first removable plug-in module **250**, accordingly the first removable plug-in module **250** may provide video processing capability as well as data routing capability to the network interface device **202**. In another particular embodiment, the data router **272**, the video unit **254**, the connection manager **252**, the test unit **260**, the controller **262**, the memory **264** and the power coupling device **266** may be on any combination of the removable plug-in modules **250** and **270** allowing any combination of functionality to be provided to the network interface device **202** based on a particular configuration desired.

In a particular embodiment, the controller **262** is adapted to send a provisioning request to the communication network **206** in response to detecting connection of a removable plug-in module to one of the modular interface connectors **242** and **244**. In response to the provisioning request, the communication network **206** may store a provisioning record **292** at a database **290** associated with the communication network **206**. The provisioning record **292** may associate an identification for the removable plug-in module **250** or **270** with a subscriber account associated with the customer premise. The provisioning record **292** may enable provision of communication services (e.g., voice, video and/or network services) via the removable plug-in module **250** or **270** to the customer premise.

FIG. **3** depicts a second particular embodiment of a system including a network interface device. The system is generally designated **300**. The network interface device **302** may be coupled via one or more communication lines **306** to a remote

communication network **305**. The communication lines **306** may include one or more twisted pair communication lines (e.g., telephone lines), one or more non-twisted pair communication lines (e.g., a T-1 line, an E-1 line or a coaxial communication line), or any combination thereof.

The network interface device **302** includes a housing **304** to provide physical protection to one or more components of the network interface device **302**. The network interface device **302** may also include a lightning protection unit **310** and a remote network interface **308**. The remote network interface **308** and lightning protection unit **310** may be coupled to the communication lines **306** to provide protection against lightning strikes and to terminate the communication lines **306**. The network interface device **302** may also include one or more local network interfaces **312** to terminate one or more connections to wiring at a customer premise. For example, the local network interface **312** may include a number of interface connectors adapted to communicate data to various user devices at a customer premises. The interface connectors may include one or more modular sockets, plugs or jacks to terminate one or more twisted pair lines. For example, the interface connectors may include RJ45 jacks **314**, RJ11 jacks **316**, RJ14 jacks (not shown), RJ25 jacks (not shown) or any other six position or eight position plug jacks or other modular connector. The local network interface **312** may also include one or more connectors for other types of communication lines, such as coaxial cables. For example, the local network interface **312** may include one or more F connectors **318** to terminate one or more coaxial cable lines. In an illustrative embodiment, the local network interface **312** may terminate connections to wiring at the customer premise to provide voice data to one or more telephones via a modular telephone connector, to provide computer data (e.g., broadband data communications) to one or more computers via one or more Ethernet or data network connectors (such as the RJ45 connector), and to provide video data to one or more display device via one or more coaxial connectors or twisted wire pair connectors.

In a particular embodiment, the network interface device **302** may include one or more interface connectors **320**. The interface connectors **320** may be adapted to receive one or more removable plug-in modules **322**. The removable plug-in modules **322** may include any combination of modules which provide line power, video processing, data routing, diagnostics, line conditioning, memory, connection management or other functionality to the network interface device **302**. For example, the removable plug-in modules **322** may include the residential gateway **100** of FIG. **1**. In an illustrative embodiment, the removable plug-in modules **322** may include a power coupling device **330** adapted to receive power via the one or more sets of communication lines **306** and to provide operating power to other components within the network interface device **302**, such as, for example, a gateway **334**, a line conditioning unit **340**, a video unit **332**, a diagnostic unit **338**, a connection manager **342**, a controller **336**, or any combination thereof.

In a particular embodiment, the removable plug-in modules **322** may include a video unit **332** (also called a video remote unit or "VRU"). The video unit **332** may be adapted to receive video data from the remote communication network **305** via the one or more communication lines **306**. The video unit **332** may process the video data for communication via the at least one coaxial connectors **318** or one or more other connectors at the local network interface **312**. For example, the video unit **332** may receive modulated video data via the communication line **306** and may demodulate the video data for distribution via the local network interface **312**.

In a particular embodiment, the removable plug-in modules **322** may include a gateway module **334**, such as the residential gateway **100** of FIG. **1**. The gateway module **334** may route data received via the remote communication network **305** to one or more devices coupled to the local network interface **312**. For example, the gateway module **334** may provide network address translation (NAT) for devices coupled to the local network interface **312**. The gateway module **334** may route the data based at least partially on a type of the data. For example, voice data may be routed to a telephone or VoIP device coupled to the local network interface **312**. In another example, network data (e.g., IPv4 data, IPv6 data, TCP data, or data in another computer-to-computer communication protocol) may be routed to a computing device coupled to the local network interface **312**. In still another example, video data may be routed to the video unit **332** for processing or from the video unit **332** to one or more display devices or set-top box devices for display.

In a particular embodiment, the removable plug-in modules **322** include the controller **336**. The controller **336** may be adapted to detect when one or more removable plug-in modules **322** are coupled to the interface connectors **320** and to automatically enable service to the one or more removable plug-in modules **322**. For example, when the controller **336** detects that the video unit **332** has been plugged into the interface connectors **320**, the controller **336** may send a provisioning request via the communication lines **306** to store a record at the remote communication network **305**. The provisioning record may be used by the remote communication network **305** to enable the video unit **332**, to enable provisioning of video data to the video unit **332**.

The removable plug-in modules **322** may also include a diagnostic unit **338**. In an illustrative embodiment, the diagnostic unit **338** is configured to implement one or functionalities as described herein with reference to the testing module **107** of FIG. **1**. The diagnostic unit **338** is adapted to monitor performance of one or more of the removable plug-in modules **322** or other component of the network interface device **302**. In an illustrative embodiment, the diagnostic unit **338** is adapted to initiate loop back testing of the communication line **306** and network interface device **302** in response to a request received via communication line **306**. In another illustrative embodiment, the diagnostic unit **338** is adapted to provide a visual display or other information to indicate an operational status of the network interface device **302**, one or more components of the network interface device **302**, communications with the remote communication network **305**, or any combination thereof. For example, the diagnostic unit **338** may be adapted to activate a green, yellow or red light to indicate whether the network interface device **302** and components therein are functioning properly.

In a particular embodiment, the removable plug-in modules **322** may include a line conditioning unit **340**. The line conditioning unit **340** is adapted to condition the communication lines **306** for data communications. In a particular embodiment, the line conditioning unit **340** operates in conjunction with a remote line conditioning unit at the remote communication network to condition the communication lines **306**. The removable plug-in modules **322** may also include a connection manager **342**. The connection manager **342** is adapted to manage a data communication connection between the network interface device **302** and the remote communication network **305**.

In a particular embodiment, the removable plug-in modules **322** may include one or more memory devices **344**. The memory devices **344** may be adapted to store performance data related to one or more of the components of the network

interface device **302**. In a particular embodiment, each of the one or more removable plug-in modules **322** stores its performance data at the memory **344**. In another particular embodiment, the controller **336** polls the one or more removable plug-in modules **322** to gather the performance data and stores the gathered performance data at the memory **344**. In still another particular embodiment, the diagnostic unit **338** determines performance data related to one or more components of the network interface device **302** and stores the performance data at the memory **344**. In yet another particular embodiment, the diagnostic unit **338** determines performance data related to one or more components of the network interface device **302** and analyzes the performance data. The diagnostic unit **338** stores the analyzed performance data at the memory **344** for communication via the communication line **306** to the remote communication network **305**.

The one or more removable plug-in modules **322** may be arranged in any configuration, form factor, or combination. For example, any one or more of the video unit **332**, the gateway **334**, the power coupling device **330**, the diagnostic unit **338**, the line conditioning unit **340**, the connection manager **342**, the controller **336**, and the memory **344** may be on a single module, such as an interface card. In another example, the gateway **334** and the video unit **332** may be on separate modules. In yet another example, the removable plug-in modules **322** may include a number of interface cards. Each of the interface cards may include its own power coupling device, memory, controller, diagnostic unit, line conditioning unit, connection manager or any combination thereof.

FIG. **4** depicts a first particular embodiment of a method of using a network interface device, the method designated generally **400**. The method **400** includes, at **402**, coupling a network interface device to a coaxial wiring system at a customer premise. In a particular embodiment, the coaxial wiring system includes a pre-existing wiring system at the customer premises, such as a wiring system previously installed for cable television access. The coaxial wiring system may include one or more communication paths that are not direct connections from the network interface device to a display device or set-top box device. For example, the coaxial wiring system may include one or more splitters, one or more amplifiers, or any combination thereof. The method **400** also includes, at **404**, coupling the network interface device to a telephone wiring system at the customer premise. The method **400** includes, at **406**, connecting the network interface device to at least one set of communication lines to couple the network interface device to a remote communication network. For example, the set of communication lines may include one or more twisted pair lines e.g., a telephone line), one or more non-twisted pair lines (e.g., a T-1 line, an E-1 line, or a coaxial line), or any combination thereof.

The method **400** also includes, at **408**, connecting a plug-in module to a modular interface connector at the network interface device. In a particular embodiment, the plug-in module is line powered, that is, the plug-in module receives power via the one or more sets of communication lines coupled to the network interface device. The one or more plug-in modules may provide particular functionality to the network interface device. For example, the plug-in modules may enable voice, video or data communications via the remote communication network at the customer premise.

In a particular embodiment, the method **400** includes, at **410**, detecting reception of the plug-in module at the modular interface connector. After detecting reception of the plug-in module at the modular interface connector, the plug-in module may automatically enable access to voice, video and/or data services at the customer premises, at **412**. For example, video data processing at the network interface device may be automatically initialized, at **412**, in response to detecting reception of the plug-in module at the modular interface connector.

In a particular embodiment, the method **400** includes, at **416**, storing a provisioning record at a database associated with the remote communication network. The provisioning record may associate the particular plug-in module received at the interface connector with a subscriber account associated with the customer premise. The remote communication network may authorize the voice, video or data services to the customer premises at the network interface device based on the provisioning record.

The method **400** includes, at **418**, receiving communication data from the remote communication network. For example, the communication data may include voice, video or data communications. The method includes, at **420**, routing the communication data to one or more devices coupled to the network interface device via the coaxial wiring system or the telephone wiring system. For example, voice communication data may be provided via a plain old telephone service (POTS) protocol to one or more telephones via the telephone wiring system. In another example, video data may be provided to one or more display devices or set-top box devices via the coaxial wiring system, via the telephone wiring system, or via another twisted wire pair wiring system (e.g., an Ethernet system). In another example, data communications may be routed to one or more computing devices via the coaxial wiring system, via the telephone wiring system, or via another twisted wire pair wiring system.

The method **400** also includes, at **422**, storing performance data associated with one or more components of the network interface device. For example, the performance data may be stored at a memory local to the network interface device or at a database associated with the remote communication network. The method **400** may also include, at **423**, analyzing the performance data. For example, analyzing the performance data may include, at **424**, comparing the performance data to one or more operational criteria **426** to identify one or more operational concerns before the operational concerns are perceptible by a user at the customer premise. The method **400** may also include, at **428**, communicating results of the performance data analysis to a network unit of the remote communication network. For example, the performance data analysis may be communicated to the network unit to schedule a preventative maintenance activity such as sending a technician to address the one or more operational concerns before the operational concerns are perceptible by the user. Examples of operational concerns may include failure or improper operation of one or more of the components of the network interface device, loss of communication with the remote communication network or reduced quality of a signal received from the remote communication network, loss of line power, lost data packets or receipt of corrupt data packets, and so forth.

The method **400** may also include, at **430**, disabling access to voice, video, or data services in response to removing one or more of the plug-in modules from the interface connectors. For example, video services provided by the remote communication network may be automatically enabled in response to connection of a video plug-in module associated with the subscriber account to the interface connector. The video services provided by the remote communication network may be disabled in response to removal of the video plug-in module from the interface connector. In another example, data communication services provided by the remote communication network may be automatically enabled in response to con-

nection of a data plug-in module (e.g., a residential gateway module) associated with the subscriber account to the interface connector. The data communication services provided by the remote communication network may be disabled in response to removal of the data plug-in module from the interface connector. In yet another example, voice services provided by the remote communication network may be automatically enabled in response to connection of a voice plug-in module associated with the subscriber account to the interface connector. The voice services provided by the remote communication network may be disabled in response to removal of the voice plug-in module from the interface connector. Thus, a shortened time of a technician may be used to install, enable or disable voice, video or data communication services. In a particular embodiment, a customer may enable or disable voice, video or data services by self installation of an appropriate removable plug-in module at the customer's premise, thereby reducing cost and time associated with providing a technician for installation of hardware to enable or disable services available via the remote communication network.

FIG. **5** depicts a flow chart of an embodiment of a method of using a residential gateway and a network interface device. The method is designated generally **500**. In an illustrative embodiment, the method **500** is performed using the residential gateway **100** of FIG. **1** and the network interface device **202** of FIG. **2** or network interface device **302** of FIG. **3**.

The method **500** includes inserting a residential gateway into an outdoor network interface device coupled to one or more communication lines, at **502**. For example, the residential gateway **100** of FIG. **1** may be inserted into the NID **202** of FIG. **2**.

The method **500** also includes coupling the NID to a communication network that transmits a composite signal including voice data, video data, and network data via the one or more communication lines, at **504**. The residential gateway has an input to receive the composite signal from the NID and includes at least one module that is powered by power received via at least one of the one or more communication lines. For example, the NID **202** of FIG. **2** may be coupled to the communication **206**.

The method **500** further includes enabling or disabling access to one or more of the voice services, video services, and data services provided by the communication network by sending a connection or disconnection message to the residential gateway, at **506**. For example, a provider may enable or disable access to voice services, video services, and data services by sending a connection or disconnection message to the residential gateway **100** of FIG. **1**.

In a particular embodiment, the residential gateway, the network interface devices, and removable plug-in modules described herein may allow customer self installation of particular communication services. The residential gateway, network interface devices, and removable plug-in modules may also allow installation, enabling, and disabling of services without requiring that a customer be at home in order to access hardware inside the customer premise. Additionally, the residential gateway, the network interface devices, and removable plug-in modules may provide for remote troubleshooting of communication problems via loopback testing and more detailed troubleshooting of the communication problems via onboard testing and performance monitoring. Such troubleshooting may help to distinguish between downstream problems inside the customer's premise (e.g., hardware or wiring), and upstream problems outside of the customer's premise. Further, the residential gateway, the network interface devices, and removable plug-in modules may provide for simplified error correction. For example, errors may be corrected by removing and replacing one or more removable plug-in modules at the network interface device. Additionally, the network interface device and removable plug-in modules may provide for recoverability, exchangeability and reusability of various components of the network interface device, such as a video unit, a residential gateway, a data router, a controller, a power coupling device, a line conditioning unit, a connection manager, a diagnostic unit, or a memory. Further, the residential gateway, the network interface devices, and removable plug-in modules may be adapted to communicate via communication lines having a two-wire configuration or a four-wire configuration. For example, the residential gateway and network interface devices may communicate via a standard twisted pair telephone line, via a T-1 line or via E-1 line.

Referring to FIG. **6**, an illustrative embodiment of a general computer system is shown and is designated **600**. The computer system **600** can include a set of instructions that can be executed to cause the computer system **600** to perform any one or more of the methods or computer based functions disclosed herein. The computer system **600** may operate as a standalone device or may be connected, e.g., using a network, to other computer systems or peripheral devices. For example, the computer system **600** may include or be included within any one or more of the databases, communication networks, field units, residential gateways, network interface devices, computing devices, or set-top box devices discussed with reference to FIGS. **1-3**.

In a networked deployment, the computer system may operate in the capacity of a server or as a client user computer in a server-client user network environment, or as a peer computer system in a peer-to-peer (or distributed) network environment. The computer system **600** can also be implemented as or incorporated into various devices, such as a personal computer (PC), a tablet PC, a set-top box (STB), a personal digital assistant (PDA), a mobile device, a palmtop computer, a laptop computer, a desktop computer, a communications device, a wireless telephone, a land-line telephone, a control system, a camera, a scanner, a facsimile machine, a printer, a pager, a personal trusted device, a web appliance, a network router, switch or bridge, or any other machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. In a particular embodiment, the computer system **600** can be implemented using electronic devices that provide voice, video or data communication. Further, while a single computer system **600** is illustrated, the term "system" shall also be taken to include any collection of systems or sub-systems that individually or jointly execute a set, or multiple sets, of instructions to perform one or more computer functions.

As illustrated in FIG. **6**, the computer system **600** may include a processor **602**, e.g., a central processing unit (CPU), a graphics processing unit (GPU), or both. Moreover, the computer system **600** can include a main memory **604** and a static memory **606** that can communicate with each other via a bus **608**. As shown, the computer system **600** may further include a video display unit **610**, such as a liquid crystal display (LCD), an organic light emitting diode (OLED), a flat panel display, a solid state display, or a cathode ray tube (CRT). Additionally, the computer system **600** may include an input device **612**, such as a keyboard, and a cursor control device **614**, such as a mouse. The computer system **600** can also include a disk drive unit **616**, a signal generation device **618**, such as a speaker or remote control, and a network interface device **620**.

In a particular embodiment, as depicted in FIG. **6**, the disk drive unit **616** may include a computer-readable medium **622** in which one or more sets of instructions **624**, e.g. software, can be embedded. Further, the instructions **624** may embody one or more of the methods or logic as described herein. In a particular embodiment, the instructions **624** may reside completely, or at least partially, within the main memory **604**, the static memory **606**, and/or within the processor **602** during execution by the computer system **600**. The main memory **604** and the processor **602** also may include computer-readable media.

In an alternative embodiment, dedicated hardware implementations, such as application specific integrated circuits, programmable logic arrays and other hardware devices, can be constructed to implement one or more of the methods described herein. Applications that may include the apparatus and systems of various embodiments can broadly include a variety of electronic and computer systems. One or more embodiments described herein may implement functions using two or more specific interconnected hardware modules or devices with related control and data signals that can be communicated between and through the modules, or as portions of an application-specific integrated circuit. Accordingly, the present system encompasses software, firmware, and hardware implementations.

In accordance with various embodiments of the present disclosure, the methods described herein may be implemented by software programs executable by a computer system. Further, in an exemplary, non-limited embodiment, implementations can include distributed processing, component/object distributed processing, and parallel processing. Alternatively, virtual computer system processing can be constructed to implement one or more of the methods or functionality as described herein.

The present disclosure contemplates a computer-readable medium that includes instructions **624** or receives and executes instructions **624**, so that a device connected to a network **626** can communicate voice, video or data over the network **626**. Further, the instructions **624** may be transmitted or received over the network **626** via the network interface device **620** or residential gateway **630** connected to the network interface device **620**.

While the computer-readable medium is shown to be a single medium, the term "computer-readable medium" includes a single medium or multiple media, such as a centralized or distributed database, and/or associated caches and servers that store one or more sets of instructions. The term "computer-readable medium" shall also include any medium that is capable of storing, encoding or carrying a set of instructions for execution by a processor or that cause a computer system to perform any one or more of the methods or operations disclosed herein.

In a particular non-limiting, exemplary embodiment, the computer-readable medium can include a solid-state memory such as a memory card or other package that houses one or more non-volatile read-only memories. Further, the computer-readable medium can be a random access memory or other volatile re-writable memory. Additionally, the computer-readable medium can include a magneto-optical or optical medium, such as a disk or tapes or other storage device. Accordingly, the disclosure is considered to include any one or more of a computer-readable medium or a distribution medium and other equivalents and successor media, in which data or instructions may be stored.

Although the present specification describes components and functions that may be implemented in particular embodiments with reference to particular standards and protocols, the disclosed embodiments are not limited to such standards and protocols. For example, standards for Internet transmission, other packet switched network transmission (e.g., TCP/IP, UDP/IP, HTML, HTTP, IPTV, IPv4, IPv6, VoIP, VDSL, VDSL2, ADSL2+, OC, HPNA) represent examples of the state of the art. Such standards are periodically superseded by faster or more efficient equivalents having essentially the same functions. Accordingly, replacement standards and protocols having the same or similar functions as those disclosed herein are considered equivalents thereof.

The illustrations of the embodiments described herein are intended to provide a general understanding of the structure of the various embodiments. The illustrations are not intended to serve as a complete description of all of the elements and features of apparatus and systems that utilize the structures or methods described herein. Many other embodiments may be apparent to those of skill in the art upon reviewing the disclosure. Other embodiments may be utilized and derived from the disclosure, such that structural and logical substitutions and changes may be made without departing from the scope of the disclosure. Additionally, the illustrations are merely representational and may not be drawn to scale. Certain proportions within the illustrations may be exaggerated, while other proportions may be reduced. Accordingly, the disclosure and the figures are to be regarded as illustrative rather than restrictive.

One or more embodiments of the disclosure may be referred to herein, individually and/or collectively, by the term "invention" merely for convenience and without intending to voluntarily limit the scope of this application to any particular invention or inventive concept. Moreover, although specific embodiments have been illustrated and described herein, it should be appreciated that any subsequent arrangement designed to achieve the same or similar purpose may be substituted for the specific embodiments shown. This disclosure is intended to cover any and all subsequent adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the description.

The Abstract of the Disclosure is submitted with the understanding that it will not be used to interpret or limit the scope or meaning of the claims. In addition, in the foregoing Detailed Description, various features may be grouped together or described in a single embodiment for the purpose of streamlining the disclosure. This disclosure is not to be interpreted as reflecting an intention that the claimed embodiments require more features than are expressly recited in each claim. Rather, as the following claims reflect, inventive subject matter may be directed to less than all of the features of any of the disclosed embodiments. Thus, the following claims are incorporated into the Detailed Description, with each claim standing on its own as defining separately claimed subject matter.

The above-disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover all such modifications, enhancements, and other embodiments, which fall within the scope of the present invention. Thus, to the maximum extent allowed by law, the scope of the present invention is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

What is claimed is:

1. A residential gateway, comprising:

a connector interface to receive a signal communication lines, wherein the signal is configured to provide multiple services to a local area network;

a network interface to the local area network;

a power coupling device to receive power from a communication line of the communication lines, the communication line powered by a source that is remote from the connector interface, and the communication line carrying at least a portion of the signal to the connector interface; and

a first module to receive first data via the signal and to route the first data to a first device coupled to the network interface via the local area network, wherein the first data is associated with a first service, and wherein the first module is powered using the power received from the communication line by the power coupling device.

2. The residential gateway of claim 1, further comprising a second module to receive second data via the signal and to route the second data to a second device coupled to the network interface, wherein the second data is associated with a second service.

3. The residential gateway of claim 2, wherein the first service is associated with a video service and wherein the second service is associated with a network data service.

4. The residential gateway of claim 2, wherein the first service is associated with a video service and wherein the second service is associated with a voice service.

5. The residential gateway of claim 2, further comprising a third module to receive third data via the signal and to route the third data to a third device coupled to the network interface, wherein the third data is associated with a third service, wherein the first service is associated with a video service, wherein the second service is associated with a network data service, and wherein the third service is associated with a voice service.

6. The residential gateway of claim 5, wherein the second module, the third module, or both, are powered using the power received from the communication line by the power coupling device.

7. The residential gateway of claim 5, further comprising a testing module to detect errors in the signal, errors in the first module, errors in the second module, errors in the third module, errors in the first device, errors in the second device, errors in the third device, or any combination thereof, wherein the testing module communicates test results to a provider of the signal.

8. The residential gateway of claim 1, wherein the first data comprises voice data and wherein the first module converts the voice data to Voice over Internet Protocol data.

9. The residential gateway of claim 1, wherein the first data comprises video data and wherein the first module converts the video data to be compliant with a Home Phone line Networking Alliance protocol.

10. The residential gateway of claim 1, wherein the first data comprises network data and wherein the first module converts the network data to an Internet Protocol version 4 format, an Internet Protocol version 6 format, a transmission control protocol format, or any combination thereof.

11. A computer-readable storage device comprising instructions that, when executed by a processor, cause the processor to perform operations including:

in response to detecting that a residential gateway has been coupled to a network interface device:

receiving power at a power coupling device of the residential gateway, wherein the network interface device is coupled to communication lines, and wherein the power coupling device receives the power from a communication line of the communication lines, the communication line powered by a source that is remote from the residential gateway; and

providing power from the power coupling device to the residential gateway; and

receiving, at the residential gateway, a composite signal via the communication lines, wherein the composite signal is configured to provide multiple services to a local area network, and wherein the communication line carries at least a portion of the composite signal.

12. The computer-readable storage device of claim 11, wherein the operations further include, in response to receiving a connection message at the residential gateway from a service provider via the communication lines, automatically enabling access to voice services, video services, network data services, or combinations thereof, provided by the service provider.

13. The computer-readable storage device of claim 11 wherein the operations further include, in response to receiving a disconnect message at the residential gateway from a service provider via the communication lines, automatically disabling access to voice services, video services, and data services provided by the service provider.

14. An apparatus comprising:

a connector interface to receive a signal via communication lines, wherein the signal is configured to provide multiple services to a local area network;

a modular interface of a network interface device coupled to the connector interface, wherein the modular interface includes a plurality of plug-in connectors, wherein a plug-in connectors of the plurality of plug-in connectors is configured to receive a first plug-in module to provide a first service of the multiple services,

the first plug-in module configured to be removably coupled to a first plug-in connector of the plurality of plug-in connectors, the first plug-in module comprising:

a power coupling device; and

a first service module,

wherein, when the first plug-in module is removably coupled to the modular interface:

the power coupling device is operable to receive power via a communication line of the communication lines from a power source and to provide power to the first service module and to at least a portion of the network interface device; and

the first service module is operable to receive first data associated with the first service of the multiple services via the communication line and to provide the first data to a device coupled to the network interface device via the local area network.

15. The apparatus of claim 14, wherein, when the first plug-in module is removably coupled to the modular interface, the power coupling device is operable to provide power to a test module removably coupled to a second plug-in connector of the plurality of plug-in connectors.

16. The apparatus of claim 14, wherein, when the first plug-in module is removably coupled to the modular interface, the power coupling device is operable to provide power to an additional plug-in module removably coupled to a second plug-in connector of the plurality of plug-in connectors, wherein the additional plug-in module provides a second service of the multiple services.

17. The apparatus of claim **16**, wherein the first service is associated with a video service, and wherein the second service is a telephone service, a network data service, or a combination thereof.

18. The apparatus of claim **14**, wherein the first service is associated with a video service.

19. The apparatus of claim **14**, wherein the first service is associated with a telephone service.

20. The apparatus of claim **14**, wherein the first service is associated with a network data service.

* * * * *