

(12) **United States Patent**  
**Goodhart et al.**

(10) **Patent No.:** **US 10,755,300 B2**  
(45) **Date of Patent:** **Aug. 25, 2020**

(54) **OPTIMIZATION OF ONLINE ADVERTISING ASSETS**

(71) Applicant: **Oracle America, Inc.**, Redwood Shores, CA (US)

(72) Inventors: **Jonah Goodhart**, Ithaca, NY (US);  
**Noah Goodhart**, Ithaca, NY (US);  
**David J. Titus**, Mount Airy, MD (US);  
**Michael Garrett Seiler**, Brooklyn, NY (US);  
**Elliot Aaron Kulakow**, Brooklyn, NY (US)

(73) Assignee: **ORACLE AMERICA, INC.**, Redwood Shores, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 424 days.

(21) Appl. No.: **15/824,833**

(22) Filed: **Nov. 28, 2017**

(65) **Prior Publication Data**  
US 2018/0137534 A1 May 17, 2018

#### Related U.S. Application Data

(63) Continuation of application No. 13/802,288, filed on Mar. 13, 2013, now abandoned, which is a (Continued)

(51) **Int. Cl.**  
**G06Q 30/02** (2012.01)

(52) **U.S. Cl.**  
CPC ..... **G06Q 30/0244** (2013.01); **G06Q 30/0201** (2013.01); **G06Q 30/0242** (2013.01)

(58) **Field of Classification Search**  
None

See application file for complete search history.

(56) **References Cited**

#### U.S. PATENT DOCUMENTS

6,108,637 A 8/2000 Blumenau  
6,115,680 A 9/2000 Coffee et al.  
(Continued)

#### OTHER PUBLICATIONS

“Clicktale heatmaps Function and Benefits” (published online at <https://www.clicktale.com/resources/blog/clicktale-heatmaps/> on Apr. 3, 2007) (Year: 2007).\*

(Continued)

*Primary Examiner* — James M Detweiler


(74) *Attorney, Agent, or Firm* — Kilpatrick Townsend & Stockton LLP

(57) **ABSTRACT**

A system for collecting and presenting information about advertising analytics comprises an ad preparation server, an ad server and an analytics server. The ad preparation server receives advertising assets (e.g., ads) and modifies them to include a data collection script. The preparation server then sends the modified ads to the ad server for delivery along with underlying content to users. The underlying content and modified ads are delivered to client devices that present the content and execute the data collection script. The data collection script collects and sends advertising analytic data back to the analytics server in a non-intrusive manner. The present invention also includes a method for preparing ads, a method for deriving a heat map, a method for generating and sending advertising data, and a method for generating a representation of a focus of attention for a user.

**20 Claims, 23 Drawing Sheets**

1200



**Related U.S. Application Data**

continuation of application No. 13/436,082, filed on Mar. 30, 2012, now abandoned.

- (60) Provisional application No. 61/542,059, filed on Sep. 30, 2011, provisional application No. 61/476,505, filed on Apr. 18, 2011.

**(56) References Cited****U.S. PATENT DOCUMENTS**

|              |     |         |                       |                           |
|--------------|-----|---------|-----------------------|---------------------------|
| 6,230,204    | B1  | 5/2001  | Fleming, III          |                           |
| 6,327,619    | B1  | 12/2001 | Blumenau              |                           |
| 6,418,470    | B2  | 7/2002  | Blumenau              |                           |
| 7,263,497    | B1  | 8/2007  | Wiser et al.          |                           |
| 7,310,609    | B2  | 12/2007 | Middleton, III et al. |                           |
| 7,386,473    | B2  | 6/2008  | Blumenau              |                           |
| 7,613,635    | B2  | 11/2009 | Blumenau              |                           |
| 7,660,737    | B1  | 2/2010  | Lim et al.            |                           |
| 7,716,326    | B2  | 5/2010  | Blumenau              |                           |
| 7,756,974    | B2  | 7/2010  | Blumenau              |                           |
| 7,917,755    | B1  | 3/2011  | Giliyaru et al.       |                           |
| 8,108,245    | B1  | 1/2012  | Hosea et al.          |                           |
| 8,190,604    | B2  | 5/2012  | Wen et al.            |                           |
| 8,255,491    | B1  | 8/2012  | Arzur                 |                           |
| 8,266,115    | B1  | 9/2012  | Park et al.           |                           |
| 8,386,314    | B2* | 2/2013  | Kirkby                | G06Q 10/10<br>705/14.42   |
| 8,508,532    | B1  | 8/2013  | Logan et al.          |                           |
| 8,880,996    | B1  | 11/2014 | Deshpande et al.      |                           |
| 9,282,048    | B1  | 3/2016  | Fichter et al.        |                           |
| 2002/0098891 | A1  | 7/2002  | Graham et al.         |                           |
| 2002/0103698 | A1  | 8/2002  | Cantrell              |                           |
| 2002/0111865 | A1  | 8/2002  | Middleton, III et al. |                           |
| 2002/0165773 | A1  | 11/2002 | Natsuno et al.        |                           |
| 2003/0200145 | A1  | 10/2003 | Krassner et al.       |                           |
| 2004/0036716 | A1  | 2/2004  | Jordahl               |                           |
| 2005/0210533 | A1  | 9/2005  | Copeland et al.       |                           |
| 2005/0235030 | A1  | 10/2005 | Lauckhart et al.      |                           |
| 2006/0026063 | A1  | 2/2006  | Collins               |                           |
| 2006/0080681 | A1  | 4/2006  | Anwar et al.          |                           |
| 2007/0050251 | A1  | 3/2007  | Jain et al.           |                           |
| 2007/0198344 | A1  | 8/2007  | Collison et al.       |                           |
| 2007/0255702 | A1  | 11/2007 | Orme                  |                           |
| 2007/0256095 | A1  | 11/2007 | Collins               |                           |
| 2007/0266305 | A1* | 11/2007 | Cong                  | G06Q 30/02<br>715/700     |
| 2008/0004958 | A1  | 1/2008  | Ralph et al.          |                           |
| 2008/0114709 | A1  | 5/2008  | Dixon et al.          |                           |
| 2008/0120165 | A1  | 5/2008  | Yan                   |                           |
| 2008/0320125 | A1  | 12/2008 | O'Sullivan et al.     |                           |
| 2009/0076899 | A1  | 3/2009  | Gbodimowo             |                           |
| 2009/0157813 | A1  | 6/2009  | Jung et al.           |                           |
| 2009/0187546 | A1  | 7/2009  | Hamilton              |                           |
| 2009/0216621 | A1  | 8/2009  | Anderson et al.       |                           |
| 2009/0265243 | A1  | 10/2009 | Karassner et al.      |                           |
| 2009/0271260 | A1  | 10/2009 | Sharma et al.         |                           |
| 2009/0300528 | A1  | 12/2009 | Stambaugh             |                           |
| 2010/0023868 | A1  | 1/2010  | Bonforte et al.       |                           |
| 2010/0095317 | A1  | 4/2010  | Toebe et al.          |                           |
| 2010/0121676 | A1  | 5/2010  | Jackson               |                           |
| 2010/0146380 | A1  | 6/2010  | Rousso et al.         |                           |
| 2010/0169792 | A1* | 7/2010  | Ascar                 | G06F 11/3414<br>715/744   |
| 2010/0241597 | A1  | 9/2010  | Chen et al.           |                           |
| 2010/0251128 | A1  | 9/2010  | Cordasco              |                           |
| 2010/0287054 | A1* | 11/2010 | Zohar                 | G06Q 30/02<br>705/14.72   |
| 2010/0295774 | A1  | 11/2010 | Hennessey             |                           |
| 2010/0310175 | A1  | 12/2010 | Holt                  |                           |
| 2011/0029393 | A1* | 2/2011  | Apprendi              | G06Q 30/0277<br>705/14.73 |
| 2011/0072131 | A1  | 3/2011  | Zohar et al.          |                           |
| 2011/0125587 | A1  | 5/2011  | Netzer et al.         |                           |
| 2011/0137737 | A1* | 6/2011  | Baird                 | G06Q 30/0272<br>705/14.73 |

|              |     |         |                     |                         |
|--------------|-----|---------|---------------------|-------------------------|
| 2011/0153362 | A1  | 6/2011  | Valin et al.        |                         |
| 2011/0153435 | A1  | 6/2011  | Pisaris-Henderson   |                         |
| 2011/0163971 | A1  | 7/2011  | Wagner et al.       |                         |
| 2011/0239243 | A1  | 9/2011  | Dierks et al.       |                         |
| 2011/0320286 | A1  | 12/2011 | Zohar et al.        |                         |
| 2012/0078707 | A1  | 3/2012  | Ramakrishnan et al. |                         |
| 2012/0106793 | A1* | 5/2012  | Gershenson          | G06K 9/00335<br>382/103 |
| 2012/0317472 | A1  | 12/2012 | Chernysh            |                         |
| 2012/0324098 | A1  | 12/2012 | De Jager et al.     |                         |
| 2013/0031470 | A1  | 1/2013  | Daly, Jr. et al.    |                         |
| 2013/0124342 | A1  | 5/2013  | Virkar et al.       |                         |
| 2013/0166377 | A1  | 6/2013  | Kirkby et al.       |                         |
| 2013/0179767 | A1  | 7/2013  | Bajric et al.       |                         |
| 2013/0335576 | A1  | 12/2013 | Gotschlich et al.   |                         |
| 2014/0040786 | A1  | 2/2014  | Swanson et al.      |                         |
| 2014/0181634 | A1  | 6/2014  | Compain et al.      |                         |
| 2014/0282642 | A1  | 9/2014  | Needham et al.      |                         |
| 2017/0316431 | A1  | 11/2017 | Goodhart et al.     |                         |
| 2017/0316443 | A1  | 11/2017 | Goodhart et al.     |                         |
| 2017/0316446 | A1  | 11/2017 | Goodhart et al.     |                         |
| 2018/0137534 | A1  | 5/2018  | Goodhart et al.     |                         |

**OTHER PUBLICATIONS**

U.S. Appl. No. 13/436,044, Non-Final Office Action dated Jan. 25, 2019, 27 pages.

U.S. Appl. No. 13/436,044, Final Office Action dated Jun. 3, 2016, 11 pages.

U.S. Appl. No. 13/436,044, Final Office Action dated Sep. 21, 2017, 19 pages.

U.S. Appl. No. 13/436,044, Non-Final Office Action dated Jul. 19, 2013, 10 pages.

U.S. Appl. No. 13/436,044, Non-Final Office Action dated Aug. 14, 2015, 15 pages.

U.S. Appl. No. 13/436,044, Non-Final Office Action dated Dec. 29, 2016, 17 pages.

U.S. Appl. No. 13/436,082, Final Office Action dated Oct. 11, 2016, 16 pages.

U.S. Appl. No. 13/436,082, Non-Final Office Action dated Apr. 25, 2017, 16 pages.

U.S. Appl. No. 13/436,082, Non-Final Office Action dated Jun. 25, 2015, 53 pages.

U.S. Appl. No. 13/436,082, Restriction Requirement dated Apr. 1, 2013, 6 pages.

U.S. Appl. No. 13/802,288, Advisory Action dated Oct. 7, 2014, 4 pages.

U.S. Appl. No. 13/802,288, Final Office Action dated Dec. 23, 2016, 14 pages.

U.S. Appl. No. 13/802,288, Final Office Action dated Jun. 17, 2014, 37 pages.

U.S. Appl. No. 13/802,288, Final Office Action dated May 26, 2015, 55 pages.

U.S. Appl. No. 13/802,288, Non-Final Office Action dated Aug. 31, 2017, 12 pages.

U.S. Appl. No. 13/802,288, Non-Final Office Action dated Jan. 2, 2014, 16 pages.

U.S. Appl. No. 13/802,288, Non-Final Office Action dated Jun. 3, 2016, 19 pages.

U.S. Appl. No. 13/802,288, Non-Final Office Action dated Jan. 30, 2015, 51 pages.

U.S. Appl. No. 13/857,897, Advisory Action dated Jul. 2, 2014, 3 pages.

U.S. Appl. No. 13/857,897, Final Office Action dated Jun. 20, 2017, 19 pages.

U.S. Appl. No. 13/857,897, Final Office Action dated Mar. 14, 2014, 27 pages.

U.S. Appl. No. 13/857,897, Final Office Action dated Feb. 2, 2016, 33 pages.

U.S. Appl. No. 13/857,897, Non-Final Office Action dated Nov. 8, 2016, 37 pages.

U.S. Appl. No. 13/857,897, Non-Final Office Action dated May 1, 2015, 40 pages.

(56)

**References Cited**

OTHER PUBLICATIONS

U.S. Appl. No. 13/857,897, Non-Final Office Action dated Jun. 28, 2013, 8 pages.

WELOVED, Web Design Served, Available online at: <http://www.webdesignserved.com/gallery/WELOVEADbeta/517326>, May 19, 2010, 15 pages.

WELOVED, WELOVED.com WELOVEAD, Available Online at: <http://web.archive.org/web/20110307041600/http://www.welovead.com/en/works/database>, Mar. 7, 2011.

\* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11




Figure 12

1300




Figure 13A




Figure 13B




Figure 14A




Figure 14B




Figure 15A




Figure 15B




Figure 16




Figure 17




Figure 18



Figure 19




Figure 20

1

## OPTIMIZATION OF ONLINE ADVERTISING ASSETS

### CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. Non-Provisional patent application Ser. No. 13/802,288, filed Mar. 13, 2013, entitled "OPTIMIZATION OF ONLINE ADVERTISING ASSETS," which is a continuation of U.S. Non-Provisional patent application Ser. No. 13/436,082 filed Mar. 30, 2012, entitled "OPTIMIZATION OF ONLINE ADVERTISING ASSETS," which claims benefit under 35 U.S.C. § 119(e) to U.S. Provisional Application Ser. No. 61/542,059, entitled "OPTIMIZATION OF ONLINE ADVERTISING ASSETS & AD SEARCH ENGINE" filed on Sep. 30, 2011, and U.S. Provisional Application Ser. No. 61/476,505, entitled "COMPUTER SOFTWARE RELATING TO ADVERTISING OVER COMPUTER NETWORKS" filed on Apr. 18, 2011. The present application is also related to U.S. Non-Provisional patent application Ser. No. 13/436,044, filed Mar. 30, 2012, entitled "AD SEARCH ENGINE," and U.S. Non-Provisional patent application Ser. No. 13/857,897, filed Mar. 30, 2012, entitled "AD SEARCH ENGINE." Each of the above-identified applications is hereby incorporated by reference in its entirety for all purposes.

### BACKGROUND OF THE INVENTION

#### 1. Field of the Invention

The present invention relates to on-line advertising and the presentation of associated advertising information. In particular, the present invention relates to computer systems and methods for collecting and presenting information about advertising analytics to improve ad copy, placement and consumption.

#### 2. Description of the Related Art

The Internet and other types of on-line communication have become increasingly popular to the point where they now compete with traditional media such as print media and broadcast media for the attention of users. Because users are spending so much more time on line viewing content, playing games and on social networks, advertisers are spending greater amounts of their advertising dollars on Internet advertising or online advertising. It is now commonplace for advertisers to use online advertising as a major component of any advertising campaign.

Online advertising typically refers to any type of promotion that uses the Internet or the World Wide Web to deliver marketing messages and attract the attention of customers. Examples of online advertising include contextual ads on search engine result pages, banner ads, rich media ads, social networking ads, interstitial advertising, etc. Online advertising is typically provided from an ad server to a publisher that includes the ads with the published or served content. These new forms of online advertising are advantageous because they provide better targeting and placement than traditional media.

In order to effectively price online advertising some analytics and metrics have been developed. For example, an impression is a measure of the number of times an ad is displayed whether users interact with that ad or not. Such placements are priced in cost per thousand impressions or

2

CPM. Internet traffic may also be measured in cost per click (CPC) where advertisers pay hosting services only when users interact with the ad or "click" on the add. There are other limited metrics that are captured by web analytics service providers in an attempt to measure the effectiveness of such online advertising campaigns.

One problem with existing web analytics is that the amount of information provided about user interaction with the ads and other context information is very limited. Most existing systems only provide limited information about impression such as the date, time and publisher that served the advertisement. In many instances, the analytics systems only confirm that the ad was served and not whether it was actually viewed by the user. For example, issues with the browser, latency, or other factors may preclude the ad from being displayed and reviewed by the user. Existing systems incorrectly consider those impressions as have been presented and viewed by the user. Existing systems are unable to provide more information about the context in which the ad was placed, actual information about user interaction with the ad and other information that is valuable to the advertisers.

Another problem with existing systems is that the ads are very transient and automatically served by web servers based on a number of factors only some which are under the control advertisers. As noted above, there is often no way for the advertisers to determine what ads were presented, and more importantly the manner in which the ads were presented to the user. For example, the prior art does not have any way to search ads that were presented and provide historical information about the presentation of those ads.

### SUMMARY OF THE INVENTION

In one innovative aspect, the present invention provides a system for collecting and presenting information about advertising analytics. The system comprises an ad preparation server, an ad server and an analytics server. The ad preparation server receives advertising assets (e.g., ads) and modifies them to include a data collection script. The preparation server then sends the modified ads to the ad server for delivery along with underlying content to users. The underlying content and modified ads are delivered to client devices that present the content and execute the data collection script. The data collection script collects and sends advertising analytic data back to the analytics server in a non-intrusive manner. The analytics server organizes and stores the analytic data. In some embodiments the analytics server includes a variety of algorithms, analytic methods, analytic reports that process the data received from the data collection script to better deploying Internet advertising assets. In particular, the analytics server is capable of processing the data from the data collection script to generate a heat map that represents the user's focus of attention for a placed advertisement. The present invention also includes several novel methods such as a method for preparing ads, a method for deriving a heat map, a method for generating and sending advertising data, and a method for generating a representation of a focus of attention for a user.

### BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example, and not by way of limitation in the figures of the accompanying drawings in which like reference numerals are used to refer to similar elements.

3

FIG. 1 is a block diagram illustrating an embodiment of an advertising system in accordance with the present invention.

FIG. 2 is a block diagram illustrating an embodiment of an ad preparation server in accordance with the present invention.

FIG. 3 is a block diagram illustrating an embodiment of an analytics server in accordance with the present invention.

FIG. 4 is a block diagram illustrating one embodiment of data flow in the analytics server in accordance with the present invention.

FIG. 5 is a block diagram illustrating an embodiment of an ad search engine in accordance with the present invention.

FIG. 6 is a block diagram illustrating an embodiment of a web browser and components using in advertising in accordance with the present invention.

FIG. 7 is a flowchart of one embodiment of a method for preparing ads in accordance with the present invention.

FIG. 8 is a flowchart of one embodiment of a method for deriving a heat map in accordance with the present invention.

FIG. 9 is a flowchart of one embodiment of a method for displaying ad search results in accordance with the present invention.

FIG. 10 is a flowchart of one embodiment of a method for generating and sending advertising data in accordance with the present invention.

FIG. 11 is a flowchart of one embodiment of a method for generating a representation of a focus of attention for a user in accordance with the present invention.

FIG. 12 is a flowchart of one embodiment of a method for generating a map of user attention or focus in accordance with the present invention.

FIGS. 13A and 13B are a flowchart of one embodiment of a method for generating an ad search result interface in accordance with the present invention.

FIGS. 14A and 14B are a flowchart of one embodiment of a method for populating an ad database in accordance with the present invention.

FIGS. 15A and 15B are a flowchart of one embodiment of a method for ad preservation in accordance with the present invention.

FIG. 16 is a flowchart of one embodiment of a method for generating derived insights in accordance with the present invention.

FIG. 17 is a graphic representation of an embodiment of a user interface for showing advertisement search results in accordance with the present invention.

FIGS. 18 and 19 are graphic representations of embodiments of user interfaces for presenting advertisement meta-data in accordance with the present invention.

FIG. 20 is a graphic representation of an embodiment of a user interface for presenting a visual image, heat map, in accordance with the present invention.

#### DETAILED DESCRIPTION OF EMBODIMENTS

FIG. 1 illustrates a block diagram of one embodiment of the advertising system 100 of the present invention. The advertising system 100 advantageously collects and presents advertising analytics for on line advertisements. The advertising system 100 also retrieves and presents on-line advertisements in a similar manner to how they were presented on line. For many examples in the specification below, an online advertisement (ad) is any text, picture or video whose purpose is advertising communication including any flash

4

asset, any image of Internet Advertising Board (IAB) or industry standard width and height that is clickable including any recursion into iframes from the original page. The illustrated ad system 100 includes an advertising asset server 116, an ad preparation server 118, an ad server 102, an analytics server 104, a network 106, an ad search engine 132, and one or more client devices 108a-108n that are accessed by users 110a-110n. In the illustrated embodiment, these entities are communicatively coupled via a network 106. Although only three client devices 108a-n are illustrated, it should be recognized that any number of client devices 108n are available to any number of users 110n. Furthermore, while only one network 106 is coupled to the advertising asset server 116, the ad preparation server 118, the ad server 102, the analytics server 104, the ad search engine 132, and the one or more client devices 108a-108n, in practice any number of networks 106 can be connected to the entities. In one embodiment, the advertising asset server 116, the ad preparation server 118, the ad server 102, the analytics server 104, and the ad search engine 132 are hardware servers including a processor, memory, and network communication capabilities.

The network 106 is a conventional type, wired or wireless, and may have any number of configurations such as a star configuration, token ring configuration or other configurations. Furthermore, the network 106 may comprise a local area network (LAN), a wide area network (WAN) (e.g., the Internet), and/or any other interconnected data path across which multiple devices may communicate. In yet another embodiment, the network 106 may be a peer-to-peer network. The network 106 may also be coupled to or include portions of a telecommunications network for sending data in a variety of different communication protocols. In yet another embodiment, the network 106 includes Bluetooth communication networks or a cellular communications network for sending and receiving data such as via short messaging service (SMS), multimedia messaging service (MMS), hypertext transfer protocol (HTTP), direct data connection, WAP, email, etc.

The client device 108a is representative of client devices 108a-108n and is a conventional type of computing device, for example, a personal computer, a hardware server, a laptop computer, a tablet computer or smart phone. The client devices 108a-108n are coupled to the network 106 by signal lines 122a-122n, respectively. In one embodiment, the client device 108 is coupled to receive online advertisements from the ad server 102 and other content from publishing sites or third party servers (not shown). The client device 108 includes a web browser 112 for presenting online content and advertisements to the user. The web browser 112 presents ads and other content, and receives input from the user 110 as represented by signal line 124. The web browser 112 and data collection script 114 are operable on the client device 108. The data collection script 114 collects information about user interaction with advertisements, ad placement and other advertising analytics, and sends that information to the analytics server 104. The operation of the data collection script 114 is described in more detail below with reference to FIG. 10. The data collection script 114 advantageously collects information non-intrusively and incrementally as will be described in more detail below. In one embodiment, the data collection script 114 is a program, code or software that: 1) Loads as a result of an ad being served; 2) Loads as a result of a network call placed on the page by its publisher; 3) Executes in the same time window as the advertising content and the page load; 4) Extracts cursor movement or gesture data, browser or user data, and

5

data pertaining to the environment in which the ad has been placed (also referred to as input data); 5) Transmits that data, during page rendering, to an analytics server **104**; and 6) creates data from which downstream analytics can determine the duration that the page was viewed during any particular rendering of the page.

The advertising asset server **116** is a computer program running on a hardware system for storing and providing advertisements or assets to other systems that will ultimately deliver the ads to the end user. The advertising asset server **116** is coupled to the network **106** by signal line **130** to receive advertisements or assets from advertisers. In one embodiment, the advertising asset server **116** stores the advertisement or asset that will be delivered to the client devices **108**. For example, the asset includes ad copy, ad content, JavaScript or flash that when executed by the client device **108** in the web browser **112** presents the advertisement to the user **110** as designed by and intended by the advertiser. The advertisers interact with the advertising asset server **116** to upload and store advertisements on the advertising asset server **116**. These advertisements are then available for delivery to the ad preparation server **118** or the ad server **102** which in turn process the advertisements and deliver them to the client device **108**.

The ad preparation server **118** is a computer program running on a hardware system for preparing advertisements for ultimate delivery to the client devices **108**. In one embodiment, the ad preparation server **118** retrieves advertisements from the advertising asset server **116** and modifies them by adding the data collection script **114**. The modified ads are then delivered by the ad preparation server **118** to the ad server **102** for combination with content and delivery to the client device **108**. The ad preparation server **118** is coupled to the network **106** by signal line **128** for communication with the advertising asset server **116** and the ad server **102**. The ad preparation server **118** is described in more detail below with reference to FIGS. 2 and 7.

The ad server **102** is a computer program running on a hardware system for placing advertisements on websites. For example, the ad server **102** may be a web server that receives advertisements from the ad preparation server **118** or the advertising asset server **116** and delivers them to website visitors. The ad server **102** is coupled to the network **106** by signal line **120** for receiving ads from the ad preparation server **118** or the advertising asset server **116** and for delivering the ads to third party servers, sites or domains (not shown).

The analytics server **104** is a computer program running on a hardware system for collecting and presenting information about advertising analytics. In particular, the analytics server **104** receives advertising data from the data collection script **114** running on the client device **108**. The analytics server **104** may also receive basic ad statistics from the ad server **102**. The analytics server **104** also processes the advertising data to produce reports and user interfaces. The analytics server **104** is described in more detail below with reference to FIGS. 3, 5, 8, 11 and 12. The analytics server **104** is coupled by signal line **126** to the network **106** for communication with the client devices **108a-108n** and the ad server **102**.

The ad search engine **132** is a computer program running on a hardware system for performing searches of advertisements and other associated metadata. The ad search engine **132** is coupled to receive advertising placement information from the ad server **102**. The ad search engine includes and maintains a database of advertisements and the context in which they were delivered. The ad search engine **132** will be

6

described in more detail below with reference to FIGS. 4, 9, 13A-15B. The ad search engine **132** is coupled by signal line **134** to the network **106** for communication with the other components of the system **100**.

#### Ad Preparation Server **118**

FIG. 2 is a block diagram of one embodiment of the ad preparation server **118**. In this embodiment, the ad preparation server **118** comprises: a processor **202**, a memory **204**, a network interface (I/F) module **206**, storage **208**, a request processor **212**, an ad selection module **214**, a script creation processor **216**, a script injector **218**, a bus **220** and an injected ad database **222**. As noted above, the ad preparation server **118** is responsive to requests from the ad server **102** for advertisements. The ad preparation server **118** receives requests from the ad server **102** and in response retrieves an ad asset from the advertising asset server **116**, injects a data collection script and then sends the modified ad to the ad server **102**.

The processor **202** comprises an arithmetic logic unit, a microprocessor, a general-purpose controller or some other processor array to perform computations and provide electronic display signals to a display device. The processor **202** is coupled to the bus **220** for communication with the other components. Processor **202** processes data signals and may comprise various computing architectures including a complex instruction set computer (CISC) architecture, a reduced instruction set computer (RISC) architecture, or an architecture implementing a combination of instruction sets. Although only a single processor is shown in FIG. 2, multiple processors may be included. Other processors, operating systems, sensors, displays and physical configurations are possible.

The memory **204** stores instructions and/or data that may be executed by processor **202**. The memory **204** is coupled to the bus **220** for communication with the other components. The instructions and/or data may comprise code for performing any and/or all of the techniques described herein. The memory **204** may be a dynamic random access memory (DRAM) device, a static random access memory (SRAM) device, flash memory or some other memory device.

The network interface (I/F) module **206** is coupled to network **106** by signal line **128** and coupled to the bus **220**. The network interface module **206** includes ports for wired connectivity such as but not limited to USB, SD, or CAT-5, etc. The network interface module **206** links the processor **202** to the network **106** that may in turn be coupled to other processing systems. The network interface module **206** provides other connections to the network **106** using standard network protocols such as TCP/IP, HTTP, HTTPS and SMTP. In other embodiments, the network interface module **206** includes a transceiver for sending and receiving signals using Wi-Fi, Bluetooth® or cellular communications for wireless communication. The network interface (I/F) module **206** provides a communication path for the components of the ad preparation server **118** to the network **106** and other systems.

In one embodiment, the storage **208** stores data, information and instructions used by the ad preparation server **118**. Such stored information includes information about users, publishers, ads, assets and other information. The storage **208** is a non-volatile memory or similar permanent storage device and media such as a hard disk drive, a floppy disk drive, a CD-ROM device, a DVD-ROM device, a DVD-RAM device, a DVD-RW device, a flash memory device, or some other mass storage device for storing information on a more permanent basis. The data storage **208** is coupled by

the bus 220 for communication with other components of the ad preparation server 118.

The request processor 212 is software, code or routines for receiving and processing requests for advertisements from the ad server 102. The request processor 212 is coupled to receive requests from the ad server 102. In some embodiments, the request processor 212 operates as a controller of the overall process of creating a modified ad and delivering it to the ad server 102 and communicates with the other components 214, 216, 218, 222 for that purpose. The request processor 212 receives the request from the ad server and promulgates the request to the ad selection module 214 and the script creation processor 216 so that an ad may be selected and a script created, respectively. The request processor 212 is coupled to bus 220 for communication with the other components of the ad preparation server 118.

The ad selection module 214 is software, code or routines for selecting an ad for delivery to the ad server 102. The ad selection module 214 is coupled to receive a request signal from the request processor 212 and coupled to retrieve ads from the advertising asset server 116. In some embodiments, the ad selection module 214 also monitors and executes campaigns for advertisers. In other words, the ad selection module 214 may control the placement, time, location of the delivery of the ads. The ad selection module 214 is responsible for retrieving the original advertisement from the advertising asset server 116. The ad selection module 214 delivers the retrieved original advertisement to the script injector 218. The ad selection module 214 is coupled by the bus 220 for communication with the advertising asset server 116, the request processor 212 and the script injector.

The script creation processor 216 is software, code or routines for creating a script for addition to an advertisement. Based upon the information that the advertiser wants collected, a script is created for addition to the advertisement. The script creation processor 216 creates a script to gather custom as well as standard information, for example, the data collection script 114. For example, the script creation processor 216 assigns the advertisement a unique identification number and includes that number in the script so that it can be used to report activity related to the advertisement back to the analytics server 104 and that activity can be associated with the specific ad in which this script is inserted. The script creation processor 216 also modifies the data collection script 114 so that it works properly with the advertisement. In other words, the operation of the data collection script 114 in collecting information and reporting back to the analytics server 104 is nonintrusive and does not interfere with the normal presentation of the content by the web page or the normal presentation of the advertisement. In one embodiment, the script creation processor 216 is coupled to the injected ad database 222 to receive script templates that can be used for creating specific instances of the data collection script 114. The script creation processor 216 is responsive to requests from the request processor 212 and provides created data collection scripts 114 to the script injector 218. The script creation processor 216 is coupled by the bus 220 for communication with the request processor 212, the injected ad database 222, and script injector 218.

The script injector 218 is software, code, or routines for inserting data collection scripts 114 into advertisements. The script injector 218 receives an original ad from the ad selection module 214. The script injector 218 also receives a data collection script 114 from the script creation processor 216. The script injector 218 combines the original advertisement and the data collection script 114 into a new

modified advertisement. The script injector 218 stores a copy of the new modified advertisement in the injected ad database 222. The original ad and data collection script 114 may also be stored in the injected ad database 222. In some embodiments, the script injector 218 also creates an association in the injected ad database 222 between the original ad, the modified ad, and the particular data collection script 114. In one embodiment, the script injector 218 sends the modified ad to the ad server 104. In another embodiment, the script injector 218 sends the modified ad to the request processor 212 which in turn provides the modified ad to the ad server 104. The script injector 218 is coupled to the bus 220 for communication with the other components 212, 214, 216, 218 and 222 of the ad preparation server 118.

The injected ad database 222 is a data store for storing information about ads that have been modified and data collection scripts 114 that have been added. In one embodiment the injected ad database is a conventional database. The injected ad database 222 stores the modified ad, the original ad, the injected script, and other information related to preparing the ad for delivery. In some embodiments, the injected ad database 222 is coupled to other systems such as the analytics server 104 to provide information about injected ads. The injected ad database 222 is coupled for communication with the other components 212, 214, 216, 218 and 222 of the ad preparation server 118.

#### Analytics Server 104

Referring now to FIG. 3, the analytics server 104 will be described in more detail. The analytics server 104 comprises a processor 202, a memory 204, a network interface (I/F) module 206, storage 208, an ad engagement tracker 302, a filter module 304, a cursor/gesture to eye movement transformer 306, an eye tracking visualization module 308, an analytics database 310, a real-time analysis and reporting module 312, a user interface module 314, a click tag parser 316, a rich media parser 318, an attention score generator 320, a placement module 322 and a placement scoring module 324. These components are communicatively coupled to each other by bus 220 for sending and receiving information.

The processor 202, the memory 204, the network interface (I/F) module 206, the storage 208 and bus 220 have the same or similar functionality to that described above with reference to FIG. 2, so that description will not be repeated here. It should be noted, however, that the network interface module 206 is coupled by signal line 126 to the network 106 and to the bus 220.

The ad engagement tracker 302 is software, code or routines for collecting information about advertisements from the data collection scripts 114. The ad engagement tracker 302 is coupled by the network 106 to numerous client devices 108 and thus numerous data collection scripts 114. Each of these data collection scripts 114 sends ad information or analytics data to the analytics server 104 and this ad information or analytics data is collected and captured by the ad engagement tracker 302. For example, the ad engagement tracker 302 collects ad information such as the ID of the ad, the domain on which the ad was presented, the placement of the ad on the page, user inputs while the ad was being displayed, browser information, or information about the entity that served the ad. In some embodiments, the ad engagement tracker 302 sends the ad information to the analytics database 310 for storage and the real-time analysis and reporting module 312 for immediate processing. The ad engagement tracker 302 is coupled to the bus 220 for communication with the other components of the analytics

server **104**, in particular the analytics database **310** and a real-time analysis and reporting module **312**.

The filter module **304** is software, code or routines for processing ad information or analytics data including click tag analysis, rich media analysis and other analysis. The filter module **304** is coupled to the analytics database **310** to retrieve ad information or analytics data and perform click tag analysis and rich media analysis. In one embodiment, the filter module **304a** processes the analytics data to produce signals that are used by the cursor/gesture to eye movement transformer **306**. In some embodiments, the filter module **304b** also processes analytics data from the real-time analysis and reporting module **312** in a real-time manner (See also FIG. 4). The filter module **304** is coupled by the bus **220** for communication with the other components of the analytics server **104**, in particular the analytics database **310**, the cursor/gesture to eye movement transformer **306**, and the real-time analysis and reporting module **312**.

The cursor/gesture to eye movement transformer **306** is software, code, or routines for translating the filtered analytics data into eye movement information. One embodiment of the operations of the cursor/gesture to eye movement transformer **306** is described in more detail below with reference to FIG. 11. The cursor/gesture to eye movement transformer **306** is coupled to the bus **220** to receive the filtered analytics data from the filter module **304**, processes that information to produce eye movement information, and provides the eye movement information to the eye tracking visualization module **308**. In some embodiments, the eye to cursor/gesture movement transformer **306b** operates on a set of real-time filtered analytics data (see FIG. 4). While the present invention is described primarily below in the context of cursor movement, it should be understood that gestures and any other type of user input can be used instead of or in combination with cursor movement. Moreover, cursor data, gesture data, and other user input are referred to in this application as input data.

The eye tracking visualization module **308** is software, code or routines for producing a visual image that represents the eye movements of the user relative to the advertisement. These eye movements are indicia of the user's focus of attention relative to the entire web page. One embodiment for operation of the eye tracking visualization module **308** is described below with reference to FIG. 12. The eye tracking visualization module **308** is coupled to the bus **220** for receiving eye movement information from the cursor/gesture to eye movement transformer **306** and providing a visual image to the user interface module **314**. One example of a user interface including a visual image generated eye tracking visualization module **308** is shown in FIG. 20.

The analytics database **310** is a data store for storing information received by the analytics server as well as data generated during intermediate processes. The analytics database **310** is a database of a conventional type. The analytics database **310** is coupled to the bus **220** for storage and retrieval of information by different components of the analytics server **104**.

The real-time analysis and reporting module **312** is software, code or routines for immediate processing of ad information and analytics data from the ad engagement tracker **302**. The real-time analysis and reporting module **312** is coupled to provide data immediately to the filter module **304** and the attention score generator **320**. The real-time analysis and reporting module **312** allows smaller segments of data to be processed immediately and sent to the user interface **314**. The real-time analysis and reporting

module **312** is coupled to the bus **220** for communication with the other components of the analytics server **104**.

In some embodiments, the real-time analysis and reporting module **312** is coupled to receive conditions or request for advertising analytics from other systems, e.g. advertiser systems (not shown). The real-time analysis and reporting module **312** receives those conditions, monitors for satisfaction of those conditions, and if they occur sends a signal or beacon to the advertiser systems indicating a satisfied condition or the requested information. For example, the real-time analysis and reporting module **312** can receive a request from an advertiser system to be notified of a condition such a placement of an ad, or even more particularly cursor over or gesture over an ad by a user. The data collection scripts of the present invention monitor user behavior and report events to the analytics server **104**. The real-time analysis and reporting module **312** in turn sends this information to the advertiser system. Thus, the analytics server **104** receives a condition from an advertiser system, captures analytics data from using a data collection script; analyzes the captured analytics data to determine whether the condition was satisfied; and generates and sends a signal if the condition was satisfied. The real-time analysis and reporting module **312** can perform some or all of these steps in real time. The real-time analysis and reporting module **312** can modify the signal or beacon sent to the advertiser to include any analytics data such as but not limited to the ad, the ad identifier, time, web page, action, event, browser, placement position, focus index, attention score, etc. This is particularly advantageous because the advertiser systems can use these signals from the real-time analysis and reporting module **312** to optimize ad campaigns while they are running such as automatically adjusting bid prices for ads, ad placement locations, etc.

The user interface module **314** is software, code or routines for presenting advertising analytics information to the user and receiving and processing inputs about that advertising analytics information. For example, the user interface module **314** receives input from the user about specific advertising analytic parameters of interest. The user interface module **314** in response to that user input generates reports, graphics and other information by communicating with the other components of the analytics server **104** and those reports, graphics and other information are provided for display. The user interface module **314** is coupled by the bus **220** for communication with the eye tracking visualization module **308**, the attention score generator **320**, and the real-time analysis and reporting module **312**. The user interface **314** is also coupled by the bus a network interface module **206** to the client device **108** that displays the reports and other information.

The click tag parser **316** is software, code or routines for processing ad information or analytics data stored in the analytics database **310** by the ad engagement tracker **302**. In particular, the click tag parser **316** processes click tag information to generate data parameters that are used by the filter module **304** for click tag analysis. In one embodiment, the click tag parser **316** process the click tag to get an approximation about the page which the user would land if the ad were clicked upon. The click tag parser **316** extracts parameters from the click tag and uses them in generating that approximation. For example, in one embodiment, the click tag parser **316** pulls out the series of URLs in the click tag, determines the last URL in the series, and assumes the user will end up at that URL. The click tag parser **316** is coupled by the bus **220** to retrieve and store information in the analytics database **310**.

11

The rich media parser **318** is software, code or routines for processing ad information and analytics data stored in the analytics database **310** by the ad engagement tracker **302**. Similar to the click tag parser **316** but for rich media, the rich media parser **318** processes the rich media information to generate data and parameters that used by the filter module **304** for rich media analysis. Such rich media information includes ad expansion, ad collapse, add duration, etc. The rich media parser **318** is coupled by the bus **220** to receive information from and store information to the analytics database **310**.

The attention score generator **320** is software, code, or routines for generating an attention score. The attention score generator **320** processes the analytics data and information in the analytics database **310** to generate the attention score. In one embodiment, the attention score is a composite score of several parameters of advertising data including but not limited to a visualization metric, a placement score, a views metric, a share metric, a velocity, a focal index, activity index, an engagement rate, etc. The attention score generator **320** is coupled by the bus **220** to the analytics database **310** to retrieve the information necessary to produce the attention score. The score generator **20** is also coupled by bus **220** to provide the attention score to the user interface module **314**.

The placement module **322** is software, code, or routines for determining the placement of a particular advertisement. The placement module **322** is coupled to retrieve information from the analytics database **310** necessary to determine the placement of an advertisement. The placement module **322** determines not only the domain or website with which the advertisement was delivered, but also the location on the web page delivered. The placement module **322** is coupled to retrieve information from the analytics database **310**. The placement module **322** stores placement information back to the analytics database **310**, and in some embodiments provides the placement information to the placement scoring module **324**.

The placement scoring module **324** is software, code or routines for generating a score representative of the value of placement of an advertisement at a particular position on a specific web page. The placement score advantageously informs publishers which locations on particular web pages are valuable. The placement score is calculated by applying a function to factors including ad position, web page, attention score and the parameters used to calculate it, engagement rate, etc. The placement scoring module **324** is coupled to receive placement information from the placement module **322** or the analytics database **310**. From the placement information, the placement scoring module **324** generates the placement score and stores it in the analytics database **310** or provides it to the attention score generator **320**.

Referring now also to FIG. 4, the data flow through the analytics server **104** is described. The raw data is received from the data collection scripts **114** by the ad engagement tracker **302**. The ad engagement tracker **302** stores the information in the analytics database **310** and also provides it to the real-time analysis and reporting module **312**. The real-time analysis and reporting module **312** and the analytics database **310** also communicate with each other to share information. The analytics database **310** provides information to a first processing pipeline including the filter module **304a**, the cursor/gesture to eye movement transformer **306a**, and the eye tracking visualization module **308a**. This first pipeline processes the raw data to produce a visual image of the user's attention that is provided to the

12

user interface module **314**. This first pipeline process includes a complete analysis of the data to produce the visual image. The real-time analysis and reporting module **312** provides a more limited set of data to a second pipeline including the real-time filter module **304b**, the real-time cursor/gesture to eye movement transformer **306b**, and the eye tracking visualization module **308b**. The second pipeline processes the raw data and produces a visual image of the user's attention that is also provided to the user interface module **314**. Since the second pipeline has a more limited set of data, it can produce the image more quickly; however, the visual image may not be as accurate as that produced by the first pipeline. The analytics database **310** and the real-time and reporting module **312** also provide information to the attention score generator **320**. The attention score generator **320** processes the received information and produces an attention score that is delivered to the user interface module **314** for presentation to the user. Finally, the real-time analysis and reporting module **312** also provides information for example tabular statistics to the user interface **314** for presentation to the user. As shown in FIG. 4, this dataflow allows the user interface module **314** to provide a unified view with the necessary advertising metrics such that advertisers can make better decisions about ad placement and effectiveness.

Ad Search Engine **132**

FIG. 5 is a block diagram of one embodiment of the ad search engine **132**. In this embodiment, the ad search engine **132** comprises: a processor **202**, a memory **204**, a network interface (I/F) module **206**, storage **208**, a bus **220**, a click tag parser **316**, a rich media parser **318**, an ad copy database **502**, a request/query processing module **504**, a user interface module **506**, a content preservation module **508**, an ad identification crowd sourcing module **510**, and a search engine (SE) derived insight generator **512**.

The processor **202**, the memory **204**, the network interface (I/F) module **206**, the storage **208**, the bus, the click tag parser **316** and the rich media parser **318** have the same or similar functionality to that described above with reference to FIGS. 2 and 3, so that description will not be repeated here. It should be noted, however, that the network interface module **206** is coupled by signal line **134** to the network **106** and to the bus **220**. It should also be noted that the click tag parser **316** and the rich media parser **318** process the information received from the data collection script **114** but in a manner different than that described above with reference to FIG. 3. The click tag parser **316** and the rich media parser **318** process the advertising information or analytics data for research purposes as opposed to for evaluation as in the analytics server **104**.

The ad copy database **502** is a data store for information from the click tag parsers **316**, the rich media parser **318**, and the content preservation module **508**. In one embodiment, the ad copy database **502** stores the original ad content as well as enough information to render the ad in the same context as the one in which it was presented to the user. In some embodiments, the ad copy database **502** also stores ad impression data, creative records, and other metadata. This advantageously allows the ad search engine **132** to reproduce the advertisement for later review by advertisers and marketing personnel. The ad copy database **502** is a database of a conventional type. The analytics database **310** is coupled to the bus **220** for storage and retrieval of information by different components of the ad search engine **132**.

The request/query processing module **504** is software, code or routines for receiving queries, performing searches of the ad copy database **502** and returning results. The

13

request/query processing module **504** is coupled to the user interface module **506** to receive query terms input by the user. The request/query processing module **504** uses those terms to formulate a query and apply the query to the ad copy database **502**. The results from the query are then processed and formatted and then sent to the user interface module **506** for delivery to the user. One method for operating the request/query processing module **504** is described below with reference to FIG. 9. The request/query processing module **504** is coupled to the bus for communication with the other components of the ad search engine **132** including the user interface module **506** and the ad copy database **502**.

The user interface module **506** is software, code or routines for providing presenting a search interface to users, receiving input and search queries, and outputting results. The operation of the user interface module **506** is described in more detail below with reference to FIGS. 9, **13A**, **13B**, and **17-19**. The user interface module **506** is coupled by the bus **220** for communication with the request/query processing module **504** and the network interface module **206** for communication with client devices **108**.

The content preservation module **508** is software, code, or routines for capturing the context in which ads were presented to the user. The context preservation module **508** receives context information and stores it in the ad copy database **502** so that the presentation of those advertisers can be rendered upon requests to the ad search engine **132**. One embodiment for the operation of the content preservation module **508** is described in more detail below with reference to FIGS. **15A** and **15B**. The content preservation module **508** is coupled to the bus **220** to receive or retrieve information about ad context from the analytics server **104** and store requisite information in the ad copy database **502**.

The ad identification crowd sourcing module **510** is software, code or routines for generating and storing identification information about ads. The ad identification crowd sourcing module **510** is adapted to send relevant information about advertisements that has been extracted from the ad copy database **508** to users. The users in turn identify the ad and associated information and send that information back to the crowd sourcing module **510**. In one embodiment, the users identify the brand, sponsor, company etc. associated with the advertisement. The ad identification crowd sourcing module **510** is coupled via the bus **220** and the network interface module **206** to present unidentified ads to users. The ad identification crowd sourcing module **510** receives the identification information from the user and stores that information into the ad copy database **502**. In some embodiments, the ad identification crowd sourcing module **510** may send a particular ad to multiple users and use the identifying information provided by the majority of crowd source users.

The search engine (SE) derived insight generator **512** is software, code, or routines for generating a derived insight score for advertisement. The operation of the search engine derived insight generator **512** is described in more detail below with reference to FIG. **16**. The derived insight score is an inferred value of an ad (e.g., how well an ad performs.) For example, the search engine derived insight generator **512** can probe the internet and ad servers to obtain leaked insights about ad performance such as the best performing ads or whether there are a lot of dollars being spent on a particular ad. This information is used to generate the derived insight score. The search engine derived insight generator **512** provides that derived insight score to the ad search engine **132**, used when ranking or presenting results, or to user interface module **506** for presentation to the user.

14

The search engine derived insight generator **512** is coupled to receive information from the ad copy database **502**.

Referring now to FIG. **6**, an embodiment of a web browser **112** and components used in the advertising system **100** in accordance with the present invention are shown. FIG. **6** shows the web browser **602** similar to that in FIG. **1** that is operable on the client device **108**. The web browser **112** is of a conventional type such as Internet Explorer provided by Microsoft Corporation, Firefox provided by Mozilla Foundation or Safari provided by Apple Computer Inc. In accordance with the present invention, ads are delivered for presentation by the web browser **112**. The ads are delivered to the client device **108** in the form of an ad container **604** that is a software object or container including code executable by the web browser **112**. The ad container **604** of the present invention advantageously includes an advertisement **606** that includes the advertising visual content **608** and an injected script **610**. In one embodiment, the ad container **604** is one or more iframes executing the advertisement **606**, presenting the advertisement visual content **606** and executing the injected script **610**. The injected script **610** is synonymous with the data collection script **114** of FIG. **1**. The present invention is particularly advantageous because the web browser **112** processes the ad container **604** and the advertisement **606** in a conventional manner as existing ad containers. However, the advertisement **606** constructed in accordance with the present invention includes both the advertising visual content **608** and the injected script **610**. The injected script **610** cooperates with the web browser **112** to capture information about the presentation of the advertising visual content **608**, and the injected script **610** non-intrusively sends the captured information to the analytics server **104**.

Methods

Referring now to FIG. **7**, one embodiment of a method **700** for preparing ads will be described. The method **700** begins by provisioning **702** an ad identifier. In other words, the ad preparation server **118** assigns a unique identification number or identifier to an ad that is about to be served. This unique identifier is used to associate any information reported by the data collection script **114** to the analytics server **104** with this particular ad. The method **700** continues by determining the types of scripts included in the ad and processing the scripts to add the data collection script **114** and create a modified ad. If JavaScript is included in the ad then it is processed with steps **704-708** of the method **700**. If action script is included in the ad then the ad is processed with steps **712-720** of the method **700**.

For those ads including only JavaScript, the method **700** retrieves **704** scripts to the JavaScript for the advertisement. For example, the script creation processor **216** can retrieve the script template from the injected ad database **222** or the storage holding the script templates. The method **700** then retrieves **706** the ad asset. For example the script creation processor **216** can retrieve the ad asset from the advertising asset server **116**. Next the data collection script **114** for the ad is created **708** by adding a script template and added to the modified ad. The method **700** completes by sending **710** the ad to the ad server **102** for insertion.

For those ads including action script, the method **700** retrieves **712** the script templates from storage. Next, the method **700** retrieves **714** the ad asset from the advertising asset server **116**. The method **700** then disassembles **716** the action script. The method **700** then adds **718** the injected script. The original action script and the injected script are combined or reassembled **722** to create a modified ad. In some embodiments, the modified ad is also validated to

15

ensure proper operation. The method **700** then completes by sending **710** the ad to the ad server **102** for insertion.

The present invention is particularly advantageous because this process for preparing the modified ad ensures that the modified will execute in the same manner as the original ad without any impact of the injected script. Furthermore, the present invention advantageously provides an injected script that non-intrusively sends data to the analytics server **104**. Furthermore, the process described with reference to FIG. 7 can be performed in fractions a second, thereby allowing the ad preparation to be performed in real-time on-the-fly.

Referring now to FIG. 8, one embodiment of a method **800** for deriving a heat map in accordance with the present invention. This general method **800** for deriving a heat map begins by capturing **802** analytics data. As noted above, this is accomplished by adding data collection script to advertisements before they are served. Once they are served along with content, they generate data that is sent from client devices **108** to an analytics server **104**. Next the captured analytics data is filtered **804** and weighted. For example, the analytics, in particular the cursor or gesture data, data may be filtered and weighted as described above by the filter module **304**. The method **800** continues by converting **806** the cursor or gesture data to a visual image. For example, the visual image may be a heat map where different colors on the heat map represent different levels of focus of the user. In one embodiment, the individual image is produced by the cursor/gesture to eye movement transformer **306** and the eye tracking visualization module **308**. The method **800** completes by providing **808** the visual image for display. For example, the user interface module **314** sends the heat map to a client device for presentation in the browser **112**.

Referring now to FIG. 9, one embodiment of a method **900** for displaying ad search results in accordance with the present invention will be described. The method **900** begins by receiving **902** a query from a client device **108** at the ad search engine **132**. The query is received and processed by the request/query processing module **504**. The query is used to perform a search **904** of the ad copy database **502**. The results are returned to the request query processing module **504** which formats **906** the results as tiles. One example of such formatted results is shown in FIG. 17. In some embodiments, the user interface module **506** is responsible for formatting the query results as tiles. The user interface module **506** then sends the formatted tiles to the client device **108** for display to the user **110**. The user **110** can interact with the tiles and input commands, make selections, or gesture or cursor over different tiles. The client device **108** sends any input from the user **110** and it is received **910** by the ad search engine **132**. The method **900** determines **912** whether the input was a hover over a particular tile. If not, the method **900** is complete and ends. In other embodiments, the method **900** loops to step **910** until the user closes the browser window **112**. On the other hand, if the method **900** determined **912** that the user input was a cursor or gesture over a tile, the method **900** identifies **914** the ad corresponding to the tile. Then the ad corresponding to the tile is retrieved **916** from the ad copy database **502**. For example, a playable version of the ad, ad metrics and associated buttons are retrieved from the ad copy database **502**. The retrieved ad is then combined **918** with ad metrics and buttons into a script executable by the web browser **112**. The method **900** concludes by providing **920** the combination (e.g., the executable script) to the client device **108** for

16

display of the ad. Examples of such ads produced by executing the script are shown in FIGS. 18 and 19 and described below.

Referring now to FIG. 10, one embodiment of a method **1000** for generating and sending advertising data in accordance with the present invention will be described. FIG. 10 shows one embodiment for the method **1000** performed by the data collection script **114** or the injected script. The method **1000** begins by determining **1002** which objects are ads in the frame or page in which the data collection script **114** is executing. Then the method **1000** gathers **1004** data from the context of the ad. For example, the method **1000** determines the ad identifier, the publisher or website, and other information. In essence, the method **1000** gathers a data snapshot of the context in which the ad is being presented. The method **1000** continues by tracking **1006** browser activities of the user related to eye tracking. For example, cursor or gesture movements, click inputs, or scroll inputs are track tracked and temporarily stored. The method **1000** also monitors **1008** for trigger events. For example, trigger events include but are not limited to execution of certain events by the web browser **112** such as the loading of an ad, a cursor or gesture being moved over an ad, ad being clicked upon, certain custom events, and other events. Next the method **1000** determines **1010** whether a trigger event has been detected. If not, the method **1000** returns to step **1006** and continues to track browser activities and monitor for trigger events. On the other hand if a trigger event was detected in step **1010**, the method **1000** continues to non-intrusively send **1012** messages from the client device **108** to the analytics server **104**. The messages include the track browser activities and trigger events. The messages are sent "non-intrusively" in that it is virtually impossible for the normal users to tell this information is being sent from the client device **108** to the analytics server **104**. In one embodiment, the messages are non-intrusively sent by using XML sockets or server call methods. After the method **1000** has nondestructively sent the messages to the analytics server **104**, the method **1000** determines **1014** whether the browser window has been closed. If not, the method **1000** returns to step **1006** and continues to track browser activities and monitor for trigger events. However, if the browser window has been closed, the method **1000** is complete and ends. From the above method **1000**, it should be understood that the data collection script **114** or the injected script is particularly advantageous because: 1) the information about user interaction with the ad is sent non-intrusively from the client device **108** to the analytics server **104**; 2) the information about user interaction is sent in multiple small messages after each trigger event thereby providing real-time data; 3) the information about user interaction is sent in multiple small messages thereby making the tracking unnoticeable to the user.

Referring now to FIG. 11, one embodiment of a method **1100** for generating a representation of a focus of attention for user will be described. In this embodiment, the method **1100** uses eye tracking as indicia for the user's focus attention. The method **1100** begins by retrieving **1102** activity data from the analytics database **310** for a campaign. In one embodiment, the method **1100** retrieves data about users activity provided by the data collection scripts **114** related to a particular ad campaign. In some embodiments, the messages provided by the data collection script and stored in the analytics database **310** are processed hundreds of times so that the data from a particular campaign is retrieved. Next the method **1100** transforms **1104** the messages from the analytics database **310** to pixel positions in ad space and

17

time. In one embodiment, the transformation is relative to the upper left corner of the ad. In another embodiment, the method **1100** transforms user messages containing client environment variables to positions in pixels relative to a corner of an ad and to times relative to the start of a notable event of importance to the ad. The method **1100** continues by generating **1106** a weighting parameter for each event from the activity data. Then the method **1100** creates **1108** a zero value matrix, and populates **1110** the matrix using weighting parameters, pixel positions and times. In one embodiment, the method **1100** builds a heat map data structure by adding the transformed user activity data to values in an initially zero value matrix corresponding to the weighting parameters with keys corresponding to time and pixel coordinates of an ad.

Referring now to FIG. 12, one embodiment of a method **1200** for generating a map of user attention or focus will be described. In this embodiment, the map is referred to as a heat map and uses the heat map data structure generated in accordance with FIG. 11. The method **1200** begins by retrieving **1202** heat map data. For example, the populated zero value matrix described above with reference to FIG. 11 is retrieved. Next the method **1200** convolves **1204** the data in the matrix with the fundamental solution to the heterogeneous heat diffusion equation. For example, the method **1200** convolves data with Green's function to the heterogeneous heat diffusion equation:

$$\nabla^2 T - \frac{\delta T}{\delta t} = \delta(\vec{x}).$$

The method **1200** continues by normalizing **1206** the data to a predefined range. In one embodiment, the method **1200** applies normalization to make the range of T zero to 255, inclusive. Finally, the method **1200** applies **1208** a color map associating a value to color and an alpha transparency proportional to that value to produce the visual image.

Referring now to FIGS. 13A and 13B, one embodiment of a method **1300** for generating an ad search result interface will be described. The method **1300** begins by receiving **1302** a search query, performing a search on the ad copy database **502**, and returning result ads. Then the method **1300** defines **1304**  $n$ , the number of columns of tiles for the user interface. In one embodiment,  $n$  equals 3 or 4. The method **1300** continues by sorting **1306** the result ads by a key or other common parameter of the ads. In one embodiment, the key is set to be a default of the date and time of the most recent impression for the ads. The method **1300** continues to place the ads to form the user interface. The method **1300** starts with the smallest key and selects **1308** an ad. For the selected ad, the method **1300** computes **1310** the thumbnail height of the ad. Then the method **1300** adds **1312** the ad to the column with the smallest height. Then the method **1300** adjusts **1314** the ad placement for tall ads. For example, if ad is very tall (e.g., 160x600 pixels), place two ads side-by-side in the column; and if one tall and has been placed and is missing a partner, add the new ad next to it. Next, the method **1300** determines **1316** whether a layout criteria has been reached or satisfied. For example, layout criteria include: 1) no more matching ads; 2) an ad minimum has been reached (e.g., 100 ads per page); or 3) the pixel page height maximum has been reached (e.g., 500 pixels per column). Once the layout criteria are satisfied, the method **1300** returns and repeats steps **1308** to **1316**. If the layout criteria are not satisfied, the method **1300** continues in step

18

**1318** of FIG. 13B. Referring now also to FIG. 13B, the method **1300** next determines **1318** whether there are more ads that are not included in the tiled user interface. If so, the method **1300** adds **1320** a "more" button to the user interface that when selected by the user presents the remaining ads. After either step **1318** or step **1320**, the method **1300** completes by providing the user interface including the ads for display. In particular, the user interface module **506** sends the tiled user interface to the client device **108**. One example of such an interface is shown in FIG. 17.

FIGS. 14A and 14B show one embodiment of a method **1400** for populating the ad copy database **502** in accordance with the present invention. The method **1400** begins by scraping the World Wide Web for ads. In one embodiment, steps **1402** through **1412** are performed by a Linux web scraper including a web browser such as Firefox, Apache HTTP server, and simple queue service from Amazon. The scraper boots and launches **1402** a plurality of virtual desktops. This is advantageous because the scraper can be scaled by increasing the number of virtual desktops according to the amount of scraping required. These virtual desktops then open up **1404** one or more browser windows or tabs. The browsers may be Firefox from Mozilla and include an Adobe flash plug-in and injected script of the present invention. Next, the method **1400** requests instructions in the tabs of the browsers. More specifically, the method **1400** loads **1406** separate uniform resource locators (URLs) into separate tabs of the browsers and waits for the web servers to respond and deliver the web page corresponding to the URL. For example, it may take up to 8 to 30 seconds for the web pages to start loading. The method **1400** then scrolls **1408** to the bottom of each web page and waits for any remaining content to be delivered to the web browsers. After scrolling to the bottom of the page, the method **1400** waits a predetermined amount of time. For example, the predetermined amount of time may be 45 seconds to ensure that the content for the web page has been provided to the virtual desktops. Next the method **1400** captures **1410** a screenshot of the advertisement and the ad characteristics or metadata. In one embodiment, the ad characteristics or metadata include the dimension of the ad, HREFs, SWF, file format, and other metadata. The scraping completes by posting **1412** the ad screenshot, URL, and other metadata for server-side processing by the analytics server **104**. For example, the posted information may include the URL of the ad, a page identifier, then ad identifier, X and Y dimensions of the ad, ad type, and flash variables. The method **1400** processes **1414** the ad, the URL, and the metadata at the analytics server **104**. The method **1400** continues by writing **1416** this information to the ad copy database **502** that may be a canonical database, for example. In one embodiment, the ad copy database **502** may hold millions of records corresponding to different advertisements ordered by impression identifier and advertising identifier. Periodically, the method **1400** publishes **1418** tasks or summary records of the information in the ad copy database **502**. In one embodiment, the tasks are published every 60 seconds. The method **1400** writes **1420** this information to the analytics database **310**. Once stored in the analytics database **310**, this information can be queried by advertisers and others using a web front end and SQL queries.

Referring now to FIGS. 15A and 15B, one embodiment of a method **1500** for ad preservation will be described. As has been noted above, the present invention is particularly advantageous because it can provide the ad, the ad context, and even replay the ad as it was presented to the user. This is in part made possible by the ad preservation method **1500**

19

of FIGS. 15A and 15B. The ad preservation method 1500 begins by obtaining 1502 the ad page scrape results. The method 1500 processes the scrape results and performs 1504 backend data collection. Then the method 1500 downloads 1506 the creative content of the ad locally to the ad copy database 502 or storage 208. Next the method 1500 calculates a hash value for the ad contents, such as using a MD5 Message-Digest Algorithm. Hashes are used to minimize the amount of redundant content that needs to be stored in the ad copy database 502. The method 1500 continues by looking up 1510 the hash value in the ad copy database 502. Then the method 1500 determines 1512 whether the hashed value was found. If the hash value was found, the method 1500 proceeds to step 1526 of FIG. 15B and skips storing the creative content. On the other hand if the hashed value was not found, a new record is created in the ad copy database 502. If the hashed value was not found 1512, the method 1500 creates 1514 a new creative record. Then the method 1500 extracts 1516 metadata for the ad. In one embodiment, the extracted metadata includes the file type, file size, etc. In another embodiment, the extracted metadata includes a process for click tag identification. The other metadata is parsed to extract click tag information. For example, the method considers URL query parameters that include "click," or "click Tag," or any similarly named flash variables, protocol identifiers, and URL encoding. The method continues by storing 1518 the extracted metadata in the ad copy database 502. In addition, the ad contents may be stored locally at an address in the storage 208 of the ad search engine. Alternatively, the ad contents may be stored at an address in storage in the cloud or another remote file storage location. The method 1500 continues by updating 1520 the creative record with the address where the ad contents are stored. Then the method 1500 stores 1522 a creative screenshot at an address. The creative record is again updated 1524 with the address where the screenshot is stored. The method 1500 then records 1526 and an ad impression in the ad copy database 502. The record for the ad impression includes a URL, and an identifier, a creative record and the date and time. Then the method 1500 determines 1528 whether the image or asset has a known advertising size and format. If not, the method 1500 ends. However, if the image or asset has a known advertising size and format, the method 1500 proceeds to create 1530 a job for crowd source brand identification and then tag 1532 the job for processing. Then the method 1500 ends.

FIG. 16 shows one embodiment of a method 1600 for generating derived insight scores in accordance with the present invention. The method 1600 begins by searching 1602 the ad copy database 502 for impressions. In one embodiment, the method 1600 is run every 60 seconds. Then the method 1600 ranks 1604 the ad impressions by recency, importance or other variables. Next, the method 1600 performs various analysis on the ranked ad impressions. The method 1600 determines 1606 different personas. For example, the method 1600 browses with different cookies, browses from other locations or mimics different browsers to determine whether these factors have any effect on ad placement. The method 1600 also determines 1608 ordering. For example, each URL is loaded multiple times. Step 1608 determines whether the impression was seen on the first load, the second load or a later load of the URL. The method 1600 also determines 1610 the number of impressions for each ad across multiple sites and multiple dates. Finally, the method 1600 determines 1612 the placement of the impression on the Web page. For example, the method 1600 determines whether the placement was above the fold,

20

within a number of pixels of the top of the page or other location information. The method 1600 completes by generating 1614 the search engine derived insight score from the personas, ordering, total impressions and placement on the page.

#### User Interfaces

FIG. 17 shows a graphic representation of one example of a user interface 1700 showing advertisement search results. The search results are shown in a browser window 1702. The user interface 1700 includes a title area, a search box 1704, a suggestions area 1706, and the display area 1708 showing the plurality of tiles 1710 of different thumbnail images of advertising. The search box 1704 provides an area in which queries can be input and a search button for initiating a search of the ad copy database 502. The suggestion area 1706 includes a number of hypertext links of other searches that can be run on the ad copy database. Below the search box 1704, the interface 1700 provides an area for providing global information such as the total number of ads that are produced by a given query. In this example, the search term is "Starbucks" and the query returned 44 ad results. The display area 1708 advantageously provides the thumbnail images of the advertisements. The display area 1708 is populated with tiles 1710 of varying size but with matching proportionality so that the user has an impression from the thumbnail images of how the advertisement was presented as an impression. In this embodiment, the display area 1708 includes four columns. A particular ad 1712 is shown in the second column for ads down the top.

Referring now to FIG. 18, a graphic representation of a modified user interface 1800 is shown after the user has moved the cursor or gesture over ad 1712 of FIG. 17. For convenience and ease of understanding, similar reference numerals as used above in FIG. 17 are used in FIG. 18 to reference components of the user interface 1800 with the same or similar functionality. Moving the cursor or gesture over ad 1712 or moving the cursor or gesture over ad 1712 and clicking, causes the user interface module 506 of the ad search engine 132 to display the pop-up window 1802. The pop-up window 1802 includes a thumbnail image 1804 of the original advertisement and other metadata 1806 and controls. For example, the other metadata 1806 includes an identification of the brand, the date and time and domain of the impression and options to share the ad are flagged. It should be understood that FIG. 18 shows only one embodiment of the metadata that can be provided according to the present invention. Other formats and metadata may be present as part of the pop-up window 1802.

Referring now to FIG. 19, a graphic representation of the modified user interface 1900 is shown. This version of the user interface 1900 again presents the information in a browser window 1702. In addition to search for a particular brand, a search of a particular site can be performed by the search engine of the present invention. In addition to top label, a search box, suggestion box, and global information similar to that of user interfaces 1700 and 1800, the user interface 1900 also provides a brand summary area 1902 and a display area 1904. The brand summary area 1902 lists the brands that were advertised on the site that was queried. The display area 1904 is similar to that described above with reference to FIGS. 17 and 18 and also provides the same pop-up functionality as described above with reference to FIG. 18.

Systems and methods for advertising analytics and advertising searching have been described. In the above description, for purposes of explanation, numerous specific details were set forth. It will be apparent, however, that the dis-

21

closed technologies can be practiced without these specific details. In other instances, structures and devices are shown in block diagram form. For example, the disclosed technologies are described in one embodiment below with reference to user interfaces and particular hardware. Moreover, the technologies are disclosed above primarily in the context of the Internet and on-line advertising; however, the disclosed technologies apply to other types of advertising.

Reference to the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the disclosed technologies. The appearances of the phrase “in one embodiment” in various places in the specification are not necessarily all referring to the same embodiment.

Some portions of the detailed descriptions above were presented in terms of processes and symbolic representations of operations on data bits within a computer memory. A process can generally be considered a self-consistent sequence of steps leading to a result. The steps may involve physical manipulations of physical quantities. These quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. These signals may be referred to as being in the form of bits, values, elements, symbols, characters, terms, numbers or the like.

These and similar terms can be associated with the appropriate physical quantities and can be considered labels applied to these quantities. Unless specifically stated otherwise as apparent from the prior discussion, it is appreciated that throughout the description, discussions utilizing terms such as “processing” or “computing” or “calculating” or “determining” or “displaying” or the like, may refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

The disclosed technologies may also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may comprise a general-purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but is not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, flash memories including USB keys with non-volatile memory or any type of media suitable for storing electronic instructions, each coupled to a computer system bus.

The disclosed technologies can take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment containing both hardware and software elements. In one embodiment, the technology is implemented in software, which includes but is not limited to firmware, resident software, microcode, etc.

Furthermore, the disclosed technologies can take the form of a computer program product accessible from a computer-usable or computer-readable medium providing program code for use by or in connection with a computer or any instruction execution system. For the purposes of this description, a computer-usable or computer-readable medium can be any apparatus that can contain, store, com-

22

municate, propagate, or transport the program for use by or in connection with the instruction execution system, apparatus, or device.

A data processing system suitable for storing and/or executing program code will include at least one processor coupled directly or indirectly to memory elements through a system bus. The memory elements can include local memory employed during actual execution of the program code, bulk storage, and cache memories which provide temporary storage of at least some program code in order to reduce the number of times code must be retrieved from bulk storage during execution.

Input/output or I/O devices (including but not limited to keyboards, displays, pointing devices, etc.) can be coupled to the system either directly or through intervening I/O controllers.

Network adapters may also be coupled to the system to enable the data processing system to become coupled to other data processing systems or remote printers or storage devices through intervening private or public networks. Modems, cable modems and Ethernet cards are just a few of the currently available types of network adapters.

Finally, the processes and displays presented herein may not be inherently related to any particular computer or other apparatus. Various general-purpose systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will appear from the description below. In addition, the disclosed technologies were not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the technologies as described herein.

The foregoing description of the embodiments of the present techniques and technologies has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the present techniques and technologies to the precise form disclosed. Many modifications and variations are possible in light of the above teaching. It is intended that the scope of the present techniques and technologies be limited not by this detailed description. The present techniques and technologies may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. Likewise, the particular naming and division of the modules, routines, features, attributes, methodologies and other aspects are not mandatory or significant, and the mechanisms that implement the present techniques and technologies or its features may have different names, divisions and/or formats. Furthermore, the modules, routines, features, attributes, methodologies and other aspects of the present invention can be implemented as software, hardware, firmware or any combination of the three. Also, wherever a component, an example of which is a module, is implemented as software, the component can be implemented as a standalone program, as part of a larger program, as a plurality of separate programs, as a statically or dynamically linked library, as a kernel loadable module, as a device driver, and/or in every and any other way known now or in the future to those of ordinary skill in the art of computer programming. Additionally, the present techniques and technologies are in no way limited to implementation in any specific programming language, or for any specific operating system or environment. Accordingly, the disclosure of the present techniques and technologies is intended to be illustrative, but not limiting.

23

What is claimed is:

1. A method, comprising:

modifying an advertisement content object to include a data collection script, wherein the data collection script executes each time a triggering event is detected to capture activity data, wherein the activity data includes cursor data and an identification of the triggering event, and wherein the advertisement content object is modified by:

provisioning an advertisement identifier;  
retrieving one or more script templates;  
retrieving an advertisement asset; and

combining the (1) advertisement identifier, (2) the one or more script templates or an injected script, and (3) the advertisement asset into a modified advertisement content object;

serving the modified advertisement content object;

receiving a set of activity data, wherein the activity data is received from the data collection script included in the modified advertisement content object;

transforming, for each activity data of the set of activity data, the activity data to a pixel position at a particular time corresponding to the triggering event, wherein the pixel position is relative to a reference pixel of the advertisement content object;

generating a weighting parameter for each activity data of the set of activity data, wherein the weighting parameter corresponds to the triggering event that triggered execution of the data collection script capturing the activity data;

creating a zero value matrix;

generating a heat map data structure by populating the zero value matrix using the pixel position and weighting parameter for each activity data of the set of activity data;

convolving the heat map data structure using a heterogeneous heat diffusion equation;

normalizing the convolved heat map data structure to a predefined range;

generating a visual image by applying a color map to the normalized convolved heat map data structure that associates a color with each value of the normalized convolved heat map data structure and modifying each value with a proportional alpha transparency value; and  
providing the visual image for display.

2. The method of claim 1, wherein the trigger event includes one of:

loading of the modified advertisement content object by a browser, a cursor being moved over the modified advertisement content object, and the modified advertisement content object being clicked upon.

3. The method of claim 1, wherein visual image is generated using captured activity data for particular advertisement campaign.

4. The method of claim 1, wherein the heterogeneous heat diffusion equation is

$$\nabla^2 T - \frac{\delta T}{\delta t} = \delta(\vec{x}).$$

5. The method of claim 1, wherein the heterogeneous heat diffusion equation is solved by applying a Green's function to the heterogeneous heat diffusion equation.

6. The method of claim 1, wherein modifying the advertisement content object further includes:

24

determining that the advertisement content object comprises an action script;

disassembling the action script;

assembling an injected script by combining the disassembled action script with the one or more script templates; and

combining the advertisement identifier, the injected script, and the advertisement asset into the modified advertisement content object.

7. The method of claim 1, wherein activity data is received upon detecting each trigger event in real-time.

8. A system comprising:

one or more processors;

a memory; and

a non-transitory machine-readable storage medium containing instructions, which when executed on the one or more processors, cause the one or more processors to perform operations including:

modifying an advertisement content object to include a data collection script, wherein the data collection script executes each time a triggering event is detected to capture activity data, wherein the activity data includes cursor data and an identification of the triggering event, and wherein the advertisement content object is modified by:

provisioning an advertisement identifier;

retrieving one or more script templates;

retrieving an advertisement asset; and

combining the (1) advertisement identifier, (2) the one or more script templates or an injected script, and (3) the advertisement asset into a modified advertisement content object;

serving the modified advertisement content object;

receiving a set of activity data, wherein the activity data is received from the data collection script included in the modified advertisement content object;

transforming, for each activity data of the set of activity data, the activity data to a pixel position at a particular time corresponding to the triggering event, wherein the pixel position is relative to reference pixel of the advertisement content object;

generating a weighting parameter for each activity data of the set of activity data, wherein the weighting parameter corresponds to the triggering event that triggered execution of the data collection script capturing the activity data;

creating a zero value matrix;

generating a heat map data structure by populating the zero value matrix using the pixel position and weighting parameter for each activity data of the set of activity data;

convolving the heat map data structure using a heterogeneous heat diffusion equation;

normalizing the convolved heat map data structure to a predefined range;

generating a visual image by applying a color map to the normalized convolved heat map data structure that associates a color with each value of the normalized convolved heat map data structure and modifying each value with a proportional alpha transparency value; and  
providing the visual image for display.

9. The system of claim 8, wherein the trigger event includes one of:

loading of the modified advertisement content object by a browser, a cursor being moved over the modified

## 25

advertisement content object, and the modified advertisement content object being clicked upon.

10. The system of claim 8, wherein visual image is generated using captured activity data for particular advertisement campaign.

11. The system of claim 8, wherein the heterogeneous heat diffusion equation is

$$\nabla^2 T - \frac{\delta T}{\delta t} = \delta(\bar{x}).$$

12. The system of claim 8, wherein the heterogeneous heat diffusion equation is solved by applying a Green's function to the heterogeneous heat diffusion equation.

13. The system of claim 8, wherein modifying the advertisement content object further includes:

determining that the advertisement content object comprises an action script;  
disassembling the action script;  
assembling an injected script by combining the disassembled action script with the one or more script templates; and  
combining the advertisement identifier, the injected script, and the advertisement asset into the modified advertisement content object.

14. The system of claim 8, wherein the activity data is received upon detecting each trigger event in real-time.

15. A non-transitory machine-readable storage medium containing instructions, which when executed by one or more processors, cause the one or more processors to perform operations including:

modifying an advertisement content object to include a data collection script, wherein the data collection script executes each time a triggering event is detected to capture activity data, wherein the activity data includes cursor data and an identification of the triggering event, and wherein the advertisement content object is modified by:

provisioning an advertisement identifier;  
retrieving one or more script templates;  
retrieving an advertisement asset; and  
combining the (1) advertisement identifier, (2) the one or more script templates or an injected script, and (3) the advertisement asset into a modified advertisement content object;

serving the modified advertisement content object;  
receiving a set of activity data, wherein the activity data is received from the data collection script included in the modified advertisement content object;

## 26

transforming, for each activity data of the set of activity data, the activity data to a pixel position at a particular time corresponding to the triggering event, wherein the pixel position is relative to reference pixel of the advertisement content object;

generating a weighting parameter for each activity data of the set of activity data, wherein the weighting parameter corresponds to the triggering event that triggered execution of the data collection script capturing the activity data;

creating a zero value matrix;

generating a heat map data structure by populating the zero value matrix using the pixel position and weighting parameter for each activity data of the set of activity data;

convolving the heat map data structure using a heterogeneous heat diffusion equation;

normalizing the convolved heat map data structure to a predefined range;

generating a visual image by applying a color map to the normalized convolved heat map data structure that associates a color with each value of the normalized convolved heat map data structure and modifying each value with a proportional alpha transparency value; and  
providing the visual image for display.

16. The non-transitory machine-readable storage medium of claim 15, wherein the trigger event includes one of:

loading of the modified advertisement content object by a browser, a cursor being moved over the modified advertisement content object, and the modified advertisement content object being clicked upon.

17. The non-transitory machine-readable storage medium of claim 15, wherein visual image is generated using captured activity data for particular advertisement campaign.

18. The non-transitory machine-readable storage medium of claim 15, wherein the heterogeneous heat diffusion equation is

$$\nabla^2 T - \frac{\delta T}{\delta t} = \delta(\bar{x}).$$

19. The non-transitory machine-readable storage medium of claim 15, wherein the heterogeneous heat diffusion equation is solved by applying a Green's function to the heterogeneous heat diffusion equation.

20. The non-transitory machine-readable storage medium of claim 15, wherein the activity data is received upon detecting each trigger event in real-time.

\* \* \* \* \*