SYSTEM AND METHOD FOR COMMUNICATING MEDIA SIGNALS

RELATED APPLICATION

This application is a non-provisional application of "Reynolds et al. a provisional application entitled "System and Method for Communicating Media Signals" attorney docket number ID-PAT-001PR1, application number 60/325,483, filed on September 26, 2001.

FIELD

This disclosure relates to a system and method for communicating media signals between source and destination devices. More specifically, it relates to a system and method for compressing and decompressing streaming and static media signals for efficiently communicating those signals between source and destination devices using artificial intelligence mechanism.

BACKGROUND

The ability to efficiently communicate streaming and static media between remotely located devices is a significant need that has emerged exponentially with the advent of networked communications such as the Internet. This need has been recently addressed with substantial development resources on a worldwide scale.

The term "media" is herein intended to mean information that may be communicated in the form of a signal from a source device to a destination device for use by the destination device; and, where used herein, media is generally contemplated to comprise either streaming or static media signals. For the purpose of this disclosure, the term "use" as applied to a destination device's operation on media signals is intended to include playing (e.g. sounds, images, video), processing (e.g. telemetry data), or any other use or operation that is the intended purpose of the media signal.

The terms "streaming media" are herein intended to mean media signals that comprise information intended to be communicated to and used by a destination device in a temporal, streaming fashion. The term "streaming" as applied to streaming media signals is herein intended to include signals communicated and processed in a continuous manner over time, or signals that may be

signals communicated and processed in a continuous manner over time, or signals that may be communicated in a series of discrete packets, pieces, or blocks that are interrelated and may be thereafter used by the destination device in a continuous, interrelated fashion. Examples of streaming media signals for the purpose of this disclosure therefore include, without limitation, the following types of media: video, audio, audio combined with video, and data strings such as temporal telemetry. The terms "streaming media" are most typically used by reference to digitized forms of data representing the subject media.

The terms "static media" are herein intended to generally mean media that is not "streaming" as defined above. Static media signals are of the type that generally may be communicated and are intended to be used as a single packet, block, or piece. Static media therefore may include for example, without limitation the following: a discrete image, an individual and relatively temporally short video clip, a sound or sound bite, or a piece or block of information such as telemetry information. It is contemplated, however, that such a "single piece" of static media may be of sufficient magnitude to consist of a plurality of smaller pieces or sub-parts, such as for example regions or pixels of an overall image, individual frames that together form a video clip, digital bits that together comprise a sound, a group of sounds that comprise a sound bite, or bits of information that together comprise a larger block of information.

Streaming media generally includes data files that are significantly larger than static media files, and also often represent many more variables over the temporal communication of such files than experienced with most static media files. Therefore, the ability to efficiently compress streaming media for appropriate communication to destination devices for use is often a much more complex and difficult to achieve goal. Accordingly, much of this disclosure is provided by reference specifically to streaming media communication, and the present invention has been observed to provide significant benefits for such communication. However, where streaming media is specifically referenced herein with respect to this background, and further with respect to the many benefits of the present invention herein disclosed, static media is also further contemplated where appropriate according to one of ordinary skill.

Many different "type-specific" media systems have been in use for quite a long time for transmitting specific types (e.g. video, audio, image, voice, etc.) of streaming and static media signals between sources and remote destinations. Typical examples of such type-specific media systems include television transmission systems, telephone line systems, and radio transmission systems, and every television, telephone, and radio is therefore a receiving device for media. Accordingly, the needs

for efficient communication of streaming and static media touch upon many diverse communications industries, including for example the telephone, television, movie, music, and more recently interactive gaming industries.

Moreover, many medial communications systems, including the various long-standing type-specific systems, are also "format specific", wherein the subject media signals are communicated in a particular format such that the source, transmission channel, and destination device must be specifically compliant to work within that format. Examples of format specific media systems include for example encoded cable television systems that work only for certain types of media and only delivered in particular encoded formats from the cable carrier. Therefore, these systems, in hardware and software, are generally dedicated to only the type and format of media to be provided by the content provider.

Society's needs have outpaced the abilities of these dedicated, content-specific and format-specific systems. In particular, these dedicated systems are not structured to accommodate the ever increasing client demand, real-time, for specified streaming media. Still further, technology developments in the recently interconnected world has tempted the palate of society for the ability to pull, receive, push, and send multiple types of media in multiple formats using one device. Moreover, content providers need to be able to deliver many different media signals to many different types of devices in their clients' offices, living rooms, and hands. Individuals and corporations also desire to communicate with each other using various different formats and using various different respective devices.

Accordingly, a significant industry has emerged for delivering streaming and static media over the centralized network of the Internet. Content delivery companies are currently delivering a wide range of streaming media, from live horse racing and entertainment to medical telemetry and education, over the Internet, and in video and audio formats. According to one published report from DFC Intelligence, video streaming on the Internet grew 215 percent in 2000 to over 900 million total streams accessed. This includes broadband streams, which made up almost 29 percent of total accesses. This same report also estimates that as much as 15 percent of available stream inventory is now being exploited with in-stream advertising. In another report published by Internet researcher Jupiter Media Metrix, business spending alone on streaming video technology will balloon from one-hundred forty million (US$140M) US dollars in 2000 to nearly three billion (US$3B) US dollars by 2005 as companies turn to electronic interaction in communicating with employees, consumers and other businesses.

Ex. 1018-2003

Still further, the population explosion and increasing number of people transmitting on these systems has severely impacted the available bandwidth for available information. Therefore, the ability to stream media efficiently, using limited bandwidth resources and limited available transmission speeds, is of increased societal importance.

5

Compression/Decompression Algorithms ("CODECS")

In view of the exponential demand for communicating the different types of media, various compression/decompression systems ("CODEC(s)") have been developed over many years, and have
10 in particular become the recent topic of significant research and development. Specific types of CODECS and systems for managing the operation of CODECS with respect to communicating streaming and static media signals have been developed for specific types of media, including for example still-frame images such as graphics and photographs, and streaming media.

15 Image CODECS

Various different types of static media CODECS have been developed, and a wide variety of these CODECS are widely known and used. One specific type of static media that has been the topic of particular attention includes images (though a long series of interrelated image frames such as in
20 video context is generally treated as streaming media due to more complex variables, e.g. size and temporal relationship between frames, that significantly impact appropriate compression/decompression needs). Examples of static media CODECing is therefore herein exemplified by reference to certain specific types of conventional image CODEC technologies and methods.

25 The two most common file formats for graphic images on the world wide web are known as "GIF" and "JPEG" formats, generally considered the respective standards for drawings (e.g. line art) and photographs, and are further described together with other image compression modalities for the purpose of further understanding as follows.

"JPEG" is an acronym for "Joint Photographic Experts Group", and is a graphic image file that
30 complies with ISO standard 10918. Commonly used for photograph compression/decompression, a JPEG file is created by choosing from a range of compression qualities, or, as has also been described, by choosing from one of a suite of compression algorithms. In order to create a JPEG file, or convert

an image from another format to JPEG, the quality of image that is desired must be specified. In general, because the highest quality results in the largest file, a trade-off may then be made, as chosen by the user, between image quality and image size. The JPEG mode of compression generally includes 29 distinct coding processes although a JPEG implementer may not use them all. A JPEG image is typically given a name suffix ".jpg".

"GIF" is an acronym for "Graphics Interchange Format", and is generally considered the de facto standard form of drawing image compression/decompression for Internet communication. GIF formatting uses a compression algorithm known as the LZW algorithm, which was developed by Abraham Lempel, Jacob Ziv, and Terry Welch and made commercially available by Unisys Corporation (though in general such algorithm has been made publicly available without requiring fee-bearing licenses). More specifically, a "LZW" compression algorithm takes each input sequence of bits of a given length (e.g. 12 bits) and creates an entry in a table, sometimes called a "dictionary" or "codebook", for that particular bit pattern. The entry consists of the pattern itself and a shorter code. As input is read, any pattern that has been read before results in the substitution of the shorter code, effectively compressing the total amount of input to something smaller. Earlier approaches, known as LZ77 and LZ78, did not include the look-up table as part of the compressed file. However, the more recent LZW algorithm modality does include the table in the file, and the decoding program that decompresses the file for viewing is able to build the table itself using the algorithm as it processes the encoded input. The GIF format uses the 2D raster data type (associated with display screens using raster lines) and is encoded in binary.

Two versions of GIF formats include GIF 87a, and more recently GIF89a that allows for "animated GIF" file creation, or short sequences of images within a single GIF file that are played in sequence to present movement or change in the image (either in an endless loop or through a progression that reaches an end). GIF89A also allows for, and also for "interlaced GIF", which is a GIF image that arrives and is displayed by the receiver first as a fuzzy outline of an image that is gradually replaced by seven successive waves of bit streams that fill in the missing lines until full resolution is reached. Interlaced GIF allows, for example, a viewer using 14.4 Kbps and 28.8 Kbps modems to observe a briefer wait-time before certain information in a subject image may be processed, such as for example to make decisions (e.g. to click on the image to execute an operation such as a link).

By presenting waves of resolution filling image sequences, interlaced GIF is similar to "Progressive JPEG", which describes an image created using the JPEG suite of compression algorithms

that will "fade in" in successive waves. While the progressive JPEG is often observed to be more appealing way to deliver an image at modem connection speeds, users with faster connections may not likely notice a difference.

"PNG" or "Portable Network Graphics" format has been more recently developed for image compression and that, in time, has been publicized to replace the GIF format for Internet use (though not generally the JPEG format allowing size/quality trade-offs). This format has been developed for public consumption and development. Similar to GIF, PNG is considered a "lossless" compression format, and therefore all image information is restored when a compressed file is decompressed during viewing. However, PNG formatted files are generally intended to be from 10 to 30 percent more compressed than with a GIF format. Further aspects of PNG file formats are provided as follows: (i) color transparency may not be limited to only one color, but the degree of transparency may be controlled ("opacity"); (ii) "interlacing" of images is improved versus standard GIF; (iii) "gamma correction" is enabled, allowing for "tuning" of images in terms of color brightness required by specific display manufacturers; (iv) images can be saved using true color, palette, and gray-scale formats similar to GIF; and (v) "animation" is generally not supported, though PNG is generally considered extensible and therefore software may be layered to provide for such scriptable image animation.

"TIFF" is an acronym for "Tag Image File Format", and is a common format for exchanging raster graphics (or "bitmap") images between application programs, such as for example graphics used for scanner images. A TIFF file is usually given a name suffix of ".tif" or ".tiff", and had generally been developed in the mid-1980's with the support of Adobe Software, Microsoft, and Hewlett-Packard. TIFF files can be in any of several classes, including gray scale, color palette, or RGB full color, the descriptions and differences of which are further developed elsewhere herein this disclosure. TIFF files may also include files with JPEG, LZW, or CCITT Group 4 standard run-length image compression, which are also further described elsewhere herein. As one of the most common graphic image formats, TIFF files are typically used in desktop publishing, faxing, 3-D applications, and medical imaging applications.

Video CODECS

Video compression has been the topic of intense development for various applications, including, for example: pre-recorded video (e.g. "video-on-demand"), teleconferencing, and live video (e.g. broadcasts). "Desk-top" computers, wireless devices, conventional televisions, and high

definition televisions are examples of the different types of receiving devices that an efficient video compression system must serve.

In general, video CODEC algorithms operate on either or both of an individual, frame-by-frame basis, and/or on a "temporal compression" basis wherein each frame is the most common video compression algorithms in conventional use are based on several mathematic principles, including the following: Discrete Cosine Transforms ("DCT"), Wavelet Transforms and Pure Fractals.

"Discrete Cosine Transforms" or "DCT's" are by far the most popular transforms used for image compression applications . In general, DCT is a technique for representing waveform data as a weighted sum of cosines. The DCT is similar to the discrete Fourier transform: it transforms a signal or image from the spatial domain to the frequency domain. The DCT helps separate the image into parts (or spectral sub-bands) of differing importance (with respect to the image's visual quality). Reasons for its popularity include not only good performance in terms of energy compaction for typical images but also the availability of several fast algorithms. DCTs are used in two international image/video compression standards, JPEG and MPEG.

"Wavelet transforms" are generally mathematical algorithms that convert signal data into a set of mathematical expressions that can then be decoded by a destination receiver device, such as for example in a manner similar to Fourier transform. Wavelets have been observed to enhance recovery of weak signals from noise, and therefore images processed in this manner can be enhanced without significant blurring or muddling of details. For this reason, wavelet signal processing has been particularly applied to X-ray and magnetic-resonance images in medical applications. In Internet communications, wavelets have been used to compress images to a greater extent than is generally possible with other conventional methods. In some cases, the wavelet-compressed image can be as small as about 25 percent the size of a similar quality image using the more familiar JPEG format, which is discussed in further detail elsewhere in this disclosure. Thus, for example, a photograph that requires 200Kb and takes a minute to download in JPEG format may require only 50Kb and take only 15 seconds to download in wavelet-compressed format. A wavelet-compressed image file is often given a name suffix ".wif", and either the receiver (e.g. Internet browser on a computer receiver) must support these format specific files, or a plug-in program will be required to read such file.

Fractal image compression is a modern technique of lossy image coding that provides several improvements over existing Fourier series compression schemes. Edge depiction is improved since, when modeled as a step function, edges require a large number of Fourier series terms to properly depict. Other advantages of fractals include fast decoding time and scale independence. Fractal

compression is based on Mandelbrot sets which take advantage of a self similar, scaling dependent, statistical feature of nature (Mandelbrot, 1983). Fractal compression and decompression involves a clustering approach to find regions which show the same characteristics as a sample region independent of rotation and scale. The fractal image compresses images as recursive equations and instructions about how to reproduce them. The equations describe the image in terms of the relationships between its components. The reduction in storage need is due to the fact that fractal compression saves equations and instructions instead of a pixel representation of the image.

"MPEG" is an acronym for Moving Picture Experts Group and has come to be used synonymously with certain evolving video and audio compression standards promulgated therefrom. In general, to use MPEG video files, a personal computer is required with sufficient processor speed, internal memory, and hard disk space to handle and play the typically large MPEG file, usually given the name suffix ".mpg". A specified MPEG viewer or client software that plays MPEG files must be available on the client system, and generally can be downloaded shareware or versions of commercial MPEG players from various sites on the Web. The modes of operation for MPEG formatted media are herein described by reference to these sequentially evolved standards as follows.

More specifically, MPEG-1 standard was designed for coding progressive video generally at a transmission rate of about 1.5Mbps. This was generally designed for the specific application for Video-CD and CD-I media. MPEG-1 audio layer-3 ("MP3") has also evolved from early MPEG work. "MPEG-2" is a standard generally designed for coding interlaced images at transmission rates above 4 Mbps, and was generally intended for use with digital TV broadcast and digital versatile disk. Though it is generally observed that many MPEG-2 players can handle MPEG-1 data as well, the opposite is not generally observed to be true and MPEG-2 encoded video is generally incompatible with MPEG-1 players. Yet another progressive standard, "MPEG-3", has also been proposed for use with high definition television ("HDTV"), though in general MPEG-3 has merged with MPEG-2 which is generally believed to meet the HDTV requirements. Finally, an "MPEG-4" standard has also been most recently developed and is intended to provide a much more ambitious standard to address speech and video synthesis, fractal geometry, and computer visualization, and has further been disclosed to incorporate artificial intelligence in order to reconstruct images.

MPEG-1 and –2 standards define techniques for compressing digital video by factors varying from 25:1 to 50:1. This compression is achieved according to these standards generally using five different compression techniques: (i) discrete cosine transform (DCT), which is a frequency-based transform; (ii) "quantization", which is a technique for losing selective information, e.g. lossy

prediction", wherein some images are predicted from the pictures immediately preceding and following the image.

Further more detailed examples of commercially available video compression technologies include: Microsoft Media Player™ (available from Microsoft Corporation), RealPlayer™ or RealSystem G2™ (commercially available from Real Networks™), Apple's QuickTime™ (commercially available from Sorenson™); and "VDO". The Microsoft Media Player™ is generally believed to apply the MPEG standard of CODEC for compression/decompression, whereas the others have been alleged to use proprietary types of CODECS. Standard compression algorithms, such as MPEG4, have made their way into the hands of developers who are building embedded systems for enterprise streaming, security, and the like.

One example of a more recent effort to provide streaming video solutions over Wireless and IP networks has been publicized by a company named Emblaze Systems (LSE:BLZ). This company has disclosed certain technology that is intended for encoding and playback of live and on-demand video messages and content on any platform: PC's, PDA's, Video cell phones and Interactive TV. Emblaze Systems is believed to be formerly GEO Interactive Media Group. The following Published International Patent Applications disclose certain streaming media compression technologies that is believed to be related to Emblaze Systems to the extent that GEO Interactive Media Group is named as "Assignee": WO9731445 to Carmel et al.; and WO9910836 to Carmel. The disclosures of these references are herein incorporated in their entirety by reference thereto.

Another company that has published CODEC technology that is intended to improve communication of streaming media for wireless applications is Packetvideo™ Corporation, more specifically intending to communicate streaming video to cellular phones. In addition, they are believed to be promoting CODEC technology that is intended to track temporal scalability and signal error resistance in order to protect video and audio streams from the hazards of the wireless environment. U.S. Patent No. 6,167,092 to Lengwehasatit discloses further examples of certain streaming media compression/decompression technology that are believed to be associated with Packetvideo as the named "Assignee" on the face of this Patent reference. The disclosure of this patent reference is herein incorporated in its entirety by reference thereto.

Another prior reference discloses CODEC technology that is intended to provide a cost effective, continuously adaptive digital video system and method for compressing color video data for moving images. The method involves capturing an analog video frame and digitizing the image into a preferred source input format for compression using a combination of unique lossy and lossless digital

Ex. 1018-2009

Another prior reference discloses CODEC technology that is intended to provide a cost effective, continuously adaptive digital video system and method for compressing color video data for moving images. The method involves capturing an analog video frame and digitizing the image into a preferred source input format for compression using a combination of unique lossy and lossless digital compression techniques including sub-band coding, wavelet transforms, motion detection, run length coding and variable length coding. The system includes encoder and decoder (CODEC) sections, generally disclosed to use a "Huffman" encoder, for compression and decompression of visual images to provide high compression that is intended to provide good to excellent video quality. The compressed video data provides a base video layer and additional layers of video data that are multiplexed with compressed digital audio to provide a data stream that can be packetized for distribution over inter or intranets, including wireless networks over local or wide areas. The CODEC system disclosed is intended to continuously adjust the compression of the digital images frame by frame in response to comparing the available bandwidth on the data channel to the available bandwidth on the channel for the previous frame to provide an output data stream commensurate with the available bandwidth of the network transmission channel and with the receiver resource capabilities of the client users. The compression may be further adjusted by adjustment of the frame rate of the output data stream.

Further more detailed examples of CODEC systems that are intended for use at least in part for streaming video communication are disclosed in the following U.S. Patent Nos.: 6,081,295 to Adolph et al.; 6,091,777 to Guetz et al.; 6,130,911 to Lei; 6,173,069 B1 to Daly et al.; 6,263,020 B1 to Gardos et al.; 6,272,177 to Murakami et al.; and 6,272,180 B1 to Lei. The disclosures of these references are herein incorporated in their entirety by reference thereto.

Most if not all prior streaming video compression methodologies look to the extremely complex mathematical tools within such CODECS, and subtle changes to them, to carry "one size fits all" video over public and private networks of all types, from ultra-low bandwidth networks such as that found in wireless networks, to satellite communications to ultra-high speed fiber optic installations. Among the various conventional methods of compression, there are generally user-definable parameters, including tradeoffs between image size, frame rate, color depth, contrast, brightness, perceived frame quality, buffer length, etc. Further, within the algorithms themselves there are numerous non-user definable qualities and weighted calculations. It is up to the developers to set these one time for one "general" interest, and then package and ship the product.

However, while the video streaming market continues to grow rapidly, the world has not chosen one standard for compression as no one algorithm is ideal for all video sources, destinations, or transmission modalities. While a first CODEC may be best for one type of signal, or for a first portion of a signal (e.g. frame or scene comprising a series of frames), another second CODEC may be best for another type of signal, or even another second portion of the same signal. Still further, one CODEC may be best suited for compression/decompression of a particular streaming signal among send, receive, and transmission devices in a communications network; another second CODEC may be better suited than the first for the same streaming media signal but for another set of communication device parameters. For example, some video streams may deliver color to handheld devices while other video streams can take advantage of the loss of pixels in a black and white transmission to a cellular phone to increase frame rate. Required sound quality, frame rates, clarity, and buffering tolerance all decidedly impact the compression algorithm of choice for optimized video and audio delivery across multiple platforms.

In fact, certain communication device parameters may be sufficiently transient during the streaming media transmission such that an initially appropriate CODEC for an initial set of parameters may be rendered less efficient than another CODEC due to changes in those parameters during the same streamed signal transmission. Examples of such transient parameters include, without limitation: available band width in the data transmission channel, available memory or processing power in either the send or receiving devices, and dedicated display resolution/window in the receiving device (e.g. minimizing windows on a screen). These problems are compounded exponentially by a vast number of iterations of different combinations of such factors that may differentiate one CODEC from another as being most efficient for compression, decompression, and delivery of a specific streaming media signal along a particular communications device system.

As CODEC systems are "format-specific", source and destination devices must be "pre-configured" to communicate media signals between each other according to common, specific compression/decompression modalities, else transcoders must be used. However, even if conventional transcoders are used, constraints in the communication system (e.g. source, transmission channel, destination device) are not generally considered and the communication may be significantly faulty. For the purpose of further illustration, Figures 1A and 1B show two different schematic representations of conventional methods for communicating media between source 110 -120 and destination devices 130 -140. These illustrations specifically exemplify streaming video communication, though other media forms may be represented by similar systems.

Ex. 1018-2011

It has been observed that CODEC algorithms can generally be modified for a specific application and then perform better than a similar unmodified set over that limited example. However, this generally must be done either for a series of frames, or ideally, for each individual frame. Some DCT based algorithms have as many as two billion mathematical operations occurring for each frame at higher resolutions and lower perceived quality. This is entirely too much math for average machines, even commercial servers, to perform thirty to sixty times in a single second. This is the reason for the advent of the dedicated compression board or ASIC.

Audio CODECS

In addition to society's recent interests in improving video compression, audio compression has likewise been the topic of significant efforts also for various live or pre-recorded applications, including audio broadcast, music, transmission synchronized with video, live interactive voice (e.g. telephone). Any and all of these audio compression applications must be compatible with a wide range of client-side receiver/players, such as on a multitude of handheld or desk-top devices having widely varied capabilities and operating parameters.

Conventional audio CODECS generally comprise several different types, a few of which are herein briefly summarized for the purpose of illustration.

"Code Excited Linear Prediction" or "CELP" is a type of speech compression method using waveform CODECS that use "Analysis-by-Synthesis" or "AbS" within the excitation-filter framework for waveform matching of a target signal. CELP-based CODECS have recently evolved as the prevailing technique for high quality speech compression, and has been published to transmit compressed speech of toll-quality at data rates nearing as low as about 6 kbps. However, at least one publication discloses that the quality of CELP coded speech is reduced significantly for bit rates at or below 4 kbps.

"Vocoders" are speech CODECS that are not based on the waveform coding scheme, but rather use a quantized parametric description of the target input speech to synthesize the reconstructed output speech. Vocoders have been disclosed to deliver better speech quality at low bit-rates, such as about 4 kbps, and have been developed for such applications. Low bit rate vocoders use the periodic characteristics of voiced speech and the "noise-like" characteristics of stationary unvoiced speech for speech analysis, coding and synthesis. Some early versions of vocoders (e.g. federal standard 1015 LPC-10, use a time-domain analysis and synthesis method. However, most of the more recent versions,

Ex. 1018-2012

which at least one publication labels "harmonic coders", utilize a harmonic spectral model for voiced speech segments.

Notwithstanding the previous description of certain specific speech compression techniques, a vast number of speech CODECs and standards have been developed by industry and managed by industry and nonprofit groups. Examples of such groups include without limitation the following, and their standards are often used as reference types of CODECS: the European Telecommunications Standards Institute ("ETSI"); the Institute of Electrical and Electronics Engineers ("IEEE"); and the International Telecommunication Union Telecommunications Standards Sector ("ITU-T"), formerly the "CCITT".

One more recently disclosed method and apparatus for hybrid coding of speech, specified at 4 Kbps, encodes sppech for communication to a decoder for reproduction of the speech where the speech signal is classified into three types: (i) steady state voiced or "harmonic"; (ii) stationary unvoiced; and (iii) "transitory" or "transition" speech. A particular type of coding scheme is used for each class. Harmonic coding is used for steady state voiced speech, "noise-like" coding is used for stationary unvoiced speech, and a special coding mode is used for transition speech, designed to capture the location, the structure, and the strength of the local time events that characterize the transition portions of the speech. The compression schemes are intended to be applied to the speech signal or to the LP residual signal.

Another recently disclosed method and arrangement for adding a new speech encoding method to an existing telecommunication system is also summarized as follows. A CODEC is introduced into a speech transmitting transceiver of a digital telecommunications system in order to use a "new" CODEC and an "old" CODEC in parallel in the system. A CODEC is selected by implementing a handshaking procedure between transceivers where a speech encoding method is implemented in all transceivers and previously used in the telecommunications system concerned. The handshaking is used at the beginning of each connection. At the beginning of a phone call and after handover, the method checks whether both parties can also use the new speech encoding. The handshaking messages have been selected so that their effect on the quality of speech is minimal, and yet so that the probability of identifying the messages is maximal.

Still another relatively recent reference discloses a tunable perceptual weighting filter for tandem CODECS intended for use in speech compression. Specific filter parameters are tuned to provide improved perfromance in tandeming contexts. More specifically, the parameters used are 10th

Ex. 1018-2013

order LPC predictor coefficients. This system is specified to use "Low-Delay Excited Linear Predictive" CODECS, or "LD-CELP".

Further more detailed examples of streaming audio communications systems using CODECS such as according to the examples just described are provided in the following US Patent references: 6,144,935 to Chen et al.; 6,161,085 to Haavisto et al.; and 6,233,550 to Gersho. The disclosures of these references are herein incorporated in their entirety by reference thereto.

Artificial Intelligence ("AI") and Neural Networks with CODECS

Various systems and methods have been recently disclosed that are intended to integrate artificial intelligence ("AI") or neural networks with the compression and decompression of streaming media signals.

The terms "artificial intelligence" are herein intended to mean the simulation of human intelligence processes by computer systems, including learning (the acquisition of information and rules for using the information), reasoning (using the rules to reach approximate or definite conclusions), and self-correction. Particular applications of AI include "expert systems", which are computer programs that simulate judgment and behavior of a human or organization that has expert knowledge and experience in a particular field. Typically, expert systems contain a knowledge base to each particular situation that is described to the program, and can be enhanced with additions to the knowledge base or to the set of rules.

The terms "neural network" are herein intended to mean a system of programs and data structures that approximates the operation of the human brain, usually involving a large number of processors operating in parallel, each with its own small sphere of knowledge and access to data in its local memory. Typically, a neural network is initially trained or fed large amounts of data and rules about data relationships, after which a program can tell the network how to behave in response to an external stimulus (e.g. input information). In making determinations, neural networks use several principles, including without limitation gradient-based training and fuzzy logic. Neural networks may be further described in terms of knowledge layers, generally with more complex networks having deeper layers. In "feedforward" neural network systems, learned relationships about data can "feed forward" to higher layers of knowledge. Neural networks can also learn temporal concepts and have been widely used in signal processing and time series analysis. Other published applications of neural

networks include oil exploration data analysis, weather prediction, the interpretation of nucleotide sequences in biology labs, and the exploration of models of thinking and consciousness.

The terms "fuzzy logic" are herein intended to mean an approach to computing based upon "degrees of truth" rather than "Boolean logic" which operates within only a true/false (or "binary", as 1 or 0) domain. Fuzzy logic was first advanced by Dr. Lotfi Zadeh of the University of California at Berkeley in the 1960's in relation to work on a problem of computer understanding of natural language, which is not easily translated into absolute Boolean logic terms. Fuzzy logic often does include the cases of 0 and 1 as extreme cases of truth, but also includes the various states of truth in between (e.g. a determination of that the state of being is at some threshold, such as 0.98, may assists in making a decision to assign a 1 with an acceptably low occurrence of error in an operation).

One example of a previously disclosed streaming media compression/decompression system intended to use with artificial intelligence through a neural network uses a Radon transform in order to compress data such as video data. Several previously disclosed AI and/or neural network systems are intended to use AI and/or neural networks for the purpose of error correction during use of certain specified lossless compression CODECS. For example, a learning system is employed to determine a difference between what was received by a receiver after compression and transmission and what is predicted to have been received at the transmission end. That difference is processed as learning to modify the tuning of the CODEC for an additional transmission.

Another example of a disclosed method and device is intended to extrapolate past signal-history data for insertion into missing data segments in order to conceal digital speech frame errors. The extrapolation method uses past-signal history that is stored in a buffer. The method is implemented with a device that is disclosed to utilize a finite-impulse response ("FIR"), multi-layer, feed-forward, artificial neural network that is trained by back-propagation for one-step extrapolation of speech compression algorithm ("SCA") parameters. Once a speech connection has been established, the speech compression algorithm device begins sending encoded speech frames. As the speech frames are received, they are decoded and converted back into speech signal voltages. During the normal decoding process, pre-processing of the required SCA parameters will occur and the results stored in the past-history buffer. If a speech frame is detected to be lost or in error, then extrapolation modules are executed and replacement SCA parameters are generated and sent as the parameters required by the SCA. In this way, the information transfer to the SCA is intended to be transparent, and the SCA processing continues as usual. This disclosure alleges that the listener will not normally notice that a

speech frame has been lost because of the smooth transition between the last-received, lost, and next-received speech frames.

Further more detailed examples of systems that are intended to use artificial intelligence and/or neural networks in systems for media compression and/or decompression, generally relating to media type-specific CODEC methods (e.g. speech, video), are variously disclosed in the following U.S. Patent References: 5,005,206 to Naillon et al.; 5,041,916 to Yoshida et al.; 5,184,218 to Gerdes; 5,369,503 to Burel et al.; 5,598,354 to Fang et al.; 5,692,098 to Kurdziel; 5,812,700 to Fang et al.; 5,872,864 to Imade et al.; 5,907,822 to Prieto, Jr.; and 6,216,267 to Mitchell. Still further examples are provided in the following Published International Patent Applications: WO 01/54285 to Rising; EPO 0372608 A1 to Naillon et al.. The disclosures of all these references cited in this paragraph are herein incorporated in their entirety by reference thereto.

Other disclosures of CODEC systems using feedback or other systems for operating CODECS for use in processing a variety of streaming media signals, but that are not believed to specifically use the labels "AI" or "neural networks", are disclosed in the following U.S. Patent Nos.: 6,072,825 to Betts et al.; 6,182,034 B1 to Malvar; 6,253,165 B1 to Malvar; 6,256,608 B1 to Malvar. The disclosures of these references are herein incorporated in their entirety by reference thereto.

Notwithstanding the significant advancements in CODEC algorithms themselves, and despite prior intended uses of AI and other feedback systems for operating CODECS in order to improve compression efficiencies in communication, there is still a need for significant improvement in the ability to efficiently provide a wide variety of streaming media signals to a wide variety of destination receiver devices over a wide variety of transmission channels with varied bandwidths and communication protocols.

There is still a need to incorporate AI and/or neural networks to apply an appropriate CODEC for communication of a streaming media signal based upon a variety of parameters, including without limitation one or more of the following: (a) the automated choosing of an appropriately optimized CODEC from a library of available CODECS of different types and operation, including in particular based upon an intelligent knowledge of the chosen CODEC's operation compared to the other CODEC's operation and/or against a standard, (b) a pre-trained and/or iteratively learned knowledge of the particular CODEC's operation within a given set of operating parameters representative of the existing situation; and (c) a tuning of the appropriate CODEC based upon an intelligent knowledge of

its operation with respect to either or both of the existing situation or a test situation with reference parameters.

In particular, there is still a need for such an intelligent CODEC system that bases an applied CODEC upon an existing situation that is defined by one or more of the following: parameters of the streaming media signal itself; parameters of the transmission channel capabilities and constraints; and parameters of the receiver device capabilities and constraints.

Still further, there is also still a need for such an intelligent CODEC system that operates based upon an intelligent knowledge with respect to all of these operations and situational parameters in order to optimize the appropriate compression, transmission, decompression, and playing of the subject streaming media signal.

Conventional Transcoders for Streaming Media

Also of recent interest in the field of streaming media communication is providing intercommunication between the wide array of "format-specific" encoding systems in present use. An existing field of various different format-specific systems and pre-encoded content has created a widely fragmented ability to process encoded content, resulting in a significant quagmire of compatibility issues between content providers and client users. If one client desires to see or hear streaming content from a particular source and that content must be put through a CODEC for compression, a compatible CODEC must be used on the client side for decompression to enjoy the signal. Unfortunately, source content is often married to only a few, and often only one, specific CODEC schemes. Therefore, if a client requests such encoded content (or if the source desires to push the encoded content to a particular client), one of two criteria must be met: (1) the client must download or otherwise possess the format-specified CODEC (decoder); or (2) the source media must be put through a "transcoder" in order to decode the source media from the first format into a second format that is compatible with the client's device/system. The term "transcoder" is herein intended to mean a system that converts a media signal from one encoded (i.e. compressed) format to another.

Various techniques for transcoding one media format into another have been previously disclosed. Figure 1C shows one illustrative example of the general process that is characteristic of many known transcoding techniques. More specifically, a request 159 is first received from a particular type of device or player for content that exists in an initial, uncompatible format. According to the specific example shown in Figure 1C, a request 159 from a Microsoft Media™ Player for Real™ Video Content is received. As the content is specifically requested, the content is decoded from the

initial format (e.g. Real-encoded format), and is then "re-encoded" into the appropriate format for the requesting player (e.g. Microsoft Media™ format). This re-encoded media is then served to the requesting client for decoding within the resident system of that player.

This conventional system has significant scalability limitations, in that simultaneous feeds on multiple channels for multiple clients must be supported by an equal number of transcoders. For example, Figure 1D shows a schematic implementation of the conventional transcoding technique just described as it manages four simultaneous stream requests from four Microsoft Media Players, wherein the requested content is initially encoded in Real™ format. The system architecture necessary to support the four encoders 151 - 154 and four decoders 155 - 158 requires significant computing resources. For example, it is believed that each encoder 151 - 154 provided in the example requires a computer having a 600 MHz (e.g. Pentium™ III) having 128 Mbytes of RAM available, or dual 400 MHz processors (e.g. Pentium II) with 256 Mb available RAM. It is further believed that each decoder 155 – 158 needs a 233 MHz machine (e.g. Pentium™ II) having 64 Mb of available RAM. So, four such streams requires the equivalent of a Quad 900 Xeon (available from Compaq, Hewlett Packard, Dell and IBM, estimated to cost at the time of this disclosure about $9K retail). This is for four simultaneous streams – society is presently demanding thousands upon thousands of simultaneous streams.

There is still a need for a transcoder system that efficiently converts multiple format-specifically encoded streaming media signals into multiple other formats using minimal computing resources and in a cost-efficient manner.

Parameters Affecting Media Communication

For the purpose of further illustrating the many variables that may impact the choice of an appropriate CODEC in order to communicate a particular streaming media signal to a desired target, the following is a brief summary of various different types of streaming video formats and processing systems. It is believed that these different systems each generally require different types of compression modalities (e.g. CODECS) in order to optimize communication and playing of streaming media signals in view of available transmission speeds and bandwidth, as well as receiver processing parameters.

Although certain specific types of communications formats and systems are further herein described in detail, the following Table 1 provides a summary of a significant cross-section of the

various different communications systems and transmission carriers currently available or disclosed in view of available speed or bandwidth.

TABLE 1: Data Rates of Various Communications Carrier systems

Technology	Speed	Physical Medium	Application
GSM mobile telephone service	9.6 to 14.4 Kbps	RF in space (wireless)	Mobile telephone for business and personal use
High-Speed Circuit-Switched Data service (HSCSD)	Up to 56 Kbps	RF in space (wireless)	Mobile telephone for business and personal use
Regular telephone service (POTS)	Up to 53 Kbps	Twisted pair	Home and small business access
Dedicated 56Kbps on Frame Relay	56 Kbps	Various	Business e-mail with fairly large file attachments
DS0	64 Kbps	All	The base signal on a channel in the set of Digital Signal levels
General Packet Radio System (GPRS)	56 to 114 Kbps	RF in space (wireless)	Mobile telephone for business and personal use
ISDN	BRI: 64 Kbps to 128 Kbps PRI: 23 (T-1) or 30 (E1) assignable 64-Kbps channels plus control channel; up to 1.544 Mbps (T-1) or 2.048 (E1)	BRI: Twisted-pair PRI: T-1 or E1 line	BRI: Faster home and small business access PRI: Medium and large enterprise access
IDSL	128 Kbps	Twisted-pair	Faster home and small business access
AppleTalk	230.4 Kbps	Twisted pair	Local area network for Apple devices; several networks can be bridged; non-Apple devices can also be connected
Enhanced Data GSM Environment (EDGE)	384 Kbps	RF in space (wireless)	Mobile telephone for business and personal use
Satellite	400 Kbps (DirecPC and others)	RF in space (wireless)	Faster home and small enterprise access
Frame relay	56 Kbps to 1.544 Mbps	Twisted-pair or coaxial cable	Large company backbone for LANs to ISP ISP to Internet infrastructure
DS1/T-1	1.544 Mbps	Twisted-pair, coaxial cable, or optical fiber	Large company to ISP ISP to Internet infrastructure
Universal Mobile Telecommunications Service (UMTS)	Up to 2 Mbps	RF in space (wireless)	Mobile telephone for business and personal use (available in 2002 or later)
E-carrier	2.048 Mbps	Twisted-pair, coaxial cable, or optical fiber	32-channel European equivalent of T-1
T-1C (DS1C)	3.152 Mbps	Twisted-pair, coaxial cable, or optical fiber	Large company to ISP ISP to Internet infrastructure
IBM Token Ring/802.5	4 Mbps (also 16 Mbps)	Twisted-pair, coaxial cable, or optical fiber	Second most commonly-used local area network after Ethernet
DS2/T-2	6.312 Mbps	Twisted-pair, coaxial cable, or optical fiber	Large company to ISP ISP to Internet infrastructure
Digital Subscriber Line (DSL)	512 Kbps to 8 Mbps	Twisted-pair (used as a digital, broadband medium)	Home, small business, and enterprise access using existing copper lines
E-2	8.448 Mbps	Twisted-pair, coaxial cable, or optical fiber	Carries four multiplexed E-1 signals
Cable modem	512 Kbps to 52 Mbps (see "Key and explanation" below)	Coaxial cable (usually uses Ethernet); in some systems, telephone used for upstream requests	Home, business, school access
Ethernet	10 Mbps	10BASE-T (twisted-pair); 10BASE-2 or -5 (coaxial cable); 10BASE-F (optical fiber)	Most popular business local area network (LAN)
IBM Token Ring/802.5	16 Mbps (also 4 Mbps)	Twisted-pair, coaxial cable, or optical fiber	Second most commonly-used local area network after Ethernet
E-3	34.368 Mbps	Twisted-pair or optical fiber	Carries 16 E-1 signals
DS3/T-3	44.736 Mbps	Coaxial cable	ISP to Internet infrastructure Smaller links within Internet infrastructure

OC-1	51.84 Mbps	Optical fiber	ISP to Internet infrastructure Smaller links within Internet infrastructure
High-Speed Serial Interface (HSSI)	Up to 53 Mbps	HSSI cable	Between router hardware and WAN lines Short-range (50 feet) interconnection between slower LAN devices and faster WAN lines
Fast Ethernet	100 Mbps	100BASE-T (twisted pair); 100BASE-T (twisted pair); 100BASE-T(optical fiber)	Workstations with 10 Mbps Ethernet cards can plug into a Fast Ethernet LAN
Fiber Distributed-Data Interface (FDDI)	100 Mbps	Optical fiber	Large, wide-range LAN usually in a large company or a larger ISP
T-3D (DS3D)	135 Mbps	Optical fiber	ISP to Internet infrastructure Smaller links within Internet infrastructure
E-4	139.264 Mbps	Optical fiber	Carries 4 E3 channels Up to 1,920 simultaneous voice conversations
OC-3/SDH	155.52 Mbps	Optical fiber	Large company backbone Internet backbone
E-5	565.148 Mbps	Optical fiber	Carries 4 E4 channels Up to 7,680 simultaneous voice conversations
OC-12/STM-4	622.08 Mbps	Optical fiber	Internet backbone
Gigabit Ethernet	1 Gbps	Optical fiber (and "copper" up to 100 meters)	Workstations/networks with 10/100 Mbps Ethernet plug into Gigabit Ethernet switches
OC-24	1.244 Gbps	Optical fiber	Internet backbone
SciNet	2.325 Gbps (15 OC-3 lines)	Optical fiber	Part of the vBNS backbone
OC-48/STM-16	2.488 Gbps	Optical fiber	Internet backbone
OC-192/STM-64	10 Gbps	Optical fiber	Backbone
OC-256	13.271 Gbps	Optical fiber	Backbone

Comments & Key for Table:

(i)The term "Kbps" as the abbreviation for "thousands of bits per second." In international English outside the U.S., the equivalent usage is "kbits s^{-1}" or "kbits/s".
(ii) Engineers use *data rate* rather than *speed*, but speed (as in "Why isn't my Web page getting here faster?") seems more meaningful for the less technically inclined.
(iii) Relative to data transmission, a related term, bandwidth or "capacity," means how wide the pipe is and how quickly the bits can be sent down the channels in the pipe. These "speeds" are aggregate speeds. That is, the data on the multiple signal channels within the carrier is usually allocated by channel for different uses or among different users.

Key: (i) "T" = T-carrier system in U.S., Canada, and Japan....(ii) "DS"= digital signal (that travels on the T-carrier or E-carrier)...(iii) "E" = Equivalent of "T" that uses all 8 bits per channel; used in countries other than U.S. Canada, and Japan....(iv) "OC" = optical carrier (Synchronous Optical Network) "STM" = Synchronous Transport Modules (see Synchronous Digital Heirarchy). (v) Only the most common technologies are shown. (vi) "Physical medium" is stated generally and doesn't specify the classes or numbers of pairs of twisted pair or whether optical fiber is single-mode or multimode. (vii) The effective distance of a technology is not shown. (viii) There are published standards for many of these technologies.

Cable modem note: The upper limit of 52 Mbps on a cable is to an ISP, not currently to an individual PC. Most of today's PCs are limited to an internal design that can accommodate no more than 10 Mbps (although the PCI bus itself carries data at a faster speed). The 52 Mbps cable channel is subdivided among individual users. Obviously, the faster the channel, the fewer channels an ISP will require and the lower the cost to support an individual user.

Internet Carrier Systems

Communication of streaming video via the Internet may take place over a variety of transmission modalities, including for example digital subscriber lines ("DSL"), "T1" lines, cable modem, plain old telephone service ("POTS") dial-up modem, and wireless carriers. While a description of the many different wireless transmission modalities is treated separately herein, a

summary of various of these other transmission modes is herein provided immediately below for the purpose of further illustration as follows.

The terms "POTS" or "plain old telephone service", or "dial-up", as applied to communications transmission channels, are herein interchangeably used. These terms are intended to mean "narrow-band" communication that generally connects end users in homes or small businesses to a telephone company office over copper wires that are wound around each other, or "twisted pair". Traditional phone service was created to let you exchange voice information with other phone users via an analog signal that represents an acoustic analog signal converted into an electrical equivalent in terms of volume (signal amplitude) and pitch (frequency of wave change). Since the telephone company's signaling is already set up for this analog wave transmission, it's easier for it to use that as the way to get information back and forth between your telephone and the telephone company. Therefore, dial-up modems are used to demodulate the analog signal and turn its values into the string of 0 and 1 values that is called digital information. Because analog transmission only uses a small portion of the available amount of information that could be transmitted over copper wires, the maximum amount of data that you can receive using ordinary modems is about 56 Kbps. The ability of your computer to receive information is constrained by the fact that the telephone company filters information that arrives as digital data, puts it into analog form for your telephone line, and requires your modem to change it back into digital. In other words, the analog transmission between your home or business and the phone company is a bandwidth bottleneck.

With "ISDN", or "Internet subscriber digital network", which some consider to be a limited precursor to DSL, incoming data rates up to about 128 Kbps may be achieved for some end user clients.

A "DSL" or "digital subscriber line" is generally defined as a "broadband" transmission carrier for communicating high-bandwidth communication over ordinary copper telephone lines. Many different types of DSL services have been disclosed, having generally varied data rates and intended applications. Though further discussion is herein provided about certain of these DSL types, the following Table 2 provides a summary of information for certain of these DSL types for the purpose of further developing an overview understanding:

TABLE 2: Types of known DSL services.

DSL Type	Description	Data Rate Downstream; Upstream	Distance Limit	Application
IDSL	ISDN Digital Subscriber Line	128 Kbps	18,000 feet on 24 gauge wire	Similar to the ISDN BRI service but data only (no voice on the same line)
CDSL	Consumer DSL from Rockwell	1 Mbps downstream; less upstream	18,000 feet on 24 gauge wire	Splitterless home and small business service; similar to DSL Lite
DSL Lite (same as G.Lite)	"Splitterless" DSL without the "truck roll"	From 1.544 Mbps to 6 Mbps downstream, depending on the subscribed service	18,000 feet on 24 gauge wire	The standard ADSL; sacrifices speed for not having to install a splitter at the user's home or business
G.Lite (same as DSL Lite)	"Splitterless" DSL without the "truck roll"	From 1.544 Mbps to 6 Mbps , depending on the subscribed service	18,000 feet on 24 gauge wire	The standard ADSL; sacrifices speed for not having to install a splitter at the user's home or business
HDSL	High bit-rate Digital Subscriber Line	1.544 Mbps duplex on two twisted-pair lines; 2.048 Mbps duplex on three twisted-pair lines	12,000 feet on 24 gauge wire	T1/E1 service between server and phone company or within a company; WAN, LAN, server access
SDSL	Symmetric DSL	1.544 Mbps duplex (U.S. and Canada); 2.048 Mbps (Europe) on a single duplex line downstream and upstream	12,000 feet on 24 gauge wire	Same as for HDSL but requiring only one line of twisted-pair
ADSL	Asymmetric Digital Subscriber Line	1.544 to 6.1 Mbps downstream; 16 to 640 Kbps upstream	1.544 Mbps at 18,000 feet; 2.048 Mbps at 16,000 feet; 6.312 Mpbs at 12,000 feet; 8.448 Mbps at 9,000 feet	Used for Internet and Web access, motion video, video on demand, remote LAN access
RADSL	Rate-Adaptive DSL from Westell	Adapted to the line, 640 Kbps to 2.2 Mbps downstream; 272 Kbps to 1.088 Mbps upstream	Not provided	Similar to ADSL
UDSL	Unidirectional DSL proposed by a company in Europe	Not known	Not known	Similar to HDSL
VDSL	Very high Digital Subscriber Line	12.9 to 52.8 Mbps downstream; 1.5 to 2.3 Mbps upstream; 1.6 Mbps to 2.3 Mbps downstream	4,500 feet at 12.96 Mbps; 3,000 feet at 25.82 Mbps; 1,000 feet at 51.84 Mbps	ATM networks; Fiber to the Neighborhood

Typically published data rates for DSL service, which may vary depending upon distance from the central office of the offering service company, includes rates up to 6.1 Mbps (theoretically published at 8.448 Mbps), which is believed to enable continuous transmission of motion video, audio, and 3-D effects. More typical individual connections provide from 512 Kbps to 1.544 Mbps downstream and about 128 Kbps upstream. A DSL line can carry both data and voice signals and the data part of the line is continuously connected. DSL has been anticipated in some publications to replace ISDN in many areas and to compete with cable modem for multimedia communication to homes and businesses. DSL operates purely within the digital domain and does not require change into analog form and back. Digital data is transmitted to destination computers directly as digital data and this allows the phone company to use a much wider bandwidth for forward transmission. Meanwhile, if

a client user chooses, the signal can be separated so that some of the bandwidth is used to transmit an analog signal so that a telephone and computer may be used on the same line and at the same time.

Most DSL technologies require that a signal splitter be installed at a home or business, requiring the expense of a phone company visit and installation. However, it is possible to manage the splitting remotely from the central office. This is known as splitterless DSL, "DSL Lite," G.Lite, or Universal ADSL (further defined below) and has recently been made a standard. Several modulation technologies are used by various kinds of DSL, although these are being standardized by the International Telecommunication Union (ITU). Different DSL modem makers are using either Discrete Multitone Technology (DMT) or Carrierless Amplitude Modulation (CAP). A third technology, known as Multiple Virtual Line (MVL), is another possibility.

A variety of parameters of DSL operation are variable and affect the effective data rates that can be achieved. DSL modems generally follow the data rate multiples established by North American and European standards. In general, the maximum range for DSL without a repeater is 5.5 km (18,000 feet). As distance decreases toward the telephone company office, the data rate increases. Another factor is the gauge of the copper wire. The heavier 24 gauge wire carries the same data rate farther than 26 gauge wire. For destination devices beyond the 5.5 kilometer range, DSL may still be provided, though only generally if the respective phone company provider has extended the local loop with optical fiber cable.

To interconnect multiple DSL users to a high-speed network as a "backbone", the telephone company uses a Digital Subscriber Line Access Multiplexer ("DSLAM"). Typically, the DSLAM connects to an asynchronous transfer mode ("ATM") network that can aggregate data transmission at gigabit data rates. At the other end of each transmission, a DSLAM demultiplexes the signals and forwards them to appropriate individual DSL connections.

"ADSL" or "Asymmetric Digital Subscriber Line" is the form of DSL that will become most familiar to home and small business users. ADSL is called "asymmetric" because most of its two-way or "duplex" bandwidth is devoted to the downstream direction, sending data to the user. Only a small portion of bandwidth is available for upstream or user-interaction messages. However, most Internet and especially graphics- or multi-media intensive Web data need lots of downstream bandwidth, but user requests and responses are small and require little upstream bandwidth. Using ADSL, up to 6.1 megabits per second of data can be sent downstream and up to 640 Kbps upstream. The high downstream bandwidth means that a telephone line may carry motion video, audio, and 3-D images to destination computers or television displays. In addition, a small portion of the downstream bandwidth

can be devoted to voice rather data, and phone conversations may be carried without requiring a separate line. Unlike a similar service over "cable" television lines, ADSL does not compete for bandwidth with neighbors in a given area. In many cases, your existing telephone lines will work with ADSL. In some areas, they may need upgrading.

"CDSL" or "Consumer DSL" is a trademarked version of DSL, to be made available by Rockwell Corporation, that is somewhat slower than ADSL (1 Mbps downstream, generally predicted to be lower upstream) but has the advantage that a "splitter" does not need to be installed at the user's end. Hardware may be required to carry CDSL by local phone companies to homes or businesses. CDSL uses its own carrier technology rather than DMT or CAP ADSL technology.

Various companies have worked with telephone companies in developing a standard and easier installation version of ADSL, called "G.Lite", that is believed to be under deployment at the time of this disclosure. "G.Lite" or "DSL Lite" (also known as "splitterless ADSL", and "Universal ADSL") is believed to be essentially a slower ADSL that doesn't require splitting of the line at the user end but manages to split it for the user remotely at the telephone company, which is believed to lower costs. G.Lite, officially ITU-T standard G-992.2, is published to provide a data rate from 1.544 Mbps to 6 Mpbs downstream and from about 128 Kbps to about 384 Kbps upstream. At least one publication has predicted G.Lite to become the most widely installed form of DSL.

"HDSL" or "High bit-rate DSL" is believed to be the earliest variation of DSL to be widely used for wideband digital transmission within a corporate site and between the telephone company and a customer. The main characteristic of HDSL is that it is symmetrical: an equal amount of bandwidth is available in both directions. For this reason, the maximum data rate is generally lower than for ADSL. HDSL can carry as much on a single wire of twisted-pair as can be carried on a T1 line in North America or an E1 line in Europe (up to about 2.32 Mbps).

"IDSL" or "ISDN DSL" is somewhat of a misnomer since it's really closer to ISDN data rates and service at about 128 Kbps than compared with the much higher rates generally associated with ADSL.

"RADSL" or "Rate-Adaptive DSL" is an ADSL technology to be made available from Westell company in which software is able to determine the rate at which signals can be transmitted on a given customer phone line and adjust the delivery rate accordingly. Westell's "FlexCap2™" version system uses RADSL to deliver from about 640 Kbps to about 2.2 Mbps downstream and from about 272 Kbps to about 1.088 Mbps upstream over an existing line.

"SDSL" or "Symmetric DSL" is similar to HDSL with a single twisted-pair line, carrying about 1.544 Mbps (U.S. and Canada) or about 2.048 Mbps (Europe) each direction on a duplex line. It's symmetric because the data rate is the same in both directions.

"UDSL" or "Unidirectional DSL" is a proposal from a European company, and is generally believed to provide a unidirectional version of HDSL.

"VDSL" or "Very high data rate DSL" is believed to be a technology under development that promises much higher data rates over relatively short distances, for example between about 51 and about 55 Mbps over lines up to about 1,000 feet or about 300 meters in length. At least one publication has predicted that VDSL may emerge somewhat after ADSL is widely deployed and co-exist with it. The transmission technology (CAP, DMT, or other) and its effectiveness in some environments is not yet determined. A number of standards organizations are working on it.

"x2/DSL" is modem from 3Com that supports 56 Kbps modem communication but is upgradeable through new software installation to ADSL when it becomes available in the user's area. At least one publication cites 3Com as describing this technology to be "the last modem you will ever need."

A "T1" transmission line is generally considered a "broadband" carrier and is defined as a type of "T-carrier" system, which is believed to have been first introduced by the Bell System in the U.S. in the 1960's as the first successful system that supported digitized voice transmission. The T-carrier system is entirely digital, using pulse code modulation and time-division multiplexing. Voice signals are typically sampled at about 8,000 times a second and each sample is digitized into an 8-bit word. With 24 channels digitized at the same time, a 192-bit frame, representing 8-bit words on each of 24 channels, is thus transmitted about 8,000 times a second. Each frame is separated from the next by a single bit, resulting in a 193-bit block. The T-1's published data rate of 1.544 Mbps generally represents the 192 bit frame, and the 1-bit signaling bit, multiplied by 8,000.

A T-1 system typically uses 4 wires and provides duplex capability, with two wires dedicated for receiving and two for sending at the same time. The T-1 digital stream includes 24, 64 Kbps channels that are multiplexed, wherein the standard 64 Kbps channel is based on the bandwidth required for a voice conversation. The four wires were originally a pair of twisted pair copper wires, but more recent systems provide coaxial cable, optical fiber, digital microwave, and other carrier technologies. The number and use of the channels may be varied from the standard guidelines.

The original transmission rate (1.544 Mbps) for T-1 lines is in common use today in Internet service provider ("ISP") connections to the Internet. Another level, the T-3 line, is published to

provide 44.736 Mbps, and is also commonly used by Internet service providers. Another commonly used service is "fractional T-1", which is the rental of some portion of the 24 channels in a T-1 line, with the other channels unused.

Display Capabilities/Constraints & Related Standards

Various different types of receiver display capabilities may also significantly impact the appropriate CODEC modality for efficiently communicating particular streaming media signals for display by the receiver. A brief summary of certain examples to illustrate such varied display parameters (e.g. resolution, clarity, color, depth, size, type/format-specific) is provided for a better understanding as follows.

One parameter that is highly variable between different types and makes of streaming media receiver devices, and therefore that may have significant impact on the appropriate CODEC to be used, is the range of colors that may be expressed by a display device, or "palette". A standard "browser-safe" palette, which may be accommodated by most software for Internet-based streaming media display, may include for example about 216 colors, though for web-based streaming media the computer display capability as well as the browser software capability must be understood.

With respect to computer display technology, a color is set for each individual pixel or addressable illumination element on the screen. Each pixel has a red, green, and blue (RGB) component. By specifying the amount of intensity for each of these components, a distinct color is given to that pixel. A "true color" display generally defines the color of a pixel on a display screen using a 24-bit value, allowing the possibility of up to 16,777,216 possible colors. The number of bits used to define a pixel's color shade is called the "bit-depth". True color is sometimes referred to as "24-bit color", though many modern color display systems offer a 32-bit color mode. An extra byte, called the "alpha channel", is typically used for control and special effects information. A "gray scale" (composed of discrete shades of gray) display setting is generally defined as having N bits of depth where N represents the saturation of black within the pixel. If N=1, the image is not called gray scale but instead monochrome, or black and white, as the bit can only be on or off and can contain no shading information.

Common computer resolutions include for example and without limitation the following:

(i) VGA or Video Graphics Array capable of displaying 640x480 pixels in 16 colors or 320x240 pixels in 256 colors in a 4:3 aspect ratio;

(ii) SVGA or Super Video Graphics Array capable of 800x600x6 bits/pixel (16 colors) or 650x480x8 bits/pixel (256 colors). SVGA was created by the Video Electronics Association (VESA); and

(iii) XGA (v1-4) or eXtended Graphics Array capable of 1024x768 pixels at 32,768 colors.

Additional standards have been added such as SXGA, defining pixel sizes above 1960x1440 and color depths of 32 bits/pixel and higher.

In the event that a larger range of colors (or palette) is used by a media signal than a particular display or browser can handle, most browsers are typically adapted to "dither" the colors, which is herein intended to mean that the browser will find colors within its palette that it can substitute for any color that is outside of its palette. To further illustrate the wide range of different system display capabilities, systems using WindowsTM (commercially available from Microsoft Corporation) and MacintoshTM (commercially available from Apple Corporation) based operating systems do not have identical palettes; within the usual 256 color palette, 216 are common to both types of browsers, whereas 40 are different and therefore require dithering by a browser operating within one of the systems if an image signal is communicated to that type of system in a format specified by the other.

Many different technologies also exist with respect to how a visual display is enabled from electronic information. The terms "VDT" or "Video Display Terminals" are generally used within the computer industry and are herein intended to be used interchangeably with simple references to "display". With respect to computer terminal use, VDT's comprise a computer output surface and projecting mechanism that shows text and graphic images to the computer user. VDT's may use a variety of specific display technologies, including for example cathode ray tubes ("CRTs"), liquid crystal displays ("LCDs"), light-emitting diodes ("LEDs"), gas plasma, or other image projection technology. The display is usually considered to include the screen or projection surface and the device that produces the information on the screen. In some computers, the display is packaged in a separate unit or "monitor", or the display may be fully integrated in a single unit with the computer processor.

With respect to LCD's in particular, this technology generally requires minimal volume and physical depth compared to other VDT's, and therefore is typically used in laptop computers and cellphone/PDA's. LCD's consume much less power than LED and gas–display VDT's because they work on the principle generally of blocking light rather than emitting it. An LCD may be either

"passive matrix" or "active matrix", which is also known as "thin film transistor" or "TFT" display. The passive matrix LCD has a grid of conductors with pixels located at each intersection in the grid. A current is sent across two conductors on the grid to control the light for any pixel. An active matrix has a transistor located at each pixel intersection, requiring less current to control the luminance of a pixel. For this reason, the current in an active matrix display can be switched on and off more frequently, improving the screen refresh time and therefore efficacy for higher speeds of streaming media (e.g. action video). Some passive matrix LCD's have dual scanning, in that they scan the grid twice with current in the same time as one scan in earlier versions; however, the active matrix is still generally considered to be the superior technology of the two. Reflective color display technology—the integration of color filters into passive-matrix display construction—is a low-power, low-cost alternative to active-matrix technology. Because they reflect ambient light, reflective LCDs deliver particularly high performance during use outside in daylight. Various different display technologies, and therefore transmission formats, have also been specifically developed for television viewing. Thus several different standards have evolved for television transmission, and their differences may significantly impact the nature and extent of compression desired (and therefore the choice of a particular CODEC) for communicating streaming media signals in television environs. These standards include in particular and without limitation: standard definition television ("SDTV"); and high definition television ("HDTV").

"SDTV" or "standard definition television" and "HDTV" or "high definition television" are the two categories of display formats for digital television ("DTV") transmissions, which are becoming the standard. These formats provide a picture quality similar to digital versatile disk ("DVD"), and are summarized relative to their similarities and differences as follows.

HDTV provides a higher quality display, with a vertical resolution display from about 720p to at least about 1080i and an aspect ratio (the width to height ratio of the screen) of generally 16:9, for a viewing experience similar to watching a movie. In comparison, SDTV has a range of lower resolutions and no defined aspect ratio. New television sets will be either HDTV-capable or SDTV-capable, with receivers that can convert the signal to their native display format. SDTV, in common with HDTV, using the MPEG-2 file compression method in a manner that generally reduces a digital signal from about 166 Mbps to about 3 Mbps. This allows broadcasters to transmit digital signals using existing cable, satellite, and terrestrial systems. MPEG-2 uses the lossy compression method, which means that the digital signal sent to the television is compressed and some data is lost, but this lost data may or may not affect how the human eye views the picture. Both the ATSC and DVB standards selected

MPEG-2 for video compression and transport. The MPEG-2 compression standard is elsewhere herein described in further detail.

Because a compressed SDTV digital signal is smaller than a compressed HDTV signal, broadcasters can transmit up to five SDTV programs simultaneously instead of just one HDTV program, otherwise known as "multicasting". Multicasting is an attractive feature because television stations can receive additional revenue from the additional advertising these extra programs provide. With today's analog television system, only one program at a time can be transmitted. Note that this use of the term "multicasting" is distinct from its use in streaming video where it involves using special addressing techniques.

When the United States decided to make the transition from analog television to DTV, the Federal Communications Commission decided to let broadcasters decide whether to broadcast SDTV or HDTV programs. Most have decided to broadcast SDTV programs in the daytime and to broadcast HDTV programs during prime time broadcasting. Both SDTV and HDTV are supported by the Digital Video Broadcasting (DTV) and Advanced Television Systems Committee (ATSC) set of standards.

HDTV as a television display technology provides picture quality similar to 35 mm. movies with sound quality similar to that of today's compact disc (further with respect to audio quality, HDTV receives, reproduces, and outputs Dolby Digital 5.1). Some television stations have begun transmitting HDTV broadcasts to users on a limited number of channels. HDTV generally uses digital rather than analog signal transmission. However, in Japan, the first analog HDTV program was broadcast on June 3, 1989. The first image to appear was the Statue of Liberty and the New York Harbor. It required a 20 Mhz channel, which is why analog HDTV broadcasting is not feasible in most countries.

HDTV provides a higher quality display than SDTV, with a vertical resolution display from 720p to 1080i. The *p* stands for *progressive scanning*, which means that each scan includes every line for a complete picture, and the *i* stands for *interlaced scanning* which means that each scan includes alternate lines for half a picture. These rates translate into a frame rate of up to 60 frames per second, twice that of conventional television. One of HDTV's most prominent features is its wider aspect ratio (the width to height ratio of the screen) of 16:9, a development based on a research-based belief that the viewer's experience is enhanced by screens that are wider. HDTV pixel numbers range from one to two million, compared to SDTV's range of 300,000 to one million. New television sets will be either HDTV-capable or SDTV-capable, with receivers that can convert the signal to their native display format.

In the United States, the FCC has assigned broadcast channels for DTV transmissions. In SDTV formats, DTV makes it possible to use the designated channels for multiple signals at current quality levels instead of single signals at HDTV levels, which would allow more programming with the same bandwidth usage. Commercial and public broadcast stations are currently deciding exactly how they will implement their use of HDTV.

Simulcast is the simultaneous transmission of the same television program in both an analog and a digital version using two different channels or frequencies. At the end of the DTV transition period, it is believed by that analog transmission will be substantially replaced such that current analog channels will be used solely for DTV. The extra channels that were used for digital broadcasting may for example then be auctioned and used for more television channels or other services such as datacasting. Simulcast is also used for the transmission of simultaneous television and Internet services, the transmission of analog and digital radio broadcasts, and the transmission of television programs in different screen formats such as the traditional format and the wide screen format. Simulcast broadcasting is used worldwide.

The transition to DTV is not an easy or inexpensive transition. For a television station to transmit DTV programming, it must build its DTV facilities, but a station must have revenue to build these facilities. Simulcast allows stations to continue receiving revenues from traditional analog programming and also gain extra revenues from the extra digital programming. Another obstacle in the transition to DTV is lack of interest among consumers. The need for special equipment is prohibiting viewers from seeing the difference between digital and analog programs, which is also slowing down public enthusiasm for DTV.

The equipment needed for operating DTV depends on whether terrestrial, cable, or satellite services are used as the transmission channel/carrier. In any event, and according to known or anticipated systems, it is generally believed that consumers will, at a minimum, have to purchase a converter to view DTV transmissions on their old television sets. In addition, consumers that use terrestrial services or antennas to receive television signals need an antenna equipped for digital signals. A consumer located in mountainous terrain in an ATSC-compliant country may not be able to receive terrestrial-based digital signals because of multipath effects. This is common even with today's analog television system. In DVB compliant countries, terrain does not affect the reception of digital signals. Satellite users are already enjoying DTV broadcasting, but a larger satellite dish might be needed to view HDTV programming.

A "set-top" box is herein defined as a device that enables a television set to become a user interface to the Internet and also enables an analog television set to receive and decode DTV broadcasts. DTV set-top boxes are sometimes called receivers. It is estimated that 35 million homes will use digital set-top boxes by the end of 2006, the estimated year ending the transition to DTV.

A typical digital set-top box contains one or more microprocessors for running the operating system, usually Linux or Windows CE, and for parsing the MPEG transport stream. A set-top box also includes RAM, an MPEG decoder chip, and more chips for audio decoding and processing. The contents of a set-top box depend on the DTV standard used. DVB-compliant set-top boxes contain parts to decode COFDM transmissions while ATSC-compliant set-top boxes contain parts to decode VSB transmissions. More sophisticated set-top boxes contain a hard drive for storing recorded television broadcasts, for storing downloaded software, and for other applications provided by the DTV service provider. Digital set-top boxes can be used for satellite and terrestrial DTV but are used mostly for cable television. A set-top box price ranges from $100 for basic features to over $1,000 for a more sophisticated box.

In the Internet realm, a set-top box often really functions as a specialized computer that can "talk to" the Internet - that is, it contains a Web browser (which is really a Hypertext Transfer Protocol client) and the Internet's main program, TCP/IP. The service to which the set-top box is attached may be through a telephone line as, for example, with Web TV or through a cable TV company like TCI.

To take advantage of Dolby Digital 5.1 channel for satellite broadcasts, a satellite receiver that provides a Dolby Digital output is necessary. For cable users, all digital set-top boxes are equipped with a Dolby Digital two-channel decoder. To use 5.1 channel sound, a 5.1 channel-compliant set-top box is needed or an external 5.1 channel decoder unit.

The most dramatic demonstration of digital television's benefits is through a high-end HDTV, because of the larger screen, wider aspect ratio and better resolution. Like most new technologies, however, HDTV is expensive. Nevertheless, less expensive digital TVs provide a markedly improved viewing experience over regular TV, and for those who choose to retain their old sets, even the addition of a set-top converter will deliver a discernibly improved picture and sound.

The FCC's schedule for transition to DTV proposes that everyone in the U.S. should have access to DTV by 2002 and that the switch to digital transmission must be completed either by 2006 or when 85% of the households in a specific area have purchased digital television sets or set-top converters.

In the early 1990s, European broadcasters, consumer equipment manufacturers, and regulatory bodies formed the European Launching Group (ELG) which launched a "DVB" or "Digital Video Broadcasting" project in order to introduce DTV throughout Europe. DVB is intended to provide an open system as opposed to a closed system. Closed systems are content-provider specific, not expandable, and optimized only for the system they were developed for. An open system, such as DVB, allows the subscriber to choose different content providers and allows integration of PCs and televisions. DVB systems are intended to be optimized for television, but as well as supporting home shopping and banking, private network broadcasting, and interactive viewing. DVB is intended to open the possibilities of providing crystal-clear television programming to television sets in buses, cars, trains, and even hand-held televisions. DVB is also promoted as being beneficial to content providers because they can offer their services anywhere DVB is supported regardless of geographic location. They can also expand their services easily and inexpensively and ensure restricted access to subscribers reducing lost revenues due to unauthorized viewing. Today, the DVB Project consists of over 220 organizations in more than 29 countries worldwide and DVB broadcast services are available in Europe, Africa, Asia, Australia, and parts of North and South America

Format-Specific Media

Various different formats for the streaming media signals themselves are also herein summarized by way of non-limiting example to also provide a further understanding of how CODECS may vary for a particular case.

"DVD" is an acronym for "digital versatile disc" is generally defined as a relatively recent optical disc technology that holds up to about 4.7 Gigabytes of information on one of its two sides, or enough for a movie about 133 minutes long on average. With two layers on each of its two sides, it may hold up to 17 Gigabytes of video, audio, or other information, compared to current CD-ROM discs of approximately the same physical size that hold about 600Mbytes (DVD holds more than about 28 times the information). DVD players are required to play DVD's, though they will also play regular CD-ROM discs. DVDs can be recorded in any of three general formats variously optimized for: (i) video (e.g. continuous movies); (ii) audio (e.g. long playing music); and (iii) or a mixture (e.g. interactive multimedia presentations). The DVD drive has a transfer rate somewhat faster than an 8-speed CD-ROM player. DVD format typically uses the MPEG-2 file and compression standard, which has about 4-times the resolution of MPEG-1 images and can be delivered at about 60 interlaced fields

per second where two fields constitute one image (MPEG-1 delvers about 30 non-interlaced frames per second. MPEG-2 and -1 standards are elsewhere herein defined in more detail. Audio quality on DVD is comparable to that of current audio compact discs.

"DVD-Video" is the name typically given for the DVD format designed for full-length movies and is a box that will work with a television set. "DVD-ROM" is a name given to the player that is believed by some to be the future replacement to CD-ROM drives in computers, as these newer drives are intended to play both regular CD-ROM discs as well as DVD-ROM discs. "DVD-RAM" is the name given to writeable versions of DVDs. "DVD-Audio" is the name typically given to players designed to replace the compact disc player.

"VHS" is an acronym for "Video Home System" and is generally defined as a magnetic videotape cartridge format, typically a half-inch wide, developed for home use with the ability to record and playback analog video and audio signals. VHS has become a popular format and the de facto standard for home movie distribution and reproduction mainly due to its pervasive presence and recordability. VHS stores signals as an analog format on a magnetic tape using technology similar to that of audiocassettes. The tapes are played back and recorded on using VHS video cassette recorders (VHS VCRs). VHS tapes store up to around two hours of video typically, although some VCRs are able to record to them at a slower speed allowing up to six or even eight hours of recording per tape.

The VHS format outputs a little over 200 lines of horizontal resolution. This compares to DVDs that output over 500 lines of horizontal resolution. Technically and perceptually, VHS is a format that has been surpassed by other formats, including for example DVD, S-VHS, Hi-8 and others. However, VHS remains a pervasive means for viewing video, and VHS tapes are still easily found across the country and around the world everywhere from movie rental stores to grocery stores making then easily accessible.

"CD" is an acronym for "compact disc" and is generally defined as small, portable, round medium for electronically recording, storing, and/or playing audio, video, text, and other information in digital form. Initially, CD's were only read-only; however, newer versions allow for recording as well (e.g. "CD-RW").

"Super audio compact disc" or "SACD" is a high resolution audio CD format that, together with DVD-Audio ("DVD-A"), are the two formats competing to replace the standard audio CD (though most of the industry generally is backing DVD-A, with a general exception believed to be Philips and Sony). SACD, like DVD-A, offers 5.1 channel surround sound in addition to 2-channel stereo. Both formats improve the complexity of sound by increasing the bit rate and the sample rate, and can be

played on existing CD players, although generally only at quality levels similar to those of traditional CDs. SACD uses Direct Stream Digital ("DSD") recording, which is published as being proprietary to Sony, that converts an analog waveform to a 1-bit signal for direct recording, instead of the pulse code modulation ("PCM") and filtering used by standard CDs. DSD uses lossless compression and a sampling rate of about 2.8 MHz to improve the complexity and realism of sound. SACD may also include additional information, such as text, graphics, and video clips.

Also for the purpose of further understanding, Internet-based communications also have particular protocols for communication that must be accommodated by a streaming media communications system using the Internet "superhighway". These protocols, in particular with respect to streaming media communication, are briefly summarized immediately below for the purpose of providing a more detailed understanding.

With respect to Internet communication, streaming media signals are generally communicated in digital format via data packets. The terms "packets" are herein intended to mean units of data that are routed between an origin and a destination via the Internet or any other packet-switched network. More specifically, when a file is sent, the protocol layer of the communications system (e.g. TCP layer of TCP/IP based system) divides the file into chunks of efficient size for routing. Each of these packets is separately numbered and includes the Internet address of the destination. The individual packets for a given file may travel different routs through the Internet. When they have all arrived, they are reassembled into the original file, for example by the TCP layer at the receiving end. A packet-switching scheme is an efficient way to handle transmissions on a connectionless network such as the Internet. An alternative scheme, circuit-switched, is used for networks allocated generally for voice connections. In circuit-switching, lines in the network are shared among many users as with packet-switching, but each connection generally requires the dedication of a particular path for the duration of the connection.

Wireless Communications & the WAP Gateway

Of equal importance to the contemporary age of the Internet, the age of wireless communications has significantly extended society's ability to interact outside of the fixed confines of the home and office, allowing our remote communications to break free from the umbilical cords of wires and cables. For example, in 2000, the number of mobile subscribers grew by close to 50%.

However, wireless communications systems, protocols, and enabling technologies have developed in a significantly fragmented, "format-specific" market on a world-wide scale. This is particularly true in comparing systems in wide use in the United States as compared to the rest of the world. Therefore, much effort has been expended in overcoming compatibility issues between format-specific systems and between the related wireless devices operating on different platforms. For the purpose of further understanding wireless communication as it is later related to the present invention, the following is a brief overview of significant technologies, systems, and protocols used in the wireless communication industry.

In general, the progression of wireless communications systems for cellular telephones is colloquially given the terms "1G", "2G", "2.5G", and "3G", representing respectively first generation, second generation, and so-on. Initial systems were purely analog, known as the 1G phones and systems. However, with rapid growth, available bandwidth for cellular phone use quickly eroded, giving way to digital signal processing in the 2G, which significantly widened the available bandwidth and ability for complex signal processing for advanced telecommunications. However, as demand progressed for wireless Internet access, so went the technology development from 2G phones (generally not Internet enabled), to 2.5G and 3G (progressively more enabled). As will be further developed immediately below, the systems, protocols, and enabling technologies thus have developed toward a concentrated focus in bringing the 2.5G and 3G modes to industry and consumers.

In general, there are four major digital wireless networks based upon 2G technology: time division multiple access ("TDMA"), code division multiple access ("CDMA"), Global System for Mobile communication ("GSM") and cellular digital packet data ("CDPD"). These are briefly herein described as follows.

Time division multiple access ("TDMA") is a technology used in digital cellular telephone communication that divides each cellular channel into three time slots in order to increase the amount of data that can be carried. TDMA is used by Digital-American Mobile Phone Service (D-AMPS), Global System for Mobile communication ("GSM"), and Personal Digital Cellular ("PDC). However, each of these systems implements TDMA in a somewhat different and incompatible way. An alternative multiplexing scheme to TDMA and FDMA (frequency division multiple access) is code division multiple access ("CDMA").

Code division multiple access ("CDMA") refers to any of several protocols used in 2G and 3G wireless communications. As the term implies, CDMA is a form of multiplexing that allows numerous signals to occupy a single transmission channel, optimizing the use of available bandwidth. the

Ex. 1018-2035

technology is used in ultra-high-frequency (UHF) cellular telephone systems in the 800 MHz to 1.9 GHz bands. CDMA uses analog-to-digital conversion (ADC) in combination with spread spectrum technology. Audio input is first digitized into binary elements. The frequency of the transmitted signal is then made to vary according to a defined pattern (code), so it can be intercepted only by a receiver whose frequency response is programmed with the same code, so it follows exactly along with the transmitter frequency. There are trillions of possible frequency-sequencing codes, thus enhancing privacy and making cloning difficult. The CDMA channel is nominally 1.23 MHz wide. CDMA networks use a scheme called "soft handoff", which minimizes signal breakup as a handset passes from one cell to another. The combination of digital and spread spectrum modes supports several times as many signals per unit bandwidth as analog modes. CDMA is compatible with other cellular technologies; this allows for nationwide roaming.

The original CDMA, also known as CDMA One, was standardized in 1993 and is considered a 2G technology that is still common in cellular telephones in the U.S. One version of cdmaOne, IS-95A, is a protocol that employs a 1.25 MHz carrier and operates in RF bands at either 800 MHz or 1.9 GHz; this supports data rates of up to 14.4 Kbps. Another version, IS-95B, is capable of supporting speeds of up to 115 Kbps by bundling up to eight channels.

More recent CDMA varieties, CDMA2000 and wideband CDMA offer data speeds many times faster. CDMA2000, also known as IMT-CDMA Multi-Carrier or IS-136, is a CDMA version of the IMT-2000 standard developed by the International Telecommunications Union (ITU). The CDMA2000 standard is a 3G technology that is intended to support data communications at speeds ranging from 144Kbps to 2 Mbps. Companies that have developed versions of this standard include Ericsson and Qualcomm corporations. Wideband CDMA, or "WCDMA", is an ITU standard derived from CDMA that is also known as IMT-2000 direct spread. WCDMA is a 3G technology intended to support data rates of up to 2Mbps for local area access, or 384 Kbps for wide area access, and supports mobile/portable voice, images, data, and video communications at these speeds. WCDMA digitizes input signals and transmits the digitized output in coded, spread-spectrum mode over a 5 MHz wide carrier – a much broader range than the 200 KHz wide narrowband CDMA.

The Global System for Mobile communication ("GSM") is a digital mobile telephone system that is widely used in Europe and other parts of the world; this system uses a variation of "TDMA" (introduced immediately below) and is the most widely used of the three digital wireless telephone technologies (TDMA, GSM, and CDMA). GSM digitizes, compresses, and then sends data down a channel with two other streams of user data, each in its own time slot. It operates at either the 900 Mhz

or 1800 MHz frequency band. At the time of this disclosure, GSM is generally considered the wireless telephone standard in Europe, and has been published to have over 120 million users worldwide and is available in 120 countries. At least one company in the United States, American Personal Communications (SprintTM subsidiary), is using GSM as the technology for a broadband personal communications services ("PCS"). PCS are telecommunications services that bundle voice communications, numeric and text messaging, voice-mail and various other features into one device, service contract and bill. PCS are most often carried over digital cellular links. This service is planned to have more than 400 base stations for various compact mobile handsets that are being made by manufacturers such as Ericsson, Motorola, and Nokia corporations; these devices generally include a phone, text pager, and answering machine. GSM is part of an evolution of wireless mobile telecommunications that includes High-Speed Circuit-Switched Data (HCSD), General Packet Radio System (GPRS), Enhanced Data GSM Environment (EDGE), and Universal Mobile Telecommunications Service (UMTS).

Cellular Digital Packet Data ("CDPD") is a wireless standard providing two-way, 19.2 kbps packet data transmission over existing cellular telephone channels.

Several different protocols have also been put into use for communicating over the various wireless networks. Various specific such protocols are briefly introduced as follows.

"X.25" is a packet-based protocol, principally used at the time of this disclosure in Europe and adapted as a standard by the Consultative Committee for International telegraph and Telephone (CCITT). X.25 is a commonly used network protocol that allows computers on different public networks (e.g. CompuServe, Tymnet, or TCP/IP network) to communicate through an intermediary computer at the network layer level. X.25's protocols correspond closely to the data-link and physical-layer protocols defined in the Open Systems Interconnection ("OSI").

"OSI" is a model of network architecture and a suite of protocols (a protocol stack) to implement it, developed by ISO in 1978 as a framework for international standards in heterogeneous computer network architecture. The OSI architecture is split between seven layers, from lowest to highest: (1) physical layer; (2) data link layer; (3) network layer; (4) transport layer; (5) session layer; (6) presentation layer; and (7) application layer. Each layer uses the layer immediately below it and provides a service to the layer above. In some implementations, a layer may itself be composed of sub-layers.

General Packet Radio Services ("GPRS") is a packet-based wireless communication service that promises data rates from 56 to 114 Kbps and continuous connection to the Internet for mobile phone

and computer users. The higher data rates will allow users to take part in video conferences and interact with multimedia Web sites and similar applications using mobile handheld devices as well as notebook computers. GPRS is based on Global System for Mobile ("GSM") communication and will complement existing services such as circuit-switched cellular phone connections and the Short Message Service ("SMS"). SMS is a message service offered by the GSM digital cellular telephone system. Using SMS, a short alphanumeric message (160 alphanumeric characters) can be sent to a mobile phone to be displayed there, much like in an alphanumeric pager system. The message is buffered by the GSM network until the phone becomes active.

The packet-based service of GPRS is publicized to cost users less than circuit-switched services since communication channels are being used on a shared-use, as-packets-are-needed basis rather than dedicated only to one user at a time. It is also intended to make applications available to mobile users because the faster data rate means that middleware currently needed to adapt applications to the slower speed of wireless systems will no longer be needed. As GPRS becomes widely available, mobile users of a virtual private network ("VPN") will be able to access the private network continuously rather than through a dial-up connection. GPRS is also intended to complement "Bluetooth", a standard for replacing wired connections between devices with wireless radio connections. In addition to the Internet Protocol ("IP"), GPRS supports X.25 protocol. GPRS is also believed to be an evolutionary step toward Enhanced Data GSM Environment ("EDGE") and Universal Mobile Telephone Service ("UMTS").

Universal Mobile Telecommunications Service ("UMTS") is intended to be a 3G, broadband, packet-based transmission of text, digitized voice, video, and multimedia at data rates up to 2 Mbps. UMTS is also intended to offer a consistent set of services to mobile computer and phone users no matter where they are located in the world. This service is based upon the GSM communication standard, and is endorsed by major standards bodies and manufacturers, and is the planned standard for mobile users around the world by 2002. Once UMTS is fully implemented, computer and phone users can be constantly attached to the Internet as they travel.

Enhanced digital GSM enterprise ("EDGE")service is a faster version of the Global System for Mobile (GSM) wireless service, designed to deliver data at rates up to 384 Kbps and enable the delivery of multimedia and other broadband applications to mobile phone and computer users. The EDGE standard is built on the existing GSM standard, using the same time-division multiple access (TDMA) frame structure and existing cell arrangements. EDGE is expected to be commercially

available in 2001. It is regarded as an evolutionary standard on the way to Universal Mobile Telecommunications Service (UMTS).

Wireless Application Protocol ("WAP") is a specification for a set of communication protocols to standardize the way that wireless devices such as cellular telephones and radio transceivers, can be used for Internet access, including e-mail, the World Wide Web, newsgroups, and Internet Relay Chat ("IRC"). While Internet access has been possible prior to WAP, different manufactures have used "format-specific" technologies. WAP enables devices and service systems to intercooperate.

In most recent times, much effort has been expended to merge the fields of wireless communications and the Internet in order to bridge the gap of cords, wires, and cables that had before separated the "information superhighway" from reaching people on wireless devices. Such technology merger has developed for example within the home and office network setting itself, where wireless infrared and radio frequency communications systems have been developed for interfacing equipment within a "wireless" office or home. Another substantial effort has also been underway to communicate and share information with more remote wireless devices, such as cell phones and personal digital assistants ("PDA's").

PDA's are typically small, mobile devices that may be "hand-held" and usually contain limited processors and display screens for managing, storing, and displaying telephone books, calendars, calculator, and the like. Recently available PDA's have been made "wireless enabled", either by having wireless modems embedded within the PDA itself, or by coupling to wireless modem "plug-ins" such as a cell phone. Wireless enabled PDA's are also generally "Internet enabled" with limited "browser" capability allowing the PDA to communicate with server devices over the Internet. Examples of commercially available wireless "enabled" PDA's include the Palm VII (from Palm, Inc.), and the iPAQ™ (from Compaq, Inc.). These PDA's include a Windows CE™ operating system that provides the limited browser capability and screen display for content. These phones have processing capabilities from about 33 MHz to about 220 MHz and varied screen display capabilities, such as for example 320 x 240 pixel screen displays.

Similarly, cellular phones themselves have also been recently rendered "Internet enabled", also with limited browser capability and screens to display content. Examples of "Internet enabled" cellular phones include, for example: Sanyo SCP-4000™, Motorola *i1000plus*™, among a wide range of others; this wide field represents hundreds of different processing and display capabilities.

In either the case of the PDA or the cellular phone that is "Internet-enabled", compatibility with the Internet protocols of communication must be achieved. In general, wireless communications take

place over a wireless applications protocol ("WAP"), whereas communications over the Internet proceed according to one of several different protocols, the most common being Transmission Control Protocol/Internet Protocol ("TCP/IP"). Therefore, a WAP Gateway, as shown in Figure 1E, forms a bridge between the world of the Internet (or any other IP packet network) and the wireless phone/data network, which are fundamentally different in their underlying technologies. The gateway, in essence, does the interpretation between these two distinct entities, allowing the consumer to use their cell phone or hand held computing device (e.g. PDA) to access the Internet wirelessly.

However, streaming media that is formatted for transmission to higher power computing devices such as desk-top computers having significant display capabilities is not generally compatible for receipt and viewing on these devices that have severely limited processing and display functionality. Particular "format-specific" compression schemes have been developed for use specifically with only these devices, and only specific media content may be transmitted to these devices in those formats.

There is still a need for a streaming media communications system that is adapted to transmit a wide variety of streaming media signals in appropriate formats to be played by wireless devices such as cellular phones and PDA's having unique constraints, such as, for example, limited and variable processing, memory, and display capabilities.

SUMMARY OF THE INVENTION

The present invention addresses and overcomes the various limitations, inefficiencies, resource limitations, and incompatibilities of prior known methods for streaming media communication, and is provided in various beneficial modes, aspects, embodiments, and variations as follows.

The present invention according to one embodiment is a streaming media communications system that uses a computer implemented intelligence system, such as artificial intelligence, in a network system, such as a neural network, to communicate a streaming media signal between a transmission device and at least one destination device.

The present invention according to another embodiment is a system for communicating a streaming media signal between a transmission device and a plurality of destination devices each having different media signal processing capabilities.

The present invention according to another embodiment is a streaming media communications system that is adapted to communicate a streaming media signal from a single transmission device and

Ex. 1018-2040

at least one destination device over a plurality of different transmission channels, each having a different transmission capability or constraints with respect to communicating the streaming media signal.

The invention according to another embodiment is a neural network incorporating an artificial intelligence implementation that is adapted to be trained in an adaptive learning process with respect to the ability of a streaming media compression system's ability to compress a streaming media signal at a source into a compressed representation of the streaming media signal, transmit the compressed representation over a transmission channel to a destination device, and decompress the compressed representation into a decompressed representation of the streaming media signal which is adapted to be played by the destination device.

The invention according to another embodiment is a system for compressing streaming media signals according to a CODEC that is used at least in part based upon at least one parameter affecting communication of the streaming media signals. According to one aspect of this mode, the CODEC is used according to at least one of the following parameters: a previously learned behavior of the CODEC with respect to another reference signal, a previously learned behavior of the CODEC with respect to a prior attempt at compressing or decompressing the same streaming media signal, a comparison of the CODEC's operation with respect to the streaming media signal against a reference algorithm compression of the streaming media signal, a learned constraint of the transmission channel, and a learned constraint of the destination device. In one beneficial embodiment, the CODEC is used based upon more than one of these parameters, and in still a further beneficial variation is used based upon all of the parameters.

The invention according to another embodiment is a system for compressing streaming media signals using a CODEC library that is adapted to store multiple CODECS of different types and operations, and that is adapted to be searched and accessed by a network system, such as a neural network, in order to provide an appropriate CODEC from the CODEC library for use in compressing the input streaming media signal into a compressed representation for transmission to a destination device.

The invention according to another embodiment is a CODEC operating system that is adapted to interface with a CODEC Library and also with a neural network in order to use the neural network in a process, such as an artificial intelligence process, to choose an appropriate CODEC from the CODEC library and use the chosen CODEC for compressing the streaming media signal into a compressed representation of the streaming media signal for transmission to a destination device.

Ex. 1018-2041

According to one aspect, the CODEC library is adapted to receive and store a new CODEC such that the new CODEC may be interfaced with the neural network in order to be chosen and applied to compress the streaming media signal as provided.

The invention according to another embodiment is a destination agent that is adapted to be stored by a destination device for use in decompressing a compressed representation of a streaming media signal. The destination agent is adapted to communicate with a remotely located, compressed streaming media transmission system in order receive and play streaming media signals therefrom. In a particularly beneficial aspect, the software agent is adapted to deliver information about the destination device to the compressed streaming media transmission system, and is also adapted to receive and decode certain encoded streaming media signals from the compressed streaming media transmission system.

The invention according to another embodiment is a system for communicating a streaming media signal having a destination agent that is adapted to be stored within a destination device for decompressing a compressed representation of a streaming media signal into a decompressed representation that may be played by the destination device.

According to one aspect of this embodiment, the destination agent has a diagnostic agent and also a decompression agent. The diagnostic agent is adapted to determine a value for at least one parameter of the destination device related to the capability for processing, storage, or display. The decompression agent is adapted to apply a CODEC decompressor to decompress the compressed representation of the streaming media signal into the decompressed representation using a CODEC based at least in part upon the value of the at least one parameter.

According to another aspect, the destination agent comprises a software agent. In one variation, the software agent is embedded within the destination device. In another variation, the software agent is adapted to be loaded onto the destination device at least in part by a remotely located source that is adapted to deliver the compressed representation of the streaming media signal to the destination device.

The invention according to another embodiment is a transcoder for trancoding streaming media signals between at least one initial format and at least one transcoded format. The transcoder includes a single thread for each of several streaming media signals.

The invention according to another embodiment is a video-on-demand streaming media system incorporating the embodiments shown in the Figures and otherwise described herein.

Ex. 1018-2042

The invention according to another embodiment is a mobile telephone communications system incorporating the embodiments shown in the Figures and otherwise described herein.

The invention according to another embodiment is an interactive gaming system incorporating the embodiments shown in the Figures and otherwise described herein.

The invention according to another embodiment incorporates the various modes, embodiments, aspects, features, and variations herein disclosed above and elsewhere to static media, as well as to media that is stored locally after processing (e.g. compressing) and not transmitted.

BRIEF DESCRIPTION OF THE FIGURES

Figures 1A-B show schematic block diagrams representing two respective variations of prior media communications systems using conventional CODEC systems.

Figures 1C-D show schematic block diagrams representing two respective variations of prior media transcoder systems.

Figure 1E shows a schematic block flow diagram of the various interrelated components in a prior WAP gateway communications system.

Figures 2-3 show schematic block diagrams of the transcoder system of one embodiment of the present invention during two respective modes of use.

Figures 4A-5 show block flow diagrams in various detail, respectively, of a media communications system according one embodiment of the invention.

Figure 6 shows a schematic block flow diagram of various interrelated components of a "video-on-demand" streaming video communications system according one embodiment of the invention.

Figure 7 shows a schematic block flow diagram of various interrelated components of a wireless streaming video communications system according to one embodiment of the present invention.

Figure 8 shows a schematic block flow diagram of various interrelated components of a WAP gateway media communications system according one embodiment of the present invention.

Figure 9 shows a schematic block flow diagram of various interrelated components of a wireless communications system during backhauling according to one particular mode of use of the media communications system of an embodiment the present invention.

Figure 10 shows a schematic block flow diagram of various interrelated components of an interactive gaming communications system and set-top TV browsing of one embodiment of the present invention.

Ex. 1018-2043

DETAILED DESCRIPTION OF THE EMBODIMENTS

The present invention as illustrated variously through the embodiments below (and by reference to the Figures) provides a media communications system that includes a compression system, a delivery system, and a decompression system, and in another aspect includes a transcoder system. In general, the combination of these individual sub-systems provides a capability to efficiently transcode media between multiple encoding formats, in addition to customize the compression, delivery, and decompression of randomly selected streaming media signals based upon a large array of system parameters as variables. These variables include for example, without limitation, parameters related to the following: the source video signal, the source transmitting device, the transmission modality, and the destination device. The compression, delivery, and decompression of a media signal is thus customized to be optimally efficient for a given, and changing, environment of use. As a result, a wide range of complex streaming media signals may be communicated with a level of efficiency and range of device compatibility that is significantly improved over other known systems.

Notwithstanding the benefits of the overall streaming media communication system herein described, each sub-system described also independently provides beneficially useful results for streaming media communication. The various subsystems themselves, and the various iterations of combinations of these sub-systems apparent to one of ordinary skill based at least in part upon this disclosure, are also contemplated within the scope of the invention. In addition, various aspects of the overall communication system, as well as of each sub-system described, are also contemplated as useful for other applications other than specifically for streaming media communication in particular. Therefore, where apparent to one of ordinary skill, such additional applications are further contemplated within the scope of the invention, despite the particularly useful modes applied to improved streaming media communication.

Transcoder

A video/audio transcoder 200 is provided according to the invention that enables one incoming video source 210 to be streamed across multiple formats 215 (for example MPEG4, Real Video™, and QuickTime™) from one device without human intervention. The transcoder 200 according to the present embodiment provides substantially greater functionality at a fraction of the price of other

commercially available transcoder systems. Moreover, because the system works "on-the-fly," pre-compressing of the video source 210 is significantly diminished.

More specifically, the transcoder 200 system and method according to the invention is adapted to transcode digitized media originating from any compressed or uncompressed format to be reproduced into any other compressed format -- on demand, real-time. The system 200 and method also enables efficient, simultaneous processing of multiple streams 215 of differing data from a multiplicity of different compressed or uncompressed formats into a multiplicity of different compressed formats.

The transcoder 200 of the present embodiment is herein described in an overall system by way of illustration by reference to Figure 3. As shown, a first player initially makes a connection to a server 300 that houses the transcoder 200. The player format (e.g., Microsoft Media), connection speed (e.g., 32 Kbps) and protocol (HTTP) are identified. The server 300 pulls the live or pre-encoded video into a "live buffer" or "cache" 310 and encodes it as digitized but nearly uncompressed data (e.g., AVI or MPEG2). The server 300 then loads an appropriate CODEC thread (e.g. Microsoft Media™) at the connection speed (e.g. 32 Kbps). Next, the server 300 loads a HTTP/MS player thread that serves the first client Then, a second stream is requested by a client using M/S Player at 100Kbps with MMS. The server loads the appropriate MS CODEC thread at the appropriate 100 Kbps rate. Then, the server 300 loads an MMS/MS player thread to serve the second client. Then, a third stream is requested by a client using Real Player at 40 Kbps with RTSP. The server 300 loads the appropriate Real CODEC thread at the appropriate 40 Kbps rate. Then, the server 300 loads an RTSP/Real player thread to serve the third client. Again, this illustration is exemplary, and other specific CODECS may be suitable substitutes, as well as other bit-rates, etc.

In order to provide still a further understanding of the present transcoder embodiment, Figure 3 shows the transcoder 200 by way of further example as applied to serve multiple different video streams to different clients.

In brief, the present transcoder 200 shown and described uses "thread" communications instead of "IPC" or "Inter Processor Communications" that are used according to many conventional transcoding techniques. For the purpose of this transcoder 200 description, the term "thread" is herein intended to mean an encapsulation of the flow of control in a program. Single-threaded programs are those that only execute one path through their code "at a time". Multithreaded programs may have several threads running through different code paths "simultaneously". In a typical process in which multiple threads exist, zero or more threads may actually be running at any one time. This depends on

Ex. 1018-2045

the number of CPUs the computer on which the process is running, and also on how the threads system is implemented. While a machine or system with a number of n CPUs may be adapted to run no more than n threads in parallel, the threading operation according to the present transcoder invention may give the appearance of running many more than *n* "simultaneously" by sharing the CPUs among threads.

The transcoder 200 provides abstract APIs, and therefore the CODEC is accessed without the (much larger) native encoder overhead. Buffering 310 is created as a function of client pull for different video streams. Moreover, the transcoder 200 of the invention utilizes a network architecture – a single thread for each different connection, combining clients into same thread if they are at they are within the buffered segment of the same content. The transcoder's 200 use of threads in the manner herein shown and described is considered highly beneficial because a context switch between two threads in a single process is believed to be considerably cheaper (processing/memory/IO) than using a context switch between two processes. In addition, the fact that all data except for stack and registers are shared between threads makes them a natural vehicle for implementing tasks that can be broken down into subtasks that can be run cooperatively.

While various specific architectures may be built around the transcoder 200 embodiments just described in order to achieve particularly desired results on a case-by-case basis. However, for the purpose of further illustration, the following is an example of a more detailed system using the transcoder 200 described. The transcoder 200 is provided adapted to support a large number of simultaneous customer streams, each with differing formats. In particular, such system may support more than 5000 simultaneous streams, and in some circumstances more than 7000 simultaneous customer streams, each with differing video formats. Still further, the transcoder 200 may be implemented to convert any of a wide number of video sources to a format uniquely appropriate or required for many different individual clients each having differing needs. In one particular example, a transcoder 200 as herein described may be implemented to support such high demand simultaneously on any of the following formats: MPEG 1; MPEG 2; MPEG 4; Motion JPEG; AVI; H.261; H.263; H.263 +; RealVideo™; G-8; QuickTime™; Shockwave Flash™; Indeo Cinepak™; ASF.

It is further contemplated that the transcoder 200 may be adapted in an overall communication system to be compliant with all existing and soon anticipated fixed and mobile terminals and devices. Moreover, the transcoder 200 may be implemented to adapt output stream format variables to dynamically accommodate the channel and platform conditions of each client. Still further, the system incorporating the transcoder is adapted to support load balancing servers and routers for multi-

transcoder installations. Accordingly, it is believed that the transcoder 200 of the present invention delivers significantly greater functionality for significantly lower cost than other prior transcoding techniques and systems.

As described above, various different system architectures may incorporate the transcoder 200 of the invention without departing from the scope of the invention. However, more details of a particular architecture that is believed to suitably provide the beneficial level of support just described includes the following aspects: (i) dual P3-933 processor; (ii) any variant of Unix OS; (iii) 512 MB RAM; Redundant Firewire or Gigabit Ethernet; Redundant Power Supplies. Such system may be provided in a rack mounted configuration, or otherwise to suit a particular need.

The following aspects of the transcoder 200 of the invention should be contemplated as broadly beneficial, both independently and in various combinations as is apparent to one of ordinary skill based at least in part from this disclosure.

A system and method is provided for utilizing asynchronous software thread communication in both user and kernel space to perform efficient transcoding on multiprocessor and/or distributed computing platforms (such as clustering). It has been observed that this method is more efficient than utilizing traditional IPC methods to implement the transcoder. A shared library of CODEC algorithms is created and used to access the various CODEC algorithms, thereby incurring a lower processing overhead as well as lower memory utilization than that required by the traditional combined encoder functionality such as that used in the majority of commercial encoders. Of particular benefit, common threads may be used for multiple connections, and in fact even a single thread may be used for every individual connection using the present transcoder.

A system and method is also provided for combining multiple clients to be served by the same thread (for efficiency) whenever the same content is demanded and dynamic buffers (caches) can accommodate all of the data points demanded.

Media Compression and Delivery System

A data compression and delivery system 400 and method is also provided according to the invention for real time dynamic data signal processing for optimal reproduction of approximations of original media data over a given set of constraints. This system 400 and method is illustrated schematically by way of block flow diagrams in Figures 4A and 5. Further description of the various

Ex. 1018-2047

beneficial features and operation of this system is provided as follows by way of exemplary embodiments generally incorporating by reference the description provided by these Figures 4A-5.

Figure 4 A ia a block diagram illustration of one embodiment of the data compression and delivery system 400 of the present invention. As shown in Figure 4A, the data compression and delivery system 400 comprises media module 405, dynamic player module 407, image processor 410, baseline snapshot module 415, classifier 417, quality of standard (QoS) module 420, network layer input module 425 and network output layer module 430. The system 400 further comprises a neural network processing module 440, timer 435, CODEC library module 445, dynamic client request module 450, ICMP module 455, device and network parameters measurement module 460 and delivery and transmit module 465.

In one embodiment, the system 400, resident at a server node(s), processes incoming uncompressed or previously compressed data. The system 400 employs neural networks 440 with artificial intelligence to monitor the incoming data to determine a plurality of key characteristics of each data segment. The system 400 correlates the incoming data characteristics with libraries 445 of pre-developed self-referencing experientially learned rules of the patterns in a scene in a sequence of frames in the input signal (e.g., a video signal) and with externally imposed constraints to optimally choose a preferred commercially available compression/decompression algorithm (e.g. CODEC) for each segment of the data. The system 400 then sets up an extensive array of usage controls, parameters and variables to optimize the chosen algorithm. Choice of algorithm and set up of parameters and variables will dynamically vary with each segment of incoming data depending upon the characteristics of the data as well as the evolving optimization process itself. The set of possible algorithms is numerous, limited only by availability and other commercial considerations. Each segment of data is encoded and compressed in the above manner and then served to a communications channel.

The compression system 400 just described is particularly useful as a streaming media compression engine, which, based upon information from the available CODEC's and the streaming media delivery system, performs frame-by-frame analysis of the incoming video using another artificially intelligent neural network 440. The system 400 then chooses the most appropriate compression format and configures the compression parameters for optimal video compression based on the best quality as measured by , in one embodiment, a selection of a peak signal to noise ratio from the underlying system environment. The result is the "optimal" video and audio service for the device and conditions present.

Ex. 1018-2048

A more specific account of the artificial intelligence/neural network 440 aspect of this system as applied to streaming media signals is provided as follows. Initially, a library of separate and distinct CODECs are added to the system as a searchable CODEC library 445. Additional libraries of relevant reference information are also provided, including: a Network Transport Standards (NTS) library 443; and a Quality-of-Service (QoS) library 447. Then, a video (media source) is introduced either in a digitized or non-digitized format (AD conversion is used) via image processor 410. Image processor 410 then decompresses the source (if required) and employs various standard image processing algorithms used for "cleaning-up" the source image(s). The resultant source media is then passed to the baseline snapshot 415 repository where it will be used as a "perfect gold standard" for later comparison. Simultaneously, this resultant source media is also fed to the classifier 417.

The classifier 417 analyzes the source media for temporal, spatial and logical features for the purpose of creating source media sub-segments which exhibit similar combinations of temporal, spatial and logic features. "Similar" is defined to mean a contiguous sub-segment of the source media that contains common temporal, spatial and logic features that would lend themselves to a particular encoding/compression algorithm (as found in the CODEC library 445). This source media sub-segment (or, in one embodiment, a group of contiguous video and audio frames) is referred to as a "scene".

The neural network process 440 then operates upon this scene by employing CODECs from the CODEC library 445 to compress the scene. The internal configuration of each CODEC are manipulated/changed in accordance with inputs obtained from the NTS library 443, QoS library 447, Timer Process 435, Network Input Layer 425, ICMP agent 455 and the Device and Network Parameter measurement agent 460. The compressed scene is then decompressed and a comparison is made against the Baseline Snapshot 415 using a quality measurement made by the quality standard process 420. In one embodiment of the present invention, the Quality Standard Process 420 employs a peak signal noise ration (PSNR) algorithm in order to perform the comparison of the decompressed scene against the baseline snapshot of the source media. The comparison process is repeated with various CODECs from the CODEC library 445 until the Neural Network Process 440 is satisfied with the quality of the resultant compressed scene, within the constraints of the inputs received from the NTS library 443, QoS library 447, Timer process 435, Network Input Layer 425, ICMP Agent 455 and the Device and Network Parameter Measurement Agent 460. Finally, the resultant compressed scene is sent to the Network Layer Output 430 which transports the compressed scene to the Client using an appropriate Network Transport protocol and QoS algorithm.

Ex. 1018-2049

The above process is repeated until the entire source media has been transmitted to the Client or until the process is aborted due to various possible conditions which may include: a Client request to abort, network transport failure, Client hardware failure, etc.

The NTS library 443 is a repository of network transport services that are selected and used by the Network layer output 430 to transport compressed source media to the Client and by the Network Layer Input 425 to receive information from the Client. The selection is based upon qualitative and quantitative inputs received from the Network Layer Input 425, ICMP agent 445 and the Device and Network Parameter Measurement agent 460.

The QoS library 447 is a repository of quality of service algorithms that are selected and used by the network layer output 430 to transport compressed source media to the Client. The selection is based upon qualitative and quantitative inputs received from the Network Layer Input 425, ICMP agent 455 and the Device and Network Parameter Measurement agent 460.

The ICMP agent 455 generates inputs to the neural network process 440 that dynamically provides it with the quantitative and qualitative characteristics of the transport in use between the processor and the client. In one embodiment of the present invention, the ICMP protocol is used for this purpose.

The Device and Network Parameters Measurement agent 460 generates inputs to the neural network process 440 that dynamically provides it with the qualitative and quantitative characteristics of the client's environment. In one embodiment of the present invention, these client environment characteristics include central processing unit (CPU) capacity, network interface characteristics, storage capacity and media rendering devices capabilities.

Still referring to Figure 4A, the Network Layer Input 425 provides inbound (originating from the client) network transport services. The Network Layer Output 430 provides outbound (originating from the processor) network transport services. The Timer Process 435 provides a way for the user of the invention to limit the maximum amount of time that the Neural Network Process 440 will spend in processing a given source media.

Figure 4B is a block diagram illustration of one embodiment of a CODEC selection scheme of the neural network processing module 440 of one embodiment of the present invention. The neural network processing module 440 shown in Figure 4B comprises a video frame selection module 475, CODEC parameters module 480, input layer module 485 , hidden layers 486 – 487 and output module 488. In one embodiment of the present invention, a CODEC representative signal suitable to be used as

Ex. 1018-2050

a reference baseline signal for incoming signals to the neural network processing module 440 is generated by the neural network processing module 440. In one embodiment, the classifier 417 determines which scenes in segments of an incoming video signal represents the best scene in light of the available parameters of the underlying CODEC. A list of standards are used by the neural network processing module 440 to determine which scene in the signal represents the best scene. In one embodiment, the Neural Network Process 440 samples a number of pixels in a particular frame of video to determine changes in the number of pixels in that particular frame vis-à-vis the pre-determined parameters of the video signal. In another embodiment, significant motion changes in a particular scene in the video signal may be used as the baseline reference scene ("best scene") for subsequent incoming video.

In one embodiment of the present invention, the neural network processing module 440 takes a segment of video from the classifier 417 as an input and subsequently takes a sample of this input to derive enough information that characterizes the video signal. For example, in the scheme illustrated in Figure 4B, the Neural Network Process 440 takes a window snap-shot (e.g., a 176 X 144 pixel window) to examine. It is advantageous for the Neural Network Process 440 to look at the center of the sample window to generate enough information about the video signal. In one embodiment of the present invention, the Neural Network Process 440 uses a minimum of 8 frames to generate the requisite information about the video signal. Information from the sample window is presented with the particular CODEC parameters from parameter module 480 to the input layer 485.

The input layer 485 is coupled to a plurality of hidden layers 486 – 487 via a plurality of neurons with each connection forming either a strong or weak synoptic link from one neuron to the other. In one embodiment, each CODEC supported by the neural network processing module 440 is provided with its own neural network to process the CODEC specific parameters that come with the particular CODEC. The Neural Network Process 440 generates the "best" video signal through a round-robin like process referred to as a "bake-off" from the plurality of CODECs processed during a video sampling capture period. In processing the best video representation from incoming signals, each of the corresponding neural networks for each of the CODECS generates the best representative sample from the hidden layers 486 – 487 and feed the signal to the output module 488. In one embodiment of the present invention, the output data set of the best CODEC from each class of CODECS being processed by the Neural Network Process 440 has two possibilities. The first being the Neural Network Process 440 submitting the best results for each CODEC to the output module 488 to a "bake-off" neural network of the plurality of "best" samples for each of the plurality of CODECS which in

turn generates the winning best CODEC from the plurality of best CODECS. The bake-off neural network is smaller and faster than the neural networks that handle the processing of the CODECS.

In a second processing scheme, the Neural Network Process 440 may implement a genetic algorithm processing of the best CODECS generated by the plurality of CODECS. The genetic algorithm follows the same statistical selection approach of a marble game. Thus, instead of feeding the winning output CODEC from the various neural networks into a "bake-off" neural network, a genetic algorithm processing may be applied to feed the output module 488 from the various neural networks into a bucket and picking the best CODEC representation from a collection of scenes at the end of the source media, for example, a movie, etc. In one embodiment of the present invention, the Neural Network Process 440 uses a combination of forward and backward propagating algorithm to process the CODECS.

Referring back to Figure 4A, for the purpose of providing a further understanding of this artificial intelligence process, the following example of one particular application is provided. It is to be appreciated that the features and operation of the system provided by this exemplary application are to be considered as broadly descriptive of the neural network 440 aspect for data compression and delivery according to the invention. Other applications may be made and fall within the scope of the invention.

A video content provider installs the system of the present invention on its server. Sample videos are introduced to the system in order to perform an initial AI process as described above. A complex matrix of CODEC characterizations, e.g. for each bit rate, pattern of video, etc., is created to be drawn from later. Next, a client end-user connects to the content provider system in order to view a video M. The communication system of the invention residing on the server delivers a software agent to the client's device, thus enabling the client to connect to the communication system in order to deliver device-specific information and receive the appropriate compressed signal with decompression CODEC for playing. Next, the AI system begins loading the video M as a streaming signal into a buffer for the purpose of choosing the appropriate CODEC for each frame and compressing each frame appropriately for transmission. The time period of the buffer depends upon multiple variables, principally the processing power of the system, and may be generally for example approximately 15 seconds for systems having appropriate capability for pre-recorded but uncompressed video media. Within the buffer, each frame is compared against each CODEC according to the "types" of sequences pre-tested in matrix as depicted in the diagram.

Next, the system 400 looks at end-user parameters, e.g. screen resolution, memory available, via information received from the software agent in the client's device. The most appropriate CODEC is then chosen and configured/tuned for optimal performance by setting certain variables within the CODEC to fixed quantities (e.g. based on comparing source video vs. patterns in past, transmission channel capabilities or constraints, and destination device capabilities or constraints). The process just described is generally done frame-by-frame by the classifier 417, but the CODECS are compared for temporal compression efficiency such that the process for each frame contemplates other leading and lagging frames. Once the appropriate CODEC is chosen and tuned for each frame (or block of frames where appropriately determined automatically by the system), the delivery system reports to the client agent and delivers the tuned CODEC ahead of the corresponding frame(s) to be decompressed and played.

It is to be appreciated that the neural network 440 of this system 400 continuously learns and remembers the performance and operation of the CODECS within the CODEC library 445, and continuously uses its learning to improve the compression efficiency of the input media signal. The process of running a signal frame through the library, modifying CODEC operating parameters, comparing compression performance by the compare logic 525 (Figure 5) against reference standard compression, and running the loop again with further modifications, is an iterative 550 (Figure 5) one that generally continues to improve compression efficiency. In fact, compression with one or more CODECS in the library 445 may reach improved levels better than the reference compression algorithm(s).

Nevertheless, when time constraints 435 (Figure 4A) are present (such as in real-time push or pull demand for the streaming media content), this process must eventually be stopped at some point so that a particular frame or series of frames being processed may be compressed 575 and delivered 580 to the destination without unacceptable delay by timer 435. Then, the next frame or series may be operated upon by the neural network 440 within the CODEC operating system. These endpoints may be defined by reaching a predetermined desired result, such as for example but without limitation: (i) reaching a predetermined percentage (%) compression efficiency, such as for example as compared to the reference standard; or (ii) reaching a predetermined or imposed time limit set on the process, such as for example according to a time related to the buffer time (e.g. 15 seconds); or (iii) the earlier occurrence of either (i) or (ii). In any event, though an endpoint is reached for choosing the appropriate CODEC and performing the compression 575 and delivery 580 operations, this does not mark an endpoint for the neural network 440 training which continues. The information that is gathered through

each loop in the process is stored 550. When subsequent similar frames or system constraint parameters in an incoming frame are encountered 545 in the future, the stored information is remembered and retrieved by the neural network 440 for improving compression 575 and delivery 580 efficiency.

While many different communication protocols are contemplated, one particular embodiment which is believed to be beneficial uses a "full duplex network stack" protocol, which allows for bi-directional communication between the server and the client device. Again, while other protocols may be appropriate for a particular application, the full duplex system is preferred.

The system 400 just described addresses the difficulties encountered with previously known CODEC systems by utilizing the streaming media delivery architecture to overcome latency issues and the embedded neural network 440 to overcome speed concerns. The system 400 is then able to reconfigure the algorithms used for compression in the neural network 440, the goal being to achieve optimum results every time over any network configuration.

A wide variety of CODECS may be used within the CODEC library 445 according to the overall compression systems and methods just described, though beneficial use of any particular CODEC according to the invention contemplates such CODEC taken either alone or in combination with other CODECS. For example, an appropriate CODEC library 445 may include one or more of the following types of CODECS: (i) block CODECS (e.g. MPEG versions, such as Microsoft Media™ or QuickTime™); (ii) fractal CODECS; and (iii) wavelet CODECS (e.g. Real™). According to another aspect, an appropriate CODEC library 445 may include one or more of the following types of CODECS: (i) motion predictive CODECS; and (ii) still CODECS. Still further, the CODEC library 445 may contain one or more of the following: (i) lossy CODECS; and (ii) lossless CODECS.

In one embodiment of the present invention, all of these different types of CODECS may be represented by the CODEC library 445 according to the invention; and, more than one particular CODEC of a given type may be included in the library. Or, various combinations of these various types may be provided in order to achieve the desired ability to optimize compression of a streaming media communication over a wide range of real-time variables in the signal itself, transmission channel constraints, or destination device constraints. Still further, an additional highly beneficial aspect of the invention allows for new CODECS to be loaded into the library 445 and immediately available for use in the neural network 440 compression/delivery system 400. Nevertheless, one particular example of a CODEC library 445 which is believed to be beneficial for use in optimally communicating a wide range of anticipated streaming media signals, and of particular benefit for image signals, includes the

Ex. 1018-2054

following specific CODECS: MPEG versions 1, 2, and 4 (e.g. Microsoft Media™ and QuickTime™); DUCK TruMotion™; ON2; Real Media™; MJPEG: H.261; H.263; H.263+; GIF; JPEG; JPEG2000; BMP; WBMP; DIVX.

The following are further examples of various aspects of the compression system and method just described that should be considered as broadly beneficial, both independently and in various combinations as is apparent to one of ordinary skill based at least in part on this disclosure. Further examples of such broad aspects are elsewhere provided in the "Summary of the Invention" as well as in the appended claims.

Use of neural networks 440 with artificial intelligence to achieve the various CODEC operations described is broadly and uniquely beneficial. In particular, a system and method is provided for pre-processing 410 of source data determined by application of learned responses to the signal quality, data content and format of the data. A system and method is provided for processing each unit (e.g. frame or block of frames) of source data by selection and application of a suitable CODEC (from a set of all available CODECS in the CODEC library 445) dependent upon observed characteristics of the source data and application of past-learned responses to compressing similar data. A system and method is provided for processing each unit of source data by setting a multiplicity of compression characteristics within a chosen compression algorithm to optimize capture and preservation of the original data integrity. Still further, each or all of the aforementioned signal processing steps is applied to each unique, sequential unit of signal data, e.g., signal clip, video frame, or individual packet as appropriate.

It is further contemplated that a CODEC management system 400 according to the invention provides a system and method for image processing that is adapted to normalize original source data/images as well as to resize and resample original data to fit the specification of the neural network processing module 440. An ability to serve any transmission or recording channel with a single system and with any source data stream is also provided. Moreover, the various systems and methods herein described, individually and beneficially in combination, are provided with compatibility to any connection or connectionless protocol, including but not limited to TCP, UDP, WTP/WDP, HTTP, etc.

The invention as herein shown and described also allows for highly beneficial applications for accelerating the learning rate of neural networks 440 while minimizing the data storage requirements to implement said networks. Different classes of data streams each have unique characteristics that require substantially greater processing by neural networks 440. For example, video data streams differ by prevalence and degree of motion, color contrast, and pattern and visibility of details. Greater

Ex. 1018-2055

processing requires longer times to reach optimal functionality. Greater processing also requires more predictive library storage, often growing to unlimitedly large sizes. For real-time neural network processing, processing time and storage can be minimized to greatly increase functionality by providing pre-developed predictive libraries characteristic of the class of data stream.

Accordingly, the following are examples of aspects of the pre-trained neural network 440 aspects of the invention that should be appreciated as broadly beneficial, both independently and in combination (including in combination with other embodiments elsewhere herein shown and described). A system and method is provided that creates and uses artificial intelligence in a neural network 440 and pre-trains that intelligent network for use in solving a problem, which problem may be for example but not necessarily limited to streaming media compression according to a particular beneficial aspect of the invention. A system and method is also provided for subdividing the universe of problems to be solved into useful classes that may be processed according to a learned history by the intelligent network.

An intelligent streaming media delivery system and method is also provided according to the invention that manages content transmission based on end-user capabilities and transmission channel constraints, such as for example, but without limitation, available transmission speeds or bandwidth, and Internet congestion. The data compression and delivery system 400 utilizes a computer implemented intelligence process, such as an artificial intelligence process based on a neural network to analyze aspects of the connection (including without limitation differing bit rates, latencies, transmission characteristics and device limitations) to make modifications in the compression methodology and to manage Quality of Service ("QoS") 420 issues. Compressed, digital, restorable and/or decompressible data streams may be therefore delivered to a multiplicity of different local and/or remote devices via a multiplicity of transmission mediums characterized by differing capabilities. In addition, a decompression system is provided for reproducing the decompressed data at the terminal device.

In one beneficial embodiment, a terminal device establishes a link with the system resident on a server node(s). Except for software normally required to establish communications, the terminal device might not initially have resident software embedded therein associated with the present system. Upon linking the terminal device to the server node, the system transmits a software agent to the terminal device that cooperates with other software modules on the server-side that together form the overall delivery system. The software agent informs the system of the terminal device configuration and processing capacities for decompressing and displaying the data. The software agent also reports

certain relevant information to the system of the characteristics of the communication channel between the terminal and the server. Such information includes, without limitation: latency, bandwidth, and signal path integrity. Based upon terminal device configuration and real time updates of channel characteristics and capabilities, the system actively manages transmission of the compressed data stream by varying parameters such as buffer length, transmitted bit rate, and error correction. The system also feeds operating conditions to the compression system to dynamically alter encoding and compression settings to optimize delivery of the data. The delivery software agent resident on the terminal device decompresses the data stream that is composed of segment-by-segment variations in compression/decompression algorithm and settings thereof. Dependent upon the terminal device configuration, and especially for very thin clients, instructions may be refreshed on a segment-by-segment basis for each decompression algorithm and encoding setting combination. Instructions for decompressing may also be kept resident if appropriate to the terminal device.

The software agent described for transmission to and operation by the destination device is therefore also considered a highly beneficial aspect of the compression/delivery systems and methods described. By delivering the software agent to the device from the source, a wide range of existing destination devices may be used for communication according to methods that may include variable uses of one or more algorithms or other operations at the transmission source. In other words, the destination devices may not be required to be "format-specific" players as is required by much of the conventional streaming and static media communication systems. Also, by providing the destination agent with a diagnostic capability, diagnostic information may be gathered at the destination device and transmitted back to the source in a format that is compliant for use by the source in its neural network process for achieving the proper CODEC operation for a given set of circumstances.

The use of a client-side agent to supply quality of service information including client-side device data and communication channel status in real time is therefore also believed to be broadly beneficial beyond the specific applications and combinations of other aspects of the invention also herein provided. In addition, the processing of each unit of compressed, transmission-ready data to accommodate client-side device and real-time communication channel conditions is also broadly contemplated as having broad-reaching benefits. Still further, a system and method is described that provides instructions to a client-side agent to enable decompression of each sequential, uniquely compressed unit of data. Therefore, another broad benefit of the invention provides a destination device (such as from the transmission source as herein described for the particular embodiments) with a CODEC that is adapted to decompress a compressed representation of an original media signal into a

Ex. 1018-2057

decompressed representation based upon variable parameters related to at least one of the following: aspects of the original media signal, transmission channel constraints, and destination device constraints. In another broad aspect, the destination device is adapted to use a CODEC that is chosen from a library of CODECS based upon a parameter related to an aspect of the original media signal.

The systems and methods herein described are also considered applicable to the signal processing of each unique, sequential unit of signal data, e.g., signal clip, video frame, or individual packet as appropriate. In addition, the system and its various sub-systems may also be purely software that must be loaded into each appropriate device, or it may be embedded in a host hardware component or chip, e.g. on the server side, or in certain circumstances, on the client side (e.g. various aspects of the destination agent), or for example may be stored such as in flash memory.

The various aspects of the media compression system and method just described are considered beneficial for use according to a wide range of known and soon anticipated media communication needs, including for example according to the various communications devices, communication/transmission channel formats and standards, and media types and formats elsewhere herein described (e.g. in the "Background" section above).

However, for the purpose of further understanding, Figure 6 shows a schematic view of the overall streaming media communications system 600 as specifically applied to "video-on-demand" aspects according to one embodiment of the present invention, wherein many different end users 610 – 620 at many different locations may request and receive, real-time (e.g. without substantial delay), pre-recorded video from a remote source. Further to the information provided in Figure 6, at least one specific implementation of the media communication system 600 delivers the following types of video at the following bit-rates (denotes compressed representations of original signals that are convertible by a destination device to decompressed representations having no or insubstantial loss as observed by the eye of the typical human observer): VHS-format video as low as about 250Kbs; DVD-format video at about 400 Kbps; and HDTV-format video at about 900Kbps. According to these speeds, it is believed that video-on-demand may be provided by telephone carriers over resident transmission line channels, such for example over existing DSL lines 630 - 640.

However, as available bandwidth and mass communication continue to present issues, it is believed that even greater efficiencies may be achieved resulting in delivery of compressed representations of these types of video signals at even lower bit rates. Again, as elsewhere herein described, the compression efficiencies of the invention are closely related to and improve as a function of the processing power made available to the neural network 440, and the neural network's 440

continued learning and training with respect to varied types of media. These resources may even make more remarkable compression efficiencies achievable without modification to the fundamental features of the present invention.

Therefore, the following are further examples of transmission rates for certain compressed video signals that are believed to be desirable and achievable according to one embodiment of the invention: VHS-format video as low as about 200Kbps, more preferably as low as about 150Kbps, and still more preferably as low as about 100Kbps; DVD-format video as low as about 350Kbps, more preferably as low as about 300Kbps, and still more preferably as low as about 250Kbps; and HDTV-format video as low as about 800Kbps, and still more preferably as low as about 700 Kbps.

Moreover, at least one implementation of the media communications system 400 of one embodiment of the invention delivers 20-24 frames/sec color video at a transmission rate of 7 Kbps. This is believed to enable substantial advances in communication of streaming media signals via to wireless destination devices via the WAP Gateway, as is further developed elsewhere hereunder.

It is also to be appreciated that, while video communication has been emphasized in this disclosure, other types of streaming or static media are also contemplated. For example, at least one implementation of the compression and delivery embodiments has been observed to provide substantially CD-quality sound (e.g. via compressed representations of original signals that are convertible by a destination device to decompressed representations having no or insubstantial loss as observed by the ear of the typical human observer) at a bit-rate of about 24 Kbps. At these rates, audiophile-quality sound may be delivered for playing over dial-up modems. However, with further regard to available resource commitment and extent of neural network training, it is further contemplated that the invention is adapted to deliver CD-quality sound at speeds as low as about 20Kbps, and even as low as about 15 Kbps or even 10Kbps.

Wireless Audio Communications System

It is further contemplated that the streaming media communication system of the invention has particularly useful applications within wireless audio communications networks, and in particular cellular telephony networks. Therefore, Figures 7 and 8 schematically show, with respectively increasing amounts of detail, streaming media communications systems 700 and 800 respectively specifically applied to wireless audio communications systems according to certain specific, respective embodiments of the present invention. While particular devices, system parameters, or arrangements

Ex. 1018-2059

of communicating devices shown are believed to be beneficial in the overall application of the invention, they are not to be considered limiting and may be suitably replaced with other substitutes according to one of ordinary skill based upon this disclosure. The various wireless communications systems 700 and 800, standards, and protocols referenced elsewhere in this disclosure are thus incorporated into this section for the purpose of integration with the various aspects of compression, delivery, decompression, and transcoding according to one embodiment of the invention.

Combination of the communications system 400 of one embodiment of the present invention with the other components of a cellular communications network allows for the enhanced compression, delivery, and decompression according to the invention to manifest in an increased quality of service for wireless audio communications. Improvements in cellular communications according to the invention include, without limitation, the following examples: increasing available bandwidth, extending range of reception, and providing graceful degradation while maintaining connectivity during periods of low signal quality or reception levels.

More specifically, cellular telephony signals are characterized by relatively high degrees of variability, due for example to the roaming positions of clients, and limited cell ranges, atmospheric conditions, and significantly limited and changing available bandwidths over daily use cycles. Therefore, a self-optimizing CODEC management system according to the present invention is particularly well suited to adjust the appropriate communications and compression modalities to the changing environment. At the very least, the increase in compression efficiency and resulting decrease in bandwidth used for given signals is a valuable achievement as wireless channel traffic continues to congest.

In one particular regard, the increased compression efficiency according to the present invention is well applied to improving bandwidth issues during "soft hand-offs" between cells, as illustrated in Figure 9. During cellular phone communications, whenever a transmitter or receiver migrates between cell coverage zones, communications bandwidth requirements and resultant costs are increased by systemic requirement to "pass off" active communications between cells. The act of passing off the communication results in a "backhaul" channel from the previously active cellular transmitter to a central office for forwarding to a newly active cellular transmitter. The backhaul channel represents a significant use of bandwidth. Savings will result from increased compression. As Figure shows, such "backhauling" may include a doubling (media sent back from first cell being left and resent to second cell for transmission) or even a quadrupling (overlapping communication from both first and second cells) in the bandwidth used for communicating a particular signal.

Ex. 1018-2060

The media communications system 400 of the present invention may recognize when backhaul is occurring, such as according to the transmission channel diagnostics provided in the software agent(s), and may respond by adjusting the degree of compression to compensate.

WAP Video Gateway

With a particular view of the rapid growth observed and predicted in the wireless or mobile Internet, embodiments of the present invention contemplate application of the intelligent compression/delivery/ decompression embodiments in combination with WAP Gateway functionality.

A system and method is therefore also provided according to the invention for encoding, compressing and transmitting complex digital media (e.g., video pictures) via bandwidth-constrained wireless communications systems utilizing Wireless Applications Protocol (WAP). In one embodiment, data is processed by the system, resident at a server node(s), employing neural networks with artificial intelligence. Sample segments of data are captured from the input stream and processed to comply with requirements unique to the class of clients. As is described in detail above, the system correlates the continuously varying digital data streams' characteristics with libraries of pre-developed experientially learned rules and with externally imposed constraints to optimally choreograph the coherence, continuity and detail of the data as ultimately received, decoded and presented at the client interface.

A gateway provided with the added functionality of the streaming media communications system herein described is shown schematically in Figure 8. According to the WAP gateway system 830 , a client agent is provided that is adapted to run on a variety of platforms, and requires no specialized hardware to decode the video streams. According to use of the streaming media delivery system of the invention elsewhere herein described, the viewer of the WAP device maintains constant communication with the system server upstream, such that the user-side client 825 may provide the encoding platform with relevant information for streaming media communication, including without limitation: available screen size, processing power, client operating system and browser version, connection speed and latency, thereby allowing the streaming media delivery system to tailor the stream to each individual client it "talks" to. Accordingly, an AI driven server 830 incorporating the AI compression as herein described may be combined with a WAP Gateway 830, combining the necessary WAP to TCP/IP protocol (or other protocol, e.g. dual server stack) translation with a Video and Audio Server 835 employing compression, delivery, and decompression systems and methods

Ex. 1018-2061

herein described. The WAP Gateway 830 may further include a video transcoder, such as for example incorporating the transcoder systems and methods herein described. An appropriate host architecture according to this system (not shown) generally includes a rack mount system running Linux OS with a modified WAP Gateway 830 or as a software plug-in to existing servers.

This WAP gateway system 830 may be further provided in a Master/Slave relationship as another beneficial aspect of the overall streaming media delivery architecture (applicable to other delivery systems other than specifically wireless). Various content distribution networks, such as available through Akamai and Inktomi, have capitalized on the concept of improving data delivery over the Internet by using "smart caching" on servers which reside on the borders of the Internet. Such a Master/Slave relationship is maintained by the present system wherein a Master Server resides at the source of the content to be delivered and Slave Servers reside on the borders. These servers communicate "intelligently" to optimize the content delivery over the Internet and reduce latency, bandwidth and storage requirements, improving the overall quality of the video/audio stream to the end-user and decreasing the cost of media delivery to the content provider.

The WAP gateway 830 of the present invention supports continued growth in mobile communications, as large telecommunications operators are transitioning to multi-service broadband networks, and as the number of subscribers to the mobile Internet continues to expand rapidly. In particular, mobile communications is a broad class of systems and protocols, each having its own constraints and needs for interacting devices to communicate streaming media. The Gateway 830 in a particularly beneficial aspect may support a variety of "2G" systems with upgradability for upcoming "2.5G" and "3G" network technologies (numerical progression of systems generally represents progression of Internet-enabled capabilities).

The following Table 3 provides examples of known mobile communication standards, and provides certain related information used by the AI system of the present invention for optimizing communication of streaming media amongst the field of mobile destination devices as media players:

Table 3: Existing/Soon Anticipated Mobile Communications Standards

MODE	**BAUD RATE (generally)**
GSM (2G)	9.6 Kbps
CDMA	9.6 Kbps
TDMA	14.4 Kbps
CDPD	14.4 Kbps

Ex. 1018-2062

iMODE	128 Kbps
GPRS	144 Kbps
WCDMA or CDMA2000	144 Kbps to 2 Mbps
GSM (3G)	2 Mbps

In addition, the present invention is particularly beneficial in its ability to stream a wide variety of media signals to various different types of wireless communications devices. Examples of wireless communications devices that are appropriate for use with the streaming media communications systems and methods of the invention, and which the systems and methods support interchangeably, are provided in the following Table 4:

Table 4: Examples of Internet-enabled PDA's

DEVICE	MAKE	SPEED	MEMORY	SCREEN DEPTH	SCREEN SIZE	MODEM TYPE	CONNECT SPEED
iPAQ	Compaq	206 MHz	16-64 Mb	12 b/pixel color	320x240	External (e.g. CDPD)	9600-14.4 Kbps
PalmVII	Palm	33 MHz	4 -16Mb	4 b/pixel b/w 8 b/pixel color		Internal	14.4 Kbps
Handspring	Palm	33 MHz	4 -16Mb	4 b/pixel b/w; 8 b/pixel color		External	14.4 Kbps
Blackberry	Research-In-Motion	33 MHz	4 Mb	2 b/pixel b/w		Internal	9.6-14.4 Kbps
Jornada	HP	133 MHz	16-32 Mb	18 b/pixel	320x240	External	9.6-14.4 Kbps

Casseopeia ▪▪▪▪▪▪▪▪▪	Casio	150 Mhz	16-31 Mb	12 b/pixel	320x240	External	9.6-14.4 Kbps

Various specific examples are described later below that provide observations of actual wireless Internet applications of the invention as herein described. Such examples include use of a CODEC library according to varied parameters associated with at least the following (without limitation): destination wireless communication device; transmission channel; communications protocol; and the respective streaming media signals themselves. The various particular features of the systems and methods used according to these examples are contemplated as further defining independently beneficial aspects of the invention.

Shared Interactive Environment

A system and method is also provided according to the invention for enabling real-time remote client interaction with a high-definition, multi-dimensional, multi-participant simulated environment without the need for significant client-side processing capacity. More specifically, Figure 10 shows an overall streaming media communication system as applied to shared interactive gaming according to the invention.

This system includes: (i) a proxy server; (ii) graphics rendering capabilities; (iii) a client software agent for feedback of client inputs to the game; (iv) a client software agent for supporting the delivery system of the invention; and (v) streaming from the server to the client. It is contemplated that for multiple clients, which typically represent shared interactive gaming by design, multiple components as just described are provided to support each client.

The interactive gaming embodiments contemplate implementation of data compression and delivery embodiments with devices that are also destination devices for compressed signals from other like, remotely located device systems. This arrangement is broadly beneficial, such as for example in further interactive media implementations such as video conferencing and the like. Accordingly, each remote system is both a source and a destination device, and sends and receives agents between it and other remote systems.

Destination Device

Although the communications systems of the present invention enables communication of streaming media signals to a wide variety of destination devices, a further contemplated feature of the invention provides a remote receiver to be housed as a destination device/player by client users. This set-top player may be adapted to serve at least one, though preferably multiple ones, and perhaps all, of the following: Video on Demand (VOD); Music on Demand (MOD); Interactive Gaming on Demand (IGOD); Voice Over Internet Protocol ("VoIP"), any technology providing voice telephony services over IP connections; Television Web Access; Digital Video Recording to record, pause, and playback live television; e-mail; chat; a DVD player; and other applications apparent to one of ordinary skill. All of this may be delivered to existing televisions in the comfort of users' own homes. Moreover, clients utilizing this box, or other systems interfacing with the communications system of the invention, may receive DVD quality video and surround sound over cable and DSL connections.

EXAMPLES

For the purpose of further illustrating the highly beneficial results that may be achieved according to the invention, the following are examples of specific embodiments that have been used for different types of streaming media communication, including observed results with pertinent discussion. These examples illustrate communication the same pre-recorded video over different transmission channels and to different destination devices, wherein the pre-recorded video has the following originating properties: 720lines of resolution and 32bits of color information, an originating file size of about 1.4Gigabytes.

Example 1

An "iPAQ" model 3650 hand-held PDA (commercially available from Compaq, Inc. for approximately $500 at the time of this disclosure) was provided. The PDA was interfaced with a 14.4 Kbps (max) wireless CDPD modem ("AirCard 300" wireless external modem, commercially available from Sierra Wireless for approximately $200 at the time of this disclosure) using an extension assembly (iPAQ™ PCMCIA expansion sleeve from Compaq, Inc.) with a PCMCIA card slot that couples to the wireless modem. The iPAQ™ used is generally characterized as having the following processing parameters: 206 MHz processor; 32 Mb memory; 12 b/pixel color; 240X320 screen dimensions; PocketPC™ operating system version 3.0 from Microsoft Corp. and stereo sound. The iPAQ™ was

Ex. 1018-2065

connected to the Internet in San Francisco, California via the interfaced CDPD modem over the AT&T cellular wireless carrier system at a connection bandwidth of about 13.3Kbit/sec. A server located in San Jose, California (approximately 50mi away) was contacted by the PDA employing the http and rtsp protocols, and the PDA was used to initiate a request for a pre-recorded video having the following originating properties: 720lines of resolution and 32bits of color information, the originating file size was 1.4Gigabytes. Within about seven seconds, a compressed approximation of the pre-recorded video was received, decompressed, and displayed by the PDA on the PDA's screen. The entire video was seen at 240x320x12bpp resolution in full motion without observable delays or defects.

Example 2

A "Jornada™" model 548 hand-held PDA (commercially available from HP, Inc. for approximately $300 at the time of this disclosure) was provided. The PDA was interfaced with a 9.6 Kbps (max) wireless CDMA phone ("Motorola i85s" wireless external digital cellular phone, commercially available from Motorola authorized vendors for approximately $200 at the time of this writing) using adaptor cables (Motorola and HP RS-232 standard interface cables from Motorola and HP.) that couple the phone and PDA together to form a wireless modem. The Jornada model PDA device used is generally characterized as having the following processing parameters: 133 MHz processor; 32 Mb memory; 12 b/pixel color; 240X320 screen dimensions; PocketPC™ operating system version 3.0 from Microsoft Corp. and stereo sound. The Jornada™ was connected to the Internet in Newark, NJ via the interfaced CDMA phone/modem over the Nextel digital cellular wireless carrier system at a connection bandwidth of 8Kbit/sec. A server -located in San Jose, California (approximately 2900mi away) was contacted by the PDA employing the http and WDP protocols, and the PDA was used to initiate a request for a pre-recorded video having the following originating properties: 720lines of resolution and 32bits of color information, the originating file size was 1.4Gigabytes. Within about seven seconds, a compressed approximation of the pre-recorded video was received, decompressed, and displayed by the PDA on the PDA's screen. The entire video was seen at 176x120x8bpp in full motion without observable delays or defects.

Example 3

A "Set-top Box" model st850 book PC (commercially available from MSI, Inc. for approximately $300 at the time of this writing) was provided. The Set-top Box was interfaced with a 10 Mbps (max) ethernet/802.11 connection using CAT5 ethernet cables (Generic) that couple the Set-top Box to a broadband connection (DS3). The Set-top Box used is generally characterized as having the following processing parameters: 400 MHz processor; 64 Mb memory; 32 b/pixel color; 720 lines of screen resolution; Windows CE operating system version 2.11 from Microsoft Corp. and AC3 digital 6 channel surround-sound. The Set-top Box was connected to the Internet in Newark, NJ via the interfaced shared DS3 connection over the Alter.Net Internet Backbone at a connection bandwidth of 376Kbit/sec. A server located in San Jose, California (approximately 2900mi away) was contacted by the Set-top Box employing the http and rtsp protocols, and the Set-top Box was used to initiate a request for a pre-recorded video having the following originating properties: 720lines of resolution and 32bits of color information, the originating file size was 1.4Gigabytes. Within
About nine seconds, a compressed approximation of the pre-recorded video was received, decompressed, and displayed by the Set-top Box on a commercially available reference monitor's (Sony) screen. The entire video was seen at 720linesx32bpp in full motion without observable delays or defects.

While various particular embodiments have been herein shown and described in great detail for the purpose of describing the invention, it is to be appreciated that further modifications and improvements may be made by one of ordinary skill based upon this disclosure without departing from the intended scope of the invention. For example, various possible combinations of the various embodiments that have not been specifically described may be made and still fall within the intended scope of the invention. According to another example, obvious improvements or modifications may also be made to the various embodiments and still fall within the intended scope of this invention.

What is claimed is:

1. A system for processing a media signal, comprising:

a searchable CODEC library that is adapted to store a plurality of separate and unique CODECS and also to be accessed by and searched by at least one of an artificial intelligence (AI) system and an operating system, such that each CODEC stored in the CODEC library may be individually located and accessed for use by at least one of the AI system and operating system in order to compress the media signal for transmission from a source to a destination device.

2. The system of Claim 1, wherein the CODEC library comprises at least one CODEC that is of at least one of the following three types of CODECS: block CODECS; fractal CODECS; and wavelet CODECS.

3. The system of Claim 2, wherein the CODEC library comprises:
a first CODEC of a first type on the three types, and
a second CODEC of a second type of the three types.

4. The system of Claim 3, wherein the CODEC library comprises:
a first CODEC of a first type of the three types,
a second CODEC of a second type of the three types; and
a third CODEC of a third type of the three types.

5. The system of Claim 4, wherein the CODEC library comprises:
a first CODEC that is a motion predictive CODEC; and
a second CODEC that is a still CODEC.

6. The system of Claim 5, wherein the CODEC library comprises:
a first CODEC that is a lossy CODEC; and
a second CODEC that is a lossless CODEC.

7. The system of Claim 1, further comprising:

a registry associated with the CODEC library and that is searchable in order to search and locate a particular CODEC within the CODEC library.

Ex. 1018-2068

8. A system for communicating a media signal from a source to a destination device over a transmission channel, comprising:

a destination agent that is adapted to be used by the destination device to communicate with the source and to receive a compressed representation of the media signal from the source and to decompress the compressed representation into a decompressed representation of the media signal such that the decompressed representation may be stored or used by the destination device.

9. The system of Claim 8, wherein the destination agent comprises:

a diagnostic agent that is adapted to provide diagnostic information for transmission to a neural network associated with the source, which diagnostic information represents an ability of the destination device to receive, store, process, or display the media signal; and

a decompression agent that is adapted to decompress the compressed representation of the media signal into the decompressed representation of the signal to be stored or played by the destination device.

10. The system of Claim 9, wherein the destination agent further comprises:

a decompression agent that is adapted to receive a compressed representation of the media signal and also to receive a CODEC decompressor associated with the compressed representation of the signal from the delivery system, and that is adapted to use the CODEC decompressor to decompress the compressed representation of the signal into a decompressed representation of the signal to be stored or played by the destination device.

11. The system of Claim 10, wherein the destination agent is adapted to be stored and operated for decompressing and playing a media signal on a plurality of different destination devices each having different capabilities for decompressing, storing, or playing the media signal.

12. The system of Claim 11, wherein the destination agent is adapted to decompress a plurality of different compressed representations of the media signal by using different CODEC decompressors that are each associated with a corresponding different CODEC compressor used to compress the signal.

13. The system of Claim 12, wherein the destination agent is adapted to decompress the compressed representation of the media using a CODEC that is provided based upon at least one of the following parameters: a computer implemented previously learned behavior of the CODEC with

Ex. 1018-2069

respect to a reference media signal, a computer implemented previously learned behavior of the CODEC with respect to a prior attempt at compressing or decompressing the same media signal, a comparison of the CODEC's operation with respect to the media signal against a reference algorithm compression of the media signal, a learned constraint of the transmission channel, and a learned constraint of the destination device.

14. The system of Claim 13, wherein the destination agent is adapted to interchangeably use a block CODEC, a fractal CODEC, or a wavelet CODEC.

15. A system for communicating a media signal from a source to a destination device over a transmission channel, comprising:

a CODEC that is adapted to compress the media signal for optimized transmission along the communications channel and decompression by the destination device, wherein the compression is done by the CODEC based upon at least one of the following parameters: a previously learned behavior of the CODEC with respect to another reference signal, a previously learned behavior of the CODEC with respect to a prior attempt at compressing or decompressing the same media signal, a comparison of the CODEC's operation with respect to the media signal against a reference algorithm compression of the media signal, a learned constraint of the transmission channel, and a learned constraint of the destination device.

16. The system of Claim 15, wherein the CODEC is adapted to compress the media signal into n different compressed representations of the media signal that are adapted to be transmitted to the destination device at n unique bit rates, respectively.

17. The system of Claim 15, further comprising:

a searchable quality of service (QoS) library associated with the CODEC and that is adapted to be used by at least one of an artificial intelligence system or an operating system in order to determine an appropriate use of the CODEC with respect to the media signal based upon at least one QoS standard stored in the QoS standards library.

18. A system for processing a media signal, comprising:

Ex. 1018-2070

a CODEC operating system that is adapted to interface with a CODEC library and also with an artificial intelligence (AI) system in order to use the AI system to identify an appropriate CODEC from the library and to process the media signal with the CODEC.

19. The system of Claim 18, further comprising:

at least one CODEC associated with the CODEC operating system for use in processing the media signal based at least in part upon an operation by the CODEC operating system.

20. The system of Claim 19, further comprising:

a searchable CODEC library that is associated with the CODEC operating system and that is adapted to store a plurality of separate and unique CODECS, wherein the CODEC operating system is adapted to cooperate with the searchable CODEC library and also with the AI system in order to determine an appropriate CODEC stored in the CODEC library for use in processing the media signal.

21. The system of Claim 20, further comprising:

a searchable network transport standards library associated with the CODEC operating system and that is adapted to be used by at least one of an AI system or the CODEC operating system in order to determine an appropriate use of a CODEC with respect to the media signal based upon at least one network transport standard stored in the network transport standards library.

22. The system of Claim 21, further comprising:

a searchable quality of standard (QoS) library associated with the CODEC operating system and that is adapted to be used by at least one of an AI system or the operating system in order to determine an appropriate use of a CODEC with respect to the media signal based upon at least one QoS standard stored in the QoS standards library.

23. The system of Claim 22, further comprising:

a destination agent that is associated with the CODEC operating system and is adapted to be used by a destination device to communicate with a source also associated with the CODEC operating system to receive a compressed representation of the media signal from the source and to decompress the compressed representation into a decompressed representation of the media signal such that the decompressed representation may be stored or used by the destination device.

Ex. 1018-2071

24. A system for processing a media signal, comprising:

a destination device that is adapted to communicate with a source and to receive a compressed representation of the media signal from the source, and that includes a CODEC that is adapted to decompress the compressed representation into a decompressed representation based upon at least one of the following parameters: a previously learned behavior of the CODEC with respect to another reference signal, a previously learned behavior of the CODEC with respect to a prior attempt at compressing or decompressing the same media signal, a comparison of the CODEC's operation with respect to the media signal against a reference algorithm compression of the media signal, a learned constraint of the transmission channel, and a learned constraint of the destination device.

25. The system of claim 24, wherein the media signal is adapted to be used according to an original format according to an original set of parameters, and the destination device is adapted to process and display the decompressed representation of the media signal in another format according to another set of parameters that are different than the original set of parameters, such that the destination device is incapable of processing and displaying the media signal in the original format according to the original set of parameters.

26. The system of claim 25, wherein the CODEC is adapted to compress the media signal into n different compressed representations of the media signal that are adapted to be transmitted to the destination device at n unique bit rates, respectively.

27. The system of claim 26, wherein the n different compressed representations are adapted to be transmitted at least at n substantially different transmission rates that are distinguished based upon at least one of the following parameters: different transmission system standards; different destination device standards; and different media type standards.

28. A system for processing a media signal, comprising:

a CODEC that is adapted to perform at least one of compression or decompression on the media signal; and

an artificial intelligence (AI) system that is adapted to operate in conjunction with the CODEC in order to tune the operation of the CODEC with respect to the media signal, wherein the AI system is adapted to learn a behavior of the CODEC with respect to at least one parameter affecting the CODEC's operation, and also to modify the operation of at least one of the AI system

Ex. 1018-2072

itself or the CODEC based upon the learned behavior in order to increase the ability to provide the CODEC in an appropriate form for optimally compressing or decompressing the media signal.

29. The system of claim 28, wherein the CODEC comprises a discrete cosine transform CODEC.

30. The system of claim 29, wherein the CODEC comprises a fractal CODEC.

31. The system of claim 30, wherein the CODEC comprises a wavelet CODEC.

32. The system of claim 31, wherein the CODEC comprises a lossy CODEC.

33. The system of claim 32, wherein the CODEC comprises a substantially lossless CODEC.

34. The system of claim 33, further comprising:

a searchable CODEC library that is adapted to store a plurality of separate and unique CODECS,

wherein the CODEC is adapted to be stored in the searchable CODEC library, and the AI system is adapted to cooperate with the CODEC library in order to locate and access the CODEC so that the AI system may perform at least one operation with respect to the CODEC.

35. A system for processing a media signal, comprising:

a CODEC library that is adapted to store a plurality of separate and unique CODECS;

an artificial intelligence (AI) system associated with the CODEC library and that is adapted to perform an operation with respect to the CODEC library in order to determine an appropriate CODEC from the plurality of CODECS for use in processing the media signal;

a CODEC operating system associated with the CODEC library and also the AI system and that is adapted to control the operation of the AI system with respect to the CODEC library;

a source system that is adapted to compress the media signal based upon a CODEC from the CODEC library and based upon an operation of the AI system;

a destination system that is adapted to communicate with the source system and to receive a compressed representation of the media signal from the source system and decompress the compressed representation into a decompressed representation for use by the destination system; and

a communications system associated with the source system and also with the destination system so that the source system is adapted to transmit the compressed representation of the media signal to the destination system, and the destination system is adapted to receive the compressed representation and also to appropriately decompress the compressed representation into the decompressed representation for storage or use by the destination system.

Ex. 1018-2073

36. The system of claim 35, further comprising:

a searchable network transport standards library associated with the AI system and also with the CODEC operating system and that is adapted to be used by the AI system in order to determine an appropriate CODEC from the CODEC library for processing the media signal based upon at least one network transport standard stored in the network transport standards library.

37. The system of claim 36, further comprising:

a searchable QoS standards library associated with the AI system and also with the CODEC operating system that is adapted to be used by the AI system in order to determine an appropriate CODEC from the CODEC library for processing the media signal based upon at least one QoS standard stored in the QoS standards library.

38. The system of claim 37, wherein the AI system is adapted to determine an appropriate use of a CODEC from the CODEC library for processing the media signal based upon at least one of the following parameters: a previously learned behavior of the CODEC with respect to another reference signal, a previously learned behavior of the CODEC with respect to a prior attempt at compressing or decompressing the same media signal, a comparison of the CODEC's operation with respect to the media signal against a reference algorithm compression of the media signal, a learned constraint of the transmission channel, and a learned constraint of the destination device.

39. A system for communicating a media signal between a source and n unique destination devices each having a unique ability to process the media signal, wherein n is an integer that is equal to or greater than one, comprising:

a compression system associated with the source and which is adapted to compress the media signal into n uniquely compressed representations of the media signal,

wherein each of the n uniquely compressed representations is adapted to be transmitted from the source to a unique one of the n destination devices, and is adapted to be decompressed by the respective destination device into a unique one of n decompressed representations of the media signal to be played by the respective destination device.

40. The system of claim 39, wherein the compression system further comprises:

a searchable CODEC library that is associated with the compression system and that is adapted to store a plurality of separate and unique CODECS, wherein the compression system is

Ex. 1018-2074

adapted to compress the media signal into each of the n uniquely compressed representations based at least in part upon at least one CODEC stored by the CODEC library.

41. The system of claim 40, wherein the compression system further comprises:

a searchable network transport standards library associated with the compression system and that is adapted to be used by the compression system in order to determine at least one appropriate CODEC for compressing the media signal into the n uniquely compressed representations based upon at least one network transport standard stored in the network transport standards library.

42. The system of claim 41, wherein the compression system further comprises:

a searchable QoS standards library associated with the compression system and that is adapted to be used by the compression system in order to determine at least one appropriate CODEC from the CODEC library for compressing the media signal into the n uniquely compressed representations based upon at least one QoS standard stored in the QoS standards library.

43. The system of claim 42, further comprising:

a destination agent that is associated with the compression system and is adapted to be used by each of the n unique destination devices to communicate with the source, so that each of the n destination devices may receive a unique one of the n compressed representation of the media signal from the source system and to use an appropriate CODEC at least in part based upon a CODEC used by the compression system to create the respective compressed representation so that the respective destination device may appropriately decompress the respective compressed representation into an appropriate one of the decompressed representations of the media signal that may be stored or used by the respective destination device.

44. The system of claim 43, wherein the compression system is adapted to compress the media signal into each of the n different compressed representations based at least in part upon at least one of the following parameters: a previously learned behavior of at least one CODEC with respect to another reference signal, a previously learned behavior of at least one CODEC with respect to a prior attempt at compressing or decompressing the same media signal, a comparison of at least one CODEC's operation with respect to the media signal against a reference algorithm compression of the media signal, a learned constraint of at least one transmission channel, and a learned constraint of at least one destination device.

45. A system for communicating n uniquely compressed representations of a media signal from at least one source to a common receiver, comprising:

a destination device that is adapted to communicate with the at least one source and to receive each of the n uniquely compressed representations from the at least one source, wherein the destination device is further adapted to decompress each of the n uniquely compressed representations into n decompressed representations of the media signal and to play each of the n decompressed representations.

46. A system for communicating a media signal from a source to a destination device over a transmission channel, comprising:

a compression system that is adapted to receive information about a parameter of the transmission channel and to compress the media signal into a compressed representation of the media signal by using a compression technique that is based at least in part upon the parameter information.

47. A system for communicating n unique media signals between a source and a destination, comprising:

a compression system that is adapted to receive information about a parameter of the media signal and to compress the media signal into a compressed representation of the media signal by using a compression technique that is based at least in part upon the parameter information.

48. A system for compressing a media signal from a source for transmission to a destination device, comprising:

a compression system that is adapted to compress the media signal into a compressed representation of the media signal based upon at least one of a transmission channel constraint, a destination channel constraint, or a comparison of a parameter of the media signal against a prior compression operation of the compression system.

49. A system for decompressing a compressed media signal received from a source at a destination device, wherein the destination device is adapted to receive a compressed representation of the media signal from the source and also a decompression instruction from the source such that the destination device is adapted to decompress the compressed representation into a decompressed representation of the media signal based at least in part on the instruction.

Ex. 1018-2076

50. A method for constructing a neural network for use in compressing media signals, comprising:

providing a plurality of CODECS; and

pre-learning at least one parameter associated with each CODEC's compression performance with respect to a predetermined type of media signal in a manner……; and

remembering each pre-learned parameter in a manner such that at least a particular one of the CODECs may be chosen in the future to compress a particular new media signal based upon the pre-learned parameter of the particular CODEC.

51. The method of claim 50, further comprising:

forming a CODEC library with the plurality of CODECS;

compressing at least one predetermined type of a test media signal with each CODEC in the CODEC library;

automatically learning at least one parameter related to each CODEC's performance in compressing the at least one predetermined type of test media signal;

automatically remembering each such learned parameter in a manner such that a particular media signal to be compressed.

52. A system for communicating a media signal between a source and a destination at least in part over a wireless transmission channel, wherein a compressed representation is

a compression system that is adapted to compress the media signal into a compressed representation of the media signal that is further adapted to be transmitted to a wireless destination device over a wireless carrier; and

a neural network that uses artificial intelligence to optimize the compression of the media signal by the compression system by learning at least one of the following parameters: a constraint of the wireless destination device, a constraint of the wireless transmission carrier, and a comparison of a parameter of the media signal against a prior compression operation of the compression system.

53. A system for compressing a media signal for transmission from a wireless source to a destination device.

54. A system for compressing a media signal into a compressed representation of the media signal for transmission to a wireless destination device.

Ex. 1018-2077

55. A system for decompressing a compressed representation of a media signal into a decompressed representation of the media signal at a destination device, wherein the compressed representation is received from a source over a wireless carrier at the destination device.

56. A system for communicating a media signal over an IP network between a source and a destination device, wherein a compressed representation of the media signal is transmitted from the source to the destination device over the IP network.

57. A system for compressing a media signal into a compressed representation of the media signal, such that the compressed representation of the media signal may be transmitted from a source to a destination device over an IP network.

58. A system for decompressing a compressed representation of a media signal into a decompressed representation of the media signal, wherein the compressed representation is received at a destination device from a source over an IP network.

59. A method for communicating a media signal over an IP network, comprising:

using artificial intelligence to determine the most appropriate CODEC from a plurality of available CODECS for compressing and decompressing the media signal, wherein the appropriate CODEC is determined based upon at least one of the following parameters: a previously learned behavior of the CODEC with respect to another reference signal, a previously learned behavior of the CODEC with respect to a prior attempt at compressing or decompressing the same media signal, a comparison of the CODEC's operation with respect to the media signal against a reference algorithm compression of the media signal, a learned constraint of the transmission channel, and a learned constraint of the destination device.

60. The method of Claim 59, wherein the system is adapted to communicate a streaming media signal over the IP network.

61. A system for communicating an audio signal between a source and a destination over a transmission channel, wherein the audio signal is compressed to form a compressed representation of the audio signal that may be transmitted over the transmission channel to the destination device

Ex. 1018-2078

so that the destination device may decompress the compressed representation into a decompressed representation for storage or use by the destination device.

62. The system of Claim 62, wherein the system is adapted to communicate a streaming audio signal.

63. A system for compressing an audio signal into a compressed representation of the audio signal for transmission from a source to a destination device over a transmission channel.

64. A system for decompressing a compressed representation of an audio signal at a destination device for storage or use by the destination device, wherein the compressed representation is received by the destination device from a source over a transmission channel.

65. A method for communicating a streaming audio signal from a source to a destination device over a transmission channel, comprising:

delivering CD-quality music from the source to the destination device over the transmission channel at a transmission rate that is as low as about 25 Kbps.

66. The method of claim 65, wherein the CD-quality music is delivered by compressing a source audio signal into a compressed representation and delivering the compressed representation over the transmission channel to the destination device at the transmission rate, wherein the compressed representation may be decompressed by the destination device into a decompressed representation that is substantially CD-quality representation of the original audio signal that may be stored or played by the destination device.

67. A system for communicating a video signal between a source and a destination over a transmission channel, wherein the streaming video signal is compressed into a compressed representation that may be transmitted from the source to the destination device over the transmission channel and decompressed into a decompressed representation by the destination device for storage or playing by the destination device.

68. A system for communicating a streaming video signal between a source and a destination, comprising:

a media processing module;

a dynamic player module;

an image processor;

a baseline snapshot module;

a signal classifier;

a plurality of CODECS dependent neural networks processors;

a CODECS library;

a network layer input module;

a network layer output module; and

a timer.

69. The system of Claim 68, further comprising a dynamic client request processing module.

70. The system of Claim 69, further comprising a device and network parameters measurement module.

Ex. 1018-2080




FIGURE 1A
(PRIOR ART)

Ex. 1018-2081




FIGURE 1B
(PRIOR ART)

Ex. 1018-2082




FIG. 1C
(PRIOR ART)

Ex. 1018-2083




FIGURE 1D
(PRIOR ART)

Ex. 1018-2084




FIGURE 1E
(PRIOR ART)




FIGURE 2

Ex. 1018-2086




310
Live Buffer = Cache
V1
V2
V3
V4
311
312
313
314
300
Video 1
Video 2
Video 3
Video 4
Network
220

FIGURE 3

Ex. 1018-2088

FIGURE 4A



Ex. 1018-2089





FIGURE 4B

Ex. 1018-2090

FIGURE 5






FIGURE 6

Ex. 1018-2091




FIGURE 7





Video and Audio Content Server
835
Internet or Other Network
830
AI Compression Server and WAP Gateway
Comp AI
Transcoder
Decomp AI
Protocol Gateway
WAP Stack TCP/IP
Wireless Network
820
Wireless Base Station
825
Mobile Phone
PDA
815
810
800

FIGURE 8


FIG. 9



Ex. 1018-2094



Browsing via the Set Top Box



Interactive Gaming

Fig. 10

Ex. 1018-2095

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US02/30874

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G06F 15/16
US CL : 709/231,232,217-219,250,220; 704/243

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
U.S. : 709/231,232,217-219; 345/335,327

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 6,195,692 B1 (HSU) 27 Febuary 2001, column 5 lines 4-19,	1-69
Y	US 6,243,676 B1 (WITTEMAN) 5 June 2001, column 7 line 55-col 8 line 56,	1-69
Y	US 6,115,755 A (KRISHAN) 5 September 2000, column 3 lines 19-45, column 4 lines 54-67	1-69
Y	US 6,085,236 A (LEA) 4 July 2000, column 18 lines 9-20, col 26 line 59-column 27 line 4,	1-69

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
10 December 2002 (10.12.2002)	15 JAN 2003
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703)305-3230	Authorized officer Mark Powell Telephone No. 703-305-9703

Form PCT/ISA/210 (second sheet) (July 1998)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
13 September 2001 (13.09.2001)

PCT

(10) International Publication Number
WO 01/67264 A1

(51) International Patent Classification[7]: G06F 15/16

(21) International Application Number: PCT/US01/40264

(22) International Filing Date: 8 March 2001 (08.03.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/520,434 8 March 2000 (08.03.2000) US

(71) Applicant *(for all designated States except US)*: **STREAMCENTER, INC.** [US/US]: 1512 Wellington Place, Aberdeen, NJ 07747 (US).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **MOGHE, Pratyush** [US/US]; 3002 Cricket Circle, Edison, NJ 08820 (US).

(74) Agents: **DIPPERT, William, H.** et al.; Cowan, Liebowitz & Latman, P.C., 1133 Avenue of the Americas, 35th Fl., New York, NY 10036 (US).


(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States *(regional)*: ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:
— *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS AND METHOD FOR PREDICTABLE AND DIFFERENTIATED DELIVERY OF MULTIMEDIA STREAMING ON THE INTERNET



(57) Abstract: The inventive method detects network congestion which interferes with streaming of multimedia audio and video packets from and reacts to it and guarantees delivery of packets. The streaming of the multimedia audio and video packets is performed when a server process executing on a sending computing device sends the packets to a player process executing on a receiving computing device via a network, such as the Internet. The detection of the network congestion is performed by communicating configuration information including network parameters from a service manager via the network to the at least one sending computing device and to the at least one receiving computing device. The network congestion (80) is then confirming by transmitting and retracting network probes. At least one buffer management technique is executed to limit degradation in the streaming of the packets. The end of the network congestion is detected by transmitting and retracting said network probes and the rate of streaming of the packets is configured accordingly (82, 84).

WO 01/67264 A1

APPARATUS AND METHOD FOR PREDICTABLE AND DIFFERENTIATED DELIVERY OF MULTIMEDIA STREAMING ON THE INTERNET

TECHNICAL FIELD

This invention relates to the field of multimedia audio and video streaming on the Internet, and more particularly, to an apparatus and method for predictable and differentiated delivery of multimedia streaming on the Internet.

BACKGROUND OF THE INVENTION

Multimedia streaming involves broadcast of audio and video information from content providers called streaming servers or senders via the Internet to clients or receivers on user computing devices called streaming players. Real-time delivery of the multimedia streaming on the Internet is inherently uncontrollable and consequently unpredictable. When an Internet delivery path is congested, packets of multimedia streaming are typically dropped, thus causing degraded audio and video playback to be received by the streaming players. Typically, manifested forms of congestion can be classified into two types: instantaneous and sustained (longer-term). Instantaneous congestion is caused by random variations in the arrival patterns of packets of multimedia streaming at different Internet routers and switches, and due to the varying sizes of these packets.

These variations cause varying amounts of delay as the packets of multimedia streaming travel from the streaming server to the streaming receiver. If the delay accumulates beyond a certain point, the packets of multimedia streaming can get lost. This type of congestion typically causes sporadic delays and losses of over hundreds of milliseconds to a few seconds, and is hence referred to as "instantaneous congestion." In contrast, sustained congestion is longer-term and results during periods of excessive demand by the streaming players, e.g., demand for multimedia streaming from popular websites over the network paths on the Internet. During these periods, packet traffic surges can overwhelm the packet buffers in network routers, which are network traffic routing and forwarding computing devices, and packets of multimedia streaming can get

lost in bursts. This is similar to a rush-hour traffic scenario on highways at peak hours. Unlike instantaneous congestion, sustained congestion can last from tens of seconds up to a few minutes.

It is well known that instantaneous congestion is an easy problem to solve. The client or the streaming player can buffer incoming packets of multimedia streaming for a short duration before playback. This reduces the effect of short-term delay between packets of multimedia streaming. Additionally, by requesting that a lost packet be immediately retransmitted, the streaming player can counter the loss of packets of multimedia streaming due to instantaneous congestion. Several existing streaming systems use these techniques, i.e., short-term buffering along with retransmits of lost packets, to isolate the streaming player from the effects of instantaneous congestion. Examples of these systems include the Robust-User Datagram Protocol (UDP) feature in the Real system from Real Networks and the NetShow 3.0 MediaPlayer from Microsoft.

The problem of sustained congestion is harder to solve. This difficulty relates to the fact that the Internet delivery lacks a uniform real-time control. Several standardization and research efforts have proposed ways to introduce such control; however, none have succeeded in creating a global Internet standard. The referred to standardization and research efforts include the following:

1. L. Kleinrock, "On Flow Control in Computer Networks", International Conference on Communications (ICC'78), pages 27.2.1-27.2.5;
2. D.E. Comer, R. S. Yavatkar, "A Rate-based Congestion Avoidance and Control Scheme for Packet Switched Networks", The 10th International Conference on Distributed Computing Systems, pages 390-397, 1990;
3. K.K. Ramakrishnan, R. Jain, "A Binary Feedback Scheme for Congestion Avoidance in Computer Networks", ACM Transactions on Computer Systems, Vol. 8, No. 2, May 1990, Pages 158-181; and
4. D. Mitra, "Asympotically Optimal Design of Congestion Control for High Speed Data Networks", IEEE Transactions on Communications, Vol. 40, No. 2, February 1992.

For example, the RSVP effort, described in Braden, R., Zhang, L., Berson, S., Herzog, S., and Jamin, S., "Resource Reservation Protocol (RSVP) - Version 1

Ex. 1018-2099

Functional Specification", RFC 2205, Proposed Standard, September 1997, seeks to add "quality of service" control within each network router and switch within the Internet. Another effort that seeks to create fast paths on the Internet is the "differentiated service" effort within the Internet Engineering Task Force (IETF) described in the following publications:

1) Nichols, K., Jacobson, V. and Zhang, L., "A Two-bit Differentiated Services Architecture for the Internet", Internet Draft, December 1997;
2) Ferguson, P., "Simple Differential Services: IP TOS and Precedence, Delay Indication, and Drop Preference", Internet Draft, November 1997; and
3) Clark, D. and Wroclawski, J., "An Approach to Service Allocation in the Internet", Internet Draft, July 1997.

The problem with these approaches is that they require structural changes throughout the Internet. This requirement assumes an explicit cooperation between various managers of the equipment comprising the Internet, which is an impractical assumption. Consequently, these efforts have stalled or are expected to have limited success. An alternative approach is to offer "adaptive applications". This approach proposes that application content be adapted based on the level of congestion. Methods based on this approach degrade the "experience" of an application in a controlled manner, but do not attempt to guarantee predictability or isolation from congestion effects. This approach is discussed in I. Busse, B. Deffner, H. Schulzrinne, "Dynamic QoS Control of Multimedia Applications based on RTP", May 30, 1995 and Real Networks, "White Paper on SureStream Technology", Available at http://www.real.com/devzone/library/whitepapers/surestrm.html.

What is needed is a "delivery framework" that will isolate streaming players from the effect of sustained congestion by providing a "predictable" delivery. Furthermore, there is also a need for a "differentiated streaming" framework that will provide for multiple levels of delivery isolation to the streaming players, without requiring structural changes in the Internet, as in K. Nichols et al., P. Ferguson and D. Clark, discussed above.

Ex. 1018-2100

SUMMARY OF THE INVENTION

The object of the present invention is to achieve a particular level of delivery isolation on particular streaming players. This level of delivery isolation may be based on factors like an importance "value" associated with particular streaming players, or the price the user of the streaming players are charged, etc. As an example, the streaming server may place specific streaming players in the high "value" category based on the demographic information on their owners, while other streaming players may be placed in the low "value" category.

Another object of the present invention is to ensure that the high value users of streaming players always receive consistent, predictable delivery of streaming content, even if there is an excessive user demand. If there is a situation of sustained congestion, wherein not all users can be satisfied, the content provider might want to ensure that the high value users are promised predictable delivery.

Accordingly, the present invention provides a method and an apparatus for predictable and differentiated streaming on the Internet. The system consists of software and random-access memory-based buffers installed at the streaming server and at the streaming players along with a service manager at a separate location. The method prescribes the manner in which the system is used to achieve predictable and differentiated delivery of streaming multimedia packets.

The invention is based on streaming multimedia packets between the software on the streaming server and the software on the streaming. The buffer sizes in the computing devices of the streaming player and of the streaming server are initialized based on the configuration information provided by the service manager software at the start of the execution of the inventive method. This configuration information includes:

a) the expected duration of sustained congestion periods,

b) the worst-case packet loss rate during the sustained congestion period,

c) the encoded bit-rate of streaming source information, and etc.

During the delivery of the streaming multimedia packets, the software on the streaming server relays the streaming packets to the software on the streaming player, which stores the packets in a playout buffer before playing them out. The playout buffer takes care of

Ex. 1018-2101

delay variation that may arise due to instantaneous congestion on the network path. In case of short-term losses caused by instantaneous congestion, the software on streaming player immediately requests the server-end software to retransmit the lost information.

Predictable Delivery Method

To deal with sustained congestion ("congestion") the invention incorporates the following method. The software on the streaming player uses estimation techniques based on probes to detect and confirm the onset of sustained congestion. Once the congestion status is verified, the streaming player software informs the streaming server software about this event. The streaming server software then modifies the manner in which it streams packets to the streaming player software. In particular, the streaming server software ensures that the transmission rate of packets never exceeds the encoded bit-rate of the streaming source. Furthermore, it gives preemptive priority to the retransmitted packets over new packets. This creates a backlog of new packets at one of the streaming server buffers.

Meanwhile, the streaming player software continuously monitors the status of received packets and detects the end of congestion through estimation techniques based on probes. Once the end of congestion is confirmed, the streaming player software informs the streaming server software about this event. The streaming server software then begins to stream its backlog of new packets to the streaming player software. The transmission rate of this stream is increased based on the estimation information from the streaming player software along with feedback obtained from other streaming players in the network. This rate is carefully selected to ensure that the network is not flooded back into congestion. The buffer sizing at the streaming player and at the streaming server is based on the configuration information and ensures that the user experiences an uninterrupted playback during sustained congestion. This assumes that the configuration information is the "worst-case" scenario. If the actual service parameters turn out to be worse than the configuration information, the streaming player software contacts the service manager after the service. The configuration information at the service manager is now updated in a persistent manner with the actual worst-case parameters.

In one preferred embodiment, this update happens as follows. At the next service invocation, the buffers are sized based on the updated configuration information. The method thus automatically learns the worst-case behavior from the actual behavior of the network each time. Eventually, the method can guarantee a predictable delivery based on a non-interrupted playout in most cases. Various other embodiments are also possible, wherein the buffer size is fixed, but the encoding bit-rate of the stream is modified to choose the largest encoding bit-rate that leads to an uninterrupted playback.

Differentiated Streaming Method

The method for differentiated streaming involves identical operations as the predictable streaming method, except for the mechanism for streaming the backlog of packets from the streaming server software. For differentiated streaming, the streaming server software transmits the stream based on the "value" associated with the particular user, in addition to the information used for predictable streaming.

Accounting Delivery Service

Additionally, the methodology of the mentioned invention is utilized to offer the inventive method as an "accountable delivery service" to a large number of content providers, i.e., streaming servers, and users, i.e., streaming players. Such a service may deliver performance contract-based services to users of the streaming players on the Internet.

The service manager plays a central role in this service, by keeping and exchanging the state of several streaming players, delivery paths, and content providers/streaming servers in its database. The method of the present invention tracks the "actual" delivered viewing/listening experience of users of streaming servers by computing the delivery statistics including but not restricted to metrics that quantify "pauses or interruptions", "content throughput", and "content loss". In addition to the features of predictability and differentiation, the delivery service can also answer the question of "service feasibility". That is, at the beginning of a session, the service manager can estimate, based on the historical and instantaneous information, whether a

particular user can receive an "expected quality experience." While the present invention does not describe the details of this service, it should be obvious to those skilled in the art to build such a service around the framework of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other objects and advantages of the invention will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which the reference characters refer to like parts throughout and in which:

Figure 1 is a schematic diagram of the devices and programs comprising the invention.

Figure 2 is a schematic diagram of the components of the devices utilized by the invention.

Figure 3 is a schematic diagram of the operation of the invention during normal streaming.

Figure 4 is a schematic diagram of the operation of the invention during congestion.

Figure 5 is a schematic diagram of the recovery scheduling operation of the invention after congestion.

Figure 6 is a diagram of the modeling the backlog operation of the invention during congestion.

Figure 7 is a state transition diagram for streaming player module (normal streaming).

Figure 8 is a state transition diagram for streaming server module (normal streaming).

Figure 9 is diagram of a congestion processing protocol at the streaming player module (during and after congestion).

Figure 10 is a diagram of an congestion processing protocol at the streaming server module (during and after congestion).

DETAILED DESCRIPTION OF THE INVENTION

Architecture

The invention, shown in Figure 1, comprises at least one computing device 10 for executing a service manager process 12, at least one computing device 14 for executing streaming server process 16, and at least one computing device 18 for executing streaming player process 20. The service manager process 12 is shown as residing on the computing device 12 only for the clarity of presentation. It may be obvious to those skilled in the art that the service manager process 12 may reside on any computing devices 14 and 18. Furthermore, server processes 16 may be present on the computing devices 18 alongside player processes 20, and vice versa the player processes 20 may be present on the computing devices 14 alongside server processes 16. Each computing device 10, 14 and 18 are connected to a network 22 and establish data paths amongst each other. In the preferred embodiment, the network is the Internet.

The streaming server process 16 transmits a single multimedia stream to each streaming player process 20 and the streaming player process 20 receives that single multimedia stream. The streaming server process consists of three buffers:

a) Output buffer 24, used to transmit new packets from the server process 16 to the player process 20;

b) Backup buffer 26 , for maintaining temporary copies of the packets transmitted to the player process 20; and

c) Retransmit buffer 28, for maintaining retransmit requests received from the player process 20. The streaming player process 20 may comprise a player buffer 29.

Before a streaming session begins, the Service Manager process 12 downloads configuration information via the network 22 to both the computing device 14 for the use of the streaming server process 16 and to the computing device 18 for the use of the streaming player process 20. At the end of each streaming session, the configuration information on the computing device 10 is updated for the future use of the Service Manager process 12 via the network 22 by both the streaming server process 16 on the computing device 14 and the streaming player process 20 on the computing device 18.

The computing devices 10, 14, and 18 may take the configuration of any computer ranging from mainframes and personal computers (PCs) to digital telephones and hand held devices, e.g., palm pilots™. In one illustrative embodiment of this invention shown in Figure 2, such computing devices may comprise a bus 30, which is connected directly to each of the following:

1. a central processing unit (CPU) 32;
2. a memory 34;
3. a system clock 36;
4. a peripheral interface 38;
5. a video interface 40;
6. an input/output (I/O) interface 42;
7. a communications interface 44; and
8. a multimedia interface 46.

The common bus 30 is further connected

1. by the video interface 40 to a display 50;
2. by the I/O interface 42 to a storage device 52, which may illustratively take the form of memory gates, disks, diskettes, compact disks (CD), digital video disks (DVD), etc.;
3. by the multimedia interface 46 to any multimedia component 56;
4. by peripheral interface 38 to the peripherals 58, such as the keyboard, the mouse, navigational buttons, e.g., on a digital phone, a touch screen, and/or writing screen on full size and hand held devices, e.g., a palm pilot ™;
5. by the communications interface 44, e.g., a plurality of modems, to a network connection 60, e.g., an Internet Service Provider (ISP) and to other services, which is in turn connected to the network 22, whereby a data path is provided between the network 22 and the computing devices 10, 14, and 18 (Figure 1) and, in particular, the common bus 30 of these computing devices; and
6. furthermore, by the communications interface 44 to the wired and/or the wireless telephone system 54.

Normal Conditions

Turning now to Figure 3, the normal streaming operation is shown when there are either zero, i.e., no losses, or sporadic streaming losses, i.e., loss occurring due to instantaneous burst of streaming packets. The overall streaming sequence works as follows. Packets streamed from the streaming server process 16 are queued up in the streaming server output buffer 24 for transmission. The server process 16 is responsible for transmitting streaming packets 70 to the computing device 18 executing the player process 20. Periodically, this process 16 checks the output buffer 24 and the retransmit buffer 28 to determine if there are streaming packets 70 awaiting transmission or any requests form the player process. Any remaining streaming packets in the output buffer 24 are then transmitted. If retransmission requests are found, any streaming packets 70 requested for retransmission and found in the backup buffer 26 are transmitted. When streaming packets 70 are transmitted, a temporary backup copy of the transmitted streaming packets 70 is kept in the backup buffer.

The streaming player process 20 receives the streaming packets 70 and stores them at the tail-end of the player buffer 29. Periodically after a user-defined interval, the player process 20 examines the received streaming packets 70 to see if any streaming packets 70 are missing. If packets are missing, the player process 20 sends a request 72 to the server process 16 to retransmit the missing packets. After assuring that all the streaming packets 70 are received, the received streaming packets 70 are forwarded from the head-end of the player buffer to the streaming player process 20.

Congested Conditions

The invention detects congestion early on, and then may take steps so that the impact of congestion on the stream is minimized. A correctly configured framework can keep a stream completely transparent of sustained congestion, thus providing an effect equivalent to a "reservation." Two principles are at the basis of this framework, detection/reaction to congestion and congestion recovery.

1. Detecting and reacting to congestion

Ex. 1018-2107

The invention detects congestion through probes launched by the player process 20. The probes are discussed in detail later. Once congestion is confirmed, the server process 16 reacts by using a technique called "constant bit-rate emulation." This name derives from the fact that the server process 16 tries to maintain a constant upper bound on the rate at which the streaming packets 70 are streamed to the player process 20. Typically, the upper bound is set equal to the encoding bit rate of the stream. In effect, the server process 16 emulates a constant bit-rate by substituting new server packets with packets that have been requested 72 for retransmission. Please recall that in congestion, the server has a large number of retransmit requests 72 issued from the player process 20. Figure 4 shows the flow of streaming packets 70 during this congestion situation. Two important reasons motivate the constant bit-rate emulation method:

a) The method demonstrates a "network-friendly" yet efficient behavior. The method is network-friendly, since it conserves bandwidth during congestion by lowering the upper bound of its streaming transmission rate. Additionally, the method is efficient for the following reasons. First, the upper bound on the transmission rate is set equal to the maximum encoding bit-rate of the source stream; this is not a restrictive setting. Unlike other schemes that voluntarily reduce the source rate during congestion, the present invention only reduces the transmission rate by the amount of incurred loss. This decision has an important implication in practice. Most practical congestion-processing algorithms will incur errors and delays in estimating and reacting to the start of congestion or end of congestion. Consequently, there will be temporary periods in which these algorithms "think" that the network is congested, when in practice, the network has cleared out of congestion. In situations like this, estimation errors do not degrade the streaming throughput. In fact, the invention delivers a throughput better or equal to the throughput of any other scheme, if there is no loss of streaming packets 70.

b) Assuming most connections sharing the network with streaming are using the Transmission Control Protocol (TCP), the constant bit-rate of the invention in congestion allows the TCP traffic on the same path to accurately sense the available bandwidth (most Internet or Web traffic uses TCP). An alternative design with

adapting bit-rate would confuse most other TCP connections and cause each to keep oscillating their TCP windows. If all TCP connections maintain a steady window-size, the performance of the network is much smoother in congestion. This behavior can drain out the congestion faster and reduce the estimation errors.

2. Detecting End-of-Congestion and Recovery from congestion

The invention detects the end of congestion through probes launched by the player process 20. Once the player process 20 confirms that congestion is over, the server process 16 enters a phase called "recovery scheduling". Figure 4 shows a recovery scheduling after congestion. To understand this phase, recall that in the previous state of congestion, the server transmits packets at a constant rate. By substituting new packets with older lost packets, the server is in effect creating a backlog of new packets in its output buffer. The idea in recovery scheduling is to exhaust the substantial backlog that may build up at the server output queue. Clearly, this backlog must not be cleared by flooding the network. Such action may cause significant losses in the intermediate switch buffers. In addition, if thousands of streams of packets 70 flood the backlog at the same time, this may cause certain network points to get congested again. Recovery scheduling is a procedure that configures the rate of streaming the backlog based on the network parameters. Additionally, recovery scheduling can also take into account the "premium" placed on the particular player process 20. The latter consideration allows the server process 16 to stream backlog of streaming packets at different priorities. "Higher value" users can receive backlog sooner than "lower value" users. This is the basic principle behind differentiated streaming.

Buffer Design

As described previously, the configuration information is downloaded to the computing devices 14 and 16 at the beginning of each streaming session. This configuration information includes the following parameters:

(1) Worst-case duration of congestion, $c*x$, where x is a sampling or retransmission interval, and c is a number of sampling intervals in a congestion period.

(2) Worst-case of loss of streaming packets 70 during congestion defined by P_{loss}

(3) Encoding bit-rate of the stream of streaming packets 70 defined by e_r

(4) Averaged and minimum service rate, SR_{avg} and SR_{min}. This is the rate at which streaming packets 70 are actually transferred from the server process 16 to the player process 20. SR_{min} is the minimum rate across the path via the Internet 22 from the server process 16 to the player process 20.

(5) Path bottleneck link bandwidth B_{min} and the hop link capacities, where B_{min} is the minimum physical bandwidth across all the hops, i.e., the routing devices between the server process 16 and the player process 20.

The parameters indicated in the list above may be obtained through historical measurements of the relevant values and through measurements made on streaming packets 70 at the computing device 14 of the server process 16. The parameters are in turn used to design the sizes of the buffers 24, 26, 28 and 29 of server process 16 and the player process 20. One preferred embodiment of achieving this is described immediately below. That embodiment ignores the upper bounds limits on the buffer sizes related to the available random-access memory 34 (Figure 2) in the computing devices 14 and 18.

Player Buffer-size (b_c)

The buffer on the computing device 18 used by the streaming player process 20 plays out the streaming packets 70 at the maximum rate of e_r bits per second. During sustained congestion, the packet loss is approximately P_{loss}, and the maximum transmission rate from the server, as explained above is e_r. It follows that the rate of the player buffer 29 fill rate equals to $e_r * (1 - P_{loss})$ bits per second. Thus, the net drain on the player buffer 29 proceeds at the rate of $e_r * P_{loss}$ bits per second. To prevent the player buffer 29 from draining out completely within the congestion period $c * x$, the buffer-size of the player buffer 29 should satisfy the constraint defined as:

$$\frac{b_c}{e_r * P_{loss}} \geq c * x \quad \text{or} \quad b_c \geq c * x * e_r * P_{loss} \qquad \text{(Equation 1)}$$

Streaming Server Output Buffer-size (b_o)

Recall that the streaming server output buffer holds the backlog of new packets created during the congestion period. Consequently, the size of this buffer is dictated by the worst-case amount of backlog during the congestion period. To calculate the worst-case backlog of the streaming packets 70, a simple model may be built up. Figure 6 shows the approximate amount of backlog as a function of time 82 during sustained congestion. As indicated, the backlog rate 80 after two retransmission intervals 84 is $2 * e_r * P_{loss}$. By extension, after c retransmission intervals 84, the backlog rate 80 will be $cx * e_r * P_{loss}$. This establishes the constraint on the size of the output buffer 14 (Figure 1) in the memory 34 (Figure 2) of the computing device 14 (Figure 1) executing streaming server process 16 (Figure 1).

$$b_o \geq c * x * e_r * P_{loss} \qquad \text{(Equation 2)}$$

Server Backup Buffer-size (b_{backup})

The backup buffer 26 (Figure 1) holds temporary copies of the server packets that have been transmitted to the player process 20 (Figure 1). The copies must be held until the server is sure that the packets have been successfully received in the player buffer 29 (Figure 1). To estimate the size of this backup buffer 26 (Figure 1) again, an operational model is built. First, the transmission rate in packets per seconds is defined as R_p. At the start of the first retransmit 84, the approximate rate of loss of the streaming packets 70 (Figure 3) is $P_{loss} * R_p$. Assuming the loss affects new as well as retransmitted streaming packets 70 (Figure 3) equally, the approximate rate of loss for older unsuccessful streaming packets 70 (Figure 3) at the second retransmit 84 is $P_{loss}^2 * R_p$. Supposing now that the number of retransmits that will reduce the loss rate for older

packets to a negligibly small number, e.g., 0.1 packets for every retransmission interval is defined by m. This implies that:

$$P_{loss}^{m} * R_p \leq \frac{0.1}{x}, \quad \text{or that} \quad m \geq \frac{\log\left(0.1/R_p * x\right)}{\log P_{loss}}$$

Alternatively, if s is the packet size, the above equation may be expressed as:

$$m \geq \frac{\log\left(0.1 * s/e_r * x\right)}{\log P_{loss}}$$

The minimum required buffer size may be defined as equal to $m * x$. Consequently, the size constraint of the backup buffer 26 (Figure 1) is

$$b_{backup} \geq m * x \quad \geq x * \frac{\log\left(0.1 * s/e_r * x\right)}{\log P_{loss}} \qquad \text{(Equation 3)}$$

The detailed operational method underlying the invention is captured through a protocol called "Streaming Congestion Protocol" (SCP). In the section below the SCP sequences during different phases of streaming are described. Figures 6 and 7 show the detailed operational sequence at the streaming server process 16 (Figure 3) and the streaming player process 20 (Figure 3) during normal streaming of the streaming packets 70 (Figure 3). The operational sequences are described with the help of state diagrams. A state diagram shows various states and transitions between states. Each state captures a specific operational state, and the transitions between states capture the events that cause the operational states to change. Figure 7 shows the state diagram of events at the streaming server process 16 (Figure 1). Figure 8 shows the corresponding state diagram at the streaming player process 20.

Processing during and after congestion

Please refer to Figure 9, by default, the streaming player process 20 is in a normal state 100. The player process 20 may keep a track of the packet loss of a received stream at a periodic interval that may be user determined. If the amount of loss exceeds a

threshold, e.g., Threshold1, across a time-window of some number of seconds which may also be user determined, e.g., TW1, the player process 20 moves into the Likely Congestion state 102. At this point, the streaming player process 16 (Figure 1) launches congestion probes to determine whether the congestion symptoms are verified. These probes form a part of a test called confirm congestion test. If the test indicates that congestion is confirmed, the process moves to a Congestion Confirmed state 104. Immediately, the streaming player process 20 contacts its server counterpart and informs it about the new state change along with some other relevant information.

Note that the transition from a Likely Congested state 102 to Congestion Confirmed State 104 can happen in two other ways. First, the player process 20 may actually receive a Remote Congestion Confirmed report in state 106 from its server process 16 (Figure 1) indicating that some other player process 20 on a related network path is in the Congestion Confirmed state. If this happens, the player immediately moves to the Congestion Confirmed State 104 itself. If the player process 20 has already started conducting congestion probes before this notification, the player process 20 may halt them at the instant it receives the notification. Alternatively, the player process 20 may receive a Local Congestion Confirmed report in state 102 reporting that some other local player process 20 on the same streaming player module has verified congestion. If the Remote or local Congestion Confirmed reports have verified congestion within a past time-window not exceeding the time defined as Tcc, the player process 20 moves to a confirmed congestion state 104.

Once the streaming player process 20 (Figure 1) enters the congestion confirmed state 104, it periodically monitors the loss of the received stream of streaming packets 70 (Figure 3). If the packet loss is less than a second user defined threshold, e.g., Threshold2, across a second user defined time-window, e.g., TW2 seconds, the player process 20 enters the likely end-of-congestion (EOC) state 106. At this point, the player process 20 launches an EOC probe test that either confirms or invalidates the EOC decision. If the EOC probe test confirms congestion, the streaming player process 20 enters the EOC state 108 and sends an EOC report 110 to its server process 16 (Figure 1) counterpart. With this transition, the process re-enters the normal state 100. Note that

during transitions from the EOC state 110 back to the Normal State 100, the streaming player process 20 also needs to continually process the arriving packets in step 120 (Figure 7), check and request for retransmission of missing packets in step 122 (Figure 7), and forward packets to the streaming player for playback in step 124 (Figure 7). These activities are indicated in Figure 7 and are not shown in Figure 9 for purposes of clarity.

Figure 10 shows the SCP state-diagram of the server process 16. After initialization, the server process 16 enters the normal state 130. If the server process 16 receives a report from its streaming player process 20 (Figure 1) indicating congestion, the server moves to the Confirmed Congestion or Confirmed Congestion State 132. At this point, the server process 16 shares the Confirmed Congestion status information with other server processes 16 running on the same computing device 14 (Figure 1) in the Propagate Confirmed Congestion state 134, and potentially also from other computing device 14 (Figure 1) through interaction with the service manager 12 (Figure 1) via the network 22 (Figure 1). The idea behind this is to have selected server processes report the congestion to their player process so that these player processes can avoid doing the Confirmed Congestion probing test. This cuts down on the congestion reaction time and significantly cuts down the probing traffic. In general, each server process that receives the Confirmed Congestion status in the Receive the Confirmed Congestion status state 140 from other server processes 16, first determines whether the Confirmed Congestion status is relevant to its target player process 20 (Figure 1). If this is the case, the server processes notify their player process 20 (Figure 1). Notification is done through a special signaling scheme involving reliable transport protocol (RTP) messages, as discussed in Schulzrinne, Casner, Frederick, Jacobson, "RTP: A Transport Protocol for Real-time Applications", RFC 1889, Internet Engineering Task Force.

The streaming server process 16 will then make transitions from the Confirmed Congestion State 132. Starting with the Confirmed Congestion state 132, the server process 16 transmits streaming packets 70 (Figure 3) at a constant bit-rate. The server process 16 moves to the Recovery Scheduling State 136 as soon as it receives an End-of-congestion or EOC report from the player process 20 (Figure 1) targeted for the reception of

its content. Thereafter the server process 16 changes its mode of transmission, using recovery scheduling to drain its backlogged output buffer 24 (Figure 1) in an intelligent way. As soon as the backlog is over, the server process 16 moves back to the normal state 130.

While in the Normal State 130 the server process 16 may receive and filter information from other server processes 16 by entering the Receive Confirmed Congestion State 140. It may also notify the player processes 20 (Figure 1) about the confirmed congestion status through the in-band RTP signaling, by entering the Confirmed Congestion Notification state 138 from where the process 16 will return to the Normal state 130.

The server process 16 also needs to continually process the departing packets in step 150 (Figure 8), check and process the requests for retransmission of missing packets in step 152 (Figure 8), and backup packets to the backup buffer 26 (Figure 1) for playback. These activities are indicated in Figure 8 and are not shown in Figure 10 for purposes of clarity.

Recovery scheduling algorithm

Supposing that the server process 16 (Figure 1) streams of streaming packets 70 (Figure 3) are classified into K number of priority classes. Class 1 being the highest priority and class "K" being the lowest priority. Each priority class "j" is associated with a weighting function α^j, where $0 < \alpha^K < \alpha^{K-1} < .. \alpha^j < .. < \alpha^1 = 1$. Considering the server process 16 (Figure 1) with priority equaling to "j", the rule for transmission rate e_t of this process is:

$$e_t = \min(\alpha^j \times SR_{min}, \alpha^j \times \frac{B - \lambda_{other}}{\sum_{i=1}^{i=K} \alpha^i n^i})$$

(Equation 4)

In equation 4, all the terms are measured at the service bottleneck hop between the computing device 14 executing the server process 16 and the computing device 18 executing the player process 16. B is the bottleneck link capacity at the bottleneck hop.

λ_{other} is the aggregate packet rate carried at the hop from traffic not utilizing the inventive method. This rate can be estimated by obtaining the aggregate packet rate of the streaming packets 70 (Figure 3) of the inventive method λ_{SME} from the service manager, and using the fact that $\lambda_{other} = B \times \rho - \lambda_{SME}$, where $\rho = 1 - \frac{SR_{\min}}{B}$ is the utilization of the bottleneck hop. The parameter n^i is defined as the number of priority "i" streams carried at the bottleneck hop. The hop is a section of a network between two network-computing devices such as routers. This parameter may be obtained from the service manager 12 (Figure 1). The logic behind this equation is as follows. The first term indicates that the new transmission rate should be set equal to the minimum service rate along the path, in order to recover from the backlog. The second term takes into account the result of increasing the transmission rate on the utilization at the bottleneck hop. In other words, since the maximum utilization can be 100%, each computing device 14 executing server process 16 must carefully weigh the effects of increasing the transmission rate. The best rate is the maximum rate that does not congest the bottleneck bandwidth during recovery. Hence the min operator. Finally, the priorities within the equation 4 provide for differentiated streaming.

Congestion Estimators

Earlier on, we described the congestion estimation tests as part of the SCP algorithm. In principle, congestion can be estimated in a variety of ways, and the invention is not restricted to any one particular method of congestion estimation. A particular embodiment of the invention for estimating congestion based on a mix of passive and active probes will now be described. This method comprises a set of rules configured around the results of the probes. A specific congestion test e.g., an end of congestion test or a confirmed congestion test mentioned in earlier sections, combines these rules in a particular way.

The following are some of a variety of methods that may be used to compute the bottleneck bandwidth on a path between the streaming player 20 (Figure 1) and the

streaming server 16 (Figure 1). These methods are shown here for exemplary purposes only and not to indicate that only these methods must be used with the present invention.

Capacity Probe

This method is described in detail in Van Jacobson, "pathchar - A tool to infer characteristics of Internet paths", MSRI, April 21, 1997; and R. L. Carter and M.E. Crovella, "Measuring Bottleneck Link Speed in Packet-switched Networks", TR-96-006, Boston University Computer Science Department, March 15, 1996. This method is initiated by the player process 20 (Figure 1) at various stages of a streaming session. The steps of this exemplary method are as follows:

1. Do a traceroute and get hop identities marked by IP addresses.
2.

a) For every hop from one onwards, send a series of ICMP timestamp requests (type 13) from the player to the hop. Packet sizes of queries are changed in steps of 1024, 512, 256, 128, and 64, where each queries are sent out with a spacing of 3 seconds between them.

b) For every hop i between the player and the server, the player must record the ICMP timestamp response (type 14) and compute the time difference between the hop i transmit time t_i and the player receive instant t_1.

c) Denote the time difference by $\tau_{i1} = t_i - t_1$.

d) Take four measurements for timestamp differences by varying packet size through five values. Discard the minimum and the maximum, and take average of the remaining two. Let s' and s'' denote the packet sizes of two selected queries to hop i. Let $\tau_{i1'}$ and $\tau_{i1''}$ denote the measurements for the respective packet sizes.

e) Calculate $X_{i1} = \frac{\tau_{i1'} - \tau_{i1''}}{s' - s''}$

$$B_{i,i-1} = \frac{1}{X_{i1} - \left(\sum_{k=1}^{i-2} \frac{1}{B_{i-k,i-k-1}} \right)}$$

It can be proved that link capacity can be computed recursively.

The path bottleneck bandwidth $B_{min} = \min_i B_{i,i-1}$. (Equation 5)

Service Rate Probe

The "Service Rate probe" computes the approximate service rate of transferring packets between the server and the player, as discussed in Van Jacobson, "pathchar - A tool to infer characteristics of Internet paths", MSRI, April 21, 1997; and R. L. Carter and M.E. Crovella, "Measuring Bottleneck Link Speed in Packet-switched Networks", TR-96-006, Boston University Computer Science Department, March 15, 1996. The minimum service rate is the least service rate on the path, while the average service rate is the "expected" service rate on the path. . The steps of this exemplary method are as follows:

1. Obtain the hop list through traceroute. Suppose there are n-1 hops between the player and the server.
2. Periodically, the player initiates a cycle. In each cycle, the player sends n-1 queries, each spaced by ¼ second. The player forms timestamp differences between query responses from consecutive hops. The results are sent back to the server.
3. The server uses results from several cycles along with the link capacities to calculate the service rate.
   a) First, the server calculates $\tau_{m,m-1}^{min} = \min(\tau_{m,1} - \tau_{m-1,1})$ where the min operator works over all collected cycle results. We approximate $\tau_{m,m-1}^{min}$ to be the base-line delay between node m and node m-1.
   b) Denote the maximum queuing delay between node m and node m-1 by $q_{m,m-1}^{max}$, where node is a computing device, e.g., a computer or a router connected to the network.

c) Then, $q_{m,m-1}^{max} = max\left(\tau_{m,m-1} - \tau_{m,m-1}^{min}\right)$

d) Denote the average queuing delay between node m and node m-1 by $q_{m,m-1}^{avg}$.

e) Then, $q_{m,m-1}^{avg} = avg\left(\tau_{m,m-1} - \tau_{m,m-1}^{min}\right)$

Finally, the minimum service rate is:

$$SR_{m,m-1}^{min} = \frac{s}{\frac{s}{B_{m,m-1}} + q_{m,m-1}^{max}},$$

and the average service rate is:

$$SR_{m,m-1}^{avg} = \frac{s}{\frac{s}{B_{m,m-1}} + q_{m,m-1}^{avg}} \qquad \text{(Equation 6)}$$

Congestion Detection Rule (CC Test)

A robust but responsive congestion detection mechanism is an essential part of the inventive method. It is important to respond quickly to congestion; this can reduce the congestion period and hence make it easier for the recovery scheduling to do its job in a shorter period of time. Ultimately this can allow the method to work with a reduced buffer size and hence a reduced connect lag. It is equally important to robustly distinguish a sustained congestion condition. False detection can lead to reduced throughput and performance. Recall that the inventive method treats sustained congestion by reducing the throughput of the newer packets, so that the throughput of older retransmitted packets is maximized.

The present invention uses the following congestion detection rule:

1. Packet losses exceeding a threshold for a consecutive time-window of duration T_s. T_s is set to 10 seconds by default.
2. If condition 1 is triggered, three short service rate probes are sent, spaced 2 seconds apart, from the player to the SR_{min} hop. Responses are averaged to form

SR_{avg}.

The player process 20 (Figure 1) computes the expected utilization $\rho = 1 - \frac{SR_{avg}}{B}$. If condition 1 is satisfied and the utilization from condition 2 is more than a specified utilization threshold, e.g., 95%, the player process 20 (Figure 1) declares sustained congestion (Confirmed Congestion), and asks the server to enter the constant bit-rate emulation mode. An alternative method may consists of a simple rule where if packet losses exceed a threshold for N_1 consecutive sampling time-windows, the player process 20 (Figure 1) declares sustained congestion and asks the server to enter the constant bit-rate emulation mode. By default, N_1 is set to 1, and time-window is set equal to 1 second.

End of Congestion Rule (EOC Test)

The end of congestion rule is analogous to the congestion detection rule:

1. No packet losses for a consecutive time-window of duration T_e. T_e is set equal to 10 seconds by default.
2. If condition 1 is triggered, three short service rate probes are sent, spaced 2 seconds apart, from the player to the SR_{min} hop. Responses are averaged to form SR_{avg}.

   The player computes the expected utilization $\rho = 1 - \frac{SR_{avg}}{B}$.

If condition 1 is satisfied and the utilization from condition 2 is less than a specified threshold, e.g., 90%, the player declares sustained congestion to be over, and asks the server to transition to the state of recovery scheduling. An alternative method may consists of a simple rule where if in a state of sustained congestion, no packet losses are manifest for N_2 consecutive sampling time-windows, the player declares sustained congestion to be over, and asks the server to transition to the state of recovery scheduling. By default, N_2 may be set equal to five, and the sampling time-window is set equal to 1 second.

Thus, an apparatus and method for predictable and differentiated delivery of multimedia streaming on the Internet is provided. One skilled in the art will appreciate that the present invention can be carried out in other ways and practiced by other than the described embodiments, yet not departing from the spirit and essential characteristics depicted herein. The present embodiments therefore should be considered in all respects as illustrative, and the present invention is limited only by the claims that follow.

Ex. 1018-2121

CLAIMS

Having thus described our invention, what we claim as new, and desire to secure by Letters Patent is:

1. A method of streaming of multimedia audio and video packets from at least one sending computing device to an at least one receiving computing device via a network, said method comprising the steps of:

a) at a start of said streaming communicating configuration information from a service manager via the network to both an at least one sending computing device for use by an at least one server process and an at least one receiving computing device for use by an at least one player process, said at least one sending computing device comprising an at least one retransmit buffer, an at least one output buffer, an at least one backup buffer and said at least one server process, said at least one receiving computing device, comprising an at least one player buffer and an at least one player process;

b) queuing same packets in the at least one output buffer and to the at least one backup buffer;

c) determining if there are packets in the at least one output buffer and transmitting the packets from the at least one output buffer to the at least one receiving computing device via the network;

d) receiving the packets on the at least one receiving device and storing them in the at least one player buffer;

e) determining if there are omissions in the packets stored in the at least one player buffer and forwarding retransmission requests to the at least one sending computing device and storing them in the at least one retransmit buffer; and

f) determining if there are said retransmit requests in the at least one retransmit buffer and transmitting the packets from the at least one backup buffer to the at least one receiving computing device via the network.

2. The method of claim 1 wherein, the network is Internet.

3. The method of claim 2 wherein, a size of the at least one player buffer is $\geq c*x*e_r*P_{loss}$, where c is a number of sampling intervals in a congestion period, x is a sampling or retransmission interval, $c*x$ is a worst-case duration of congestion, e_r is an encoding bit-rate of a stream of the packets and P_{loss} is a worst case of loss of the packets.

4. The method of claim 3 wherein, a size of the at least one output buffer is $\geq c*x*e_r*P_{loss}$.

5. The method of claim 4 wherein, a size of the at least one backup buffer is $\geq m*x \geq x*\frac{\log\left(0.1*s/e_r*x\right)}{\log P_{loss}}$, where m is a number of retransmits that will reduce the loss rate for older packets to a negligibly small number, and $m*x$ is a minimum required size of the at least one player buffer.

6. A method of detecting and reacting to a network congestion which interferes with streaming of multimedia audio and video packets from at least one sending computing device to an at least one receiving computing device via a network, said method comprising the steps of:

a) communicating configuration information including network parameters from a service manager via the network to the at least one sending computing device and to the at least one receiving computing device, the at least one sending computing device comprising at least one server process, the at least one receiving computing device comprising at least one player process;

b) confirming the network congestion by transmitting and retracting network probes;

c) executing at least one congestion control technique to limit degradation in the streaming of the packets;

d) detecting an end of the network congestion by transmitting and retracting said network probes;

e) configuring a rate of streaming of the packets according to said network parameters

7. The method of claim 6, wherein said at least one congestion control technique is the constant bit-rate emulation.

8. The method of claim 7, wherein said at least one congestion control technique only reduces a transmission rate of the packets by the amount of incurred loss of the packets.

9. The method of claim 7, further comprising the steps of:

detecting an end of congestion;

computing available bandwidth in the network; and

transmitting packets according to said bandwidth.

10. The method of claim 9, wherein some of the at least one player process are differentiated and protected from effects of said network congestion to a greater than others by receiving a stream backlog sooner.

11. The method of claim 10, wherein some of the at least one player process are differentiated and protected from effects of said network congestion to a greater than others by receiving a stream backlog sooner according to a rule for transmission rate of the packets

$$e_t = \min(\alpha^j \times SR_{min}, \alpha^j \times \frac{B - \lambda_{other}}{\sum_{i=1}^{i=K} \alpha^i n^i})$$

, where e_t indicates said transmission rate of packets, α^j is a weighting function, for class $\{1 \ldots K\}$.

12. The method of claim 11, wherein said detecting of said end of the network congestion is performed according to the expected utilization $\rho = 1 - \frac{SR_{avg}}{B}$, where SR_{avg} is the average rate at which the packets are transferred from the at least one server process to the at least one player process and B is a bottleneck link capacity at a bottleneck hop.

13. The method of claim 12, wherein said network probes compute an approximate service rate of transferring the packets from said at least one server process to said at least one player process according to the following equation:

$SR^{min}_{m,m-1} = \frac{s}{\frac{s}{B_{m,m-1}} + q^{max}_{m,m-1}}$, and $SR^{avg}_{m,m-1} = \frac{s}{\frac{s}{B_{m,m-1}} + q^{avg}_{m,m-1}}$, where SR_{avg} and SR_{min} are averaged and minimum service rate, $q^{max}_{m,m-1}$ is the maximum queuing delay between a node m and a node m-1.

14. A method of guaranteed delivery of streaming multimedia audio and video packets from at least one sending computing device to an at least one receiving computing device via a network, said method comprising the steps of:

a) continuously processing arriving packets;

b) keeping track of loss of the packets at the at least one receiving computing device, said at least one receiving computing device comprising one or more player processes;

c) determining if said loss exceeds a first threshold during a first interval;

d) verifying congestion symptoms;

e) communicating said verified congestion symptoms to the at least one sending computing device, said at least one sending computing device comprising one or more server processes;

f) monitoring said loss and determining if said loss exceeds a second threshold during a second interval to determine an end of congestion; and

g) verifying congestion symptoms.

15. The method of claim 14, wherein said step of keeping track is performed at user define intervals.

16. The method of claim 15, wherein said first threshold, said second threshold, said first interval, and said second interval are user defined.

17. The method of claim 16, wherein said congestion symptoms are verified by receiving a remote congestion confirmed report.

18. The method of claim 17, wherein said congestion symptoms are verified by performing a congestion probe.



10
Service Manager
12
14
Server
Server Process
16
Retransmit Buffer
Output Buffer
Backup Buffer
24
26
28
18
Player
Player Process
21
Player Buffer
29
Internet
22

Figure 1




Figure 2

Ex. 1018-2128




Figure 3

Ex. 1018-2129

Ex. 1018-2130




Figure 4



14
16
Server Process
18
20
Player Process
28
Retransmit Buffer
Server-side Buffers
Output Buffer
Backup Buffer
26
10
Client-side Buffer
29
24
Internet
Recovery Scheduling
(Retransmits + Backlog + New Packets)
Internet
22
Retransmit Requests
72

Figure 5



80
$e_r.P_{loss}$
Backlog rate
$2e_r.P_{loss}$
Backlog rate
New Traffic
e_r
Backlog Rate +
New Traffic e_r
New Traffic
e_r
e_r
e_r
$e_r(1+P_{loss})$
$e_r(1+2P_{loss})$
82
Lost Traffic
$e_r.P_{loss}$
Retransmits
$e_r.P_{loss}$
Retransmits
$e_r.P_{loss}$
time
x
x
84

Figure 6

Ex. 1018-2133




Figure 7

Ex. 1018-2134

Figure 8




Figure 9

Ex. 1018-2135

Ex. 1018-2136

Figure 10

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US01/40264

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) :G06F 15/16
US CL :709/231, 232, 235

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 709/231, 232, 235

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X, P	US 6,031,818 A (LO et al) 29 February 2000, col. 2, line 54-col. 5, line 28.	1, 2
X,P	US 6,018,515 A (SORBER) 25 January 2000, col. 4, line 18-col. 10, line 65.	6-10, 14-18
A, P	US 6,014,706 A (CANNON et al) 11 January 2000, see all.	1-18
A	US 5,339,392 A (RISBERG et al) 16 August 1994, see all.	1-18

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

*	Special categories of cited documents:	"T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A"	document defining the general state of the art which is not considered to be of particular relevance	"X"	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E"	earlier document published on or after the international filing date	"Y"	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&"	document member of the same patent family
"O"	document referring to an oral disclosure, use, exhibition or other means		
"P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search 06 JUNE 2001	Date of mailing of the international search report 27 July 2001 (27.07.01)
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231 Facsimile No. (703) 305-3230	Authorized officer Peggy Harwood TOD KUPSTAS Telephone No. 703-305-2655

Form PCT/ISA/210 (second sheet) (July 1998) ★

PTO/AIA/80 (07-12)
Approved for use through 11/30/2014. OMB 0651-0035
U.S. Patent and Trademark Office; U.S DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

POWER OF ATTORNEY TO PROSECUTE APPLICATIONS BEFORE THE USPTO

I hereby revoke all previous powers of attorney given in the application identified in the attached statement under 37 CFR 3.73(c).

I hereby appoint:

■ Practitioners associated with Customer Number: 70560

OR

☐ Practitioner(s) named below (If more than ten patent practitioners are to be named, then a customer number must be used):

Name	Registration Number	Name	Registration Number

As attorney(s) or agent(s) to represent the undersigned before the United States Patent and Trademark Office (USPTO) in connection with any and all patent applications assigned only to the undersigned according to the USPTO assignment records or assignments documents attached to this form in accordance with 37 CFR 3.73(c).

Please change the correspondence address for the application identified in the attached statement under 37 CFR 3.73(c) to:

■ The address associated with Customer Number: 70560

OR

☐

Firm or Individual Name			
Address			
City		State	Zip
Country			
Telephone		Email	

Assignee Name and Address: Echostar Technologies L.L.C.
100 Inverness Terrace East
Englewood, CO 80112

A copy of this form, together with a statement under 37 CFR 3.73(c) (Form PTO/AIA/96 or equivalent) is required to be filed in each application in which this form is used. The statement under 37 CFR 3.73(c) may be completed by one of the practitioners appointed in this form, and must identify the application in which this Power of Attorney is to be filed.

SIGNATURE of Assignee of Record

The individual whose signature and title is supplied below is authorized to act on behalf of the assignee

Signature		Date	10/11/2012
Name	Dean A. Manson	Telephone	303.706.4554
Title	Executive Vice President, General Counsel and Secretary		

This collection of information is required by 37 CFR 1.31, 1.32 and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Electronic Patent Application Fee Transmittal

Application Number:	11116783
Filing Date:	28-Apr-2005
Title of Invention:	APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT
First Named Inventor/Applicant Name:	R. Drew Major
Filer:	Brett Carlson
Attorney Docket Number:	066.0141 (P2004-04-01.1)

Filed as Large Entity

Utility under 35 USC 111(a) Filing Fees

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD($)
Miscellaneous:				
RCE - 2nd and Subsequent Request	1820	1	1700	1700
		Total in USD ($)		**1700**

PTO/SB/96 (02-09)
Approved for use through 03/31/2009. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

STATEMENT UNDER 37 CFR 3.73(b)

Applicant/Patent Owner: ECHOSTAR TECHNOLOGIES L.L.C.

Application No./Patent No.: 11/116,783 Filed/Issue Date: April 28, 2005

Titled: APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT

ECHOSTAR TECHNOLOGIES L.L.C. , a limited liability company

(Name of Assignee) (Type of Assignee, e.g., corporation, partnership, university, government agency, etc.

states that it is:

1. ☒ the assignee of the entire right, title, and interest in;

2. ☐ an assignee of less than the entire right, title, and interest in (The extent (by percentage) of its ownership interest is _____ %); or

3. ☐ the assignee of an undivided interest in the entirety of (a complete assignment from one of the joint inventors was made)

the patent application/patent identified above, by virtue of either:

A. ☐ An assignment from the inventor(s) of the patent application/patent identified above. The assignment was recorded in the United States Patent and Trademark Office at Reel _____, Frame _____, or for which a copy therefore is attached.

OR

B. ☒ A chain of title from the inventor(s), of the patent application/patent identified above, to the current assignee as follows:

1. From: DISH Digital L.L.C. To: EchoStar Technologies L.L.C.

The document was recorded in the United States Patent and Trademark Office at
Reel 033470 , Frame 0726 , or for which a copy thereof is attached.

2. From: _____ To: _____

The document was recorded in the United States Patent and Trademark Office at
Reel _____ , Frame _____ , or for which a copy thereof is attached.

3. From: _____ To: _____

The document was recorded in the United States Patent and Trademark Office at
Reel _____ , Frame _____ , or for which a copy thereof is attached.

☐ Additional documents in the chain of title are listed on a supplemental sheet(s).

☐ As required by 37 CFR 3.73(b)(1)(i), the documentary evidence of the chain of title from the original owner to the assignee was, or concurrently is being, submitted for recordation pursuant to 37 CFR 3.11.

[NOTE: A separate copy (*i.e.*, a true copy of the original assignment document(s)) must be submitted to Assignment Division in accordance with 37 CFR Part 3, to record the assignment in the records of the USPTO. See MPEP 302.08]

The undersigned (whose title is supplied below) is authorized to act on behalf of the assignee.

/BRETT A. CARLSON, REG. NO. 39928/	August 20, 2014
Signature	Date
Brett A. Carlson	Attorney of Record
Printed or Typed Name	Title

This collection of information is required by 37 CFR 3.73(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Acknowledgement Receipt

EFS ID:	19910924
Application Number:	11116783
International Application Number:	
Confirmation Number:	5535
Title of Invention:	APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT
First Named Inventor/Applicant Name:	R. Drew Major
Customer Number:	110240
Filer:	Brett Carlson/Sharron Castillo
Filer Authorized By:	Brett Carlson
Attorney Docket Number:	066.0141 (P2004-04-01.1)
Receipt Date:	20-AUG-2014
Filing Date:	28-APR-2005
Time Stamp:	13:59:45
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	Credit Card
Payment was successfully received in RAM	$1700
RAM confirmation Number	204
Deposit Account	502091
Authorized User	CARLSON, BRETT A.

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Charge any Additional Fees required under 37 C.F.R. Section 1.17 (Patent application and reexamination processing fees)

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Request for Continued Examination (RCE)	20140820_RCE_P2004-04-01-1.pdf	697806 3f538d9d1ec23c574b0806fc99fcbc06300c9ff4	no	3
Warnings:					
Information:					
2	Information Disclosure Statement (IDS) Form (SB08)	20140820_IDS_P2004-04-01-1.pdf	622803 5faf9c5af0565f42f3c98af24c6689f8fdb94ade	no	25
Warnings:					
Information:					
3	Transmittal Letter	20140820_IDSCert_P2004-04-01-1.pdf	94670 c41a2a53e48520d663c0f4652854ac423d8e68c4	no	1
Warnings:					
Information:					
4	Foreign Reference	EP1202487A2.pdf	1169542 e3961c13249effa85f97034caddedff4dbedc77d	no	21
Warnings:					
Information:					
5	Foreign Reference	EP1298931A2.pdf	564750 17988c97c90278abafab90accdb307ac133ea832	no	9
Warnings:					
Information:					
6	Foreign Reference	EP1395014A1.pdf	430935 5bd3cb3cce066c412e84ceb0db005d86ebc13605	no	11
Warnings:					
Information:					
7	Foreign Reference	GB2367219A.pdf	1022882 4b911a5301386062eb7560e4982065ed5cfef6d	no	24
Warnings:					
Information:					
8	Foreign Reference	JP2000201343.pdf	21958041 852daf4ae4a533b5a36984e992609dbc8888bebb	no	14
Warnings:					
Information:					

9	Foreign Reference	JP2001092752.pdf	9449147 3115b20d4cc1a9898d8742728f2946d9e91da1b7	no	12
Warnings:					
Information:					
10	Foreign Reference	JP2004054930.pdf	7662878 7215a4460b43c2d5f49cd2e80dcb034a81c3604b	no	36
Warnings:					
Information:					
11	Foreign Reference	JP2011004225A.pdf	2693988 c96187633b1948096c41bf2f2558ceb94073c945	no	11
Warnings:					
Information:					
12	Foreign Reference	WO2001067264.pdf	1561090 14ea9fe21f267c32636564e07838fe524ecef3c8	no	41
Warnings:					
Information:					
13	Foreign Reference	WO2003003760.pdf	2622813 40ea384993705bc0f97d2b4db0cc677369e25769	no	87
Warnings:					
Information:					
14	Foreign Reference	WO2003027876.pdf	5592281 937b4925b48acf8bed9f4226067eb00e31f2dcf8	no	97
Warnings:					
Information:					
15	Foreign Reference	WO2004025405.pdf	825266 e160c7648ab3c92ae53aad7efe41ffe5c6b0ebc9	no	20
Warnings:					
Information:					
16	Foreign Reference	WO2004036824.pdf	1597410 20a96cbb41a14278a3c60b1b5236e3ae012280f0	no	41
Warnings:					
Information:					
17	Foreign Reference	WO2006010113.pdf	5663204 6e292580427daf9fc8f17d85c0318e226cf0bd6a	no	118
Warnings:					
Information:					

18	Foreign Reference	WO20003009581.pdf	826054 99622cbf7cd9f4e0b6bc5216aae980d2282bd893	no	21
Warnings:					
Information:					
19	Non Patent Literature	NPL_AustraliaFirstExamRpt20111017_2011213730.pdf	27546 795a661c5ca609878f5c957bb8b15d556c8271c1	no	2
Warnings:					
Information:					
20	Non Patent Literature	NPL_CanadaOA20121015_2564861.pdf	263323 73b61068d8859ee06f177b151517158507 3e244e	no	5
Warnings:					
Information:					
21	Non Patent Literature	NPL_CanadaOA20130909_2564861.pdf	202703 3d8f8a42328da94a7d28048ccef3ec8978661d18	no	4
Warnings:					
Information:					
22	Non Patent Literature	NPL_Clement_MoveClosesFunding.pdf	172934 c65a317075d6d88f73613f212b13b4e09646ea79	no	2
Warnings:					
Information:					
23	Non Patent Literature	NPL_EuropeExtSrchRpt20140710_12154559.pdf	1844529 380cc4633ad5f0a18a11207e5e7cbeceddc08c59	no	11
Warnings:					
Information:					
24	Non Patent Literature	NPL_Fujisawa_ImplementationOfEfficientAcdess.pdf	511563 91dff145bd502cbcca14ed40adf4002af21abab7	no	10
Warnings:					
Information:					
25	Non Patent Literature	NPL_Guo_DirectStream.pdf	7958674 612e3ca1a57a5f239df3d1d3d3235b392d47e87b	no	22
Warnings:					
Information:					
26	Transmittal Letter	NPL_IntlSrchRptPCTUS0809281_20081105.pdf	702188 e54822cc1d944d018ede70f2e776c29629d4c2d8	no	9
Warnings:					
Information:					

27	Non Patent Literature	NPL_IntlSrchRptPCTUS0861035_20081212.pdf	572640 d2cc221e0b33cab41ecf754d09a3d4f72f9a6757	no	8
Warnings:					
Information:					
28	Non Patent Literature	NPL_JPInterrogation20121106_2007511070.pdf	4923875 ccdd5d93559e144eaf0d083e2725122e6f55148e	no	24
Warnings:					
Information:					
29	Non Patent Literature	NPL_JPNtcOfReject20110426_2007511070.pdf	11221634 cbdd88f13ae97d297a47f32aa0eb08a141d1bcb9	no	13
Warnings:					
Information:					
30	Non Patent Literature	NPL_JPOA20120228_20075110 70.pdf	1719065 490d56a11aa22798c9d5097086d7e9f75df6397c	no	6
Warnings:					
Information:					
31	Non Patent Literature	NPL_Kozamernik_MediaStreaming.pdf	6407225 7f5c49521521198a912e04f054f8405ed84f9614	no	15
Warnings:					
Information:					
32	Non Patent Literature	NPL_KROA20110728_1020067025274.pdf	283253 a519519fe766d2f1062733b2fa400e76dcbef021	no	3
Warnings:					
Information:					
33	Non Patent Literature	NPL_Lienhart_DistributedVideo.pdf	11245900 37342a4029d40ede417d94095bbd90befa4931d5	no	29
Warnings:					
Information:					
34	Non Patent Literature	NPL_Liu_AdaptiveVideoMulticast.pdf	5897378 6d1568a810d08f4e566bfcc4b02748abfa471b64	no	12
Warnings:					
Information:					
35	Non Patent Literature	NPL_Liu_PeerToPeerInternetVideo.pdf	1125709 1dbfd7983420ecb8f68943b0539a4d344045f5fb	no	12
Warnings:					
Information:					

36	Non Patent Literature	NPL_MoveNetworks_NextGeneration.pdf	1128862 446af274461f93a7d60548a003fcc17a6c5e4a0f	no	21
Warnings:					
Information:					
37	Non Patent Literature	NPL_Nguyen_MultipleSenderDistVideo.pdf	1053500 af974412420b4c476c2c59e0e76443e17141b1bb	no	12
Warnings:					
Information:					
38	Non Patent Literature	NPL_NOA20140624_13757571.pdf	873532 5af7d70921b96be007abc0a25e5399863d602287	no	16
Warnings:					
Information:					
39	Non Patent Literature	NPL_OA20130913_13757571.pdf	1418297 94f483bfda2f69a58937df26fd2e02470cc4151c	no	36
Warnings:					
Information:					
40	Non Patent Literature	NPL_OA20140807_14106051.pdf	3247593 d022383de49b57b0c1db511f3db35b099a3b66ae	no	84
Warnings:					
Information:					
41	Non Patent Literature	NPL_Rejaie_ArchitecturalConsiderations.pdf	3252815 d638402b4b84964353e12f7de0a6dc071af47d63	no	6
Warnings:					
Information:					
42	Non Patent Literature	NPL_Roy_SystemArchitecture.pdf	2812918 7e9c5ee17749c18ea0bd37428a2cfaa78b62fddc	no	6
Warnings:					
Information:					
43	Non Patent Literature	NPL_Tsuru_RecentEvolution.pdf	1522645 c5225e2e26324cd4748599f0753210c21c47441b	no	9
Warnings:					
Information:					
44	Non Patent Literature	NPL_WeblioDictionaryPgs.pdf	525676 eec0a963413300c3b5fb79ab7eacbae55666efc2	no	3
Warnings:					
Information:					

45	Non Patent Literature	NPL_Xu_PeerToPeer.pdf	4454232 01dcd4f73c5fcba31a2d951f592bf59eaebca748	no	10
Warnings:					
Information:					
46	Non Patent Literature	NPL_Yoshimura_MobileStreamnigMedia.pdf	378918 aac54a2603ed446586676ed16c15022af1acc1eb	no	20
Warnings:					
Information:					
47	Foreign Reference	NPL_Zhang_CoolStreaming.pdf	293506 79257b4aeb9b9510bf46f97c437f91285abb9784	no	14
Warnings:					
Information:					
48	Power of Attorney	20140820_POA_P2004-04-01-1.pdf	108457 8d94544b413874551 2d15aea41385f405931aa88	no	1
Warnings:					
Information:					
49	Assignee showing of ownership per 37 CFR 3.73.	20140820_Stmt373b_P2004-04-01-1.pdf	435001 30264538176621ad0b160e5190e928bf1bbd1564	no	2
Warnings:					
Information:					
50	Assignee showing of ownership per 37 CFR 3.73.	20140820_Stmt373bAddlSheet_P2004-04-01-1.pdf	432436 d33c0c028f21e71b4dc482341532d8cc2317932d	no	2
Warnings:					
Information:					
51	Fee Worksheet (SB06)	fee-info.pdf	30480 d7413bb6f5112dba1784ac498a196f7c4a55aa7e	no	2
Warnings:					
Information:					
		Total Files Size (in bytes):	142104567		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.

PTO/SB/96 (02-09)
Approved for use through 03/31/2009. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

STATEMENT UNDER 37 CFR 3.73(b)

Applicant/Patent Owner: ECHOSTAR TECHNOLOGIES L.L.C.

Application No./Patent No.: 11/116,783 Filed/Issue Date: April 28, 2005

Titled: APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT

ECHOSTAR TECHNOLOGIES L.L.C. , a limited liability company

(Name of Assignee) (Type of Assignee, e.g., corporation, partnership, university, government agency, etc.

states that it is:

1. ☒ the assignee of the entire right, title, and interest in;

2. ☐ an assignee of less than the entire right, title, and interest in (The extent (by percentage) of its ownership interest is _____ %); or

3. ☐ the assignee of an undivided interest in the entirety of (a complete assignment from one of the joint inventors was made)

the patent application/patent identified above, by virtue of either:

A. ☐ An assignment from the inventor(s) of the patent application/patent identified above. The assignment was recorded in the United States Patent and Trademark Office at Reel _____, Frame _____, or for which a copy therefore is attached.

OR

B. ☒ A chain of title from the inventor(s), of the patent application/patent identified above, to the current assignee as follows:

1. From: R. Drew Major, Mark B. Hurst To: Move Networks, Inc.

The document was recorded in the United States Patent and Trademark Office at Reel 018020, Frame 0750, or for which a copy thereof is attached.

2. From: Move Networks, Inc. To: EchoStar Advanced Technologies L.L.C.

The document was recorded in the United States Patent and Trademark Office at Reel 025570, Frame 0047, or for which a copy thereof is attached.

3. From: EchoStar Advanced Echnologies L.L.C. To: DISH Digital L.L.C.

The document was recorded in the United States Patent and Trademark Office at Reel 029894, Frame 0512, or for which a copy thereof is attached.

☒ Additional documents in the chain of title are listed on a supplemental sheet(s).

☐ As required by 37 CFR 3.73(b)(1)(i), the documentary evidence of the chain of title from the original owner to the assignee was, or concurrently is being, submitted for recordation pursuant to 37 CFR 3.11.

[NOTE: A separate copy (*i.e.*, a true copy of the original assignment document(s)) must be submitted to Assignment Division in accordance with 37 CFR Part 3, to record the assignment in the records of the USPTO. See MPEP 302.08]

The undersigned (whose title is supplied below) is authorized to act on behalf of the assignee.

/BRETT A. CARLSON, REG. NO. 39928/	August 20, 2014
Signature	Date
Brett A. Carlson	Attorney of Record
Printed or Typed Name	Title

This collection of information is required by 37 CFR 3.73(b). The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

PTO/SB/30EFS (07-09)
Approved for use through 07/31/2012. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

REQUEST FOR CONTINUED EXAMINATION(RCE)TRANSMITTAL
(Submitted Only via EFS-Web)

Application Number	11116783	Filing Date	2005-04-28	Docket Number (if applicable)	066.0141 (P2004-04-01.1)	Art Unit	2444
First Named Inventor	R. Drew Major			Examiner Name	Ninos Donabed		

This is a Request for Continued Examination (RCE) under 37 CFR 1.114 of the above-identified application.
Request for Continued Examination (RCE) practice under 37 CFR 1.114 does not apply to any utility or plant application filed prior to June 8 1995, or to any design application. The Instruction Sheet for this form is located at WWW.USPTO.GOV

SUBMISSION REQUIRED UNDER 37 CFR 1.114

Note: If the RCE is proper, any previously filed unentered amendments and amendments enclosed with the RCE will be entered in the orde in which they were filed unless applicant instructs otherwise. If applicant does not wish to have any previously filed unentered amendment(s entered, applicant must request non-entry of such amendment(s).

☐ Previously submitted. If a final Office action is outstanding, any amendments filed after the final Office action may be considered as a submission even if this box is not checked.

☐ Consider the arguments in the Appeal Brief or Reply Brief previously filed on _____

☐ Other _____

☒ Enclosed

☐ Amendment/Reply

☒ Information Disclosure Statement (IDS)

☐ Affidavit(s)/ Declaration(s)

☐ Other _____

MISCELLANEOUS

☐ Suspension of action on the above-identified application is requested under 37 CFR 1.103(c) for a period of months _____ (Period of suspension shall not exceed 3 months; Fee under 37 CFR 1.17(i) required)

☐ Other _____

FEES

The RCE fee under 37 CFR 1.17(e) is required by 37 CFR 1.114 when the RCE is filed.

☒ The Director is hereby authorized to charge any underpayment of fees, or credit any overpayments, to Deposit Account No 502091

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED

☒ Patent Practitioner Signature

☐ Applicant Signature

PTO/SB/30EFS (07-09)
Approved for use through 07/31/2012. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Signature of Registered U.S. Patent Practitioner			
Signature	/BRETT A. CARLSON/	Date (YYYY-MM-DD)	2014-08-20
Name	Brett A. Carlson	Registration Number	39928

This collection of information is required by 37 CFR 1.114. The information is required to obtain or retain a benefit by the public which is t file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Tim will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions fo reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the informatio solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.

2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.

3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.

4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).

5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.

6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).

7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.

8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record ma be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.

9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
11/116,783	04/28/2005	R. Drew Major	066.0141 (P2004-04-01.1)

CONFIRMATION NO. 5535

70560
INGRASSIA FISHER & LORENZ, P.C. (EchoStar)
7010 E. COCHISE ROAD
SCOTTSDALE, AZ 85253

POA ACCEPTANCE LETTER

OC000000070369889

Date Mailed: 08/28/2014

NOTICE OF ACCEPTANCE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 08/20/2014.

The Power of Attorney in this application is accepted. Correspondence in this application will be mailed to the above address as provided by 37 CFR 1.33.

/zabraha/

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
11/116,783	04/28/2005	R. Drew Major	066.0141 (P2004-04-01.1)

CONFIRMATION NO. 5535

POWER OF ATTORNEY NOTICE

110240
Ingrassia Fisher & Lorenz, P.C. (DISH Digital)
7010 East Cochise Road
Scottsdale, AZ 85253

OC000000070369882

Date Mailed: 08/28/2014

NOTICE REGARDING CHANGE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 08/20/2014.

- The Power of Attorney to you in this application has been revoked by the assignee who has intervened as provided by 37 CFR 3.71. Future correspondence will be mailed to the new address of record(37 CFR 1.33).

/zabraha/

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

NOTICE OF ALLOWANCE AND FEE(S) DUE

70560 7590 09/12/2014

INGRASSIA FISHER & LORENZ, P.C. (EchoStar)
7010 E. COCHISE ROAD
SCOTTSDALE, AZ 85253

EXAMINER
DONABED, NINOS

ART UNIT	PAPER NUMBER
2444	

DATE MAILED: 09/12/2014

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
11/116,783	04/28/2005	R. Drew Major	066.0141 (P2004-04-01.1)	5535

TITLE OF INVENTION: APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	$480	$0	$0	$480	12/12/2014

THE APPLICATION IDENTIFIED ABOVE HAS BEEN EXAMINED AND IS ALLOWED FOR ISSUANCE AS A PATENT. PROSECUTION ON THE MERITS IS CLOSED. THIS NOTICE OF ALLOWANCE IS NOT A GRANT OF PATENT RIGHTS. THIS APPLICATION IS SUBJECT TO WITHDRAWAL FROM ISSUE AT THE INITIATIVE OF THE OFFICE OR UPON PETITION BY THE APPLICANT. SEE 37 CFR 1.313 AND MPEP 1308.

THE ISSUE FEE AND PUBLICATION FEE (IF REQUIRED) MUST BE PAID WITHIN THREE MONTHS FROM THE MAILING DATE OF THIS NOTICE OR THIS APPLICATION SHALL BE REGARDED AS ABANDONED. THIS STATUTORY PERIOD CANNOT BE EXTENDED. SEE 35 U.S.C. 151. THE ISSUE FEE DUE INDICATED ABOVE DOES NOT REFLECT A CREDIT FOR ANY PREVIOUSLY PAID ISSUE FEE IN THIS APPLICATION. IF AN ISSUE FEE HAS PREVIOUSLY BEEN PAID IN THIS APPLICATION (AS SHOWN ABOVE), THE RETURN OF PART B OF THIS FORM WILL BE CONSIDERED A REQUEST TO REAPPLY THE PREVIOUSLY PAID ISSUE FEE TOWARD THE ISSUE FEE NOW DUE.

HOW TO REPLY TO THIS NOTICE:

I. Review the ENTITY STATUS shown above. If the ENTITY STATUS is shown as SMALL or MICRO, verify whether entitlement to that entity status still applies.

If the ENTITY STATUS is the same as shown above, pay the TOTAL FEE(S) DUE shown above.

If the ENTITY STATUS is changed from that shown above, on PART B - FEE(S) TRANSMITTAL, complete section number 5 titled "Change in Entity Status (from status indicated above)".

For purposes of this notice, small entity fees are 1/2 the amount of undiscounted fees, and micro entity fees are 1/2 the amount of small entity fees.

II. PART B - FEE(S) TRANSMITTAL, or its equivalent, must be completed and returned to the United States Patent and Trademark Office (USPTO) with your ISSUE FEE and PUBLICATION FEE (if required). If you are charging the fee(s) to your deposit account, section "4b" of Part B - Fee(s) Transmittal should be completed and an extra copy of the form should be submitted. If an equivalent of Part B is filed, a request to reapply a previously paid issue fee must be clearly made, and delays in processing may occur due to the difficulty in recognizing the paper as an equivalent of Part B.

III. All communications regarding this application must give the application number. Please direct all communications prior to issuance to Mail Stop ISSUE FEE unless advised to the contrary.

IMPORTANT REMINDER: Utility patents issuing on applications filed on or after Dec. 12, 1980 may require payment of maintenance fees. It is patentee's responsibility to ensure timely payment of maintenance fees when due.

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), to: Mail **Mail Stop ISSUE FEE**
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450
or Fax (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

70560 7590 09/12/2014
INGRASSIA FISHER & LORENZ, P.C. (EchoStar)
7010 E. COCHISE ROAD
SCOTTSDALE, AZ 85253

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission
I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being facsimile transmitted to the USPTO (571) 273-2885, on the date indicated below.

(Depositor's name)
(Signature)
(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
11/116,783	04/28/2005	R. Drew Major	066.0141 (P2004-04-01.1)	5535

TITLE OF INVENTION: APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	$480	$0	$0	$480	12/12/2014

EXAMINER	ART UNIT	CLASS-SUBCLASS
DONABED, NINOS	2444	709-231000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).
- ❑ Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached.
- ❑ "Fee Address" indication (or "Fee Address" Indication form PTO/SB/47; Rev 03-02 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list
(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,
(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.
1 _____
2 _____
3 _____

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document has been filed for recordation as set forth in 37 CFR 3.11. Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE (B) RESIDENCE: (CITY and STATE OR COUNTRY)

Please check the appropriate assignee category or categories (will not be printed on the patent) : ❑ Individual ❑ Corporation or other private group entity ❑ Government

4a. The following fee(s) are submitted:
- ❑ Issue Fee
- ❑ Publication Fee (No small entity discount permitted)
- ❑ Advance Order - # of Copies _____

4b. Payment of Fee(s): (**Please first reapply any previously paid issue fee shown above**)
- ❑ A check is enclosed.
- ❑ Payment by credit card. Form PTO-2038 is attached.
- ❑ The Director is hereby authorized to charge the required fee(s), any deficiency, or credits any overpayment, to Deposit Account Number _____ (enclose an extra copy of this form).

5. **Change in Entity Status** (from status indicated above)
- ❑ Applicant certifying micro entity status. See 37 CFR 1.29
  NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.
- ❑ Applicant asserting small entity status. See 37 CFR 1.27
  NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.
- ❑ Applicant changing to regular undiscounted fee status.
  NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature _____ Date _____

Typed or printed name _____ Registration No. _____

PTOL-85 Part B (10-13) Approved for use through 10/31/2013. OMB 0651-0033 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
11/116,783	04/28/2005	R. Drew Major	066.0141 (P2004-04-01.1)	5535

70560 7590 09/12/2014

INGRASSIA FISHER & LORENZ, P.C. (EchoStar)
7010 E. COCHISE ROAD
SCOTTSDALE, AZ 85253

EXAMINER	
DONABED, NINOS	

ART UNIT	PAPER NUMBER
2444	

DATE MAILED: 09/12/2014

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b)
(Applications filed on or after May 29, 2000)

The Office has discontinued providing a Patent Term Adjustment (PTA) calculation with the Notice of Allowance.

Section 1(h)(2) of the AIA Technical Corrections Act amended 35 U.S.C. 154(b)(3)(B)(i) to eliminate the requirement that the Office provide a patent term adjustment determination with the notice of allowance. See Revisions to Patent Term Adjustment, 78 Fed. Reg. 19416, 19417 (Apr. 1, 2013). Therefore, the Office is no longer providing an initial patent term adjustment determination with the notice of allowance. The Office will continue to provide a patent term adjustment determination with the Issue Notification Letter that is mailed to applicant approximately three weeks prior to the issue date of the patent, and will include the patent term adjustment on the patent. Any request for reconsideration of the patent term adjustment determination (or reinstatement of patent term adjustment) should follow the process outlined in 37 CFR 1.705.

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Customer Service Center of the Office of Patent Publication at 1-(888)-786-0101 or (571)-272-4200.

OMB Clearance and PRA Burden Statement for PTOL-85 Part B

The Paperwork Reduction Act (PRA) of 1995 requires Federal agencies to obtain Office of Management and Budget approval before requesting most types of information from the public. When OMB approves an agency request to collect information from the public, OMB (i) provides a valid OMB Control Number and expiration date for the agency to display on the instrument that will be used to collect the information and (ii) requires the agency to inform the public about the OMB Control Number's legal significance in accordance with 5 CFR 1320.5(b).

The information collected by PTOL-85 Part B is required by 37 CFR 1.311. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, Virginia 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450. Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Notice of Allowability	Application No. 11/116,783	Applicant(s) MAJOR ET AL.	
	Examiner NINOS DONABED	Art Unit 2444	AIA (First Inventor to File) Status No

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address--

All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this application. If not included herewith (or previously mailed), a Notice of Allowance (PTOL-85) or other appropriate communication will be mailed in due course. **THIS NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHTS.** This application is subject to withdrawal from issue at the initiative of the Office or upon petition by the applicant. See 37 CFR 1.313 and MPEP 1308.

1. ☒ This communication is responsive to *and RCE filed 8/20/2014 - board descision dated 7/23/2014*.
   ☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on_____.
2. ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.
3. ☒ The allowed claim(s) is/are *20,21,23-26,35-38 and 40-50*. As a result of the allowed claim(s), you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to PPHfeedback@uspto.gov .
4. ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

   Certified copies:

   a) ☐ All b) ☐ Some *c) ☐ None of the:
      1. ☐ Certified copies of the priority documents have been received.
      2. ☐ Certified copies of the priority documents have been received in Application No. _____ .
      3. ☐ Copies of the certified copies of the priority documents have been received in this national stage application from the International Bureau (PCT Rule 17.2(a)).

   * Certified copies not received: _____.

Applicant has THREE MONTHS FROM THE "MAILING DATE" of this communication to file a reply complying with the requirements noted below. Failure to timely comply will result in ABANDONMENT of this application.
THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.

5. ☐ CORRECTED DRAWINGS (as "replacement sheets") must be submitted.
   ☐ including changes required by the attached Examiner's Amendment / Comment or in the Office action of Paper No./Mail Date _____.

   Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings in the front (not the back) of each sheet. Replacement sheet(s) should be labeled as such in the header according to 37 CFR 1.121(d).

6. ☐ DEPOSIT OF and/or INFORMATION about the deposit of BIOLOGICAL MATERIAL must be submitted. Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOGICAL MATERIAL.

Attachment(s)

1. ☒ Notice of References Cited (PTO-892)
2. ☒ Information Disclosure Statements (PTO/SB/08), Paper No./Mail Date 8/20/2014
3. ☐ Examiner's Comment Regarding Requirement for Deposit of Biological Material
4. ☐ Interview Summary (PTO-413), Paper No./Mail Date _____ .
5. ☐ Examiner's Amendment/Comment
6. ☒ Examiner's Statement of Reasons for Allowance
7. ☐ Other _____.

/NINOS DONABED/
Primary Examiner, Art Unit 2444

1. The present application is being examined under the pre-AIA first to invent provisions.

Information Disclosure Statement

The IDS filed on 7/29/2014 has been considered.

REASONS FOR ALLOWANCE

The following is an examiner's statement of reasons for allowance: Claims 20,21,23-26,35-38 and 40-50 are allowable over the prior art of record: the closest prior art of record (Birney "Intelligent Streaming") does not teach or suggest in detail "streaming by a media player operating on an end user station a video from a set of one or more servers, wherein each of a plurality of different copies of the video encoded at different bit rates is stored as multiple files on the set of servers, wherein each of the multiple files yields a different portion of the video on playback, wherein the multiple files across the different copies yield the same portions of the video on playback, each of said files having a time index such that the files whose playback is the same portion of the video for each of the different copies have the same time index in relation to the beginning of the video, and wherein the streaming comprises: requesting by the media player a plurality of sequential ones of the files of one of the copies from the set of servers over a plurality of Transmission Control Protocol (TCP) connections based on the time indexes; automatically requesting by the media player from the set of servers over the plurality of TCP connections subsequent portions of the video by requesting for each such portion one of the files from one of the copies dependent upon successive determinations by the media player to shift the playback quality to a higher or lower

quality one of the different copies, said automatically requesting including, repeatedly generating a set of one or more factors indicative of the current ability to sustain the streaming of the video using the files from different ones of the copies, wherein the set of one or more factors relate to the performance of the network; and making the successive determinations to shift the playback quality based on at least one of the set of factors to achieve continuous playback of the video using the files of the highest quality one of the copies determined sustainable at that time; and presenting the video by playing back with the media player on the end user station the requested files in order of ascending playback time" in combination with all the elements of the independent claim as argued by the Applicant.

Birney teaches multiple copies of the same stream being stored on a server at different bit rates with the same time index used to switch between the stream based on network bandwidth limitations. Whereas, stated above, Applicant's claimed invention states "streaming by a media player operating on an end user station a video from a set of one or more servers, wherein each of a plurality of different copies of the video encoded at different bit rates is stored as multiple files on the set of servers, wherein each of the multiple files yields a different portion of the video on playback, wherein the multiple files across the different copies yield the same portions of the video on playback, each of said files having a time index such that the files whose playback is the same portion of the video for each of the different copies have the same time index in relation to the beginning of the video, and wherein the streaming comprises: requesting by the media player a plurality of sequential ones of the files of one of the copies from

the set of servers over a plurality of Transmission Control Protocol (TCP) connections based on the time indexes; automatically requesting by the media player from the set of servers over the plurality of TCP connections subsequent portions of the video by requesting for each such portion one of the files from one of the copies dependent upon successive determinations by the media player to shift the playback quality to a higher or lower quality one of the different copies, said automatically requesting including, repeatedly generating a set of one or more factors indicative of the current ability to sustain the streaming of the video using the files from different ones of the copies, wherein the set of one or more factors relate to the performance of the network; and making the successive determinations to shift the playback quality based on at least one of the set of factors to achieve continuous playback of the video using the files of the highest quality one of the copies determined sustainable at that time; and presenting the video by playing back with the media player on the end user station the requested files in order of ascending playback time." So as indicated in the above statements. Applicant's arguments have been considered persuasive, in light of the claims limitation as well as the enabling portions of the specification.

Examiner also notes the board decision and reversal on 7/23/2014.

Any comments considered necessary by applicant must be submitted no later than the payment of the issue fee and, to avoid processing delays, should preferably accompany the issue fee. Such submissions should be clearly labeled “Comments on Statement of Reasons for Allowance.”

Any inquiry concerning this communication or earlier communications from the examiner should be directed to NINOS DONABED whose telephone number is (571)272-8757. The examiner can normally be reached on Monday-Friday, 7:30 AM-5:00 PM EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Peter-Anthony Pappas can be reached on (571) 272-7646. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/NINOS DONABED/
Primary Examiner, Art Unit 2444

Notice of References Cited	Application/Control No. 11/116,783	Applicant(s)/Patent Under Reexamination MAJOR ET AL.	
	Examiner NINOS DONABED	Art Unit 2444	Page 1 of 1

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	Classification
*	A	US-8,135,852	03-2012	Nilsson et al.	709/231
	B	US-			
	C	US-			
	D	US-			
	E	US-			
	F	US-			
	G	US-			
	H	US-			
	I	US-			
	J	US-			
	K	US-			
	L	US-			
	M	US-			

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	11116783	MAJOR ET AL.
	Examiner	**Art Unit**
	NINOS DONABED	2444

CPC								
Symbol							**Type**	**Version**
H04N		21	/	84			F	2013-01-01
H04N		21	/	25808			I	2013-01-01
H04N		21	/	2662			I	2013-01-01
H04N		21	/	643			I	2013-01-01
H04N		21	/	64769			I	2013-01-01
H04N		21	/	64792			I	2013-01-01
H04N		21	/	845			I	2013-01-01
			/					
			/					
			/					
			/					
			/					
			/					
			/					
			/					

CPC Combination Sets									
Symbol							**Type**	**Set**	**Ranking**	**Version**
			/							
			/							

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	21	
/NINOS DONABED/ Primary Examiner.Art Unit 2444	09/05/2014	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	20	7

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	11116783	MAJOR ET AL.
	Examiner	**Art Unit**
	NINOS DONABED	2444

US ORIGINAL CLASSIFICATION		INTERNATIONAL CLASSIFICATION	
CLASS	SUBCLASS	CLAIMED	NON-CLAIMED
709	231	G 0 6 F 15 / 16 (2006.01.01)	

CROSS REFERENCE(S)					
CLASS	SUBCLASS (ONE SUBCLASS PER BLOCK)				
709	246				

NONE		**Total Claims Allowed:**	
(Assistant Examiner)	(Date)	21	
/NINOS DONABED/ Primary Examiner.Art Unit 2444	09/05/2014	O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)	(Date)	20	7

Issue Classification	Application/Control No.	Applicant(s)/Patent Under Reexamination
	11116783	MAJOR ET AL.
	Examiner	**Art Unit**
	NINOS DONABED	2444

☐ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47

Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original
-	1	-	17	-	33	20	49								
-	2	-	18	-	34	21	50								
-	3	-	19	7	35										
-	4	1	20	8	36										
-	5	2	21	9	37										
-	6	-	22	10	38										
-	7	3	23	-	39										
-	8	4	24	11	40										
-	9	5	25	12	41										
-	10	6	26	13	42										
-	11	-	27	14	43										
-	12	-	28	15	44										
-	13	-	29	16	45										
-	14	-	30	17	46										
-	15	-	31	18	47										
-	16	-	32	19	48										

NONE (Assistant Examiner)	(Date)	**Total Claims Allowed:** 21	
/NINOS DONABED/ Primary Examiner.Art Unit 2444 (Primary Examiner)	09/05/2014 (Date)	O.G. Print Claim(s) 20	O.G. Print Figure 7

A test-bed for the dynamic **adaptive streaming** over HTTP featuring session mobility

C Müller, C Timmerer - Proceedings of the second annual ACM ..., 2011 - dl.acm.org
Abstract In this paper, we present a multimedia test-bed enabling session mobility in the context of the emerging ISO/IEC MPEG standard, Dynamic **Adaptive Streaming** over HTTP (DASH). In general, session mobility is defined as the transfer of a running **streaming ...**
Cited by 21 Related articles All 8 versions Cite Save

Low overhead container format for **adaptive streaming**

H Riiser, P Halvorsen, C Griwodz... - Proceedings of the first ..., 2010 - dl.acm.org
Abstract Current segmented HTTP **streaming** systems provide scalable and quality **adaptive** video delivery services to a huge number of users. However, while they support a wide range of bandwidths and enable arbitrary content-based composition, their current formats **...**
Cited by 20 Related articles All 9 versions Cite Save

Client intelligence for **adaptive streaming** solutions

D Jarnikov, T Özçelebi - Signal Processing: Image Communication, 2011 - Elsevier
In state-of-the-art **adaptive streaming** solutions, to cope with varying network conditions, the client side can switch between several video copies encoded at different bit-rates during **streaming**. Each video copy is divided into chunks of equal duration. To achieve **...**
Cited by 21 Related articles All 7 versions Cite Save

Parallel **adaptive** HTTP media **streaming**

C Liu, I Bouazizi, M Gabbouj - Computer Communications and ..., 2011 - ieeexplore.ieee.org
3GPP have paved the way to the development of media **streaming** over HTTP. The traditional HTTP **streaming** relies on a series of request segments and receive segments sequentially. In the current Internet media segments can be delivered through distributed **...**
Cited by 18 Related articles All 4 versions Cite Save

An end-to-end architecture for quality **adaptive streaming** applications in the internet

R Rejaie - 1999 - cs.usc.edu
The Internet has been experiencing explosive growth of audio and video **streaming**. Such applications are delay-sensitive, semi-reliable and rate-based. Thus they require isochronous processing and quality-of-service (QoS) from the end-to-end point of view. **...**
Cited by 24 Related articles All 2 versions Cite Save More

Adaptive streaming of MPEG-based audio/video content over wireless networks

M Burza, J Kang, P Stok - Journal of Multimedia, 2007 - academypublisher.com
Abstract This paper describes a method for robust **streaming** of combined MPEG audio/video content (encoded either with MPEG-2 or MPEG-4/H. 264) over in-home wireless networks. We make use of currently used content distribution format (MPEG Transport **...**
Cited by 18 Related articles All 12 versions Cite Save

Using scalable video coding for dynamic **adaptive streaming** over HTTP in mobile environments

C Muller, D Renzi, S Lederer, S Battista... - ... , 2012 Proceedings of ..., 2012 - ieeexplore.ieee.org
ABSTRACT Dynamic **Adaptive Streaming** over HTTP (DASH) is a convenient approach to transfer videos in an **adaptive** and dynamic way to the user. As a consequence, this system provides high bandwidth flexibility and is especially suitable for mobile use cases where **...**
Cited by 15 Related articles All 5 versions Cite Save

System and method for providing an **adaptive streaming** flow control mechanism between the TCP and IP layers of the TCP/IP suite of protocols

L Denecheau, D Esteve, JP Marce... - US Patent 6,880,017, 2005 - Google Patents
In a data communication network operated under the TCP/IP suite of protocols the invention adds an **adaptive streaming** (AS) layer, inserted between the IP and the TCP protocol layers, in which the received data packets of each open TCP connection are temporarily queued **...**
Cited by 18 Related articles All 2 versions Cite Save

A personalized HTTP **adaptive streaming** WebTV

RS Cruz, MS Nunes, JE Gonçalves - User Centric Media, 2010 - Springer
Abstract This paper presents a HTTP based multimedia content **streaming** architecture able to provide large scale WebTV services to end users connected over several access network technologies. The architecture features smooth Rate Adaptation, context Personalization **...**
Cited by 13 Related articles All 4 versions Cite Save

Adaptive streaming of audiovisual content using MPEG DASH

TC Thang, QD Ho, JW Kang... - ... , IEEE Transactions on, 2012 - ieeexplore.ieee.org
Abstract—HTTP **streaming** has become a cost effective means for multimedia delivery nowadays. In this paper, we study the use of MPEG DASH standard to stream audiovisual content. We first describe a novel estimation method for connection throughput. Then, **...**
Cited by 18 Related articles Cite Save

Industry and Standards

I Sodagar - 2011 - mobile.computer.org
... MPEG-Dynamic **Adaptive Streaming** (DASH) was developed to do just that. **...** Iraj Sodagar Microsoft Corporation Editor's Note MPEG has recently finalized a new standard to enable dynamic and **adaptive streaming** of media over HTTP. **...**
Cited by 119 Related articles All 10 versions Cite Save

Watching video over the web: Part 1: **Streaming** protocols

AC Begen, T Akgul, M Baugher - Internet Computing, IEEE, 2011 - ieeexplore.ieee.org
... Page 3. 3 QuickTime and Adobess Flash as well as the emerging **adaptive streaming** technologies such as Microsoftss Smooth **Streaming**, Appless HTTP Live **Streaming** and Adobess HTTP Dynamic **Streaming** run over mostly unmanaged, ie, bestĞeffort, networks. **...**
Cited by 87 Related articles All 5 versions Cite Save

Interactions between HTTP **adaptive streaming** and TCP

J Esteban, SA Benno, A Beck, Y Guo, V Hilt... - Proceedings of the 22nd ..., 2012 - dl.acm.org
Abstract HTTP **adaptive streaming** (HAS) is quickly becoming a popular mechanism for delivering on-demand video content over the Internet. The chunked transmission and application-layer adaptation create a very different traffic pattern than traditional **...**
Cited by 15 Related articles Cite Save

End-to-end frame-rate **adaptive streaming** of video data

C Fung, SC Liew - Multimedia Computing and Systems, 1999. ..., 1999 - ieeexplore.ieee.org
Abstract We propose a best-eflort video delivery scheme that can be deployed on networks in use today, including Ethernet LAN's or the Internet. This scheme detects congestion by m) easuring the buffer occupancy and loss rate and estimate available channel bandwidth by **...**
Cited by 13 Related articles All 7 versions Cite Save

Advances in channel **adaptive** video **streaming**

B Girod, M Kalman, YJ Liang... - ... and Mobile Computing, 2002 - Wiley Online Library
Abstract Despite the well-known challenges of variations in throughput, delay, and packet loss over the Internet, video **streaming** has experienced phenomenal growth, owing to the extensive research in video coding and transmission. In this paper, we review several **...**
Cited by 156 Related articles All 16 versions Cite Save

Adaptive stereoscopic 3D video **streaming**

CG Gurler
ABSTRACT This paper presents a comparative analysis of scalable stereoscopic video coding strategies for **adaptive streaming**. In particular, we compare scalable simulcast coding of both views using SVC with scalable coding of one view with SVC and non- **...**
Cited by 13 Related articles All 3 versions Cite Save

Rate adaptation for dynamic **adaptive streaming** over HTTP in content distribution network

C Liu, I Bouazizi, MM Hannuksela... - Signal Processing: Image ..., 2012 - Elsevier
Recently the 3rd Generation Partnership Project (3GPP) and the Moving Picture Experts Group (MPEG) specified Dynamic **Adaptive Streaming** over HTTP (DASH) to cope with the shortages in progressive HTTP based downloading and Real-time Transport Protocol (**...**
Cited by 19 Related articles All 7 versions Cite Save

Http **adaptive streaming** in practice

M Watson - Proceedings of the ACM Multimedia Systems ..., 2011
Cited by 15 Related articles Cite Save

PALS: peer-to-peer **adaptive** layered **streaming**

R Rejaie, A Ortega - Proceedings of the 13th international workshop on ..., 2003 - dl.acm.org
Abstract This paper presents a new framework for Peer-to-Peer **Adaptive** Layered **Streaming**, called PALS. PALS is a receiver-driven approach for quality **adaptive** playback of layer encoded **streaming** media from a group of congestion controlled sender peers to a **...**
Cited by 237 Related articles All 18 versions Cite Save

Adaptive streaming on heterogeneous networks

M Bernaschi, F Cacace, R Clementelli... - Proceedings of the 1st ..., 2005 - dl.acm.org

Abstract Specific network protocols, like MobileIP, offer seamless connectivity to mobile systems. However, the QoS requirements of **streaming** applications and video conferencing systems require an approach that spans across different layers of the network stack. In this **...**

Cited by 13 Related articles All 3 versions Cite Save

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	4780	(upconvert$3 or upshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L2	4780	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L3	0	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near3 copi$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L4	16	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L5	256	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L6	247	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.) and network	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L7	23173	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L8	760253	((multiple or plurality or many or	US-PGPUB;	OR	ON	2014/08/21

		three or two) near5 (version or format$4 or copies or cop$4))	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:42
L9	23173	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L10	2360	L9 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L11	2360	L9 and "709"/$$$.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L12	745	L9 and "709"/231.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L13	8	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L14	44	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L15	21	L14 and (Stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L16	5	L14 and (Stream$3 or (video with stream$3)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/08/21 22:42

			DERWENT; IBM_TDB			
L17	260	L9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L18	260	L9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L19	0	L9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" same (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L20	260	L9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L21	8168	L9 and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L22	191	L9 and @ad<"20040430" and (upshift$3 or upconvert$3 or downshift$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L23	10	L22 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L24	1	L22 and "709"/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L25	1	L22 and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR;	OR	ON	2014/08/21 22:42

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
L26	20864	"709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L27	43	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L28	43	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L29	18	(real near2 network).as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L30	202	(sure-stream or sure adj stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:42
L31	45	(sure-stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L32	4	"7054948".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L33	1	"7054948".pn. and surestream	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L34	11	"7406527".pn.	US-PGPUB;	OR	ON	2014/08/21

			USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L35	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L36	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L37	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L38	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls. and @ad< "20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L39	107	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L40	0	L39 and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L41	0	L39 and (upconvert$3 or upshift$3 or downshift$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L42	140	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

		@ad<"20040430")	IBM_TDB			
L43	0	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad<"20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L44	4	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L45	23	((dynamically) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L46	0	((dynamical) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L47	47	((dynamic$5) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L48	24	L47 not L45	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L49	927	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L50	166	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L51	88	(((multiple or plurality or many or	US-PGPUB;	OR	ON	2014/08/21

		three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/$$$.ccls.	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L52	32	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L53	20864	"709""/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L54	3588	(multi-rate and (stream$3 or (video with stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L55	49	(multi-rate and (stream$3 or (video with stream$3))).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L56	8	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L57	44	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L58	21	L57 and (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43

L59	1	L57 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L60	4	L57 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3 or quality or (high and low)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L61	1173017	(plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L62	1239	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4 or dynamic$5) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L63	138	L62 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L64	68	L62 and "709"/$$$.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L65	5	L62 and "709"/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L66	741	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L67	742	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5 or (bit adj2 rate or bit-rate))) with ((automatic$4) near5 (switch$3 or	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/08/21 22:43

		chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	DERWENT; IBM_TDB			
L68	5	L67 and "709"/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L69	23849	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near8 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L70	13449	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L71	73	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L72	0	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L73	3	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/230-234.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L74	14726	709/231-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L75	6098	709/231-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L76	851	L75 and ((multiple or plurality or many or three) near5 files)	US-PGPUB; USPAT; USOCR;	OR	ON	2014/08/21 22:43

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
L77	733	L75 and ((multiple or plurality or many or three) near3 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L78	276	L75 and ((multiple or plurality or many or three) near3 copies)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L79	1	L75 and ((multiple or plurality or many or three) near3 copies) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L80	18	L75 and ((multiple or plurality or many or three) near3 (copies or files)) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L81	1	L75 and ((multiple or plurality or many or three) near3 (copies))with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L82	1	L75 and ((multiple or plurality or many or three) near3 (copies)) with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L83	276	L75 and ((multiple or plurality or many or three) near3 (copies))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L84	1	L75 and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L85	8	@ad< "20050408" and ((multiple or	US-PGPUB;	OR	ON	2014/08/21

		plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L86	905	(dynamic near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L87	315	(dynamic near5 stream$3).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L88	16	(dynamic near5 stream$3).ti. and @ad<"20050408" and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L89	3	"5832300".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L90	0	(dautomatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L91	728	(automatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L92	358	@ad<"20050408" and L91	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L93	0	(automatic$4 near5 stream$3 with (upshif$3 or downshif$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

			IBM_TDB			
L94	0	(automatic$4 near5 stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L95	0	(automatic$4 with stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L96	5	(stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L97	0	(stream$3 with (video with stream$3)).ti. and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L98	0	(stream$3 with (video with stream$3)) and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L99	2163208	(dynamic$3 and switch$3 and stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L100	525324	(dynamic$3 and switch$3 and stream$3 or video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L101	1	(dynamic$3 and switch$3 and stream$3 and video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L102	1	(dynamic$3 and switch$3 and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2014/08/21 22:43

			JPO; DERWENT; IBM_TDB			
L103	1	(dynamic$3 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L104	14	(automatic$4 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L105	15	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L106	245	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video))	DERWENT	OR	ON	2014/08/21 22:43
L107	9	(automatic$4 near5 (switch$3 or shift$3 or upshift$3) near5 (stream$3 and video))	DERWENT	OR	ON	2014/08/21 22:43
L108	2	(automatic$4 near5 (copies or files or versions) near5 (stream$3 and video))	DERWENT	OR	ON	2014/08/21 22:43
L109	30	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	DERWENT	OR	ON	2014/08/21 22:43
L110	956	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L111	118	L110 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L112	223139	(multiple or many or three or plurality) near5 ((files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L113	2953	L112 and 709/230-234.ccls.	US-PGPUB; USPAT;	OR	ON	2014/08/21 22:43

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
L114	1281	L112 and 709/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L115	28	L112 and 709/230-234.ccls. and (upshift$3 or downshift$3 or upcovert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L116	12	L112 and 709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L117	18	709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L118	28	((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L119	100721	microsoft.as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L120	1733	microsoft.as. and (stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L121	753	microsoft.as. and (stream$3).ti. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43

L122	7	microsoft.as. and (stream$3 with quality).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L123	0	(automatica$3 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L124	0	(automatic$5 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L125	0	(automatic$5 near5 switch$3 near5 ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L126	1	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L127	6	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L128	2	"20050262257".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L129	0	"20050262257".pn. and (ration or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L130	1	"20050262257".pn. and (ratio or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/08/21 22:43

			DERWENT; IBM_TDB			
L131	0	"20050262257".pn. and (sub-parts or subparts)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L132	1	"20050262257".pn. and (safe$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L133	2	"2002174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L134	2	"20020174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L135	2	"20020144276".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L136	11	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L137	1	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN. and clip$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L138	1	"20020188745".pn. and play$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L139	0	"20020188745".pn. and tcp	US-PGPUB; USPAT; USOCR;	OR	ON	2014/08/21 22:43

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
L140	0	"20020188745".pn. and http	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L141	1	"20020188745".pn. and web	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L142	2	"20020188745".pn. and internet	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L143	8077890	((plurality or mutiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L144	8078220	((plurality or multiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L145	4637	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L146	120	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L147	64	(((plurality or multiple) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L148	0	"20020188745".pn. and cache	US-PGPUB;	OR	ON	2014/08/21

			USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L149	0	"20020188745".pn. and operator	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L150	1	"20020188745".pn. and separate	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L151	1	"20050262257".pn. and (cache)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L152	1	"20050262257".pn. and (saf$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L153	4780	(upconvert$3 or upshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L154	4780	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L155	0	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near3 copi$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L156	16	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

			IBM_TDB			
L157	256	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L158	247	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.) and network	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L159	23173	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L160	760253	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L161	23173	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L162	2360	L161 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L163	2360	L161 and "709"/$$$.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L164	745	L161 and "709"/231.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L165	8	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2014/08/21 22:43

			JPO; DERWENT; IBM_TDB			
L166	44	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L167	21	L166 and (Stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L168	5	L166 and (Stream$3 or (video with stream$3)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L169	260	L161 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L170	260	L161 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L171	0	L161 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" same (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L172	260	L161 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L173	8168	L161 and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L174	191	L161 and @ad<"20040430" and	US-PGPUB;	OR	ON	2014/08/21

		(upshift$3 or upconvert$3 or downshift$3 or downconvert$3)	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L175	10	L174 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L176	1	L174 and "709"/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L177	1	L174 and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L178	20864	"709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L179	43	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L180	43	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L181	18	(real near2 network).as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L182	202	(sure-stream or sure adj stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

			IBM_TDB			
L183	45	(sure-stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L184	4	"7054948".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L185	1	"7054948".pn. and surestream	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L186	11	"7406527".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L187	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L188	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L189	2279	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L191	107	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad<"20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L192	0	L191 and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2014/08/21 22:43

			JPO; DERWENT; IBM_TDB			
L193	0	L191 and (upconvert$3 or upshift$3 or downshift$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L194	140	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L195	0	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L196	4	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L197	23	((dynamically) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L198	0	((dynamical) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L199	47	((dynamic$5) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L200	24	L199 not L197	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L201	927	(((multiple or plurality or many or	US-PGPUB;	OR	ON	2014/08/21

		three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430")	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L202	166	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L203	88	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L204	32	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L205	20864	"709""/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L206	3588	(multi-rate and (stream$3 or (video with stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L207	49	(multi-rate and (stream$3 or (video with stream$3))).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L208	8	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

			IBM_TDB			
L209	44	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L210	21	L209 and (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L211	1	L209 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L212	4	L209 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3 or quality or (high and low)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L213	1173017	(plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L214	1239	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4 or dynamic$5) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L215	138	L214 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L216	68	L214 and "709"/$$$.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L217	5	L214 and "709"/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR;	OR	ON	2014/08/21 22:43

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
L218	741	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L219	742	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5 or (bit adj2 rate or bit-rate))) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L220	5	L219 and "709"/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L221	23849	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near8 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L222	13449	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L223	73	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L224	0	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L225	3	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/230-234.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L226	14726	709/231-234.ccls.	US-PGPUB;	OR	ON	2014/08/21

			USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L227	6098	709/231-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L228	851	L227 and ((multiple or plurality or many or three) near5 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L229	733	L227 and ((multiple or plurality or many or three) near3 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L230	276	L227 and ((multiple or plurality or many or three) near3 copies)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L231	1	L227 and ((multiple or plurality or many or three) near3 copies) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L232	18	L227 and ((multiple or plurality or many or three) near3 (copies or files)) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L233	1	L227 and ((multiple or plurality or many or three) near3 (copies))with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L234	1	L227 and ((multiple or plurality or many or three) near3 (copies)) with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

			IBM_TDB			
L235	276	L227 and ((multiple or plurality or many or three) near3 (copies))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L236	1	L227 and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L237	8	@ad<"20050408" and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L238	905	(dynamic near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L239	315	(dynamic near5 stream$3).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L240	16	(dynamic near5 stream$3).ti. and @ad<"20050408" and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L241	3	"5832300".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L242	0	(dautomatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L243	728	(automatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2014/08/21 22:43

			JPO; DERWENT; IBM_TDB			
L244	358	@ad<"20050408" and L243	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L245	0	(automatic$4 near5 stream$3 with (upshif$3 or downshif$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L246	0	(automatic$4 near5 stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L247	0	(automatic$4 with stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L248	5	(stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L249	0	(stream$3 with (video with stream$3)).ti. and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L250	0	(stream$3 with (video with stream$3)) and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L251	2163208	(dynamic$3 and switch$3 and stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L252	525324	(dynamic$3 and switch$3 and stream$3 or video).ti.	US-PGPUB; USPAT;	OR	ON	2014/08/21 22:43

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
L253	1	(dynamic$3 and switch$3 and stream$3 and video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L254	1	(dynamic$3 and switch$3 and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L255	1	(dynamic$3 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L256	14	(automatic$4 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L257	15	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L258	245	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video))	DERWENT	OR	ON	2014/08/21 22:43
L259	9	(automatic$4 near5 (switch$3 or shift$3 or upshift$3) near5 (stream$3 and video))	DERWENT	OR	ON	2014/08/21 22:43
L260	2	(automatic$4 near5 (copies or files or versions) near5 (stream$3 and video))	DERWENT	OR	ON	2014/08/21 22:43
L261	30	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	DERWENT	OR	ON	2014/08/21 22:43
L262	956	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43

L263	118	L262 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L264	223139	(multiple or many or three or plurality) near5 ((files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L265	2953	L264 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L266	1281	L264 and 709/230-234.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L267	28	L264 and 709/230-234.ccls. and (upshift$3 or downshift$3 or upcovert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L268	12	L264 and 709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L269	18	709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L270	28	((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L271	100721	microsoft.as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/08/21 22:43

			DERWENT; IBM_TDB			
L272	1733	microsoft.as. and (stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L273	753	microsoft.as. and (stream$3).ti. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L274	7	microsoft.as. and (stream$3 with quality).ti. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L275	0	(automatica$3 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L276	0	(automatic$5 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L277	0	(automatic$5 near5 switch$3 near5 ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L278	1	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L279	6	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L280	2	"20050262257".pn.	US-PGPUB; USPAT; USOCR;	OR	ON	2014/08/21 22:43

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
L281	0	"20050262257".pn. and (ration or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L282	1	"20050262257".pn. and (ratio or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L283	0	"20050262257".pn. and (sub-parts or subparts)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L284	1	"20050262257".pn. and (safe$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L285	2	"2002174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L286	2	"20020174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L287	2	"20020144276".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L288	11	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L289	1	("20020078209" | "20040117459" |	US-PGPUB;	OR	ON	2014/08/21

		"20050021616" | "20060031523").PN. and clip$4	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			22:43
L290	1	"20020188745".pn. and play$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L291	0	"20020188745".pn. and tcp	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L292	0	"20020188745".pn. and http	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L293	1	"20020188745".pn. and web	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L294	2	"20020188745".pn. and internet	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L295	8077890	((plurality or mutiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L296	4637	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L297	120	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/08/21 22:43

			IBM_TDB			
L298	64	(((plurality or multiple) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L299	0	"20020188745".pn. and cache	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L300	0	"20020188745".pn. and operator	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L301	1	"20020188745".pn. and separate	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L302	1	"20050262257".pn. and (cache)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L303	1	"20050262257".pn. and (saf$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L304	103	((R) near2 (Major)).INV.	US-PGPUB; USPAT; USOCR	OR	ON	2014/08/21 22:43
L305	19	((Mark) near2 (Hurst)).INV.	US-PGPUB	OR	ON	2014/08/21 22:43
L306	57	(709/246.ccls.) and L296	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L307	67	((Mark) near2 (Hurst)).INV.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/08/21 22:43

			DERWENT; IBM_TDB			
L308	1	((Mark) near2 (Hurst)).INV. and tcp.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 22:43
L309	103	((R) near2 (Major)).INV.	US-PGPUB; USPAT; USOCR	OR	ON	2014/08/21 22:43
L314	129563	35 ((H04N21/84 OR H04N21/6125 OR H04N21/47202 OR H04N21/482 OR H04W84/045 OR H04W12/06 OR H04W76/023 OR H04L65/80 OR H04L65/1016 OR H04L65/607).CPC.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 23:19
L315	524	35 and ((H04N21/84 OR H04N21/6125 OR H04N21/47202 OR H04N21/482 OR H04W84/045 OR H04W12/06 OR H04W76/023 OR H04L65/80 OR H04L65/1016 OR H04L65/607).CPC.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 23:19
L316	524	38 and ((H04N21/84 OR H04N21/6125 OR H04N21/47202 OR H04N21/482 OR H04W84/045 OR H04W12/06 OR H04W76/023 OR H04L65/80 OR H04L65/1016 OR H04L65/607).CPC.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 23:19
L317	177	49 and ((H04N21/84 OR H04N21/6125 OR H04N21/47202 OR H04N21/482 OR H04W84/045 OR H04W12/06 OR H04W76/023 OR H04L65/80 OR H04L65/1016 OR H04L65/607).CPC.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/08/21 23:19
S1	899	(upconvert$3 or upshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:04
S2	899	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:04
S3	0	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near3 copi$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:05

S4	2	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:06
S5	85	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:06
S6	81	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.) and network	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:06
S7	12707	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:08
S8	441696	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:08
S9	12707	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:08
S10	1044	S9 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:09
S11	1044	S9 and "709"/$$$.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:09
S12	299	S9 and "709"/231.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2009/02/09 17:09

			DERWENT; IBM_TDB			
S13	6	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:12
S14	32	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:12
S15	21	S14 and (Stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:13
S16	5	S14 and (Stream$3 or (video with stream$3)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:13
S17	229	S9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:15
S18	229	S9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:15
S19	0	S9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" same (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:16
S20	229	S9 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:16
S21	7262	S9 and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT;	OR	ON	2009/02/09 17:18

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S22	186	S9 and @ad<"20040430" and (upshift$3 or upconvert$3 or downshift$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:19
S23	10	S22 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:19
S24	1	S22 and "709"/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:20
S25	1	S22 and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:20
S26	7913	"709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:20
S27	7	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:21
S28	7	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:22
S29	14	(real near2 network).as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:32

S30	142	(sure-stream or sure adj stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:35
S31	26	(sure-stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:35
S32	2	"7054948".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:37
S33	1	"7054948".pn. and surestream	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 17:37
S34	9	"7406527".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:01
S35	855	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:02
S36	855	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:03
S37	855	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:03
S38	855	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls. and	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2009/02/09 18:03

		@ad< "20040430"	DERWENT; IBM_TDB			
S39	94	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:04
S40	0	S39 and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:08
S41	0	S39 and (upconvert$3 or upshift$3 or downshift$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 18:08
S42	121	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:25
S43	0	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:30
S44	0	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:31
S45	2	((dynamically) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:33
S46	0	((dynamical) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:34
S47	5	((dynamic$5) with (((multiple or plurality or many or three or two)	US-PGPUB; USPAT;	OR	ON	2009/02/09 19:34

		near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S48	3	S47 not S45	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:36
S49	782	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:45
S50	146	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:56
S51	78	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 19:58
S52	29	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 20:01
S53	7913	"709""/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 20:02
S54	1660	(multi-rate and (stream$3 or (video with stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 20:04

S55	11	(multi-rate and (stream$3 or (video with stream$3))).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/09 20:04
S56	6	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:44
S57	32	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:45
S58	21	S57 and (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:45
S59	1	S57 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:46
S60	4	S57 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3 or quality or (high and low)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:47
S61	670510	(plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:51
S62	662	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4 or dynamic$5) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 14:52
S64	72	S62 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2009/02/11 15:02

			JPO; DERWENT; IBM_TDB			
S65	62	S62 and "709"/$$$.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:05
S66	5	S62 and "709"/230-234.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:06
S67	424	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:07
S68	425	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5 or (bit adj2 rate or bit-rate))) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:08
S69	5	S68 and "709"/230-234.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:09
S70	12589	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near8 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:10
S71	6937	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:10
S72	26	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:11
S73	0	(stream$3 or (video with stream$3)) and ((plurality or many or multiple)	US-PGPUB; USPAT;	OR	ON	2009/02/11 15:11

		near4 automat$5) and 709/231.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S74	2	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/230-234.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:12
S75	5236	709/231-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:12
S76	4485	709/231-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:12
S77	691	S76 and ((multiple or plurality or many or three) near5 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:13
S78	591	S76 and ((multiple or plurality or many or three) near3 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:14
S79	233	S76 and ((multiple or plurality or many or three) near3 copies)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:14
S80	1	S76 and ((multiple or plurality or many or three) near3 copies) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:15
S81	9	S76 and ((multiple or plurality or many or three) near3 (copies or files)) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:25

S82	1	S76 and ((multiple or plurality or many or three) near3 (copies))with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:27
S83	1	S76 and ((multiple or plurality or many or three) near3 (copies)) with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:27
S84	233	S76 and ((multiple or plurality or many or three) near3 (copies))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:28
S85	1	S76 and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:28
S86	6	@ad<"20050408" and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:29
S87	251	(dynamic near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:32
S88	169	(dynamic near5 stream$3).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:34
S89	10	(dynamic near5 stream$3).ti. and @ad<"20050408" and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:34
S90	2	"5832300".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2009/02/11 15:40

			DERWENT; IBM_TDB			
S91	0	(dautomatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:41
S92	326	(automatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:41
S93	241	@ad<"20050408" and S92	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:42
S94	0	(automatic$4 near5 stream$3 with (upshif$3 or downshif$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:43
S95	0	(automatic$4 near5 stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:43
S96	0	(automatic$4 with stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:43
S97	3	(stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:43
S98	0	(stream$3 with (video with stream$3)).ti. and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:52
S99	0	(stream$3 with (video with stream$3)) and (automatic$4 near4 switch$3 near4 different near4	US-PGPUB; USPAT; USOCR;	OR	ON	2009/02/11 15:52

		quality)	FPRS; EPO; JPO; DERWENT; IBM_TDB			
S100	1081374	(dynamic$3 and switch$3 and stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:57
S101	271819	(dynamic$3 and switch$3 and stream$3 or video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:58
S102	0	(dynamic$3 and switch$3 and stream$3 and video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:58
S103	0	(dynamic$3 and switch$3 and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:59
S104	0	(dynamic$3 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:59
S105	5	(automatic$4 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:59
S106	6	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 15:59
S107	108	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video))	DERWENT	OR	ON	2009/02/11 16:00
S108	6	(automatic$4 near5 (switch$3 or shift$3 or upshift$3) near5 (stream$3 and video))	DERWENT	OR	ON	2009/02/11 16:02
S109	1	(automatic$4 near5 (copies or files or	DERWENT	OR	ON	2009/02/11

		versions) near5 (stream$3 and video))				16:02
S110	11	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	DERWENT	OR	ON	2009/02/11 16:03
S111	365	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:04
S112	37	S111 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:04
S113	108249	(multiple or many or three or plurality) near5 ((files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:10
S114	1240	S113 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:11
S115	1038	S113 and 709/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:11
S116	11	S113 and 709/230-234.ccls. and (upshift$3 or downshift$3 or upcovert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:12
S117	3	S113 and 709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:14
S118	3	709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2009/02/11 16:14

			IBM_TDB			
S119	7	((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:15
S120	50419	microsoft.as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:15
S121	981	microsoft.as. and (stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:16
S122	650	microsoft.as. and (stream$3).ti. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:16
S123	6	microsoft.as. and (stream$3 with quality).ti. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:17
S124	0	(automatica$3 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:19
S125	0	(automatic$5 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:20
S126	0	(automatic$5 near5 switch$3 near5 ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:20
S127	0	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2009/02/11 16:20

			JPO; DERWENT; IBM_TDB			
S128	6	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/11 16:22
S129	2	"20050262257".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:34
S130	0	"20050262257".pn. and (ration or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:38
S131	1	"20050262257".pn. and (ratio or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:39
S132	0	"20050262257".pn. and (sub-parts or subparts)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:39
S133	1	"20050262257".pn. and (safe$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:43
S134	2	"2002174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:49
S135	2	"20020174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 17:49
S136	2	"20020144276".pn.	US-PGPUB; USPAT;	OR	ON	2009/02/13 17:51

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S137	8	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 18:33
S138	1	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN. and clip$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 18:33
S139	1	"20020188745".pn. and play$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 18:37
S140	0	"20020188745".pn. and tcp	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:00
S141	0	"20020188745".pn. and http	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:00
S142	1	"20020188745".pn. and web	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:00
S143	2	"20020188745".pn. and internet	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:01
S144	4765975	((plurality or mutiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:03

S145	4766104	((plurality or multiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:03
S146	2131	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:03
S147	30	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:04
S148	12	(((plurality or multiple) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:07
S149	0	"20020188745".pn. and cache	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:22
S150	0	"20020188745".pn. and operator	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:22
S151	1	"20020188745".pn. and separate	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:25
S152	1	"20050262257".pn. and (cache)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2009/02/13 19:25
S153	1	"20050262257".pn. and (saf$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2009/02/13 19:36

			DERWENT; IBM_TDB			
S154	4705	(upconvert$3 or upshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S155	4705	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S156	0	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near3 copi$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S157	16	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) same ((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S158	253	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S159	244	(upconvert$3 or upshift$3) with (stream$3 or (video with stream$3)) and ("709"/$$$.ccls. or "725"/$$$.ccls.) and network	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S160	23030	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)) same (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S161	756102	((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S162	23030	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same	US-PGPUB; USPAT; USOCR;	OR	ON	2014/07/31 00:31

		(stream$3 or (video with stream$3))	FPRS; EPO; JPO; DERWENT; IBM_TDB			
S163	2345	S162 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S164	2345	S162 and "709"/$$$.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S165	738	S162 and "709"/231.ccls. and (stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S166	8	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S167	44	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S168	21	S167 and (Stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S169	5	S167 and (Stream$3 or (video with stream$3)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S170	260	S162 and "709"/231.ccls. and (stream$3 or video) and @ad< "20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31

S171	260	S162 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S172	0	S162 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" same (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S173	260	S162 and "709"/231.ccls. and (stream$3 or video) and @ad<"20040430" and (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S174	8168	S162 and (stream$3 or video) and @ad<"20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S175	191	S162 and @ad<"20040430" and (upshift$3 or upconvert$3 or downshift$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S176	10	S175 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S177	1	S175 and "709"/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S178	1	S175 and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S179	20509	"709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/07/31 00:31

			DERWENT; IBM_TDB			
S180	42	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with strem$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S181	42	"709"/230-234.ccls. and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S182	18	(real near2 network).as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S183	202	(sure-stream or sure adj stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S184	45	(sure-stream or surestream)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S185	4	"7054948".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S186	1	"7054948".pn. and surestream	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S187	11	"7406527".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S188	2259	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same	US-PGPUB; USPAT; USOCR;	OR	ON	2014/07/31 00:31

		(stream$3 or (video with stream$3)) same server	FPRS; EPO; JPO; DERWENT; IBM_TDB			
S189	2259	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S190	2259	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S191	2259	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and709/231.ccls. and @ad< "20040430"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S192	107	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S193	0	S192 and (upconvert$3 or upshift$3 or downshift$3) with (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S194	0	S192 and (upconvert$3 or upshift$3 or downshift$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S195	140	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S196	0	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server and (709/231.ccls. and @ad< "20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31

S197	4	((dynamically near3 chang$4) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S198	23	((dynamically) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S199	0	((dynamical) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S200	46	((dynamic$5) with (((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4)))) same3 (stream$3 or (video with stream$3)) same server	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S201	23	S200 not S198	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S202	927	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430")	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S203	166	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S204	88	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31

S205	32	(((multiple or plurality or many or three or two) near5 (version or format$4 or copies or cop$4))) same3 (stream$3 or (video with stream$3)) same server and (@ad<"20040430") and ((dynamic$5 or automatical$5) near3 (upshift$3 or downshift$3 or upconvert$3 or downcovnert$3 or chan$4)) and "709"/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S206	20509	"709""/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S207	3562	(multi-rate and (stream$3 or (video with stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S208	49	(multi-rate and (stream$3 or (video with stream$3))).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S209	8	("20020174434" | "20030067872" | "20040030797").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S210	44	("20020174434" | "20030067872" | "20040030797").PN. or ("20020073167" | "20050123058" | "20070024705" | "20080028428" | "20080056373" | "6091775" | "6091777" | "6510553" | "6731600" | "6732183" | "6968387" | "7075986" | "7349976").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S211	21	S210 and (stream$3 or (video with stream$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S212	1	S210 and (stream$3 or (video with stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S213	4	S210 and (stream$3 or (video with	US-PGPUB;	OR	ON	2014/07/31

		stream$3)) and ((plurality or many or multiple) near5 (version or format or cop$3 or quality or (high and low)))	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			00:31
S214	1166673	(plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S215	1235	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4 or dynamic$5) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S216	138	S215 and "709"/$$$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S217	68	S215 and "709"/$$$.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S218	5	S215 and "709"/230-234.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S219	739	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5)) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S220	740	((plurality or many or three or two or multiple) near5 (file or cop$3 or version or format$3 or compress$5 or (bit adj2 rate or bit-rate))) with ((automatic$4) near5 (switch$3 or chang$3 or upshift$3 or downshift$3 or upconvert$3 or downconvert$3))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S221	5	S220 and "709"/230-234.ccls. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/07/31 00:31

			IBM_TDB			
S222	23672	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near8 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S223	13352	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S224	73	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S225	0	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/231.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S226	3	(stream$3 or (video with stream$3)) and ((plurality or many or multiple) near4 automat$5) and 709/230-234.ccls. and (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S227	14464	709/231-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S228	6072	709/231-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S229	851	S228 and ((multiple or plurality or many or three) near5 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S230	733	S228 and ((multiple or plurality or many or three) near3 files)	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2014/07/31 00:31

			JPO; DERWENT; IBM_TDB			
S231	276	S228 and ((multiple or plurality or many or three) near3 copies)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S232	1	S228 and ((multiple or plurality or many or three) near3 copies) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S233	18	S228 and ((multiple or plurality or many or three) near3 (copies or files)) near5 (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S234	1	S228 and ((multiple or plurality or many or three) near3 (copies))with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S235	1	S228 and ((multiple or plurality or many or three) near3 (copies)) with (encod$3 or bit-rate or qualilty)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S236	276	S228 and ((multiple or plurality or many or three) near3 (copies))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S237	1	S228 and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S238	8	@ad<"20050408" and ((multiple or plurality or many or three) near3 (copies)) near5 (bit adj3 rate)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S239	898	(dynamic near5 stream$3).ti.	US-PGPUB; USPAT;	OR	ON	2014/07/31 00:31

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S240	315	(dynamic near5 stream$3).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S241	16	(dynamic near5 stream$3).ti. and @ad<"20050408" and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S242	3	"5832300".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S243	0	(dautomatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S244	727	(automatic$4 near5 stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S245	358	@ad<"20050408" and S244	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S246	0	(automatic$4 near5 stream$3 with (upshif$3 or downshif$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S247	0	(automatic$4 near5 stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31

S248	0	(automatic$4 with stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S249	5	(stream$3 with (upshift$3 or downshift$3 or upconvert$3 or downconvert$3)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S250	0	(stream$3 with (video with stream$3)).ti. and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S251	0	(stream$3 with (video with stream$3)) and (automatic$4 near4 switch$3 near4 different near4 quality)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S252	2150270	(dynamic$3 and switch$3 and stream$3 or video)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S253	523542	(dynamic$3 and switch$3 and stream$3 or video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S254	1	(dynamic$3 and switch$3 and stream$3 and video).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S255	1	(dynamic$3 and switch$3 and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S256	1	(dynamic$3 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2014/07/31 00:31

			DERWENT; IBM_TDB			
S257	13	(automatic$4 and (switch$3 or shivt$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S258	14	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video)).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S259	241	(automatic$4 and (switch$3 or shift$3 or upshift$3) and (stream$3 and video))	DERWENT	OR	ON	2014/07/31 00:31
S260	9	(automatic$4 near5 (switch$3 or shift$3 or upshift$3) near5 (stream$3 and video))	DERWENT	OR	ON	2014/07/31 00:31
S261	2	(automatic$4 near5 (copies or files or versions) near5 (stream$3 and video))	DERWENT	OR	ON	2014/07/31 00:31
S262	29	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	DERWENT	OR	ON	2014/07/31 00:31
S263	945	(multiple or many or three or plurality) near5 ((files or version) near5 (quality or bit-rate or bit adj rate))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S264	117	S263 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S265	221423	(multiple or many or three or plurality) near5 ((files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S266	2932	S265 and 709/230-234.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S267	1281	S265 and 709/230-234.ccls. and @ad< "20050408"	US-PGPUB; USPAT; USOCR;	OR	ON	2014/07/31 00:31

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
S268	28	S265 and 709/230-234.ccls. and (upshift$3 or downshift$3 or upcovert$3 or downconvert$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S269	12	S265 and 709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S270	17	709/230-234.ccls. and ((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S271	27	((upshift$3 or downshift$3 or upcovert$3 or downconvert$3) with (quality with (video or stream$3)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S272	100080	microsoft.as.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S273	1724	microsoft.as. and (stream$3).ti.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S274	753	microsoft.as. and (stream$3).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S275	7	microsoft.as. and (stream$3 with quality).ti. and @ad<"20050408"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S276	0	(automatica$3 near5 switch$3 near5	US-PGPUB;	OR	ON	2014/07/31

		(different near5 qualit$5) near5 (files or version))	USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			00:31
S277	0	(automatic$5 near5 switch$3 near5 (different near5 qualit$5) near5 (files or version))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S278	0	(automatic$5 near5 switch$3 near5 ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S279	1	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((different near5 qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S280	6	((automatic$5 near5 (switch$3 or upshift$3 or downshift$3 or upconvert$3)) with ((qualit$5) near5 (files or version)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S281	2	"20050262257".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S282	0	"20050262257".pn. and (ration or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S283	1	"20050262257".pn. and (ratio or average)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S284	0	"20050262257".pn. and (sub-parts or subparts)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT;	OR	ON	2014/07/31 00:31

			IBM_TDB			
S285	1	"20050262257".pn. and (safe$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S286	2	"2002174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S287	2	"20020174434".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S288	2	"20020144276".pn.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S289	11	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S290	1	("20020078209" | "20040117459" | "20050021616" | "20060031523").PN. and clip$4	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S291	1	"20020188745".pn. and play$3	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S292	0	"20020188745".pn. and tcp	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S293	0	"20020188745".pn. and http	US-PGPUB; USPAT; USOCR; FPRS; EPO;	OR	ON	2014/07/31 00:31

			JPO; DERWENT; IBM_TDB			
S294	1	"20020188745".pn. and web	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S295	2	"20020188745".pn. and internet	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S296	8046629	((plurality or mutiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S297	8046958	((plurality or multiple or two or threee or many) near5 tcp mear5 connection)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S298	4601	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection)))	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S299	119	(((plurality or multiple or two or threee or many) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S300	64	(((plurality or multiple) near5 (tcp near5 connection))) and 709/231.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S301	0	"20020188745".pn. and cache	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S302	0	"20020188745".pn. and operator	US-PGPUB; USPAT;	OR	ON	2014/07/31 00:31

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S303	1	"20020188745".pn. and separate	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S304	1	"20050262257".pn. and (cache)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S305	1	"20050262257".pn. and (saf$3)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:31
S306	103	((R) near2 (Major)).INV.	US-PGPUB; USPAT; USOCR	OR	ON	2014/07/31 00:32
S307	19	((Mark) near2 (Hurst)).INV.	US-PGPUB	OR	ON	2014/07/31 00:32
S308	57	(709/246.ccls.) and S298	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 00:33
S309	67	((Mark) near2 (Hurst)).INV.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 01:14
S310	1	((Mark) near2 (Hurst)).INV. and tcp.clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2014/07/31 01:15
S311	103	((R) near2 (Major)).INV.	US-PGPUB; USPAT; USOCR	OR	ON	2014/07/31 01:15

EAST Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp

L310	0	(media player video playback multipl tcp connection subsequent).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/08/21 22:43
L311	1	(media player video playback multiple tcp connection subsequent).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/08/21 22:43
L312	1	(media player video playback multiple tcp connection subsequent).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/08/21 22:43
L313	0	(media player video playback multiple tcp connection subsequent generat$5).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/08/21 22:43
S312	0	(media player video playback multipl tcp connection subsequent).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/07/31 01:19
S313	1	(media player video playback multiple tcp connection subsequent).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/07/31 01:19
S314	1	(media player video playback multiple tcp connection subsequent).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/07/31 01:19
S315	0	(media player video playback multiple tcp connection subsequent generat$5).clm.	US-PGPUB; USPAT; UPAD	AND	ON	2014/07/31 01:20

8/21/2014 11:19:46 PM
C:\Users\ndonabed\Documents\EAST\Workspaces\11116783_amendment.wsp

Search Notes	Application/Control No.	Applicant(s)/Patent Under Reexamination
	11116783	MAJOR ET AL.
	Examiner	Art Unit
	NINOS DONABED	2444

CPC- SEARCHED		
Symbol	Date	Examiner

CPC COMBINATION SETS - SEARCHED		
Symbol	Date	Examiner

US CLASSIFICATION SEARCHED			
Class	Subclass	Date	Examiner
709	246	05/07/2008	ND

SEARCH NOTES		
Search Notes	Date	Examiner
See EAST Search History	05/07/2008	ND
Conducted double patenting search	05/07/2008	ND
Consulted with SPE William Vaughn	11/13/2008	ND
See updated EAST search	12/13/2009	ND
Consulted with SPE William Vaughn regarding Final	02/12/2009	ND
Consulted with SPE William Vaughn regarding Advisory	03/29/2009	ND
Consulted with SPE William Vaughn regarding Advisory	5/7/2009	ND
Consulted with Primary Paul Kang	02/10/2009	ND
See updated east search	7/30/2009	ND
Consulted with SPe William Vaughn regarding search	7/30/2009	ND
Consulted SPE William Vaughn regarding Final	2/4/2010	nd
Consulted SPE William Vaughn regarding Appeal	1/27/2011	nd
Consulted with Qas Mark Radtke regarding IDS	7/30/2014	nd
Conducted 101 claim analysis	7/31/2014	nd
Conducted 112 2nd paragraph analysis	7/31/2014	nd
Conducted 112 6th paragraph claim analysis	7/31/2014	nd
Conducted double patenting search (EAST, eDAN, PALM) *Inventor **Assignee	7/31/2014	nd
East Search	7/31/2014	nd

SEARCH NOTES		
Search Notes	**Date**	**Examiner**
Plus Serch	7/31/2014	nd
NPL Seach (Google, Google Scholar)	7/31/2014	nd
709/246,231 + texted searched1	7/31/2014	nd
Conducted double patenting search (EAST, eDAN, PALM) *Inventor **Assignee	8/21/2014	nd
East Search	8/21/2014	nd
Plus Search	8/21/2014	nd
NPL Seach (Google, Google Scholar)	8/21/2014	nd
709/246,231 + texted searched1	8/21/2014	nd
(H04N21/84 OR H04N21/6125 OR H04N21/47202 OR H04N21/482 OR H04W84/045 OR H04W12/06 OR H04W76/023 OR H04L65/80 OR H04L65/1016 OR H04L65/607).CPC. + texted searched	8/21/2014	nd

INTERFERENCE SEARCH			
US Class/ CPC Symbol	**US Subclass / CPC Group**	**Date**	**Examiner**
	Conducted Interference Search - See EAST Search History	7/28/2014	nd
	Conducted Interference Search - See EAST Search History	8/21/2014	nd

INFORMATION DISCLOSURE STATEMENT BY APPLICANT

(Not for submission under 37 CFR 1.99)

Application Number	11116783
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

U.S.PATENTS Remove

Examiner Initial*	Cite No	Patent Number	Kind Code[1]	Issue Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	7523181	B2	2009-04-21	Swildens et al.	
	2	6976090	B2	2005-12-13	Ben-Shaul et al.	
	3	7240100	B1	2007-07-03	Wein et al.	
	4	6850965	B2	2005-02-01	Allen	
	5	7334044	B1	2008-02-19	Allen	
	6	7760801	B2	2010-07-20	Ghanbari et al.	
	7	7099954	B2	2006-08-29	Li et al.	
	8	7054911	B1	2006-05-30	Lango et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014		
INFORMATION DISCLOSURE STATEMENT BY APPLICANT **(Not for submission under 37 CFR 1.99)**	Application Number	11116783 11116783 - GAU: 2444
	Filing Date	2005-04-28
	First Named Inventor	R. Drew Major
	Art Unit	2444
	Examiner Name	Donabed, Ninos J.
	Attorney Docket Number	066.0141 (P2004-04-01.1)

	9	7349358	B2	2008-03-25	Hennessey et al.	
	10	7797439	B2	2010-09-14	Cherkasova et al.	
	11	7477688	B1	2009-01-13	Zhang et al.	
	12	7054774	B2	2006-05-30	Batterberry et al.	
	13	6760772	B2	2004-07-06	Zou et al.	
	14	5168356		1992-12-01	Acampora et al.	
	15	7546355	B2	2009-06-09	Kalnitsky	
	16	7174385	B2	2007-02-06	Li	
	17	7376747	B2	2008-05-20	Hartop	
	18	7719985	B2	2010-05-18	Lee et al.	
	19	8683066	B2	2014-03-25	Hurst et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	20	5768527		1998-06-16	Zhu et al.	
	21	7274740	B2	2007-09-25	van Beek et al.	
	22	6185736	B1	2001-02-06	Ueno	
	23	6845107	B1	2005-01-18	Kitazawa et al.	
	24	6874015	B2	2005-03-29	Kaminsky et al.	
	25	7093001	B2	2006-08-15	Yang et al.	
	26	7599307	B2	2009-10-06	Seckni et al.	
	27	7788395	B2	2010-08-31	Bowra et al.	
	28	7536469	B2	2009-05-19	Chou et al.	
	29	7412531	B2	2008-08-12	Lango et al.	
	30	7295520	B2	2007-11-13	Lee et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	31	6795863	B1	2004-09-21	Doty, Jr.	
	32	7609652	B2	2009-10-27	Kellerer et al.	
	33	7325073	B2	2008-01-29	Shao et al.	
	34	6374289	B2	2002-04-16	Delaney et al.	
	35	7194549	B1	2007-03-20	Lee et al.	
	36	7054365	B2	2006-05-30	Kim et al.	
	37	6122660		2000-09-19	Baransky et al.	
	38	7391717	B2	2008-06-24	Klemets et al.	
	39	7260640	B1	2007-08-21	Kramer et al.	
	40	7310678	B2	2007-12-18	Gunaseelan et al.	
	41	7593333	B2	2009-09-22	Li et al.	

EFS Web 2.1.17 ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	42	6618752	B1	2003-09-09	Moore et al.	
	43	6721723	B1	2004-04-13	Gibson et al.	
	44	6859839	B1	2005-02-22	Zahorjan et al.	
	45	7779135	B2	2010-08-17	Hudson et al.	
	46	7369610		2008-05-06	Xu et al.	
	47	7330908		2008-02-12	Jungck	
	48	7577750		2009-08-18	Shen et al.	
	49	7328243		2008-02-05	Yeager et al.	
	50	7116894		2006-10-03	Chatterton	
	51	7653735		2010-01-26	Mandato et al.	
	52	8135852	B2	2012-03-13	Nilsson et al.	

EFS Web 2.1.17 ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	53	5841432		1998-11-24	Carmel et al.	
	54	5404446		1995-04-04	Bowater et al.	
	55	6449719	B1	2002-09-10	Baker	
	56	7817985	B2	2010-10-19	Moon	
	57	8209429	B2	2012-06-26	Jacobs et al.	
	58	7733830	B2	2010-06-08	Curcio et al.	
	59	7660906	B1	2010-02-09	Armour	
	60	8036265	B1	2011-10-11	Reynolds et al.	
	61	5267334		1993-11-30	Normille et al.	
	62	8370514	B2	2013-02-05	Hurst et al.	
	63	8612624	B2	2013-12-17	Frueck et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	64	6654790	B2	2003-11-25	Ogle et al.	
	65	6675199	B1	2004-01-06	Mohammed et al.	
	66	6697072	B2	2004-02-24	Russell et al.	
	67	6792449	B2	2004-09-14	Colville et al.	
	68	6801947	B1	2004-10-05	Li	
	69	6885471	B1	2005-04-26	Minowa et al.	
	70	7031700	B1	2006-04-18	Weaver et al.	
	71	7046805	B2	2006-05-16	Fitzhardinge et al.	
	72	7111044	B2	2006-09-19	Lee	
	73	7124164	B1	2006-10-17	Chemtob	
	74	7176957	B2	2007-02-13	Ivashin et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	75	7177642	B2	2007-02-13	Sanchez Herrero et al.	
	76	7190670	B2	2007-03-13	Varsa et al.	
	77	7313236	B2	2007-12-25	Amini et al.	
	78	7529541	B2	2009-05-05	Cho et al.	
	79	6552227	B2	2003-04-22	Mendelovici et al.	
	80	7555464	B2	2009-06-30	Candelore	
	81	7558472	B2	2009-07-07	Locket et al.	
	82	7631039	B2	2009-12-08	Eisenberg	
	83	7761609	B1	2010-07-20	Srinivasan et al.	
	84	7873040	B2	2011-01-18	Karlsgodt	
	85	7818444	B2	2010-10-19	Brueck et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	86	8402156	B2	2013-03-19	Brueck et al	

If you wish to add additional U.S. Patent citation information please click the Add button. Add

U.S.PATENT APPLICATION PUBLICATIONS Remove

Examiner Initial*	Cite No	Publication Number	Kind Code[1]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	20040083283	A1	2004-04-29	Sundaram et al.	
	2	20080219151	A1	2008-09-11	Ma et al.	
	3	20020152318	A1	2002-10-17	Menon et al.	
	4	20060080718	A1	2006-04-13	Gray et al.	
	5	20050120107	A1	2005-06-02	Kagan et al.	
	6	20040103444	A1	2004-05-27	Weinberg et al.	
	7	20050188051	A1	2005-08-25	Sneh	
	8	20030154239	A1	2003-08-14	Davis et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	9	20080133766	A1	2008-06-05	Luo	
	10	20070079325	A1	2007-04-05	de Heer	
	11	20030014684	A1	2003-01-16	Kashyap	
	12	20060206246	A1	2006-09-14	Walker	
	13	20050076136	A1	2005-04-07	Cho et al.	
	14	20030018966	A1	2003-01-23	Cook et al.	
	15	20040030599	A1	2004-02-12	Sie et al.	
	16	20050262257	A1	2005-11-24	Major et al.	
	17	20030140159	A1	2003-07-24	Campbell et al.	
	18	20010047423	A1	2001-11-29	Shao et al.	
	19	20030021166	A1	2003-01-30	Soloff	

EFS Web 2.1.17 ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	20	20020176418	A1	2002-11-28	Hunt et al.	
	21	20020169926	A1	2002-11-14	Pinckney, III et al.	
	22	20020178330	A1	2002-11-28	Schlowsky-Fischer et al.	
	23	20050084166	A1	2005-04-21	Bonch et al.	
	24	20020091840	A1	2002-07-11	Pulier et al.	
	25	20040117427	A1	2004-06-17	Allen et al.	
	26	20040030547	A1	2004-02-12	Leaning et al.	
	27	20060165166	A1	2006-07-27	Chou et al.	
	28	20020097750	A1	2002-07-25	Gunaseelan et al.	
	29	20020152317	A1	2002-10-17	Wang et al.	
	30	20080037527	A1	2008-02-14	Chan et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	31	20040168052	A1	2004-08-26	Clisham et al.	
	32	20050066063	A1	2005-03-24	Grigorovitch et al.	
	33	20050204046	A1	2005-09-15	Watanabe	
	34	20060059223	A1	2006-03-16	Klemets et al.	
	35	20060168295	A1	2006-07-27	Batterberry et al.	
	36	20080281803	A1	2008-11-13	Gentric	
	37	20050185578	A1	2005-08-25	Padmanabhan et al.	
	38	20070280255	A1	2007-12-06	Tsang et al.	
	39	20100098103	A1	2010-04-22	Xiong et al.	
	40	20090210549	A1	2009-08-20	Hudson et al.	
	41	20090055547	A1	2009-02-26	Hudson et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	42	20080205291	A1	2008-08-28	Li et al.	
	43	20070094405	A1	2007-04-26	Zhang	
	44	20060184688	A1	2006-08-17	Ganguly et al.	
	45	20080263180	A1	2008-10-23	Hurst et al.	
	46	20090055471	A1	2009-02-26	Kozat et al.	
	47	20040260701	A1	2004-12-23	Lehikoinen et al.	
	48	20060168290	A1	2006-07-27	Doron	
	49	20070030833	A1	2007-02-08	Pirzada et al.	
	50	20070067480	A1	2007-03-22	Beek et al.	
	51	20060133809	A1	2006-06-22	Chow et al.	
	52	20040049780	A1	2004-03-11	Gee	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	53	20030065803	A1	2003-04-03	Heuvelman	
	54	20020161911	A1	2002-10-31	Pinckney, III et al.	
	55	20060236219	A1	2006-10-19	Grigorovitch et al.	
	56	20080046939	A1	2008-02-21	Lu et al.	
	57	20060130118	A1	2006-06-15	Damm	
	58	20070204310	A1	2007-08-30	Hua et al.	
	59	20020176418	A1	2002-11-28	Hunt et al.	
	60	20050223087	A1	2005-10-06	Van Der Stok	
	61	20040010613	A1	2004-01-15	Apostolopoulos et al.	
	62	20030204602	A1	2003-10-30	Hudson et al.	
	63	20010013128	A1	2001-08-09	Hagai et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	64	20050055425		2005-03-10	Lango et al.	
	65	20050015509		2005-01-20	Sitaraman, Ramesh K.	
	66	20020131496		2002-09-19	Vasudevan et al.	
	67	20020161898		2002-10-31	Hartop et al.	
	68	20040220926		2004-11-04	Lamkin et al.	
	69	20100158101	A1	2010-06-24	Wu et al.	
	70	20090132721	A1	2009-05-21	Soroushian et al.	
	71	20090132599	A1	2009-05-21	Soroushian et al.	
	72	20090055417	A1	2009-02-26	Hannuksela	
	73	20090049186	A1	2009-02-19	Agnihotri et al.	
	74	20090006538	A1	2009-01-01	Risney, JR. et al.	

EFS Web 2.1.17 ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	75	20060277564	A1	2006-12-07	Jarman	
	76	20040153458	A1	2004-08-05	Noble et al.	
	77	20020087634	A1	2002-07-04	Ogle et al.	
	78	20020118809	A1	2002-08-29	Eisenberg	
	79	20020122491	A1	2002-09-05	Karczewicz et al.	
	80	20020133547	A1	2002-09-19	Lin	
	81	20020136406	A1	2002-09-26	Fitzhardinge et al.	
	82	20020138619	A1	2002-09-26	Ramaley et al.	
	83	20020146102	A1	2002-10-10	Lang	
	84	20020178138	A1	2002-11-28	Ender et al.	
	85	20020184391	A1	2002-12-05	Phillips	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	86	20020194608	A1	2002-12-19	Goldhor	
	87	20030007464	A1	2003-01-09	Balani	
	88	20030037103	A1	2003-02-20	Salmi et al.	
	89	20030078972	A1	2003-04-24	Tapissier et al.	
	90	20030220972	A1	2003-11-27	Montet et al.	
	91	20040098748	A1	2004-05-20	Bo et al.	
	92	20050009520	A1	2005-01-13	Herrero et al.	
	93	20050024487	A1	2005-02-03	Chen	
	94	20050050152	A1	2005-03-03	Penner et al.	
	95	20050066063	A1	2005-03-24	Grigorovitch et al.	
	96	20050204385	A1	2005-09-15	Sull et al.	

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014

INFORMATION DISCLOSURE STATEMENT BY APPLICANT
(Not for submission under 37 CFR 1.99)

Application Number	11116783 11116783 - GAU: 2444
Filing Date	2005-04-28
First Named Inventor	R. Drew Major
Art Unit	2444
Examiner Name	Donabed, Ninos J.
Attorney Docket Number	066.0141 (P2004-04-01.1)

	97	20050254508	A1	2005-11-17	Aksu et al.	
	98	20060047779	A1	2006-03-02	Deshpande	
	99	20060218264	A1	2006-09-28	Ogawa et al.	
	100	20060242315	A1	2006-10-26	Nichols	
	101	20060270404	A1	2006-11-30	Tuohino et al.	
	102	20060282540	A1	2006-12-14	Tanimoto	
	103	20060288099	A1	2006-12-21	Jefferson et al.	
	104	20070037599	A1	2007-02-15	Tillet et al.	
	105	20070078768	A1	2007-04-05	Dawson	
	106	20080060029	A1	2008-03-06	Park et al.	
	107	20080091838	A1	2008-04-17	Miceli	

EFS Web 2.1.17 ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	108	20140207966	A1	2014-07-24	Hurst et al.		

If you wish to add additional U.S. Published Application citation information please click the Add button. Add

FOREIGN PATENT DOCUMENTS Remove

Examiner Initial*	Cite No	Foreign Document Number[3]	Country Code[2] i	Kind Code[4]	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear	T[5]
	1	2006010113	WO	A2	2006-01-26	Network Foundation Technologies, LLC		☐
	2	200192752	JP		2001-04-06	Hitachi Information Systems Ltd.		☒
	3	2003009581	WO	A1	2003-01-30	British Telecommunications Public Limited Company		☐
	4	2004036824	WO	A1	2004-04-29	Nokia corporation		☐
	5	2004054930	JP		2004-02-19	Microsoft Corporation		☒
	6	2001067264	WO	A1	2001-09-13	Streamcenter, Inc.		☐
	7	2003003760	WO	A2	2003-01-09	Burst.com		☐
	8	2003027876	WO	A1	2003-04-03	Reynolds et al.		☐

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	9	2004025405	WO	A2	2004-03-25	Thomson Licensing S.A.		☐
	10	1298931	EP	A2	2003-02-04	Oplayo		☐
	11	1202487	EP	A2	2001-10-31	Kabushiki Kaisha Toshiba		☐
	12	1395014	EP	A1	2002-08-27	Matsushita Electric Industrial Co.		☐
	13	2367219	GB	A	2000-09-20	Vintage Global		☐
	14	2011004225	JP	A	2011-01-06	NEC Infronta Corp.		☒
	15	2000201343	JP	A	2000-07-18	Toshiba Corp.		☒

If you wish to add additional Foreign Patent Document citation information please click the Add button Add

NON-PATENT LITERATURE DOCUMENTS Remove

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T[5]
	1	USPTO "International Search Report" mailed December 12, 2008; International Appln. No. PCT/US2008/061035, filed April 21, 2008.	☐
	2	AUSTRALIAN GOVERNMENT "Examiner's First Report" dated October 17, 2011; Australian Patent Appln. No. 2011213730.	☐

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (**Not for submission under 37 CFR 1.99**)	Filing Date	2005-04-28	
	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	3	KOREAN INTELLECTUAL PROPERTY OFFICE "Official Notice of Preliminary Rejection" issued July 28, 2011; Korean Patent Appln. No. 10-2006-7025274.	☒
	4	JAPAN PATENT OFFICE "Notice of Rejection Ground" mailed April 26, 2011; Japanese Patent Appln. No. 2007-511070.	☒
	5	FUJISAWA, HIROSHI ET AL. "Implementation of Efficient Access Mechanism for Multiple Mirror-Servers" IPSJ SIG Technical Report, vol. 2004, no. 9 (2004-DPS-116), January 30, 2004, Information Processing Society of Japan, pp. 37-42	☒
	6	LIU, JIANGCHUAN ET AL. "Opportunities and Challenged of Peer-to-Peer Internet Video Broadcast," School of Computing Science, Simon Fraser University, British Columbia, Canada	☐
	7	USPTO INTERNATIONAL SEARCHING AUTHORITY "International Search Report and Written Opinion," mailed November 5, 2008; International Appln. No. PCT/US2008/009281, filed August 1, 2008.	☐
	8	ZHANG, XINYAN ET AL. "CoolStreaming/DONet: A Data-Driven Overlay Network for Peer-to-Peer Live Media Streaming" IEEE 2005.	☐
	9	GUO, YANG "DirectStream: A Directory-Based Peer-To-Peer Video Streaming Service" LexisNexis, Elsevier B.V. 2007.	☐
	10	LIU, JIANGCHUAN ET AL. "Adaptive Video Multicast Over the Internet" IEEE Computer Society, 2003.	☐
	11	REJAIE, REZA ET AL. "Architectural Considerations for Playback of Quality Adaptive Video Over the Internet" University of Southern California, Information Sciences Institute, 1998.)	☐
	12	ROY, SUMIT ET AL. "A System Architecture for Managing Mobile Streaming Media Services" Streaming Media Systems Group, Hewlett-Packard Laboratories, 2003.	☐
	13	XU, DONGYAN ET AL. "On Peer-to-Peer Media Streaming" Department of Computer Sciences, Purdue University, 2002.	☐

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT	Filing Date	2005-04-28	
(Not for submission under 37 CFR 1.99)	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	14	KOZAMERNIK, FRANC "Media Streaming Over the Internet - An Over of Delivery Technologies" EBU Technical Review, October 2002.	☐
	15	LIENHART, RAINER ET AL. "Challenges in Distributed Video Management and Delivery" Intel Corporation, EECS Dept., UC Berkeley, 2000-2002.	☐
	16	JAPAN PATENT OFFICE "Final Office Action" mailed February 28, 2012 in Patent Application No. 2007-511070 filed on October 26, 2006.	☒
	17	JAPAN PATENT OFFICE "Interrogation" mailed November 06, 2012 in Patent Application No. 2007-511070 filed on October 26, 2006.	☒
	18	CANADIAN INTELLECTUAL PROPERTY OFFICE "Office Action" mailed September 09, 2013 in Patent Application No. 2,564,861 filed on October 30, 2006.	☐
	19	USPTO "Office Action" mailed September 13, 2013 in Patent Application No. 13/757,571 filed on February 01, 2013.	☐
	20	USPTO "Notice of Allowance" mailed June 24, 2014 in Patent Application No. 13/757.571, filed on February 01, 2013.	☐
	21	EUROPEAN PATENT OFFICE "Extended Search Report" dated July 10, 2014 in Patent Application No. 12154559.4 filed on September 20, 2002.	☐
	22	NGUYEN, Thinh, "Multiple Sender Distributed Video Streaming" in IEEE Transactions on Multimedia, Volume 6, No. 2, Published April 2, 2004.	☐
	23	WEBLIO, The Meaning of Performance Factor --- English-Japanese Weblio Dictionary, [online], February 24, 2012; retrieved from the internet - URL:http://ejje, weblio.jp/content/performance+factor	☐
	24	MASATO TSURU ET AL., Recent Evolution of the Internet Measurement and Inference Techniques, IEICE Technical Report, vol. 103, no. 123 (IN2003-16 to 23), IEICE, June 12, 2003, pp. 37 to 42, ISSN: 0913-05685.	☐

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (**Not for submission under 37 CFR 1.99**)	Filing Date	2005-04-28	
	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

	25	TAKESHI YOSHIMURA ET AL., Mobile Streaming Media CDN Enabled by Dynamic SMIL, WWW2002, May 7-11, 2002; retrieved from the Internet at http://www2002.org/CDROM/refereed/515/	☐
	26	CANADIAN INTELLECTUAL PROPERTY OFFICE, Office Action, mailed October 15, 2012 for Patent Application No. 2,564,861.	☐
	27	CLEMENT, B., Move Networks Closes $11.3 Million on First Round VC Funding, Page One PR, Move Networks, Inc. Press Releases, February 7, 2007, http://www.move.tv/press/press20070201.html.	☐
	28	MOVE NETWORKS, INC., The Next Generation Video Publishing System, April 11, 2007; http://www.movenetworks.com/wp-content/uploads/move-networks-publishing-system.pdf.	☐
	29	U.S. Patent and Trademark Office, Non-Final Office Action, dated August 7, 2014 for U.S. Patent Application No. 14/106,051.	☐

If you wish to add additional non-patent literature document citation information please click the Add button Add

EXAMINER SIGNATURE

Examiner Signature	/Ninos Donabed/	Date Considered	08/21/2014

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

[1] See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. [2] Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). [3] For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. [4] Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. [5] Applicant is to place a check mark here if English language translation is attached.

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Receipt date: 08/20/2014	Application Number	11116783	11116783 - GAU: 2444
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (**Not for submission under 37 CFR 1.99**)	Filing Date	2005-04-28	
	First Named Inventor	R. Drew Major	
	Art Unit	2444	
	Examiner Name	Donabed, Ninos J.	
	Attorney Docket Number	066.0141 (P2004-04-01.1)	

CERTIFICATION STATEMENT

Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):

☐ That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).

OR

☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).

☒ See attached certification statement.

☐ Fee set forth in 37 CFR 1.17 (p) has been submitted herewith.

☐ None

SIGNATURE

A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.

Signature	/BRETT A. CARLSON/	Date (YYYY-MM-DD)	2014-08-20
Name/Print	Brett A. Carlson	Registration Number	39928

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these record s.

2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.

3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.

4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).

5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.

6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).

7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.

8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.

9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

ALL REFERENCES CONSIDERED EXCEPT WHERE LINED THROUGH. /N.D

Adaptive streaming and rendering of large terrains using strip masks

J Pouderoux, JE Marvie - ... of the 3rd international conference on ..., 2005 - dl.acm.org
Abstract Terrain rendering is an important factor in the rendering of virtual scenes. If they are large and detailed, digital terrains can represent a huge amount of data and therefore of graphical primitives to render in real-time. In this paper we present an efficient technique **...**
Cited by 41 Related articles All 7 versions Cite Save

A VLC media player plugin enabling dynamic **adaptive streaming** over HTTP

C Müller, C Timmerer - Proceedings of the 19th ACM international ..., 2011 - dl.acm.org
Abstract This paper describes the implementation of a VLC media player plugin enabling Dynamic **Adaptive Streaming** over HTTP (DASH). DASH is an emerging ISO/IEC MPEG and 3GPP standard for HTTP **streaming**. It aims to standardize formats enabling segmented **...**
Cited by 37 Related articles All 4 versions Cite Save

Layer-encoded video in scalable **adaptive streaming**

M Zink, J Schmitt, R Steinmetz - Multimedia, IEEE Transactions ..., 2005 - ieeexplore.ieee.org
Abstract—Combining the concepts of caching and transmis-sion control protocol (TCP)-friendly **streaming** of layer-encoded video bears the problem that those videos might not be cached in full quality. Therefore, we focus in this work on the scheduling of **...**
Cited by 40 Related articles All 7 versions Cite Save

Global messaging with distributed **adaptive streaming** control

Y Lee, C Chao, R Ngai, M Chiang... - US Patent ..., 2002 - freepatentsonline.com
Abstract: A software implementable approach capable of creating, delivering, reassembling, rendering, and storing asynchronous and synchronous multimedia message. This approach integrates video/audio **streaming** with existing Internet/Intranet e-mail messaging and **...**
Cited by 47 Related articles Cite Save More

System and method for **adaptive streaming** of predictive coded video data

C Anantharamu, D Manoranjan - 2001 - Google Patents
This invention provides an **adaptive** transcoder which streams predictive coded video data over variable bandwidth networks and to devices having varying processing capabilities. The invention dynamically and continuously determines an available network bandwidth **...**
Cited by 35 Related articles All 2 versions Cite Save

Adaptive systems for improved media **streaming** experience

J Chakareski, P Frossard - Communications Magazine, IEEE, 2007 - ieeexplore.ieee.org
ABSTRACT Supporting **streaming** media applications over current packet network infrastructures represents a challenging task in many regards. For one, the lack of quality of service (QoS) guarantees in existing networks such as the Internet means that time- **...**
Cited by 33 Related articles All 6 versions Cite Save

of Sports Videos

SF Chang, D Zhong, R Kumar, RTCBA **Streaming** - ... of the IEEE Workshop on Content ..., 2001
Cited by 15 Related articles Cite Save

What happens when HTTP **adaptive streaming** players compete for bandwidth?

S Akhshabi, L Anantakrishnan, AC Begen... - Proceedings of the 22nd ..., 2012 - dl.acm.org
Abstract With an increasing demand for high-quality video content over the Internet, it is becoming more likely that two or more **adaptive streaming** players share the same network bottleneck and compete for available bandwidth. This competition can lead to three **...**
Cited by 40 Related articles All 9 versions Cite Save

IIS smooth **streaming** technical overview

A Zambelli - Microsoft Corporation, 2009 - bogotobogo.com
... 6 HTTP-Based **Adaptive Streaming**..... 7 **...** Introduction In October 2008, Microsoft announced that Internet Information Services (IIS) 7.0 would feature a new HTTP-based **adaptive streaming** extension: Smooth **Streaming**. **...**
Cited by 158 Related articles All 6 versions Cite Save More

Adaptive streaming of high-quality video over wireless LANs

P Van Beek, S Deshpande... - Electronic ..., 2004 - proceedings.spiedigitallibrary.org
abstract We address the problem of robust **streaming** of high-quality video over wireless local area networks in a home environment. By robust **streaming**, we mean maintaining the highest possible video quality and preventing interruptions to the video under varying **...**

Cited by 30 Related articles All 8 versions Cite Save

Multimedia over IP and wireless networks: compression, networking, and systems

M Van der Schaar, PA Chou - 2011 - books.google.com

... Coding and Error Concealment Strategies for Audio Communication 59 Dinei Florêncio Mechanisms for Adapting Compressed Multimedia to Varying Bandwidth Conditions 81 Antonio Ortega and Huisheng Wang Scalable Video Coding for **Adaptive Streaming** Applications 117 ...

Cited by 138 Related articles All 4 versions Cite Save More

Low-latency **adaptive streaming** over TCP

A Goel, C Krasic, J Walpole - ACM Transactions on Multimedia ..., 2008 - dl.acm.org

Abstract Media **streaming** over TCP has become increasingly popular because TCP's congestion control provides remarkable stability to the Internet. **Streaming** over TCP requires adapting to bandwidth availability, but unforunately, TCP can introduce significant latency ...

Cited by 29 Related articles All 7 versions Cite Save

Adaptation algorithm for **adaptive streaming** over HTTP

K Miller, E Quacchio, G Gennari... - Packet Video Workshop ..., 2012 - ieeexplore.ieee.org

Abstract—Internet video makes up a significant part of the Internet traffic and its fraction is constantly growing. In order to guarantee best user experience throughout different network access technologies with dynamically varying network conditions, it is fundamental to ...

Cited by 30 Related articles All 2 versions Cite Save

Adaptive scalable video **streaming** in wireless networks

S Xiang, L Cai, J Pan - Proceedings of the 3rd multimedia systems ..., 2012 - dl.acm.org

Abstract In this paper, we investigate the optimal **streaming** strategy for dynamic **adaptive streaming** over HTTP (DASH). Specifically, we focus on the rate adaptation algorithm for **streaming** scalable video (H. 264/SVC) in wireless networks. We model the rate ...

Cited by 24 Related articles Cite Save

A comparison of quality scheduling in commercial **adaptive** http **streaming** solutions on a 3g network

H Riiser, HS Bergsaker, P Vigmostad... - Proceedings of the 4th ..., 2012 - dl.acm.org

Abstract There are many available commercial **streaming** solutions that perform quality adaption. An important issue with respect to users' perceived quality is how the system schedules the quality levels to match the available network resources. In this study, we ...

Cited by 25 Related articles All 12 versions Cite Save

Channel sharing by rate-**adaptive streaming** applications

N Argiriou, L Georgiadis - Performance Evaluation, 2004 - Elsevier

There are various techniques for adapting the transmission rate of an application while maintaining the perceived quality at the receiver at acceptable levels. Shared-channel systems can use this rate adaptation capability to increase the number of concurrent ...

Cited by 25 Related articles All 10 versions Cite Save

Quality of experience estimation for **adaptive** HTTP/TCP video **streaming** using H. 264/AVC

KD Singh, Y Hadjadj-Aoul... - ... Conference (CCNC), 2012 ..., 2012 - ieeexplore.ieee.org

ABSTRACT Video services are being adopted widely in both mobile and fixed networks. For their successful deployment, the content providers are increasingly becoming interested in evaluating the performance of such traffic from the final users' perspective, that is, their ...

Cited by 23 Related articles All 10 versions Cite Save

Adaptive low-bitrate **streaming** over IEEE 802.15. 4 low rate wireless personal area networks (LR-WPAN based on link quality indication

S Deshpande - Proceedings of the 2006 international conference on ..., 2006 - dl.acm.org

Abstract The IEEE 802.15. 4 Low-Rate Wireless Personal Area Network (LR-WPAN)[1] working group defines physical layer (PHY) and medium access control layer (MAC) standards specifications for low data rate wireless connections operating in the personal ...

Cited by 20 Related articles All 2 versions Cite Save

Securing media for **adaptive streaming**

C Venkatramani, P Westerink, O Verscheure... - Proceedings of the ..., 2003 - dl.acm.org

Abstract This paper describes the ARMS system which enables secure and **adaptive** rich media **streaming** to a large-scale, heterogeneous client population. The secure **streaming** algorithms ensure end-to-end security while the content is adapted and streamed via ...

Cited by 20 Related articles All 9 versions Cite Save

Streaming multimedia data with **adaptive** QoS characteristics

C Bouras, A Gkamas - Protocols for Multimedia Systems, 2000 - ru6.cti.gr

ABSTRACT In this paper, we describe the design and the implementation of an **adaptive streaming** architecture, which is based on real time protocols. The **adaptive streaming** application, which we have developed, can be used for **streaming** multimedia data over ...

Cited by 20 Related articles All 4 versions Cite Save More

Multimedia proxy caching mechanism for quality **adaptive streaming** applications in the internet

R Rejaie, H Yu, M Handley... - ... 2000. Nineteenth Annual ..., 2000 - ieeexplore.ieee.org

Absrrmr-The Internet has witnessed a rapid growth in deployment of Web-based **streaming** applications during recent years. In these applications, server should be able to perform end-to-end congestion control and quality adaptation to match the delivered stream quality to **...**

Cited by 289 Related articles All 33 versions Cite Save

Dynamic **adaptive streaming** over HTTP--: standards and design principles

T Stockhammer - Proceedings of the second annual ACM conference on ..., 2011 - dl.acm.org

Abstract In this paper, we provide some insight and background into the Dynamic **Adaptive Streaming** over HTTP (DASH) specifications as available from 3GPP and in draft version also from MPEG. Specifically, the 3GPP version provides a normative description of a **...**

Cited by 245 Related articles All 8 versions Cite Save

An experimental evaluation of rate-adaptation algorithms in **adaptive streaming** over HTTP

S Akhshabi, AC Begen, C Dovrolis - Proceedings of the second annual ..., 2011 - dl.acm.org

Abstract **Adaptive** (video) **streaming** over HTTP is gradually being adopted, as it offers significant advantages in terms of both user-perceived quality and resource utilization for content and network service providers. In this paper, we focus on the rate-adaptation **...**

Cited by 214 Related articles All 16 versions Cite Save

Quality-**adaptive** media **streaming** by priority drop

C Krasic, J Walpole, W Feng - ... of the 13th international workshop on ..., 2003 - dl.acm.org

Abstract This paper presents a general design strategy for **streaming** media applications in best effort computing and networking environments. Our target application is video on demand using personal computers and the Internet. In this scenario, where resource **...**

Cited by 122 Related articles All 18 versions Cite Save

A survey of application layer techniques for **adaptive streaming** of multimedia

B Vandalore, W Feng, R Jain, S Fahmy - Real-Time Imaging, 2001 - Elsevier

Though the integrated services model and resource reservation protocol (RSVP) provide support for quality of service, in the current Internet only best-effort traffic is widely supported. New high-speed technologies such as ATM (asynchronous transfer mode), gigabit **...**

Cited by 89 Related articles All 11 versions Cite Save

Adaptive streaming of MPEG video over IP networks

RS Ramanujan, JA Newhouse... - Local Computer ..., 1997 - ieeexplore.ieee.org

Abstract We present the design of an **adaptive** service for **streaming** MPEG video over a best-effort IP network environment. The **adaptive** video **streaming** service exploits the inherent adaptiveness of video applications to pelform controlled and graceful adjustments to the **...**

Cited by 87 Related articles All 8 versions Cite Save

Real-time content-based **adaptive streaming** of sports videos

SF Chang, D Zhong, R Kumar - Content-Based Access of ..., 2001 - ieeexplore.ieee.org

Abstract In this paper, we present a real-time software system for filtering live video content and then adaptively **streaming** the video over resource limited networks or devices. The rate adaptation is content-based and dynamically varied according to the event structure and **...**

Cited by 77 Related articles All 5 versions Cite Save

Method and system for indexing and content-based **adaptive streaming** of digital video content

SF Chang, A Jaimes, R Kumar, D Zhong - 2001 - Google Patents

The present invention discloses systems and methods for automatically parsing digital video content into segments corresponding to fundamental semantic units, events, and camera views, and **streaming** parsed digital video content to users for display and browsing. The **...**

Cited by 91 Related articles All 4 versions Cite Save

Dynamic **adaptive streaming** over HTTP dataset

S Lederer, C Müller, C Timmerer - Proceedings of the 3rd Multimedia ..., 2012 - dl.acm.org

Abstract The delivery of audio-visual content over the Hypertext Transfer Protocol (HTTP) got lot of attention in recent years and with dynamic **adaptive streaming** over HTTP (DASH) a standard is now available. Many papers cover this topic and present their research results, **...**

Cited by 64 Related articles All 5 versions Cite Save

Adaptive streaming within the 3GPP packet-switched **streaming** service

P Frojdh, U Horn, M Kampmann, A Nohlgren... - Network, ..., 2006 - ieeexplore.ieee.org

Abstract The 3GPP Packet-Switched **Streaming** Service (PSS) is a standard for audio and video **streaming** to handheld 2.5 G and 3G terminals and provides a complete **streaming** and download framework for commercial content. This article gives an overview of the **...**
Cited by 59 Related articles All 6 versions Cite Save

Quality of experience for HTTP **adaptive streaming** services

O Oyman, S Singh - Communications Magazine, IEEE, 2012 - ieeexplore.ieee.org
ABSTRACT The growing consumer demand for mobile video services is one of the key drivers of the evolution of new wireless multimedia solutions requiring exploration of new ways to optimize future wireless networks for video services towards delivering enhanced **...**
Cited by 61 Related articles All 5 versions Cite Save

Adaptive streaming of stored video in a TCP-friendly context: Multiple versions or multiple layers?

P de Cuetos, D Saparilla, KW Ross - in Proc. Packet Video Workshop, 2001 - Citeseer
Abstract Video transmission over the current best-effort Internet should be made fair to competing TCP traffic. Because the available bandwidth to a TCP-friendly stream changes significantly over medium and long time scales, it is desirable to adapt the **streaming** rate **...**
Cited by 35 Related articles Cite Save More

On performance bounds for the integration of elastic and **adaptive streaming** flows

T Bonald, A Proutière - ACM SIGMETRICS Performance Evaluation ..., 2004 - dl.acm.org
Abstract We consider a network model where bandwidth is fairly shared by a dynamic number of elastic and **adaptive streaming** flows. Elastic flows correspond to data transfers while **adaptive streaming** flows correspond to audio/video applications with variable rate **...**
Cited by 51 Related articles All 8 versions Cite Save

3GPP compliant **adaptive** wireless video **streaming** using H. 264/AVC

T Schierl, T Wiegand... - Image Processing, 2005. ..., 2005 - ieeexplore.ieee.org
Abstract—In 3GPP a standard for multimedia **streaming** over mobile networks called PSS (Packet-switched **Streaming** Service) has been specified. In order to deal with changing transmission characteristics like varying link bit-rate or handover, **adaptive streaming ...**
Cited by 43 Related articles All 10 versions Cite Save

An evaluation of dynamic **adaptive streaming** over http in vehicular environments

C Müller, S Lederer, C Timmerer - Proceedings of the 4th Workshop on ..., 2012 - dl.acm.org
Abstract MPEGs' Dynamic **Adaptive Streaming** over HTTP (MPEG-DASH) is an emerging standard designed for media delivery over the top of existing infrastructures and able to handle varying bandwidth conditions during a **streaming** session. This requirement is very **...**
Cited by 49 Related articles All 5 versions Cite Save

An experimental investigation of the Akamai **adaptive** video **streaming**

L De Cicco, S Mascolo - 2010 - Springer
Abstract Akamai offers the largest Content Delivery Network (CDN) service in the world. Building upon its CDN, it recently started to offer High Definition (HD) video distribution using HTTP-based **adaptive** video **streaming**. In this paper we experimentally investigate **...**
Cited by 49 Related articles All 8 versions Cite Save

Adaptive live video **streaming** by priority drop

J Huang, C Krasic, J Walpole - 2003 - pdxscholar.library.pdx.edu
Abstract In this paper we explore the use of Priority-progress **streaming** (PPS) for video surveillance applications. PPS is an **adaptive streaming** technique for the delivery of continuous media over variable bit-rate channels. It is based on the simple idea of **...**
Cited by 42 Related articles All 14 versions Cite Save

Implementation of **adaptive streaming** of stored MPEG-4 FGS video over TCP

P de Cuetos, P Guillotel, KW Ross... - Multimedia and Expo, ..., 2002 - ieeexplore.ieee.org
ABSTRACT This paper presents an implementation of an end-to-end application for **streaming** stored MPEG-4 Fine-Grained Scalable (FGS) videos over the best-effort Internet. Our current implementation ms over TCP but can also be run over TCP-friendly RTPNDP **...**
Cited by 36 Related articles All 2 versions Cite Save

An evaluation of TCP-based rate-control algorithms for **adaptive** Internet **streaming** of H. 264/SVC

R Kuschnig, I Kofler, H Hellwagner - Proceedings of the first annual ACM ..., 2010 - dl.acm.org
Abstract Recent work in TCP video **streaming** indicates that multimedia **streaming** via TCP provides satisfactory performance when the achievable TCP throughput is approximately twice the media bit rate. However, these conditions may not be achievable on the Internet, **...**

Cited by 45 Related articles All 6 versions Cite Save

iDASH: improved dynamic **adaptive streaming** over HTTP using scalable video coding

Y Sánchez de la Fuente, T Schierl, C Hellge... - Proceedings of the ..., 2011 - dl.acm.org

Abstract HTTP-based delivery for Video on Demand (VoD) has been gaining popularity within recent years. Progressive Download over HTTP, typically used in VoD, takes advantage of the widely deployed network caches to relieve video servers from sending ...

Cited by 44 Related articles All 5 versions Cite Save

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), to: Mail **Mail Stop ISSUE FEE**
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450
or Fax (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

70560 7590 09/12/2014
INGRASSIA FISHER & LORENZ, P.C. (EchoStar)
7010 E. COCHISE ROAD
SCOTTSDALE, AZ 85253

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission
I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being facsimile transmitted to the USPTO (571) 273-2885, on the date indicated below.

(Depositor's name)
(Signature)
(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
11/116,783	04/28/2005	R. Drew Major	066.0141 (P2004-04-01.1)	5535

TITLE OF INVENTION: APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	$480	$0	$0	$480	12/12/2014

EXAMINER	ART UNIT	CLASS-SUBCLASS
DONABED, NINOS	2444	709-231000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).
☒ Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached.
☒ "Fee Address" indication (or "Fee Address" Indication form PTO/SB/47; Rev 03-02 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list
(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,
(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.
1 Ingrassia Fisher & Lorenz, P.C.
2
3

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document has been filed for recordation as set forth in 37 CFR 3.11. Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE: EchoStar Technologies L.L.C.
(B) RESIDENCE: (CITY and STATE OR COUNTRY): Englewood, CO

Please check the appropriate assignee category or categories (will not be printed on the patent) : ☐ Individual ☒ Corporation or other private group entity ☐ Government

4a. The following fee(s) are submitted:
☒ Issue Fee
☐ Publication Fee (No small entity discount permitted)
☐ Advance Order - # of Copies

4b. Payment of Fee(s): **(Please first reapply any previously paid issue fee shown above)**
☐ A check is enclosed.
☐ Payment by credit card. Form PTO-2038 is attached.
☒ The Director is hereby authorized to charge the required fee(s), any deficiency, or credits any overpayment, to Deposit Account Number 50-2091 (enclose an extra copy of this form).

5. **Change in Entity Status** (from status indicated above)
☐ Applicant certifying micro entity status. See 37 CFR 1.29 — NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.
☐ Applicant asserting small entity status. See 37 CFR 1.27 — NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.
☐ Applicant changing to regular undiscounted fee status. — NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature /BRETT A. CARLSON/ Date September 18, 2014
Typed or printed name Brett A. Carlson Registration No. 39928

PTOL-85 Part B (10-13) Approved for use through 10/31/2013. OMB 0651-0033 U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

PTO/SB/47 (03-09)
Approved for use through 03/31/2012. OMB 0651-0016
U.S. Patent and Trademark Office; U. S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

"FEE ADDRESS" INDICATION FORM

Address to:
Mail Stop M Correspondence
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

- OR -

Fax to:
571-273-6500

INSTRUCTIONS: The issue fee must have been paid for application(s) listed on this form. In addition, only an address represented by a Customer Number can be established as the fee address for maintenance fee purposes (hereafter, fee address). A fee address should be established when correspondence related to maintenance fees should be mailed to a different address than the correspondence address for the application. **When to check the first box below**: If you have a Customer Number to represent the fee address. **When to check the second box below**: If you have no Customer Number representing the desired fee address, in which case a completed Request for Customer Number (PTO/SB/125) must be attached to this form. For more information on Customer Numbers, see the Manual of Patent Examining Procedure (MPEP) § 403.

For the following listed application(s), please recognize as the "Fee Address" under the provisions of 37 CFR 1.363 the address associated with:

☑ Customer Number: 000197

OR

☐ The attached Request for Customer Number (PTO/SB/125) form.

PATENT NUMBER (if known)	APPLICATION NUMBER
	11/116,783

Completed by (check one):

☐ Applicant/Inventor

☑ Attorney or Agent of record 39928 (Reg. No.)

☐ Assignee of record of the entire interest. See 37 CFR 3.71. Statement under 37 CFR 3.73(b) is enclosed. (Form PTO/SB/96)

☐ Assignee recorded at Reel _____ Frame_____

/BRETT A. CARLSON/
Signature

Brett A. Carlson
Typed or printed name

480.385.5060
Requester's telephone number

September 18, 2014
Date

NOTE: Signatures of all the inventors or assignees of record of the entire interest or their representative(s) are required. Submit multiple forms if more that one signature is required, see below*.

☑ * Total of 1 forms are submitted.

This collection of information is required by 37 CFR 1.363. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1. 11 and 1.14. This collection is estimated to take 5 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313- 1450. DO NOT SEND COMPLETED FORMS TO THIS ADDRESS.
SEND TO: Mail Stop M Correspondence, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Acknowledgement Receipt

EFS ID:	20181010
Application Number:	11116783
International Application Number:	
Confirmation Number:	5535
Title of Invention:	APPARATUS, SYSTEM, AND METHOD FOR ADAPTIVE-RATE SHIFTING OF STREAMING CONTENT
First Named Inventor/Applicant Name:	R. Drew Major
Customer Number:	70560
Filer:	Brett Carlson/Sharron Castillo
Filer Authorized By:	Brett Carlson
Attorney Docket Number:	066.0141 (P2004-04-01.1)
Receipt Date:	18-SEP-2014
Filing Date:	28-APR-2005
Time Stamp:	17:28:15
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	Credit Card
Payment was successfully received in RAM	$960
RAM confirmation Number	4144
Deposit Account	502091
Authorized User	CARLSON, BRETT A.

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Charge any Additional Fees required under 37 C.F.R. Section 1.17 (Patent application and reexamination processing fees)