

Proceedings



2003 International Conference on *Computer Networks and Mobile Computing*

ICCNMC 2003

20-23 October 2003 • Shanghai, China

Sponsored by

China Computer Federation

In cooperation with

IEEE Computer Society Beijing Center
IEEE Computer Society Technical Committee on Distributed Processing
Shanghai Computer Society



Los Alamitos, California

Washington • Brussels • Tokyo

fuboTV Media Inc.
Exhibit 1058
fuboTV v. Dish
IPR2024-00917, -00918, -00919
Ex. 1058-001

Copyright © 2003 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved

Copyright and Reprint Permissions: Abstracting is permitted with credit to the source. Libraries may photocopy beyond the limits of US copyright law, for private use of patrons, those articles in this volume that carry a code at the bottom of the first page, provided that the per-copy fee indicated in the code is paid through the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923.

Other copying, reprint, or republication requests should be addressed to: IEEE Copyrights Manager, IEEE Service Center, 445 Hoes Lane, P.O. Box 133, Piscataway, NJ 08855-1331.

The papers in this book comprise the proceedings of the meeting mentioned on the cover and title page. They reflect the authors' opinions and, in the interests of timely dissemination, are published as presented and without change. Their inclusion in this publication does not necessarily constitute endorsement by the editors, the IEEE Computer Society, or the Institute of Electrical and Electronics Engineers, Inc.

IEEE Computer Society Order Number PR02033
ISBN 0-7695-2033-2
Library of Congress Number 2003110764

Additional copies may be ordered from:

IEEE Computer Society
Customer Service Center
10662 Los Vaqueros Circle
P.O. Box 3014
Los Alamitos, CA 90720-1314
Tel: + 1 800 272 6657
Fax: + 1 714 821 4641
<http://computer.org/cspress>
csbooks@computer.org

IEEE Service Center
445 Hoes Lane
P.O. Box 1331
Piscataway, NJ 08855-1331
Tel: + 1 732 981 0060
Fax: + 1 732 981 9667
[http://shop.ieee.org/store/](http://shop.ieee.org/store/customer-service@ieee.org)
customer-service@ieee.org


IEEE Computer Society
Asia/Pacific Office
Watanabe Bldg., 1-4-2
Minami-Aoyama
Minato-ku, Tokyo 107-0062
JAPAN
Tel: + 81 3 3408 3118
Fax: + 81 3 3408 3553
tokyo.ofc@computer.org

Individual paper REPRINTS may be ordered at: reprints@computer.org

Editorial production by Stephanie Kawada
Cover art production by Joe Daigle/Studio Productions
Printed in the United States of America by The Printing House



2003 International Conference on
**Computer Networks and
Mobile Computing**



Shanghai, China
20-23 October 2003

2003 International Conference on
Computer Networks and Mobile Computing



Published by the IEEE Computer Society
10662 Los Vaqueros Circle
P.O. Box 3014
Los Alamitos, CA 90720-1314

IEEE Computer Society Order Number PR02033
Library of Congress Number 2003110764
ISBN 0-7695-2033-2



Sponsored by
China Computer Federation

In cooperation with
IEEE Computer Society Beijing Center
IEEE Computer Society Technical Committee on Distributed Processing
Shanghai Computer Society

Ex. 1058-003

Proceedings



ICCNMC 2003

Table of Contents

Welcome Address from the General Chairs	xii
Message from the Program Chairs	xiii
Organizing and Program Committees	xiv
Referees	xv
Keynote and Invited Speakers:	
Abstract and Résumé	xvi

Paper Sessions: Regular Paper

MAC and Wireless Network

On the Use of Genetic Algorithms in the Medium Access Control of Broadcast Communication Networks	3
<i>G. I. Papadimitriou, M. S. Obaidat, and A. S. Pomportsis</i>	
SROAM: An End-to-End Service Model for Improved Performance in Roaming over Wireless LAN Networks.....	10
<i>J. Yuan, C. Liu, and X. Li</i>	
An Effective Collision Resolution Mechanism for Wireless LAN	18
<i>C. Wang, B. Li, B. Li, and K. Sohraby</i>	

Network Security

A Hypersphere Oriented Key Exchange Scheme for Multiparty	27
<i>C.-C. Chang and C.-W. Chan</i>	
Active Traffic Analysis Attacks and Countermeasures.....	31
<i>X. Fu, B. Graham, R. Bettati, and W. Zhao</i>	

Active Vulnerability Assessment of Computer Networks by Simulation of Complex Remote Attacks	40
<i>I. Kotenko</i>	

QoS and Multicast Routing

A Multiobjective Model for QoS Multicast Routing Based on Genetic Algorithm	49
<i>X. Cui, C. Lin, and Y. Wei</i>	
Available Bandwidth-Based Real-Time Multicast Routing Distributed Algorithm	54
<i>J. Huang, X. Du, Z. Yang, and W. Cheng</i>	
A Mechanism for Restorable QoS Routing	61
<i>H. Long and S. Shen</i>	

QoS Control I

Survey on QoS Management of VoIP	69
<i>X. Chen, C. Wang, D. Xuan, Z. Li, Y. Min, and W. Zhao</i>	
Efficient Distributed Admission Control for Anycast Flows	78
<i>W. Jia, W. Tu, and L. Lin</i>	
Double-Layer Stream Scheduling Scheme with QoS Control for Cluster Video Servers	86
<i>X. Liao, H. Jin, and H. Chen</i>	
Frequency-Based Reconstruction of Multi-Description Coded JPEG2000 Images	92
<i>H. Yu and B. W. Wah</i>	

QoS Control II

A Scheduling Mechanism on OGSA	101
<i>L. Jin, W. Tong, B. Wang, and Y. Zong</i>	
Adaptive IP QoS Architecture and Algorithms	107
<i>X. Fan, C. Lin, X. Fan, and Y. Wei</i>	
Session Based Differentiated Quality of Service Admission Control for Web Servers	112
<i>Y. Wei, C. Lin, F. Ren, E. Dutkiewicz, and R. Raad</i>	
Regulating Best Effort Flows on Per Domain Basis	117
<i>Y. Xiang, Q. Gu, and Z. Li</i>	

Router and Switch

A TCAM-Based IP Lookup Scheme for Multi-Nexthop Routing	128
<i>Z. Liang, J. Wu, and K. Xu</i>	
A Fast Two-Way IP Lookup Algorithm Based Multibit-Trie	136
<i>J. Jia, C. Lin, and W. Liu</i>	

Design and Implementation of a 320 Gb/s Switch Fabric	143
<i>W. Li, Y. Gong, Y. Xu, K. Zheng, and B. Liu</i>	

High-Speed Discrete Content Sensitive Pattern Match Algorithm for Deep Packet Filtering	149
<i>B. Jiang and B. Liu</i>	

Network Applications

Web Intelligence for Business Coalition Operations	158
<i>A. Smirnov, M. Pashkin, N. Chilov, and T. Levashova</i>	

Arbitrator-Based Algorithm for Measurement Collaboration Problem	166
<i>Q. Wu, J. Huang, and J. Bi</i>	

Agent-Based Transactions on Distributed Object Servers	174
<i>M. Shiraishi, T. Enokido, and M. Takizawa</i>	

MAGE: Multi-Agent Environment	181
<i>Z. Shi, H. Zhang, M. Dong, Z. Zhao, Q. Sheng, Y. Jiang, and Y. Cheng</i>	

Wireless Network and Mobile Computing I

Information Service on Scalable Ad-Hoc Mobile Wireless Networks	190
<i>Y.-M. Huang and H.-Y. Lin</i>	

A Probability-Based Adaptive Algorithm for Call Admission Control in Wireless Network	197
<i>X.-P. Wang, J.-L. Zheng, W. Zeng, and G.-D. Zhang</i>	

Concurrency Control of Real-Time Transactions with Disconnections in Mobile Computing Environment	205
<i>G. Liao, Y. Liu, L. Wang, and C. Peng</i>	

Wireless Network and Mobile Computing II

Camel: A Mobile Applications Framework	214
<i>A. M. Al-Bar and I. Wakeman</i>	

Adaptive Real-Time Publish-Subscribe Service Model for Mobile Communication Environments	224
<i>Q. Wang, H. Wang, H. Tang, and G. Dai</i>	

The Location Management Scheme Using Mobility Information of Mobile Users in Wireless Mobile Networks	230
<i>S.-J. Oh</i>	

A Power-Saving Scheduling for IEEE 802.11 Mobile Ad Hoc Network	238
<i>M. Liu and M. T. Liu</i>	

P2P System and Overlay Network

An Efficient Interest-Group Based Search Mechanism in Unstructured Peer-to-Peer Networks.....	247
<i>J. Yang, Y. Zhong, and S. Zhang</i>	
RChord: An Enhanced Chord System Resilient to Routing Attacks.....	253
<i>D. Xuan, S. Chellappan, and M. Krishnamoorthy</i>	
A Genetic Algorithm for the Overlay Multicast Routing Problem	261
<i>Y. Pan, Z. Yu, and L. Wang</i>	
A Study on the Content Distribution of Cooperative Proxy Caching Using Total Cost-Aware Scheme	266
<i>T.-C. Hu, Y. Ikeda, M. Nakazawa, and S. Hattori</i>	

Performance Model and Evaluation

Performance Models in GSM and GPRS Networks	275
<i>L. Yue, I. Awan, and K. Al-Begain</i>	
Research on Dynamic Feedback and Elastic Scheduling Model and Algorithm for Flexible Workload.....	283
<i>Y. Chen and Q. Dai</i>	
Extending Life Cycle of Legacy Systems.....	291
<i>D. Cohen, G. Larson, D. McDougal, and B. Ware</i>	
Research on Model and Scheduling Algorithm for Double-Mode VoD Servers	297
<i>Y. Chen and Q. Dai</i>	

TCP and Traffic Control

End-to-End Stored FGS Video Transmission Based on Adaptive Smoothing and TCP-Friendly Rate Control.....	304
<i>H. Yin, C. Lin, and Q. Zhang</i>	
Integrated TCP/IP Protocol Software Testing for Vulnerability Detection	311
<i>S. Xiao, L. Deng, S. Li, and X. Wang</i>	
A New Method of Fault Tolerance TCP	320
<i>Z. Li, K. Xu, M. Xu, L. Fu, and J. Wu</i>	

Paper Sessions: Short Paper

Network Security I

Traceability of Double Spending in Secure Electronic Cash System	330
<i>H. J. Lee, M. S. Choi, and C. S. Rhee</i>	

Verifiable Threshold Cryptosystems Based on Elliptic Curve.....	334
<i>Y. Han, X. Yang, J. Sun, and D. Li</i>	
An Efficient and Robust Conference Key Distribution Protocol.....	338
<i>Y. Guo and J. Ma</i>	
Agent-Based Distributed Intrusion Source Identification.....	341
<i>H. Wang, R. Wang, C. Wang, and Y. Gao</i>	
A Database Record Encryption Scheme Using the RSA Public Key Cryptosystem and Its Master Keys	345
<i>C.-C. Chang and C.-W. Chan</i>	
A Network Early-Warning Architecture Using Mobile Agent.....	349
<i>J. Zhang and C. Xiao</i>	
Authentication and Key Distribution Methods in Mobile Computing Environments	353
<i>B. Zhang and J. Wu</i>	

Network Security II

A Security Improved OpenSST Prototype Combining with Smart Card.....	358
<i>X. Zhang, C. Meinel, and A. Dulaunoy</i>	
Scalable PKI Model Based on Location Information	362
<i>Y. Wang and D. Gu</i>	
Analysis for Active Network Security Abased on Pi-Calculus Model.....	366
<i>Z. Xia, Y. Zhong, and S. Zhang</i>	
Comparison of Several Wavelet Coefficient Confusion Methods Applied in Multimedia Encryption.....	372
<i>S. Lian and Z. Wang</i>	
A Study of Secure Multi-Party Statistical Analysis	377
<i>W. Luo and X. Li</i>	
The Construction of BCA in China.....	383
<i>Y. Liu, X. Liu, and J. Ju</i>	

Routing and Multicast

Dynamic Multicast Routing for Mobile Networks	390
<i>Y. Liu, J. Wu, and A. Chen</i>	
An Approach for Checking Persistent Route Oscillation of BGP.....	395
<i>H. Wang, R. Wang, C. Zhang, and Y. Gao</i>	
Heuristic QoS Routing Based on Possibility Distribution and Soft Computing.....	399
<i>J. Hu, H. Zhang, and S. Zhang</i>	
NRLM: A Novel Router-Assisted Layered Multicast Scheme	404
<i>F. Shi, K. Xu, J. Wu, and M. Xu</i>	

A Dynamic Broadcast Ring Based Multicast Routing Protocol for Ad Hoc Networks	409
<i>Y. Zhou, G. Li, Q. Mao, Y. Zhan, and Y. Hou</i>	
A Packet-Order-Keeping-Demultiplexer in Parallel-Structure Router Based on Flow Classification	415
<i>Y. Chen, Y. Dong, Y. Lin, and J. Lan</i>	
On the Model of OoS Multicast Routing Problems in Active Networks	419
<i>Z. Yu, Y. Pan, and L. Wang</i>	

Multimedia and Network Applications

MOM-G: Message-Oriented Middleware on Grid Environment Based on OGSA	424
<i>J. Tang, W. Tong, J. Ding, and L. Cai</i>	
A Novel Method of Keyframe Setting in Video Coding: Fast Adaptive Dynamic Keyframe Selecting	428
<i>Y. Yuan, D. Feng, and Y. Zhong</i>	
Architecture of Hydrological Telemetry Software Based on Web Services.....	432
<i>P. Ai, Z. Wang, X. Zhou, and Y. Lou</i>	
A New Proxy Caching Scheme for Parallel Video Servers.....	438
<i>H. Chen, H. Jin, J. Sun, X. Liao, and D. Deng</i>	
Multi-Thread IO in High Quality Digital Broadcasting System.....	442
<i>S. Wang, J. Zhang, and D. Feng</i>	
A BSU-Based Sports Video Content Analysis Framework for Content-Based Streams Filtering.....	446
<i>J. Chen, Y. Li, S. Lao, and L. Wu</i>	
An Effective Image Steganographic Scheme Based on Wavelet Transformation and Pattern-Based Modification	450
<i>C.-C. Chang, T.-S. Chen, and H.-C. Hsia</i>	
XML-Based Communication Protocols for WebGIS	454
<i>Y. Luo, X. Liu, X. Wang, and Z. Xu</i>	

Wireless Network and Mobile Computing

A Multi-Standard SDR Base Band Platform	461
<i>Z. Luo, W. Li, Y. Zhang, and W. Guan</i>	
A Cooperative Two-Tier Framework for Efficient Routing in MANET.....	465
<i>X. Jin, H. Wang, and Y. Zhang</i>	
TPBDSR: A New DSR-Based Energy Saving Routing in MANET	470
<i>L. Xu, Z. Wu, and B. Zheng</i>	
A Distributed Tokens-Based Distance-Vector Routing Algorithm for Mobile Ad-Hoc Networks.....	474
<i>L. Wang, Y. Lin, and Z. Chen</i>	

MPSSF: A Buffering and Forwarding Handover Scheme Reducing Out-of-Sequence Packets	478
<i>J.-L. Zheng, X.-P. Wang, and G.-D. Zhang</i>	

Hybrid Error Control Mechanism for Wireless ATM Based on Traffic Type	483
<i>Y. Ren, W. Zhang, and B. Wang</i>	

Performance Model and Testing

Study of Main Technology in Rich Media Grid Delivery.....	488
<i>Z. Lv, Y. Zhong, S. Zhang, and J. Wu</i>	

Laxity Threshold Polling for Scalable Real-Time/Non-Real-Time Scheduling	493
<i>R. A. Lackman and J. Xu</i>	

Performance Analysis for Multimedia CDMA Networks under the Received Power Minimization Control	497
<i>X. Bo and Z. Chen</i>	

Improve Performance of Disconnected Operation Through Submitting by Probability and Transferring Transactions in Groups.....	502
<i>Y. Lu and X. Shao</i>	

Analysis of Multi-Access Performance Based on Non-Period Chaotic Frequency Hopping Sequences	506
<i>Z. Li, Y. Tie, L. Jin, Y. Chang, and J. Cai</i>	

Providing Efficient Video-on-Demand Service	509
<i>Y. Hu, H. Zang, R. Yan, and Y. Gao</i>	

An Enhanced Passive Testing Tool for Network Protocols	513
<i>D. Chen, J. Wu, and T. I. Chu</i>	

Refusal Testing for MIOTS with Nonlockable Output Channels	517
<i>Z. Li, J. Wu, and X. Yin</i>	

Author Index	523
---------------------------	-----

A Novel Method of Keyframe Setting in Video Coding: Fast Adaptive Dynamic Keyframe Selecting

Yu Yuan David Feng Yuzhuo Zhong
Computer Science Department Information Technologies School Computer Science Department
Tsinghua University The University of Sydney Tsinghua University
Beijing, P.R.China Sydney, Australia Beijing, P.R.China
yyu@media.cs.tsinghua.edu.cn feng@staff.cs.usyd.edu.au zyz-dcs@mail.tsinghua.edu.cn

Abstract

In this paper, we describe a novel method of keyframe setting in video coding: Fast Adaptive Dynamic Keyframe Selecting. The method analyzes video contents and decides keyframe setting dynamically and adaptively. Utilizing information generated by motion-estimation, our method involves only a little additional computing cost. Our method can improve both objective and subjective quality compared with traditional keyframe setting. It can be applied to any motion-estimation based video compression. We tested the method on not only standard test sequences but also real movie sequences proving that it gives valuable results.

1. Introduction

As a mature video technology, motion-estimation has existed for many years. Keyframes, also known as reference frames, are bases of prediction in motion-estimation. However, if one frame contains a lot of things or a large part of the picture that cannot be found in the keyframes, the prediction efficiency will turn very low. In traditional video coding, the intervals between keyframes are static and fixed, so that the problem above is inevitable. JVT (MPEG-4 AVC) involves multi-reference-frame prediction, but this technique can only slightly reduce the problem.




Figure 1



If we do content-based keyframe setting, as shown in Figure 1, we can find out those shot-edge or big-change frames and set them as keyframes, so the prediction will be more efficient. A.Y. Lan [3] proposed a Scene Context Dependent Reference Frame Placement method. But his motion-analysis preprocessing involved lots of additional computing costs. His results were also not very good. Actually, there are many existing video-analysis techniques. They can extract as many features as you want. But they are too sophisticated to be integrated into video coding. Till now, we are still using fixed keyframe intervals.

In adjacent research area, D.T. Hoang [4] proposed a real-time VBR rate-control algorithm. He utilized VBV-buffer information generated by existing encoder as rate-control guide. So his algorithm didn't require heavy preprocessing and became single-pass actually. This inspired us to design such a single-pass dynamic keyframe selecting method.

In this paper, we describe a novel method of keyframe setting: Fast Adaptive Dynamic Keyframe Selecting, as follows: in section 2, we present a detailed analysis of the relationship between keyframe intervals and compression efficiency. In section 3, we present our method. In section 4, we describe our experiments and results. Finally, in section 5, we describe the usability of our method, and forecast its application foreground.

2. The relationship between keyframe intervals and compression efficiency

Let us discuss how keyframe intervals influence compression efficiency. To make our discussion easier, we take a simplification that there are only I-frames and B-frames in our sequence. Since P-frame's behavior, such as its compression ratio and prediction mode, is between I-frame and B-frame, this simplification will not make any significant differences. Now, keyframe means I-frame only, so keyframe interval is the interval between two adjacent I-frames – that is, the number of B-frames between them.



3.2. The algorithm description

The kernel algorithm of our method is as follows:

Let $\text{diff}(f_1, f_2)$ represent the difference between frame f_1 and frame f_2 (The definition of the function diff will be described later). Let R_k represent the no. k reference frame in the whole video sequence (I-frames and P-frames are all considered as reference frames).

Step 1: The first frame of the whole sequence is always an I-frame. Mark it as the first reference frame, represented by R_1 (that is, R_k when $k=1$);

Step 2: Calculate $\text{Avg}(\text{diff}(R_1, R_2), \text{diff}(R_2, R_3), \dots, \text{diff}(R_{k-1}, R_k))$ – the average of differences (The definition of the function Avg will be described later);

Step 3: Suppose that the original codec's keyframe interval is m . Find next "reference frame candidate" with m . Mark it as R_{k+1} ;

Step 4: Calculate $\text{diff}(R_k, R_{k+1})$. Let λ represent $\text{diff}(R_k, R_{k+1}) / \text{Avg}(\text{diff}(R_1, R_2), \text{diff}(R_2, R_3), \dots, \text{diff}(R_{k-1}, R_k))$:

if $\lambda \leq \alpha$

Make the no. σ frame following the frame R_{k+1} be new "reference frame candidate" R_{k+1} , as shown in Figure 5. Repeat step 4;

else if $\lambda \geq \beta$

Make the frame R_{k+1} be I-frame, as shown in Figure 5. $k++$. Go to step 2;

else if $\lambda \in (\alpha, \beta)$

Make the frame R_{k+1} be P-frame, as shown in Figure 5. $k++$. Go to step 2.




Figure 5

The description of the function diff : Generally, there are many calculating methods that can be used to measure the difference between two frames. For example, the sum of absolute differences between corresponding pixels of two frames, the mean arithmetical value of the modules of every macroblock's motion vectors from last frame to next frame, the mean square of the modules of every macroblock's motion vectors from last frame to next frame, and so on. We use the mean square of the modules of every macroblock's motion vectors from last frame to next frame. The original encoder generates the motion vectors when it encodes our "candidates" as P-frames. A reason to choose the mean square is that spatial local motions are very important to human's subjective vision.

The description of the function Avg : There are also many average calculating methods, such as, mean arithmetical, mean square, median, and so on. In order to emphasize the importance of temporal local motion to human's subjective vision, we choose mean square again.

3.3. The parameters in the algorithm

There are three parameters in our algorithm: α , β , σ . What values should they take? It's a key problem. The parameters will affect the final results deeply.

In theory, we think that adjusting the parameters dynamically during encoding process will generate best results. But it seems a little too complex till now. There are two ways to choose three static and fixed values for them as follows:

First, create a mathematical model; get the optimal values from lots of formulas.

Second, do lots of experiments; get the average best values from various real video sequences.

My experiences make me choose the second way. As I believe, videos in the real world are as chaotic as the world. Their shot distributions are very random. I don't think it is feasible to design such a mathematical model.

On the other hand, almost all the existing video codecs and methods have Achilles' heel. It is not very difficult to "design" a tragic sequence against a given codec. So, if one codec does well in many familiar-type sequences, it is successful.

Finally, we use up to 100 sequences to train our method and get three usable values: 0.4, 0.7, and 4.

4. Experiments

We implemented our Fast Adaptive Dynamic Keyframe Selecting method on both MPEG-2 codec and JVT (MPEG-4 AVC) JM codec.

The common standard test sequences are too short to test our method. There are usually only 1 or 2 shot

conversions in each of them, such as Foreman, Coastguard, and so on. So we must prepare test sequences by ourselves.

Our test sequences consist of four kinds as follows:

1. Patchworks from standard test sequences, as shown in Figure 6.



Figure 6

2. Movie trailers. They have most frequent rapid shot conversions and will be difficult to any codec.
3. Segments from movies. Every genre, such as Drama, Action, Sci-Fi, Horror, Animation, has several spokesmen in our test sequences.
4. Segments from TV. News, sports, ads, cosmic, and so on.

4.1. Tests on MPEG-2 codec

The resolutions of all the sequences tested on MPEG-2 codec are all 720x480. Original codec and our modified codec were set to generate the same average bitrates. The frame type pattern of the original codec was set as "IBBBBPBBBBPBBBB".

Our modified codec's average PNSR is about 0.2~0.3dB higher than the original codec. In some scenarios our method tied with the original but most of these sequences are slow-motion clips. In some other scenarios, especially movie trailers, our method notched up to 0.6dB higher than the original.

The average coding speed of our method is about 10~15 percent slower than the original.

Not only objective quality but also subjective quality was improved by our method. Especially at those shot conversion and rapid motion scenes, we noticed that images turned more stable and had fewer noticeable compression artifacts than the original.

The results proved that our method is valuable on MPEG-2.

4.2. Tests on JVT codec

The resolutions of all the sequences tested on JVT codec are CIF and QCIF. Original codec and our modified codec were set to generate the same average bitrates. The frame type pattern of the original codec was set as "IBBBBPBBBBPBBBB". No "multi-reference-frames" was enabled.

Our modified codec's average PNSR is about 0.1dB higher than the original codec. In some scenarios our method tied with the original but most of these sequences are slow-motion clips. In some other scenarios, especially

movie trailers, our method notched up to 0.8dB higher than the original.

The average coding speed of our method is about 5~11 percent slower than the original.

There was also noticeable subjective quality improvement by our method.

The results also proved that our method is valuable on JVT.

5. Conclusions and outlook

Traditional static and fixed keyframe setting doesn't exert all the potentials of prediction coding. We present a method to do fast adaptive dynamic keyframe selecting to make the prediction more effective. This method adopts a quasi single-pass strategy to avoid unacceptable additional computing costs. Experiments proved that our method is valuable.

This method doesn't change any bitstream grammar and syntax of existing video coding standards. It outputs standard bitstreams, which can be decoded by any compatible decoders. Actually, it can easily be implemented in any prediction-coding based video codecs, such as MPEG-1, MPEG-2, MPEG-4, and JVT.

Since our method mainly utilizes information generated by existing encoders as its guide, it doesn't involve any very special processes. So, it can also benefit from available hardware accelerating.

Our future work is to research better functions *Avg* and *Diff*, as well as better parameters.

In some particular applications, such as video database and transcoding, there are already many extracted features and existing information. Utilizing these features and information to improve the efficiency of our method is also an interesting problem.

References

- [1] Y. Wang, J. Ostermann, and Y.Q. Zhang, *Video Processing and Communications*, Prentice Hall, 2002.
- [2] ISO/IEC, "Information technology - Generic coding of moving pictures and associated audio", International Standard ISO/IEC 13818, 1995.
- [3] A.Y. Lan, "Scene Context Dependent Reference Frame Placement for MPEG Video Coding", M.S. Thesis, University of Washington, Seattle, March 1996.
- [4] D.T. Hoang, "Real-time VBR rate control of MPEG video based upon lexicographic bit allocation", *Data Compression Conference 1999 Proceedings, DCC '99*, 1999, pp. 374-383.
- [5] M.T. Sun and A.R. Reibman, "Variable bit rate video coding", *Compressed Video over Networks*, Marcel Dekker, New York, 2001.
- [6] A. Vetro, H. Sun, and Y. Wang, "MPEG-4 rate control for multiple video objects", *IEEE Transactions on Circuit and System For Video Technology*, Feb 1999.