



US007738015B2

(12) **United States Patent**
Steinberg et al.

(10) **Patent No.:** **US 7,738,015 B2**
(45) **Date of Patent:** ***Jun. 15, 2010**

(54) **RED-EYE FILTER METHOD AND APPARATUS**

(75) Inventors: **Eran Steinberg**, San Francisco, CA (US); **Yury Prilutsky**, San Mateo, CA (US); **Peter Corcoran**, Claregalway (IE); **Petronel Bigioi**, Galway (IE); **Michael J. DeLuca**, Boca Raton, FL (US)

(73) Assignee: **FotoNation Vision Limited**, Galway (IE)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1230 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/919,226**

(22) Filed: **Aug. 16, 2004**

(65) **Prior Publication Data**

US 2005/0041121 A1 Feb. 24, 2005

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/772,767, filed on Feb. 4, 2004, now Pat. No. 7,352,394, which is a continuation-in-part of application No. 10/635,862, filed on Aug. 5, 2003, now Pat. No. 7,630,006, which is a continuation-in-part of application No. 10/170,511, filed on Jun. 12, 2002, now Pat. No. 7,042,505, which is a continuation of application No. 08/947,603, filed on Oct. 9, 1997, now Pat. No. 6,407,777.

(51) **Int. Cl.**

H04N 5/76 (2006.01)

H04N 9/73 (2006.01)

(52) **U.S. Cl.** **348/223.1; 348/224.1; 396/158; 382/117**

(58) **Field of Classification Search** 348/223, 348/224; 382/117, 260, 275
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,285,588 A 8/1981 Mir

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 884 694 A1 12/1998

(Continued)

OTHER PUBLICATIONS

Translation of JP404192681A, Tatsutoshi Kitajima, Electronic Camera, Jul. 10, 1992.*

(Continued)

Primary Examiner—Sinh Tran


Assistant Examiner—Hung H Lam

(74) *Attorney, Agent, or Firm*—Andrew V. Smith

(57) **ABSTRACT**

A digital image acquisition system having no photographic film, such as a digital camera, has a flash unit for providing illumination during image capture and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, the detection being based upon a comparison of the captured image and a reference image of nominally the same scene taken without flash. In the embodiment the reference image is a preview image of lower pixel resolution than the captured image, the filter matching the pixel resolutions of the captured and reference images by up-sampling the preview image and/or sub-sampling the captured image. The filter also aligns at least portions of the captured image and reference image prior to comparison to allow for, e.g. movement in the subject.

35 Claims, 10 Drawing Sheets



Sony Exhibit 1049
Sony v. Optimum

US 7,738,015 B2

Page 2

U.S. PATENT DOCUMENTS

4,577,219	A	3/1986	Klie et al.	6,249,315	B1	6/2001	Holm	
4,646,134	A	2/1987	Komatsu et al.	6,252,976	B1	6/2001	Schildkraut et al.	
4,777,620	A	10/1988	Shimoni et al.	6,266,054	B1	7/2001	Lawton et al.	
4,881,067	A	11/1989	Watanabe et al.	6,268,939	B1	7/2001	Klassen et al.	
4,978,989	A	12/1990	Nakano et al.	6,275,614	B1	8/2001	Krishnamurthy et al.	
5,016,107	A	5/1991	Sasson et al.	6,278,491	B1 *	8/2001	Wang et al.	348/370
5,070,355	A	12/1991	Inoue et al.	6,285,410	B1	9/2001	Marni	
5,130,789	A	7/1992	Dobbs et al.	6,292,574	B1	9/2001	Schildkraut et al.	
5,164,831	A	11/1992	Kuchta et al.	6,295,378	B1	9/2001	Kitakado et al.	
5,202,720	A	4/1993	Fujino et al.	6,298,166	B1	10/2001	Ratnakar et al.	
5,249,053	A	9/1993	Jain	6,300,935	B1	10/2001	Sobel et al.	
5,274,457	A	12/1993	Kobayashi et al.	6,381,345	B1	4/2002	Swain	
5,301,026	A	4/1994	Lee	6,393,148	B1	5/2002	Bhaskar	
5,303,049	A	4/1994	Ejima et al.	6,396,963	B2	5/2002	Shaffer et al.	
5,335,072	A	8/1994	Tanaka et al.	6,407,777	B1	6/2002	DeLuca	
5,384,601	A	1/1995	Yamashita et al.	6,421,468	B1	7/2002	Ratnakar et al.	
5,400,113	A	3/1995	Sosa et al.	6,426,775	B1	7/2002	Kurokawa	
5,432,863	A	7/1995	Benati et al.	6,429,924	B1	8/2002	Milch	
5,432,866	A	7/1995	Sakamoto	6,433,818	B1	8/2002	Steinberg et al.	
5,452,048	A	9/1995	Edgar	6,438,264	B1	8/2002	Gallagher et al.	
5,455,606	A	10/1995	Keeling et al.	6,441,854	B2	8/2002	Fellegara et al.	
5,537,516	A	7/1996	Sherman et al.	6,459,436	B1	10/2002	Kumada et al.	
5,568,187	A	10/1996	Okino	6,473,199	B1	10/2002	Gilman et al.	
5,568,194	A *	10/1996	Abe	6,496,655	B1	12/2002	Malloy Desormeaux	
5,671,013	A	9/1997	Nakao	6,501,911	B1	12/2002	Malloy Desormeaux	
5,694,926	A	12/1997	DeVries et al.	6,505,003	B1	1/2003	Malloy Desormeaux	
5,719,639	A	2/1998	Imamura	6,510,520	B1	1/2003	Steinberg	
5,719,951	A	2/1998	Shackleton et al.	6,516,154	B1	2/2003	Parulski et al.	
5,724,456	A	3/1998	Boyack et al.	6,614,471	B1	9/2003	Ott	
5,734,425	A	3/1998	Takizawa et al.	6,614,995	B2	9/2003	Tseng	
5,748,764	A *	5/1998	Benati et al.	6,621,867	B1	9/2003	Sazzad et al.	
5,748,784	A	5/1998	Sugiyama	6,628,833	B1	9/2003	Horie	
5,751,836	A	5/1998	Wildes et al.	6,700,614	B1	3/2004	Hala	
5,761,550	A	6/1998	Kancigor	6,707,950	B1	3/2004	Burns et al.	
5,781,650	A	7/1998	Lobo et al.	6,714,665	B1	3/2004	Hanna et al.	
5,805,720	A	9/1998	Suenaga et al.	6,718,051	B1 *	4/2004	Eschbach	382/117
5,805,727	A	9/1998	Nakano	6,724,941	B1	4/2004	Aoyama	
5,805,745	A	9/1998	Graf	6,728,401	B1 *	4/2004	Hardeberg	382/167
5,815,749	A	9/1998	Tsukahara et al.	6,765,686	B2	7/2004	Maruoka	
5,818,975	A	10/1998	Goodwin et al.	6,786,655	B2	9/2004	Cook et al.	
5,847,714	A	12/1998	Naqvi et al.	6,792,161	B1	9/2004	Imazumi et al.	
5,850,470	A	12/1998	Kung et al.	6,798,913	B2	9/2004	Toriyama	
5,862,217	A	1/1999	Steinberg et al.	6,859,565	B2	2/2005	Baron	
5,862,218	A	1/1999	Steinberg	6,873,743	B2	3/2005	Steinberg	
5,892,837	A	4/1999	Luo et al.	6,885,766	B2	4/2005	Held et al.	
5,949,904	A	9/1999	Delp	6,895,112	B2	5/2005	Chen et al.	
5,974,189	A	10/1999	Nicponski	6,900,882	B2	5/2005	Iida	
5,990,973	A	11/1999	Sakamoto	6,912,298	B1	6/2005	Wilensky	
5,991,456	A	11/1999	Rahman et al.	6,937,997	B1	8/2005	Parulski	
5,991,549	A	11/1999	Tsuchida	6,967,680	B1	11/2005	Kagle et al.	
5,991,594	A	11/1999	Froeber et al.	6,980,691	B2	12/2005	Nesterov et al.	
5,999,160	A	12/1999	Kitamura et al.	6,984,039	B2	1/2006	Agostinelli	
6,006,039	A	12/1999	Steinberg et al.	7,024,051	B2	4/2006	Miller et al.	
6,009,209	A	12/1999	Acker et al.	7,027,662	B2	4/2006	Baron	
6,011,547	A	1/2000	Shiota et al.	7,035,461	B2	4/2006	Luo et al.	
6,016,354	A	1/2000	Lin et al.	7,035,462	B2	4/2006	White et al.	
6,028,611	A	2/2000	Anderson et al.	7,042,501	B1	5/2006	Matama	
6,035,072	A	3/2000	Read	7,042,505	B1	5/2006	De Luca	
6,035,074	A	3/2000	Fujimoto et al.	7,062,086	B2	6/2006	Chen et al.	
6,036,072	A	3/2000	Lee	7,116,820	B2	10/2006	Luo et al.	
6,101,271	A	8/2000	Yamashita et al.	7,133,070	B2	11/2006	Wheeler et al.	
6,104,839	A	8/2000	Cok et al.	7,155,058	B2	12/2006	Gaubatz et al.	
6,118,485	A	9/2000	Hinoue et al.	7,216,289	B2	5/2007	Kagle et al.	
6,134,339	A	10/2000	Luo et al.	7,224,850	B2	5/2007	Zhang et al.	
6,151,403	A	11/2000	Luo	7,269,292	B2	9/2007	Steinberg	
6,172,706	B1	1/2001	Tatsumi	7,289,664	B2	10/2007	Enomoto	
6,192,149	B1	2/2001	Eschbach et al.	7,295,233	B2	11/2007	Steinberg et al.	
6,195,127	B1	2/2001	Sugimoto	7,310,443	B1	12/2007	Kris et al.	
6,201,571	B1	3/2001	Ota	7,315,631	B1	1/2008	Corcoran et al.	
6,204,858	B1	3/2001	Gupta	7,336,821	B2	2/2008	Ciuc et al.	
6,233,364	B1	5/2001	Krainioux et al.	7,352,394	B1 *	4/2008	DeLuca et al.	348/241
				7,362,368	B2	4/2008	Steinberg et al.	
				7,369,712	B2	5/2008	Steinberg et al.	

US 7,738,015 B2

Page 3

7,403,643	B2	7/2008	Ianculescu et al.	2004/0196503	A1	10/2004	Kurtenbach et al.
7,436,998	B2	10/2008	Steinberg et al.	2004/0213476	A1	10/2004	Luo et al.
7,454,040	B2	11/2008	Luo et al.	2004/0223063	A1	11/2004	DeLuca et al.
7,515,740	B2	4/2009	Corcoran et al.	2004/0227978	A1	11/2004	Enomoto
2001/0015760	A1	8/2001	Fellegara et al.	2004/0228542	A1	11/2004	Zhang et al.
2001/0031142	A1	10/2001	Whiteside	2004/0233299	A1	11/2004	Ioffe et al.
2001/0052937	A1	12/2001	Suzuki	2004/0233301	A1	11/2004	Nakata et al.
2002/0019859	A1	2/2002	Watanabe	2004/0234156	A1	11/2004	Watanabe et al.
2002/0041329	A1	4/2002	Steinberg	2004/0239779	A1	12/2004	Washisu
2002/0051571	A1	5/2002	Jackway et al.	2004/0240747	A1	12/2004	Jarman et al.
2002/0054224	A1	5/2002	Wasula et al.	2004/0258308	A1	12/2004	Sadovsky et al.
2002/0085088	A1	7/2002	Eubanks	2005/0001024	A1	1/2005	Kusaka et al.
2002/0090133	A1	7/2002	Kim et al.	2005/0013602	A1	1/2005	Ogawa
2002/0093577	A1	7/2002	Kitawaki et al.	2005/0013603	A1	1/2005	Ichimasa
2002/0093633	A1	7/2002	Milch	2005/0024498	A1	2/2005	Iida et al.
2002/0105662	A1	8/2002	Patton et al.	2005/0031224	A1	2/2005	Prilutsky et al.
2002/0114513	A1	8/2002	Hirao	2005/0041121	A1	2/2005	Steinberg et al.
2002/0126893	A1	9/2002	Held et al.	2005/0047655	A1	3/2005	Luo et al.
2002/0131770	A1	9/2002	Meier et al.	2005/0047656	A1	3/2005	Luo et al.
2002/0136450	A1	9/2002	Yan et al.	2005/0053279	A1	3/2005	Chen et al.
2002/0141661	A1	10/2002	Steinberg	2005/0058340	A1	3/2005	Chen et al.
2002/0150306	A1 *	10/2002	Baron 382/275	2005/0058342	A1	3/2005	Chen et al.
2002/0159630	A1	10/2002	Buzuloiu et al.	2005/0062856	A1	3/2005	Matsushita
2002/0172419	A1	11/2002	Lin et al.	2005/0063083	A1	3/2005	Dart et al.
2002/0176623	A1	11/2002	Steinberg	2005/0068452	A1	3/2005	Steinberg et al.
2003/0007687	A1	1/2003	Nesterov et al.	2005/0074164	A1	4/2005	Yonaha
2003/0021478	A1	1/2003	Yoshida	2005/0074179	A1	4/2005	Wilensky
2003/0025811	A1	2/2003	Keelan et al.	2005/0078191	A1	4/2005	Battles
2003/0044063	A1	3/2003	Meckes et al.	2005/0117132	A1	6/2005	Agostinelli
2003/0044070	A1	3/2003	Fuersich et al.	2005/0129331	A1	6/2005	Kakiuchi et al.
2003/0044176	A1	3/2003	Saitoh	2005/0140801	A1	6/2005	Prilutsky et al.
2003/0044177	A1	3/2003	Oberhardt et al.	2005/0147278	A1	7/2005	Rui et al.
2003/0044178	A1	3/2003	Oberhardt et al.	2005/0151943	A1	7/2005	Iida
2003/0052991	A1	3/2003	Stavely et al.	2005/0163498	A1	7/2005	Battles et al.
2003/0058343	A1	3/2003	Katayama	2005/0168965	A1	8/2005	Yoshida
2003/0058349	A1	3/2003	Takemoto	2005/0196067	A1	9/2005	Gallagher et al.
2003/0095197	A1	5/2003	Wheeler et al.	2005/0200736	A1	9/2005	Ito
2003/0107649	A1	6/2003	Flickner et al.	2005/0207649	A1	9/2005	Enomoto et al.
2003/0118216	A1	6/2003	Goldberg	2005/0212955	A1	9/2005	Craig et al.
2003/0137597	A1	7/2003	Sakamoto et al.	2005/0219385	A1	10/2005	Terakawa
2003/0142285	A1	7/2003	Enomoto	2005/0219608	A1	10/2005	Wada
2003/0161506	A1	8/2003	Velazquez et al.	2005/0220346	A1	10/2005	Akahori
2003/0190072	A1 *	10/2003	Adkins et al. 382/154	2005/0220347	A1	10/2005	Enomoto et al.
2003/0194143	A1	10/2003	Iida	2005/0226499	A1	10/2005	Terakawa
2003/0202715	A1	10/2003	Kinjo	2005/0232490	A1	10/2005	Itagaki et al.
2004/0017481	A1	1/2004	Takasumi et al.	2005/0238230	A1	10/2005	Yoshida
2004/0027593	A1	2/2004	Wilkins	2005/0243348	A1	11/2005	Yonaha
2004/0032512	A1	2/2004	Silverbrook	2005/0275734	A1	12/2005	Ikeda
2004/0032526	A1	2/2004	Silverbrook	2005/0276481	A1	12/2005	Enomoto
2004/0033071	A1	2/2004	Kubo	2005/0280717	A1	12/2005	Sugimoto
2004/0037460	A1	2/2004	Luo et al.	2005/0286766	A1	12/2005	Ferman
2004/0046878	A1	3/2004	Jarman	2006/0008171	A1	1/2006	Petschnigg et al.
2004/0047491	A1	3/2004	Rydbeck	2006/0017825	A1	1/2006	Thakur
2004/0056975	A1	3/2004	Hata	2006/0038916	A1	2/2006	Knoedgen et al.
2004/0057623	A1	3/2004	Schuhcke et al.	2006/0039690	A1	2/2006	Steinberg et al.
2004/0057715	A1	3/2004	Tsuchida et al.	2006/0045352	A1	3/2006	Gallagher
2004/0090461	A1	5/2004	Adams	2006/0050300	A1	3/2006	Mitani et al.
2004/0093432	A1	5/2004	Luo et al.	2006/0066628	A1	3/2006	Brodie et al.
2004/0114796	A1 *	6/2004	Kaku 382/165	2006/0082847	A1	4/2006	Sugimoto
2004/0114797	A1	6/2004	Meckes	2006/0093212	A1	5/2006	Steinberg et al.
2004/0114829	A1	6/2004	LeFeuvre et al.	2006/0093213	A1	5/2006	Steinberg et al.
2004/0114904	A1	6/2004	Sun et al.	2006/0093238	A1	5/2006	Steinberg et al.
2004/0119851	A1	6/2004	Kaku	2006/0098867	A1	5/2006	Gallagher
2004/0120598	A1	6/2004	Feng	2006/0098875	A1	5/2006	Sugimoto
2004/0125387	A1	7/2004	Nagao et al.	2006/0119832	A1	6/2006	Iida
2004/0126086	A1	7/2004	Nakamura et al.	2006/0120599	A1	6/2006	Steinberg et al.
2004/0141657	A1	7/2004	Jarman	2006/0140455	A1	6/2006	Costache et al.
2004/0150743	A1	8/2004	Schinner	2006/0150089	A1	7/2006	Jensen et al.
2004/0160517	A1	8/2004	Iida	2006/0203108	A1	9/2006	Steinberg et al.
2004/0165215	A1	8/2004	Raguet et al.	2006/0204052	A1	9/2006	Yokouchi
2004/0184044	A1	9/2004	Kolb et al.	2006/0204110	A1	9/2006	Steinberg et al.
2004/0184670	A1	9/2004	Jarman et al.	2006/0221408	A1	10/2006	Fukuda
2004/0196292	A1	10/2004	Okamura	2006/0285754	A1	12/2006	Steinberg et al.

2007/0110305	A1	5/2007	Corcoran et al.
2007/0116379	A1	5/2007	Corcoran et al.
2007/0116380	A1	5/2007	Ciuc et al.
2007/0133863	A1*	6/2007	Sakai et al. 382/151
2007/0201724	A1	8/2007	Steinberg et al.
2007/0263104	A1	11/2007	DeLuca et al.
2008/0002060	A1	1/2008	DeLuca et al.
2008/0013798	A1	1/2008	Ionita et al.
2008/0043121	A1	2/2008	Prilutsky et al.
2008/0112599	A1	5/2008	Nanu et al.
2008/0144965	A1	6/2008	Steinberg et al.
2008/0186389	A1	8/2008	DeLuca et al.
2008/0211937	A1	9/2008	Steinberg et al.
2008/0232711	A1	9/2008	Prilutsky et al.
2008/0240555	A1	10/2008	Nanu et al.

FOREIGN PATENT DOCUMENTS

EP	0 911 759	A2	4/1999
EP	0 911 759	A3	4/1999
EP	1 199 672	A2	4/2002
EP	1 229 486	A1	8/2002
EP	1 288 858	A1	3/2003
EP	1 288 859	A1	3/2003
EP	1 288 860	A1	3/2003
EP	1 293 933	A1	3/2003
EP	1 296 510	A	3/2003
EP	1 429 290	A	6/2004
EP	1 429 290	A2	6/2004
EP	1 429 290	A3	6/2004
EP	1 429 290	A2	6/2004
EP	1 478 169	A	11/2004
EP	1 528 509	A2	5/2005
EP	979 487	B1	3/2006
EP	1 429 290	B1	7/2008
GB	841 609	A	7/1960
JP	4-192 681		7/1992
JP	2005-A2224271		3/1993
JP	921 4839	A2	8/1997
JP	2000-134486		5/2000
JP	22247596	A2	8/2002
JP	2002-271808		9/2002
JP	2003-030647	*	1/2003
WO	WO-9802844	A1	1/1998
WO	WO 99/17254		4/1999
WO	WO 99-17254		4/1999
WO	WO-9933684	A2	7/1999
WO	WO 01-71421	A1	7/2001
WO	WO 01/71421	A1	9/2001
WO	WO-0192614	A1	12/2001
WO	WO 02/45003	A	6/2002
WO	WO 02/45003	A1	6/2002
WO	WO 03-026278	A1	2/2003
WO	WO 03/026278	A1	3/2003
WO	WO 03/071484	A	8/2003
WO	WO 03/071484	A1	8/2003
WO	WO 03-071484	A1	8/2003
WO	WO-2004034696	A1	4/2004
WO	WO 2005-015896	A1	2/2005
WO	WO 2005-041558	A	5/2005
WO	WO 2005/041558	A	5/2005
WO	WO 2005-109853	A1	5/2005
WO	WO 2005-076217	A2	8/2005
WO	WO 2005-076217	A3	8/2005
WO	WO-2005087994	A1	9/2005
WO	WO 2006/018056	A1	2/2006
WO	WO-2006011635	A1	2/2006
WO	WO 2006-045441	A1	5/2006
WO	WO-2007057063	A1	5/2007
WO	WO-2007057064	A1	5/2007
WO	WO-2007093199	A2	8/2007
WO	WO-2007093199	A3	8/2007
WO	WO-2007095553	A2	8/2007

WO	WO-2007095553	A3	8/2007
WO	WO-2007142621	A1	12/2007
WO	WO-2008023280	A2	2/2008
WO	WO-2008109644	A2	9/2008
WO	WO-2008109644	A3	9/2008

OTHER PUBLICATIONS

PCT Notification of Transmittal of the International Search Report and Written Opinion of the International Searching Authority for PCT Application No. PCT/EP2005/005907, (12 pages).

International Search Report and Written Opinion of the International

Searching Authority for PCT Application No. PCT/EP2004/008706.

International Search Report and Written Opinion of the International

Searching Authority for PCT Application No. PCT/EP2005/005033.

International Search Report and Written Opinion of the International

Searching Authority for PCT Application No. PCT/EP2005/005907.

Patent Abstracts of Japan, publication No. 2000050062, application

No. 10-217124, published Feb. 18, 2000.

U.S. Appl. No. 10/170,511, filed Jun. 12, 2002, inventor Michael J.

DeLuca.

U.S. Appl. No. 10/772,767, filed Feb. 4, 2004, inventors Michael J.

DeLuca, et al.

U.S. Appl. No. 11/217,788, filed Aug. 30, 2005, inventors Eran

Steinberg, et al.

Mathew Gaubatz, et al., Automatic Red-Eye Detection and Correc-

tion, IEEE ICIP, 2002, pp. I-804-I-807.

Written Opinion of the International Searching Authority, PCT appli-

cation No. PCT/EP2004/008706, 4 pages.

European Examination Report, Appln. No. 05792584.4, May 13,

2008, 8 pages.

Gaubatz, M., "Automatic Red-Eye Detection and Correction," IEEE

ICIP, 2002, pp. I-804-I807.

Ioffe, S., Red Eye Detection with Machine Learning, Proceedings of

2003 IEEE Intl. Conf. Image Processing, vol. 2, Sep. 14, 2003, pp.

871-874.

International Search Report and Written Opinion, PCT/EP2004/

010199, Dec. 9, 2004, 6 pages.

International Preliminary Examination Report, PCT/EP2005/

011010, Jan. 26, 2007, 18 pages.

Nguyen, K. et al., "Differences in the Infrared Bright Pupil Response

of Human Eyes," Proc. Of 2002 symposium on Eye tracking research

and applns., 2002, New Orleans, LA, pp. 133-138.

Sahba, F. et al., "Filter Fusion of Image Enhancement Using Rein-

forcement Learning," CCECE 2003, Canadian Conf. on Electrical

and Computer Engrg, Montreal, Canada, May 4-7, 2003, IEEE, US,

vol. 3 of 3, May 4, 2003, pp. 847-850, XP010654204, ISBN: 0-7803-

7781-8.

Shen, J., Inpainting and the Fundamental Problem of Image Process-

ing, Nov. 25, 2002, 6 pgs.

Combiar, Nathalie et al., "Removal of Defects on Flash Radiographic

Images by Fuzzy Combination, Conference: Machine Vision Appli-

cations in Industrial Inspection III, [http://links2.dialog.com/](http://links2.dialog.com/NASApp/ChannelWEB/Dialog/ProServlet?ChName=engineering)

NASApp/ChannelWEB/Dialog/ProServlet?ChName=engineering",

Proceedings of SPIE—The International Society for Optical Engi-

neering, Society of Photo-Optical Instrumentation, 1995, pp. 301-

312.

Corcoran, P. et al., "Automated In-Camera Detection of Flash-Eye

Defects", IEEE Transactions on Consumer Electronics, 2005, pp.

11-17, vol. 51—Issue 1.

Cucchiara, R. et al., "Detection of Luminosity Profiles of Elongated

Shapes", International Conference on Image Processing, 1996, pp.

635-638, vol. 3.

EPO Communication pursuant to Article 94(3) EPC, for European

Patent Application No. 05 792 584.4, paper dated May 13, 2008, 8

pages.

European Patent Office, Communication pursuant to Article 94(3)

EPC for Application No. 04763763.2, dated Mar. 7, 2008, 7 pages.

European Patent Office, Communication pursuant to Article 96(2)

EPC for Application No. 04763763.2, dated Aug. 29, 2006, 4 pages.

Han, T. et al., "Detection and Correction of abnormal Pixels In

Hyperion Images", IEEE International Symposium on Geoscience

and Remote Sensing, 2002, pp. 1327-1330, vol. 3.

- Iivarinen, J. et al., "Content-Based Retrieval of Defect Images, <http://www.cs.tut.fi/~about.avisa/digger/Publications/acivs02.pdf>", Proceedings of Advanced Concepts for Intelligent Vision, Laboratory of Computer Information Science, 2002.
- Ito, M., "An Automated System for LSI Fine Pattern Inspection Based on Comparison of Sem Images and Cad Data", IEEE International Conference on Robotics and Automation, 1995, pp. 544-549, vol. 1.
- Jin, B. et al., "Modeling and Analysis of Soft-Test/Repair for CCD-Based Digital X-Ray Systems", Instrumentation and Measurement, IEEE Transactions, 2003, pp. 1713-1721, vol. 52—Issue 6.
- PCT International Preliminary Report on Patentability (IPRP) for PCT Application PCT/EP2005/011010, dated Jan. 23, 2007, 18 pages. cited by other.
- PCT International Preliminary Report on Patentability for PCT Application No. PCT/EP2005/005907, dated Nov. 15, 2006, 8 pages.
- PCT International Preliminary Report on Patentability for PCT Application PCT/EP2004/008706, dated Feb. 6, 2006, 7 pages.
- PCT International Preliminary Report on Patentability for PCT Application PCT/EP2004/010199, dated Apr. 3, 2006, 7 pages.
- PCT International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, for PCT Application No. PCT/US2008/055864, dated Jul. 30, 2008, 8 pages.
- PCT Notification Concerning Transmittal of International Preliminary Report on Patentability, for PCT Application No. PCT/US2007/062090, dated Aug. 28, 2008, 6 pages.
- PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration (PCT/EP2006/008342), dated Dec. 28, 2006.
- PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for PCT Application No. PCT/US07/62090 issued Mar. 10, 2008, 10 pages.
- PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for PCT/EP2005/011010, dated Jan. 23, 2006, 14 pages.
- PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration for PCT/EP2005/05907, dated Aug. 1, 2005, 12 pages.
- PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, for PCT Application No. PCT/EP2006/008358, Dec. 5, 2006, 14 pages.
- PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration, for PCT Application No. PCT/US2008/055964, paper dated Jul. 30, 2008, 8 Pages.
- PCT Notification of Transmittal of the International Search Report and Written Opinion of the International Searching Authority for PCT Application No. PCT/EP2005/001171, (11 pages).
- Plotnikov, Yuri et al., "Advanced Image Processing for Defect Visualization in Infrared Thermography, <http://citeseer.ist.psu.edu/plotnikov98advanced.html>", NASA Langley Research Center, M.S. Posted: ACM Portal, 1998.
- Plotnikov, Yuri et al., Winfree, "Visualization of Subsurface Defects in Composites Using a Focal Plane Array Infrared Camera", <http://citeseer.ist.psu.edu/357066.html>", NASA Langley Research Center, 1999.
- Smolka, B. et al., "Towards Automatic Redeye Effect Removal, XP004416063", Pattern Recognition Letters, 2003, pp. 1767-1785, vol. 24—Issue 11, North-Holland Publ.
- Soriano, M. et al., "Making Saturated Facial Images Useful Again, XP002325961, ISSN: 0277-786X", Proceedings of The Spie, 1999, pp. 113-121, vol. 3826.
- Tan, Yap-peng et al., "Robust Sequential Approach for the Detection of Defective Pixels in an Image Sensor, <http://ieeexplore.ieee.org/search/freesrchabstract.jsp?arnumber=758382&isnumber=16342&punumber=6110&k2dockey=758382&ieeefn&query=%28%28%28%28images+and+defects+and+correction%29%29%29%29+%3Cin%3E>", IEEE International Conference on Acoustics, Speech, and Signal Proc, 1999, pp. 2239-2242, vol. 4.
- Toet, A., "Multiscale Color Image Enhancement, Posted online: Aug. 6, 2002 18:09:24.0 <http://ieeexplore.ieee.org/search/freesrchabstract.jsp?arnumber=146865&isnumber=3917&punumber=1197&k2dockey=146865&ieeefn&query=%28%28images+and+defects+and+luminance%29%29+%3Cin%3E+metadata&pos=1>", International Conference on Image Processing and its Applications, 1992, pp. 583-585.
- United Kingdom Search Report dated May 22, 2007, issued in Application No. GB 0701957.3.
- Willamowski, J. et al., "Probabilistic Automatic Red Eye Detection and Correction", The 18th International Conference on Pattern Recognition (ICPR'06), 2006, pp. 762-765, vol. 3, IEEE Computer Society.

* cited by examiner




Figure 1




Figure 2




Figure 3-a




Figure 3-b



Figure 3-c




Figure 3-d




Figure 3-e





Figure 4

**Figure 5-a**




Figure 5-b




Figure 5-c




Figure 5-d




Figure 6-a




Figure 6-b

1

**RED-EYE FILTER METHOD AND
APPARATUS****PRIORITY AND RELATED APPLICATIONS**

This application is a continuation-in-part (CIP) application which claims the benefit of priority to U.S. patent application Ser. No. 10/772,767, filed Feb. 4, 2004, now U.S. Pat. No. 7,352,394, issued Apr. 1, 2008, which is a CIP that claims the benefit of priority to U.S. patent application Ser. No. 10/635,862 filed Aug. 5, 2003, now U.S. Pat. No. 7,630,006 which is a CIP that claims the benefit of priority to U.S. patent application Ser. No. 10/170,511, filed Jun. 12, 2002, now U.S. Pat. 7,042,505, issued May 9, 2006, which is a continuation of U.S. patent application No. 08/947,603, filed Oct. 9, 1997, now U.S. Pat. No. 6,407,777, issued Jun. 18, 2002, which are each hereby incorporated by reference. This application is also related to U.S. patent applications Ser. No. 10/635,918, filed Aug. 5, 2003, and Ser. No. 10/773,092, filed Feb. 4, 2004.

FIELD OF THE INVENTION

The invention relates generally to the area of digital photography, and more specifically to filtering "red-eye" artefacts from a flash-induced digital camera image.

BACKGROUND OF THE INVENTION

"Red-eye" is a phenomenon in flash photography where a flash is reflected within a subject's eye and appears in a photograph as a red dot where the black pupil of the subject's eye would normally appear. The unnatural glowing red of an eye is due to internal reflections from the vascular membrane behind the retina, which is rich in blood vessels. This objectionable phenomenon is well understood to be caused in part by a small angle between the flash of the camera and the lens of the camera. This angle has decreased with the miniaturization of cameras with integral flash capabilities. Additional contributors include the relative closeness of the subject to the camera and ambient light levels.

The red-eye phenomenon can be minimized by causing the iris to reduce the opening of the pupil. This is typically done with a "pre-flash", a flash or illumination of light shortly before a flash photograph is taken. This causes the iris to close. Unfortunately, the pre-flash is an objectionable 0.2 to 0.6 seconds prior to the flash photograph. This delay is readily discernible and easily within the reaction time of a human subject. Consequently the subject may believe the pre-flash is the actual photograph and be in a less than desirable position at the time of the actual photograph. Alternately, the subject must be informed of the pre-flash, typically losing any spontaneity of the subject captured in the photograph.

Those familiar with the art have developed complex analysis processes operating within a camera prior to invoking a pre-flash. Various conditions are monitored prior to the photograph before the pre-flash is generated; the conditions include the ambient light level and the distance of the subject from the camera. Such a system is described in U.S. Pat. No. 5,070,355, which is hereby incorporated by reference. Although that invention minimizes the occurrences where a pre-flash is used, it does not eliminate the need for a pre-flash.

Digital cameras are becoming more popular and smaller in size. Digital cameras have several advantages over film cameras. Digital cameras eliminate the need for film as the image is digitally captured and stored in a memory array for display on a display screen on the camera itself. This allows photo-

2

graphs to be viewed and enjoyed virtually instantaneously as opposed to waiting for film processing. Furthermore, the digitally captured image may be downloaded to another display device such as a personal computer or color printer for further enhanced viewing. Digital cameras include microprocessors for image processing and compression and camera systems control. It is possible to exploit the computation capabilities of such microprocessors for performing operations to improve the red-eye detection and elimination. Thus, what is needed is a method of better tools for eliminating red-eye phenomenon within, for example, a digital camera having a flash unit without the distraction of a pre-flash.

U.S. Patent Application 2002/0150306 (Baron), which is hereby incorporated by reference, describes a method for the removal of flash artefacts by capturing two digital images of a subject, one with flash and one without flash, and subtracting one image from the other to provide an artefact image which is then thresholded and subtracted from the flash image. However, the technique is directed to flash artefacts in general, and not specifically to red-eye removal. There is no attempt to identify red-eye regions as compared to any other flash-induced artefacts. Indeed, there is no attempt to identify particular regions at all, since the technique is simply one of subtraction and thresholding.

BRIEF SUMMARY OF THE INVENTION

A system in accordance with the present invention there is provided a digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said detection being based upon a comparison of said captured image and at least one reference eye color characteristic.

According to one embodiment of the invention, the at least one reference eye color characteristic includes a reference image of nominally the same scene taken without flash.

According to this embodiment, the reference image may be a preview image of lower pixel resolution than the captured image, the filter may include programming code for matching the pixel resolutions of the captured and reference images by up-sampling the preview image and/or sub-sampling the captured image.

To allow for inadvertent movement in the subject between taking the two images, preferably the filter may further include programming code for aligning at least portions of the captured image and reference image prior to said comparison.

In the embodiment the filter detects said region indicative of a red-eye phenomenon by identifying a region in the captured image at least having a color indicative of a red-eye phenomenon and comparing said identified region with the corresponding region in the reference image. The filter may further designate the region as indicative of a red-eye phenomenon if said corresponding region does not have a color indicative of a red-eye phenomenon. The decision as to whether a region has a color indicative of a red-eye phenomenon may be determined on a statistical basis as a global operation on the entire region.

According to a further embodiment, the filter includes a shape analyser so that the filter is configured to identify a region in the captured image having both a shape and color indicative of a red-eye phenomenon for subsequent comparison with a reference eye shape characteristic and the reference eye color characteristic, respectively.

In another embodiment, a pixel modifier is included for modifying the color of the pixels within a region indicative of a red-eye phenomenon.

A method in accordance with the present invention is also provided for detecting a red-eye phenomenon within a digital image acquired by a digital image acquisition device having no photographic film. The device includes a portable apparatus for capturing digital images, and a flash unit for providing illumination during image capture. The method includes identifying a region within a captured image indicative of a red-eye phenomenon including comparing the captured image and at least one reference eye color characteristic.

According to one embodiment, the at least one reference eye color characteristic includes an eye color characteristic of a reference image of nominally the same scene taken without flash.

The reference image may be a preview image of lower pixel resolution than the captured image. The method may further include matching the pixel resolutions of the captured and reference images including up-sampling the preview image or sub-sampling the captured image, or a combination thereof.

The method may further include aligning at least portions of the captured image and reference image prior to said comparison.

The method may further include analysing a shape so that the identifying comprises identifying a region in the captured image having both a shape and color indicative of a red-eye phenomenon for subsequent comparison with the corresponding region in the reference image. A shape may be analysed to determine subsequent to the comparison whether a region designated as indicative of a red-eye phenomenon has a shape indicative of a red-eye phenomenon.

The method may also include detecting a region indicative of a red-eye phenomenon by identifying a region in the captured image at least having a color indicative of a red-eye phenomenon and comparing the identified region with the corresponding region in the reference image, and designating the region as indicative of a red-eye phenomenon if the corresponding region does not have a color indicative of a red-eye phenomenon.

The method may also include deciding whether a region has a color indicative of a red-eye phenomenon by determining on a statistical basis as a global operation on the entire region.

The method may also include modifying the color of the pixels within a region indicative of a red-eye phenomenon.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a camera apparatus operating in accordance with an embodiment of the present invention.

FIG. 2 illustrates the workflow of the initial stage of a red-eye filter using preview data according to the embodiment.

FIGS. 3-a to 3-d illustrates the pixelation process of an image in different resolutions.

FIG. 3-e is an enlargement of a hypothetical digitization of an eye in an image.

FIG. 4. illustrates the pixel differences between a red-eye image and a non red-eye image.

FIGS. 5-a to 5-d and 6-a and 6-b illustrate the detailed workflow of the red-eye filter according to the embodiment, and alternatives.

DESCRIPTION OF A PREFERRED EMBODIMENT

FIG. 1 shows a block diagram of a image acquisition system such as a digital camera apparatus operating in accordance with the present invention. The digital acquisition device, also generically referred to in this application as a camera 20, includes a processor 120. It can be appreciated that many of the processes implemented in the digital camera may be implemented in or controlled by software operating in a microprocessor (μ Proc), central processing unit (CPU), controller, digital signal processor (DSP) and/or an application specific integrated circuit (ASIC), collectively depicted as block 120 and termed as "processor". Generically, all user interface and control of peripheral components such as buttons and display is controlled by a μ -controller 122. The processor 120, in response to a user input at 122, such as half pressing a shutter button (pre-capture mode 32), initiates and controls the digital photographic process. Ambient light exposure is determined using light sensor 40 in order to automatically determine if a flash is to be used. The distance to the subject is determined using focusing means 50 which also focuses the image on image capture means 60. If a flash is to be used, processor 120 causes the flash means 70 to generate a photographic flash in substantial coincidence with the recording of the image by image capture means 60 upon full depression of the shutter button. The image capture means 60 digitally records the image in color. The image capture means is known to those familiar with the art and may include a CCD (charge coupled device) or CMOS to facilitate digital recording. The flash may be selectively generated either in response to the light sensor 40 or a manual input 72 from the user of the camera. The image recorded by image capture means 60 is stored in image store means 80 which may comprise computer memory such a dynamic random access memory or a non-volatile memory. The camera is equipped with a display 100, such as an LCD, for preview and post-view of images. In the case of preview images, which are generated in the pre-capture mode 32, the display 100 can assist the user in composing the image, as well as being used to determine focusing and exposure. In case of postview, the image display can assist the user in viewing suspected red-eye regions and to manually decide if the region should be corrected or not after viewing it. A temporary storage space 82 is used to store one or plurality of the preview images and be part of the image store means 80 or a separate component. The preview image is usually generated by the same image capture means 60, and for speed and memory efficiency reasons may be generated by subsampling the image 124 using software which can be part of the general processor 120 or dedicated hardware, before displaying 100 or storing 82 the preview image. Depending on the settings of this hardware subsystem, the pre-acquisition image processing may satisfy some predetermined criteria prior to storing the preview image. Such criteria may be chronological—such as save images every 0.5 seconds; more sophisticated criteria may be analysis of the image for changes, or the detection of faces in the image. A straightforward preferred embodiment is to constantly replace the previous saved preview image with a new captured preview image during the pre-capture mode 32, until the final full resolution image is captured by full depression of the shutter button.

The red-eye filter 90 can be integral to the camera 20 or part of an external processing device 10 such as a desktop computer, a hand held device, a cell phone handset or a server. In this embodiment, the filter receives the captured image from the full resolution image storage 80 as well as one or a plu-

ality of preview images from the temporary storage **82**. The filter **90** analyzes the stored image for characteristics of red-eye and, if found, modifies the image and removes the red-eye phenomenon from the image as will be describe in more detail. The red-eye filter includes a pixel locator **92** for locating pixels having a color indicative of red-eye; a shape analyzer **94** for determining if a grouping of at least a portion of the pixels located by the pixel locator comprise a shape indicative of red-eye; an falsing analyzer **96** for processing the image around the grouping for details indicative of an image of an eye; and a pixel modifier **98** for modifying the color of pixels within the grouping. The modified image may be either displayed on image display **100**, saved on a persistent storage **112** which can be internal or a removable storage such as CF card, SD card or the like, or downloaded to another device, such as a personal computer, server or printer via image output means **110** which can be tethered or wireless.

In a further embodiment where the red-eye filter **90** is located on an external application in a separate device, **10**, such as a desktop computer, the final captured image stored in block **80** along with a representation of the preview image as temporarily stored in **82**, may be stored prior to modification on the storage device **112**, or transferred together via the image output means **110** onto the external device **10**, later to be processed by the red-eye filter **90**.

FIG. **2** details the initial stage of the workflow of this embodiment. It will be understood both this initial stage as well as the subsequent red-eye correction stage (See FIGS. **5a** to **5d**) will typically be performed by software in the camera and/or separate device **10**. A preview image (normally of lesser resolution than the final image) is generated while the camera is in the pre-capture mode **32** such as when the user half presses the shutter button. While in this mode, shown in FIG. **2** as the preview mode **210**, the camera constantly captures the preview images **220**. The capture interval is usually semi-real time which means fractions of a tenth of a second or less. The camera saves each new preview image if it satisfies some test criteria, **122**. If not, the camera continues, **211**, to capture the next preview image without saving the previous one. The process will continue until the final full resolution image is acquired **280** and saved **282** by fully depressing the shutter button.

In a simple embodiment, if the test criteria are met, or if no test criteria exist, the system will constantly replace the previous saved preview image with the new preview image, **230**. Alternatively, where multiple preview images can be saved, **240**, the new image will be placed on a chronological FIFO stack, namely First In First Out, where the system continuously captures and saves new preview images **244** while each time clearing the oldest image **242** from the stack, until the user takes the final picture. The reason for storing multiple preview images is based on the fact that the last image, or any single image, may not be the best reference image for comparison with the final full resolution image in the red-eye correction process. By storing multiple images, a better reference image can be achieved, and a closer alignment between the preview and the final captured image can be achieved. This concept will be further discussed in FIGS. **5a** to **5c**, in the alignment stage **540**. Other reasons for capturing multiple images are that a single image may be blurred due to motion, the subject had their eyes closed, the exposure was not set, etc. In a yet alternative embodiment, the multiple images may assist in creating a single higher quality reference image; either higher resolution or by taking different portions of different regions from the multiple images. This concept of sub-pixel resolution may be combined with the upsampling process as described in FIGS. **5a** to **5c**, block **534**.

The test criteria **222** may involve the actual analysis of the preview image content before deciding whether the new preview image should replace a previously saved image. Such criteria may be based on image analysis such as the existence of faces in the image, detection of eyes or metadata analysis such as the exposure condition, whether a flash is going to happen, the distance to the subjects, etc.

As part of the red-eye filter **90** the full resolution image **292** and the preview image or images **294** will be loaded into working memory, **292** and **294**, unless they are already in memory in which they will just be accessed through a pointer. Referring to FIGS. **3a-3e**, the digitization process in various resolutions is explained and depicted. FIG. **3a** illustrates the grid like nature of a sensor as illustrated in FIG. **1**, block **60**. The sensor comprises multiple cells **302** which determine the camera resolution. For example a sensor of 2000×3000 cells will be a 6 Million pixel sensor (it will be understood that each cell in fact comprises a plurality of individual sensor elements sensitive to different colors, e.g. RGB or RGBG, to create each colored image pixel).

FIG. **3-b** depicts the optical projection of a face **310** onto the sensor **60**. Each of the cells **302** records the average light information it receives for the image. This is the process of digitization and quantization.

The degree of details is determined by the resolution of the sensor as depicted in FIG. **3-c**. In this illustration a much smaller sensor is used, and in this case the same face **310** is digitized into a smaller number of pixels, or alternatively subsampled from the full resolution sensor data into a smaller number of pixel representations.

FIG. **3-d** describes the inverse process where the subsampled image of FIG. **3-c** is upsampled to the same size as the original. When comparing the resolution, naturally the some of the details are lost in this process. For illustrative example, while in FIG. **3-b** the face was roughly $25 \times 25 = 625$ pixels, in FIG. **3-d** the face is made of only $5 \times 5 = 25$ pixels.

Of course, the above are only for illustration purposes. In practice, due to the larger resolution of the sensors than in this illustration, a normal eye will be depicted by a much larger pixel count to be noticeable. FIG. **3-e** displays such a digitized eye. In this figure, an eye **350**, as imaged on a sensor **60**, will consist of roughly 25 pixels wide, **352**. In particular interest for this invention the inner portion, the iris **360**, in this case will be roughly 8 pixels in diameter, as illustrated in **462**.

According to a preferred embodiment of this invention, the preview image and the final image, or portions of them, need to be aligned as depicted in FIG. **5**, block **540**. As explained above, the reference image and the final image may have different resolutions. The discrepancy in resolution may lead to differences in content, or pixel values, even though no data was changed in the subject image. In particular, edge regions when downsampled and then upsampled may have a blurring or an averaging effect on the pixels. Thus direct comparison of different resolution images, even when aligned, may lead to false contouring. In addition, the reference image may be acquired prior to or after the final image is captured. Due to the above reasons, there is a need to match the two images, both in content and pixel resolution, as described below.

FIG. **4** better illustrates the effect of the sub- and up-sample process in finding the difference pixelwise between two images. In this case, the input images are the ones illustrated in FIGS. **3-b** and **3-d** respectively high resolution and low resolution. In this figure, white squares such as **430** means that there is no difference between the two. Checkered squares or pixels, such as **420** means that there is a difference between the images.

The flat regions should display no significant differences due to resolution changes. The main difference will be caused by two reasons namely edge regions where changes in value occur such as in blocks 410. However, there is another cause for difference which is of interest to this invention and displayed in 430. In these pixels, the difference is caused by the actual change in the color of the eye from normal eyes to red-eyes. Not only is there a change in the pixel value but the change is also more specifically reflected as change to a red or light color from the normal color of the iris or from the black color of the pupil.

FIGS. 5-a to 5-d illustrate the workflow of the red-eye filter 90 of this embodiment, as well as variations thereof.

Referring first to FIG. 5-a, there are two input images into the filter, namely a full resolution image 510, $I(x,y)$ which is the one that was captured by full depression of the shutter button and needs to be analyzed for red-eye artefacts, and a preview image 520, $P(x,y)$ which is used as a reference image and is nominally the same scene as the image $I(x,y)$ but taken without the flash. The preview image may be a result of some image processing taking into account multiple preview images and creating a single image, 522. Methods of improving image quality based on multiple images are familiar to those versed in the art of image processing. The resulting output from the analysis process of 522 is a single preview image.

The preview image 520 is normally, but not necessarily, of lower resolution than the full resolution image 510, typically being generated by clocking out a subset of the sensor cells or by averaging the raw sensor data. Therefore, the two images, or alternatively the relevant regions in the images (i.e. the regions containing or suspected to contain eyes, which can be determined by image processing techniques known in the art), need to be matched in pixel resolution, 530. In the present context "pixel resolution" means the size of the image, or relevant region, in terms of the number of pixels constituting the image or region concerned. Such a process may be done by either upsampling the preview image, 534, downsampling the acquired image, 532, or a combination thereof. Those familiar in the art will be aware of several techniques best used for such sampling methods. The result of step 530 is a pair of images $I'(x,y)$ and $P'(x,y)$ corresponding to the original images $I(x,y)$ and $P(x,y)$, or relevant regions thereof, with matching pixel resolution. The system and method of the preferred embodiment involves the detection and removal of red-eye artefacts. The actual removal of the red-eye will eventually be performed on the full resolution image. However, all or portions of the detection of red-eye candidate pixel groupings, the subsequent testing of said pixel groupings for determining false red-eye groupings, and the initial step of the removal, where the image is presented to the user for user confirmation of the correction, can be performed on the entire image, the subsampled image, or a subset of regions of the entire image or the subsampled image.

Although nominally of the same scene, the preview image and the finally acquired full resolution image may differ spatially due to the temporal lag between capturing the two images. Therefore, the two images, or relevant regions thereof, may need to be aligned, 540, especially in respect of regions of the images containing or suspected to contain eyes. Essentially, alignment means transforming at least one of the images, and in this embodiment the preview image $P'(x,y)$, to obtain maximum correlation between the images, or relevant regions thereof, based on measurable characteristics such as color, texture, edge analysis. Those familiar in the art are aware of several algorithms to achieve such alignment; see, for example, U.S. Pat. No. 6,295,367 which is hereby incor-

porated by reference and which describes alignment of images due to object and camera movement, and U.S. Pat. No. 5,933,546, which is also hereby incorporated by reference and which addresses the use of multi-resolution data for pattern matching.

Further discussion on the alignment is presented in FIG. 5-c. In this Figure, the inputs are the two images $I'(x,y)$ and $P'(x,y)$ as defined in FIG. 5-a. The alignment may be global for the entire image or local for specific regions. For example, a simple linear alignment, such as a shift in the horizontal direction by H pixels, and/or in the vertical direction by V pixels, or a combination of the two. Mathematically, the shifted image, $P''(x,y)$, can be described as:

$$P''(x,y) = P'(x-H, y-V)$$

However, simple translation operation may not suffice in the need to align the image. Therefore, there may be a need for X-Y shearing, which is a symmetrical shift of the object's points in the direction of the axis to correct for perspective changes; X-Y tapering where the object is pinched by shifting its coordinates towards the axis, the greater the magnitude of the coordinate the further the shift; or rotation around an arbitrary point.

In general, the alignment process may involve an affine transformation, defined as a special class of projective transformations that do not move any objects from the affine space R_3 to the plane at infinity or conversely, or any transformation that preserves collinearity (i.e. all points lying on a line initially still lie on a line after transformation) and ratios of distances (e.g., the midpoint of a line segment remains the midpoint after transformation). Geometric contraction, expansion, dilation, reflection, rotation, shear, similarity transformations, spiral similarities and translation are all affine transformations, as are their combinations. In general, the alignment 540 may be achieved via an affine transformation which is a composition of rotations, translations, dilations, and shears, all well-known to one familiar in the art of image processing.

If it is determined through a correlation process that a global transformation suffices, as determined in block 542=YES, one of the images, and for simplicity the preview image, will undergo an affine transformation, 544, to align itself with the final full resolution image. Mathematically, this transformation can be depicted as:

$$P'' = AP' + q$$

where A is a linear transformation and q is a translation.

However, in some cases a global transformation may not work well, in particular for cases where the subject matter moved, as could happen when photographing animated objects. In such case, in particular in images with multiple human subjects, and when the subjects move in independent fashion, the process of alignment 540 may be broken down, 546, to numerous local regions each with its own affine transformation. What is important is to align the eyes between the images. Therefore, according to this alternative, one or multiple local alignments may be performed, 548, for regions in the vicinity surrounding the eyes, such as faces.

Only after the images are aligned can one compare the potential red-eye colors.

In the preferred embodiment of FIG. 5-a, the preview image information is used as part of the falsing stage 96. Blocks 92, 94 and 98 correspond to the same blocks in FIG. 1, being the stages of pixel locator, shape analyzer and pixel modification respectively. This embodiment can incorporate pixel locator 92, shape analyzer 94 and pixel modifier 98 as

described in U.S. Pat. No. 6,407,777 (DeLuca), incorporated by reference above, the functions of the pixel locator 92 and shape analyzer 94 being performed on the image $I'(x,y)$ and the pixel modifier 98 operating on the original acquired image $I(x,y)$. Block 96, which is the falsing stage, is improved in this embodiment as compared to the falsing stage of DeLuca.

Referring to block 96, for each region of the image $I'(x,y)$ suspected as red-eye, step 596-2, as identified by steps 92 and 94, the suspected region is tested by comparing the pixel values of the region with the pixel values of the corresponding region in the aligned preview image $P''(x,y)$, 596-6. However, prior to doing so, the regions need to be prepared and modified for such comparison, 596-4.

Due to the fact that the regions may not match exactly, a pixel-by-pixel comparison may not suffice. The reason for the mismatch may occur due to the original size discrepancy. For example, in edges this phenomenon is graphically illustrated in FIG. 4. Other reasons for a mismatch are potential movement of the object, or there may be some averaging that is done in the low resolution preview image that may lose high frequency color data. Such effects are referred to as smoothing and aliasing. In addition, even if the alignment is optimal, there may be sub-pixel alignment that can not be accounted for. Moreover, there may be color differences between the preview image, shot using available light and the acquired full resolution image which is shot using flash. In many cases, the color transformation between one image to another is not global and uniform. Therefore, the process of preparing the regions for comparison.

This process as illustrated in block 596-4 will be further described in FIG. 5-d. The underlying concept behind step 596-4 is to distinguish between differences that are caused due to the acquisition process and the differences that are caused due to the existence of red-eye in the image. This problem is well known to one familiar in the art of statistical pattern matching and scene analysis and image recognition. An example of such an application taking into account differences due to resolution is described in U.S. Pat. No. 5,933,546, which is hereby incorporated by reference.

If a region in the aligned preview image $P''(x,y)$ was red and the equivalent region is red in the image $I'(x,y)$, 596-6, that region will be eliminated from $I'(x,y)$ as a red-eye artefact, 596-9, and the corresponding region will be eliminated as a red-eye artefact from the original full resolution image $I(x,y)$. Otherwise, the region will continue to remain suspected as red-eye, 596-8. The process will continue, 596-3, for all suspected regions.

The comparison of the regions for a color value is done as a global operation on the entire region, and the answer to the question of whether a region is red or not is made statistically for the entire region and not pixel by pixel, i.e. it does not depend on the value of any particular individual pixel. Such approach will account for inconsistencies on the pixel level that may be resolved statistically when analyzing a larger collection of pixels consisting of a region. For example, some regions of the eye may not be fully red, or display other artefacts such as a glint of high luminance. Other example for the need of a global statistical operation is the presence of noise in the image. Techniques are known in the art for such global comparison.

Based on the information above, the regions finally identified as red-eye artefacts can be modified, 98, to eliminate the red-eye from the original full resolution image $I(x,y)$. The modification can be done using any one of numerous available techniques such as luminance reduction, chrominance reduction, or subtraction of the artefact, as described in US

Published Patent Application 2002/0150306 (Baron), which is hereby incorporated by reference.

FIG. 5-d describes the preparation of regions suspected of red-eye for comparison as described in FIG. 5-a, block 596-4. As discussed above, a simple pixel level comparison may not be enough to determine whether the region is not of red-eye nature. The process of preparation may include a combination of several components such as creating color balance between the regions of the preview image and the final image, 1510, analyzing the texture, or differences in high frequency patterns between the two regions that may have occurred due to the change in resolution, 1520, and comparing the edges between the two regions, 1530, where the differences may have occurred due to change in exposure, color balance, resolution or alignment, and in particular sub pixel alignment. The color balance step 1510 comprises marking each red-eye region in $I'(x,y)$ and the corresponding region in $P''(x,y)$, steps 1512 and 1514, determining the difference in color balance between the region in $I'(x,y)$ surrounding, but not including, the suspected red-eye region and the corresponding region of $P''(x,y)$, step 1516, and transforming the entire region, including the suspected red-eye region, based on the color balance difference so determined, step 1518.

As an alternative embodiment of this invention, the preview image can be used as part of the pixel locator stage 92, as illustrated in FIG. 5-b, rather than as part of the falsing analyzer 96. In FIG. 5-b, blocks 510, 520, 522, 530, 532, 534, 540, 94 and 98 are identical to those in FIG. 5-a. According to this embodiment, the use of the preview image in order to detect red-eye artefacts is implemented as part of the red-eye identification process, otherwise described as the pixel locator 92 in FIG. 1 but here identified as Pixel Analyser and Region Segmenter 592.

After the suspected red-eye regions are identified, the process continues via the shape analysis 94, false detection elimination 96 and correction 98 as described in FIG. 1. In this case, the falsing detector 96 may be performed according to DeLuca.

According to this embodiment, after the alignment step 540 the following steps 592-1a and 592-1b analyse both images $I'(x,y)$ and $P''(x,y)$ for the presence of pixels having a color indicative of red-eye (592-1a), for example in the manner of DeLuca, and then identifies clusters of contiguous red pixels so detected (592-1b). This is known as segmentation and is more fully described in US Pat. Appn. 2002/0176623, which is hereby incorporated by reference.

Now, each region (cluster) with red content in the acquired image $I'(x,y)$, step 592-2, is compared with the corresponding region in the aligned preview image $P''(x,y)$. The regions will need to be prepared, 592-4, as previously described in relation to block 596-4 of FIG. 5-a. If the regions are red in both cases, 592-6=YES, the region will not be marked as red-eye, no action will be taken and the process will continue to the next suspected region, 592-3. If the region is red in the acquired image $I'(x,y)$ while the corresponding region is not red in the preview image $P''(x,y)$, 592-6=NO, then the region will be marked as suspected red-eye, 592-8.

FIG. 6-a shows a modification of the embodiment of FIG. 5-b in which Step 540 (Align Images) has been divided into two steps, Step 541 (If Possible Globally Align Images) and Step 592-3 (If Required Locally Align Images). Step 541 corresponds to Steps 542 and 544 of FIG. 5-c. However, if a global alignment is not possible or practical, the local alignment is deferred until after red pixel identification and clustering has been performed, since the presence of such clusters

in the two images $I(x,y)$ and $P(x,y)$ will assist in the local alignment. FIG. 6-b shows a similar modification applied to FIG. 5-a.

In the embodiments of the invention, in the comparison stages, 592-6 and 596-6 the pixel values do not necessarily have to be compared with red but may alternatively or additionally be compared with other values such as yellow, white, pink, brown or other color indicative of a red-eye phenomenon, or to a range of values, to accommodate other flash related eye artefacts that are not purely red. Due to the fact that the eye surface is retro-reflective (due to the smoothness created by the tears, and the spherical shape of the eyeball), the technique as described in this specification can assist in the detection of the eyes in an image. Such existence of an eye can be found by comparison of the spectral reflection of the flash in the eye with the same region where no flash was used, and thus without spectral reflection. This comparison may assist in locating eyes in general and not just eyes with red-eye artefacts. This process may be implemented by finding the change of small specular reflections that occur in the eye region when flash illumination is used such as described in WO 03/026278 (Jarman). The specular reflections may be used as another indication of suspected regions as defined in blocks 592-2 and 596-2 by comparing the specular reflection of the flash image with no specular reflection of the preview image.

Alternatively to a binary decision of adding or eliminating a region, 596-8 and 596-9, in the case of a continuous probability for each region, the process will be revised from a binary decision to changing a probability decision. The quantitative determination of such change in probability may be decided based on analysis of the confidence level of the comparison 592-4 and 596-4.

The preferred embodiments described above may be modified by adding or changing operations, steps and/or components in many ways to produce advantageous alternative embodiments. For example, the reference image can be a post-view image rather than a preview image, i.e. an image taken without flash immediately after the flash picture is taken.

A red-eye correction procedure may begin as described by block 92 with detecting a human face in a digital image and, based on this detection, finding the eyes in the face (see, e.g., U.S. Pat. No. 6,252,976, U.S. Publ. Pat. App. No. 2003/0044070 and U.S. Pat. No. 6,278,491, which are hereby incorporated by reference). This procedure may also be used for creating the regional alignment 546 and color balance 1510.

A range of alternative techniques may be employed to detect and verify the existence of red-eye defects in an image (see, e.g., U.S. Publ. Pat. Apps. No. 2003/0044177 and 2003/0044178, which are hereby incorporated by reference). These techniques may be incorporated into the pixel locator, shape analyzer, falsing analyzer and pixel modifier corresponding to blocks 92, 94, 96 and 98. A camera may include software or firmware for automatically detecting a red-eye image using a variety of image characteristics such as image brightness, contrast, the presence of human skin and related colors. The analysis of these image characteristics may be utilized, based on certain pre-determined statistical thresholds, to decide if red-eye defects exist and if a flash was used to take the original image.

The preferred embodiments described herein may involve expanded digital acquisition technology that inherently involves digital cameras, but that may be integrated with other devices such as cell-phones equipped with an acquisition component, toy cameras etc. The digital camera or other

image acquisition device of the preferred embodiment has the capability to record not only image data, but also additional data referred to as meta-data. The file header of an image file, such as JPEG, TIFF, JPEG-2000, etc., may include capture information including the preview image, for processing and red-eye detection at a later post processing stage, which may be performed in the acquisition device or in a separate device such as a personal computer. The preferred embodiments described herein serve to improve the detection of red-eyes in images, while eliminating or reducing the occurrence of false positives, and to improve the correction of the detected artefacts.

While an exemplary drawing and specific embodiments of the present invention have been described and illustrated, it is to be understood that the scope of the present invention is not to be limited to the particular embodiments discussed. Thus, the embodiments shall be regarded as illustrative rather than restrictive, and it should be understood that variations may be made in those embodiments by workers skilled in the arts without departing from the scope of the present invention, as set forth in the claims below and structural and functional equivalents thereof.

In addition, in methods that may be performed according to preferred embodiments herein and that may have been described above, the operations have been described in selected typographical sequences. However, the sequences have been selected and so ordered for typographical convenience and are not intended to imply any particular order for performing the operations, unless expressly set forth or understood by those skilled in the art being necessary.

Thus, the preferred embodiments described herein provide an improved method and apparatus for detecting red-eye phenomenon within images taken by a digital camera having a flash while eliminating or reducing the occurrence of false positives by using preview information.

In addition to all of the references cited above that have been incorporated by reference, the sections entitled BACKGROUND, SUMMARY OF THE INVENTION, ABSTRACT and BRIEF DESCRIPTION OF THE DRAWINGS, are hereby incorporated by reference into the DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT.

What is claimed is:

1. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said detection being based upon a comparison of said captured image and at least one reference eye color characteristic,

wherein said at least one reference eye color characteristic comprises an eye color characteristic of a reference image of nominally the same scene taken without flash, and wherein the reference image comprises a preview image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the preview image and sub-sampling the captured image.

2. A system according to claim 1, the filter including further programming code for aligning at least portions of the captured image and reference image prior to said comparison.

3. A system according to claim 2, wherein the filter also includes a shape analyser so that the filter is configured to identify a region in the captured image having both a shape

13

and color indicative of a red-eye phenomenon for subsequent comparison with the corresponding region in the reference image.

4. A system according to claim 2, wherein the filter also includes a shape analyser to determine subsequent to said comparison whether a region designated as indicative of a red-eye phenomenon has a shape indicative of a red-eye phenomenon.

5. A system according to claim 1, wherein said at least one reference eye color characteristic comprises an eye color characteristic of a reference image of nominally the same scene taken without flash, and the filter further including programming code for spatially aligning at least portions of the captured image and reference image prior to said comparison.

6. A system according to claim 5, wherein the filter also includes a shape analyser so that the filter is configured to identify a region in the captured image having both a shape and color indicative of a red-eye phenomenon for subsequent comparison with the corresponding region in the reference image.

7. A system according to claim 5, wherein the filter also includes a shape analyser to determine subsequent to said comparison whether a region designated as indicative of a red-eye phenomenon has a shape indicative of a red-eye phenomenon.

8. A system according to claim 1, wherein the filter detects said region indicative of a red-eye phenomenon by identifying a region in the captured image at least having a color indicative of a red-eye phenomenon and comparing said identified region with the corresponding region in the reference image, the filter further designating said region as indicative of a red-eye phenomenon if said corresponding region does not have a color indicative of a red-eye phenomenon.

9. A system according to claim 8, wherein the decision as to whether a region has a color indicative of a red-eye phenomenon is determined on a statistical basis as a global operation on the entire region.

10. A system according to claim 1, wherein said digital image acquisition system is a camera is a combination of a digital camera and an external processing device.

11. A system as claimed in claim 10, wherein said red-eye filter is located in said external processing device.

12. A system according to claim 1, further including a pixel modifier for modifying the color of the pixels within a region indicative of a red-eye phenomenon.

13. A system according to claim 1, further including a pixel modifier for modifying the color of the pixels within a region indicative of a red-eye phenomenon.

14. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said detection being based upon a comparison of said captured image and at least one reference eye color characteristic,

wherein the filter also includes a shape analyser so that the filter is configured to identify a region in the captured image having both a shape and color indicative of a red-eye phenomenon for subsequent comparison with stored information of characteristics of red eye phenomenon, and

wherein the at least one reference eye color characteristic is determined from a reference image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the

14

captured and reference images by at least one of up-sampling the reference image and sub-sampling the captured image.

15. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said detection being based upon a comparison of said captured image and at least one reference eye color characteristic, wherein the filter also includes a shape analyser to determine subsequent to said comparison whether a region designated as indicative of a red-eye phenomenon has a shape indicative of a red-eye phenomenon, and wherein the at least one reference eye color characteristic is determined from a reference image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the reference image and sub-sampling the captured image.

16. A system according to claim 15, wherein said digital image acquisition system comprises a digital camera.

17. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said detection being based upon a comparison of said captured image and at least one reference eye color characteristic, wherein the filter also includes a shape analyser so that the filter is configured to identify a region in the captured image having both a shape and color indicative of a red-eye phenomenon for subsequent comparison with a reference eye shape characteristic and the reference eye color characteristic, respectively, and

wherein the at least one reference eye color characteristic is determined from a reference image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the reference image and sub-sampling the captured image.

18. A system according to claim 17, further including a pixel modifier for modifying the color of the pixels within a region indicative of a red-eye phenomenon.

19. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting red-eye phenomenon in a captured image based upon a comparison of said captured image and a reference image of nominally the same scene taken without flash, wherein the reference image is a preview image of lower pixel resolution than the captured image, the filter including means for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the preview image and sub-sampling the captured image.

20. A system according to claim 19, the filter further including means for aligning at least portions of the captured image and reference image prior to said comparison.

21. A system according to claim 20, wherein the filter detects said red-eye phenomenon by identifying a region in the captured image having a color indicative of a red-eye phenomenon and comparing said identified region with the corresponding region in the reference image, the filter further designating said region as indicative of a red-eye phenomenon.

15

enon if said corresponding region does not have a color indicative of a red-eye phenomenon.

22. A system according to claim 19, wherein the decision as to whether a region has a color indicative of a red-eye phenomenon is determined on a statistical basis as a global operation on the entire region.

23. A system according to claim 19, wherein the filter detects said red-eye phenomenon by identifying a region in the captured image having a color indicative of a red-eye phenomenon and comparing said identified region with the corresponding region in the reference image, the filter further designating said region as indicative of a red-eye phenomenon if said corresponding region does not have a color indicative of a red-eye phenomenon.

24. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said red eye filter comprising a falsing analyzer for processing the captured image around the region for details indicative of an image of an eye, and wherein the detecting is based upon a comparison of an eye grouping characteristic of said captured image and at least one reference eye grouping characteristic, and wherein the reference eye grouping characteristic is determined from a reference image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the reference image and sub-sampling the captured image.

25. A system according to claim 24, wherein said at least one reference eye grouping characteristic comprises an eye grouping characteristic of a reference image of nominally the same scene taken without flash, and wherein the reference image is a preview image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the preview image and sub-sampling the captured image.

26. A system according to claim 25, the filter including further programming code for aligning at least portions of the captured image and reference image prior to said comparison.

27. A system according to claim 26, wherein the filter also includes a shape analyser so that the filter is configured to identify a region in the captured image having both a shape and grouping indicative of a red-eye phenomenon for subsequent comparison with the corresponding region in the reference image.

28. A system according to claim 26, wherein the filter also includes a shape analyser to determine subsequent to said comparison whether a region designated as indicative of a red-eye phenomenon has a shape indicative of a red-eye phenomenon.

29. A method of detecting a red-eye phenomenon within a digital image acquired by a digital image acquisition device having no photographic film, the device comprising a portable apparatus for capturing digital images, and a flash unit for providing illumination during image capture, the method comprising identifying a region within a captured image indicative of a red-eye phenomenon including comparing

16

said captured image and at least one reference eye grouping characteristic and processing the captured image around the region for details indicative of an image of an eye, and wherein the reference eye grouping characteristic is determined from a reference image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the reference image and sub-sampling the captured image.

30. A method according to claim 29, wherein said at least one reference eye grouping characteristic comprises an eye grouping characteristic of a reference image of nominally the same scene taken without flash, and wherein the reference image is a preview image of lower pixel resolution than the captured image, the method further comprising matching the pixel resolutions of the captured and reference images including up-sampling the preview image or sub-sampling the captured image, or a combination thereof.

31. A method according to claim 30, further comprising aligning at least portions of the captured image and reference image prior to said comparison.

32. A method according to claim 31, further comprising analysing a shape so that the identifying comprises identifying a region in the captured image having both a shape and grouping indicative of a red-eye phenomenon for subsequent comparison with the corresponding region in the reference image.

33. A method according to claim 31, further comprising analysing a shape to determine subsequent to said comparison whether a region designated as indicative of a red-eye phenomenon has a shape indicative of a red-eye phenomenon.

34. A method according to claim 29, further comprising correcting the red eye phenomenon, comprising separating a red pupil color component from an iris color component of a pupil/iris pixel, and modifying the red pupil color component to a black component.

35. A digital image acquisition system having no photographic film, comprising a portable apparatus for capturing digital images, a flash unit for providing illumination during image capture, and a red-eye filter for detecting a region within a captured image indicative of a red-eye phenomenon, said detection being based upon a comparison of said captured image and at least one reference eye color characteristic,

wherein the filter also includes a grouping analyser so that the filter is configured to identify a region in the captured image having both a grouping characteristic and color indicative of a red-eye phenomenon for subsequent comparison with a reference eye grouping characteristic and the reference eye color characteristic, respectively, and

wherein the reference eye grouping or color characteristic, or both, is determined from a reference image of lower pixel resolution than the captured image, the filter including programming code for matching the pixel resolutions of the captured and reference images by at least one of up-sampling the reference image and sub-sampling the captured image.

* * * * *