US010318781B2

(12) **United States Patent**
Prusik et al.

(10) **Patent No.: US 10,318,781 B2**
(45) **Date of Patent: Jun. 11, 2019**

(54) **TWO DIMENSIONAL BARCODE WITH DYNAMIC ENVIRONMENTAL DATA SYSTEM, METHOD, AND APPARATUS**

(71) Applicant: **Temptime Corporation**, Morris Plains, NJ (US)

(72) Inventors: **Thaddeus Prusik**, Stroudsburg, PA (US); **Mohannad Abdo**, Clifton, NJ (US); **Clive Hohberger**, Highland Park, IL (US)

(73) Assignee: **TEMPTIME CORPORATION**, Morris Plains, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 138 days.

(21) Appl. No.: **15/084,987**

(22) Filed: **Mar. 30, 2016**

(65) **Prior Publication Data**

US 2016/0292486 A1 Oct. 6, 2016

Related U.S. Application Data

(60) Provisional application No. 62/140,258, filed on Mar. 30, 2015.

(51) **Int. Cl.**
G06K 7/14 (2006.01)
G06K 19/06 (2006.01)

(52) **U.S. Cl.**
CPC ***G06K 7/1473*** (2013.01); ***G06K 19/06037*** (2013.01); ***G06K 19/06046*** (2013.01)

(58) **Field of Classification Search**
CPC G01D 7/005; G01D 7/00; G06K 19/06028; G06K 19/0614; G06K 19/0615; G06K 7/1473; G06K 19/06046; G06K 19/06037
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,646,066 A 2/1987 Baughman et al.
4,729,671 A 3/1988 Asano et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101769884 7/2010
CN 103543146 1/2014
(Continued)

OTHER PUBLICATIONS

Search Report and Written Opinion dated Aug. 5, 2016 issued for International PCT Application No. PCT/US16/24884 filed: Mar. 30, 2016.
(Continued)

Primary Examiner — Sonji N Johnson
(74) *Attorney, Agent, or Firm* — K&L Gates LLP

(57) **ABSTRACT**

Methods, systems, and apparatus for combining preprinted information together with coded sensor information within a two-dimensional barcode. The sensor information may be of an environmental, physical or biological nature, and records a change in status of the environmental or biological condition to which the labeled product has been exposed. A sensor dye chemistry is employed and when a specified condition of the sensed property occurs it causes a change in the color state of sensor dye modules embedded within the sensor-augmented two-dimensional barcode, encoding sensor digital information. Sensor information is recovered utilizing the error-correction feature during barcode reading.

23 Claims, 26 Drawing Sheets



Abbott Laboratories
Exhibit 1022
Page 001

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,935,206	A	6/1990	Heim	
5,053,339	A	10/1991	Patel	
5,109,864	A	5/1992	Lu	
6,642,016	B1	11/2003	Sjoholm et al.	
6,685,094	B2	2/2004	Cameron	
7,209,042	B2	4/2007	Martin et al.	
7,490,575	B2	2/2009	Taylor et al.	
7,604,398	B1	10/2009	Akers et al.	
7,691,634	B2	4/2010	Vaillant	
7,719,404	B2	5/2010	Makela et al.	
7,878,410	B2	2/2011	Norrby et al.	
8,267,576	B2	9/2012	Haarer et al.	
8,395,521	B2	3/2013	Kauffman et al.	
8,579,193	B2	11/2013	Nemet et al.	
8,629,081	B2	1/2014	Azizian	
8,757,503	B2	6/2014	Conzelmann	
8,870,082	B2	10/2014	Cattaneo et al.	
8,899,829	B1	12/2014	Butera et al.	
8,957,780	B2	2/2015	Cooperman	
8,968,662	B2	3/2015	Haarer et al.	
9,011,794	B2	4/2015	Haarer et al.	
9,606,140	B2 *	3/2017	Burghardt	G01P 15/02
2004/0092023	A1	5/2004	Wright	
2004/0212509	A1	10/2004	Zweig	
2006/0083657	A1	4/2006	McDonnell et al.	
2006/0227669	A1	10/2006	Pennaz et al.	
2007/0058493	A1	3/2007	Kuczynski et al.	
2008/0063575	A1	3/2008	Rakow et al.	
2008/0173712	A1	7/2008	Nemet et al.	
2008/0232427	A1	9/2008	Leute et al.	
2009/0010304	A1	1/2009	Skinner et al.	
2011/0084128	A1	4/2011	Haarer et al.	
2011/0258130	A1	10/2011	Grabiner et al.	
2011/0312096	A1	12/2011	Whitman et al.	
2012/0079981	A1	4/2012	Huffman et al.	
2012/0172825	A1	7/2012	Ales et al.	
2012/0175412	A1	7/2012	Grabiner et al.	
2012/0286028	A1	11/2012	Simske et al.	
2012/0326878	A1	12/2012	Viguie et al.	
2013/0015236	A1	1/2013	Porter	
2013/0215004	A1	8/2013	Nordlinder	
2013/0224875	A1	8/2013	Haarer et al.	
2014/0009605	A1	1/2014	Lane	
2014/0023264	A1	1/2014	Branch et al.	
2014/0127738	A1	5/2014	Lee et al.	
2014/0154808	A1	6/2014	Patel	
2014/0252096	A1	9/2014	Nemet	
2014/0334723	A1	11/2014	Chatow et al.	
2014/0339312	A1	11/2014	Simske	
2015/0116093	A1	4/2015	Swager et al.	
2015/0193677	A1 *	7/2015	Nemet	G06Q 30/06 235/376
2015/0332135	A1 *	11/2015	Dixit	G06F 21/36 235/469
2016/0292486	A1	10/2016	Prusik et al.	

FOREIGN PATENT DOCUMENTS

CN	104250715	12/2014
CN	204155296	2/2015
DE	19912529	9/2000
DE	10325714	10/2004
DE	202005006301	6/2005
DE	102006004974	8/2007
EP	1319928	6/2003
EP	1645856	4/2006
FI	200300299	2/2003
IN	1280/CHENP/2004	5/2006
JP	2007285838	11/2007
JP	2013122341	6/2013
JP	5723474	5/2015
KR	101519317	5/2015
WO	WO200550192	4/2006
WO	WO200756752	5/2007
WO	WO200806154	1/2008
WO	WO200961831	5/2009
WO	WO201061134	6/2010
WO	WO201078422	7/2010
WO	WO201085755	7/2010
WO	WO201302552	1/2013
WO	WO201390407	6/2013
WO	WO2014102556	7/2014
WO	WO2014153476	9/2014
WO	WO2015113086	8/2015

OTHER PUBLICATIONS

Windl, et al., "Reactivable passive radio-frequency identification temperature indicator" J. Appl. Phys. 117, 17C125 (2015).

R. E. Blahut, "Theory and Practice of Error Control Codes (corr. Edition)", 1983, p. 166.

S.A. Vanstone et al, "An Introduction to Error Correcting Codes with Applications", 1989, p. 219.

FreshCode TTI Labels—Varcode.

GSI General Specifications, V15, Issue 2, Jan. 2015, http://www.gs1.org/docs/barcodes/GS1_General_Specifications.pdf.

Tanguy, et al., "Enhanced Radio Frequency Biosensor for Food Quality Detection Using Functionalized Carbon . . . ", ACS Appl. Mater. Interfaces, 2015, 7 (22), pp. 11939-11947.

Wu, et al., "3D-printed microelectronics for integrated circuitry and passive wireless sensors", Microsystems & Nanoengineering 1, Article number: 15013 (2015).

Yang, "3D-printed 'smart cap' uses electronics to sense spoiled food", Jul. 20, 2015, UC Berkeley, http://news.berkeley.edu/2015/07/20/3d-printed-electronic-smart-cap/.

Wan, A new type of TTI based on an electrochemical pseudo transistor, Journal of Food Engineering, vol. 168, Jan. 2016, pp. 79-83.

News: New 3D technique . . . Aug. 15, 2015,AIPIA Active & Intelligent Packaging Industry Assoc., http://www.aipia.info/news-New-3D-technique-Prints-Embedded-Smart-Cap--Sensor-444.php.

http://www.businesswire.com/news/home/20151013005396/en/3615067/Palladio-Group-Ink-Introduce-PhutureMed%E2%84%A2-Advanced-Packaging.

Search Report and Written Opinion dated Jul. 26, 2018 issued for International PCT Application No. PCT/US18/23068.

* cited by examiner


100
barcode data
encoded data 104
reference data 106

FIG. 1A


104
encoded data
content data 108
format and version data 110

FIG. 1B



FIG. 1C



FIG. 1D



FIG. 1E



FIG. 2B



FIG. 2D



FIG. 2A



FIG. 2C



FIG. 3B



FIG. 3D



FIG. 3A



FIG. 3C


Start
400
Determine a set of payload data
402
Generate a 2D barcode
404
Designate a part of the redundant space as a dynamic region
406
Print 2D barcode using a static ink and an encoded version of the dynamic data on the dynamic region using dynamic ink
408

FIG. 4


500
PRINT 2D BARCODE
502
504
198
120, 192
198
EXPOSE TO AN ENVIRONMENTAL CHANGE
506
508
198
120, 192
198

FIG. 5


210
136
<
SN. 498760003 BN. 654 LN. 35A1
Threshold temp – 30 degrees °C
134
212
136
>
SN. 498760003 BN. 654 LN. 35A1
Threshold temp – 30 degrees °C
134

FIG. 6A


binary (8-bit) dynamic region
7
6 5
4 3
2 1
0
binary representation of
136
<
00111110
0
1 1
1 1
1 0
0
binary representation of
136
<
00111100
0
0 1
1 1
1 0
0

FIG. 6B


210
136
136
212
State 1
barcode exposed to a
temperature < 30 °C
State 2
barcode exposed to a
temperature > 30 °C

FIG. 6C


210
136
136
212
State 1
barcode exposed to a
temperature of > 0 °C
State 2
barcode exposed to a
temperature of < 0 °C

FIG. 6D


Start
420
Determine a set of static data
422
Determine a set of dynamic data
424
Generate a first 2D barcode
426
Generate a second 2D barcode
428
Compare the first 2D barcode with the second 2D barcode
430
Categorize the information modules
432
Print the 2D barcode using a static ink and a dynamic ink
434

FIG. 7


222
198
224
198
226
224
194
226
234
194
198
232
232
218
230
198
216
234
218
220

FIG. 8


Start
440
Determine a set of static data
442
Determine a set of dynamic data
444
Generate a first 2D barcode
446
Generate a second 2D barcode
448
Compare the first 2D barcode with the second 2D barcode
450
Categorize the information modules
452
Print the 2D barcode using a static ink, a first dynamic ink, and a second dynamic ink
454

FIG. 9



FIG. 10A



FIG. 10B



FIG. 10C


Start
460
Determine a set of payload data
462
Generate a 2D barcode including an encoded version of the set of static data, an encoded version of the set of dynamic data, and error detection and correction data
464
Print 2D barcode using a static ink and an encoded version of the dynamic data on the dynamic region using dynamic ink
466

FIG. 11


Start
470
Read a set of static data included in the 2D barcode
472
Read a set of dynamic data included in the 2D barcode
474
Generate a first output of the static data
476
Generate a second output of the set of dynamic data
478

FIG. 12


Start
490
Read a set of static data included in the 2D barcode
492
Read a set of dynamic data included in the 2D barcode
494
Generate an output based on the set of static data and the set of dynamic data
496

FIG. 13



FIG. 14



FIG. 15A



FIG. 15B



FIG. 16



FIG. 17


300
310

FIG. 18


405
410
Row
1
2
3
4
5
6
7
8
Col
1
2
3
4
5
6
...
2.1 2.2 3.6 3.7 3.8 4.3 4.4 4.5
2.3 2.4 2.5 5.1 5.2 4.6 4.7 4.8
2.6 2.7 2.8 5.3 5.4 5.5
6.1 6.2 5.6 5.7 5.8
6.3 6.4 6.5
6.6 6.7 6.8

FIG. 19



FIG. 20


600
630a
650
640a
620
660
610a
670a
610b
670b
630b
640b
2.1 2.2 3.6 3.7 B15 4.3 4.4 4.5 13.1
2.3 2.4 2.5 3.1 B14 4.6 4.7 4.8 13.3
2.6 2.7 2.8 B13 B12 B11 12.1 12.2 13.6
1.5 B7 B10 B9 B8 12.3 14.6 14.7 14.8
1.8 B6 B5 B4 8.1 8.2 12.6 15.5 1.1 1.2
7.2 B3 B2 B1 8.3 15.8 1.3 1.4
7.4 7.5 10.1 10.2 8.6 22.2 1.6 1.7
7.7 7.8 10.3 22.4 22.5 7.1
9.1 9.2 10.6 22.8 7.3
23.2 7.6
23.4 23.5
18.6 18.7 18.8 20.3
19.5 3.1 3.2 20.6 20.7 20.8 24.3
19.8 3.3 3.4 3.5 4.1 4.2 24.6

FIG. 21


700

FIG. 22


800
2.1 2.2 3.6 3.7 B15 4.3 4.4 4.5 13.1
2.3 2.4 2.5 5.1 B14 4.6 4.7 4.8 13.3
2.6 2.7 2.8 B13 B12 B11 12.1 12.2 13.6
1.5 6.1 B7 B10 B9 B8 12.3 14.6 14.7 14.8
1.8 B6 B5 B4 8.1 8.2 12.6 15.5 1.1 1.2
7.2 B3 B2 B1 8.3 15.8 1.3 1.4
7.4 7.5 10.1 10.2 8.6 22.2 1.6 1.7
7.7 7.8 10.3 22.4 22.5 7.1
9.1 9.2 10.6 22.8 7.3
23.2 7.6
23.4 23.5
18.6 18.7 18.8 20.3
19.5 3.1 3.2 20.6 20.7 20.8 24.3
19.8 3.3 3.4 3.5 4.1 4.2 24.6

FIG. 23



FIG. 24



FIG. 25


1100
2.1 2.2 3.6 3.7 B15 4.3 4.4 4.5 13.1
2.3 2.4 2.5 5.1 B14 4.6 4.7 4.8 13.3
2.6 2.7 2.8 B13 B12 B11 12.1 12.2 13.6
1.5 6.1 B7 B10 B9 B8 12.3 14.6 14.7 14.8
1.8 B6 B5 B4 8.1 8.2 12.6 15.5 1.1 1.2
7.2 B3 B2 B1 8.3 15.8 1.3 1.4
7.4 7.5 10.1 10.2 8.6 22.2 1.6 1.7
7.7 7.8 10.3 22.4 22.5 7.1
9.1 9.2 10.6 22.6 7.3
23.2 7.6
23.4 23.5
18.6 18.7 18.8 20.3
19.5 3.1 3.2 20.6 20.7 20.8 24.3
19.8 3.3 3.4 3.5 4.1 4.2 24.6

FIG. 26


1200
1210
1220

FIG. 27


1300
1310
2.1 2.2 3.6 3.7 3.8 4.3 4.4 4.5 13.1
2.3 2.4 2.5 5.1 5.2 4.6 4.7 4.8 13.3
2.6 2.7 2.8 5.3 5.4 5.5 12.1 12.2 13.6
1.5 6.1 6.2 5.6 5.7 5.8 12.3 14.6 14.7 14.8
1.8 6.3 6.4 6.5 6.1 6.2 12.6 15.5 1.1 1.2
7.2 6.6 6.7 6.8 8.3 15.8 1.3 1.4
7.4 7.5 10.1 10.2 8.6 22.2 1.6 1.7
7.7 7.8 10.3 22.4 22.5 7.1
9.1 9.2 10.6 22.8 7.3
23.2 7.6
23.4 23.5
18.6 18.7 18.8 20.3
19.5 3.1 3.2 20.6 20.7 20.8 24.3
19.8 3.3 3.4 3.5 4.1 4.2 24.6

FIG. 28


1400

FIG. 29



FIG. 30



FIG. 31

TWO DIMENSIONAL BARCODE WITH DYNAMIC ENVIRONMENTAL DATA SYSTEM, METHOD, AND APPARATUS

PRIORITY CLAIM

This application claims the benefit of U.S. provisional patent application No. 62/140,258 filed on Mar. 30, 2015, the entire disclosure of which is incorporated by reference herein for all purposes.

BACKGROUND

A barcode is an optical machine-readable representation of data. A two dimensional (2D) barcode (e.g., Data Matrix or QR Code), is a two dimensional way to represent information in a bar code. The 2D barcodes can represent more data per unit area than a one dimensional barcode. Bar codes have many uses, including documenting inventory, tracking deliveries, matching a product against a pricing file, and providing information to the user. For some systems, data recovery from barcodes may be system critical. Many barcode technologies provide robust error correction capabilities, and typically, using duplicate barcodes or larger sized barcodes may increase data recovery capabilities. However, space available for barcodes may be limited in many aspects. Moreover, the current barcode technology may be improved upon as presently disclosed.

SUMMARY

The present disclosure provides a new and innovative system, methods and apparatus for providing and reading 2D barcodes that include dynamic environmental data, where modules of the barcode may change state in response to environmental conditions. In an exemplary aspect of the present disclosure, a sensor-augmented two-dimensional barcode includes a substrate; a two-dimensional error-correcting barcode symbol provided on the substrate; a first layer provided on the substrate in a permanent color state; and a second layer provided on the substrate. The bar code symbol further includes a plurality of modules, the modules optionally being square, rectangular, or circulate, each module having one of a first color state or a second color state. The second layer is optionally provided by overprinting the first layer, in a sensor dye module pattern, the sensor dye module pattern containing sensor digital information. The second layer further includes a sensor dye having a chemistry that is configured, responsive to the occurrence of an environmental, physical or biological condition, to undergo a chemical or physical state change causing a change in the color state of the sensor dye, thereby changing the color state of a subset of the plurality of modules.

In accordance with another exemplary aspect of the present disclosure, an article of manufacture includes pharmaceutical, biological, or food product, preferably a vaccine; a container holding the pharmaceutical, biological, or food product, preferably a vaccine vial; and a sensor-augmented two-dimensional barcode symbol provided on or in the container, preferably being applied to the outside surface of the container.

In accordance with another exemplary aspect of the present disclosure, a method of reading of a sensor-augmented two-dimensional barcode symbol includes scanning and optically processing an image of the sensor-augmented two-dimensional barcode symbol, including construction of a scan binary bitmap from scanned modules of the sensor-augmented two-dimensional barcode symbol. The method further includes constructing a symbol codeword sequence from the scan binary bitmap. Then, underlying data codewords are recovered from the symbol codeword sequence, preferably by utilizing error correction process on the symbol codeword sequence, the error correction process preferably being a Reed-Solomon code. Next, the underlying data codewords are processed to form the underlying symbol codeword sequence. The method further includes constructing an underlying binary bitmap from the scan binary bitmap from the underlying symbol codeword sequence, the underlying binary bitmap preferably equal in size to the scan binary bitmap. At each bit position an exclusive-OR of the scan binary bitmap and the underlying binary bitmap may be performed to form a sensor digital information bitmap. Optionally, the method includes, processing the sensor digital information bitmap to recover a binary information sequence that incorporates binary encoded sensor data, preferably by processing the binary information sequence as an error-correcting code sequence and utilizing an error correction process to recover binary-encoded sensor data. The error-correcting code preferably is selected from the group consisting of Hamming Codes, Bose-Chaudhuri-Hocquenghem Codes, Golay Codes, Simplex Codes, Reed-Muller Codes, Fire Codes, Convolutional Codes, and Reed-Solomon Codes.

In accordance with another exemplary aspect of the present disclosure, a method of generating a 2D barcode, includes determining a set of payload data including a set of static data and a set of dynamic data, generating a 2D barcode which includes an encoded version of the set of static data and includes redundant space, designating at least part of the redundant space as a dynamic region which is adapted to store the set of dynamic data, and printing the 2D barcode using a static ink and an encoded version of the set of the dynamic data on the dynamic region using a dynamic ink which changes states responsive to at least one environmental change, such that the set of dynamic data is in one of a plurality of states. The set of dynamic data is readable by a reader of the 2D barcode and the set of static data is readable by the reader of the 2D barcode when the set of dynamic data is in each one of the plurality of possible states.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, a method of providing a 2D barcode, includes determining a set of static data, determining a set of dynamic data, generating a first 2D barcode, generating a second 2D barcode, comparing the first 2D barcode and the second 2D barcode and categorizing the information modules into a first group and a second group, and printing the 2D barcode in static ink and dynamic ink. The set of dynamic data has a first state and a second state. The first 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the first state. The set of static data and the set of dynamic data in the first state include a first plurality of information modules and a second plurality of information modules. The second 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the second state. The set of static data and the set of dynamic data in the second state include a third plurality of information modules and a fourth plurality of information modules. The third plurality of information modules includes all of the first plurality of information modules plus a set of one or more information modules. The second plurality of information modules includes all of the fourth plurality of information modules

plus the set of one or more information modules. The first group includes common information modules between the first plurality of information modules of the first 2D barcode and the third plurality of information modules of the second 2D barcode. The second group includes unique information modules of the third plurality of information modules of the second 2D barcode. The first group is printed in the static ink, and the second group is printed in the dynamic ink. The dynamic ink is adapted to activate in response to the occurrence of a specific environmental factor.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, a method of providing a 2D barcode, includes determining a set of static data, determining a set of dynamic data, generating a first 2D barcode, generating a second 2D barcode, comparing the first 2D barcode and the second 2D barcode and categorizing the information modules into a first group, a second group, and a third group, and printing the 2D barcode using a static ink, a first dynamic ink, and a second dynamic ink. The set of dynamic data has a first state and a second state. The first 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the first state. The set of static data and the set of dynamic data in the first state include a first plurality of information modules and a second plurality of information modules. The second 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the second state. The set of static data and the set of dynamic data in the second state include a third plurality of information modules and a fourth plurality of information modules. The first group includes common information modules between the first plurality of information modules of the first 2D barcode and the third plurality of information modules of the second 2D barcode. The second group includes unique information modules of the third plurality of information modules of the second 2D barcode, and the third group includes unique information modules of the first plurality of information modules of the first 2D barcode. The first group is printed in the static ink, the second group is printed in a first dynamic ink, and the third group is printed in a second dynamic ink. The first dynamic ink is adapted to deactivate in response to the occurrence of a specific environmental factor, and the second dynamic ink is adapted to activate in response to the occurrence of the specific environmental factor.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, a method of providing a 2D barcode, includes determining a set of payload data including a set of static data and a set of dynamic data having a first state and a second state, generating a 2D barcode which includes an encoded version of the set of static data, a dynamic region which is adapted to store the set of dynamic data, and error detection and correction data, and printing the 2D barcode using a static ink and an encoded set of the dynamic data on the dynamic region using a dynamic ink which changes states responsive to at least one environmental change, such that the set of dynamic data is in the first state or the second state, and the error detection and correction data accommodates for changes in the set of dynamic data in the dynamic region such that the 2D barcode is readable by a reader and produces a first output when the set of dynamic data is in the first state and the 2D barcode is readable by a reader and produces a second output when the set of dynamic data is in the second state.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, a method of reading a 2D barcode includes scanning a set of static data included in the 2D barcode, scanning a set of dynamic data included in the 2D barcode, generating a first output of the set of static data, and generating a second output of the set of dynamic data. The 2D barcode is printed in static ink and dynamic ink, and an encoded version of the set of static data is printed in the static ink. An encoded version of the set of dynamic data is printed in the dynamic ink which changes states responsive to at least one environmental change, such that the dynamic data is in one of the plurality of states. The set of dynamic data is printed in a redundant space on the 2D barcode. The second output indicates on which state of the plurality of states the dynamic data is in.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, a method of reading a two dimensional (2D) includes scanning a set of static data included in the 2D barcode, scanning a set of dynamic data included in the 2D barcode, and generating an output based on the set of static data and the set of dynamic data. The 2D barcode includes static ink and dynamic ink. An encoded version of the set of static data is printed in the static ink. An encoded version of the set of dynamic data is printed in the dynamic ink, which changes states responsive to at least one environmental change, such that the dynamic data is in one of a plurality of states. The set of dynamic data is printed in the dynamic region. The output is a first output when the set of dynamic data is in a first state of the plurality of states, and the output is a second output when the set of dynamic data is in a second state of the plurality of states.

Additional features and advantages of the disclosed system, method, and apparatus are described in, and will be apparent from, the following Detailed Description and the Figures.

BRIEF DESCRIPTION OF THE FIGURES

FIG. **1**A is a block diagram of an example data structure of barcode data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **1**B is a block diagram of an example data structure of the encoded data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **1**C is a block diagram of an example data structure of the content data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **1**D is a block diagram of an example data structure of the reference data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **1**E is a block diagram of an example data structure of the payload data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **2**A is an example 2D barcode, according to an example embodiment of the present disclosure.

FIG. **2**B is an example of the reference data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **2**C is an example 2D barcode, according to an example embodiment of the present disclosure.

FIG. **2**D is an example of the reference data of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **3**A is a representation of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **3**B is a representation of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **3**C is a representation of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **3**D is a representation of a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **4** includes a flowchart illustrating an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **5** is a flow diagram illustrating a 2D barcode printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **6**A is a textual representation of a set of static data and a set of dynamic data, according to an example embodiment of the present disclosure.

FIG. **6**B is an example of textual dynamic data encoded as binary information modules, according to an example embodiment of the present disclosure.

FIG. **6**C is a flow chart diagram illustrating a 2D barcode printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **6**D is a flow chart diagram illustrating a 2D barcode printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **7** includes a flowchart illustrating an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **8** is a flow diagram illustrating a portion of 2D barcode printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **9** includes a flowchart illustrating an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **10**A is a block diagram of an example set of information modules printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **10**B is a block diagram of an example set of information modules printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **10**C is a block diagram of an example set of information modules printed using an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **11** includes a flowchart illustrating an example process for providing a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **12** includes a flowchart illustrating an example process for reading a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **13** includes a flowchart illustrating an example process for reading a 2D barcode, according to an example embodiment of the present disclosure.

FIG. **14** is a block diagram of a 2D barcode providing system, according to an example embodiment of the present disclosure.

FIG. **15**A is a block diagram of a 2D barcode reading system, according to an example embodiment of the present disclosure.

FIG. **15**B is a block diagram of a 2D barcode reading system, according to an example embodiment of the present disclosure.

FIG. **16** is a block diagram of a 14×14 Data Matrix symbol encoding the data "1234567890", according to an example embodiment of the present disclosure.

FIG. **17** is an illustration of Codeword and utah placement and bitmap matrix for a 14×14 Data matrix symbol, according to an example embodiment of the present disclosure.

FIG. **18** is a Schematic of the general codeword placement within a 10×10 Data Matrix bitmap, according to an example embodiment of the present disclosure.

FIG. **19** is a block diagram of Invariant utah placement in all practical sizes of Data Matrix symbols, according to an example embodiment of the present disclosure.

FIG. **20** is a representation of a 14×14 bitmap and utah placement within a 16×16 Data Matrix symbol, according to an example embodiment of the present disclosure.

FIG. **21** is a representation of Utahs used in the GS1 AI (90) string and placement of the 15 BCH(15,5,7) encoding bits, according to an example embodiment of the present disclosure.

FIG. **22** is a block diagram of a 16×16 Data Matrix using W→X sensor dye chemistry and encoding the GS1 AI (90) string, according to an example embodiment of the present disclosure.

FIG. **23** is a Detail of utahs **1**-**7** in FIG. **7**, according to an example embodiment of the present disclosure.

FIG. **24** is a block diagram of the 16×16 Data Matrix of FIG. **7** with unactivated, overprinted sensor dye modules, according to an example embodiment of the present disclosure.

FIG. **25** is a block diagram of a 16×16 Data Matrix using X→B sensor dye chemistry and encoding the GS1 AI (90) string, according to an example embodiment of the present disclosure.

FIG. **26** is a Detail of utahs **1**-**7** in FIG. **25**, according to an example embodiment of the present disclosure.

FIG. **27** is a block diagram of the 16×16 Data Matrix of FIG. **25** with unactivated, overprinted sensor dye modules, according to an example embodiment of the present disclosure.

FIG. **28** is a Detail of a 16×16 Data Matrix encoding the data of Table 8 showing a 4×4 frame area, according to an example embodiment of the present disclosure.

FIG. **29** is a block diagram of an Underlying 16×16 Data Matrix encoded using the data on Table 8, according to an example embodiment of the present disclosure.

FIG. **30** is a block diagram of the 16×16 Data Matrix of FIG. **29** with an overprinted 4×4 white frame, according to an example embodiment of the present disclosure.

FIG. **31** is a block diagram of the 16×16 Data Matrix of FIG. **30** showing an overprinted and activated sensor dye patch, according to an example embodiment of the present disclosure.

DETAILED DESCRIPTION OF EXAMPLE EMBODIMENTS

Prior approaches have been with one-dimensional (linear or 1D) barcodes that either become unreadable or change with stimuli. Noteworthy, are the FreshCode smart barcode labels supplied by Varcode Ltd. See: http://www.varcode.com/portfolio_item/freshcode/).

There have been a plurality of 1D barcode patent applications including Nemet et al., US20140252096 A1. While combining environmental measurements into data value of 1D barcodes has been generally described, the techniques

applicable to 1D barcodes do not appear to be applicable to two-dimensional (2D) barcodes with environmental monitoring.

The area taken by 1D barcodes limit their practicality in applications were space is critical, e.g., unit of use applications, vials, etc. Two-dimensional barcodes with high density encoding technologies, for example Data Matrix, could have an encoded area approximately 30 times or more smaller in practice than a 1D barcode representing the same data.

Prior applications involving 2D barcodes have not addressed environmental monitoring and focus on high density of information stored that is static and not sensitive to environmental factors such as temperature, time, time-temperature product, freezing, nuclear radiation, toxic chemicals, or the like.

Some solutions have addressed having two sets of data, primary/secondary or covert/overt data, whereby the second set of information is stored into the redundant space of the barcode and can be read with a conventional reader or independently using a second reader or other decrypting methods. While these solutions including the secondary/covert data have addressed matters such as security and authenticity, none have addressed environmental monitoring where data is dynamic. A pending US Patent Application by Porter et al. US 20130015236 A1 High-value document authentication system and method and references contained therein describe primary and secondary information sets and the application to document authentication.

Other solutions have addressed multiple sets of data, primary/secondary/tertiary etc., whereby different data sets (secondary, tertiary, etc.) are progressively stored over the prior set. Multiple information sets are incrementally added, for example, by printing over the prior set with different color modules and then decrypting the data utilizing readers configured to interpret various color modules. See for example Simske et al., US20140339312 A1. These solutions are progressively introducing static data one layer at a time and address matters pertaining to tracking, tracing, inspection, quality assurance and not dynamic environmental data.

Some example embodiments described in this disclosure provide a unique way of combining preprinted data together with coded sensor information in a two-dimensional barcode on a media. The preprinted data and coded sensor information may be combined in a single step, or the coded sensor information may be added dynamically to the preprinted data in a secondary step depending on the actual planned sensor usage.

A sensor dye chemistry may be employed where the sensed property is an environmental, physical, or biological property. A specified condition of the sensed property causes activation of a chemical or physical state change resulting in a change in the color state of the sensor dye. The change in the color state results in sensor digital information being revealed in the pattern of sensor dye modules within the sensor-augmented two-dimensional barcode. Sensor digital information is recovered when the barcode is read using an extension of the standard reading and error correction algorithms for the two-dimensional barcode symbology in use.

Examples of environmental sensors include temperature monitors, measuring either cumulative heat exposure or passing beyond a set high or low temperature threshold value(s); time, time-temperature product, nuclear radiation exposure monitors; gas or humidity exposure monitors each passing above a cumulative exposure threshold or an instantaneous threshold value. Examples of medical sensors include recording patient thermometers; threshold assays measuring levels to biological toxins such as aflatoxin or botulism toxin; and includes colorimetric immunoassays for sensing of the presence of biological agents such as prions or biological organisms such as infectious bacteria.

Block diagrams of an example data structure **100** of a two dimensional (2D) barcode, an example data structure of the encoded data of a 2D barcode, an example data structure of the content data of a 2D barcode, and an example data structure of the reference data of a 2D barcode are shown in FIG. **1**A, FIG. **1**B, FIG. **1**C, and FIG. **1**D respectively. The 2D barcode includes encoded data **104** and reference data **106**. The encoded data **104** may include content data **108** and format and version data **110**. The content data **108** may include payload data **112**, padding data **114**, error detection and correction data **116**, and remainder space **118**. The format and version data **110** provides information needed to decode the content data **108**. For example, the format and version data **110** may include mask information. The reference data **106** is the data required to identify which protocol is being used and allows a reader to locate and scan the 2D barcode. The reference data **106** may include alignment data **124**, finder data **126**, timing data **128**, positioning data **130**, and orientation data **132**. The payload data may include static data **134** and dynamic data **136**. For example, as illustrated in FIGS. **2**A, **2**B, **2**C, and **2**D discussed in further detail below, the positioning data **130** may include a position block **138** or positioning modules, and the finder data **126** may include a finder pattern **142** or finder modules. Additionally, the alignment data **124** may include an alignment block **146**. The timing data **128** may include a timing pattern **148**. The reference data **106** may also include separators, identification modules, and orientation modules.

Example 2D barcodes are shown in FIG. **2**A and FIG. **2**C and their respective reference data **106** and format and version data **110** are shown in FIG. **2**B and FIG. **2**D. FIG. **2**A includes all the encoded data **104** and reference data **106** for a 2D barcode **156** (e.g., Data Matrix). FIG. **2**B shows only the reference data **106** for a 2D barcode **156**. For example, the reference data **106**, which includes the finder pattern **142** and the timing pattern **148**, encloses the content data **108** of the 2D barcode **156**. FIG. **2**C includes all the encoded data **104** and reference data **106** for a 2D barcode **158** (e.g., QR code). FIG. **2**D shows only the reference data **106** for a 2D barcode **158**. For example, the reference data **106** may include the position blocks **138**, the alignment block **146**, and the timing patterns **148**.

A representation of a 2D barcode **156** is shown in FIG. **3**A and FIG. **3**B. A representation of a 2D barcode **158** is shown in FIG. **3**C and FIG. **3**D. The representation of each 2D barcode shows the reference data region **160** and the encoded data region **162**. The encoded data region **162** may include static data **134**, dynamic data **136**, and error detection and correction data **116**. Also, the 2D barcode **156** may include a plurality of unused bits which may not be used for encoded data **104** or providing reference data **106**. The 2D barcode **158** may include remainder space **118** which may include a plurality of unused bits.

Some examples described herein employ Data Matrix, although it will be appreciated that similar approaches may be employed with other two dimensional bar codes schemes by varying the approach to conform with the applicable 2D barcode standard. Data Matrix is a two-dimensional error-correcting barcode symbol formed in compliance with ISO/IEC 16022 Information technology—automatic identification and data capture techniques—Data Matrix barcode symbology specification. The ECC **200** Data Matrix symbology utilizes Reed-Solomon error correction to recover

the encoded data from symbols which have suffered a limited amount of accidental damage or deliberate alternation. All Data Matrix referred to herein are of the ECC **200** symbol type, and may be either square or rectangular in shape, and are identified by the number of rows and columns respectively.

Data is encoded in a Data Matrix as a sequence of 8-bit codewords, or symbol character values. Codewords may either contain data or Reed-Solomon error correction (RSEC) check character values. It will be appreciated that the general approach described herein may use other codeword sizes, other data layouts, and other forms of error correcting codes, and that this common Data Matrix is only described as an example.

Each module is a visual cell in matrix comprising the Data Matrix symbol that is used to encode one bit of data. Each module is colored either nominally black or nominally white. The module matrix is the visual manifestation of the binary bitmap matrix contained with the area of the symbol bounded by the Finder Pattern. The Finder Pattern may be an 'L' formed by connected solid lines along two edges of the symbol module matrix, with an alternating pattern of white and black modules along the opposite edges of the symbol. See FIG. **16**. It will be appreciated that in other bar code symbologies, other finder patterns may be employed.

FIG. **16** illustrates a 14×14 square Data Matrix **320** encoding the data "1234567890". This Data Matrix has two parts: the Finder Pattern forming an 'L' formed by connected solid lines **312***a* and **312***b* along two edges of the symbol with an alternating pattern of white and black modules **322***a* and **322***b* along the opposite edges of the symbol. Symbol codewords are encoded in the 12×12 module matrix **330** interior to the Finder Pattern.

The detailed structure of the 12×12 module matrix **330** of the 14×14 Data Matrix **320** is shown as the bitmap matrix **200** in FIG. **17**. A 14×14 Data Matrix contains 18 codewords, each formed of eight modules corresponding to the eight bits of the codeword, referred to as a "utah." The 12×12 bitmap matrix shows the layout of all the 18 codewords in a 14×14 Data Matrix.

A "utah" is an arrangement of 8 modules to encode 1 codeword. It may be arranged either as a single connected group with a pattern frequently in the shape of the State of Utah, or formed as two subgroups of connected modules split across two patterns. The contiguous utah **270** encoding codeword **9** shows the typical arrangement of bits within a contiguous utah. Conversely, the utah for codeword **4** consists of two smaller subgroups: Subgroup **272***a* at the top of the bitmap matrix **200** encoding bits **4.3** through **4.8**, and subgroup **272***b* at the bottom of the bitmap matrix encoding bits **4.1** and **4.2**.

The general layout of codeword utah placement within a 10×10 Data Matrix bitmap matrix **300** is shown in FIG. **18**. Trace lines **310** shows the overall method for placing codeword utahs within a bitmap matrix. Note in comparing FIG. **17** and FIG. **18** that the placement of:

All bits of utah **2**

Utah **3** bits **3.6-3.8**

Utah **4** bits **4.3-4.8**

All bits of utahs **5** and **6**

These bit positions in identical positions relative to the upper left-hand corner (ULC) of the Data Matrix symbol. In accordance with ISO/IEC 16022 standard Annex F.3, all square Data Matrix symbols up to size 26×26 and all rectangular Data Matrix symbols, these bit positions are invariant in their placement relative to the ULC of each Data Matrix symbol. These bit positions define an "invariant bitmap" for Data Matrix symbols. It will be appreciated that other barcode standards may have different invariant bitmaps. In FIG. **19**, invariant bitmap **410** is shown in the ULC of Data Matrix symbol **405**. To define terminology, the printed Data Matrix symbol prior to augmentation with sensor modules is referred to as the "underlying Data Matrix symbol"; its codeword sequence as the "underlying symbol codeword sequence" encoding "underlying data codewords and their RSEC error correction codewords". It will be appreciated that other symbologies have their own underlying symbols, underlying codeword sequences, underlying data codewords and error correction codewords, depending on the particular type of error correction employed.

FIG. **4** includes a flowchart of an example process **400** of providing a 2D barcode. Although the process **400** is described with reference to the flowchart illustrated in FIG. **4**, it will be appreciated that many other methods of performing the acts associated with the process **400** may be used. For example, the order of many of the blocks may be changed, many blocks may be intermittently repeated or continually performed, certain blocks may be combined with other blocks, and many of the blocks described are optional or may only be contingently performed.

The example process **400** may begin with determining a set of payload data **112** which includes a set of static data **134** and a set of dynamic data **136** (block **402**). For example, the set of static data **134** may include a serial number, a lot number, a batch number, and a threshold exposure temperature for a product (e.g., 30° C.). Additionally, the set of dynamic data **136** may include information that when decoded by a reader informs a user whether the product exceeded the threshold exposure temperature. Next, a 2D barcode which includes an encoded version of the set of static data is generated, and the 2D barcode includes redundant space (block **404**). In an example embodiment, the redundant space may include a plurality of unused bits, a padding region, and/or error detection and correction region (e.g., remainder space **118**). Additionally, the redundant space may include a format information region, a version information region, and/or a reference data region. Furthermore, the redundant space may include all of the remainder space and/or all of the plurality of unused bits. Additionally, the redundant space may include a portion of the padding data, or may include all of the padding data. The redundant space may also include a portion of the content data, a portion of the reference data, or a combination of various portions and/or all of data included in the content data and the reference data. Next, at least part of the redundant space is designated as a dynamic region which is adapted to store the set of dynamic data **136** (block **406**). Next, the 2D barcode is printed using a static ink and an encoded version of the set of the dynamic data on the dynamic region using a dynamic ink which changes states responsive to at least one environmental change, such that the set of dynamic data **136** is in one of a plurality of states (block **408**). In an example embodiment, the set of dynamic data **136** is readable by a reader of the 2D barcode and the set of static data **134** is readable by the reader of the 2D barcode when the set of dynamic data **136** is in each one of the plurality of states. In an example embodiment, the dynamic ink may be sensitive to an environmental factor such as temperature, time, time and temperature, freezing, radiation, toxic chemicals, or a combination of such factors, or the like. In an example embodiment, the ink may be a thermochromic ink. For example, the dynamic ink may be a water-based irreversible thermochromic ink designed to change permanently from white to black at 40° C. Additionally, the thermochromic ink

may be reversible. For example, the reversible thermochromic ink may be a liquid crystal ink or a leuco dye ink (examples include QCR Solutions Reversible Thermochromic Inks and H.W. Sands Corporation inks). In an example embodiment, the ink may be a photochromic ink which may be either reversible or irreversible. For example, the dynamic ink may change states based upon exposure to UV light. Additionally, the ink may be an ink sensitive to time and temperature (an example includes the OnVu indicator). The dynamic ink may change from a darker color to a lighter color, a lighter color to a darker color, may change levels of transparency or opacity, and/or may change levels of reflectivity or absorptivity, or may change any other suitable characteristic allowing the barcode to be readable in one or more states by a reader. For example, a dynamic ink may change from a lighter color to a dark blue, which may be readable by a reader as black. Moreover, any suitable combination of colors may be used for the states of one or more dynamic inks.

In an example embodiment, the dynamic ink may permanently change or irreversibly change in response to an environmental factor. For example, a certain chemical may experience thermal degradation when it is exposed to a certain temperature. A supplier may want to know if the chemical ever reached a temperature above 30° C. during transportation and storage. If the dynamic ink irreversibly changes, the set of dynamic data **136** may be decoded to inform the supplier that the chemical was exposed to a temperature above 30° C. and that the contents of the container may have experienced thermal degradation. Providing a 2D barcode with the set of dynamic data **136** in the redundant space advantageously allows an individual to use a reader to read the 2D barcode both before the dynamic ink has activated and after the dynamic ink has activated from the set of dynamic data **136** in a first state to represent a set of dynamic data **136** in a second state. For example, the original 2D barcode is still readable and allows a reader to obtain the set of static data **134**, such as serial number, lot number, and batch number even after the set of dynamic data **136** is in a second state, this advantageously allows both the set of static data **134** and the set of dynamic data **136** to be printed on the same 2D barcode without losing the static data **134** upon the set of dynamic data **136** changing from the first state to the second state.

A sensor dye chemistry is utilized to detect the change in condition of a sensed environmental or medical property. Since Data Matrix modules are nominally either black or white, 6 types of sensor dye chemistries may be utilized as shown in Table 1. Here "B" refers to black color state; "W" refers to white color state; and "X" refers to the dye being in a transparent color state.

TABLE 1

Types and Color Properties of Selected Sensor Dye Chemistries

Sensor dye chemistry	Unactivated State	Activated State
W→X	White	Transparent
W→B	White	Black
B→W	Black	White
B→X	Black	Transparent
X→W	Transparent	White
X→B	Transparent	Black

It is assumed that black and white dye color states are opaque and thus hide the underlying color when in either the black or white state. However, when a dye is in the transparent color state (X), the underlying color is now visible.

Since sensor dye module patterns can be either overprinted on either black or white modules of the Data Matrix symbol, or printed in place of Data Matrix modules, the color state of the sensor dye modules in the Data Matrix symbol changes upon sensor dye chemistry activation. Different sensor dye chemistry systems have different properties with respect to encoding sensor data.

The sensor dye systems which go from the colored to transparent state are typically used with an underlying bit pattern that is printed in the Data Matrix, and all of the bits in that pattern are covered with sensor dye creating a uniform black or white color state covering those modules until activated. Once activated, the sensor dye turns transparent and the underlying bit pattern in the Data Matrix barcode is visible. Alternately dye systems which go from transparent color state to a black or white color state may selectively cover modules of a uniform black or white pattern printed in the Data Matrix symbol, and upon activation, the data encoded in the sensor dye module pattern is now visible. This latter system has the advantage that the sensor dye encoded data may be determined at the time of printing of the sensor dye modules which may be at a different time and location than the pre-printing of the Data Matrix symbol.

In the example, the sensor dye chemistry in use can be accurately printed on a module by module basis over a preprinted Data Matrix module, or printed in place of Data Matrix module. For example, this may be done on a multi-station printing press. Another method of doing this is on-demand through the use of a 2-channel piezoelectric inkjet printer, where one channel contains black ink for printing the Data Matrix and the other channel contains sensor dye to be printed either on top of or in place of Data Matrix modules. The final Data Matrix symbol, augmented by the addition of sensor modules, is one example of a "sensor-augmented two-dimensional barcode symbol".

If a 2-channel inkjet printer is used, then the sensor dye chemistry in use should be known at the time of printing, especially if sensor modules are printed in place of normally-printed Data Matrix symbol modules.

In the case of overprinted sensor modules where the sensor dye chemistry is known at the time of printing the underlying Data Matrix, it is possible to encode indicator bits itself which specify the dye system in use. Indicator bits in the underlying Data Matrix are over printed with sensor dye modules. Use of these indicator bits will enable the Data Matrix reader to know what dye system is in use and its activation state and thus how to interpret a scanned Data Matrix symbol.

Note that in Table 2, 0=white and 1=black for each indicator bit. Only the 4 most common dye chemistries, where one of the states is transparent and the other is either black or white, are coded by the indicator bits.

TABLE 2

Indicator Bits for the Most Common Sensor Dye Chemistries

Sensor Dye System	Data Matrix Printed Bits 3.6 and 3.7	Indication Before Sensor Activation	Indication After Sensor Activation
W→X	11	00	11
B→X	00	11	00
X→B	10	10	11
X→W	01	01	00

The value of the printed indicator bits may be recovered from the scanned image regardless of whether it is before or after sensor activation, and may be compared with the indicator bits read from the underlying Data Matrix. Then both the dye system and activation state are determined according to Table 3.

TABLE 3

Recovering the Activation State and Indicator Bits from the Scanned Image

Underlying Data Matrix Indicator Bits	Scanned Indicator Bits	Sensor Dye System	Sensor Dye State
00	00	B→X	Activated
00	11	B→X	Unactivated
01	00	X→W	Activated
01	01	X→W	Unactivated
10	10	X→B	Unactivated
10	11	X→B	Activated
11	00	W→X	Unactivated
11	11	X→W	Activated

The colors values of sensor dye modules themselves may be used to encode sensor data which either only becomes visible or changes due to module color state change upon sensor dye activation.

encoding this sensor data itself in an error correcting code is useful when the sensor color change activation threshold is not precise for each sensor dye module; where the entire sensor-augmented two-dimensional barcode may not have been exposed uniformly to the condition activating each sensor dye module; or when sensor modules may be missing or damaged.

Here it is assumed that the sensor module colors may be binarised to 0 or 1. For, example 5 bits of sensor module color data may encode two useful pieces of data: The sensor product type and the activation condition. The associated parameters may encoded using internal tables indexed by the 5-bit data value.

Many types of error correcting codes may be used to encode sensor digital information. Typically encoded is a sensor dye bit pattern of binary-encoded sensor data. Useful error correcting codes include Hamming Codes, Bose-Chaudhuri-Hocquenghem Codes, Golay Codes, Simplex Codes, Reed-Muller Codes, Fire Codes, Convolutional Codes, and Reed-Solomon Codes.

As an example, Bose-Chaudhuri-Hocquenghem BCH (n,k,t) binary error correcting codes are well known for encoding a string of binary data; here a string of k bits are within an n-bit length code with T error correction bits. Up to (t div 2) bits may be error corrected. For example, the QR Code and Ultracode 2-dimensional barcode symbologies use a BCH(15,5,7) code which can encode k=5 bits in n=15 bits and correct up to (7 div 2)=3 bit errors. There are standard decoding and error correction techniques for decoding and error correcting these codes. Table C.1 in Annex C of ISO/IEC 18004 Information technology—Automatic identification and data capture techniques—QR Code 2005 bar-code symbology specification gives the complete 15 bit code sequences for data values 0, 1 . . . 31. ISO/IEC 18004 Table C.1 is summarized in Table 4. Data Values 0 and 31 are reserved and not to be encoded, as they represent unactivated dye module states: Data value 0 (all BCH bits=0) for W→X and W→B Sensor dye chemistries; data value 31 (all BCH bits=1) for B→X and B→W sensor dye chemistries.

TABLE 4

BCH (15, 5, 3) Encoding of 5 Bits of Sensor Data

5-Bit Data Value	BCH (15, 5, 3) Encoding Bit 15	Bits 14–>8	Bits 7–>1
0	0	0000000	0000000
1	0	0001010	0110111
2	0	0010100	1101110
3	0	0011110	1011001
4	0	0100011	1101011
5	0	0101001	1011100
6	0	0110111	0000101
7	0	0111101	0110010
8	0	1000111	1010110
9	0	1001101	1100001
10	0	1010011	0111000
11	0	1011001	0001111
12	0	1101110	0111101
13	0	1101110	0001010
14	0	1110000	1010011
15	0	1111010	1100100
16	1	0000101	0011011
17	1	0001111	0101100
18	1	0010001	1110101
19	1	0011011	1110101
20	1	0100110	1000000
21	1	0101100	1000111
22	1	0110010	0011110
23	1	0111000	0101001
24	1	1000010	1001101
25	1	1001000	1111010
26	1	1010110	0100011
27	1	1011100	0010100
28	1	1100001	0100110
29	1	1101001	0010001
30	1	1110101	1001000
31	1	1111111	1111111

Recovery of the sensor bit data when BCH(15,5,7) is encoded in a Data Matrix symbol (whether the sensor bits have been activated or not) may be done by first recovering the sensor digital information from scanning and decoding on the sensor-augmented two-dimensional barcode symbol. From the particular sensor dye module pattern, extract the 15-bit BCH-encoded binary number. Note that there are many standard methods for decoding and error-correcting BCH encoded data. The classic Peterson-Gorenstein Zierler Decoder is discussed in R. E. Blahut, "*Theory and Practice of Error Control Codes (corr. edition)*", 1983 (ISBN-10: 0-201-10102-5), p. 166. A useful and practical algorithm for a BCH(15,5,7) decoding is given by S. A Vanstone and P. C. van Oorschot, "*An Introduction to Error Correcting Codes with Applications*", 1989 (ISBN-10: 0-7923-9017-2), p. 219. Using any method for decoding and error-correcting BCH(15,5,7) encoded data, extract the 5-bit sensor data.

Other types of sensor digital information may be encoded in the sensor dye module pattern. This includes visual patterns and images of any type, such as ISO or ANSI or ISO warning signs and symbols, or any other type of designed graphic. The number of bits which are encoded and the number of utahs deliberately damaged in the process (which is affected by the physical extent of the visual pattern on the underlying Data Matrix symbol) as well as the size of the underlying Data Matrix and its available number of RSEC codewords all affect the visual pattern and image encoding capability.

Sensor dye module patterns may also be encoded after the underlying Data Matrix symbol has been preprinted. This allows different technologies to be used for printing the underlying Data Matrix and later printing the sensor dye module pattern. This also allows different kinds of sensor

dye chemistries to be used on a previously printed Data Matrix without that sensor dye chemistry being known at the time that the underlying Data Matrix itself was printed.

In an example embodiment, a non-privileged reader may be capable of reading the static data **134** and may not be capable of reading the dynamic data **136** of the 2D barcode. In another example embodiment, only privileged readers may be capable of reading the static data **134** and the dynamic data **136** of the 2D barcode. In some cases, having dynamic data **136** on a barcode that cannot be read by non-privileged readers may advantageously allow a manufacturer or supplier to include information on a 2D barcode that they may not want to provide to the public or a customer. Additionally, having a privileged reader that may read both the static data **134** and the dynamic data **136** advantageously allows an individual using the privileged reader to obtain both the static data **134** and the dynamic data **136** without having to use multiple readers.

FIG. **5** is a flow chart diagram **500** illustrating an example 2D barcode printed using process **400**. As shown in FIG. **5**, the 2D barcode is printed by a process **502** with an encoded version of the set of dynamic data on the dynamic region **192**. In this example, the set of dynamic data **136** is printed on a plurality of unused bits **120** in the lower right hand corner of the 2D barcode. The dynamic ink **198** is used on the upper left hand and bottom right hand information modules of the plurality of unused bits **120**. After the dynamic region is printed with the dynamic ink **198**, the barcode is in a first state **504** (i.e., the dynamic ink **198** has not activated yet). The dynamic ink **198** used in the dynamic region **192** activates to a solid black color upon exposure to a specified environmental change **506**. Once the 2D barcode is exposed to the environmental change **506**, the set of dynamic data **136** in the dynamic region **192** changes and the 2D barcode changes to a second state **508** and conveys the information of the environmental change **506** to a reader.

FIG. **6**A is a textual representation of a set of static data **134** and a set of dynamic data **136** that may be encoded into a 2D barcode, and FIG. **6**B is an example of textual dynamic data encoded as binary information modules. FIG. **6**C and FIG. **6**D are flow chart diagrams illustrating the dynamic data of a 2D barcode changing from a first state to a second state. For example, the set of static data **134** includes product information such as serial number (SN), batch number (BN), and lot number (LN). In this example, the serial number is 498760003, the batch number is 654, and the lot number is 35A1. The set of static data **134** does not change. Additionally, the set of dynamic data **136** is shown in a first state **210** (top) and a second state **212** (bottom) in FIG. **6**A. For example, the set of dynamic data **136** may be printed with a dynamic ink **198** that changes from a first state **210** to a second state **212** upon reaching a threshold exposure temperature above 30° C. The textual representation of the set of dynamic data **136** in the first state **210** is "<" (i.e., less than) the threshold exposure temperature specified in the set of static data **134**, and the textual representation of the set of dynamic data **136** in the second state **212** is ">" (i.e., greater than) the threshold exposure temperature specified in the set of static data **134**, in this case 30° C. In an example embodiment, the 2D barcode may be encoded using a binary 8-bit representation of the set of static data **134** and the set of dynamic data **136**, as shown in FIG. **6**B. For example, the binary representation of "<" may be "00111100" and the binary representation of ">" may be "00111110." In the present example, binary zero (0) bits are colored white and the binary one (1) bits are colored black. It should be appreciated that various other color combinations may be used to print the 2D barcode, and various other encoding methodologies may be used. The colors of black and white and binary (8-bit) encoding have been provided for illustrative purposes. FIG. **6**C represents a 2D barcode with the set of dynamic data **136** in a first state **210** transitioning to a second state **212** in response to an environmental change such as the temperature rising above 30° C. For example, the dynamic ink **198** used in the 2D barcode represented in FIG. **6**C shows a dynamic ink **198** that activates from white to black in response to an a temperature greater than the threshold exposure temperature. In another example embodiment, shown in FIG. **6**D, the dynamic ink **198** may activate from black to white in response to an environmental change **506**, such as freezing or exposure to a threshold exposure temperature below 0° C.

FIG. **7** includes a flowchart of an example process **420** of providing a 2D barcode as illustrated in FIG. **8**, discussed in further detail below. Although the process **420** is described with reference to the flowchart illustrated in FIG. **7**, it will be appreciated that many other methods of performing the acts associated with the process **420** may be used. For example, the order of many of the blocks may be changed, many blocks may be intermittently repeated or continually performed, certain blocks may be combined with other blocks, and many of the blocks described are optional or may only be contingently performed.

The example process **420** may begin with determining a set of static data **134** (block **422**). For example, the set of static data **134** may be a serial number, a batch number, and/or a lot number, etc. Next, a set of dynamic data **136** is determined (block **424**). In an example embodiment, the set of dynamic data **136** may have a first state **210** and a second state **212**. For example, dynamic data **136** in a first state may be unexposed to UV light while the dynamic data **136** in a second state may be exposed to UV light. Additionally, dynamic data **136** in a first state may be a temperature less than 30° C. while the dynamic data **136** in a second state may be a temperature greater than 30° C. Then, a first 2D barcode is generated (block **426**). For example, a computer may generate the first 2D barcode based on inputs of the set of static data **134** and the set of dynamic data **136** in the first state **210**. In an example embodiment, the first 2D barcode may include an encoded version of the set of static data and the encoded version of the set of dynamic data **196** in the first state **210**. Additionally, the set of static data **134** and the set of dynamic data **136** in the first state **210** may include a first plurality of information modules **218** and a second plurality of information modules **220**. For example, the first plurality of information modules **218** may be black modules and the second plurality of information modules **220** may be white information modules. Then, a second 2D barcode is generated (block **428**). For example, a computer may generate the second 2D barcode based on inputs of the set of static data **134** and the set of dynamic data **136** in the second state **212**. In an example embodiment, the second 2D barcode may include an encoded version of the set of static data and an encoded version of the set of dynamic data **196** in the second state **212**. Additionally, the set of static data **134** and the set of dynamic data **136** in the second state **212** may include a third plurality of information modules **224** and a fourth plurality of information modules **226**. For example, the third plurality of information modules **224** may be black modules and the fourth plurality of information modules **226** may be white information modules. It should be appreciated that the first plurality of information modules **218** and the third plurality of information modules **224** may be white while the second plurality of information modules

220 and the fourth plurality of information modules 226 may be black. Furthermore, it should be appreciated that the first plurality of information modules 218 and the third plurality of information modules 224 and/or the second plurality of information modules 220 and the fourth plurality of information modules 226 may be various colors, levels of transparency, and/or levels of reflectivity, or may have any other suitable characteristic allowing the 2D barcode to be readable by a reader. In an example embodiment, the third plurality of information modules 224 may include all of the first plurality of information modules 218 plus a set of one or more information modules 228. Additionally, the second plurality of information modules 220 may include all of the fourth plurality of information modules 226 plus the set of one ore more information modules 228. Then, compare the first 2D barcode and the second 2D barcode (block 430). For example, the first 2D barcode and the second 2D barcode may include binary data having values of zero (0) or one (1), which may correspond to each information module being colored white for a binary value of zero (0) and black for a binary value of one (1). Then, categorize the information modules 214 into a first group 230 and a second group 232 (block 432). In an example embodiment, the first group 230 may include common information modules between the first plurality of information modules 218 of the first 2D barcode and the third plurality of information modules 224 of the second 2D barcode. Additionally, the second group 232 may include unique information modules of the third plurality of information modules 224 of the second 2D barcode. For example, a computer may categorize all the black information modules that are common to the first 2D barcode and the second 2D barcode into the first group 230. Additionally, the computer may categorize all the black information modules that are unique to the second 2D barcode (i.e., the information modules that were white in the first 2D barcode and are black in the second 2D barcode) into the second group 232. Then, print the 2D barcode using a static ink 194 and a dynamic ink 198 (block 434). In an example embodiment, the first group 230 may be printed in the static ink 194, and the second group 232 may be printed in the dynamic ink 198. Additionally, the dynamic ink 198 may be adapted to activate in response to the occurrence of a specific environmental factor. In an example embodiment, the dynamic ink 198 may be sensitive to an environmental factor such as temperature, time, time and temperature, freezing, radiation, toxic chemicals, or a combination of such factors, or the like.

In an example embodiment, the first plurality of information modules 218 and the third plurality of information modules 224 may be adapted to be visually distinguishable from a printing surface 234 and the third plurality of information modules 224 and the fourth plurality of information modules 226 may be visually indistinguishable from the printing surface 234. It should be appreciated that various printing techniques may be used that involve printing with ink, dye, paint, and/or any other suitable material, or the like. Additionally, various other techniques may be used to change the visual appearance of the printing surface 234 of the 2D barcode such as etching, burning, melting, removing material, and/or any other process adapted to print a 2D barcode. For example, a printing surface 234 may include a white substrate covered with a black top layer which is etched away to reveal the white substrate underneath. Additionally, a printing surface 234 may include a blue substrate covered with a yellow top layer, along with various other color combinations.

FIG. 8 is flow diagram illustrating an example portion of a 2D barcode printed using process 420. As shown in FIG. 8, the first 2D barcode portion 216 is a portion of an example barcode that includes an encoded version of a portion of the set of static data and an encoded version of a portion of the set of dynamic data 196 in a first state 210. The second 2D barcode portion 222 is the portion of the example barcode that includes the encoded version of the portion of the set of static data and the encoded version of the portion of the set of dynamic data 196 in a second state 212. All of the black information modules are the first group 230 of common information modules between the first plurality of information modules 218 of the first 2D barcode portion 216 and the third plurality of information modules 224 of the second 2D barcode portion 222. Additionally, the information modules outlined in dotted lines may be the second group 232 of unique information modules of the third plurality of information modules 224 of the second 2D barcode portion 222. For example, the second group 232 of information modules may include all of the information modules that are changing from white to black when the set of dynamic data 136 transitions from the first state 210 to the second state 212. Only using one dynamic ink 198 advantageously allows the 2D barcodes to be printed in a more efficient and cost effective manner. Additionally, the use of only one dynamic ink 198 advantageously reduces the risk of the code becoming unreadable due to an offset or delayed activation time of multiple dynamic inks. It should be appreciated that the example embodiments disclosed herein may translate to various 2D barcodes including an Aztec Code, Code 1, CrontoSign, CyberCode, DataGlyphs, Data Matrix, Datastrip code, EZcode, High Capacity Color Barcode, InterCode, MaxiCode, MMCC, NexCode, PDF417, Qode, QR code, ShotCode, SPARQCode, and the like.

FIG. 9 includes a flowchart of an example process 440 of generating a 2D barcode. Although the process 440 is described with reference to the flowchart illustrated in FIG. 9, it will be appreciated that many other methods of performing the acts associated with the process 440 may be used. For example, the order of many of the blocks may be changed, many blocks may be intermittently repeated or continually performed, certain blocks may be combined with other blocks, and many of the blocks described are optional or may only be contingently performed.

The example process 440 may begin with determining a set of static data 134 (block 442). For example, the set of static data 134 may be a serial number, a batch number, and/or a lot number, etc. Next, a set of dynamic data 136 is determined (block 444). In an example embodiment, the set of dynamic data 136 may have a first state 210 and a second state 212. The set of dynamic data 136 may have more than two states. For example, the set of dynamic data 136 may have a first state 210, a second state 212 (e.g., activated by going above 25° C.), and a third state (e.g., activated by going above 40° C.). Then, a first 2D barcode is generated (block 446). For example, a computer may generate the first 2D barcode based on inputs of the set of static data 134 and the set of dynamic data 136 in the first state 210. In an example embodiment, the first 2D barcode may include an encoded version of the set of static data and an encoded version of the set of dynamic data 196 in the first state 210. Additionally, the set of static data 134 and the set of dynamic data 136 in the first state 210 may include a first plurality of information modules 218 and a second plurality of information modules 220. For example, the first plurality of information modules 218 may be black modules and the second plurality of information modules 220 may be white information modules. Then, a second 2D barcode is generated (block 448). For example, a computer may generate the

second 2D barcode based on inputs of the set of static data **134** and set of dynamic data **136** in the second state **212**. In an example embodiment, the second 2D barcode may include an encoded version of the set of static data and an encoded version of the set of dynamic data **196** in the second state **212**. Additionally, the set of static data **134** and the set of dynamic data **136** in the second state **212** may include a third plurality of information modules **224** and a fourth plurality of information modules **226**. For example, the third plurality of information modules **224** may be black modules and the fourth plurality of information modules **226** may be white information modules. It should be appreciated that the first plurality of information modules **218** and the third plurality of information modules **224** may be white while the second plurality of information modules **220** and the fourth plurality of information modules **226** may be black. Furthermore, it should be appreciated that the first plurality of information modules **218** and the third plurality of information modules **224** and/or the second plurality of information modules **220** and the fourth plurality of information modules **226** may be various colors, levels of transparency or opacity, and/or levels of reflectivity or absorptivity, or may have any other suitable characteristic allowing the barcode to be readable by a reader. Then, the first 2D barcode is compared to the second 2D barcode (block **450**). For example, the first 2D barcode and the second 2D barcode may include binary data having values of zero (0) or one (1), which may correspond to each information module being colored white for a binary value of zero (0) and black for a binary value of one (1). Then, the information modules are categorized into a first group **230**, a second group **232**, and a third group (block **452**). In an example embodiment, the first group **230** may include common information modules between the first plurality of information modules **218** of the first 2D barcode and the third plurality of information modules **224** of the second 2D barcode. Additionally, the second group **232** may include unique information modules of the third plurality of information modules **224** of the second 2D barcode. In an example embodiment, the third group may include unique information modules of the first plurality of information modules **218** of the first 2D barcode. For example, a computer may categorize all the black information modules that are common to the first 2D barcode and the second 2D barcode into the first group **230**. Additionally, the computer may categorize all the black information modules that are unique to the first 2D barcode into a third group (i.e. the information modules that are black in the first 2D barcode, but white in the second 2D barcode). Also, the computer may categorize all the black information modules that are unique to the second 2D barcode into a second group **232** (i.e., the information modules that were white in the first 2D barcode, but are black in the second 2D barcode). Then, the 2D barcode is printed using a static ink **194**, a first dynamic ink, and a second dynamic ink (block **454**). In an example embodiment, the first group **230** may be printed in the static ink **194**. Additionally, the second group **232** may be printed in the first dynamic ink. The first dynamic ink may be adapted to activate in response to the occurrence of a specific environmental factor. Furthermore, the third group may be printed in a second dynamic ink, and the second dynamic ink may be adapted to activate in response to the occurrence of the specific environmental factor. For example, the first dynamic ink may be printed in white and active to black upon reaching 30° C. and the second dynamic ink may be printed in black and activate to white upon reaching 30° C. It should be appreciated that the first and second dynamic ink may be printed in several color combinations. In an example embodiment, the first dynamic ink and the second dynamic ink may be sensitive to an environmental factor such as temperature, time, time and temperature, freezing, radiation, toxic chemicals, or a combination of such factors, or the like. Additionally, in an example embodiment, the first dynamic ink and the second dynamic ink may activate simultaneously. For example, the first dynamic ink and the second dynamic ink may both activate 72 hours after printing such that the first dynamic ink changes from white to black and the second dynamic ink simultaneously changes from black to white. Additionally, the first dynamic ink and the second dynamic ink may both simultaneously activate after a temperature threshold is met (e.g., precision within 0.1° C. temperature range). Having the first dynamic ink and second dynamic ink active simultaneously advantageously allows the 2D barcode to be readable at all times because the 2D barcode will either be in a first state (i.e., the first 2D barcode) or a second state (i.e., the second 2D barcode).

FIG. **10**A, FIG. **10**B, and FIG. **10**C are block diagrams of an example set of information modules of a 2D barcode printed using process **440**. Specifically, FIG. **10**A shows the first plurality of information modules **218** and the second plurality of information modules **220** of the first 2D barcode portion **216** (i.e., the set of dynamic data **136** is in the first state **210**). FIG. **10**B shows the third plurality of information modules **224** and the fourth plurality of information modules **226** of the second 2D barcode portion **222** (i.e., the set of dynamic data **136** is in the second state **212**). FIG. **10**C shows the first group **230**, the third group **238**, and the second group **232** of information modules, from top to bottom respectively. For example, the first group **230** includes common information modules between the first plurality of information modules **218** of the first 2D barcode portion **216** and the third plurality of information modules **224** of the second 2D barcode portion **222**, these information modules are depicted as cross-hatched modules. The second group **232** includes unique information modules of the third plurality of information modules **224** of the second 2D barcode portion **222**, this group of information modules is depicted as a black module in the bottom picture in FIG. **10**C. Additionally, the third group **238** includes unique information modules of the first plurality of information modules **218** of the first 2D barcode portion **216**, and this group of information modules is depicted by black modules in the middle picture of FIG. **10**C. In this example, the first group **230** may be printed in a static ink **194**, the second group **232** may be printed in a first dynamic ink **240**, and the third group **238** may be printed in a second dynamic ink **242**. For example, the second group **232** may be printed with a first dynamic ink **240** adapted to activate (i.e., transition from white to black) in response to the occurrence of a specific environmental factor. Additionally, the third group **238** may be printed with a second dynamic ink **242** adapted to activate (i.e., transition from black to white) in response to the occurrence of the specific environmental factor. It should be appreciated that generating a 2D barcode with more than one dynamic ink advantageously allows the 2D barcode to be printed with larger portions of changing dynamic data that may include error detection and correction data **116**. For example, by using multiple dynamic inks, the 2D barcode is capable of changing several different regions of the 2D barcode enabling a non-privileged reader to read both the set of static data **134** and the set of dynamic data **136** in a plurality of states to give a plurality of outputs without the error detection and correction data **116** overwriting a designated output.

FIG. **11** includes a flowchart of an example process **460** of generating a 2D barcode. Although the process **460** is described with reference to the flowchart illustrated in FIG. **11**, it will be appreciated that many other methods of performing the acts associated with the process **460** may be used. For example, the order of many of the blocks may be changed, many blocks may be intermittently repeated or continually performed, certain blocks may be combined with other blocks, and many of the blocks described are optional or may only be contingently performed.

The example process **460** may begin with determining a set of payload data **112** (block **462**). In an example embodiment, the set of payload data **112** may include a set of static data **134** and a set of dynamic data **136**. Additionally, the set of dynamic data **136** may have a first state **210** and a second state **212**. Next, a computer may generate a 2D barcode (block **464**). In an example embodiment, the 2D barcode may include an encoded version of the set of static data, a dynamic region **192** which is adapted to store an encoded version of the set of dynamic data, and error detection and correction data **116**. Then, a printer may print the 2D barcode using a static ink **194** and the encoded set of the dynamic data on the dynamic region **192** using a dynamic ink **198** (block **466**). In an example embodiment, the 2D barcode may be attached to various products such as food product, pharmaceutical products, etc. In an example embodiment, the dynamic ink **198** may change states responsive to at least one environmental change, such that the set of dynamic data **136** is in either the first state **210** or the second state **212**. Additionally, in an example embodiment, the error detection and correction data **116** may accommodate for changes in the set of dynamic data **136** in the dynamic region **192** such that the 2D barcode may be readable by a reader and may produce a first output when the set of dynamic data **136** is in the first state **210** and the 2D barcode may be readable by a reader and may produce a second output when the set of dynamic data **136** is in the second state **212**. In an example embodiment, the dynamic region **192** may be provided in a padding region. Additionally, the dynamic region **192** may be provided at an end of a data region. Providing a 2D barcode that includes error detection and correction data **116** that accommodates for changes in the set of dynamic data **136** advantageously allows an individual to use a non-privileged reader and also advantageously allows an individual to obtain two different output readings using the non-privileged reader. For example, without generating a 2D barcode with error detection and correction data **116** that accommodates for changes in the set of dynamic data **136** in the dynamic region **192**, a non-privileged reader may only produce the first output regardless of whether the 2D barcode included a set of dynamic data **136** in the first state **210** or a set of dynamic data **136** in the second state **212**.

FIG. **12** includes a flowchart of an example process **470** of reading a 2D barcode. Although the process **470** is described with reference to the flowchart illustrated in FIG. **12**, it will be appreciated that many other methods of performing the acts associated with the process **470** may be used. For example, the order of many of the blocks may be changed, many blocks may be intermittently repeated or continually performed, certain blocks may be combined with other blocks, and many of the blocks described are optional or may only be contingently performed.

The example process **470** may begin with a reader reading a set of static data **134** included in the 2D barcode (block **472**). In an example embodiment, the 2D barcode may be printed in static ink **194** and dynamic ink **198**. Additionally, an encoded version of the set of static data may be printed in the static ink **194**. Next, a reader may read a set of dynamic data **136** included in the 2D barcode (block **474**). In an example embodiment, an encoded version of the set of dynamic data **196** may be printed in the dynamic ink **198**. Additionally, the set of dynamic data **136** may be printed in a redundant space on the 2D barcode. Next, the reader may generate a first output of the set of static data **134** (block **476**). Then, the reader may generate a second output of the set of dynamic data **136** (block **478**). In an example embodiment, the second output may depend on which state of the one of a plurality of states the dynamic data is in, such as greater than 30° C. or less than 30° C.

FIG. **13** includes a flowchart of an example process **490** of reading a 2D barcode. Although the process **490** is described with reference to the flowchart illustrated in FIG. **13**, it will be appreciated that many other methods of performing the acts associated with the process **490** may be used. For example, the order of many of the blocks may be changed, many blocks may be intermittently repeated or continually performed, certain blocks may be combined with other blocks, and many of the blocks described are optional or may only be contingently performed.

The example process **490** may begin with a reader reading a set of static data **134** included in the 2D barcode (block **492**). In an example embodiment, the 2D barcode may be printed in static ink **194** and dynamic ink **198**. Additionally, an encoded version of the set of static data may be printed in the static ink **194**. Next, a reader may read a set of dynamic data **136** included in the 2D barcode (block **494**). In an example embodiment, an encoded version of the set of dynamic data **196** may be printed in the dynamic ink **198**. Additionally, the set of dynamic data **136** may be printed in a dynamic region **192** of the 2D barcode. Next, the reader may generate an output of the set of static data **134** and the set of dynamic data **136** (block **496**). In an example embodiment, the output may be a first output when the set of dynamic data **136** is in a first state **210**, and the output may be a second output when the set of dynamic data **136** is in a second state **212**.

FIG. **14** is a block diagram of a 2D barcode providing system. The system may include a computer **292** and a printer **290**. The system may be used to provide barcodes **102**. The computer **292** may include one or more computer programs or components. It will be appreciated that all of the disclosed methods and procedures described herein can be implemented using one or more computer programs or components. These components may be provided as a series of computer instructions on any conventional computer readable medium or machine readable medium, including volatile or non-volatile memory, such as RAM, ROM, flash memory, magnetic or optical disks, optical memory, or other storage media. The instructions may be provided as software or firmware, and/or may be implemented in whole or in part in hardware components such as ASICs, FPGAs, DSPs or any other similar devices. The instructions may be configured to be executed by one or more processors, which when executing the series of computer instructions, performs or facilitates the performance of all or part of the disclosed methods and procedures. Additionally, the computer **292** may include a display and may have a connection to one or more communications channels such as the Internet or some other voice and/or data network, including, but not limited to, any suitable wide area network or local area network.

The computer **292** may include one or more processors electrically coupled by an address/data bus to one or more memory devices, other computer circuitry, and one or more

interface circuits. The processor may be any suitable processor, such as a microprocessor. The memory preferably includes volatile memory and non-volatile memory. Additionally, the memory may store a software program that interacts with the other devices in the barcode providing system. This program may be executed by the processor in any suitable manner. The memory may also store digital data indicative of documents, files, programs, barcodes, etc. received from a computer or a barcode reader. Other computer circuitry may include a wide variety of hardware components including ASICs, or other specialized circuitry for manipulating data in a specific format, such as barcode data.

One or more displays, printers **290**, and/or other output devices may also be connected to the computer **292** via interface circuits. The display may be a liquid crystal display or any other type of display. The printer **290** may print a barcode that is generated and received from the computer **292**. Additionally, one or more storage devices may also be connected to the computer **292** via the interface circuits. For example, a hard drive, CD drive, DVD drive, and/or other storage devices may be connected to the computer **292**. The storage devices may store any type of data, such as barcode data **100**, image data, historical access or usage data, etc.

FIG. **15**A and FIG. **15**B is a block diagram of a 2D barcode reading system. The system may include a reader **200**, the system may be used to read barcodes **102**. In an example embodiment, the reader **200** may be a privileged reader or a non-privileged reader. The reader **200** may be a dedicated barcode reader or an apparatus configured to read barcodes such as a mobile device, a personal digital assistant or PDA, a smartphone, a laptop, a tablet computer, or a desktop computer, as well as any other user devices. The reader **200** may be adapted to read 1D and 2D barcodes, or may be adapted to read only 2D barcodes. The reader **200** may also transmit, receive, or exchange data with other network devices via a communication network. A network device may be a computer **292**, a different reader **200**, or any other device accessible via a communication network. Also, certain data may be stored in a reader **200** which is also stored on the server, either temporarily or permanently, for example in memory or a storage device. The network connection may be any type of network connection, such as a cellular or wireless connection, an Ethernet connection, digital subscriber line, telephone line, coaxial cable, etc. Access to a reader **200** or dynamic data **136** may be controlled by appropriate security software or security measures. An individual users' access may be defined by reader **200** and limited to certain data and/or actions. For example, a user may only have access to a non-privileged reader which may only be capable of reading the static data **134** on a barcode **102**. Additionally, a user may have access to a privileged reader which may be capable of reading just the dynamic data or both the dynamic and static data on a barcode **102**. Accordingly, users and/or administrators of the barcode reading system may be required to register with one or more readers **200**. Additionally, various options for managing data located within a reader **200** and/or in a server may be implemented. For example, a management system may be implemented in the reader **200** and may update, store, and/or back up barcode data **100** locally and/or remotely using any suitable method of data transmission.

The method of reading of a sensor-augmented two-dimensional barcode symbol has a number of requirements. Reading a sensor-augmented Data Matrix symbol is possible

1. If only a limited number of modules change color state in the sensor dye module pattern, and
2. If the changed modules are restricted to a small number of utahs, and
3. If there is sufficient Reed Solomon Error Correction capability in the underlying Data Matrix,

then the RSEC process may be utilized to recover the underlying codeword data in the underlying Data Matrix prior to the color state changes of modules caused by sensor activation.

Table 5 shows the data and RSEC codeword capacities of all square Data Matrix symbols up to 26×26 and all rectangular Data Matrix symbols.

Each data codeword normally requires two RSEC codewords to recover the underlying data. As an example, a 16×16 square Data Matrix which has a capacity for 12 data codewords (12 data utahs) and has 12 RSEC codewords (12 RSEC utahs). Thus if activated sensor modules change 4 data utahs in that 16×16 symbol, then eight RSEC codewords are utilized to recover the data in those for altered utahs. This leaves 4 additional RSEC codewords available for correction of any other symbol damage.

TABLE 5

Total Data and RSEC Codewords for Different Sizes of Data Matrix Symbols

Symbol Size			Maximum Data Capacity			Total Codewords		Error Correction	
Size	Rows	Cols	Digits	Alphanum	Bytes	Data	RSEC	Max Cwds	% EC
SQUARE SYMBOLS									
10 × 10	10	10	6	3	1	3	5	2	63%
12 × 12	12	12	10	6	3	5	7	3	58%
14 × 14	14	14	16	10	6	8	10	5	56%
16 × 16	16	16	24	16	10	12	12	6	50%
18 × 18	18	18	36	25	16	18	14	7	44%
20 × 20	20	20	44	31	20	22	18	9	45%
22 × 22	22	22	60	43	28	30	20	10	40%
24 × 24	24	24	72	52	34	36	24	12	40%
26 × 26	26	26	88	64	42	44	28	14	39%
RECTANGULAR SYMBOLS									
8 × 18	8	18	10	6	3	5	7	3	58%
8 × 32	8	32	20	13	8	10	11	5	52%
12 × 26	12	26	32	22	14	16	14	7	47%
12 × 36	12	36	44	31	18	22	18	9	45%

TABLE 5-continued

Total Data and RSEC Codewords for Different Sizes of Data Matrix Symbols

Symbol Size			Maximum Data Capacity			Total Codewords		Error Correction	
Size	Rows	Cols	Digits	Alphanum	Bytes	Data	RSEC	Max Cwds	% EC
16 × 36	16	36	64	46	24	32	24	12	43%
16 × 48	16	48	98	72	28	49	28	14	36%

Two types of reading processes for the sensor-augmented two-dimensional barcode are utilized, depending on whether or not the structure of sensor dye module pattern has been encoded in the underlying Data Matrix. In the first case, where the the structure of sensor dye module pattern has not been encoded in the underlying Data Matrix of the sensor-augmented two-dimensional barcode:

1. Scan and optically process the image as part of the Data Matrix reading process and construct a scan binary bitmap of the scanned image. See ISO/IEC 16022 for one methodology.
2. Process the scan binary bitmap to construct the underlying symbol codeword sequence,
3. Utilize the Reed-Solomon error correction process on the symbol codeword sequence to recover the underlying data codewords prior to any alteration by activated sensor modules. See ISO/IEC 16022 for one methodology.
4. Construct an underlying binary bitmap from the underlying data codeword sequence equal in size to the scan binary bitmap. See ISO/IEC 16022 for one methodology.
5. At each bit position, Exclusive OR the scan binary bitmap and the underlying binary bitmap to form a sensor digital information bitmap of the same size as the scan binary bitmap.
6. Process the sensor digital information bitmap according to the situational rules.

In the case where the the structure of sensor dye module pattern has been encoded in the underlying Data Matrix of the sensor-augmented two-dimensional barcode:

1. Scan and optically process the image as part of the Data Matrix reading process and construct a scan binary bitmap of the scanned image. See ISO/IEC 16022 for one methodology.
2. Process the scan binary bitmap to construct the underlying symbol codeword sequence,
3. Utilize the Reed-Solomon error correction process on the symbol codeword sequence to recover the underlying data codewords prior to any alteration by activated sensor modules. See ISO/IEC 16022 for one methodology.
4. Utilize the information encoded in the underlying data codewords to determine within the scan binary bitmap a sensor dye bit pattern containing the sensor digital information and extract the binary information sequence in its appropriate bit order.
5. When the sensor data has been BCH(15,5,7) encoded, use standard methods the BCH error-correcting process to recover the 5-bit binary-encoded sensor data (or else decode decoding fails).

The first preferred embodiment utilizes a temperature threshold-sensitive sensor dye chemistry. The sensor dye chemistry is W→X; white dye elements overprinted on black modules of the printed underlying Data Matrix on a white printing media. It is assumed the sensor dye chemistry used is known at the time of printing the Data Matrix symbol.

It is assumed that the data structure encoded in the Data Matrix symbol utilizes GS1 Application Identifiers and conforms to the GS1 General Specifications, V 15 Issue 2 (January 2015) (http://www.gs1.org/docs/barcodes/GS1_General_Specifications.pdf).

Here 15-bit BCH(15,5,7) error correction used to encode 5 bits of sensor data. Since the overprinted sensor dye modules are white, the black modules corresponding to '1' bits of the 15-bit BCH encoding needs to be printed in underlying Data Matrix.

The sensor data BCH encoding along with 2 indicator bits to indicate the sensor dye chemistry in use utilizes only utahs **3**, **5** and **6** of the 16×16 ECC **200** Data Matrix symbol shown in FIG. **19** for exemplary purposes. Utahs **5**, **6** and utah bits **3.6**-**3.8** are in the same bitmap position relative to the symbol ULC as in the invariant bitmap **410** in FIG. **19**.

The indicator utah bits **3.6** and **3.7** indicate which of the sensor dye chemistries in Table 1 is in use. It is assumed that the sensor dye chemistry to be used is known at the time of printing of the Data Matrix.

Modules of the selected sensor chemistry overprint both utah bits **3.6** and **3.7**. Depending upon the sensor dye chemistry selected, bits **3.6** and **3.7** will appear as in Table 4 when the sensor dye is in either the unactivated or activated state.

FIG. **20** shows the size **14** Data Matrix bitmap **505** from ISO/IEC 16022 and identifies utah bit **3.8** and utahs **5** and **6** of the invariant bitmap **410**. These are references **510**, **520** and **530** respectively. The upper 5 bits of utah **3**, bits **3.1**-**3.5** referenced as **540**, which are not in the invariant bitmap **410**, may be used to encode additional information about the sensor dye chemistry in use and/or the sensor dye bit pattern.

In keeping with the GS1 System as defined in the GS1 General Specifications, the most widely used system for encoding information in Data Matrix, the GS1 Application Identifier AI (90) may be used. AI (90) is reserved for information mutually agreed upon between trading partners, such as the presence of a sensor-enabled Data Matrix. Since the Application Identifiers may appear within any sequence in a GS1 Data Matrix, AI (90) will appear immediately after the FNC1 to ensure that the 15 BCH—encoded sensor bits B**1**-B**15** are in the invariant bitmap **410**. Since only 7-bit characters can be encoded in a GS1 application identifier, the most significant bit **5.1** of utah **5** at **520** and bit **6.1** of utah **6** at **530** and their color state both before and after activation are unimportant here.

As shown in FIG. **21**, the invariant bitmap **410** portion of the 16×16 Data Matrix **600** includes **610***a*, utah **1** bits **1.5** and **1.8**; **620** utah **2**; **630***a* utah **3** bits **3.6**-**3.8**; **640***a* utah **4** bits **4.3**-**4.8**; **650** utah **5**; **660** utah **6** and **670***a* utah **7** bits **7.2**, **7.4**, **7.5**, **7.7** and **7.8**. Note that other utah bits surrounding these seven utahs are shown in **600** for reference purposes

and easy correspondence with the bitmap of FIG. **20**. For example, **610***b* utah **1** bits **1.1**-**1.4**, **1.6**, and **1.7**; **640***b* utah **4** bits **4.1** and **4.2**; and **670***b* utah **7** bits **7.1**, **7.3**, and **7.6**.

The most significant bit B**15** will be encoded in **630***a* utah bit **3.8** at **630***a*. Utah **5** at **650** bits **5.2** through **5.8** will encode B**14** through B**7** of the BCH encoded sensor bits. Utah **6** at **660** bits **6.2** through **6.8** will encode bits B**7** through B**1** of the BCH encoded sensor bits.

Since a white to transparent sensor dye chemistry is utilized in the first preferred embodiment, the encoded sensor data bit black and white pattern B**15**-B**1** should be preprinted in the Data Matrix. The W→X sensor dye is then overprinted on these encoded bits; her either all of the bits B**1**-**15** or at least those of the black bits B**15**-B**1** in the underlying Data Matrix.

Consider an example when the sensor data value is '4'. From Table 2, the BCH encoding B**15**-B**1** is 001000111101011. Thus in the Data Matrix size **14** bitmap in FIG. **20**, utah bits **3.8**, **5.2**-**5.8** and **6.2**-**6.8** are set to encode the black modules corresponding to these bits B**15**-B**1**, as these modules will be over printed with the white to transparent sensor dye. Utah bits **5.1** and **6.1** are set to '0' to ensure white modules are printed. Table 6 shows the AI (90) data string is printed in the first seven utahs of the 16×16 Data Matrix. Recall that each utah encodes one 8-bit codeword.

TABLE 6

AI (90) ASCII and Data Matrix Codeword String Example for W→X Sensor Dye

Utah	AI (90) Data	7-bit ASCII Input	Hexadecimal Codeword	Notes
1	FNC1	Printer dependent see Notes	E8	FNC1 is not a 7-bit ASCII value, so a special character string is sent to the printer to include at the start of the GS1 AI string
2	90	90	DC	AI (90)
3	See Notes	5	36	Indicator bits 3.6, 3.7 = "11", B15 in 3.8 = '0' and Bits 3.1-3.4 set to "0011" to flag as an example of a W→X sensor dye chemistry product
4	X	X	59	Any 7-bit ASCII. Here 'X' 'is used as an example of an additional data character
5	Example	"	23	Sets bits B14-B8 to print '0100011'
6	Example	j	6B	Sets bits B7-B1 to print '1101011'
7	GS or FNC1	GS	1E	Terminates AI (90) string

Bits **3.1**-**3.5** of utah **3** at **630***b* are not in the invariant bitmap **410** as they are on the bottom edge of the Data Matrix symbol for all sizes of Data Matrix. However data may be encoded here which is useful in communicating specific information about the properties of the sensor dye in use, and the sensor dye pattern which is encoded in the augmented Data Matrix.

Since only part **640***a* of utah **4** appears in the invariant bitmap portion **410**, utah **4** is used as a spacer to ensure that bits B**14**-B**1** are printed in utahs **5** and **6** at **650** and **660** respectively. Any 7-bit ASCII character may be encoded in utah **4**. It is typically used for product-related information.

A 16×16 Data Matrix **700** printed only with the information in Table 6 is shown in FIG. **22**. In FIG. **23**, Data Matrix **800** is shown similar in structure to Data Matrix **600**. Here however, the appropriate modules in the invariant bitmap portion are set to either black or white as per the encodation underlying Data Matrix **700** in FIG. **22**. The remaining Data Matrix codewords (utahs **8**-**12**) are filled with pad characters to fill out the 12 available data codewords. The last 12 codewords in the symbol (utahs **13**-**24**) are RSEC error correction codewords. In FIG. **23**, for convenience the contents of utahs **8**-**24** are shown in grey, since they are not relevant to the encoding of AI (90).

The visual image of the unactivated sensor-augmented Data Matrix **900** is shown in FIG. **24**. Note the white sensor dye is overprinted indicator bits **910**. The overprinted BCH encoding **920** of B**15**-B**1** of the sensor data is shown as white dye modules, indistinguishable from the unprinted and not-overprinted white modules at utah bits **5.1** and **6.1**. These have value '00000000000000', indicating the unactivated default sensor data value '0' for B**15**-B**1** in this sensor dye chemistry system. Note indicator bits are '00' indicating the unactivated state of a W→X sensor dye chemistry.

Once activated, all sensor modules become transparent and the visual image reverts to FIG. **22**, showing the correct 15 bit BCH bit pattern 001000111101011 which is decoded using one of the standard methods for BCH (15,5,7) described above to recover the sensor data value '4'.

The second preferred embodiment utilizes a temperature threshold sensitive sensor dye chemistry X→B as is frequently represented by the thermally-activated leuco dye systems used to make thermal paper. Here transparent dye modules are overprinted on white (unprinted) modules of the underlying Data Matrix printed on a white media.

Here also 15-bit BCH(15,5,7) error correction used to encode 5 bits of sensor data which are also encoded by overprinting sensor dye modules on an underlying printed Data Matrix symbol only at bit map locations where a black module is to appear upon sensor dye activation. It is also assumed here that the sensor dye chemistry used is known at the time of printing the Data Matrix symbol.

With any sensor dye chemistry that is initially transparent, different printers may be used to print the underlying Data Matrix symbol and later overprint it with the sensor dye modules as a separate process, thus augmenting the Data Matrix information be known at time the sensor modules are overprinted. In an example embodiment, the two-dimensional barcode may be attached to various products such as food products, pharmaceutical products, biologics, or any other product that may benefit from environmental, physical, or biological monitoring. For example, the bar code may be printed on or applied to a container for such a product.

The sensor data 15-bit BCH encoding pattern, along with 2 indicator bits, is identical to that of the first preferred embodiment. From Table 2, for an X→B sensor dye chemistry the printed indicator bits **3.6** and **3.7** will be "10". As in the first preferred embodiment, the upper 5 bits of utah **3**,

bits **3.1-3.5** may be used to encode additional information about the sensor dye chemistry in use and/or the sensor dye bit pattern.

In keeping with the most broadly used system for encoding information in a Data Matrix, the GS1 Application Identifier AI (90) is used. AI (90) is reserved for information mutually agreed upon between trading partners, such as the presence of a sensor-enabled Data Matrix. AI (90) is used in utah **1-7** data structure format as in the first preferred embodiment, with the specific data here encoded in Table 7.

Consider the same example as in the first preferred embodiment when the sensor data value is 4. From Table 4, the BCH encoding B**15**-B**1** is 001000111101011. Since a transparent-to-black sensor dye chemistry is utilized in this second preferred embodiment, the BCH-encoded sensor dye modules for what will become black modules in B**15**-B**1** once active must be selectively overprinted on B**15**-B**1** white modules in the underlying Data Matrix. The indicator bits **3.6** and **3.7** are also overprinted with sensor dye modules.

Table 7 shows the AI (90) data string that is printed for this second preferred embodiment example in the first 7 utahs of the 16×16 underlying Data Matrix **1000** in FIG. **25**. The underlying Data Matrix **1000** printed only with the information in Table 7 is shown in FIG. **25**.

Referring to the ULC detail **1100** in FIG. **26**, indicator bits **3.6** and **3.7** are set to '1' and '0' respectively. Utah bits **3.8**, **5.2-5.8** and **6.2-6.8** are white modules corresponding to '0' for all these bits B**15**-B**1**. Utah bits **5.1** and **6.1** are set to '1' as they are not part of the BCH bit encoding sequence, and the Data Matrix standard ISO/IEC standard requires every utah to have at least 1 black module. The remaining Data Matrix codewords (utahs **8-12**) are filled with pad characters to fill out the 12 available data codewords, which are specially encoded as per ISO/IEC 16022. The last 12 codewords in the symbol (utahs **13-24**) are RSEC error correction codewords. In FIG. **26**, for convenience the contents of utahs **8-24** are shown in grey, since they are not relevant to the encoding of AI (90).

TABLE 7

AI (90) ASCII and Data Matrix Codeword String Example for X→B Sensor Dye

Utah	AI (90) Data	7-bit ASCII Input	Hexadecimal Codeword	Notes
1	FNC1	Printer dependent see Notes	E8	FNC1 is not a 7-bit ASCII value, so a special character string is sent to the printer to include at the start of the GS1 AI string
2	90	90	DC	
3	See Notes	C	44	Indicator bits 3.6, 3.7 = '10', B15 in 3.8 = '0' and Bits 3.1-3.4 set to "0100" to flag as an example of a W→X sensor dye chemistry product
4	H	H	49	Any 7-bit ASCII. Here 'H' is used as an example of an additional data character
5	Example	Printer Dependent	80	Sets bits B14-B8 to print '0000000' '~~' is a common printer string as ~ is 7F and Data Matrix encodes ASCII value +1
6	Example	Printer Dependent	80	Sets bits B7-B1 to print '0000000' See note for utah 5
7	GS or FNC1	GS	1E	Terminates AI (90) string

The white modules of the underlying Data Matrix will be visible when the sensor-augmented Data Matrix barcode symbol is in the unactivated state, showing a BCH encoding for B**15**-B**1** of 00000000000000, or sensor data value 0 as in the sensor-augmented Data Matrix **1000** in FIG. **25** and the Data Matrix ULC detail **1100** in FIG. **26**.

Once the sensor modules are activated, the visual sensor-augmented Data Matrix **1200** ideally will appear, as shown in in FIG. **27**. The sensor data bit pattern B**15**-B**1** of 001000111101011 will now show, and through reading of the Data Matrix as described above using supplemental standard BCH decoding techniques on the sensor dye bit pattern the sensor data value 4 will be recovered. Note that the Data Matrix **1200** is the same as the underlying Data Matrix **1000** with the overprinted sensor dyes modules now activated to black (but shown in dark grey as **1220** in FIG. **27**, for clarity) to reveal the sensor data bit pattern B**15**-B**1**, and the indicator bit pattern **1210** now as '11'.

The third preferred embodiment also utilizes a temperature-sensitive sensor dye chemistry. Here sensor dye modules in the unactivated color state are overprinted as a single sensor dye patch in the invariant bitmap of an underlying Data Matrix printed on a white media.

Any sensor dye chemistry R→S may be used, provided the arbitrary color states R and S both have 1) sufficient visual color state change and 2) sufficient contrast under 660 nm reader illumination that the R color state scans as W or B and the S color state scans as the complementary color, B or W. This enables the sensor dye patch, in either the unactivated or activated color state, to be both visually discriminable and machine readable to using the aforementioned Data Matrix reading techniques to recover the sensor dye modules as an image and further process it to determine the activation state of the sensor dye patch.

Different printers, or different stations of the same printing press, may be used: First to print the underlying Data Matrix symbol and later to overprint it with the sensor dye patch in a separate process.

In this example, an X→B sensor dye chemistry is illustrated. The sensor dye patch is a square approximately 2×2 sensor dye modules in size. It is framed by and centered in a white area 4×4 modules in size. This 4×4 white frame is positioned in the invariant bitmap of a 16×16 Data Matrix, to ensure that the 4×4 white frame and its enclosed sensor dye patch will always be in the same position relative to ULC over broad range of Data Matrix symbol sizes.

FIG. **28** shows the position of the 4×4 white frame **1310** (from bit **3.6** to bit **5.8**) within the example 16×16 Data Matrix symbol **1300**. The 4×4 white frame **1310** contains 4 rows of utah bits comprised as follows:

Abbott Laboratories
Exhibit 1022
Page 043

Row **1**: Bits **3.6**, **3.7**, **3.8**, **4.3**
Row **2**: Bits **2.5**, **5.1**, **5.2**, **5.3**
Row **3**: Bits **2.8**, **5.3**, **5.4**, **5.5**
Row **4**: Bits **6.2**, **5.6**, **5.7**, **5.8**

Note that in this third preferred embodiment, bits **3.6** and **3.7** are not used as indicator bits, as in the first and second preferred embodiments but are rather here they are part of the 4×4 white frame.

A naive approach would be to create the underlying printed Data Matrix symbol without data restriction and simply overprint white modules on the 16 underlying Data Matrix modules in the 4×4 white frame **1310**. Depending on the data encoded, and whether any black modules in **1310** were deliberately overprinted, up to 5 utahs and their encoded codewords could be deliberately damaged by overprinting. A conventional approach to the use of Reed-Solomon error correction to recover up to 5 damaged codewords during reading a Data Matrix would require the use of up to 10 of the 12 available RSEC codewords in a 16×16 Data Matrix symbol. This would leave few RSEC codewords available for other accidental symbol damage.

As in the examples shown in the first and second preferred embodiments, in this example symbol data encoding is also performed using the GS1 Application Identifier AI (90) and the utah **1-7** data structure format. Symbol data specific to the third preferred embodiment is encoded in Table 8. For convenience the contents of utahs **8-24** are shown in grey in Data Matrix **1300**, since they are not relevant to the encoding of AI (90).

Utahs **1** and **7** are unaffected by the creation of the 4×4 white frame **1310**, as they have no bits within **1310**. Utah bits **2.5** and **2.8** are within **1310**. In the AI(90) data encoding bit **2.5**='1', and therefore utah **2** will be deliberately damaged when overwritten by a white module. Utah **5** is entirely within the 4×4 white frame **1310**. Since by the way data is encoded with ISO/IEC 16022 Data Matrix there will always be at least 1 black module in any valid utah; therefore no matter what 7-bit ASCII data character is encoded in utah **5** it and its codeword will be deliberately damaged by overprinting all utah **5** modules with white modules.

However, is possible to avoid deliberate damage to bit positions in utahs **3**, **4** and **6** which are within the 4×4 white frame merely by restricting the data allowed to be encoded in these codewords so that there are no black modules ('1' bits) in utah bits **3.6**-**3.8**, **4.3**, **4.6** and **6.2**. Assuming than 'x' represents a "don't care" bit position in each specific bit position within a utah, the allowable 8-bit Data Matrix codeword forms are:

Utah **3**: xxxxx000

Utah **4**: xx0xx0xx

Utah **6**: x0xxxxxx

Table 8 shows the AI (90) data string for this 3rd preferred embodiment example in the first 7 utahs of the 16×16 underlying Data Matrix **1400** in FIG. **29**.

TABLE 8

AI (90) ASCII and Data Matrix Codeword String Example for Patch sensor

Utah	AI (90) Data	7-bit ASCII Input	Hexadecimal Codeword	Notes
1	FNC1	Printer dependent see Notes	E8	FNC1 is not a 7-bit ASCII value, so a special character string is sent to the printer to include at the start of the GS1 AI string
2	90	90	DC	Data Matrix encodes 2 digits/codeword
3	See Notes	BEL	08	Binary form: xxxxx000 so bits 3.6-3.8 = '000'. As an example, here bits 3.1-3.5 are set to "00001" to signal a dye patch symbol with an X→B sensor dye chemistry
4	See Notes	'Q'	52	Binary form: xx0xx0xx Here binary form 01010010 (7-bit ASCII 'Q') is an example of an additional data character
5	Product Related	'?'	40	Any 7-bit ASCII value. Here ASCII 63 corresponding to '?' is used as an example.
6	Product Related	'7'	38	Binary form: x0xxxxxx Any 7-bit ASCII value less than 64 decimal may be used. As an example, '7' (ASCII 55) is used.
7	GS or FNC1	GS	1E	Terminates AI (90) string

In FIG. **29**, the underlying Data Matrix **1400** is printed only with the information in Table 8. The remaining Data Matrix data codewords (utahs **8-12**) are filled with Data Matrix pad characters. The last 12 codewords in the symbol (utahs **13-24**) are RSEC error correction codewords.

In FIG. **30**, a 4×4 white frame **1510** is shown within the invariant bitmap of Data Matrix **1400**, corresponding to the 4×4 white area **1310** in FIG. **28**. There are several ways of producing this 4×4 white frame **1510**, including physically overprinting white modules on the underlying Data Matrix **1400**. A better way is a modification to the Data Matrix encoding and symbol generation software for the underlying symbol is by altering the Data Matrix's encoded 14×14 bitmap to ensure that all bit positions in **1510** are set to '0' prior to conversion to black and white modules, or alternatively setting all modules to white in the 4×4 white area **1510** prior to printing Data Matrix **1400**. Thus, no black modules are ever printed in the 4×4 white area **1510** in the first place, requiring no white module overprinting step.

As in the second preferred embodiment, in the third preferred embodiment a secondary printing step is used to print an approximately 2×2 sensor dye patch **1620** within the 4×4 white frame **1510**, as shown in FIG. **31**. Here the sensor dye patch **1602** is shown as activated (for clarity in a purple color).

One of the objectives of the third preferred embodiment that there is a visible change of the sensor dye patch **1520** color state within the 4×4 white frame **1510** upon sensor dye activation. The second objective is that a sensor dye chemistry is employed that has adequate contrast to the Data Matrix reader as described above so that the sensor dye patch **1620** is read as W or B modules when unactivated and read as the complementary color B or W modules when activated. Then the presence of both the unactivated and

activated sensor dye patch can be machine readable to a Data Matrix reader using reading methods described above.

A further improvement to the third preferred embodiment is in the Data Matrix reading process: It is to apply the knowledge that the codewords of utahs **2** and **5** have been deliberately damaged to improve the efficiency of the Reed-Solomon error correction process in the symbol codeword sequence recovery. Detection and correction of an erroneous codeword at an unknown location in the combined data plus RSEC codeword sequence requires the use of 2 RSEC characters per damaged codeword. But, if the location of the damaged codewords are known prior to applying the Reed-Solomon error correction process (in this case in codewords **2** and **5**) then only 1 RSEC codeword is required to recover the correct codeword value of each identified damaged codeword. This leaves additional unused RSEC codewords available for other accidental Data Matrix symbol damage correction.

Alternative embodiments include use of one or more of

- other two-dimensional error correcting barcode symbols in place of Data Matrix including QR Code, Aztec Code, MaxiCode, PDF417 and Dot Code;
- alternate sensor dye chemistries utilizing color states other than black, white or transparent;
- underlying printed two-dimensional error correcting barcode symbols where either first color state or the second color state of the symbol are colors other than black or white
- underlying two-dimensional error correcting barcode symbols where either the first color state may be the unmarked media surface and the second color state a directly-marked media surface change, or vice versa.

In an exemplary aspect of the present disclosure, a sensor-augmented two-dimensional barcode includes a substrate; a two-dimensional error-correcting barcode symbol provided on the substrate; a first layer provided on the substrate in a permanent color state; and a second layer provided on the substrate. The bar code symbol further includes a plurality of modules, the modules optionally being square, rectangular, or circulate, each module having one of a first color state or a second color state. The second layer is optionally provided by overprinting the first layer, in a sensor dye module pattern, the sensor dye module pattern containing sensor digital information. The second layer further includes a sensor dye having a chemistry that is configured, responsive to the occurrence of an environmental, physical or biological condition, to undergo a chemical or physical state change causing a change in the color state of the sensor dye, thereby changing the color state of a subset of the plurality of modules.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the environmental condition is selected from the group consisting of time, temperature, time-temperature product, light, humidity, gas vapor and nuclear radiation, and wherein, preferably, the sensor dye permanently changes color state when the environmental condition crosses a threshold value.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the first layer forms a readable barcode symbol in the symbology of the two-dimensional barcode.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the two-dimensional error-correcting barcode symbol is from the symbology group consisting of Data Matrix, QR Code, Aztec Code, MaxiCode, PDF417 and Dot Code symbologies.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the two-dimensional error-correcting barcode symbol utilizes Reed-Solomon error correction.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the sensor dye is initially in a black, white or transparent color state when unactivated and changes to a different color state upon activation.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the sensor dye permanently changes color state when the specified condition of the sensed property is above or below a threshold value.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the specified condition of the sensed property is the detection of the presence of a biological organism, biological agent or biological toxin, preferably by utilizing a colorimetric immunoassay.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the second layer provides sensor digital information, the sensor digital information preferably encoded in an invariant bitmap of the two-dimensional symbol, and more preferably encoded as binary encoded sensor data, and more preferably the binary encoded sensor data is in an error correcting code, preferably chosen from the group consisting of Hamming Codes, Bose-Chaudhuri-Hocquenghem Codes, Golay Codes, Simplex Codes, Reed-Muller Codes, Fire Codes, Convolutional Codes, and Reed-Solomon Codes.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the sensor digital information encoded in the sensor dye module pattern is a visual pattern or image.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an article of manufacture includes pharmaceutical, biological, or food product, preferably a vaccine; a container holding the pharmaceutical, biological, or food product, preferably a vaccine vial; and a sensor-augmented two-dimensional barcode symbol provided on or in the container, preferably being applied to the outside surface of the container.

In accordance with another exemplary aspect of the present disclosure, a method of reading of a sensor-augmented two-dimensional barcode symbol includes scanning and optically processing an image of the sensor-augmented two-dimensional barcode symbol, including construction of a scan binary bitmap from scanned modules of the sensor-augmented two-dimensional barcode symbol. The method further includes constructing a symbol codeword sequence from the scan binary bitmap. Then, underlying data codewords are recovered from the symbol codeword sequence, preferably by utilizing error correction process on the symbol codeword sequence, the error correction process preferably being a Reed-Solomon code. Next, the underlying data codewords are processed to form the underlying symbol codeword sequence. The method further includes construct-

ing an underlying binary bitmap from the scan binary bitmap from the underlying symbol codeword sequence, the underlying binary bitmap preferably equal in size to the scan binary bitmap. At each bit position an exclusive-OR of the scan binary bitmap and the underlying binary bitmap may be performed to form a sensor digital information bitmap. Optionally, the method includes, processing the sensor digital information bitmap to recover a binary information sequence that incorporates binary encoded sensor data, preferably by processing the binary information sequence as an error-correcting code sequence and utilizing an error correction process to recover binary-encoded sensor data. The error-correcting code preferably is selected from the group consisting of Hamming Codes, Bose-Chaudhuri-Hocquenghem Codes, Golay Codes, Simplex Codes, Reed-Muller Codes, Fire Codes, Convolutional Codes, and Reed-Solomon Codes.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the method includes processing the sensor digital information bitmap to identify a sensor dye patch and determine from a color state of the sensor dye patch whether or not activation of a sensor dye has occurred in response to an environmental condition.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the sensor dye patch is located in an invariant area of a Data Matrix barcode symbol.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the method includes recovering a visual pattern or image from the sensor digital information bitmap.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an apparatus may perform a method of generating a 2D barcode, includes determining a set of payload data including a set of static data and a set of dynamic data, generating a 2D barcode which includes an encoded version of the set of static data and includes redundant space, designating at least part of the redundant space as a dynamic region which is adapted to store the set of dynamic data, and printing the 2D barcode using a static ink and an encoded version of the set of the dynamic data on the dynamic region using a dynamic ink which changes states responsive to at least one environmental change, such that the set of dynamic data is in one of a plurality of states. The set of dynamic data is readable by a reader of the 2D barcode and the set of static data is readable by the reader of the 2D barcode when the set of dynamic data is in each one of the plurality of states.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with the preceding aspect, the dynamic ink is responsive to environmental factors including at least one of temperature, time, radiation, light, and toxic chemicals.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the dynamic ink is responsive to time and temperature.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the dynamic ink is responsive to freezing.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the dynamic ink permanently changes in response to an environmental factor.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the dynamic ink transitions from a first state to a second state in response to the occurrence of a specific environmental factor and returns to the first state when the specific environmental factor is no longer occurring.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the redundant space includes at least one of a plurality of unused bits, a padding region, and an error detection and correction region.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, wherein the redundant space includes at least one of a format information region, a version information region, and a reference data region.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, a non-privileged reader is capable of reading the static data and cannot read the dynamic data of the 2D barcode.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, only privileged readers are capable of reading the static data and cannot read the dynamic data of the 2D barcode.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an apparatus may perform a method of providing a 2D barcode, includes determining a set of static data, determining a set of dynamic data, generating a first 2D barcode, generating a second 2D barcode, comparing the first 2D barcode and the second 2D barcode and categorizing the information modules into a first group and a second group, and printing the 2D barcode in static ink and dynamic ink. The set of dynamic data has a first state and a second state. The first 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the first state. The set of static data and the set of dynamic data in the first state include a first plurality of information modules and a second plurality of information modules. The second 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the second state. The set of static data and the set of dynamic data in the second state include a third plurality of information modules and a fourth plurality of information modules. The third plurality of information modules includes all of the first plurality of information modules plus a set of one or more information modules. The second plurality of information modules includes all of the fourth plurality of information modules plus the set of one or more information modules. The first group includes common information modules between the first plurality of information modules of the first 2D barcode and the third plurality of information modules of the second 2D barcode. The second group includes unique information modules of the third plurality of information modules of the second 2D barcode. The first group is printed in the static ink, and the second group is printed in the dynamic ink. The dynamic ink is adapted to activate in response to the occurrence of a specific environmental factor.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with

any one or more of the preceding aspects, the first plurality of information modules and the third plurality of information modules are black modules and the second plurality of information modules and the fourth plurality of information modules are white modules.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the first plurality of information modules and the third plurality of information modules are adapted to be visually distinguishable from a printing surface and the third plurality of information modules and the fourth plurality of information modules are visually indistinguishable from the printing surface.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an apparatus may perform a method of providing a 2D barcode, includes determining a set of static data, determining a set of dynamic data, generating a first 2D barcode, generating a second 2D barcode, comparing the first 2D barcode and the second 2D barcode and categorizing the information modules into a first group, a second group, and a third group, and printing the 2D barcode using a static ink, a first dynamic ink, and a second dynamic ink. The set of dynamic data has a first state and a second state. The first 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the first state. The set of static data and the set of dynamic data in the first state include a first plurality of information modules and a second plurality of information modules. The second 2D barcode includes an encoded version of the set of static data and the set of dynamic data in the second state. The set of static data and the set of dynamic data in the second state include a third plurality of information modules and a fourth plurality of information modules. The first group includes common information modules between the first plurality of information modules of the first 2D barcode and the third plurality of information modules of the second 2D barcode. The second group includes unique information modules of the third plurality of information modules of the second 2D barcode, and the third group includes unique information modules of the first plurality of information modules of the first 2D barcode. The first group is printed in the static ink, the second group is printed in a first dynamic ink, and the third group is printed in a second dynamic ink. The first dynamic ink is adapted to deactivate in response to the occurrence of a specific environmental factor, and the second dynamic ink is adapted to activate in response to the occurrence of the specific environmental factor.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the first dynamic ink and the second dynamic ink are responsive to environmental factors including at least one of temperature, time, radiation, light, and toxic chemicals.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the first dynamic ink and the second dynamic ink are responsive to time and temperature.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the first dynamic ink and the second dynamic ink are responsive to freezing.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the first dynamic ink and the second dynamic ink activate simultaneously.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an apparatus may perform a method of providing a 2D barcode, includes determining a set of payload data including a set of static data and a set of dynamic data having a first state and a second state, generating a 2D barcode which includes an encoded version of the set of static data, a dynamic region which is adapted to store the set of dynamic data, and error detection and correction data, and printing the 2D barcode using a static ink and an encoded set of the dynamic data on the dynamic region using a dynamic ink which changes states responsive to at least one environmental change, such that the set of dynamic data is in the first state or the second state, and the error detection and correction data accommodates for changes in the set of dynamic data in the dynamic region such that the 2D barcode is readable by a reader and produces a first output when the set of dynamic data is in the first state and the 2D barcode is readable by a reader and produces a second output when the set of dynamic data is in the second state.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the dynamic region is provided in a padding region.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, the dynamic region is provided at an end of a data region.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an apparatus may perform a method of reading a 2D barcode includes scanning a set of static data included in the 2D barcode, scanning a set of dynamic data included in the 2D barcode, generating a first output of the set of static data, and generating a second output of the set of dynamic data. The 2D barcode is printed in static ink and dynamic ink, and an encoded version of the set of static data is printed in the static ink. An encoded version of the set of dynamic data is printed in the dynamic ink which changes states responsive to at least one environmental change, such that the dynamic data is in one of the plurality of states. The set of dynamic data is printed in a redundant space on the 2D barcode. The second output indicates on which state of the plurality of states the dynamic data is in.

In accordance with another exemplary aspect of the present disclosure, which may be used in combination with any one or more of the preceding aspects, an apparatus may perform a method of reading a two dimensional (2D) includes scanning a set of static data included in the 2D barcode, scanning a set of dynamic data included in the 2D barcode, and generating an output based on the set of static data and the set of dynamic data. The 2D barcode includes static ink and dynamic ink. An encoded version of the set of static data is printed in the static ink. An encoded version of the set of dynamic data is printed in the dynamic ink, which changes states responsive to at least one environmental change, such that the dynamic data is in one of a plurality of states. The set of dynamic data is printed in the dynamic region. The output is a first output when the set of dynamic data is in a first state of the plurality of states, and the output is a second output when the set of dynamic data is in a second state of the plurality of states.

It should be understood that various changes and modifications to the example embodiments described herein will be apparent to those skilled in the art. Such changes and

modifications can be made without departing from the spirit and scope of the present subject matter and without diminishing its intended advantages. It is therefore intended that such changes and modifications be covered by the appended claims. Also, it should be appreciated that the features of the dependent claims may be embodied in the systems, methods, and apparatus of each of the independent claims.

Many modifications to and other embodiments of the invention set forth herein will come to mind to one skilled in the art to which these inventions pertain, once having the benefit of the teachings in the foregoing descriptions and associated drawings. Therefore, it is understood that the inventions are not limited to the specific embodiments disclosed, and that modifications and other embodiments are intended to be included within the scope of the appended claims. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purpose of limitation.

The invention is claimed as follows:

1. A sensor-augmented two-dimensional barcode, comprising:

a substrate;

a two-dimensional error-correcting barcode symbol provided on the substrate, the bar code symbol further comprising a plurality of modules, each module having one of a first color state or a second color state;

a first layer provided on the substrate in a permanent color state; and

a second layer provided on the substrate in a sensor dye module pattern, the sensor dye module pattern containing sensor digital information, the second layer further comprising a sensor dye having a chemistry that is configured, responsive to the occurrence of an environmental, physical or biological condition, to undergo a chemical or physical state change causing a change in the color state of the sensor dye, thereby changing the color state of a subset of the plurality of modules.

2. The sensor-augmented two-dimensional barcode symbol of claim **1** wherein the environmental condition is selected from the group consisting of time, temperature, time-temperature product, light, humidity, gas vapor and nuclear radiation.

3. The sensor augmented two-dimensional barcode of claim **2**, wherein, the sensor dye permanently changes color state when the environmental condition crosses a threshold value.

4. The sensor-augmented two-dimensional barcode of claim **1**, wherein the first layer forms a readable barcode symbol in the symbology of the two-dimensional barcode, and wherein the two-dimensional barcode is readable both prior to and after the color state of a subset of the plurality of modules is changed.

5. The sensor-augmented two-dimensional barcode claim **1** wherein the two-dimensional error-correcting barcode symbol is from the symbology group consisting of Data Matrix, QR Code, Aztec Code, MaxiCode, PDF417 and Dot Code symbologies.

6. The sensor-augmented two-dimensional barcode symbol of claim **1** wherein the two-dimensional error-correcting barcode symbol utilizes Reed-Solomon error correction.

7. The sensor-augmented two-dimensional barcode symbol of claim **1** wherein the sensor dye is initially in a black, white or transparent color state when unactivated and changes to a different color state upon activation.

8. The sensor-augmented two-dimensional barcode symbol of claim **7** wherein the sensor dye permanently changes color state when the specified condition of a sensed property of the environmental, physical, or biological condition is above or below a threshold value.

9. The sensor-augmented two-dimensional barcode symbol of claim **1** wherein the specified condition of a sensed property is a detection of the presence of a biological organism, biological agent or biological toxin.

10. The sensor-augmented two-dimensional barcode of claim **9**, wherein a colorimetric immunoassay detects the presence of the biological organism, biological agent or biological toxin.

11. The sensor-augmented two-dimensional barcode symbol of claim **1** wherein the second layer provides sensor digital information.

12. The sensor-augmented two-dimensional barcode symbol of claim **11**, wherein the sensor digital information is encoded in an invariant bitmap of the two-dimensional symbol.

13. The sensor-augmented two-dimensional barcode symbol of claim **12**, wherein the sensor digital information is encoded as binary encoded sensor data.

14. The sensor-augmented two-dimensional barcode symbol of claim **13**, wherein the binary encoded sensor data is in an error correcting code.

15. The sensor augmented two-dimensional barcode of claim **14**, wherein the error correcting code is chosen from the group consisting of Hamming Codes, Bose-Chaudhuri-Hocquenghem Codes, Golay Codes, Simplex Codes, Reed-Muller Codes, Fire Codes, Convolutional Codes, and Reed-Solomon Codes.

16. The sensor-augmented two-dimensional barcode symbol of claim **1** wherein the sensor digital information encoded in the sensor dye module pattern is a visual pattern or image.

17. The sensor augmented two-dimensional barcode of claim **1**, wherein the modules are square, rectangular, or circular.

18. The sensor augmented two-dimensional barcode of claim **1**, wherein the second layer is overprinted on the first layer.

19. The sensor-augmented two-dimensional barcode of claim **1**, wherein the sensor dye module pattern has a fixed position, both before and after the change in the color state of the subset of the plurality of modules.

20. The sensor-augmented two-dimensional barcode of claim **1**, wherein the modules are at least one of square shaped, rectangular shaped, and circular shaped.

21. An article of manufacture, comprising:

pharmaceutical, biological, or food product;

a container holding the pharmaceutical, biological, or food product; and

a sensor-augmented two-dimensional barcode symbol provided on or in the container, wherein the sensor-augmented two-dimensional barcode symbol includes:

a plurality of modules, each module having one of a first color state or a second color state,

a first layer in a permanent color state, and

a second layer in a sensor dye module pattern, the sensor dye module pattern containing sensor digital information, the second layer further comprising a sensor dye having a chemistry that is configured, responsive to the occurrence of an environmental, physical or biological condition, to undergo a chemical or physical state change causing a change in the color state of the sensor dye, thereby changing the color state of a subset of the plurality of modules.

22. The article of manufacture of claim **21**, wherein the pharmaceutical, biological, or food product is a vaccine, and

wherein the sensor-augmented two-dimensional barcode symbol is applied to the outside surface of the container.

23. The article of manufacture of claim **21**, wherein the container is a vaccine vial.

* * * * *

Abbott Laboratories
Exhibit 1022
Page 049